



---

≡ Protocols and APIs > **Tools Invoke API**

---

## Protocols and APIs

# Tools Invoke API

OpenClaw's Gateway exposes a simple HTTP endpoint for invoking a single tool directly. It is always enabled, but gated by Gateway auth and tool policy.

`POST /tools/invoke`

Same port as the Gateway (WS + HTTP multiplex): `http://<gateway-host>:<port>/tools/invoke`

Default max payload size is 2 MB.

## Authentication

Uses the Gateway auth configuration. Send a bearer token:

`Authorization: Bearer <token>`

Notes:

When `gateway.auth.mode="token"` , use `gateway.auth.token` (or `OPENCLAW_GATEWAY_TOKEN` ).

When `gateway.auth.mode="password"` , use `gateway.auth.password` (or `OPENCLAW_GATEWAY_PASSWORD` ).

If `gateway.auth.rateLimit` is configured and too many auth failures occur, the endpoint returns `429` with `Retry-After` .

## Request body



```
{
  "tool": "sessions_list",
  "action": "json",
  "args": {},
  "sessionKey": "main",
  "dryRun": false
}
```

### Fields:

`tool` (string, required): tool name to invoke.

`action` (string, optional): mapped into args if the tool schema supports `action` and the args payload omitted it.

`args` (object, optional): tool-specific arguments.

`sessionKey` (string, optional): target session key. If omitted or "main", the Gateway uses the configured main session key (honors `session.mainKey` and default agent, or `global` in global scope).

`dryRun` (boolean, optional): reserved for future use; currently ignored.

## Policy + routing behavior

Tool availability is filtered through the same policy chain used by Gateway agents:

`tools.profile` / `tools.byProvider.profile`

`tools.allow` / `tools.byProvider.allow`

`agents.<id>.tools.allow` / `agents.<id>.tools.byProvider.allow`

group policies (if the session key maps to a group or channel)

subagent policy (when invoking with a subagent session key)

If a tool is not allowed by policy, the endpoint returns **404**.



Gateway HTTP also applies a hard deny list by default (even if session policy allows the tool):

```
sessions_spawn
```

```
sessions_send
```

```
gateway
```

```
whatsapp_login
```

You can customize this deny list via `gateway.tools` :

```
{
  gateway: {
    tools: {
      // Additional tools to block over HTTP /tools/invoke
      deny: ["browser"],
      // Remove tools from the default deny list
      allow: ["gateway"],
    },
  },
}
```

To help group policies resolve context, you can optionally set:

`x-openclaw-message-channel: <channel>` (example: `slack` , `telegram` )

`x-openclaw-account-id: <accountId>` (when multiple accounts exist)

## Responses

200 → { ok: true, result }

400 → { ok: false, error: { type, message } } (invalid request or tool input error)

401 → unauthorized



429 → auth rate-limited ( Retry-After set)

404 → tool not available (not found or not allowlisted)

405 → method not allowed

500 → { ok: false, error: { type, message } } (unexpected tool execution error; sanitized message)

## Example

```
curl -sS http://127.0.0.1:18789/tools/invoke \  
-H 'Authorization: Bearer YOUR_TOKEN' \  
-H 'Content-Type: application/json' \  
-d '{  
  "tool": "sessions_list",  
  "action": "json",  
  "args": {}  
}'
```

< OpenAI Chat Completions

CLI Backends >

Powered by [mintlify](#)