



---

☰ CLI commands > **gateway**

---

## CLI commands

# gateway

The Gateway is OpenClaw's WebSocket server (channels, nodes, sessions, hooks).

Subcommands in this page live under `openclaw gateway ...`.

Related docs:

[/gateway/bonjour](#)

[/gateway/discovery](#)

[/gateway/configuration](#)

## Run the Gateway

Run a local Gateway process:

```
openclaw gateway
```

Foreground alias:

```
openclaw gateway run
```

Notes:



By default, the Gateway refuses to start unless `gateway.mode=local` is set in `~/.openclaw/openclaw.json` . Use `--allow-unconfigured` for ad-hoc/dev runs.

Binding beyond loopback without auth is blocked (safety guardrail).

`SIGUSR1` triggers an in-process restart when authorized (enable `commands.restart` or use the gateway tool/config apply/update).

`SIGINT` / `SIGTERM` handlers stop the gateway process, but they don't restore any custom terminal state. If you wrap the CLI with a TUI or raw-mode input, restore the terminal before exit.

## Options

`--port <port>` : WebSocket port (default comes from config/env; usually `18789` ).

`--bind <loopback|lan|tailnet|auto|custom>` : listener bind mode.

`--auth <token|password>` : auth mode override.

`--token <token>` : token override (also sets `OPENCLAW_GATEWAY_TOKEN` for the process).

`--password <password>` : password override (also sets `OPENCLAW_GATEWAY_PASSWORD` for the process).

`--tailscale <off|serve|funnel>` : expose the Gateway via Tailscale.

`--tailscale-reset-on-exit` : reset Tailscale serve/funnel config on shutdown.

`--allow-unconfigured` : allow gateway start without `gateway.mode=local` in config.

`--dev` : create a dev config + workspace if missing (skips `BOOTSTRAP.md` ).

`--reset` : reset dev config + credentials + sessions + workspace (requires `--dev` ).

`--force` : kill any existing listener on the selected port before starting.



`--verbose` : verbose logs.

`--claude-cli-logs` : only show claude-cli logs in the console (and enable its stdout/stderr).

`--ws-log <auto|full|compact>` : websocket log style (default `auto`).

`--compact` : alias for `--ws-log compact`.

`--raw-stream` : log raw model stream events to jsonl.

`--raw-stream-path <path>` : raw stream jsonl path.

## Query a running Gateway

All query commands use WebSocket RPC.

Output modes:

Default: human-readable (colored in TTY).

`--json` : machine-readable JSON (no styling/spinner).

`--no-color` (or `NO_COLOR=1`): disable ANSI while keeping human layout.

Shared options (where supported):

`--url <url>` : Gateway WebSocket URL.

`--token <token>` : Gateway token.

`--password <password>` : Gateway password.

`--timeout <ms>` : timeout/budget (varies per command).

`--expect-final` : wait for a “final” response (agent calls).

Note: when you set `--url`, the CLI does not fall back to config or environment credentials. Pass `--token` or `--password` explicitly. Missing explicit credentials is an error.

## gateway health



```
openclaw gateway health --url ws://127.0.0.1:18789
```

&gt;

## gateway status

`gateway status` shows the Gateway service (launchd/systemd/schtasks) plus an optional RPC probe.

```
openclaw gateway status
openclaw gateway status --json
```

### Options:

- `--url <url>` : override the probe URL.
- `--token <token>` : token auth for the probe.
- `--password <password>` : password auth for the probe.
- `--timeout <ms>` : probe timeout (default 10000 ).
- `--no-probe` : skip the RPC probe (service-only view).
- `--deep` : scan system-level services too.

## gateway probe

`gateway probe` is the “debug everything” command. It always probes:

your configured remote gateway (if set), and  
localhost (loopback) **even if remote is configured.**

If multiple gateways are reachable, it prints all of them. Multiple gateways are supported when you use isolated profiles/ports (e.g., a rescue bot), but most installs still run a single gateway.



```
openclaw gateway probe
openclaw gateway probe --json
```

&gt;

## Remote over SSH (Mac app parity)

The macOS app “Remote over SSH” mode uses a local port-forward so the remote gateway (which may be bound to loopback only) becomes reachable at `ws://127.0.0.1:<port>` .

CLI equivalent:

```
openclaw gateway probe --ssh user@gateway-host
```

Options:

- `--ssh <target>` : `user@host` or `user@host:port` (port defaults to 22 ).
- `--ssh-identity <path>` : identity file.
- `--ssh-auto` : pick the first discovered gateway host as SSH target (LAN/WAB only).

Config (optional, used as defaults):

```
gateway.remote.sshTarget
gateway.remote.sshIdentity
```

## gateway call <method>

Low-level RPC helper.

```
openclaw gateway call status
openclaw gateway call logs.tail --params '{"sinceMs": 60000}'
```

## Manage the Gateway service



```
openclaw gateway install
openclaw gateway start
openclaw gateway stop
openclaw gateway restart
openclaw gateway uninstall
```

### Notes:

`gateway install` supports `--port` , `--runtime` , `--token` , `--force` , `--json` .

Lifecycle commands accept `--json` for scripting.

## Discover gateways (Bonjour)

`gateway discover` scans for Gateway beacons ( `_openclaw-gw._tcp` ).

Multicast DNS-SD: `local`.

Unicast DNS-SD (Wide-Area Bonjour): choose a domain (example: `openclaw.internal.` ) and set up split DNS + a DNS server; see

Only gateways with Bonjour discovery enabled (default) advertise the beacon.

Wide-Area discovery records include (TXT):

```
role (gateway role hint)
transport (transport hint, e.g. gateway )
gatewayPort (WebSocket port, usually 18789 )
sshPort (SSH port; defaults to 22 if not present)
tailnetDns (MagicDNS hostname, when available)
```



gatewayTls / gatewayTlsSha256 (TLS enabled + cert fingerprint)

cliPath (optional hint for remote installs)

>

## gateway discover

```
openclaw gateway discover
```

### Options:

--timeout <ms> : per-command timeout (browse/resolve); default 2000 .

--json : machine-readable output (also disables styling/spinner).

### Examples:

```
openclaw gateway discover --timeout 4000  
openclaw gateway discover --json | jq '.beacons[].wsUrl'
```

< doctor

health >

Powered by [mintlify](#)