



≡ Agent coordination > Agent Send

Agent coordination

Agent Send

`openclaw agent` runs a single agent turn without needing an inbound chat message. By default it goes **through the Gateway**; add `--local` to force the embedded runtime on the current machine.

Behavior

Required: `--message <text>`

Session selection:

- `--to <dest>` derives the session key (group/channel targets preserve isolation; direct chats collapse to `main`), **or**

- `--session-id <id>` reuses an existing session by id, **or**

- `--agent <id>` targets a configured agent directly (uses that agent's `main` session key)

Runs the same embedded agent runtime as normal inbound replies.

Thinking/verbose flags persist into the session store.

Output:

- default: prints reply text (plus `MEDIA:<url>` lines)

- `--json` : prints structured payload + metadata

Optional delivery back to a channel with `--deliver` + `--channel` (target formats match `openclaw message --target`).



Use `--reply-channel / --reply-to / --reply-account` to override delivery without changing the session.

If the Gateway is unreachable, the CLI **falls back** to the embedded local run.

Examples

```
openclaw agent --to +15555550123 --message "status update"
openclaw agent --agent ops --message "Summarize logs"
openclaw agent --session-id 1234 --message "Summarize inbox" --thinking medium
openclaw agent --to +15555550123 --message "Trace logs" --verbose on --json
openclaw agent --to +15555550123 --message "Summon reply" --deliver
openclaw agent --agent ops --message "Generate report" --deliver --reply-channel :
```

Flags

`--local` : run locally (requires model provider API keys in your shell)

`--deliver` : send the reply to the chosen channel

`--channel` : delivery channel

(whatsapp|telegram|discord|googlechat|slack|signal|imessage , default: whatsapp)

`--reply-to` : delivery target override

`--reply-channel` : delivery channel override

`--reply-account` : delivery account id override

`--thinking <off|minimal|low|medium|high|xhigh>` : persist thinking level (GPT-5.2 + Codex models only)

`--verbose <on|full|off>` : persist verbose level

`--timeout <seconds>` : override agent timeout

`--json` : output structured JSON



Powered by **mintlify**

