



≡ Built-in tools > **Web Tools**

Built-in tools

Web Tools

OpenClaw ships two lightweight web tools:

`web_search` — Search the web via Brave Search API (default) or Perplexity Sonar (direct or via OpenRouter).

`web_fetch` — HTTP fetch + readable extraction (HTML → markdown/text).

These are **not** browser automation. For JS-heavy sites or logins, use the **Browser tool**.

How it works

`web_search` calls your configured provider and returns results.

Brave (default): returns structured results (title, URL, snippet).


Perplexity: returns AI-synthesized answers with citations from real-time web search.

Results are cached by query for 15 minutes (configurable).

`web_fetch` does a plain HTTP GET and extracts readable content (HTML → markdown/text). It does **not** execute JavaScript.

`web_fetch` is enabled by default (unless explicitly disabled).

Choosing a search provider

 Provider	Pros	Cons	API Key
Brave (default)	Fast, structured results, free tier	Traditional search results	BRAVE_API_KEY
Perplexity	AI-synthesized answers, citations, real-time	Requires Perplexity or OpenRouter access	OPENROUTER_API_KEY or PERPLEXITY_API_KEY

See [Brave Search setup](#) and [Perplexity Sonar](#) for provider-specific details.

Set the provider in config:

```
{
  tools: {
    web: {
      search: {
        provider: "brave", // or "perplexity"
      },
    },
  },
}
```

Example: switch to Perplexity Sonar (direct API):



```
tools: {  
  web: {  
    search: {  
      provider: "perplexity",  
      perplexity: {  
        apiKey: "pplx-...",  
        baseUrl: "https://api.perplexity.ai",  
        model: "perplexity/sonar-pro",  
      },  
    },  
  },  
},  
}
```

Getting a Brave API key

1. Create a Brave Search API account at <https://brave.com/search-api/>
2. In the dashboard, choose the **Data for Search** plan (not “Data for AI”) and generate an API key.
3. Run `openclaw configure --section web` to store the key in config (recommended), or set `BRAVE_API_KEY` in your environment.

Brave provides a free tier plus paid plans; check the Brave API portal for the current limits and pricing.

Where to set the key (recommended)

Recommended: run `openclaw configure --section web` . It stores the key in `~/.openclaw/openclaw.json` under `tools.web.search.apiKey` .

Environment alternative: set `BRAVE_API_KEY` in the Gateway process environment. For a gateway install, put it in `~/.openclaw/.env` (or your service environment). See [Brave API Key](#) .

Using Perplexity (direct or via OpenRouter)



Perplexity Sonar models have built-in web search capabilities and return AI-synthesized answers with citations. You can use them via OpenRouter (no credit card required – supports crypto/prepaid).

Getting an OpenRouter API key

1. Create an account at <https://openrouter.ai/>
2. Add credits (supports crypto, prepaid, or credit card)
3. Generate an API key in your account settings

Setting up Perplexity search

```
{
  tools: {
    web: {
      search: {
        enabled: true,
        provider: "perplexity",
        perplexity: {
          // API key (optional if OPENROUTER_API_KEY or PERPLEXITY_API_KEY is set)
          apiKey: "sk-or-v1-...",
          // Base URL (key-aware default if omitted)
          baseUrl: "https://openrouter.ai/api/v1",
          // Model (defaults to perplexity/sonar-pro)
          model: "perplexity/sonar-pro",
        },
      },
    },
  },
}
```

Environment alternative: set `OPENROUTER_API_KEY` or `PERPLEXITY_API_KEY` in the Gateway environment. For a gateway install, put it in

```
~/openclaw/.env .  
🤖
```

If no base URL is set, OpenClaw chooses a default based on the API key source:

```
PERPLEXITY_API_KEY or pplx-... → https://api.perplexity.ai  
OPENROUTER_API_KEY or sk-or-... → https://openrouter.ai/api/v1  
Unknown key formats → OpenRouter (safe fallback)
```

Available Perplexity models

Model	Description	Best for
perplexity/sonar	Fast Q&A with web search	Quick lookups
perplexity/sonar-pro (default)	Multi-step reasoning with web search	Complex questions
perplexity/sonar-reasoning-pro	Chain-of-thought analysis	Deep research

web_search

Search the web using your configured provider.

Requirements

```
tools.web.search.enabled must not be false (default: enabled)
```

API key for your chosen provider:

```
Brave: BRAVE_API_KEY or tools.web.search.apiKey  
Perplexity: OPENROUTER_API_KEY , PERPLEXITY_API_KEY , or  
tools.web.search.perplexity.apiKey
```

Config



```
tools: {
  web: {
    search: {
      enabled: true,
      apiKey: "BRAVE_API_KEY_HERE", // optional if BRAVE_API_KEY is set
      maxResults: 5,
      timeoutSeconds: 30,
      cacheTtlMinutes: 15,
    },
  },
},
}
```

Tool parameters

query (required)

count (1-10; default from config)

country (optional): 2-letter country code for region-specific results (e.g., "DE", "US", "ALL"). If omitted, Brave chooses its default region.

search_lang (optional): ISO language code for search results (e.g., "de", "en", "fr")

ui_lang (optional): ISO language code for UI elements

freshness (optional): filter by discovery time

Brave: pd , pw , pm , py , or YYYY-MM-DDtoYYYY-MM-DD

Perplexity: pd , pw , pm , py

Examples:

```
 // German-specific search
await web_search({
  query: "TV online schauen",
  count: 10,
  country: "DE",
  search_lang: "de",
});

// French search with French UI
await web_search({
  query: "actualités",
  country: "FR",
  search_lang: "fr",
  ui_lang: "fr",
});

// Recent results (past week)
await web_search({
  query: "TMBG interview",
  freshness: "pw",
});
```

web_fetch

Fetch a URL and extract readable content.

web_fetch requirements

`tools.web.fetch.enabled` must not be `false` (default: `enabled`)

Optional Firecrawl fallback: set `tools.web.fetch.firecrawl.apiKey` or `FIRECRAWL_API_KEY` .

web_fetch config



```
tools: {
  web: {
    fetch: {
      enabled: true,
      maxChars: 50000,
      maxCharsCap: 50000,
      maxResponseBytes: 2000000,
      timeoutSeconds: 30,
      cacheTtlMinutes: 15,
      maxRedirects: 3,
      userAgent: "Mozilla/5.0 (Macintosh; Intel Mac OS X 14_7_2) AppleWebKit/53",
      readability: true,
      firecrawl: {
        enabled: true,
        apiKey: "FIRECRAWL_API_KEY_HERE", // optional if FIRECRAWL_API_KEY is set
        baseUrl: "https://api.firecrawl.dev",
        onlyMainContent: true,
        maxAgeMs: 86400000, // ms (1 day)
        timeoutSeconds: 60,
      },
    },
  },
},
}
```

web_fetch tool parameters

`url` (required, http/https only)

`extractMode` (`markdown` | `text`)

`maxChars` (truncate long pages)

Notes:

`web_fetch` uses Readability (main-content extraction) first, then Firecrawl (if configured). If both fail, the tool returns an error.



Firecrawl requests use bot-circumvention mode and cache results by default.

`web_fetch` sends a Chrome-like User-Agent and Accept-Language by default; override `userAgent` if needed.

`web_fetch` blocks private/internal hostnames and re-checks redirects (limit with `maxRedirects`).

`maxChars` is clamped to `tools.web.fetch.maxCharsCap` .

`web_fetch` caps the downloaded response body size to `tools.web.fetch.maxResponseBytes` before parsing; oversized responses are truncated and include a warning.

`web_fetch` is best-effort extraction; some sites will need the browser tool.

See [Firecrawl](#) for key setup and service details.

Responses are cached (default 15 minutes) to reduce repeated fetches.

If you use tool profiles/allowlists, add `web_search / web_fetch` or `group:web` .

If the Brave key is missing, `web_search` returns a short setup hint with a docs link.

< Exec Tool

apply_patch Tool >

Powered by [mintlify](#)