



☰ Other install methods > Podman

Other install methods

Podman

Run the OpenClaw gateway in a **rootless** Podman container. Uses the same image as Docker (build from the repo [Dockerfile](#)).

Requirements

Podman (rootless)

Sudo for one-time setup (create user, build image)

Quick start

1. **One-time setup** (from repo root; creates user, builds image, installs launch script):

```
./setup-podman.sh
```

This also creates a minimal `~openclaw/.openclaw/openclaw.json` (sets `gateway.mode="local"`) so the gateway can start without running the wizard.

By default the container is **not** installed as a systemd service, you start it manually (see below). For a production-style setup with auto-start and restarts, install it as a systemd Quadlet user service instead:

```
 /setup-podman.sh --quadlet
```

(Or set `OPENCLAW_PODMAN_QUADLET=1` ; use `--container` to install only the container and launch script.)

2. Start gateway (manual, for quick smoke testing):

```
./scripts/run-openclaw-podman.sh launch
```

3. Onboarding wizard (e.g. to add channels or providers):

```
./scripts/run-openclaw-podman.sh launch setup
```

Then open `http://127.0.0.1:18789/` and use the token from `~openclaw/.openclaw/.env` (or the value printed by setup).

Systemd (Quadlet, optional)

If you ran `./setup-podman.sh --quadlet` (or `OPENCLAW_PODMAN_QUADLET=1`), a `openclaw.service` unit is installed so the gateway runs as a systemd user service for the `openclaw` user. The service is enabled and started at the end of setup.

Start: `sudo systemctl --machine openclaw@ --user start openclaw.service`


Stop: `sudo systemctl --machine openclaw@ --user stop openclaw.service`

Status: `sudo systemctl --machine openclaw@ --user status openclaw.service`

Logs: `sudo journalctl --machine openclaw@ --user -u openclaw.service -f`

The quadlet file lives at

`~openclaw/.config/containers/systemd/openclaw.container` . To change ports or env, edit that file (or the `.env` it sources), then `sudo systemctl --`

machine openclaw@ --user daemon-reload and restart the service. On boot,  the service starts automatically if lingering is enabled for openclaw (setup does this when loginctl is available).

>

To add quadlet **after** an initial setup that did not use it, re-run:
`./setup-podman.sh --quadlet .`

The openclaw user (non-login)

`setup-podman.sh` creates a dedicated system user `openclaw` :

Shell: `nologin` – no interactive login; reduces attack surface.

Home: e.g. `/home/openclaw` – holds `~/.openclaw` (config, workspace) and the launch script `run-openclaw-podman.sh` .

Rootless Podman: The user must have a **subuid** and **subgid** range. Many distros assign these automatically when the user is created. If setup prints a warning, add lines to `/etc/subuid` and `/etc/subgid` :

```
openclaw:100000:65536
```

Then start the gateway as that user (e.g. from cron or systemd):

```
sudo -u openclaw /home/openclaw/run-openclaw-podman.sh
sudo -u openclaw /home/openclaw/run-openclaw-podman.sh setup
```

Config: Only `openclaw` and root can access `/home/openclaw/.openclaw` .
 To edit config: use the Control UI once the gateway is running, or
`sudo -u openclaw $EDITOR /home/openclaw/.openclaw/openclaw.json` .

Environment and config



Token: Stored in `~openclaw/.openclaw/.env` as `OPENCLAW_GATEWAY_TOKEN` .
`setup-podman.sh` and `run-openclaw-podman.sh` generate it if missing
 (uses `openssl` , `python3` , or `od`).

Optional: In that `.env` you can set provider keys (e.g.
`GROQ_API_KEY` , `OLLAMA_API_KEY`) and other OpenClaw env vars.

Host ports: By default the script maps `18789` (gateway) and `18790`
 (bridge). Override the **host** port mapping with
`OPENCLAW_PODMAN_GATEWAY_HOST_PORT` and `OPENCLAW_PODMAN_BRIDGE_HOST_PORT`
 when launching.

Paths: Host config and workspace default to `~openclaw/.openclaw` and
`~openclaw/.openclaw/workspace` . Override the host paths used by the
 launch script with `OPENCLAW_CONFIG_DIR` and `OPENCLAW_WORKSPACE_DIR` .

Useful commands

Logs: With quadlet: `sudo journalctl --machine openclaw@ --user -u`
`openclaw.service -f` . With script: `sudo -u openclaw podman logs -f`
`openclaw`

Stop: With quadlet: `sudo systemctl --machine openclaw@ --user stop`
`openclaw.service` . With script: `sudo -u openclaw podman stop openclaw`

Start again: With quadlet: `sudo systemctl --machine openclaw@ --user`
`start openclaw.service` . With script: re-run the launch script or
`podman start openclaw`

Remove container: `sudo -u openclaw podman rm -f openclaw` — config and
 workspace on the host are kept

Troubleshooting

Permission denied (EACCES) on config or auth-profiles: The
 container defaults to `--userns=keep-id` and runs as the same uid/gid
 as the host user running the script. Ensure your host
`OPENCLAW_CONFIG_DIR` and `OPENCLAW_WORKSPACE_DIR` are owned by that user.



Gateway start blocked (missing gateway.mode=local): Ensure `~openclaw/.openclaw/openclaw.json` exists and sets `gateway.mode="local"` . `setup-podman.sh` creates this file if missing.

Rootless Podman fails for user openclaw: Check `/etc/subuid` and `/etc/subgid` contain a line for `openclaw` (e.g. `openclaw:100000:65536`). Add it if missing and restart.

Container name in use: The launch script uses `podman run --replace` , so the existing container is replaced when you start again. To clean up manually: `podman rm -f openclaw` .

Script not found when running as openclaw: Ensure `setup-podman.sh` was run so that `run-openclaw-podman.sh` is copied to `openclaw`'s home (e.g. `/home/openclaw/run-openclaw-podman.sh`).

Quadlet service not found or fails to start: Run `sudo systemctl --machine openclaw@ --user daemon-reload` after editing the `.container` file. Quadlet requires `cgroups v2`: `podman info --format '{{.Host.CgroupsVersion}}'` should show `2` .

Optional: run as your own user

To run the gateway as your normal user (no dedicated `openclaw` user): build the image, create `~/.openclaw/.env` with `OPENCLAW_GATEWAY_TOKEN` , and run the container with `--userns=keep-id` and mounts to your `~/.openclaw` . The launch script is designed for the `openclaw-user` flow; for a single-user setup you can instead run the `podman run` command from the script manually, pointing `config` and `workspace` to your home. Recommended for most users: use `setup-podman.sh` and run as the `openclaw` user so `config` and `process` are isolated.

< Docker

Nix >



Powered by **mintlify**

>