Canada's Capital University

Obstacle Detection Using Monocular Camera for Low Flying Unmanned Aerial Vehicle

Fan Zhang, B.Sc.

Systems and Computer Engineering
Carleton University
January 2015






Canada's Capital University

Bearing and Range Sensors

- Radar, Lidar, Sonar
 - Require Scanning
- 3D Flash Lidar





Bearing Only Sensor

- Camera
 - Binocular Configuration
 - Monocular Configuration


Computer Algorithm

- Machine Vision
- Simultaneous Localization and Mapping (SLAM)






Problem Statement





Problem Statement

Canada's Capital University




UAV Vertical Rise: 122 meters per minute

Clearance: 10 meters

303.64 meters or further @ 60 knots (30.87m/s) 505.97 meters or further @ 100 knots (51.44m/s)



Problem Statement





Canada's Capital University

SUAS Take Off










Canada's Capital University

Sensors and Data Acquisition Equipment





GS-111M



GPS Antenna



CDAC





Canada's Capital University

Aerial Video Footage





Canada's Capital University

Camera Calibration


Parameter	Result
f_x	887.6 pixels
f_y	805.7 pixels
c_x	381.8 pixels
c_y	293.7 pixels
k_1	-0.102
k_2	-0.535
p_1	1.15e-003
p_2	8.40e-003

















Contribution 2: CC-EKF-SLAM









Contribution 2: CC-EKF-SLAM



Inverse Depth Parameterization



Camera Centric Coordinate System



* n = number of landmarks currently tracked by filter



Contribution 3: Aerial Data Processed by CC-EKF-SLAM

Canada's Capital University

Natural Scene


New features Kalman predicted points LK output points Feature ID LK input points Kalman updated points

Airport Landing Scene





Contribution 3: Flight Result Convergence Analysis





Landmark 13 at various frames




Contribution 3: Flight Result SUAS Localization

Canada's Capital University

Natural Scene

Airport Landing Scene







Contribution 3: Flight Result Landmark Mapping

Canada's Capital University

Natural Scene



Airport Landing Scene





Contribution 3: Flight Result

Canada's Capital University

This contribution is published in


The 2012 IEEE International Instrumentation and Measurement Technology Conference

[7] F. Zhang, R. Goubran, and P. Straznicky, "Obstacle detection for low flying UAS using monocular camera," in *Proceedings of the IEEE International Instrumentation and Measurement Technology Conference*, 2012, pp. 2133-2137.

Contribution 4: Error Analysis

Canada's Capital University

Oscillatory Motion of the UAV




Error from Camera Calibration

$$x = f_x\left(\frac{X}{Z}\right) + c_x$$


$$y = f_y\left(\frac{Y}{Z}\right) + c_y$$

Image Resolution





Contribution 4: Error Analysis Effect of Oscillatory Rotation






Contribution 4: Error Analysis Effect of Camera Calibration Error and

Canada's Capital University


Image Resolution



 f_r

 $(f_y \text{ affects})$

No Effect





Contribution 4: Error Analysis Effect of Camera Calibration Error and Image Resolution

Canada's Capital University

UAV Localization

Landmarks Mapping

Lens Distortion

Diverging Error




Image Resolution 1080 x 1440 or higher

1080 x 1440 or higher

Canada's Capital University

Contribution 1:

Aerial Video and Data Collected through Test Flight

Contribution 2:

CC-EKF-SLAM Implemented

Contribution 3:

Aerial Data Processed by CC-EKF-SLAM

Contribution 4:

Error Analysis



Recommendations for Future Work

- Add lens distortion model
- Increase sensor resolution
- Add landmark quality checking and filtering function
- Research on map joining algorithm
- Increase accuracy by syncing to GPS
- Investigate on the sensitivity problem to oscillatory rotation



Acknowledgement

- Rafik Goubran, Paul Straznicky
- Sander Geophysics Ltd.
- Ontario Centers of Excellence and NSERC
- My Family