

Proposed list of corrections for NIST SP 800-90B 6.3 Estimators

Gen'ya SAKURAI

2025/6/1

Chapter 1

Proposed list of corrections for NIST SP 800-90B 6.3 Estimators

1.1 Introduction

This list of corrections for NIST SP 800-90B [1] 6.3 Estimators has been drafted so that an entropy estimating tool for claiming conformance can be developed in a traceable manner.

1.2 Corrections to 6.3.4 The Compression Estimate

1. Correction to step 4-b-ii

If $\text{dict}[s_i]$ is zero, add that value to the dictionary, i.e., $\text{dict}[s'_i] = i$. Let $D_{i-d} = i$.

should be replaced by the following:

If $\text{dict}[s_i']$ is zero, add that value to the dictionary, i.e., $\text{dict}[s'_i] = i$. Let $D_{i-d} = i$.

2. Correction to the expression of $G(z)$

The Eq.(1.1) should be replaced by Eq.1.2.

$$G(z) = \frac{1}{\nu} \sum_{t=d+1}^L \sum_{u=1}^t \log_2(u) F(z, t, u) \quad (1.1)$$

$$G(z) = \frac{1}{\nu} \sum_{t=d+1}^{\lfloor L/b \rfloor} \sum_{u=1}^t \log_2(u) F(z, t, u) \quad (1.2)$$

This correction makes sense if the summation over t starts from $d+1$ then it should end at $\lfloor L/b \rfloor$. Also the factor $\frac{1}{\nu}$ coincides with this argument as $\nu = \lfloor L/b \rfloor - d$.

The Eq.(1.2) can be further rewritten to as Eq.(1.3), as $\log_2(1) = 0$.

$$G(z) = \frac{1}{\nu} \sum_{t=d+1}^{\lfloor L/b \rfloor} \sum_{u=2}^t \log_2(u) F(z, t, u) \quad (1.3)$$

Note that the r.h.s. of Eq.(1.3) can be optimized further for algorithmic efficiency (see [3]).

1.3 Corrections to 6.3.10 The LZ78Y Prediction Estimate

1. Missing step

The variable C is used in step 4 without its definition. So the following new step should be introduced just before step 4, and steps 4 to 6 should be renumbered accordingly.

Let C be the number of ones in *correct*.

2. Corrections to step 3-a-ii

ii: If $(s_{i-j-1}, \dots, s_{i-2})$ is in D ,

Let $D[s_{i-j-1}, \dots, s_{i-2}][s_{i-1}] = D[s_{i-j-1}, \dots, s_{i-2}][s_{i-1}] + 1$

should be replaced by the following:

ii: **if** $(s_{i-j-1}, \dots, s_{i-2})$ is in D , **then**

iii: **if** $[(s_{i-j-1}, \dots, s_{i-2}), s_{i-1}]$ is in D , **then**

iv: Let $D[s_{i-j-1}, \dots, s_{i-2}][s_{i-1}] = D[s_{i-j-1}, \dots, s_{i-2}][s_{i-1}] + 1$

v: **else**

vi: **if** $dictionarySize < maxDictionarySize$ **then**

vii: Let $D[s_{i-j-1}, \dots, s_{i-2}][s_{i-1}] = 0$

▷ With this step, the issue can be resolved that the value of $D[s_{i-j-1}, \dots, s_{i-2}][s_{i-1}]$ is undefined, when $(s_{i-j-1}, \dots, s_{i-2})$ is in D but $[(s_{i-j-1}, \dots, s_{i-2}), s_{i-1}]$ is not in D .

viii: $dictionarySize = dictionarySize + 1$

▷ The value $dictionarySize$ is equal to the size of dictionary D , or the number of (x, y) pairs in $D[x][y]$.

ix: **end if**

x: **end if**

xi: **end if**

Justification

The above proposed corrections are based on the following analysis:

- a The variable C is used in step 4 without its definition.
- b *dictionarySize* is counted on parent node level.
 From the current step 3-a-i, it can be read as if *dictionarySize* is counted on parent node level (i.e. $D[s_{i-j-1}, \dots, s_{i-2}]$). However, in the other prediction estimates, *dictionarySize* is counted not on parent node level but on leaf node level (i.e. $D[s_{i-j-1}, \dots, s_{i-2}][s_{i-1}]$). In addition, $maxDictionarySize = 65536$ is used in 6.3.7 through 6.3.10 of NIST SP 800-90B. It should also be noted that, counting *dictionarySize* on parent node level can mean that larger $maxDictionarySize$ is used when we see overall dictionary size (i.e. dictionary size at leaf node level). So it is inconsistent to count *dictionarySize* on parent node level only in 6.3.10 The

LZ78Y Prediction Estimate. From the above, it should be reasonable to count *dictionarySize* on the leaf node level.

- c The behavior of step 3-a-ii-1 is undefined when $D[s_{i-j-1}, \dots, s_{i-2}][s_{i-1}]$ is not initialized.

In step 3-a-i-2, only specific value of $D[s_{i-j-1}, \dots, s_{i-2}][s_{i-1}]$ is initialized to zero, based on the value of s_{i-1} . In step 3-a-ii-1, $D[s_{i-j-1}, \dots, s_{i-2}][s_{i-1}]$ is incremented.

From the above, the behavior of step 3-a-ii-1 is undefined when $D[s_{i-j-1}, \dots, s_{i-2}][s_{i-1}]$ is not initialized.

3. Column header in Example

Also the column header

Max $D[prev]$ entry

in the table for *Example* should be replaced by

$\arg \max_y D[prev][y]$

Bibliography

- [1] Meltem Sönmez Turan, Elaine Barker, John Kelsey, Kerry A. McKay, Mary L. Baish, Mike Boyle *Recommendation for the Entropy Sources Used for Random Bit Generation*, NIST Special Publication 800-90B, Jan. 2018
- [2] Franck W. J. Oliver, Daniel W. Lozier, Ronald F. Boisvert, Charles W. Clark, *NIST Handbook of Mathematical Functions*, National Institute of Standards and Technology, 2010
- [3] Gen'ya SAKURAI, *Implementation Notes for entropy estimation based on NIST SP 800-90B non-IID track*, June 27, 2023 https://github.com/g-g-sakura/AnotherEntropyEstimationTool/blob/main/documentation/SP800-90B_EntropyEstimate_ImplementationNotes.pdf