



Stability of Linear Fractional Differential Equations with Delays

A coupled Parabolic-Hyperbolic PDEs formulation

IFAC WC 2017, Toulouse

13 July 2017

Florian MONTEGHETTI,^{1*} Ghislain Haine,² Denis MATIGNON²

¹ONERA – The French Aerospace Lab, Toulouse

²ISAE-SUPAERO, Université de Toulouse, Toulouse

Contact: florian.monteghetti@onera.fr



Outline

- 1 Introduction
 - Introduction
- 2 Coupled PDEs formulation: stability results
- 3 An eigenvalue approach to stability
- 4 Conclusion

Motivation: fractional delay systems in aeroacoustics

Context: Noise regulations \Rightarrow research into sound absorption.

Modelling of locally-reacting sound absorbing material

Passive LTI system:


$$p(t, x) = [z \star_t \mathbf{u} \cdot \mathbf{n}(\cdot, x)](t)$$

with kernel $z \in \mathcal{D}'_+(\mathbb{R}) \cap \mathcal{S}'(\mathbb{R})$.

Perforated plate

Cavity

Rigid plate



Motivation: fractional delay systems in aeroacoustics

Context: Noise regulations \Rightarrow research into sound absorption.

Modelling of locally-reacting sound absorbing material

Passive LTI system:


$$p(t, x) = [z \star_t \mathbf{u} \cdot \mathbf{n}(\cdot, x)](t)$$

with kernel $z \in \mathcal{D}'_+(\mathbb{R}) \cap \mathcal{S}'(\mathbb{R})$.

Perforated plate

Cavity

Rigid plate



Key components of \hat{z} : (Monteghetti et al. 2016)

$$\hat{z}(s) = a_0 + a_{1/2}\sqrt{s} + a_\tau e^{-s\tau}$$

Motivation: fractional delay systems in aeroacoustics

Context: Noise regulations \Rightarrow research into sound absorption.

Modelling of locally-reacting sound absorbing material

Passive LTI system:


$$p(t, x) = [z \star_t \mathbf{u} \cdot \mathbf{n}(\cdot, x)](t)$$

with kernel $z \in \mathcal{D}'_+(\mathbb{R}) \cap \mathcal{S}'(\mathbb{R})$.

Perforated plate

Cavity

Rigid plate



Key components of \hat{z} : (Monteghetti et al. 2016)

$$\hat{z}(s) = a_0 + a_{1/2}\sqrt{s} + a_\tau e^{-s\tau}$$

\Rightarrow Boundary condition of a PDE on (p, u) .

Motivation: fractional delay systems in aeroacoustics

Context: Noise regulations \Rightarrow research into sound absorption.

Modelling of locally-reacting sound absorbing material

Passive LTI system:

$$p(t, x) = [z \star_t \mathbf{u} \cdot \mathbf{n}(\cdot, x)](t)$$

with kernel $z \in \mathcal{D}'_+(\mathbb{R}) \cap \mathcal{S}'(\mathbb{R})$.

Perforated plate

Cavity

Rigid plate

Key components of \mathbf{z} : (Monteghetti et al. 2016)

$$\hat{\mathbf{z}}(s) = a_0 + a_{1/2} \sqrt{s} + a_\tau e^{-s\tau}$$

\Rightarrow Boundary condition of a PDE on (p, u) .

\Rightarrow Spatial discretisation yields fractional delay equation ($x \in \mathbb{R}^n$):

$$M \cdot \dot{x}(t) + K \cdot x(t) = F_1 \cdot d^{1/2} x(t) + F_2 \cdot x(t - \tau).$$

Motivation: fractional delay systems in aeroacoustics

Context: Noise regulations \Rightarrow research into sound absorption.

Modelling of locally-reacting sound absorbing material

Passive LTI system:

$$p(t, x) = [z \star_t \mathbf{u} \cdot \mathbf{n}(\cdot, x)](t)$$

with kernel $z \in \mathcal{D}'_+(\mathbb{R}) \cap \mathcal{S}'(\mathbb{R})$.

Perforated plate

Cavity

Rigid plate

Key components of z : (Monteghetti et al. 2016)

$$\hat{z}(s) = a_0 + a_{1/2}\sqrt{s} + a_\tau e^{-s\tau}$$

\Rightarrow Boundary condition of a PDE on (p, u) .

\Rightarrow Spatial discretisation yields fractional delay equation ($x \in \mathbb{R}^n$):

$$M \cdot \dot{x}(t) + K \cdot x(t) = F_1 \cdot d^{1/2}x(t) + F_2 \cdot x(t - \tau).$$

Objective: use parabolic-hyperbolic realisations to study stability.

Outline

- 1 Introduction
- 2 Coupled PDEs formulation: stability results
- 3 An eigenvalue approach to stability
- 4 Conclusion

Outline

- 1 Introduction
- 2 Coupled PDEs formulation: stability results
 - Existing stability results
 - Scalar “toy” model
 - Vector-valued model
- 3 An eigenvalue approach to stability
- 4 Conclusion

Existing stability results

Time-delay system of retarded type

$$\dot{x}(t) = A_0 x(t) + \sum_i A_i x(t - \tau_i) \Leftrightarrow \dot{X} = \mathcal{A} X$$

- Roots of characteristic equation $\det \Delta(\lambda) = 0 \Leftrightarrow \lambda \in \sigma_p(\mathcal{A})$.
(Michiels and Niculescu 2014, Chap. 1) (Curtain and Zwart 1995, § 2.4)
- Lyapunov-Krasovskii equivalence theorem.
(Fridman 2014, Chap. 3) (Briat 2014, Thm. 5.2.9)

Existing stability results

Time-delay system of retarded type

$$\dot{x}(t) = A_0 x(t) + \sum_i A_i x(t - \tau_i) \Leftrightarrow \dot{X} = \mathcal{A} X$$

- Roots of characteristic equation $\det \Delta(\lambda) = 0 \Leftrightarrow \lambda \in \sigma_p(\mathcal{A})$.
(Michiels and Niculescu 2014, Chap. 1) (Curtain and Zwart 1995, § 2.4)
- Lyapunov-Krasovskii equivalence theorem.
(Fridman 2014, Chap. 3) (Briat 2014, Thm. 5.2.9)

Fractional differential equation

- BIBO & asymptotic stability with commensurate fractional powers. (Matignon 1996)

Fractional delay differential equation

- BIBO stability with commensurate delays.
(Bonnet and Partington 2002)
- Asymptotic stability with non-commensurate delays.
(Deng, Li and Lü 2007)

Toy model: Laplace technique

Objective: delay-independent stability of

$$\dot{x}(t) = ax(t) + b x(t - \tau) - g d_{\mathcal{C}}^{\alpha} x(t) \quad \text{for } t > \tau, \alpha \in (0, 1)$$


$$x(t) := x^0(t) \quad \text{for } t \in [0, \tau].$$

Theorem. Toy model stability

Under the following algebraic condition:

$$\Re(a) < -|b| \leq 0 \quad \text{and} \quad g \in J_{\alpha},$$

toy model is delay-independent stable.



Toy model: Laplace technique

Objective: delay-independent stability of

$$\dot{x}(t) = a x(t) + b x(t - \tau) - g d_C^\alpha x(t) \quad \text{for } t > \tau, \alpha \in (0, 1)$$


$$x(t) := x^0(t) \quad \text{for } t \in [0, \tau].$$

Theorem. Toy model stability

Under the following algebraic condition:

$$\Re(a) < -|b| \leq 0 \quad \text{and} \quad g \in J_\alpha,$$

toy model is delay-independent stable.



Proof (Sketch). Expression of $\hat{x}(s)$ has 5 terms:

$$\begin{aligned} \hat{x}(s) = & g x^0(0) \hat{h}_c(s) + g x^0(\tau) \hat{h}_d(s) + x^0(\tau) \hat{h}_e(s) \\ & + \hat{x}^0 \hat{h}_a(s) + g \mathcal{L}[d_C^\alpha x^0 \mathbf{1}_{[0, \tau]}] \hat{h}_b(s). \end{aligned}$$

- ① $\hat{h}_{c,d,e}(s)$: final-value theorem.
- ② $\hat{h}_{a,b}(s)$: Callier-Desoer $\hat{\mathcal{A}}(0)$ class and dominated convergence.

Toy model: coupled PDEs formulation (1)

$$\begin{aligned}\dot{x}(t) &= a x(t) + b x(t - \tau) - g d_C^\alpha x(t) \quad \text{for } t > \tau, \alpha \in (0, 1) \\ x(t) &:= x^0(t) \quad \text{for } t \in [0, \tau].\end{aligned}$$

Proposition. Toy model stability

Under the algebraic condition

$$\Re(a) < -|b| \leq 0 \quad \text{and} \quad g > 0,$$

toy model with $x^0(0) = 0$ is delay-independent stable.

Toy model: coupled PDEs formulation (1)

$$\begin{aligned}\dot{x}(t) &= a x(t) + b x(t - \tau) - g d_C^\alpha x(t) \quad \text{for } t > \tau, \alpha \in (0, 1) \\ x(t) &:= x^0(t) \quad \text{for } t \in [0, \tau].\end{aligned}$$

Proposition. Toy model stability

Under the algebraic condition

$$\Re(a) < -|b| \leq 0 \quad \text{and} \quad g > 0,$$

toy model with $x^0(0) = 0$ is delay-independent stable.

Proof. Let $E_x := \frac{1}{2} |x|^2$. Decay rate along trajectories is

$$\dot{E}_x = 2 \Re(a) E_x + \Re \left[\bar{x} (b x_\tau - g d_C^\alpha x(t)) \right], \quad (1)$$

whose sign is *a priori* indefinite.

Toy model: coupled PDEs formulation (1)

$$\begin{aligned}\dot{x}(t) &= a x(t) + b x(t - \tau) - g d_C^\alpha x(t) \quad \text{for } t > \tau, \alpha \in (0, 1) \\ x(t) &:= x^0(t) \quad \text{for } t \in [0, \tau].\end{aligned}$$

Proposition. Toy model stability

Under the algebraic condition

$$\Re(a) < -|b| \leq 0 \quad \text{and} \quad g > 0,$$

toy model with $x^0(0) = 0$ is delay-independent stable.

Proof. Let $E_x := \frac{1}{2} |x|^2$. Decay rate along trajectories is

$$\dot{E}_x = 2 \Re(a) E_x + \Re \left[\bar{x} (b x_\tau - g [D_{RL}^\alpha x - x^0(0) c/t^\alpha]) \right], \quad (1)$$

whose sign is *a priori* indefinite.

Toy model: coupled PDEs formulation (1)

$$\begin{aligned}\dot{x}(t) &= a x(t) + b x(t - \tau) - g d_C^\alpha x(t) \quad \text{for } t > \tau, \alpha \in (0, 1) \\ x(t) &:= x^0(t) \quad \text{for } t \in [0, \tau].\end{aligned}$$

Proposition. Toy model stability

Under the algebraic condition

$$\Re(a) < -|b| \leq 0 \quad \text{and} \quad g > 0,$$

toy model with $x^0(0) = 0$ is delay-independent stable.

Proof. Let $E_x := \frac{1}{2} |x|^2$. Decay rate along trajectories is

$$\dot{E}_x = 2 \Re(a) E_x + \Re \left[\bar{x} (b x_\tau - g [D_{RL}^\alpha x - x^0(0) c/t^\alpha]) \right], \quad (1)$$

whose sign is *a priori* indefinite.

However, energy decay can be proven using suitable realisations.


- ① Hyperbolic for $x_\tau(t)$: transport equation.
- ② Parabolic for $D_{RL}^\alpha x(t)$: heat equation.
- ③ Extended energy $\mathcal{E} \Rightarrow$ sufficient condition for decay.

Toy model: coupled PDEs formulation (2)

Hyperbolic realisation $z \in (0, \ell)$ Transport PDE.

(Engel and Nagel 2000, § VI.6) (Curtain and Zwart 1995, § 2.4)

(Michiels and Niculescu 2014, § 2.2)



$$\begin{cases} \partial_t \psi(t, z) = -c \partial_z \psi(t, z) \\ \psi(t, z=0) := x(t) \\ x(t-\tau) = \psi(t, z=\ell) \end{cases}$$


Initial data $\psi(t = \tau, z) := x^0(\tau - z/c)$.

Toy model: coupled PDEs formulation (2)

Hyperbolic realisation $z \in (0, \ell)$ Transport PDE.

(Engel and Nagel 2000, § VI.6) (Curtain and Zwart 1995, § 2.4)

(Michiels and Niculescu 2014, § 2.2)



Initial data $\psi(t=\tau, z) := x^0(\tau - z/c)$.

Natural energy: $E_\psi(t) := \frac{1}{2} \int_0^\ell |\psi(t, z)|^2 dz$.

Energy balance reflects lossless transport:

$$\begin{aligned} \frac{d}{dt} E_\psi(t) &= -c \int_0^\ell \Re(\partial_z \psi(t, z) \bar{\psi}(t, z)) dz \\ &= -\frac{c}{2} [|\psi(t, z)|^2]_0^\ell \\ &= \frac{c}{2} (|x(t)|^2 - |x(t-\tau)|^2). \end{aligned}$$

Toy model: coupled PDEs formulation (3)

Parabolic realisation $\xi \in (0, \infty)$ (Parabolic) ODE.

(Staffans 1994) (Montseny 1998) (Matignon 2009) (Hélie and Matignon 2006a)

$$\begin{cases} \partial_t \varphi(\xi, t) = -\xi \varphi(\xi, t) + u(t), \quad \varphi(\xi, 0) = 0, \\ D_{\text{RL}}^\alpha x(t) = \int_0^\infty \mu_{1-\alpha}(\xi) [u(t) - \xi \varphi(\xi, t)] d\xi. \end{cases}$$

Toy model: coupled PDEs formulation (3)

Parabolic realisation $\xi \in (0, \infty)$ (Parabolic) ODE.

(Staffans 1994) (Montseny 1998) (Matignon 2009) (Hélie and Matignon 2006a)

$$\begin{cases} \partial_t \varphi(\xi, t) = -\xi \varphi(\xi, t) + u(t), \quad \varphi(\xi, 0) = 0, \\ D_{\text{RL}}^\alpha x(t) = \int_0^\infty \mu_{1-\alpha}(\xi) [u(t) - \xi \varphi(\xi, t)] d\xi. \end{cases}$$

Natural energy: $E_\varphi(t) := \frac{1}{2} \int_0^\infty \xi |\varphi(\xi, t)|^2 \mu_{1-\alpha}(\xi) d\xi.$

Energy balance (expresses dissipativity of D_{RL}^α):

$$\begin{aligned} \frac{d}{dt} E_\varphi(t) &= \Re(\bar{x} D_{\text{RL}}^\alpha x) - \int_0^\infty |x - \xi \varphi(\xi, \cdot)|^2 \mu_{1-\alpha}(\xi) d\xi. \\ &\leq \Re(\bar{x} D_{\text{RL}}^\alpha x). \end{aligned}$$

Toy model: coupled PDEs formulation (4)

Extended energy $\mathcal{E}_k := E_x(t) + k E_\psi(t) + g E_\varphi(t)$,

with $k > 0$ unknown.

- **Parabolic** realisation: cross terms $g \Re(\bar{x} D_{\text{RL}}^\alpha x)$ cancel out

Toy model: coupled PDEs formulation (4)

Extended energy $\mathcal{E}_k := E_x(t) + k E_\psi(t) + g E_\varphi(t)$,

with $k > 0$ unknown.

- **Parabolic** realisation: cross terms $g \Re(\bar{x} D_{\text{RL}}^\alpha x)$ cancel out
- **Hyperbolic** realisation leads to

$$\dot{\mathcal{E}}_k \leq -X^H \Sigma_k X$$

where $X := (x, x_\tau)^\top$ and

$$\Sigma_k := - \begin{pmatrix} \Re(a) + k \frac{c}{2} & \frac{b}{2} \\ \frac{\bar{b}}{2} & -k \frac{c}{2} \end{pmatrix} \stackrel{?}{>} 0.$$

Toy model: coupled PDEs formulation (4)

Extended energy $\mathcal{E}_k := E_x(t) + k E_\psi(t) + g E_\varphi(t)$,

with $k > 0$ unknown.

- **Parabolic** realisation: cross terms $g \Re(\bar{x} D_{\text{RL}}^\alpha x)$ cancel out
- **Hyperbolic** realisation leads to

$$\dot{\mathcal{E}}_k \leq -X^H \Sigma_k X$$

where $X := (x, x_\tau)^\top$ and

$$\Sigma_k := - \begin{pmatrix} \Re(a) + k \frac{c}{2} & \frac{b}{2} \\ \frac{\bar{b}}{2} & -k \frac{c}{2} \end{pmatrix} \stackrel{?}{>} 0.$$

- Eigenvalues: $\lambda_2(k) > \lambda_1(k) = -\frac{\Re(a) + \sqrt{P(k)}}{2}$, with $P(k) > 0$.
- Least stringent condition:

$$\min_{k>0} \lambda_1(k) = -\frac{\Re(a) + |b|}{2} \quad \text{for} \quad k^* = -\frac{\Re(a)}{c}.$$

$$\lambda_1 > 0 \iff \Re(a) < -|b|$$



Vector-valued model

Vector-valued fractional system with delay:

$$\dot{x}(t) = Ax(t) + Bx(t - \tau) - G d_C^\alpha x(t) \quad \text{for } t > \tau, \alpha \in (0, 1)$$

$$x(t) := x^0(t) \quad \text{for } t \in [0, \tau],$$

with $x(t) \in \mathbb{R}^n$.

Theorem. Stability.

Let G be a diagonalisable matrix with eigenvalues $(g_1, \dots, g_n) \geq 0$.
Under the algebraic condition

$$\max_{a \in \sigma(A)} \Re(a) < -\sqrt{\max_{b \in \sigma(B^H B)} |b|} \leq 0,$$

the system with $x^0(0) = 0$ is delay-independent stable.

Proof. Similar in spirit to toy model, with extended energy

$$\mathcal{E}(t) := \sum_{i \in \llbracket 1, n \rrbracket} E_{x_i}(t) + k E_{\psi_i}(t) + g_i E_{\varphi_i}(t).$$

Outline

- 1 Introduction
- 2 Coupled PDEs formulation: stability results
- 3 An eigenvalue approach to stability
 - State of the art
 - Eigenvalue approach to stability
- 4 Conclusion

Numerical methods for stability: state of the art

Time-delay system of retarded type

- Design an approximate Lyapunov-Krasovskii functional, and formulate a numerically-tractable LMI.

(Seuret, Gouaisbaut and Ariba 2015) (Baudouin, Seuret and Safi 2016)

Numerical methods for stability: state of the art

Time-delay system of retarded type

- Design an approximate Lyapunov-Krasovskii functional, and formulate a numerically-tractable LMI.
(Seuret, Gouaisbaut and Ariba 2015) (Baudouin, Seuret and Safi 2016)
- Study of characteristic roots. (Michiels and Niculescu 2014, § 2)
 - Count unstable roots. (Li, Niculescu and Cela 2015)
 - Locate unstable roots : eigenvalue approach.
 - Spectrum of operator semigroup $e^{t\mathcal{A}}$.
DDE-BIFTOOL (Engelborghs, Luzyanina and Roose 2002)
 - Spectrum of generator \mathcal{A} using **hyperbolic** realisation.
TRACE-DDE (Breda, Maset and Vermiglio 2005)

Numerical methods for stability: state of the art

Time-delay system of retarded type

- Design an approximate Lyapunov-Krasovskii functional, and formulate a numerically-tractable LMI.

(Seuret, Gouaisbaut and Ariba 2015) (Baudouin, Seuret and Safi 2016)

- Study of characteristic roots. (Michiels and Niculescu 2014, § 2)

- Count unstable roots. (Li, Niculescu and Cela 2015)

- Locate unstable roots : eigenvalue approach.

- Spectrum of operator semigroup $e^{t\mathcal{A}}$.

DDE-BIFTOOL (Engelborghs, Luzyanina and Roose 2002)

- Spectrum of generator \mathcal{A} using **hyperbolic** realisation.

TRACE-DDE (Breda, Maset and Vermiglio 2005)

Fractional delay differential equation

- YALTA. (Fioravanti et al. 2012) (Avanessoff, Fioravanti and Bonnet 2013)

- Count unstable roots. (Zhang et al. 2016)

⇒ Eigenvalue approach using **parabolic**-**hyperbolic** realisation?

Eigenvalue approach to stability: overview

Vector-valued fractional delay system:

$$\dot{x}(t) = Ax(t) + Bx(t - \tau) - G d_C^\alpha x(t - \tau_\alpha) \quad (\tau_\alpha \geq 0).$$

Hyperbolic realisation (PDE)

$$z \in (0, 1)$$

$$\partial_t \psi_h = -\tau^{-1} \partial_z \psi_h$$

$$\psi_h(0) = x$$

$$x(t - \cdot) = \psi_h(z = 1)$$

⇒ High-order discretisation

Parabolic realisation (ODE)

$$\xi \in (0, \infty)$$

$$\partial_t \varphi_h = -\xi \varphi_h + x$$

$$d_C^\alpha x = \sum_{k \in \llbracket 1, N_\xi \rrbracket} \mu_k \varphi_h(\xi_k)$$

⇒ Quadrature or optimisation

Eigenvalue approach to stability: overview

Vector-valued fractional delay system:

$$\dot{x}(t) = Ax(t) + Bx(t - \tau) - G d_C^\alpha x(t - \tau_\alpha) \quad (\tau_\alpha \geq 0).$$

Hyperbolic realisation (PDE)

$$z \in (0, 1)$$

$$\partial_t \psi_h = -\tau^{-1} \partial_z \psi_h$$

$$\psi_h(0) = x$$

$$x(t - \cdot) = \psi_h(z = 1)$$

⇒ High-order discretisation

Parabolic realisation (ODE)

$$\xi \in (0, \infty)$$

$$\partial_t \varphi_h = -\xi \varphi_h + x$$

$$d_C^\alpha x = \sum_{k \in \llbracket 1, N_\xi \rrbracket} \mu_k \varphi_h(\xi_k)$$

⇒ Quadrature or optimisation

⇒ Cauchy problem on \mathbb{C}^n :

$$\dot{X}_h(t) = \mathcal{A}_h X_h(t), \quad \text{with } X_h := (x, \psi_h, \varphi_h).$$


Challenge: ensure $\sigma(\mathcal{A}_h)$ is “meaningful”.

Numerical experiment: spectral structure

Case 1: $x(t) \in \mathbb{R}^2$, $\dot{x}(t) = A \cdot x(t) + B \cdot x(t - \tau) - g I_2 \cdot d_C^{1/2} x(t)$,
with

$$\max_{a \in \sigma(A)} \Re(a) < -\sqrt{\max_{b \in \sigma(B^H B)} |b|} \leq 0 \quad \text{verified.}$$

$$\sigma(\mathcal{A})$$




Pure delay $g = 0$ (●) $\sigma(\mathcal{A}) = \sigma_p(\mathcal{A})$ (discrete)

Numerical experiment: spectral structure

Case 1: $x(t) \in \mathbb{R}^2$, $\dot{x}(t) = A \cdot x(t) + B \cdot x(t - \tau) - g I_2 \cdot d_C^{1/2} x(t)$,
with

$$\max_{a \in \sigma(A)} \Re(a) < -\sqrt{\max_{b \in \sigma(B^H B)} |b|} \leq 0 \quad \text{verified.}$$

$$\sigma(\mathcal{A})$$



Pure delay $g = 0$ (●) $\sigma(\mathcal{A}) = \sigma_p(\mathcal{A})$ (discrete)

Fractional derivative $g \neq 0 \Rightarrow \sigma_c(\mathcal{A}) \neq \emptyset$ (essential)


(○) $g = +2 > 0 \Rightarrow$ stable

Numerical experiment: spectral structure

Case 1: $x(t) \in \mathbb{R}^2$, $\dot{x}(t) = A \cdot x(t) + B \cdot x(t - \tau) - g I_2 \cdot d_C^{1/2} x(t)$,
with

$$\max_{a \in \sigma(A)} \Re(a) < -\sqrt{\max_{b \in \sigma(B^H B)} |b|} \leq 0 \quad \text{verified.}$$

$$\sigma(\mathcal{A})$$



Pure delay $g = 0$ (●) $\sigma(\mathcal{A}) = \sigma_p(\mathcal{A})$ (discrete)

Fractional derivative $g \neq 0 \Rightarrow \sigma_c(\mathcal{A}) \neq \emptyset$ (essential)


(○) $g = +2 > 0 \Rightarrow$ stable

(⊗) $g = -2 < 0 \Rightarrow$ unstable

Numerical experiment: spectral structure

Case 1: $x(t) \in \mathbb{R}^2$, $\dot{x}(t) = A \cdot x(t) + B \cdot x(t - \tau) - g I_2 \cdot d_C^{1/2} x(t)$,
with

$$\max_{a \in \sigma(A)} \Re(a) < -\sqrt{\max_{b \in \sigma(B^H B)} |b|} \leq 0 \quad \text{verified.}$$



Pure delay $g = 0$ (●) $\sigma(\mathcal{A}) = \sigma_p(\mathcal{A})$ (discrete)

Fractional derivative $g \neq 0 \Rightarrow \sigma_c(\mathcal{A}) \neq \emptyset$ (essential)


(○) $g = +2 > 0 \Rightarrow$ stable

(⊗) $g = -2 < 0 \Rightarrow$ unstable

What about $g \in \mathbb{C}$?


Numerical experiment: delay-dependent stability

Case 2: Scalar model $\dot{x}(t) = -x(t) + \frac{1}{2}x(t - \tau) - g d_C^{1/2}x(t)$.
For delay-independent stability, $g \in J_{1/2}$.




Numerical experiment: delay-dependent stability

Case 2: Scalar model $\dot{x}(t) = -x(t) + \frac{1}{2}x(t - \tau) - g d_C^{1/2}x(t)$.
For delay-independent stability, $g \in J_{1/2}$.




What about the
delay-dependent stability
region?




Numerical experiment: delay-dependent stability

Case 2: Scalar model $\dot{x}(t) = -x(t) + \frac{1}{2}x(t - \tau) - g d_C^{1/2}x(t)$.

For delay-independent stability, $g \in J_{1/2}$.




What about the delay-dependent stability region?




Numerical experiment: delay-dependent stability

Case 2: Scalar model $\dot{x}(t) = -x(t) + \frac{1}{2}x(t - \tau) - g d_C^{1/2}x(t)$.
For delay-independent stability, $g \in J_{1/2}$.




What about the
delay-dependent stability
region?




Numerical experiment: delay-dependent stability

Case 2: Scalar model $\dot{x}(t) = -x(t) + \frac{1}{2}x(t - \tau) - g d_C^{1/2}x(t)$.
For delay-independent stability, $g \in J_{1/2}$.




What about the
delay-dependent stability
region?



Numerical experiment: composition (exploratory)

Case 3: Scalar model $\dot{x}(t) = -x(t) + \frac{1}{2} x(t - \tau) - g d_C^{1/2} x(t - \tau_\alpha)$.
 $\sigma(\mathcal{A})$



Effect of delaying the fractional derivative

$$g = |a|/4.$$

① $\tau_\alpha = 0$ (○).


$$g = |a|.$$

① $\tau_\alpha = 0$ (◇).

Numerical experiment: composition (exploratory)

Case 3: Scalar model $\dot{x}(t) = -x(t) + \frac{1}{2} x(t - \tau) - g d_C^{1/2} x(t - \tau_\alpha)$.

$\sigma(\mathcal{A})$



Effect of delaying the fractional derivative

$g = |a|/4$.

① $\tau_\alpha = 0$ (○).

② $\tau_\alpha = \tau$ (●).


$g = |a|$.

① $\tau_\alpha = 0$ (◇).

Numerical experiment: composition (exploratory)

Case 3: Scalar model $\dot{x}(t) = -x(t) + \frac{1}{2} x(t - \tau) - g d_C^{1/2} x(t - \tau_\alpha)$.

$\sigma(\mathcal{A})$



Effect of delaying the fractional derivative

$g = |a|/4$.

① $\tau_\alpha = 0$ (○).

② $\tau_\alpha = \tau$ (●).

$g = |a|$.

① $\tau_\alpha = 0$ (◇).


② $\tau_\alpha = \tau$ (◆).

Application in acoustics


Computational case Infinite 2D duct.

DG: $N = 4$. Mesh: $N_K = 188$.

Time-integration: CFL = 0.5. (LSERK (8,4) (Toulorge and Desmet 2012))



$$\hat{z}(s, x) = \infty \text{ (Rigid Wall)}$$




Application in acoustics


Computational case Infinite 2D duct.

DG: $N = 4$. Mesh: $N_K = 188$.

Time-integration: CFL = 0.5. (LSERK (8,4) (Toulorge and Desmet 2012))



$$\hat{z}(s) = a + a\sqrt{s} + \frac{a}{2}e^{-s\tau} \quad (\text{Soft Wall})$$



Outline

- 1 Introduction
- 2 Coupled PDEs formulation: stability results
- 3 An eigenvalue approach to stability
- 4 Conclusion**
 - Conclusion

Conclusion

Takeaways

- Parabolic - Hyperbolic PDE realisations \Rightarrow time-local coupled system (x, φ, ψ)
- Natural extended energy $\mathcal{E} = E_x + E_\varphi + k E_\psi$
 - \Rightarrow sufficient asymptotic stability condition
 - \Rightarrow eigenvalue approach to stability
- Application to aeroacoustics

Perspectives

- | | |
|---|--|
| <ul style="list-style-type: none">• Multiple delay case• Semigroup formulation | <ul style="list-style-type: none">• Composition: $D_{\text{RL}}^\alpha x(t - \tau)$?• Theoretical study of eigenvalue approach |
|---|--|

Conclusion

- 1 Introduction
- 2 Coupled PDEs formulation: stability results
- 3 An eigenvalue approach to stability
- 4 Conclusion

► Appendix

Thanks for your attention. Any questions?

(Contact: florian.monteghetti@onera.fr)

References I



Avanessoﬀ, D., A. Fioravanti and C. Bonnet (2013). “YALTA: a Matlab toolbox for the H_∞ -stability analysis of classical and fractional systems with commensurate delays”. In: *IFAC Proceedings Volumes* 46.2, pp. 839–844. ISSN: 1474-6670 (cit. on pp. 27–29).



Baudouin, L., A. Seuret and M. Safi (2016). “Stability analysis of a system coupled to a transport equation using integral inequalities”. In: *IFAC-PapersOnLine* 49.8, pp. 92–97. ISSN: 2405-8963. DOI: 10.1016/j.ifacol.2016.07.424 (cit. on pp. 27–29).








Bonnet, C. and J. R. Partington (2002). “Analysis of fractional delay systems of retarded and neutral type”. In: *Automatica* 38.7, pp. 1133–1138. ISSN: 0005-1098 (cit. on pp. 10, 11).







Breda, D., S. Maset and R. Vermiglio (2005). “Pseudospectral Differencing Methods for Characteristic Roots of Delay Differential Equations”. In: *SIAM Journal on Scientific Computing* 27.2, pp. 482–495. DOI: 10.1137/030601600 (cit. on pp. 27–29).





References II

-  Briat, C. (2014). *Linear Parameter-Varying and Time-Delay Systems*. Berlin: Springer (cit. on pp. 10, 11).
-  Curtain, R. F. and H. Zwart (1995). *An Introduction to Infinite-Dimensional Linear Systems Theory*. New York: Springer (cit. on pp. 10, 11, 18, 19, 60).
-  Deng, W., C. Li and J. Lü (2007). “Stability analysis of linear fractional differential system with multiple time delays”. In: *Nonlinear Dynamics* 48.4, pp. 409–416. ISSN: 1573-269X. DOI: 10.1007/s11071-006-9094-0 (cit. on pp. 10, 11).
-  Engel, K.-J. and R. Nagel (2000). *One-parameter semigroups for linear evolution equations*. New York: Springer-Verlag (cit. on pp. 18, 19).
-  Engelborghs, K., T. Luzyanina and D. Roose (2002). “Numerical bifurcation analysis of delay differential equations using DDE-BIFTOOL”. In: *ACM Transactions on Mathematical Software (TOMS)* 28.1, pp. 1–21 (cit. on pp. 27–29).

References III

-  Fioravanti, A. R. et al. (2012). “A numerical method for stability windows and unstable root-locus calculation for linear fractional time-delay systems”. In: *Automatica* 48.11, pp. 2824–2830. ISSN: 0005-1098. DOI: 10.1016/j.automatica.2012.04.009 (cit. on pp. 27–29).
-  Fridman, E. (2014). *Introduction to Time-Delay Systems*. Basel: Birkhäuser (cit. on pp. 10, 11).
-  Heleschewitz, D. (2000). “Analyse et simulation de systemes différentiels fractionnaires et pseudo-différentiels sous représentation diffusive”. PhD thesis. ENST Paris (cit. on p. 66).
-  Hélie, T. and D. Matignon (2006a). “Diffusive representations for the analysis and simulation of flared acoustic pipes with visco-thermal losses”. In: *Mathematical Models and Methods in Applied Sciences* 16.04, pp. 503–536. DOI: 10.1142/S0218202506001248 (cit. on pp. 20, 21).

References IV

-  Hélie, T. and D. Matignon (2006b). “Representations with poles and cuts for the time-domain simulation of fractional systems and irrational transfer functions”. In: *Signal Processing* 86.10, pp. 2516–2528. DOI: 10.1016/j.sigpro.2006.02.017 (cit. on p. 66).
-  Li, X.-G., S.-I. Niculescu and A. Cela (2015). *Analytic curve frequency-sweeping stability tests for systems with commensurate delays*. Springer (cit. on pp. 27–29).
-  Matignon, D. and H. J. Zwart (in revision). “Standard diffusive systems as well-posed linear systems”. In: *Int. J. Control* (cit. on p. 63).
-  Matignon, D. (1996). “Stability results for fractional differential equations with applications to control processing”. In: *IMACS/IEEE-SMC conference on Computational Engineering in Systems Application*. Vol. 2. Lille, France, pp. 963–968 (cit. on pp. 10, 11).

References V



Matignon, D. (2009). “An introduction to fractional calculus”. In: *Scaling, Fractals and Wavelets, vol. 1*. Ed. by P. Abry, P. Gonçalves and J. Levy-Vehel. Digital signal and image processing series. ISTE - Wiley, pp. 237–277 (cit. on pp. 20, 21).



Michiels, W. and S.-I. Niculescu (2014). *Stability, Control, and Computation for Time-Delay Systems*. 2nd. Philadelphia: SIAM (cit. on pp. 10, 11, 18, 19, 27–29).



Monteghetti, F. et al. (2016). “Design of broadband time-domain impedance boundary conditions using the oscillatory-diffusive representation of acoustical models”. In: *The Journal of the Acoustical Society of America* 140.3, pp. 1663–1674. DOI: 10.1121/1.4962277 (cit. on pp. 3–7).



Montseny, G. (1998). “Diffusive representation of pseudo-differential time-operators”. In: *ESAIM: Proceedings*. Vol. 5. EDP Sciences, pp. 159–175. DOI: 10.1051/proc:1998005 (cit. on pp. 20, 21).

References VI



Seuret, A., F. Gouaisbaut and Y. Ariba (2015). “Complete quadratic Lyapunov functionals for distributed delay systems”. In: *Automatica* 62, pp. 168–176. ISSN: 0005-1098. DOI: 10.1016/j.automatica.2015.09.030 (cit. on pp. 27–29).



Shampine, L. (2008). “Vectorized adaptive quadrature in MATLAB”. In: *J. Comput. Appl. Math.* 211.2, pp. 131–140. ISSN: 0377-0427 (cit. on p. 66).



Staffans, O. J. (1994). “Well-posedness and stabilizability of a viscoelastic equation in energy space”. In: *Trans. Amer. Math. Soc.* 345, pp. 527–575 (cit. on pp. 20, 21).



Toulorge, T. and W. Desmet (2012). “Optimal Runge-Kutta schemes for discontinuous Galerkin space discretizations applied to wave propagation problems”. In: *Journal of Computational Physics* 231.4, pp. 2067–2091. ISSN: 0021-9991. DOI: 10.1016/j.jcp.2011.11.024 (cit. on pp. 44, 45).

References VII



Zhang, L. et al. (2016). “Complete stability of linear fractional order time delay systems: A unified frequency-sweeping approach”. In: *35th Chinese Control Conference (CCC)*. Chengdu, pp. 1605–1609 (cit. on pp. 27–29).

Additional slides

- 5 Coupled formulation: stability results
- 6 An eigenvalue approach to stability

◀ Main presentation

Outline

- 5 Coupled formulation: stability results
 - Toy model: Laplace analysis
 - Vector-valued case
 - Parabolic realisation and heat equation
- 6 An eigenvalue approach to stability

Toy model: Laplace analysis

$$\begin{aligned}
 \hat{x}(s) = & \underbrace{(s-a)\hat{h}(s)\hat{x}^0(s)}_{(a)} + g \underbrace{\hat{h}(s)\mathcal{L}_0[d_C^\alpha x^0 \mathbb{1}_{[0,\tau]}](s)}_{(b)} \\
 & + g x^0(0) \underbrace{\hat{h}(s)s^\alpha}_{(c)} + g x^0(\tau) \underbrace{\hat{h}(s)s^\alpha e^{-s\tau}}_{(d)} \\
 & + x^0(\tau) \underbrace{\hat{h}(s)e^{-s\tau}}_{(e)},
 \end{aligned}$$

where $\hat{h}(s) := (s - a - b \exp(-\tau s) + g s^\alpha)^{-1}$. \hat{h} is defined over \mathbb{C}_β^+ for $\beta \geq 0$ (cut).

Toy model: Laplace analysis (2)

$\hat{h}(s) := (s - a - b \exp(-\tau s) + g s^\alpha)^{-1}$ is defined over \mathbb{C}_β^+ for $\beta \geq 0$ (cut).

Analyticity? Let $s = x + iy = r \exp(i\theta)$ with $\{x \geq 0 \text{ and } y \in \mathbb{R}\}$ or $\{r \geq 0 \text{ and } |\theta| \leq \frac{\pi}{2}\}$.

$$\begin{aligned} \Re(s - a - b e^{-\tau s} + g s^\alpha) &= x - \Re(a) - |b| e^{-\tau x} \cos(\tau y - \theta_b) + \Re(g s^\alpha) \\ &\geq x - \Re(a) - |b| + |g| |s|^\alpha \\ &\geq -\Re(a) - |b|, \end{aligned}$$

using $\theta_g \in J_\alpha$. If $\Re(a) < -|b|$, then \hat{h} analytic in $\overline{\mathbb{C}_0^+}$.

Toy model: Laplace analysis (3)

If $\theta_g \in J_\alpha$ and $\Re(a) < -|b|$,

$\hat{h}(s) := (s - a - b \exp(-\tau s) + g s^\alpha)^{-1} \in \hat{\mathcal{A}}(0)$, the Callier-Desoer class. (Curtain and Zwart 1995, Thm. A.7.49)

- $(s - a)^{-1} \in \hat{\mathcal{A}}(0)$, since $\Re(a) < 0$. It remains to show that

$$[1 - (b \exp(-\tau s) - g s^\alpha)/(s - a)]^{-1} \in \hat{\mathcal{A}}(0).$$

We first notice that

$$\hat{f}(s) = 1 - (b \exp(-\tau s) - g s^\alpha)/(s - a) \in \hat{\mathcal{A}}(0).$$

Then, it is enough to prove that $\inf_{\Re(s) \geq 0} |\hat{f}(s)| > 0$ to ensure that $1/\hat{f} \in \hat{\mathcal{A}}(0)$.

- As a consequence, $h \in \mathcal{A}(0)$, i.e. can be decomposed into

$$h(t) = h_a(t) + \sum_{n \in \mathbb{N}} h_n \delta(t - t_n), \quad (2)$$

with $h_a \in L^1(\mathbb{R}^+)$ and $(h_n)_{n \in \mathbb{N}} \in l^1(\mathbb{N})$; and

$0 = t_0 < t_1 < t_2 < \dots$.

Vector-valued case

The energy balance reads

$$\dot{\mathcal{E}} = \dot{x} \cdot x + \frac{kc}{2} [\|x\|^2 - \|x(\cdot - \tau)\|^2] + \sum_{i \in \llbracket 1, n \rrbracket} g_i \dot{\tilde{\varphi}}_i.$$

G diagonal \Rightarrow no coupling btw diffusive variables $\tilde{\varphi}_i$:
delay/fractional coupling is straightforward.

Since $g_i \geq 0$, it is sufficient for to prove that

$$-\Sigma_k := \begin{bmatrix} \frac{A + A^H}{2} + \frac{kc}{2} I & \frac{1}{2} B \\ \frac{1}{2} B^H & -\frac{kc}{2} I \end{bmatrix} < 0,$$

Let us denote $A^S = (A + A^H)/2$ the symmetric part of A . We have for all x and y in \mathbb{C}^n

$$-\Sigma_k \begin{bmatrix} x \\ y \end{bmatrix} \cdot \begin{bmatrix} x \\ y \end{bmatrix} = A^S x \cdot x + \frac{kc}{2} \|x\|^2 + \frac{1}{2} B y \cdot x + \frac{1}{2} B^H x \cdot y - \frac{kc}{2} \|y\|^2.$$

Now, for any $\varepsilon > 0$, from

Vector-valued case (2)

Now, for any $\varepsilon > 0$, from

$$\frac{1}{2}By \cdot x + \frac{1}{2}B^H x \cdot y = \Re(By \cdot x) \leq \frac{\varepsilon}{2}\|By\|^2 + \frac{1}{2\varepsilon}\|x\|^2,$$

and

$$\|By\|^2 = B^H By \cdot y \leq \max_{b \in \sigma(B^H B)} |b| \|y\|^2,$$

we can choose $k^* = k_\varepsilon = \varepsilon \max_{b \in \sigma(B^H B)} |b|/c > 0$ to get

$$-\Sigma_k \begin{bmatrix} x \\ y \end{bmatrix} \cdot \begin{bmatrix} x \\ y \end{bmatrix} \leq \left(\max_{a \in \sigma(A)} \Re(a) + \frac{k_\varepsilon c}{2} + \frac{1}{2\varepsilon} \right) \|x\|^2.$$

Taking the least stringent value of $\varepsilon > 0$, we derive

$$\max_{a \in \sigma(A)} \Re(a) + \sqrt{\max_{b \in \sigma(B^H B)} |b|} < 0$$

as a delay-independent stability sufficient condition.

Long-memory impedance: link with heat equation

Monodimensional heat equation

(Matignon and Zwart in revision, Ex. 3.2)

$$\begin{cases} \partial_t \theta(t, x) &= \partial_x^2 \theta(t, x) + u(t) \delta_0(x) \quad (x \in \mathbb{R}, t > 0) \\ y(t) &= 4 \theta(t, x = 0). \end{cases}$$

Take the Fourier and Laplace transform

$$\hat{\theta}(s, k) := \int_0^\infty \int_{\mathbb{R}} \theta(t, x) e^{-ikx} e^{-st} dx dt \quad (\Re[s] > 0, k \in \mathbb{R})$$

to get

$$\hat{\theta}(s, k) = \frac{1}{s + k^2} \hat{u}(s),$$

hence

$$\hat{y}(s) = 4 \times \frac{1}{2\pi} \int_{\mathbb{R}} \hat{\theta}(s, k) dk = \underbrace{\left(\int_{\mathbb{R}} \frac{1}{s + k^2} \frac{2dk}{\pi} \right)}_{=1/\sqrt{s}} \hat{u}(s).$$

Outline

- 5 Coupled formulation: stability results
- 6 An eigenvalue approach to stability
 - Discretisation of parabolic realisation

Discretisation of parabolic representation

Discretisation problem (Laplace domain):

$$\forall \Re(s) > 0, \quad \hat{h}(s) = \int_0^\infty \frac{1}{s + \xi} d\mu(\xi) \simeq \sum_{k \in \llbracket 1, N_\xi \rrbracket} \frac{\mu_k}{s + \xi_k} = \hat{h}_{\text{num}}(s).$$

Challenges:

- Parsimonious approximation
- Spectral accuracy (no spurious instabilities)
- Monotone convergence for $N_\xi \rightarrow \infty$

Discretisation of parabolic representation (2)

Discretisation problem (Laplace domain):

$$\forall \Re(s) > 0, \quad \hat{h}(s) = \int_0^\infty \frac{1}{s + \xi} d\mu(\xi) \simeq \sum_{k \in \llbracket 1, N_\xi \rrbracket} \mu_k \frac{1}{s + \xi_k} = \hat{h}_{\text{num}}(s).$$

Methods:

- Interpolation (Heleschewitz 2000)
- Optimisation (Hélie and Matignon 2006b, SP).

$$J(\xi, \mu) = \int_{\omega_{\min}}^{\omega_{\max}} |\hat{h}(i\omega) - \hat{h}_{\text{num}}(i\omega)|^2 w(\omega) d\omega.$$

Parameters: ξ_{\min} , ξ_{\max} , N_ξ and ω_{\min} , ω_{\max} and w .

⇒ Quadrature (analytical expressions for μ_k and ξ_k).

$$\int_0^\infty \mu_{\bar{\alpha}}(\xi) \varphi(\xi, t) d\xi = \int_0^1 \mu_{\bar{\alpha}}(\Phi(v)) \varphi(\Phi(v), t) \Phi'(v) dv,$$

with $\Phi(v) := v^2(1-v)^{-2}$ for regularity at $\xi = 0$, see (Shampine 2008, S 4.2). Then Gauss-Legendre quadrature rule.