

Structure-Preserving Discretization of a Coupled Heat-Wave System, as Interconnected Port-Hamiltonian Systems

Ghislain Haine¹ Denis Matignon¹

¹ISAE-Supaero, Toulouse

- 1 Introduction
 - Main Objective
 - Definitions and Notations
- 2 The simplified, linearised “fluid–structure” model (Zhang and Zuazua, 2007)
- 3 Partitioned Finite Element Method (PFEM)
- 4 Numerical simulations
- 5 Conclusion

1 Introduction

- Main Objective
- Definitions and Notations

2 The simplified, linearised “fluid–structure” model (Zhang and Zuazua, 2007)

3 Partitioned Finite Element Method (PFEM)

4 Numerical simulations

5 Conclusion

Main Objective

Aim:

Simulate a coupled heat-wave system by using the *Partitioned Finite Element Method*, and investigate the long-time behaviour of the approximated solution.

Aim:

Simulate a coupled heat-wave system by using the *Partitioned Finite Element Method*, and investigate the long-time behaviour of the approximated solution.

■ Finite Element Method:

- **Complex geometries** are allowed.
- A wide range of **implementation** tools are available.

Aim:

Simulate a coupled heat-wave system by using the *Partitioned Finite Element Method*, and investigate the long-time behaviour of the approximated solution.

- Finite Element Method:

- **Complex geometries** are allowed.
- A wide range of **implementation** tools are available.

- Port-Hamiltonian Systems (PHS):

- Model **“energy” exchanges** between simpler open subsystems.
- The power balance is *encoded* in a **Stokes-Dirac structure**.

Aim:

Simulate a coupled heat-wave system by using the Partitioned Finite Element Method, and investigate the long-time behaviour of the approximated solution.

■ Finite Element Method:

- **Complex geometries** are allowed.
- A wide range of **implementation** tools are available.

■ Port-Hamiltonian Systems (PHS):

- Model **“energy” exchanges** between simpler open subsystems.
- The power balance is *encoded* in a **Stokes-Dirac structure**.

■ Partitioned Finite Element Method (PFEM):

- It translates the Stokes-Dirac structure into a **Dirac structure**.
- The **discrete Hamiltonian** satisfies the “discrete” power balance.

A Partitioned Finite Element Method for Power-Preserving Discretization of Open Systems of Conservation Laws

Cardoso-Ribeiro F.L., Matignon D. and Lefèvre L.

IMA Journal of Mathematical Control and Information, 38(2):493–533, (2020)

1 Introduction

- Main Objective

- Definitions and Notations

2 The simplified, linearised “fluid–structure” model (Zhang and Zuazua, 2007)

3 Partitioned Finite Element Method (PFEM)

4 Numerical simulations

5 Conclusion

Linear Port-Hamiltonian Systems (PHS)

- The **energy variables** $\vec{\alpha}$ (vector field);
- The **Hamiltonian** $\mathcal{H}(\vec{\alpha}(t))$ (*quadratic* functional);

Linear Port-Hamiltonian Systems (PHS)

- The **energy variables** $\vec{\alpha}$ (vector field);
- The **Hamiltonian** $\mathcal{H}(\vec{\alpha}(t))$ (*quadratic* functional);
- The **co-energy variables** $\vec{e}_{\vec{\alpha}} := \delta_{\vec{\alpha}} \mathcal{H}$ (vector field),
 \rightsquigarrow the variational derivative of \mathcal{H} w.r.t $\vec{\alpha}$;
- The **constitutive operator** Q (linear and *positive-definite*): $\vec{e}_{\vec{\alpha}} = Q \vec{\alpha}$;

Linear Port-Hamiltonian Systems (PHS)

- The **energy variables** $\vec{\alpha}$ (vector field);
- The **Hamiltonian** $\mathcal{H}(\vec{\alpha}(t))$ (*quadratic* functional);
- The **co-energy variables** $\vec{e}_{\vec{\alpha}} := \delta_{\vec{\alpha}} \mathcal{H}$ (vector field),
 \rightsquigarrow the variational derivative of \mathcal{H} w.r.t $\vec{\alpha}$;
- The **constitutive operator** Q (linear and *positive-definite*): $\vec{e}_{\vec{\alpha}} = Q \vec{\alpha}$;
- The **structure operator** J (linear and *formally skew-symmetric*);
- The **resistive/dissipative operator** $R = GSG^*$ (linear and *S positive-definite*);

Linear Port-Hamiltonian Systems (PHS)

- The **energy variables** $\vec{\alpha}$ (vector field);
- The **Hamiltonian** $\mathcal{H}(\vec{\alpha}(t))$ (*quadratic* functional);
- The **co-energy variables** $\vec{e}_{\vec{\alpha}} := \delta_{\vec{\alpha}} \mathcal{H}$ (vector field),
 \rightsquigarrow the variational derivative of \mathcal{H} w.r.t $\vec{\alpha}$;
- The **constitutive operator** Q (linear and *positive-definite*): $\vec{e}_{\vec{\alpha}} = Q \vec{\alpha}$;
- The **structure operator** J (linear and *formally skew-symmetric*);
- The **resistive/dissipative operator** $R = GSG^*$ (linear and S *positive-definite*);
- The **control operator** B (linear);
- The **input** u and the **collocated output** y (boundary scalar fields).

Linear Port-Hamiltonian Systems (PHS)

- The **energy variables** $\vec{\alpha}$ (vector field);
- The **Hamiltonian** $\mathcal{H}(\vec{\alpha}(t))$ (*quadratic* functional);
- The **co-energy variables** $\vec{e}_{\vec{\alpha}} := \delta_{\vec{\alpha}} \mathcal{H}$ (vector field),
 \rightsquigarrow the variational derivative of \mathcal{H} w.r.t $\vec{\alpha}$;
- The **constitutive operator** Q (linear and *positive-definite*): $\vec{e}_{\vec{\alpha}} = Q\vec{\alpha}$;
- The **structure operator** J (linear and *formally skew-symmetric*);
- The **resistive/dissipative operator** $R = GSG^*$ (linear and S *positive-definite*);
- The **control operator** B (linear);
- The **input** u and the **collocated output** y (boundary scalar fields).




$$\begin{bmatrix} Q^{-1} & 0 & 0 \\ 0 & S^{-1} & 0 \\ 0 & 0 & I \end{bmatrix} \begin{bmatrix} \partial_t \vec{e}_{\vec{\alpha}}(t) \\ \vec{e}_R(t) \\ -\mathbf{y}(t) \end{bmatrix} = \begin{bmatrix} J & -G & B \\ G^* & 0 & 0 \\ -B^* & 0 & 0 \end{bmatrix} \begin{bmatrix} \vec{e}_{\vec{\alpha}}(t) \\ \vec{e}_R(t) \\ \mathbf{u}(t) \end{bmatrix}.$$

Lossy Power Balance




$$\frac{d}{dt} \mathcal{H}(\vec{\alpha}(t)) = - \langle RQ\vec{\alpha}(t), Q\vec{\alpha}(t) \rangle_J + \langle \mathbf{u}(t), \mathbf{y}(t) \rangle_B \leq \langle \mathbf{u}(t), \mathbf{y}(t) \rangle_B.$$

- 1 Introduction
- 2 The simplified, linearised “fluid–structure” model (Zhang and Zuazua, 2007)
- 3 Partitioned Finite Element Method (PFEM)
- 4 Numerical simulations
- 5 Conclusion

System and configurations






System and configurations



Heat:

$$\begin{cases} \partial_t T(t, \vec{x}) - \Delta T(t, \vec{x}) = 0, & \vec{x} \in \Omega_1, \\ T(t, \vec{x}) = 0, & \vec{x} \in \Gamma_1, \end{cases}$$




System and configurations



Heat:
$$\begin{cases} \partial_t T(t, \vec{x}) - \Delta T(t, \vec{x}) = 0, & \vec{x} \in \Omega_1, \\ T(t, \vec{x}) = 0, & \vec{x} \in \Gamma_1, \end{cases}$$

Wave:
$$\begin{cases} \partial_{tt} w(t, \vec{x}) - \Delta w(t, \vec{x}) = 0, & \vec{x} \in \Omega_2, \\ w(t, \vec{x}) = 0, & \vec{x} \in \Gamma_2, \end{cases}$$

System and configurations






Heat:
$$\begin{cases} \partial_t T(t, \vec{x}) - \Delta T(t, \vec{x}) = 0, & \vec{x} \in \Omega_1, \\ T(t, \vec{x}) = 0, & \vec{x} \in \Gamma_1, \end{cases}$$

Wave:
$$\begin{cases} \partial_{tt} w(t, \vec{x}) - \Delta w(t, \vec{x}) = 0, & \vec{x} \in \Omega_2, \\ w(t, \vec{x}) = 0, & \vec{x} \in \Gamma_2, \end{cases}$$

Transmission:
$$\begin{cases} T(t, \vec{x}) = \partial_t w(t, \vec{x}), & \vec{x} \in \Gamma_{\text{int}}, \\ \partial_{\vec{n}_1} T(t, \vec{x}) = -\partial_{\vec{n}_2} w(t, \vec{x}), & \vec{x} \in \Gamma_{\text{int}}, \end{cases}$$

System and configurations






Heat:
$$\begin{cases} \partial_t T(t, \vec{x}) - \Delta T(t, \vec{x}) = 0, & \vec{x} \in \Omega_1, \\ T(t, \vec{x}) = 0, & \vec{x} \in \Gamma_1, \end{cases}$$

Wave:
$$\begin{cases} \partial_{tt} w(t, \vec{x}) - \Delta w(t, \vec{x}) = 0, & \vec{x} \in \Omega_2, \\ w(t, \vec{x}) = 0, & \vec{x} \in \Gamma_2, \end{cases}$$

Transmission:
$$\begin{cases} T(t, \vec{x}) = \partial_t w(t, \vec{x}), & \vec{x} \in \Gamma_{\text{int}}, \\ \partial_{\vec{n}_1} T(t, \vec{x}) = -\partial_{\vec{n}_2} w(t, \vec{x}), & \vec{x} \in \Gamma_{\text{int}}, \end{cases}$$

Initial data:
$$\begin{cases} T(0, \vec{x}) = T_0(\vec{x}), & \vec{x} \in \Omega_1, \\ w(0, \vec{x}) = w_0(\vec{x}), & \vec{x} \in \Omega_2, \\ \partial_t w(0, \vec{x}) = w_1(\vec{x}), & \vec{x} \in \Omega_2. \end{cases}$$

System and configurations



Heat:
$$\begin{cases} \partial_t T(t, \vec{x}) - \Delta T(t, \vec{x}) = 0, & \vec{x} \in \Omega_1, \\ T(t, \vec{x}) = 0, & \vec{x} \in \Gamma_1, \end{cases}$$

Wave:
$$\begin{cases} \partial_{tt} w(t, \vec{x}) - \Delta w(t, \vec{x}) = 0, & \vec{x} \in \Omega_2, \\ w(t, \vec{x}) = 0, & \vec{x} \in \Gamma_2, \end{cases}$$

Transmission:
$$\begin{cases} T(t, \vec{x}) = \partial_t w(t, \vec{x}), & \vec{x} \in \Gamma_{\text{int}}, \\ \partial_{\vec{n}_1} T(t, \vec{x}) = -\partial_{\vec{n}_2} w(t, \vec{x}), & \vec{x} \in \Gamma_{\text{int}}, \end{cases}$$

Initial data:
$$\begin{cases} T(0, \vec{x}) = T_0(\vec{x}), & \vec{x} \in \Omega_1, \\ w(0, \vec{x}) = w_0(\vec{x}), & \vec{x} \in \Omega_2, \\ \partial_t w(0, \vec{x}) = w_1(\vec{x}), & \vec{x} \in \Omega_2. \end{cases}$$

Geometric Control Condition (GCC):

All characteristics of the wave equation must encountered Ω_1 in finite time.

Long-time behavior of a coupled heat-wave system arising in fluid-structure interaction

Zhang X. and Zuazua E.

Archive for Rational Mechanics and Analysis, 184(1):49–120, (2007)

Well-posedness (Zhang and Zuazua 2007)

For any smooth enough initial data, there exists a unique solution to the coupled Heat-Wave system.

Long-time behavior of a coupled heat-wave system arising in fluid-structure interaction

Zhang X. and Zuazua E.

Archive for Rational Mechanics and Analysis, 184(1):49–120, (2007)

Well-posedness (Zhang and Zuazua 2007)

For any smooth enough initial data, there exists a unique solution to the coupled Heat-Wave system.

Strong stability (Zhang and Zuazua 2007)

- Every solution is strongly stable (to zero if Γ_2 is non-empty, to a constant solution otherwise).
- The rate of decay is **never** exponential nor uniform;
- If the GCC holds: the decay is **polynomial**;
- If the GCC fails: the decay is **logarithmic**.

Long-time behavior of a coupled heat-wave system arising in fluid-structure interaction

Zhang X. and Zuazua E.

Archive for Rational Mechanics and Analysis, 184(1):49–120, (2007)

Well-posedness (Zhang and Zuazua 2007)

For any smooth enough initial data, there exists a unique solution to the coupled Heat-Wave system.

Strong stability (Zhang and Zuazua 2007)

- Every solution is strongly stable (to zero if Γ_2 is non-empty, to a constant solution otherwise).
- The rate of decay is **never** exponential nor uniform;
- If the GCC holds: the decay is **polynomial**;
- If the GCC fails: the decay is **logarithmic**.

Remark

In our numerical simulations, the initial data are such that the constant solution is the null solution.

Fluid: the heat equation as a PHS

Hamiltonian: $\mathcal{H}_T(T) := \frac{1}{2} \int_{\Omega_1} |T(t, \vec{x})|^2 d\vec{x}.$

Fluid: the heat equation as a PHS

Hamiltonian: $\mathcal{H}_T(T) := \frac{1}{2} \int_{\Omega_1} |T(t, \vec{x})|^2 d\vec{x}$.

Energy and co-energy variables: $\alpha_T = T$ and $e_{\alpha_T} := \delta_{\alpha_T} \mathcal{H}_T = T$ (temperature).

Fluid: the heat equation as a PHS

Hamiltonian: $\mathcal{H}_T(T) := \frac{1}{2} \int_{\Omega_1} |T(t, \vec{x})|^2 d\vec{x}$.

Energy and co-energy variables: $\alpha_T = T$ and $e_{\alpha_T} := \delta_{\alpha_T} \mathcal{H}_T = T$ (temperature).

Resistive port: $\vec{f}_R = -\nabla T$ and $\vec{e}_R = J_Q$ (heat flux).

Constitutive relation: Fourier's law (with thermal conductivity $\equiv 1$) $\vec{e}_R = \vec{f}_R$.

Fluid: the heat equation as a PHS

Hamiltonian: $\mathcal{H}_T(T) := \frac{1}{2} \int_{\Omega_1} |T(t, \vec{x})|^2 d\vec{x}$.

Energy and co-energy variables: $\alpha_T = T$ and $e_{\alpha_T} := \delta_{\alpha_T} \mathcal{H}_T = T$ (temperature).

Resistive port: $\vec{f}_R = -\nabla T$ and $\vec{e}_R = J_Q$ (heat flux).

Constitutive relation: Fourier's law (with thermal conductivity $\equiv 1$) $\vec{e}_R = \vec{f}_R$.

PHS formulation (co-energy):

$$\begin{pmatrix} \partial_t T \\ J_Q \end{pmatrix} = \begin{bmatrix} 0 & -\text{div} \\ -\nabla & 0 \end{bmatrix} \begin{pmatrix} T \\ J_Q \end{pmatrix},$$

Fluid: the heat equation as a PHS

Hamiltonian: $\mathcal{H}_T(T) := \frac{1}{2} \int_{\Omega_1} |T(t, \vec{x})|^2 d\vec{x}$.

Energy and co-energy variables: $\alpha_T = T$ and $e_{\alpha_T} := \delta_{\alpha_T} \mathcal{H}_T = T$ (temperature).

Resistive port: $\vec{f}_R = -\nabla T$ and $\vec{e}_R = J_Q$ (heat flux).

Constitutive relation: Fourier's law (with thermal conductivity $\equiv 1$) $\vec{e}_R = \vec{f}_R$.

PHS formulation (co-energy):

$$\begin{pmatrix} \partial_t T \\ J_Q \end{pmatrix} = \begin{bmatrix} 0 & -\text{div} \\ -\nabla & 0 \end{bmatrix} \begin{pmatrix} T \\ J_Q \end{pmatrix},$$

Boundary ports:

$$\begin{cases} -J_Q(t, \vec{x}) \cdot \vec{n}_1(\vec{x}) = \mathbf{u}_1(t, \vec{x}), & \mathbf{y}_1(t, \vec{x}) = T(t, \vec{x}), \quad \forall t > 0, \vec{x} \in \Gamma_{\text{int}}, \\ T(t, \vec{x}) = 0, & \mathbf{y}_T(t, \vec{x}) = -J_Q(t, \vec{x}) \cdot \vec{n}_1(\vec{x}), \quad \forall t > 0, \vec{x} \in \Gamma_1. \end{cases}$$

Fluid: the heat equation as a PHS

Hamiltonian: $\mathcal{H}_T(T) := \frac{1}{2} \int_{\Omega_1} |T(t, \vec{x})|^2 d\vec{x}$.

Energy and co-energy variables: $\alpha_T = T$ and $e_{\alpha_T} := \delta_{\alpha_T} \mathcal{H}_T = T$ (temperature).

Resistive port: $\vec{f}_R = -\nabla T$ and $\vec{e}_R = J_Q$ (heat flux).

Constitutive relation: Fourier's law (with thermal conductivity $\equiv 1$) $\vec{e}_R = \vec{f}_R$.

PHS formulation (co-energy):

$$\begin{pmatrix} \partial_t T \\ J_Q \end{pmatrix} = \begin{bmatrix} 0 & -\text{div} \\ -\nabla & 0 \end{bmatrix} \begin{pmatrix} T \\ J_Q \end{pmatrix},$$

Boundary ports:

$$\begin{cases} -J_Q(t, \vec{x}) \cdot \vec{n}_1(\vec{x}) = \mathbf{u}_1(t, \vec{x}), & \mathbf{y}_1(t, \vec{x}) = T(t, \vec{x}), \quad \forall t > 0, \vec{x} \in \Gamma_{\text{int}}, \\ T(t, \vec{x}) = 0, & \mathbf{y}_T(t, \vec{x}) = -J_Q(t, \vec{x}) \cdot \vec{n}_1(\vec{x}), \quad \forall t > 0, \vec{x} \in \Gamma_1. \end{cases}$$

Lossy Power Balance

$$\frac{d}{dt} \mathcal{H}_T = - \int_{\Omega_1} \|J_Q\|^2 + \langle \mathbf{u}_1, \mathbf{y}_1 \rangle_{H^{-\frac{1}{2}}(\Gamma_{\text{int}}), H^{\frac{1}{2}}(\Gamma_{\text{int}})}.$$

Structure: the wave equation as a PHS

Hamiltonian: $\mathcal{H}_w(\partial_t w, \nabla w) := \frac{1}{2} \int_{\Omega_2} |\partial_t w(t, \vec{x})|^2 + \|\nabla w(t, \vec{x})\|^2 \mathrm{d}\vec{x}.$

Structure: the wave equation as a PHS

Hamiltonian: $\mathcal{H}_w(\partial_t w, \nabla w) := \frac{1}{2} \int_{\Omega_2} |\partial_t w(t, \vec{x})|^2 + \|\nabla w(t, \vec{x})\|^2 d\vec{x}.$

Energy and co-energy variables:

$$\vec{\alpha}_w = \begin{pmatrix} \partial_t w \\ \nabla w \end{pmatrix} \text{ and } \vec{e}_{\vec{\alpha}_w} := \delta_{\vec{\alpha}_w} \mathcal{H}_w = \begin{pmatrix} \partial_t w \\ \nabla w \end{pmatrix} \text{ (velocity-stress).}$$

Structure: the wave equation as a PHS

Hamiltonian: $\mathcal{H}_w(\partial_t w, \nabla w) := \frac{1}{2} \int_{\Omega_2} |\partial_t w(t, \vec{x})|^2 + \|\nabla w(t, \vec{x})\|^2 d\vec{x}.$

Energy and co-energy variables:

$$\vec{\alpha}_w = \begin{pmatrix} \partial_t w \\ \nabla w \end{pmatrix} \text{ and } \vec{e}_{\vec{\alpha}_w} := \delta_{\vec{\alpha}_w} \mathcal{H}_w = \begin{pmatrix} \partial_t w \\ \nabla w \end{pmatrix} \text{ (velocity-stress).}$$

PHS formulation (co-energy):

$$\begin{pmatrix} \partial_t(\partial_t w) \\ \partial_t(\nabla w) \end{pmatrix} = \begin{bmatrix} 0 & \text{div} \\ \nabla & 0 \end{bmatrix} \begin{pmatrix} \partial_t w \\ \nabla w \end{pmatrix},$$

Structure: the wave equation as a PHS

Hamiltonian: $\mathcal{H}_w(\partial_t w, \nabla w) := \frac{1}{2} \int_{\Omega_2} |\partial_t w(t, \vec{x})|^2 + \|\nabla w(t, \vec{x})\|^2 d\vec{x}.$

Energy and co-energy variables:

$$\vec{\alpha}_w = \begin{pmatrix} \partial_t w \\ \nabla w \end{pmatrix} \text{ and } \vec{e}_{\vec{\alpha}_w} := \delta_{\vec{\alpha}_w} \mathcal{H}_w = \begin{pmatrix} \partial_t w \\ \nabla w \end{pmatrix} \text{ (velocity-stress).}$$

PHS formulation (co-energy):

$$\begin{pmatrix} \partial_t(\partial_t w) \\ \partial_t(\nabla w) \end{pmatrix} = \begin{bmatrix} 0 & \text{div} \\ \nabla & 0 \end{bmatrix} \begin{pmatrix} \partial_t w \\ \nabla w \end{pmatrix},$$

Boundary ports:

$$\begin{cases} \partial_t w(t, \vec{x}) = \mathbf{u}_2(t, \vec{x}), & \mathbf{y}_2(t, \vec{x}) = \nabla w(t, \vec{x}) \cdot \vec{n}_2(\vec{x}), & \forall t > 0, \vec{x} \in \Gamma_{\text{int}}, \\ \partial_t w(t, \vec{x}) = 0, & \mathbf{y}_w(t, \vec{x}) = \nabla w(t, \vec{x}) \cdot \vec{n}_2(\vec{x}), & \forall t > 0, \vec{x} \in \Gamma_2. \end{cases}$$

Structure: the wave equation as a PHS

Hamiltonian: $\mathcal{H}_w(\partial_t w, \nabla w) := \frac{1}{2} \int_{\Omega_2} |\partial_t w(t, \vec{x})|^2 + \|\nabla w(t, \vec{x})\|^2 d\vec{x}.$

Energy and co-energy variables:

$$\vec{\alpha}_w = \begin{pmatrix} \partial_t w \\ \nabla w \end{pmatrix} \text{ and } \vec{e}_{\vec{\alpha}_w} := \delta_{\vec{\alpha}_w} \mathcal{H}_w = \begin{pmatrix} \partial_t w \\ \nabla w \end{pmatrix} \text{ (velocity-stress).}$$

PHS formulation (co-energy):

$$\begin{pmatrix} \partial_t(\partial_t w) \\ \partial_t(\nabla w) \end{pmatrix} = \begin{bmatrix} 0 & \text{div} \\ \nabla & 0 \end{bmatrix} \begin{pmatrix} \partial_t w \\ \nabla w \end{pmatrix},$$

Boundary ports:

$$\begin{cases} \partial_t w(t, \vec{x}) = \mathbf{u}_2(t, \vec{x}), & \mathbf{y}_2(t, \vec{x}) = \nabla w(t, \vec{x}) \cdot \vec{n}_2(\vec{x}), & \forall t > 0, \vec{x} \in \Gamma_{\text{int}}, \\ \partial_t w(t, \vec{x}) = 0, & \mathbf{y}_w(t, \vec{x}) = \nabla w(t, \vec{x}) \cdot \vec{n}_2(\vec{x}), & \forall t > 0, \vec{x} \in \Gamma_2. \end{cases}$$

Lossless Power Balance

$$\frac{d}{dt} \mathcal{H}_w = \langle \mathbf{y}_2, \mathbf{u}_2 \rangle_{H^{-\frac{1}{2}}(\Gamma_{\text{int}}), H^{\frac{1}{2}}(\Gamma_{\text{int}})}.$$

Gyrator interconnection on Γ_{int} :

$$\mathbf{u}_1(t, \vec{x}) = -\mathbf{y}_2(t, \vec{x}), \quad \mathbf{u}_2(t, \vec{x}) = \mathbf{y}_1(t, \vec{x}), \quad \forall t > 0, \vec{x} \in \Gamma_{\text{int}}.$$

Gyrator interconnection on Γ_{int} :

$$\mathbf{u}_1(t, \vec{x}) = -\mathbf{y}_2(t, \vec{x}), \quad \mathbf{u}_2(t, \vec{x}) = \mathbf{y}_1(t, \vec{x}), \quad \forall t > 0, \vec{x} \in \Gamma_{\text{int}}.$$

The **total Hamiltonian** of the coupled Heat-Wave system is given by:

$$\mathcal{H}(T, \partial_t w, \nabla w) := \underbrace{\frac{1}{2} \int_{\Omega_1} |T(t, \vec{x})|^2 d\vec{x}}_{\mathcal{H}_T} + \underbrace{\frac{1}{2} \int_{\Omega_2} |\partial_t w(t, \vec{x})|^2 + \|\nabla w(t, \vec{x})\|^2 d\vec{x}}_{\mathcal{H}_w}.$$

Coupling: transmission condition

Gyrator interconnection on Γ_{int} :

$$\mathbf{u}_1(t, \vec{x}) = -\mathbf{y}_2(t, \vec{x}), \quad \mathbf{u}_2(t, \vec{x}) = \mathbf{y}_1(t, \vec{x}), \quad \forall t > 0, \vec{x} \in \Gamma_{\text{int}}.$$

The **total Hamiltonian** of the coupled Heat-Wave system is given by:

$$\mathcal{H}(T, \partial_t w, \nabla w) := \underbrace{\frac{1}{2} \int_{\Omega_1} |T(t, \vec{x})|^2 d\vec{x}}_{\mathcal{H}_T} + \underbrace{\frac{1}{2} \int_{\Omega_2} |\partial_t w(t, \vec{x})|^2 + \|\nabla w(t, \vec{x})\|^2 d\vec{x}}_{\mathcal{H}_w}.$$

Dissipative Power Balance

$$\begin{aligned} \frac{d}{dt} \mathcal{H} &= \frac{d}{dt} \mathcal{H}_T + \frac{d}{dt} \mathcal{H}_w \\ &= - \int_{\Omega_1} |J_Q|^2 + \langle \mathbf{u}_1, \mathbf{y}_1 \rangle_{H^{-\frac{1}{2}}(\Gamma_{\text{int}}), H^{\frac{1}{2}}(\Gamma_{\text{int}})} + \langle \mathbf{y}_2, \mathbf{u}_2 \rangle_{H^{-\frac{1}{2}}(\Gamma_{\text{int}}), H^{\frac{1}{2}}(\Gamma_{\text{int}})} \\ &= - \int_{\Omega_1} |J_Q|^2 - \langle \mathbf{y}_2, \mathbf{y}_1 \rangle_{H^{-\frac{1}{2}}(\Gamma_{\text{int}}), H^{\frac{1}{2}}(\Gamma_{\text{int}})} + \langle \mathbf{y}_2, \mathbf{y}_1 \rangle_{H^{-\frac{1}{2}}(\Gamma_{\text{int}}), H^{\frac{1}{2}}(\Gamma_{\text{int}})} \\ &= - \int_{\Omega_1} |J_Q|^2. \end{aligned}$$

- 1 Introduction
- 2 The simplified, linearised “fluid–structure” model (Zhang and Zuazua, 2007)
- 3 Partitioned Finite Element Method (PFEM)**
- 4 Numerical simulations
- 5 Conclusion

3 steps: Weak formulation – Stokes identity – FEM

3 steps: Weak formulation – Stokes identity – FEM

Weak formulation:

For all test functions v_T , \vec{v}_Q on Ω_1 , v_w , \vec{v}_w on Ω_2 and v_∂ on Γ_{int} :

$$\text{Heat:} \quad \left\{ \begin{array}{l} \langle \partial_t T, v_T \rangle_{L^2(\Omega_1)} = \langle -\text{div}(J_Q), v_T \rangle_{L^2(\Omega_1)}, \\ \langle J_Q, \vec{v}_Q \rangle_{\mathbf{L}^2(\Omega_1)} = \langle -\nabla T, \vec{v}_Q \rangle_{\mathbf{L}^2(\Omega_1)}, \\ \langle v_\partial, \mathbf{y}_1 \rangle_{\Gamma_{\text{int}}} = \langle v_\partial, T \rangle_{\Gamma_{\text{int}}}, \end{array} \right.$$

3 steps: Weak formulation – Stokes identity – FEM

Weak formulation:

For all test functions v_T , \vec{v}_Q on Ω_1 , v_w , \vec{v}_w on Ω_2 and v_∂ on Γ_{int} :

$$\text{Heat:} \quad \left\{ \begin{array}{l} \langle \partial_t T, v_T \rangle_{L^2(\Omega_1)} = \langle -\text{div}(J_Q), v_T \rangle_{L^2(\Omega_1)}, \\ \langle J_Q, \vec{v}_Q \rangle_{\mathbf{L}^2(\Omega_1)} = \langle -\nabla T, \vec{v}_Q \rangle_{\mathbf{L}^2(\Omega_1)}, \\ \langle v_\partial, \mathbf{y}_1 \rangle_{\Gamma_{\text{int}}} = \langle v_\partial, T \rangle_{\Gamma_{\text{int}}}, \end{array} \right.$$

$$\text{Wave:} \quad \left\{ \begin{array}{l} \langle \partial_t(\partial_t w), v_w \rangle_{L^2(\Omega_2)} = \langle \text{div}(\nabla w), v_w \rangle_{L^2(\Omega_2)}, \\ \langle \partial_t(\nabla w), \vec{v}_w \rangle_{\mathbf{L}^2(\Omega_2)} = \langle \nabla \partial_t w, \vec{v}_w \rangle_{\mathbf{L}^2(\Omega_2)}, \\ \langle \mathbf{y}_2, v_\partial \rangle_{\Gamma_{\text{int}}} = \langle \nabla w \cdot \mathbf{n}_2, v_\partial \rangle_{\Gamma_{\text{int}}}, \end{array} \right.$$

3 steps: Weak formulation – Stokes identity – FEM

Weak formulation:

For all test functions v_T, \vec{v}_Q on Ω_1 , v_w, \vec{v}_w on Ω_2 and v_∂ on Γ_{int} :

$$\text{Heat:} \quad \begin{cases} \langle \partial_t T, v_T \rangle_{L^2(\Omega_1)} = \langle -\text{div}(J_Q), v_T \rangle_{L^2(\Omega_1)}, \\ \langle J_Q, \vec{v}_Q \rangle_{\mathbf{L}^2(\Omega_1)} = \langle -\nabla T, \vec{v}_Q \rangle_{\mathbf{L}^2(\Omega_1)}, \\ \langle v_\partial, \mathbf{y}_1 \rangle_{\Gamma_{\text{int}}} = \langle v_\partial, T \rangle_{\Gamma_{\text{int}}}, \end{cases}$$

$$\text{Wave:} \quad \begin{cases} \langle \partial_t(\partial_t w), v_w \rangle_{L^2(\Omega_2)} = \langle \text{div}(\nabla w), v_w \rangle_{L^2(\Omega_2)}, \\ \langle \partial_t(\nabla w), \vec{v}_w \rangle_{\mathbf{L}^2(\Omega_2)} = \langle \nabla \partial_t w, \vec{v}_w \rangle_{\mathbf{L}^2(\Omega_2)}, \\ \langle \mathbf{y}_2, v_\partial \rangle_{\Gamma_{\text{int}}} = \langle \nabla w \cdot \mathbf{n}_2, v_\partial \rangle_{\Gamma_{\text{int}}}, \end{cases}$$

$$\text{Gyrator:} \quad \begin{cases} \langle \mathbf{u}_1, v_\partial \rangle_{\Gamma_{\text{int}}} = -\langle \mathbf{y}_2, v_\partial \rangle_{\Gamma_{\text{int}}}, \\ \langle v_\partial, \mathbf{u}_2 \rangle_{\Gamma_{\text{int}}} = \langle v_\partial, \mathbf{y}_1 \rangle_{\Gamma_{\text{int}}}. \end{cases}$$

Stokes (Green) identity:

$$\text{Heat: } \left\{ \begin{array}{l} \langle \partial_t T, v_T \rangle_{L^2(\Omega_1)} = \langle J_Q, \nabla v_T \rangle_{L^2(\Omega_1)} - \left\langle \underbrace{J_Q \cdot \mathbf{n}_1}_{\mathbf{u}_1}, v_\partial \right\rangle_{\Gamma_{\text{int}}} - \left\langle \underbrace{J_Q \cdot \mathbf{n}_1}_{\mathbf{y}_T}, v_\partial \right\rangle_{\Gamma_1}, \\ \langle J_Q, \vec{v}_Q \rangle_{\mathbf{L}^2(\Omega_1)} = \langle -\nabla T, \vec{v}_Q \rangle_{\mathbf{L}^2(\Omega_1)}, \\ \langle v_\partial, \mathbf{y}_1 \rangle_{\Gamma_{\text{int}}} = \langle v_\partial, T \rangle_{\Gamma_{\text{int}}}, \end{array} \right.$$

Stokes (Green) identity:

$$\begin{aligned}
 \text{Heat: } & \left\{ \begin{aligned} \langle \partial_t T, v_T \rangle_{L^2(\Omega_1)} &= \langle J_Q, \nabla v_T \rangle_{L^2(\Omega_1)} - \left\langle \underbrace{J_Q \cdot \mathbf{n}_1}_{\mathbf{u}_1}, v_\partial \right\rangle_{\Gamma_{\text{int}}} - \left\langle \underbrace{J_Q \cdot \mathbf{n}_1}_{\mathbf{y}_T}, v_\partial \right\rangle_{\Gamma_1}, \\ \langle J_Q, \vec{\mathbf{v}}_Q \rangle_{\mathbf{L}^2(\Omega_1)} &= \langle -\nabla T, \vec{\mathbf{v}}_Q \rangle_{\mathbf{L}^2(\Omega_1)}, \\ \langle v_\partial, \mathbf{y}_1 \rangle_{\Gamma_{\text{int}}} &= \langle v_\partial, T \rangle_{\Gamma_{\text{int}}}, \end{aligned} \right. \\
 \\
 \text{Wave: } & \left\{ \begin{aligned} \langle \partial_t(\partial_t w), v_w \rangle_{L^2(\Omega_2)} &= \langle \text{div}(\nabla w), v_w \rangle_{L^2(\Omega_2)}, \\ \langle \partial_t(\nabla w), \vec{\mathbf{v}}_w \rangle_{\mathbf{L}^2(\Omega_2)} &= \langle \partial_t w, -\text{div}(\vec{\mathbf{v}}_w) \rangle_{L^2(\Omega_2)} + \left\langle v_\partial, \underbrace{\partial_t w}_{\mathbf{u}_2} \right\rangle_{\Gamma_{\text{int}}} + \left\langle v_\partial, \underbrace{\partial_t w}_0 \right\rangle_{\Gamma_2}, \\ \langle \mathbf{y}_2, v_\partial \rangle_{\Gamma_{\text{int}}} &= \langle \nabla w \cdot \mathbf{n}_2, v_\partial \rangle_{\Gamma_{\text{int}}}, \end{aligned} \right.
 \end{aligned}$$

Stokes (Green) identity:

$$\text{Heat: } \left\{ \begin{array}{l} \langle \partial_t T, v_T \rangle_{L^2(\Omega_1)} = \langle J_Q, \nabla v_T \rangle_{L^2(\Omega_1)} - \left\langle \underbrace{J_Q \cdot \mathbf{n}_1}_{\mathbf{u}_1}, v_\partial \right\rangle_{\Gamma_{\text{int}}} - \left\langle \underbrace{J_Q \cdot \mathbf{n}_1}_{\mathbf{y}_T}, v_\partial \right\rangle_{\Gamma_1}, \\ \langle J_Q, \vec{v}_Q \rangle_{\mathbf{L}^2(\Omega_1)} = \langle -\nabla T, \vec{v}_Q \rangle_{\mathbf{L}^2(\Omega_1)}, \\ \langle v_\partial, \mathbf{y}_1 \rangle_{\Gamma_{\text{int}}} = \langle v_\partial, T \rangle_{\Gamma_{\text{int}}}, \end{array} \right.$$

$$\text{Wave: } \left\{ \begin{array}{l} \langle \partial_t(\partial_t w), v_w \rangle_{L^2(\Omega_2)} = \langle \text{div}(\nabla w), v_w \rangle_{L^2(\Omega_2)}, \\ \langle \partial_t(\nabla w), \vec{v}_w \rangle_{\mathbf{L}^2(\Omega_2)} = \langle \partial_t w, -\text{div}(\vec{v}_w) \rangle_{\mathbf{L}^2(\Omega_2)} + \left\langle v_\partial, \underbrace{\partial_t w}_{\mathbf{u}_2} \right\rangle_{\Gamma_{\text{int}}} + \left\langle v_\partial, \underbrace{\partial_t w}_0 \right\rangle_{\Gamma_2}, \\ \langle \mathbf{y}_2, v_\partial \rangle_{\Gamma_{\text{int}}} = \langle \nabla w \cdot \mathbf{n}_2, v_\partial \rangle_{\Gamma_{\text{int}}}, \end{array} \right.$$

$$\text{Gyrator: } \left\{ \begin{array}{l} \langle \mathbf{u}_1, v_\partial \rangle_{\Gamma_{\text{int}}} = -\langle \mathbf{y}_2, v_\partial \rangle_{\Gamma_{\text{int}}}, \\ \langle v_\partial, \mathbf{u}_2 \rangle_{\Gamma_{\text{int}}} = \langle v_\partial, \mathbf{y}_1 \rangle_{\Gamma_{\text{int}}}. \end{array} \right.$$

Partitioned Finite Element Method (PFEM)

Stokes (Green) identity:

$$\text{Heat: } \begin{cases} \langle \partial_t T, v_T \rangle_{L^2(\Omega_1)} = \langle J_Q, \nabla v_T \rangle_{L^2(\Omega_1)} - \underbrace{\left\langle J_Q \cdot \underbrace{n_1}_{\mathbf{u}_1}, v_\partial \right\rangle}_{\Gamma_{\text{int}}} - \underbrace{\left\langle J_Q \cdot \underbrace{n_1}_{\mathbf{y}_T}, v_\partial \right\rangle}_{\Gamma_1}, \\ \langle J_Q, \vec{v}_Q \rangle_{\mathbf{L}^2(\Omega_1)} = \langle -\nabla T, \vec{v}_Q \rangle_{\mathbf{L}^2(\Omega_1)}, \\ \langle v_\partial, \mathbf{y}_1 \rangle_{\Gamma_{\text{int}}} = \langle v_\partial, T \rangle_{\Gamma_{\text{int}}}, \end{cases} \quad \triangle \text{ Warning: } T \equiv 0 \text{ on } \Gamma_1.$$

$$\text{Wave: } \begin{cases} \langle \partial_t(\partial_t w), v_w \rangle_{L^2(\Omega_2)} = \langle \text{div}(\nabla w), v_w \rangle_{L^2(\Omega_2)}, \\ \langle \partial_t(\nabla w), \vec{v}_w \rangle_{\mathbf{L}^2(\Omega_2)} = \langle \partial_t w, -\text{div}(\vec{v}_w) \rangle_{\mathbf{L}^2(\Omega_2)} + \underbrace{\left\langle v_\partial, \partial_t w \right\rangle}_{\mathbf{u}_2}_{\Gamma_{\text{int}}} + \underbrace{\left\langle v_\partial, \partial_t w \right\rangle}_0_{\Gamma_2}, \\ \langle \mathbf{y}_2, v_\partial \rangle_{\Gamma_{\text{int}}} = \langle \nabla w \cdot \mathbf{n}_2, v_\partial \rangle_{\Gamma_{\text{int}}}, \end{cases}$$

$$\text{Gyrator: } \begin{cases} \langle \mathbf{u}_1, v_\partial \rangle_{\Gamma_{\text{int}}} = -\langle \mathbf{y}_2, v_\partial \rangle_{\Gamma_{\text{int}}}, \\ \langle v_\partial, \mathbf{u}_2 \rangle_{\Gamma_{\text{int}}} = \langle v_\partial, \mathbf{y}_1 \rangle_{\Gamma_{\text{int}}}. \end{cases}$$

Partitioned Finite Element Method (PFEM)

Projection on finite element basis: $(\xi_k^{\text{int}})_{1 \leq k \leq N_{\Gamma_{\text{int}}}}$ for u_1 & u_2 & y_1 & y_2 and

$$\begin{array}{cccccc}
 (\varphi_j^1)_{1 \leq j \leq N_T} & (\vec{\psi}_i^1)_{1 \leq i \leq N_Q} & (\xi_k^1)_{1 \leq k \leq N_{\Gamma_1}} & (\varphi_j^2)_{1 \leq j \leq N_p} & (\vec{\psi}_i^2)_{1 \leq i \leq N_q} & (\xi_k^2)_{1 \leq k \leq N_{\Gamma_2}} \\
 T & J_Q & 0 \text{ \& } y_T & \partial_t w & \nabla w & 0 \text{ \& } y_w
 \end{array}$$

Partitioned Finite Element Method (PFEM)

Projection on finite element basis: $(\xi_k^{\text{int}})_{1 \leq k \leq N_{\Gamma_{\text{int}}}}$ for \mathbf{u}_1 & \mathbf{u}_2 & \mathbf{y}_1 & \mathbf{y}_2 and

$$\begin{array}{cccccc} (\varphi_j^1)_{1 \leq j \leq N_T} & (\vec{\psi}_i^1)_{1 \leq i \leq N_Q} & (\xi_k^1)_{1 \leq k \leq N_{\Gamma_1}} & (\varphi_j^2)_{1 \leq j \leq N_p} & (\vec{\psi}_i^2)_{1 \leq i \leq N_q} & (\xi_k^2)_{1 \leq k \leq N_{\Gamma_2}} \\ T & J_Q & \mathbf{0} \text{ \& } \mathbf{y}_T & \partial_t w & \nabla w & \mathbf{0} \text{ \& } \mathbf{y}_w \end{array}$$

$$\text{Heat: } \begin{bmatrix} M_1 & 0 & 0 & 0 \\ 0 & \vec{M}_1 & 0 & 0 \\ 0 & 0 & M_{\text{bnd},1} & 0 \\ 0 & 0 & 0 & M_{\text{int}} \end{bmatrix} \begin{pmatrix} \frac{d}{dt} T \\ J_Q \\ \underline{0} \\ -\underline{y}_1 \end{pmatrix} = \begin{bmatrix} 0 & D_1 & B_1 & B_{1,\text{int}} \\ -D_1^\top & 0 & 0 & 0 \\ -B_1^\top & 0 & 0 & 0 \\ -B_{1,\text{int}}^\top & 0 & 0 & 0 \end{bmatrix} \begin{pmatrix} T \\ J_Q \\ \underline{y}_T \\ \underline{u}_1 \end{pmatrix},$$

$$(D_1)_{j,i} = \int_{\Omega_1} \vec{\psi}_i^1 \cdot \nabla \varphi_j^1 \in \mathbb{R}^{N_T \times N_Q}, \quad (B_1)_{j,k} = - \int_{\Gamma_1} \xi_k^1 \gamma_0(\varphi_j^1) \in \mathbb{R}^{N_T \times N_{\Gamma_1}}, \quad B_{1,\text{int}} \in \mathbb{R}^{N_T \times N_{\Gamma_{\text{int}}}}.$$

Partitioned Finite Element Method (PFEM)

Projection on finite element basis: $(\xi_k^{\text{int}})_{1 \leq k \leq N_{\Gamma_{\text{int}}}}$ for \mathbf{u}_1 & \mathbf{u}_2 & \mathbf{y}_1 & \mathbf{y}_2 and

$$\begin{array}{cccccc} (\varphi_j^1)_{1 \leq j \leq N_T} & (\vec{\psi}_i^1)_{1 \leq i \leq N_Q} & (\xi_k^1)_{1 \leq k \leq N_{\Gamma_1}} & (\varphi_j^2)_{1 \leq j \leq N_P} & (\vec{\psi}_i^2)_{1 \leq i \leq N_q} & (\xi_k^2)_{1 \leq k \leq N_{\Gamma_2}} \\ T & J_Q & \mathbf{0} \text{ \& } \mathbf{y}_T & \partial_t w & \nabla w & \mathbf{0} \text{ \& } \mathbf{y}_w \end{array}$$

$$\text{Heat: } \begin{bmatrix} M_1 & 0 & 0 & 0 \\ 0 & \vec{M}_1 & 0 & 0 \\ 0 & 0 & M_{bnd,1} & 0 \\ 0 & 0 & 0 & M_{\text{int}} \end{bmatrix} \begin{pmatrix} \frac{d}{dt} T \\ J_Q \\ \underline{0} \\ -\underline{y}_1 \end{pmatrix} = \begin{bmatrix} 0 & D_1 & B_1 & B_{1,\text{int}} \\ -D_1^\top & 0 & 0 & 0 \\ -B_1^\top & 0 & 0 & 0 \\ -B_{1,\text{int}}^\top & 0 & 0 & 0 \end{bmatrix} \begin{pmatrix} T \\ J_Q \\ \underline{y}_T \\ \underline{u}_1 \end{pmatrix},$$

$$(D_1)_{j,i} = \int_{\Omega_1} \vec{\psi}_i^1 \cdot \nabla \varphi_j^1 \in \mathbb{R}^{N_T \times N_Q}, \quad (B_1)_{j,k} = - \int_{\Gamma_1} \xi_k^1 \gamma_0(\varphi_j^1) \in \mathbb{R}^{N_T \times N_{\Gamma_1}}, \quad B_{1,\text{int}} \in \mathbb{R}^{N_T \times N_{\Gamma_{\text{int}}}}.$$

$$\text{Wave: } \begin{bmatrix} M_2 & 0 & 0 & 0 \\ 0 & \vec{M}_2 & 0 & 0 \\ 0 & 0 & M_{bnd,2} & 0 \\ 0 & 0 & 0 & M_{\text{int}} \end{bmatrix} \begin{pmatrix} \frac{d}{dt} \partial_t w \\ \frac{d}{dt} \nabla w \\ -\underline{y}_w \\ -\underline{y}_2 \end{pmatrix} = \begin{bmatrix} 0 & D_2 & 0 & 0 \\ -D_2^\top & 0 & B_2 & B_{2,\text{int}} \\ 0 & -B_2^\top & 0 & 0 \\ 0 & -B_{2,\text{int}}^\top & 0 & 0 \end{bmatrix} \begin{pmatrix} \partial_t w \\ \nabla w \\ \underline{0} \\ \underline{u}_2 \end{pmatrix},$$

$$(D_2)_{j,i} = \int_{\Omega_2} \text{div}(\vec{\psi}_i^2) \varphi_j^2 \in \mathbb{R}^{N_P \times N_q}, \quad (B_2)_{j,k} = \int_{\Gamma_2} \xi_k^2 \vec{\psi}_j^2 \cdot \mathbf{n}_2 \in \mathbb{R}^{N_q \times N_{\Gamma_2}}, \quad B_{2,\text{int}} \in \mathbb{R}^{N_q \times N_{\Gamma_{\text{int}}}}.$$

Partitioned Finite Element Method (PFEM)

Projection on finite element basis: $(\xi_k^{\text{int}})_{1 \leq k \leq N_{\Gamma_{\text{int}}}}$ for \mathbf{u}_1 & \mathbf{u}_2 & \mathbf{y}_1 & \mathbf{y}_2 and

$$\begin{array}{cccccc} (\varphi_j^1)_{1 \leq j \leq N_T} & (\vec{\psi}_i^1)_{1 \leq i \leq N_Q} & (\xi_k^1)_{1 \leq k \leq N_{\Gamma_1}} & (\varphi_j^2)_{1 \leq j \leq N_P} & (\vec{\psi}_i^2)_{1 \leq i \leq N_q} & (\xi_k^2)_{1 \leq k \leq N_{\Gamma_2}} \\ T & J_Q & \mathbf{0} \text{ \& } \mathbf{y}_T & \partial_t w & \nabla w & \mathbf{0} \text{ \& } \mathbf{y}_w \end{array}$$

Heat:
$$\begin{bmatrix} M_1 & 0 & 0 & 0 \\ 0 & \vec{M}_1 & 0 & 0 \\ 0 & 0 & M_{\text{bnd},1} & 0 \\ 0 & 0 & 0 & M_{\text{int}} \end{bmatrix} \begin{pmatrix} \frac{d}{dt} T \\ J_Q \\ \underline{0} \\ -\underline{y}_1 \end{pmatrix} = \begin{bmatrix} 0 & D_1 & B_1 & B_{1,\text{int}} \\ -D_1^\top & 0 & 0 & 0 \\ -B_1^\top & 0 & 0 & 0 \\ -B_{1,\text{int}}^\top & 0 & 0 & 0 \end{bmatrix} \begin{pmatrix} T \\ J_Q \\ \underline{y}_T \\ \underline{u}_1 \end{pmatrix},$$

$$(D_1)_{j,i} = \int_{\Omega_1} \vec{\psi}_i^1 \cdot \nabla \varphi_j^1 \in \mathbb{R}^{N_T \times N_Q}, \quad (B_1)_{j,k} = - \int_{\Gamma_1} \xi_k^1 \gamma_0(\varphi_j^1) \in \mathbb{R}^{N_T \times N_{\Gamma_1}}, \quad B_{1,\text{int}} \in \mathbb{R}^{N_T \times N_{\Gamma_{\text{int}}}}.$$

Wave:
$$\begin{bmatrix} M_2 & 0 & 0 & 0 \\ 0 & \vec{M}_2 & 0 & 0 \\ 0 & 0 & M_{\text{bnd},2} & 0 \\ 0 & 0 & 0 & M_{\text{int}} \end{bmatrix} \begin{pmatrix} \frac{d}{dt} \partial_t w \\ \frac{d}{dt} \nabla w \\ -\underline{y}_w \\ -\underline{y}_2 \end{pmatrix} = \begin{bmatrix} 0 & D_2 & 0 & 0 \\ -D_2^\top & 0 & B_2 & B_{2,\text{int}} \\ 0 & -B_2^\top & 0 & 0 \\ 0 & -B_{2,\text{int}}^\top & 0 & 0 \end{bmatrix} \begin{pmatrix} \partial_t w \\ \nabla w \\ \underline{0} \\ \underline{u}_2 \end{pmatrix},$$

$$(D_2)_{j,i} = \int_{\Omega_2} \text{div}(\vec{\psi}_i^2) \varphi_j^2 \in \mathbb{R}^{N_P \times N_q}, \quad (B_2)_{j,k} = \int_{\Gamma_2} \xi_k^2 \vec{\psi}_j^2 \cdot \mathbf{n}_2 \in \mathbb{R}^{N_q \times N_{\Gamma_2}}, \quad B_{2,\text{int}} \in \mathbb{R}^{N_q \times N_{\Gamma_{\text{int}}}}.$$

Gyrator:
$$M_{\text{int}} \underline{u}_1 = -M_{\text{int}} \underline{y}_2, \quad M_{\text{int}} \underline{u}_2 = M_{\text{int}} \underline{y}_1.$$

Partitioned Finite Element Method (PFEM)

Let $\mathcal{C} := B_{1,\text{int}} M_{\text{int}}^{-1} B_{2,\text{int}}^\top$ the **gyrator interconnection** matrix.

$$\text{Diag} \begin{bmatrix} \underline{M}_1 \\ \underline{\dot{M}}_1 \\ \underline{M}_2 \\ \underline{\dot{M}}_2 \\ M_{bnd,1} \\ \underline{M}_{bnd,2} \end{bmatrix} \begin{pmatrix} \frac{d}{dt} \underline{T} \\ J_Q \\ \frac{d}{dt} \underline{\partial_t w} \\ \frac{d}{dt} \underline{\nabla w} \\ \underline{0} \\ -\underline{y_w} \end{pmatrix} = \begin{bmatrix} 0 & D_1 & 0 & -\mathcal{C} & B_1 & 0 \\ -D_1^\top & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & D_2 & 0 & 0 \\ \mathcal{C}^\top & 0 & -D_2^\top & 0 & 0 & B_2 \\ -B_1^\top & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & -B_2^\top & 0 & 0 \end{bmatrix} \begin{pmatrix} \underline{T} \\ J_Q \\ \underline{\partial_t w} \\ \underline{\nabla w} \\ \underline{y_T} \\ \underline{0} \end{pmatrix}$$

Partitioned Finite Element Method (PFEM)

Let $\underline{C} := \underline{B}_{1,\text{int}} \underline{M}_{\text{int}}^{-1} \underline{B}_{2,\text{int}}^\top$ the **gyrator interconnection** matrix.



$$\text{Diag} \begin{bmatrix} \underline{M}_1 \\ \underline{\vec{M}}_1 \\ \underline{M}_2 \\ \underline{\vec{M}}_2 \\ \underline{M}_{bnd,1} \\ \underline{M}_{bnd,2} \end{bmatrix} \begin{pmatrix} \frac{d}{dt} \underline{T} \\ \underline{J_Q} \\ \frac{d}{dt} \underline{\partial_t w} \\ \frac{d}{dt} \underline{\nabla w} \\ \underline{0} \\ -\underline{y_w} \end{pmatrix} = \begin{bmatrix} 0 & \underline{D}_1 & 0 & -\underline{C} & \underline{B}_1 & 0 \\ -\underline{D}_1^\top & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & \underline{D}_2 & 0 & 0 \\ \underline{C}^\top & 0 & -\underline{D}_2^\top & 0 & 0 & \underline{B}_2 \\ -\underline{B}_1^\top & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & -\underline{B}_2^\top & 0 & 0 \end{bmatrix} \begin{pmatrix} \underline{T} \\ \underline{J_Q} \\ \underline{\partial_t w} \\ \underline{\nabla w} \\ \underline{y_T} \\ \underline{0} \end{pmatrix}$$

Discrete Lossy Power Balance

The discrete Hamiltonian \mathcal{H}^d is defined as the continuous Hamiltonian \mathcal{H} evaluated in the *approximated solution*.


$$\frac{d}{dt} \mathcal{H}^d(\underline{T}, \underline{\partial_t w}, \underline{\nabla w}) = -\underline{J_Q}^\top \underline{\vec{M}}_1 \underline{J_Q}.$$

- 1 Introduction
- 2 The simplified, linearised “fluid–structure” model (Zhang and Zuazua, 2007)
- 3 Partitioned Finite Element Method (PFEM)
- 4 Numerical simulations**
- 5 Conclusion




Switching Ω_1 and Ω_2 , **four cases** are covered.

Hamiltonian vs time (log-log), Circles



Hamiltonian vs time (log-log), L-shape



GCC holds, $\Gamma_1 \neq \emptyset$ and $\Gamma_2 = \emptyset$

GCC fails, $\Gamma_1 = \emptyset$ and $\Gamma_2 \neq \emptyset$

GCC holds, $\Gamma_1 \neq \emptyset$ and $\Gamma_2 \neq \emptyset$

GCC fails, $\Gamma_1 \neq \emptyset$ and $\Gamma_2 \neq \emptyset$

- 1 Introduction
- 2 The simplified, linearised “fluid–structure” model (Zhang and Zuazua, 2007)
- 3 Partitioned Finite Element Method (PFEM)
- 4 Numerical simulations
- 5 Conclusion**

To sum up:

A numerical validation of the interest of PHS has been performed:

- The long-time behaviour is as expected at the discrete level;
- The simulation process is intrinsically object oriented.

To go further:

- Choice for the **finite elements families**?
- **Symplectic** time scheme? ⚠ *DAE!!!*
- Structure-preserving **model reduction**?

- A Partitioned Finite Element Method for Power-Preserving Discretization of Open Systems of Conservation Laws
Cardoso-Ribeiro F.L., Matignon D. and Lefèvre L.
IMA Journal of Mathematical Control and Information, 38(2):493–533, (2020)
- Numerical Approximation of Port-Hamiltonian Systems for Hyperbolic or Parabolic PDEs with Boundary Control
Brugnoli A., Haine G., Serhani A. and Vasseur X.
Journal of Applied Mathematics and Physics, 9(6):1278–1321 (2021)
- Long-time behavior of a coupled heat-wave system arising in fluid-structure interaction
Zhang X. and Zuazua E.
Archive for Rational Mechanics and Analysis, 184(1):49–120, (2007)

Thank you for your attention!

Institut Supérieur de l'Aéronautique et de l'Espace

10 avenue Édouard Belin – BP 54032

31055 Toulouse Cedex 4 – France

Phone: +33 5 61 33 80 80

www.isae-superaero.fr