

# LAB 2: FUN WITH SYSTEM CALLS

**Handed out Tuesday Feb 7 2022**

**Due Tuesday Mar 1 2022**

## 1. INTRODUCTION

In this assignment, you will design a new system call for xv6, and use it in some fork synchronization problems. The goals of this assignment are:

- Understand the system call interface
- Understand how user programs send parameters to the kernel, and receive values back
- See how the event handling in the Operating System works
- Understand the process structure and modify it

The deliverables for the assignment are the code that includes the required changes (the new system call, and modifications to exit), as well as the user test program(s).

You will be graded by reports. Randomly selected students (~10%) are expected to demonstrate that you understand what you did and why you did it that way.

## 2. GETTING STARTED

Based on Lab 1 to set up xv6 on your own machine.

Open two terminal windows. In one, enter `make qemu-gdb` (or `make qemu-nox-gdb`). This starts up QEMU, but QEMU stops just before the processor executes the first instruction and waits for a debugging connection from GDB. In the second terminal, from the same directory you ran `make`, run `gdb`. You should see something like this,

## Yue Duan' Homepage

```
% gdb

GNU gdb (GDB) 6.8-debian
Copyright (C) 2008 Free Software Foundation, Inc.
License GPLv3+: GNU GPL version 3 or later
<http://gnu.org/licenses/gpl.html>
This is free software: you are free to change and redistribute it.
There is NO WARRANTY, to the extent permitted by law.  Type "show
copying"
and "show warranty" for details.
This GDB was configured as "i486-linux-gnu".
+ target remote localhost:26000
The target architecture is assumed to be i8086
[f000:fff0] 0xffff0:ljmp  $0xf000,$0xe05b
0x0000fff0 in ?? ()
+ symbol-file obj/kern/kernel
(gdb)
```

Now set a breakpoint on `exec()` by typing `break exec` in the gdb window type `continue`  
You should see something like:

```
(gdb) cont

Continuing.
[New Thread 2]
[Switching to Thread 2]
The target architecture is assumed to be i386
=> 0x80100af8
:push  %ebp

Breakpoint 1, exec (path=0x1c "/init", argv=0x8dffffe98) at exec.c:12
12{
    (gdb)
```

Here we stop execution after the OS is initialized at the stage where it is starting the first process (init). If you type `continue` again, you will break again as follows:

## Yue Duan' Homepage

```
gdb) cont

Continuing.
[Switching to Thread 1]
=> 0x80100af8
:push    %ebp

Breakpoint 1, exec (path=0x8c3 "sh", argv=0x8dffee98) at exec.c:12
12{
```

As you can see, at this stage, init started a shell process which is the xv6 shell we get when the OS boots. If you continue again, gdb will not return since it is waiting for a command to be started in the shell. Switch to the other window and try typing a command (for example, `cat README`) at which time you will get another break as the shell forks then execs the cat program. Feel free to look around at the program when it breaks to see how we reach the system call which should give you ideas about how to add one.

### 3. ASSIGNMENT

Extend the current xv6 process implementation to maintain an exit status. To get this done, add a field to the process structure (see `proc.h`) in order to save an exit status of the terminated process. We will need this for implementing `wait`. Next, you have to change all system calls affected by this change (e.g., `exit`, `wait` etc.).

**a) Change the exit system call signature to `void exit(int status)`.** The exit system call must act as previously defined (i.e., terminate the current process) but it must also store the exit status of the terminated process in the corresponding structure. In order to make the changes in exit system call you must update the following files: `user.h`, `defs.h`, `sysproc.c`, `proc.c` and all the user space programs that uses exit system call. Note, from now on, all user space programs must supply an exit status when terminated.

Hassle: one hassle that this change (and the one in part b below) introduces is that all existing places that used `exit()`, including ones that are in test programs have now to be changed to use the new prototype. You can either do that yourself (e.g., use `grep` to find all locations of this call and change them), or create a new exit call to match the new prototype.

Goals of this part of the assignment: Get familiar with system call arguments and how

## Yue Duan' Homepage

prototype. Carry out a gentle modification to an existing system call and to the Process Control Block (PCB), which will be needed by the next part of the Lab.

**b) Update the wait system call signature to `int wait(int *status)`.** The wait system call must prevent the current process from execution until any of its child processes is terminated (if any exists) and return the terminated child exit status through the status argument. The system call must return the process id of the child that was terminated or -1 if no child exists (or unexpected error occurred). Note that the wait system call can receive NULL as an argument. In this case the child's exit status must be discarded.

Goal of this part of the assignment: Continue to get familiar with system call arguments, in this case with how to return a value.

**c) Add a waitpid system call: `int waitpid(int pid, int *status, int options)`.** This system call must act like wait system call with the following additional properties: The system call must wait for a process (not necessary a child process) with a pid that equals to one provided by the pid argument. The return value must be the process id of the process that was terminated or -1 if this process does not exist or if an unexpected error occurred. We are required only to implement a blocking waitpid where the kernel prevents the current process from execution until a process with the given pid terminates.

**d) Write an example program to illustrate that your waitpid works.** You have to modify the makefile to add your example program so that it can be executed from inside the shell once xv6 boots.

## 4. HELP, HINTS, QUESTIONS TO EXPLORE, ETC...

I will be extending this section based on how I see progress (for example, to help you understand the code base, or provide ideas to make you more effective in working with the code base).

- **Investing in learning gdb will really make your life easier this semester!** There are only a few commands that you need to learn to get started.
  - `break` places a break point which causes the program to stop when it reaches that point. There are many ways to set a break point; I like to use `break` function to cause a stop at the function that I want to look at.
  - `continue` causes gdb to continue execution until the next break point. If you want to execute only one line of the code use `next` or `step`. The difference

## Yue Duan' Homepage

THE HERE.

- `print` allows you to examine a variable. You can use some of the C semantics here, for example to dereference a pointer and see the memory location it points to (e.g., `print *p`), to print a specific format such as string or hex (e.g., `print %x p`). `display` is like `print` but it repeats the print every time gdb stops (e.g., after a break point or after a step or next)
- `list` shows the code around the area you are.  
You can find more gdb help in the gdb resources linked on the class page under resources.
- Another really useful tool is `grep`. You can `grep` for a keyword (or if you are adventurous, a regular expression) in a file or group of files to find if/where it exists. So, let's say I am interested in a specific function or variable and want to see where it is used. In the `xv6` directory, you can type: `grep wait *.c` to search for the string in all files ending with `.c`  
There are a couple of other useful options for `grep`. The `-i` option (e.g., `grep -i wait *.c`) will make `grep` ignore case. The `-v` option excludes a pattern. So, let's say you want to search for `wait`, but not `waitpid`. One way you can do it is `grep wait *.c | grep -v waitpid`
- (Background/deeper understanding): When any event in `xv6` occurs, the hardware switches mode to the operating system, and jumps to the code in `trapasm.S` (starting at label `alltraps`). This code builds the trap frame (first segment), and then sets up the memory segments for the kernel (second segment--unimportant for now).  
The trap frame is a data structure built on the stack that is used to pass some important arguments to the trap handler including pointers to the user stack to enable getting arguments to system calls. Note that the user stack and the kernel stack for a process are separate. We discussed why in class. So, when we push arguments for a system call on the user stack, we need to give a pointer to the kernel to be able to access them.

You can see the `trapframe` structure in `x86.h` -- it's ok to abstract it away since we will not be working with it in detail.

After filling parts of the `trapframe`, it calls `trap()` with the `trap frame` as argument, which takes us to `trap` in `trap.c`

Here you find a big switch statement based on the `trapno` that caused the trap (this is stored in the `trap frame`). Each case represents an event and implements its trap handler. Only a few events are currently supported such as system calls and the

## Yue Duan' Homepage

If you look under the system call case (the first case), you see some sanity checks (OS code is typically paranoid to avoid kernel panics), you see that we eventually call `syscall()` which is the top level handler for system calls. Lets follow `syscall` which is located at the bottom of `syscall.c`

We get the system call number from the `eax` register in the user code (saved on the trapframe) and use it to index into the system call table and pick up the appropriate handler to call. The return value from the system call handler is stored in the register `eax` in the trapframe (which is used by convention to store return values in Linux/x86) to provide the return value back to the user.

The handlers are all of the same function type (they are all called `sys_xyz` where `xyz` is the system call they handle) which enables us to use this trap handler table and call any one of them as appropriate.

Lets look at the implementation of one of these, lets say `sys_kill()` which passes a signal to a process, often to kill it.

`sys_kill()` and several other handlers are implemented in `sysproc.c` because they have to do with processes. Other handlers are implemented in the file system code, or memory code as appropriate to their operation. Use `grep` to find them if you can't figure out where they are.

You will note that `sys_kill` eventually calls `kill` where the real implementation of the system call is. This enables us to pass different parameters to each system call to get around the fact that the `sys_` handler are all the same type.

Note also that `sys_kill` had to get those parameters fro the user stack. To help with this low level read, there are a number of accessor functions (`argint`, `argstr`, etc...) defined to get access to the arguments based by the user by using information in the trapframe.

## 5. WHAT TO SUBMIT

You need to submit a report that includes the folowing:

- All code changes you made on `xv6` source code (hint: `diff -r original_xv6 your_xv6` )
- Detailed explanation about these changes

# Yue Duan' Homepage

---