АИС «Служба такси» — датологическая модель
База данных TaxiService_Db · PostgreSQL

PK — первичный ключ; FK — внешний ключ
Клиент и тариф: у заказа ровно один
Водитель: у заказа ноль или один
У каждой родительской записи: ноль или много заказов
Один активный заказ на водителя — отдельное бизнес-правило

clients

PK	**id**	SERIAL
	full_name	VARCHAR(150), NOT NULL
	phone	VARCHAR(50)

drivers

PK	**id**	SERIAL
	full_name	VARCHAR(150), NOT NULL
	car_name	VARCHAR(100), NOT NULL
	car_number	VARCHAR(30), NOT NULL
	is_available	BOOLEAN, NOT NULL, DEFAULT TRUE

tariffs

PK	**id**	SERIAL
	name	VARCHAR(100), NOT NULL
	base_price	NUMERIC(10,2), NOT NULL
	price_per_km	NUMERIC(10,2), NOT NULL

orders

PK	**id**	SERIAL
FK	**client_id**	INTEGER, NOT NULL
FK	**driver_id**	INTEGER, NULL
FK	**tariff_id**	INTEGER, NOT NULL
	pickup_address	TEXT, NOT NULL
	destination_address	TEXT, NOT NULL
	distance_km	DOUBLE PRECISION, NOT NULL, DEFAULT 4
	cost	NUMERIC(10,2), NOT NULL
	status	VARCHAR(50), NOT NULL, DEFAULT 'Создан'
	created_at	TIMESTAMP, NOT NULL, DEFAULT NOW()

clients 1 — ON DELETE RESTRICT — orders (0..N)
drivers 0..1 — ON DELETE SET NULL — orders (0..N)
tariffs 1 — ON DELETE RESTRICT — orders (0..N)