

# Apache Labs LLC



## piHPSDR Controller Users Guide

by

**John Melton GØORX/N6LYT**

This document contains references to the Apache Labs Transceiver products  
<http://www.apache-labs.com>

In cooperation with VK6PH, NRØV, W5WC, K5SO  
and the OpenHPSDR Hardware and Software Projects  
<http://openhpsdr.org>

all images and manufacturer data is copied here with permission of the owner

# Contents - piHPSDR Controller Users Guide

<b>Introduction.....</b>	<b>5</b>
Introduction by John Melton GØORX/N6LYT.....	5
<b>1. Front panel controls.....</b>	<b>6</b>
Default assignments of switches and rotary encoders.....	6
Power ON/OFF – switches external 12vdc 2A power to the Controller.....	6
TUN – MOX/TUNE.....	6
S1 - Band.....	6
S2 - Band Stack.....	6
S3 - Mode.....	6
S4 - Filter.....	6
S5 - Noise Blanker.....	6
S6 - AGC.....	6
FN – Function switch to toggle TUNE or MOX button and E1, E2, E3.....	6
E1 -- two functions AF Gain / MIC Gain.....	6
E2 - two function RF Drive / TUNE Drive.....	6
E3 - two function AGC Gain / Rx Attenuation.....	6
E4 VFO – main tuning knob.....	6
Appendix page 40 has a table showing the Switch, Encoder, and Touch Screen activation details.....	6
Network LAN connection.....	7
Controller Hardware requirements.....	7
13.8vdc 2.5A (minimum 12vdc 2A) Power connection.....	7
100BT LAN connection to your Apache Transceiver.....	7
Controller software requirements:.....	8
PiHPSDR Controller Raspbian Operating System and application program are factory installed on an SDHC card.....	8
PiHPSDR Controller - side panel.....	9
<b>2. Quick Start Instructions.....</b>	<b>10</b>
Hardware Setup.....	10
Software Setup.....	10
<b>3. Discovery.....</b>	<b>11</b>
Discovery → Start.....	13
<b>4. Menu.....</b>	<b>14</b>
Menu Exit piHPSDR.....	15
Menu → General.....	16
Menu → Audio.....	17
Menu → ANT.....	18
Menu → Display.....	19
Menu → DSP.....	21
Menu → PA Gain by Band.....	22
Menu → CW.....	23
Menu → OC Open Collector Aux I/O connectors.....	24
MENU → FreeDV.....	25
Menu → XVTR.....	26
<b>5. Screen Controls and Push Buttons.....</b>	<b>27</b>

Function.....	27
AF Gain Slider.....	28
MIC Gain Slider.....	29
PA Drive Slider.....	30
Tune Drive Slider.....	31
AGC Gain Slider.....	32
Receive Attenuation Slider.....	33
Band Selection.....	34
Band Stack.....	35
Mode.....	36
Filter.....	37
Noise.....	38
NR - Noise Reduction.....	38
NR2 - New NROV algorithm.....	38
ANF - Automatic Notch Filter.....	38
SNB - Spectral Noise Blanker.....	38
AGC.....	39
Off - AGC disabled.....	39
Long - Hangtime = 2000 ms. Decay_time_constant = 2000 ms.....	39
Slow - Hangtime = 1000 ms. Decay_time_constant = 500 ms.....	39
Medium - Hang is turned OFF. Decay_time_constant = 250 ms.....	39
Fast - Hang is turned OFF. Decay_time_constant = 50 ms.....	39
The AGC Gain levels are adjusted using the AGC encoder (or the AGC Slider if no encoders).....	39
VFO Lock.....	40
VFO Step.....	41
Meter.....	42
<b>6. Tuning.....</b>	<b>43</b>
VFO Encoder.....	43
Touch Screen.....	43
Mouse.....	43
CTUN - Click Tuning.....	44
RIT.....	45
<b>7. Mode PSK31 - Receive.....</b>	<b>46</b>
TUNE/SWR/FWD power.....	46
<b>8. Appendix.....</b>	<b>47</b>
Encoders and Switches.....	47
Switch or Encoder.....	47
Power ON/OFF.....	47
TUN - TUNE button.....	47
generates a carrier with Tune power selection slider.....	47
generates a carrier with Tune power selection slider.....	47
S1 - Band.....	47
S2 - Mode.....	47
S3 - Filter.....	47
S4 - Noise.....	47
S5 -AGC.....	47
S6 - MOX.....	47

FN – Function.....	47
Function switch to toggle TUNE or MOX button displayed on the bottom left of the screen.....	47
Function switch to toggle TUNE or MOX and the action of E1, E2, E3 knobs.....	47
E1 --.....	47
two functions AF Gain / MIC Gain.....	47
two functions AF Gain / MIC Gain.....	47
E2 –.....	47
two function RF Drive / TUNE Drive.....	47
two function RF Drive / TUNE Drive.....	47
E3 –.....	47
two function AGC Gain / Rx ATTEN.....	47
two function AGC Gain / Rx ATTEN.....	47
E4 VFO – Main tuning knob.....	47
PIO pin Assignments (RaspberryPi).....	49
RaspberryPi-3b TRRS connector.....	49
MIC Input is easily done with an inexpensive USB adapter.....	50
<b>9. Reference materials.....</b>	<b>51</b>
GOORX Friedrichshaven pdf and video.....	51
<b>10. Volunteer Programmers can help with ideas.....</b>	<b>51</b>
PureSignal.....	51
PSK31 Transmit encoding.....	51
RTTY receive decoding.....	51
VOX.....	51
Thin Pipe Remote Audio/Video.....	51
Panadapter color selection.....	51
IF-shift, Hi-Cut, Low-Cut.....	51
<b>Apache Support.....</b>	<b>52</b>
Apache Labs International Support.....	52
Apache Yahoo Support Group.....	52
OpenHPSDR Group.....	52
<b>Apache Service and Repair.....</b>	<b>52</b>
<b>Early prototypes by John Melton GOORX.....</b>	<b>53</b>

## Introduction

Introduction by John Melton GØORX/N6LYT

Thu Aug 5, 2016 12:52 am (PDT) .

Posted by: ["John Melton" g0orx](#)

I think it is time to answer some of the questions about the controller.

Some background ...

I presented a paper at DCC last year on how to build a CAT controller using an Arduino and some buttons and encoders, even one with an LCD screen showing the mode, frequency and an S meter. The idea of this was to try to get people building them.

When I returned I started looking at what a Raspberry Pi (model 2 at the time) could do as a standalone controller. I had already ported WDSP to Linux so had a good starting point. Very soon after I received

an email from LA2NI, Kjell Karlsen asking if my Android code would run on the Raspberry Pi as he wanted to try to build a standalone system with a touch screen. I told him about my early development work on the Raspberry Pi and that started a project that is still on going today.

The idea was not to build an all singing/dancing copy of PowerSDR but to build something that could be used with a small portable system. Kjell has since gone on to build a very nice system using a Hermes and Apollo all built into a small case with the Raspberry Pi (now a model 3).

Abhi (Apache Labs) got interested in the project and wanted to build a controller initially without the built in Hermes/Apollo. Hopefully we will see a complete portable system sometime from Apache Labs.

So, that is what we have today. The software is still in development and new features are being added as well as bugs being fixed. It is designed to use with the radio, not as a remote console. The RPi does not have any audio input but does have audio output. It is currently possible to output the audio locally on the RPi but to connect a microphone you will need to plug a USB audio card into the device. I will be adding support for connecting a microphone to the this as well.

The RPi will work over WiFi using the built in controller. The signal quality will determine what sample rate it will run at. The RPi does not have GigE so cannot connect directly to a radio running the new Ethernet protocol, but will work through a switch or over WiFi. However, it has been tested using a USB to GigE dongle and that does work. Just remember this will not run at the higher sample rates.

I have looked at several other more powerful single board computers, but always I have run into problems with their implementation of the GPIO, which is used to interface the buttons and encoders.

We are using the Raspberry Pi official 7 inch touch screen. This has a resolution of 800x480 so we are struggling with screen real estate.

There is work in progress to also use the controller remotely across the Internet. This will require a server running at the radio that is connected to by a thin client running on the controller. This will stream the audio and spectrum information with all the DSP work being done on the server. It is not based on my gbpsdr3 project but of course that was a good starting point for the design.


Finally, all the software is open source. It will run on a Raspberry Pi without the buttons/encoders. It will also run on other Linux systems and I have even built it and had it running on Mac OS X. I have not tried to build it on Windows as I do not have a Windows system.

-- John g0orx/n6lyt

---

 Note: This Note: this document assumes familiarity with the Apache Transceiver and standard software such as PowerSDR or Thetis. The Apache Transceiver Users Guides are located here: <https://apache-labs.com/al-downloads/1001/ANAN-USER-GUIDES.html>

## 1. Front panel controls



Switches

Encoder  
S


### Default assignments of switches and rotary encoders

- Power ON/OFF – switches external 12vdc 2A power to the Controller
- TUN – MOX/TUNE
- S1 - Band
- S2 - Band Stack
- S3 - Mode
- S4 - Filter
- S5 - Noise Blanker
- S6 - AGC
- FN – Function switch to toggle TUNE or MOX button and E1, E2, E3
- E1 -- two functions AF Gain / MIC Gain
- E2 – two function RF Drive / TUNE Drive
- E3 – two function AGC Gain / Rx Attenuation
- E4 VFO – main tuning knob


**Appendix** page 40 has a table showing the Switch, Encoder, and Touch Screen activation details.

## Network LAN connection

Auto-negotiation of a the RaspberryPi 100BT Ethernet connection allows operation of the Controller at the 48000, 96000, and 192Ksps sample rates.



The new piHPSDR-Controller can be connected directly to your ANAN Transceiver and each unit will make use of the APIPA assignment for an IP address.



CAT-5 or CAT-6 shielded cables are recommended for connection of the Controller

## Controller Hardware requirements

-  13.8vdc 2.5A (minimum 12vdc 2A) Power connection
-  100BT LAN connection to your Apache Transceiver

## Controller software requirements:

- Pihpsdr Controller Raspbian Operating System and application program are factory installed on an SDHC card.

If you have purchased the piHPSDR-Controller KIT, you will need to create and install an SDHC card with the RaspberryPi operating system and pihpsdr application.

Instructions for Installation are detailed in the [Install pdf document](#) that is available at:

<https://github.com/g0orx/pihpsdr/raw/master/release/documentation/pihpsdr-install.pdf>

- If you wish to get the latest version of pihpsdr source code, executable binaries, and documentation the instructions are available at:

<https://github.com/g0orx/pihpsdr/raw/master/release/documentation/pihpsdr-build.pdf>

**Note:** it is a good idea to make a backup of your Operating System and piHPSDR software. Use the RaspberryPi Menu → Accessories → SD Card Copier” utility. Use a new SDHC card of the same capacity as the original.

This is easily done using a USB – SDHC card reader/writer dongle plugged into one of the RPi USB ports on the left side of the piHPSDR Controller.

**A pdf document reader is included in the standard RaspberryPi operating system distribution.**



PiHPSDR Controller - side panel

{side panel picture goes here}

## 2. Quick Start Instructions

please refer to front and back panel illustrations

### Hardware Setup

- Carefully unpack the piHPSDR Controller.
- Connect a CAT 5/6 Ethernet cable between the rear panel LAN jack with proper access to your Apache Transceiver, Gigabit switch, or suitable router. Please see Network LAN connection page 9.
- Connect the supplied piHPSDR Controller power cable to a **fused** 12vdc typical Amateur Radio power supply.

### Software Setup

The piHPSDR Controller software is pre-formatted on the Operating System SDHC card inserted in the RaspberryPi.

Alternative software configurations are not provided by Apache Labs.


A person familiar with the Raspbian operating system may wish to modify or update the contents of the SDHC card using appropriate Linux tools. Please refer to page 10.

Note: pihpsdr is OpenSource. If you would like to compile the program on a Linux system, the source, binaries, and documentation are located at <https://github.com/g0orx>

### 3. Discovery


When first started, piHPSDR will try to discover all the HPSDR compatible radios on the network. It will look for devices running both the original (old) and the new Ethernet (new) protocol.

**If one or more Transceiver interfaces are found they will be identified by the device type,** the software version, the IP address and the MAC address of the device.




If no devices are found you should check connectivity between the radio and the network that piHPSDR is connected to. Tapping on OK will try discovery again. Tapping on Cancel will exit piHPSDR back to the Raspberry Pi desktop.

The discovery protocol will allow a device to see and respond even if they are not on the same subnet. If this is the case, the Start button will be disabled and the text replaced with **Subnet**. The most common cause of this problem is usually that the radio has not been able to get a DHCP address and has defaulted to the Self Assigned IP Address, or the device has a static IP address that is not on the same subnet as the piHPSDR.




## Discovery → Start

Tapping on the Start button will start the radio running.



## 4. Menu


Tapping the Menu button brings up the menu dialog.



The menu dialog lets you select the different menu options for configuring the radio.

You can close the menu by tapping on the Close Menu button or by tapping on the Menu button again.

Menu Exit piHPSDR




The Exit piHPSDR button will bring up another dialog allowing you to end the piHPSDR application in a number of ways:

-  **Close** - close this dialog box
-  **Exit** - exit piHPSDR back to the Raspberry Pi Desktop
-  **Reboot** - reboot the Raspberry Pi
-  **Shutdown** - Shutdown the Raspberry Pi

You can also tap the Menu button again to close the Exit Menu and bring up the Menu selection.

Menu → General



**Sample Rate** - The Sample Rate selection selects the width of the Panadapter displayed on the piHPSDR Controller screen. This is the rate which **pihpsdr** uses to decode a portion of the 30Mhz spectrum data from the Apache Transceiver.

**Note: 768k and 1.536K are not available on Rpi.**

**ALEX** - selects the automatic LPF/BPF filters selected inside each [Apache](#) Transceiver


**APOLLO** - refers to the Linear Amplifier and filters designed by Kjell LA2NI.

**Dither** - Dither is a built-in electronic feature of the Linear Technologies LTC-2208 Analog to Digital Converter chip inside each [Apache](#) Software Defined Radio Transceiver.

**Random** - Ramdom is a built-in electronic feature of the Linear Technologies LTC-2208 Analog to Digital Converter chip inside each [Apache](#) Software Defined Radio Transceiver.

**VFO Encoder Divisor** - The VFO Encoder Divisor lets you adjust the sensitivity of the VFO encoder. The value specifies the number of encoder steps required to step the VFO up or down.

Menu → Audio



 **Mic Line In** - When enabled the audio from the radio will come from Line In rather than the microphone socket.

 **Mic Boost** - is a 20db boost of the MIC connected to your [Apache Transceiver](#).


The Raspberry Pi does not have any audio input capability. However, you can connect a USB sound dongle to the Raspberry Pi which will enable additional audio input and output.

 **Local Audio** - When enabled selects the selected audio interface on the Raspberry Pi to output sound.


 **Microphone Audio** - When enabled selects the selected audio interface on the Raspberry Pi for the microphone input.

Menu → ANT

The Ant menu selects which antenna is used for receive and transmit on each band.



Menu → Display



**Fill Panadapter** – when enabled the panadapter graph will be filled. When not enabled it will be drawn as a line.

**Frames Per Second** – Update rate of Panadapter and Waterfall

**Panadapter High** - Maximum signal level displayed in Panadapter

**Panadapter Low** - Minimum signal level displayed in Panadapter

**Waterfall Automatic** – When enabled the Waterfall High and Waterfall Low are adjusted automatically.


**Waterfall High** – When Automatic is not set this will set the maximum signal used in the waterfall.

**Waterfall Low** - When Automatic is not set this will set the minimum signal used in the waterfall.

**Detector** – Selects Peak, Rosenfell, Average or Sample for the Panadapter display.

- **Averaging** - Selects the method for averaging the Panadapter display.
- **Display Panadapter** - when selected the Panadapter is displayed on the main screen.
- **Display Waterfall** - when selected the Waterfall display is displayed on the main screen.
- **Display Sliders** - when selected the slider controls are displayed on the main screen.
- **Display Toolbar** - when selected the toolbar is displayed on the main screen.
- **Buttons Display Dialog** - when selected the presses on the toolbar or the physical buttons displays a dialog to select the options. When not set the button steps forward or reverse (if Function is enabled) through the options.

Menu → DSP



The DSP has options for the DSP functions.

 **AGC Hang Threshold** – sets the HangThreshold for the AGC when enabled.

 **NR/NR2/ANF** – selects where in the DSP processing the noise reduction functions are performed/ The default id Pre AGC processing.

Pre AGC - perform noise reduction pre AGC

Post AGC - perform noise reduction post AGC

 **NR2 Gain Method** – selects the method used for the gain processing. The default is Gamma.

Linear - Gaussian speech distribution, linear amplitude scale

Log - Gaussian speech distribution, log amplitude scale

Gamma - Gamma speech distribution


 **NR2 NPE Method** – selects the Noise-Power-Estimation method. The default is OSMS.

OSMS - Optimal Smoothing Minimum Statistics

MMSE - Minimum Mean -Square Error

 **NR2 AE Filter** - Enable Artifact elimination. Default enabled.

## Menu → PA Gain by Band




Sets the gain for each band to set the maximum drive level. Note that as the setting are increased the drive level is decreased.



**Transmit out of band** – enables transmit outside of ham bands. Default disabled.


Menu → CW



Controls the firmware CW Keyer.

- CW Speed (WPM) – sets speed of dot/dash generator when in Mode A or Mode B.
- CW Break In – when enabled sets the delay time in milliseconds to switching to receive.
- CW KEYER STRAIGHT – selects the key connected will be a straight key.
- CW KEYER MODE A – selects a paddle key running in Mode A
- CW KEYER MODE B – selects a paddle key running in Mode B
- Keys reversed – when enabled the dot/dash paddles are reversed.
- Sidetone Level – sets the audio level of the sidetone.
- Sidetone Freq – set the frequency of the sidetone.
- Weight – sets the dot/dash weighting.

Menu → OC Open Collector Aux I/O connectors




Configure the Open Collector outputs for each band. These can be used to control an external filter when not using the Apache Labs filters or the Alex filters. The default is none are enabled.

When an external ATU is used the Tune option can be used to signal to the ATU to start its tune function. The default is none are enabled.

- Tune – configure an OC to be turned on when Tune is enabled. Currently only the Full Tune is implemented.
- Full Tune – specifies the time the OC is enabled when the Tuning.

MENU → FreeDV



Sets the FreeDV Text Message that is send along with the digitized voice.

Menu → XVTR



Configure up to 8 transverters.


- Title – the name as it appears in the Band, Ant and OC menus.
- Min Freq – The minimum frequency in Hz.
- Max Freq – The maximum frequency in Hz.
- LO Freq – The Local Oscillator frequency in Hz.
- Disable PA – When checked the PA will be disabled on transmit.

Note that the frequency the radio is tuned to is the selected frequency minus the LO frequency. In the example above the 144MHz to 146MHz transverter frequency will be tuned to 28MHz to 30MHz on the radio.

When one or more transverters are configured they will appear in the band selection dialog and also in the ANT selection menu and the PA Gain menu.

## 5. Screen Controls and Push Buttons

### Function



The function touch screen button or physical button enable the optional functions of some of the buttons and encoders.


When enabled the **Function** text appears in the VFO panel and the Mox button changes to Tune.

In addition the 3 encoders change function:

- The **E1** encoder selects **AF Gain or Mic Gain**
- The **E2** encoder selects **PA Drive Level or Tune Drive Level**
- The **E3** encoder selects **AGC Gain or Rx Attenuation**


## AF Gain Slider

AF Gain Slider is selected using Function key and then rotating E1




## MIC Gain Slider

MIC Gain Slider is selected using Function key and then rotating E1




## PA Drive Slider

PA Drive Slider is selected using the Function Key and then rotating E2




## Tune Drive Slider

Tune Drive Slider is selected using the Function Key and then rotating E2




## AGC Gain Slider

AGC Gain Slider is selected using the Function Key and then rotating E3




## Receive Attenuation Slider

Receive Attenuation Slider is selected using the Function Key and then rotating E3



## Band Selection




Tapping the Band touch screen button or pressing the physical button will display the list of bands with the current band highlighted in orange.

Tapping the current band will step through the band stack for that band. Tapping on any other band will switch to that band and the last used band stack entry.

Tapping on Close will close the menu.

## Band Stack




Tapping the BStack touch screen button or the physical button will display the list of Band Stack entries for the current band with the current selection highlighted in orange.

Tapping on an entry will switch to that entry.

Tapping on close will Close the menu.

## Mode




Tapping the Mode touch screen button or pressing the physical button will display the list of modes with the current mode highlighted in orange.

Tapping a mode will switch to the selected mode.

Tapping on Close will close the menu.

Filter




Tapping the Filter touch screen button or pressing the physical button will display the list of filters with the current filter highlighted in orange.

Tapping a filter will switch to the selected filter width.

Tapping on Close will close the menu.

## Noise




Tapping the Noise touch screen button or physical button will display the list of noise reduction modes available.

You can select one of the following functions:

- NR - Noise Reduction
- NR2 - New NR0V algorithm
- ANF - Automatic Notch Filter
- SNB - Spectral Noise Blanker

## AGC




Tapping the AGC touch screen button or physical button will display the list of AGC options.

- Off - AGC disabled
- Long - Hangtime = 2000 ms. Decay\_time\_constant = 2000 ms.
- Slow - Hangtime = 1000 ms. Decay\_time\_constant = 500 ms
- Medium - Hang is turned OFF. Decay\_time\_constant = 250 ms
- Fast - Hang is turned OFF. Decay\_time\_constant = 50 ms

The AGC Gain levels are adjusted using the AGC encoder (or the AGC Slider if no encoders).

## VFO Lock



The VFO can be locked by pressing the button on the AF Gain encoder or by tapping on the left side of the VFO display. To unlock press the AF Gain encoder button again or tap on the left side of the VFO display.

When locked the text will be displayed in Red on the VFO.


## VFO Step



By tapping on the right side of the VFO the menu to select the step rate can be selected.

This will set the stepping rate when using the VFO encoder, dragging the panadapter or waterfall or using a mouse wheel

## Meter



Tapping on the Meter will display a list of options for updating the meter.

## 6. Tuning

### VFO Encoder

The VFO encoder can be used to tune the radio. By turning the encoder clockwise and anticlockwise the frequency will increment or decrement by the amount of the step value.

The General Menu has a field to set the resolution of the encoder.

### Touch Screen

Touching and dragging on the panadapter or waterfall will move the frequency up or down. Note that it will move in step increments.

Tapping a frequency on the panadapter or waterfall will move to that frequency.


### Mouse

Left down and holding then dragging while on the panadapter or waterfall will move the frequency up or down.

Left clicking will move to the selected frequency.

Moving the scroll wheel will increment or decrement the frequency by the step value.


## CTUN - Click Tuning



Tapping on the CTUN button will enable or disable the click tuning function. When the function is enabled the CTUN button text will be red.


When CTUN is enabled tuning is restricted to be within the passband currently being received. The tuned frequency and filter moves withing the current passband without scrolling the panadapter or waterfall left or right.

RIT



Tapping on the RIT button will enable RIT. The RIT+ and RIT- buttons can be tapped or held to increment decrement the RIT frequency in Hz.

## 7. Mode PSK31 - Receive



## TUNE/SWR/FWD power

When the Function button is touched or selected, it toggles the TUNE/MOX button on the far left. FWD power and SWR can then be read in the top of the pihpsdr window.

## 8. Appendix


### Encoders and Switches

#### Factory Switch/Encoder/Touch activation

Switch or Encoder	Function	Touch Screen	GPIO
 Power ON/OFF	Controller power on/off	Controller power on/off	
 TUN - TUNE button	generates a carrier with Tune power selection slider	generates a carrier with Tune power selection slider	
 S1 - Band	10 HF Bands + General Coverage + WWV	10 HF Bands + General Coverage + WWV	
 S2 - Mode	LSB USB DSB CWL CWU FMN AM DRM FreeDV PSK	LSB USB DSB CWL CWU FMN AM DRM FreeDV PSK	
 S3 - Filter	10 IF Filter widths	10 IF Filter widths	
 S4 - Noise	5 Noise Reduction modes	5 Noise Reduction modes	
 S5 -AGC	5 AGC Decay settings	5 AGC Decay settings	
 S6 - MOX	Space bar toggle for PTT or MOX button	Space bar toggle for PTT or MOX button	
 FN - Function	Function switch to toggle TUNE or MOX button displayed on the bottom left of the screen	Function switch to toggle TUNE or MOX and the action of E1, E2, E3 knobs	
 E1 --	two functions AF Gain / MIC Gain	two functions AF Gain / MIC Gain	
 E2 -	two function RF Drive / TUNE Drive	two function RF Drive / TUNE Drive	
 E3 -	two function AGC Gain / Rx ATTEN	two function AGC Gain / Rx ATTEN	
 E4 VFO - Main tuning knob	-----	-----	
Menu	-----	Main piHPSDR Menu	
	-----		


<b>Switch or Encoder</b>	<b>Function</b>	<b>Touch Screen</b>	<b>GPIO</b>
Meter → Band		S-Meter and ALC Meter	
Meter → Band Stack	3 to 5 level quick freq change	3 to 5 level quick freq change	
Meter → Mode	Mode	Mode	
Meter → Filter	IF Filter width	IF Filter Width	
Meter → Noise	Noise Blanker mode	Noise Blanker Mode	
Meter → AGC	Automatic Gain Attack speed	Automatic Gain Attack speed	
Locked	Right click on VFO Frequency to toggle Frequency Lock	Touch VFO Frequency to toggle Frequency Lock	
Meter	Right click on S-Meter for S-Meter and ALC peak/average	Touch S-Meter for S-Meter and ALC peak/average	

## PIO pin Assignments (RaspberryPi)



## RaspberryPi-3b TRRS connector

The four wire **TRRS** audio/video connector on the RaspberryPi-3b should be used carefully. The Video output may connect incorrectly on a standard 3-pin Stereo plug.



Adafruit has an adapter that may be helpful for experimenters:

<URL: <https://www.adafruit.com/products/2914> >



SparkFun has an open wire plug and cable  
<URL: <https://www.sparkfun.com/products/11580> >



MIC Input is easily done with an inexpensive USB adapter

<URL: <https://www.adafruit.com/product/1475>>



## 9. Reference materials

G0ORX Friedrichshafen pdf and video

Friedrichshafen 2016 publication

<https://www.dropbox.com/sh/fva5d5mi93c93tq/AAD6dU-eBMR0cVK-E95hJC5la?dl=0>

Jacinto Rebelo CU2ED for his Homebrew of a piPSDR Controller

Kjell Lasen LA2NI for his complete RPi-e System

F'Hafen video on YouTube:

<https://www.youtube.com/watch?v=U7QfP28YjCw>

## 10. Volunteer Programmers can help with ideas

PureSignal

PSK31 Transmit encoding

RTTY receive decoding

VOX

Thin Pipe Remote Audio/Video

Panadapter color selection

IF-shift, Hi-Cut, Low-Cut

## Apache Support

### Apache Labs International Support

Technical support for ANAN-10 from the factory is available via the Apache Labs Yahoo Group

<http://groups.yahoo.com/group/apache-labs/>

or directly via email <[support@apache-labs.com](mailto:support@apache-labs.com)>

### Apache Yahoo Support Group

<http://groups.yahoo.com/group/apache-labs/>

### OpenHPSDR Group

Instructions relating to joining the OpenHPSDR Group reflector are here:

<http://lists.openhpsdr.org/listinfo.cgi/hpsdr-openhpsdr.org>

The OpenHPSDR archives may also be searched here:

<http://lists.openhpsdr.org/mmsearch.cgi/hpsdr-openhpsdr.org>

The latest version of the OpenHPSDR User Manual can be obtained from

<http://openhpsdr.org/documents.php> Author Phil Harman VK6PH

### Apache Service and Repair

1023 Tower B4, Spaze I-Tech Park

Sector - 49, Sohna Road

Gurgaon - 122001



Haryana, India

Tel: 91-0124-4245173/4/5 (10AM - 6PM IST]

Email: [support@apache-labs.com](mailto:support@apache-labs.com)

Website: <http://www.apache-labs.com>

Early prototypes by John Melton G0ORX



Note: pihpsdr is OpenSource. If you would like to run the program on a Linux system, the source, binaries, and documentation are located here:  
<http://g0orx.blogspot.com/>

## NOTES

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

# Alphabetical Index

100BT LAN connection.....	8
13.8vdc 2.5A (minimum 12vdc 2A).....	8
5. Screen Controls and Push Buttons.....	29
AF Gain or Mic Gain.....	29
AF Gain Slider.....	30
AGC.....	41
AGC Gain or Rx Attenuation.....	29
AGC Gain Slider.....	34
AGC Hang Threshold.....	23
ALEX.....	17
ANF.....	40
Apache Labs International Support.....	54
Apache Service and Repair.....	54
Apache Support.....	54
Apache Yahoo Support Group.....	54
APOLLO.....	17
Appendix.....	49
Automatic Notch Filter.....	40
Averaging.....	22
backup of your Operating System and piHPSDR software.....	9
Band Selection.....	36
Band Stack.....	37
Buttons Display Dialog.....	22
Close.....	16
Controller software requirements:.....	9
CTUN - Click Tuning.....	46
CW Break In.....	25
CW key.....	8
CW KEYER MODE A.....	25
CW KEYER MODE B.....	25
CW KEYER STRAIGHT.....	25
CW Speed (WPM).....	25
Default assignments of switches and rotary encoders.....	7
Detector.....	21
Discovery.....	12
Discovery → Start.....	14
Display Panadapter.....	22
Display Sliders.....	22
Display Toolbar.....	22
Display Waterfall.....	22
Dither.....	17

E1.....	7, 29
E2.....	7, 29
E3.....	7, 29
E4 VFO.....	7
Encoders and Switches.....	49
Exit.....	16
factory installed.....	9
familiarity with the Apache Transceiver.....	6
Fast.....	41
Fill Panadapter.....	21
Filter.....	39
FN.....	7
Frames Per Second.....	21
Full Tune.....	26
Function.....	29
GØORX Friedrichshaven pdf and video.....	53
Ham band resonant 50 ohm HF antenna.....	8
Hardware Setup.....	11
headphones.....	8
Install and Build pdf documents.....	9
Install pdf document.....	9
Introduction by John Melton GØORX/N6LYT.....	6
Local Audio.....	19
Long.....	41
Medium.....	41
Menu.....	15
Menu → ANT.....	20
Menu → Audio.....	18
Menu → CW.....	25
Menu → Display.....	21
Menu → DSP.....	23
MENU → FreeDV Mode.....	27
Menu → General.....	17
Menu → OC.....	26
Menu → PA Gain by Band.....	24
Menu → XVTR.....	28
Menu Exit piHPSDR.....	16
Meter.....	44
Mic Boost.....	18
MIC Gain Slider.....	31
Mic Line In.....	18
Microphone Audio.....	19
Mode.....	38

Mode PSK31 – Receive.....	48
Mouse.....	45
Network LAN connection.....	8
Noise.....	40
Noise Reduction.....	40
NR.....	40
NR/NR2/ANF.....	23
NR2.....	40
NR2 AE Filter.....	23
NR2 Gain Method.....	23
NR2 NPE Method.....	23
Open Collector Aux I/O connectors.....	26
OpenHPSDR Group.....	54
PA Drive Level or Tune Drive Level.....	29
PA Drive Slider.....	32
Panadapter High.....	21
Panadapter Low.....	21
PC condenser microphone.....	8
Pihpsdr Controller Raspbian Operating System.....	9
pihpsdr software release.....	9
piHPSDR-Controller KIT.....	9
PIO pin Assignments (RaspberryPi).....	51
Power ON/OFF.....	7
powered stereo speakers.....	8
Quick Start Instructions.....	11
Random.....	17
Reboot.....	16
Receive Attenuation Slider.....	35
Reference materials.....	53
reversed.....	25
RIT.....	47
S1 - Band.....	7
S2 - Band Stack.....	7
S3 - Mode.....	7
S4 - Filter.....	7
S5 - Noise Blanker.....	7
S6 - AGC.....	7
Sample Rate.....	17
Screen Controls and Push Buttons.....	29
SD Card Copier.....	9
SDHC card.....	9
Shutdown.....	16
Sidetone Fre.....	25

Sidetone Level.....	25
Slow.....	41
SNB.....	40
Software Setup.....	11
Spectral Noise Blanker.....	40
standard software such as PowerSDR.....	6
Subnet.....	13
sudo apt-get.....	9
tar.....	9
Touch Screen.....	45
Transceiver interfaces.....	12
Transmit out of band.....	24
TRRS connector.....	51
TUN - TUNE.....	7
Tune - configure an OC.....	26
Tune Drive Slider.....	33
TUNE/SWR/FWD power.....	48
Tuning.....	45
USB Sound Card.....	19
VFO Encoder.....	45
VFO Encoder Divisor.....	17
VFO Lock.....	42
VFO Step.....	43
Waterfall Automatic.....	21
Waterfall Automatic – When enabled the Waterfall High and Waterfall Low are adjusted automatically.....	21
Waterfall High.....	21
Waterfall Low.....	21
Weight.....	25
wget.....	9
– When enabled the Waterfall High and Waterfall Low are adjusted automatically.....	21
“git clone https://github.com/g0orx/pihpsdr pihpsdr.src.....	9
“git clone https://github.com/g0orx/wdsp” .....	9

