



CP-WX5506M

3LCD projector installation, wireless, 5400 ANSI lumens,
10000:1 contrast ratio, WXGA (1280 x 800) resolution

HITACHI
Inspire the Next

Technical Specifications



- a:** Projection distance
b: Lens centre to the higher edge of the screen
c: Lens centre to the lower edge of the screen

IMAGE SIZE 16:10 (FROM PROJECTOR'S LENS END)

Screen size (diagonal)	Projection distance (a)		Screen height (cm)	
	Wide (m)	Tele (m)	b (top)	c (bottom)
30" (0.8 m)	0.9	1.4	0	40
50" (1.3 m)	1.5	2.4	0	67
100" (2.5 m)	3.0	4.9	0	135
150" (3.8 m)	4.6	7.4	0	202
200" (5.1 m)	6.1	9.9	0	269
250" (6.3 m)	7.6	12.3	0	337
300" (7.6 m)	9.2	14.8	0	404

IMAGE SIZE 16:10 (FROM PROJECTOR'S LENS END)

Screen size (diagonal)	Projection distance (a)		Screen height (cm)	
	Wide (m)	Tele (m)	b (top)	c (bottom)
30" (0.8 m)	0.9	1.5	-2	39
50" (1.3 m)	1.5	2.5	-3	66
100" (2.5 m)	3.1	5.0	-7	131
150" (3.8 m)	4.7	7.6	-10	197
200" (5.1 m)	6.3	10.1	-14	263
250" (6.3 m)	7.8	12.7	-17	329
300" (7.6 m)	9.4	15.2	-21	394

ITEM	SPECIFICATIONS
Standard	IEEE802.11 a/b/g/n/ac
Frequency	2.4GHz/5GHz (only non-DFS band)
Connection	SoftAP, WiFi Direct, STA (infrastructure)
Security	WPA2-PSK(TKIP/AES), WPA-PSK(TKIP/AES), WEP(128/64bit)
RF Regulatory	<ul style="list-style-type: none"> Support Regulatory : CE, FCC, IC, SRRC, MIC(JPN) Other : Dealer Option

OPTICAL

Panel Size	16mm (0.63 inches)
Panel Structure	3LCD, 16:10 Aspect Ratio
Resolution	WXGA (1280 x 800)
Light Output (Brightness) ANSI Lumens	5400 (Normal), 3618 (Eco)
Contrast Ratio	10000:1
Lamp Life (Hours)	4000 (Normal), 6000 (Eco)
Lens	Built-in
Lens Zoom	Manual Zoom x 1.6
Lens Focus	Manual Focus
Lens Shift	Manual
Projection Lens F Number	f = 1.65 ~ 2.15
Throw Distance	0.8m ~ 13.6m
Distance to Width Ratio/ Throw Ratio (-1)	1.3 (Wide), 2.1 (Tele)
Display Size Diagonal	30 ~ 300 inches

FEATURES

Speakers	16W Mono
Digital Keystone Correction (Degrees)	Horizontal ± 30 degrees, Vertical ± 30 degrees
Picture Modes	Standard, Natural, Cinema, Dynamic, Board (Black), Board (Green), Whiteboard, Daytime, DICOm Sim
Picture Adjustments	Eco Mode (Normal, Eco), Equalizing Color temperature Adjustment, Equalizing Digital Gamma Correction, Magnify 4 times (WXGA) by RS232C/Remote control, Mirror Reverse Image, Up-side Down Image

Operating Features

Network	AMX Device Discovery, Command Control via the Network, Configuring and Controlling the Projector via a Web Browser, Controlling the Projector via Scheduling, Crestron RoomView® (Not accessible through the wireless adapter), Displaying text data transferred via network, Extron XTP system, Failure and Warning Alerts via E-mail, My Image (still image transfer) Display, Network Bridge, PJLink TM, Projector Management via SNMP, Multimedia Function, Support USB-WL-5G (Not support USB-WL-11n) (*This projector does not support Bluetooth), Simple Access Point (SAP) mode / Infrastructure mode, Miracast, Web control, 4 screens can be displayed simultaneously (still image), Moderator mode, LiveViewer Pro (Not support conventional LiveViewer), Mirroring (Win / MacOSX), Streaming Video (Supported Format: MP4, MOV), Streaming Audio (Supported Format: MP3, AAC), Dual IP, MAC Address filtering (with SAP mode)
Security	PIN Security Lock, MyScreen Password Lock, Transition Detector, MyText Password Lock, Key Lock (Key pad, Remote Control)

CONNECTIONS

Digital Input	HDMI x 2, HDBaseT x 1
Analogue Input	15 pin Mini D-Sub x 2, RCA Jack x 1
Video Output	15 pin Mini D-Sub x 1, HDMI x 1 (Supporting HDCP decoding)
Audio Input	3.5mm Stereo Mini Jack x1, RCA Jack (L/R) x 1
Audio Output	3.5mm Stereo Mini Jack x 1
RS-232C Control	1 x 9-pin D-Sub
Wireless LAN	Yes (included)
Wired LAN	Yes
USB Type-A	USB type A x 1 for wireless adapter
USB Type-B	Mini USB type B x 1 for service

POWER

Power Supply	AC 100 ~ 120V / AC 220 ~ 240V (50/60Hz)
Power Consumption Operating / Standby	470W / Less than 0.5W

PHYSICAL

Weight	6.8kg
Dimensions (W x H x D)	460 x 138 x 334mm
Noise	38dB (Normal), 29dB (Eco)

ACCESSORIES

Supplied Accessories	Remote Control with Batteries, USB Wireless Adapter (USB-WL-5G), Power Cord, Computer Cable, Lens Cover, Adapter Cover, Terminal Cover, Application CD, User's Manual (Book, CD-ROM), Security Label, Hook Metal, Screw, Cable Tie, HDMI Cable Holder
Remote Control	HL03037
Replacement Lamp / Filter	DT01931, UX41161
Projector / Lamp Warranty	3 years / 6 months (for education and extended warranties please contact your local dealer)

