Energy Demand Forecasting & RL Load Scheduling

Buenafe, Ashley Dyriel V.
Holy Angel University
Tarlac City, Tarlac
+63 917 811 4366
ashleydyrielbuenafe@gmail.com

Lobo, Rendel Gion B.
Holy Angel University
Angeles City, Pampanga
+63 976 290 2804
schoolgeun2@gmail.com

Sison, Anoucshka Ysabeli A.
Holy Angel University
San Fernando City, Pampanga
+ 925 781 6178
anoucshkaysabelisison04@gmail.com

1. INTRODUCTION

Electric power demand fluctuates throughout the day due to various factors such as human activities, weather conditions, and seasonal patterns. For example, electricity usage typically increases in the morning when people start their daily routines and again in the evening when households use appliances, lighting, and cooling systems. These fluctuations often create peak demand periods where electricity generation becomes more expensive and less efficient for energy providers.

Managing these demand variations is an important challenge for modern energy systems. During peak demand periods, power providers may need to activate additional generation resources, which increase operational costs and can reduce energy efficiency. One potential solution is to predict future electricity demand and adjust certain energy loads accordingly by shifting consumption to lower-demand periods.

This project aims to develop an artificial intelligence-based system that predicts short-term electricity demand and schedules flexible energy loads to reduce proxy operational costs. The system combines time-series forecasting techniques with reinforcement learning to support intelligent scheduling decisions.

A forecasting model analyzes historical electricity consumption data to estimate future demand levels. These predictions are then used by a reinforcement learning agent that learns scheduling strategies for flexible energy loads. The agent receives rewards based on cost reduction and learns to shift energy usage away from peak periods whenever possible.

By combining forecasting and decision-making methods, this project demonstrates how artificial intelligence can contribute to smarter energy management and more efficient energy consumption strategies.

2. PROBLEM STATEMENT

Electricity demand varies significantly over time due to factors such as human activity patterns, weather conditions, and seasonal changes. These variations often lead to periods of peak demand, during which electricity generation and distribution become more expensive and less efficient. When demand rises rapidly, power providers may need to activate additional energy resources, increasing operational costs and reducing overall energy efficiency.

Accurate demand forecasting plays a crucial role in addressing this challenge. By predicting future electricity consumption patterns, energy systems can make more informed decisions about how and when energy should be used. However, forecasting alone is not sufficient. To fully benefit from demand prediction, intelligent strategies are needed to adjust energy usage in response to predicted demand levels.

This project addresses the problem of improving energy usage efficiency by combining demand forecasting with automated load scheduling. The proposed system uses a deep learning model to predict short-term electricity demand based on historical consumption data. These predictions are then used by a reinforcement learning agent that learns how to schedule flexible energy loads in a way that reduces proxy energy costs. By integrating forecasting and decision-making techniques, the system aims to demonstrate how artificial intelligence can support smarter and more efficient energy management.

3. PROJECT SCOPE

The scope of this project focuses on the development and evaluation of a simulated artificial intelligence system for electricity demand forecasting and load scheduling. The system will analyze historical electricity consumption data and predict short-term demand using machine learning techniques.

The project includes the implementation of several components. A deep learning forecasting model based on Long Short-Term Memory (LSTM) networks will be used to predict electricity demand. A Temporal Convolutional Network (TCN) will also be implemented as an alternative forecasting approach to allow comparison between convolutional and recurrent models. In addition, a lightweight natural language processing (NLP) module will be included to demonstrate the integration of text-based information using a simple text classification model.

The system also incorporates a reinforcement learning component that teaches how to schedule flexible energy loads based on predicted demand levels. The scheduling decisions are evaluated in a simulated environment where actions are rewarded based on their ability to reduce proxy energy costs.

The project uses publicly available electricity consumption data from the UCI Individual Household Electric Power Consumption dataset. The data will be preprocessed and aggregated into hourly intervals for model training. The system will be developed and evaluated within a simulated environment and will not interact with real power grid infrastructure.

4. SUCCESS METRICS AND CONSTRAINTS

4.1 Success Metrics

The performance of the proposed system will be evaluated using both forecasting and reinforcement learning metrics.

For the electricity demand forecasting models, prediction accuracy will be measured using Mean Absolute Error (MAE) and Mean Absolute Percentage Error (MAPE). These metrics evaluate how closely the predicted demand values match the actual electricity consumption values in the dataset.

The reinforcement learning scheduling component will be evaluated using reward-based performance measures. The RL agent receives rewards based on the reduction of proxy energy costs achieved by shifting flexible loads away from predicted peak demand periods. The performance of the RL agent will be compared with baseline scheduling strategies, such as immediate scheduling or simple rule-based policies.

Together, these evaluation metrics allow the project to assess both the accuracy of demand forecasting and the effectiveness of load scheduling decisions.

4.2 Constraints

Several constraints influence the design and implementation of the system.

First, the project relies on publicly available electricity consumption data, which represents a single household. While the dataset provides detailed time-series measurements, it may not fully represent broader energy consumption patterns across different households or regions.

Second, the system must operate within practical computational limits suitable for a standard development environment. This constraint affects model complexity, training time, and dataset preprocessing decisions, such as aggregating minute-level data into hourly intervals.

Third, the reinforcement learning component operates in a simulated environment rather than a real energy management system. As a result, the scheduling results demonstrate the feasibility of the approach rather than real-world deployment.

Despite these constraints, the project aims to provide a meaningful demonstration of how machine learning and reinforcement learning techniques can be combined to support demand-aware energy management.

5. RELATED WORK

Energy demand forecasting is an essential component of modern energy management systems, particularly in smart grid environments where electricity consumption varies significantly over time. Accurate forecasting enables energy providers and grid operators to anticipate demand fluctuations and allocate energy resources efficiently. With the increasing availability of smart meter data and large-scale electricity consumption datasets, data-driven forecasting methods have become increasingly important for predicting energy demand patterns. Recent studies emphasize that advanced machine learning and deep learning techniques have significantly improved forecasting accuracy compared to traditional statistical methods in smart grid applications (Aguiar-Pérez & Pérez-Juárez, 2023; Kiasari et al., 2024).

Deep learning models have become widely used for time-series forecasting tasks because of their ability to capture nonlinear relationships and temporal dependencies in sequential data. Among these models, Long Short-Term Memory (LSTM) networks are commonly applied in electricity demand prediction due to their capability to retain long-term dependencies in time-series datasets. LSTM architectures utilize memory cells and gating mechanisms that allow the model to store relevant information over extended sequences of data. Semmelmann et al. (2022) demonstrated that LSTM-based forecasting models can effectively predict short-term electricity demand using smart meter datasets, outperforming traditional machine learning approaches. Similarly, Zhang et al. (2023) proposed a hybrid deep learning model combining convolutional neural networks and bidirectional LSTM networks for real-time load forecasting, achieving improved forecasting accuracy in smart grid environments. These findings indicate that LSTM models are well-suited for modeling complex energy consumption behaviors and forecasting electricity demand.

In addition to recurrent neural network models, convolution-based architectures have also been explored for time-series forecasting. Temporal Convolutional Networks (TCNs) provide an alternative approach for sequence modeling by utilizing causal and dilated convolution layers to capture long-range temporal dependencies. Unlike recurrent models, convolution-based architectures allow parallel computation and often exhibit more stable training behavior. Wang (2023) proposed a hybrid forecasting model integrating Temporal Convolutional Networks with bidirectional recurrent networks and attention mechanisms to improve energy prediction performance in smart grid systems. The results demonstrated that TCN-based architectures are capable of capturing complex temporal patterns in electricity demand data while maintaining efficient model training.

While deep learning models provide accurate demand predictions, forecasting alone is insufficient for optimizing energy management decisions. Intelligent scheduling mechanisms are required to determine how electricity loads should be distributed over time in order to improve operational efficiency and reduce energy costs. Reinforcement learning has emerged as a promising approach for solving sequential decision-making problems in energy management systems. Reinforcement learning algorithms enable an agent to interact with an environment and learn optimal actions based on feedback in the form of rewards. In smart grid applications, RL agents can learn scheduling strategies that shift electricity loads across time periods in order to reduce costs or balance system demand (Cheng et al., 2023; Liu et al., 2023).

Recent research has also explored the integration of forecasting models with reinforcement learning frameworks to create intelligent energy management systems. In these systems, forecasting models first estimate future electricity demand based on historical data, while reinforcement learning agents use these predictions to determine optimal control or scheduling actions. Li et al. (2025) proposed a hybrid approach combining deep learning-based load forecasting with reinforcement learning to optimize energy management decisions in smart grids. Similarly, Wang (2025) demonstrated that integrating deep learning forecasting models with reinforcement learning-based dispatch strategies can significantly improve dynamic load scheduling and system efficiency. These hybrid forecasting and decision-making frameworks allow energy management systems to anticipate demand fluctuations and adjust scheduling strategies accordingly.

Evaluating the performance of forecasting models and scheduling algorithms is also an important aspect of energy management research. Forecasting accuracy is commonly measured using statistical metrics such as Mean Absolute Error (MAE) and Mean Absolute Percentage Error (MAPE), which quantify the difference between predicted and actual electricity demand values. These metrics are widely used in energy forecasting studies because they provide clear indicators of prediction accuracy and model reliability. In reinforcement learning-based energy management systems, the effectiveness of scheduling policies is typically evaluated by comparing the cumulative rewards achieved by the RL agent against baseline policies or rule-based scheduling strategies. This approach allows researchers to determine whether reinforcement learning algorithms can achieve better performance in terms of cost reduction and energy efficiency.

Overall, the reviewed literature demonstrates that recent advancements in deep learning-based forecasting and reinforcement learning optimization have significantly improved the capabilities of smart grid energy management systems. Deep learning models such as LSTM and TCN architectures provide accurate time-series demand forecasts, while reinforcement learning algorithms enable adaptive load scheduling strategies that optimize system performance. The integration of forecasting models with reinforcement learning agents provides a promising approach for developing intelligent energy management systems capable of predicting electricity demand and dynamically scheduling energy loads to reduce operational costs.

6. DATASET PLAN

This project uses the *Individual Household Electric Power Consumption dataset* from the UCI Machine Learning Repository. The dataset contains electricity consumption measurements collected from a household in Sceaux, France over a period of approximately four years, from December 2006 to November 2010.

The dataset includes more than two million observations recorded at one-minute intervals. Each record contains electrical measurements such as global active power, voltage, current intensity, and three sub-metering values corresponding to different groups of household appliances. These variables provide detailed information about electricity usage patterns over time.

To make the dataset more suitable for model training and reduce computational complexity, the raw data will be aggregated into hourly intervals. This resampling process reduces the dataset size while preserving overall demand trends.

The dataset contains a small percentage of missing values. These missing entries will be handled during preprocessing using techniques such as forward filling or interpolation.

The dataset is distributed under the Creative Commons Attribution 4.0 (CC BY 4.0) license, which allows reuse and adaptation for research purposes if proper attribution is provided.

Although the dataset represents electricity consumption from a single household, it provides sufficient temporal variability to evaluate forecasting models and reinforcement learning scheduling strategies. The sub-metering measurements also allow the simulation of flexible loads that can be scheduled at different times.

7. SYSTEM DESIGN AND METHODOLOGY

The proposed system consists of multiple components that work together to forecast electricity demand and optimize load scheduling.

7.1 Time-Series Forecasting Model

The primary forecasting model is based on a Long Short-Term Memory (LSTM) neural network. The model is trained using historical electricity consumption data and learns temporal patterns that influence demand. Input features include previous demand values and time-related variables such as hour of day and day of week. The model outputs predicted electricity demand for the next time interval. In addition to the deep learning forecasting model, a simple tabular baseline model such as linear regression will be implemented to provide a performance comparison.

7.2 CNN Component

A Temporal Convolutional Network (TCN) will be implemented as an alternative forecasting approach. TCN models use one-dimensional convolution layers to process time-series data and capture temporal dependencies. This component allows comparison between convolutional and recurrent architectures for energy demand forecasting.

7.3 NLP Component

A lightweight natural language processing module will be included to demonstrate the integration of text-based information into the system. The NLP component will classify short energy-related text snippets into categories such as increased demand, decreased demand, or neutral conditions. This component will use a simple TF-IDF representation combined with a logistic regression classifier.

7.4 Reinforcement Learning Scheduling

A reinforcement learning agent will be implemented to determine how flexible energy loads should be scheduled. The RL environment includes states representing the predicted demand level and time of day. The agent chooses actions such as scheduling a load immediately or delaying it to a later time. The reward function is designed to encourage actions that reduce energy costs by shifting consumption away from peak demand periods.

7.5 Evaluation Metrics

The system will be evaluated using both forecasting and reinforcement learning metrics. Forecasting performance will be measured using Mean Absolute Error (MAE) and Mean Absolute Percentage Error (MAPE). Reinforcement learning performance will be evaluated based on average reward values and cost reduction compared to baseline scheduling policies.

8. ETHICS RISK REGISTER

One potential risk involves equity concerns. Automated load scheduling systems could potentially affect users differently depending on their energy usage patterns. To mitigate this issue, the system design assumes that only flexible loads can be scheduled, while essential energy usage remains unaffected.

Another concern relates to user autonomy. Fully automated systems could reduce user control over energy consumption decisions. To address this risk, the system concept includes the possibility of manual overrides or opt-out mechanisms that allow users to retain control over their energy usage.

A third risk involves dataset bias and representativeness. The dataset used in this project represents a single household, which may not fully reflect broader energy consumption patterns. This limitation will be clearly documented, and results will be interpreted accordingly.

9. TEAM ROLES AND MILESTONES

The Project Lead and Integration Lead are responsible for coordinating the project timeline, managing system integration, and ensuring that all components work together properly.

The Data and Modeling Lead is responsible for dataset acquisition, preprocessing, and implementing the forecasting models including LSTM and CNN-based approaches.

The Evaluation and Ethics Lead is responsible for implementing evaluation metrics, managing reinforcement learning experiments, maintaining reproducibility through environment configuration files, and ensuring ethical considerations are properly addressed.

The project development will follow a milestone-based schedule that includes dataset preparation, model development, reinforcement learning implementation, evaluation, and final documentation.

REFERENCES

[1] Aguiar-Pérez, J.M. and Pérez-Juárez, M.Á. 2023. An insight of deep learning-based demand forecasting in smart grids. Sensors. 23, 3 (2023), 1467. https://doi.org/10.3390/s23031467

[1] Cheng, Y., Zhang, J., Jiang, W., Wang, L. and Zhang, H. 2023. Reinforcement learning and stochastic optimization with deep learning-based forecasting on power grid scheduling. Processes. 11, 11 (2023), 3188. https://doi.org/10.3390/pr11113188

[2] Kiasari, M., Ghaffari, M. and Aly, H.H. 2024. A comprehensive review of the current status of smart grid technologies for renewable energy integration and future trends. Energies. 17, 16 (2024), 4128. https://doi.org/10.3390/en17164128

[3] Liu, D., Cheng, P., Liu, J., et al. 2023. Improved reinforcement learning-based real-time energy scheduling for prosumer with elastic loads in smart grid. Knowledge-Based Systems. 280 (2023), 111004. https://doi.org/10.1016/j.knosys.2023.111004

[4] Li, X., Zhang, Y., Chen, H. and Liu, J. 2025. Power load forecasting using deep learning and reinforcement learning. Information Sciences. 720 (2025), 122523. https://doi.org/10.1016/j.ins.2025.122523

[5] Semmelmann, L., Henni, S. and Weinhardt, C. 2022. Load forecasting for energy communities: A novel LSTM-XGBoost hybrid model based on smart meter data. Energy Informatics. 5, 24 (2022). https://doi.org/10.1186/s42162-022-00212-9

[6] Wang, R. 2023. Enhancing energy efficiency with smart grid technology: A fusion of TCN, BiGRU, and attention mechanism. Frontiers in Energy Research. 11 (2023), 1283026. https://doi.org/10.3389/fenrg.2023.1283026

[7] Wang, Z. 2025. Research on deep learning-based dynamic load forecasting and optimal dispatch in smart grids. Journal of Electronic Research and Application. 9, 2 (2025). https://doi.org/10.26689/jera.v9i2.10083

[8] Wen, X., Liao, J., Niu, Q., Shen, N. and Bao, Y. 2024. Deep learning-driven hybrid model for short-term load forecasting and smart grid information management. Scientific Reports. 14 (2024), 13720. https://doi.org/10.1038/s41598-024-63262-x

[9] Zhang, D., Jin, X., Shi, P. and Chew, X. 2023. Real-time load forecasting model for the smart grid using Bayesian optimized CNN-BiLSTM. Frontiers in Energy Research. 11 (2023), 1193662. https://doi.org/10.3389/fenrg.2023.1193662