

Schema

title: OpenC2 Language Objects
module: oasis-open.org/openc2/v1.0/openc2-lang
patch: wd07
description: Datatypes that define the content of OpenC2 commands and responses.
exports: OpenC2-Command, OpenC2-Response
imports: slpf: oasis-open.org/openc2/v1.0/ap-slpf
jadn: oasis-open.org/openc2/v1.0/jadn

Types

OpenC2-Command (Record)

ID	Name	Type	#	Description
1	action	Action	1	The task or activity to be performed (i.e., the 'verb')
2	target	Target	1	The object of the action. The action is performed on the target
3	actuator	Actuator	0..1	The subject of the action. The actuator executes the action on the target
4	args	Args	0..1	Additional information that applies to the command
5	id	Command-ID	0..1	Identifier used to link responses to a command

Action (Enumerated)

ID	Name	Description
1	scan	Systematic examination of some aspect of the entity or its environment in order to obtain information.
2	locate	Find an object physically, logically, functionally, or by organization.
3	query	Initiate a request for information.
6	deny	Prevent a certain event or action from completion, such as preventing a flow from reaching a destination or preventing access.
7	contain	Isolate a file, process, or entity so that it cannot modify or access assets or processes.
8	allow	Permit access to or execution of a target.
9	start	Initiate a process, application, system, or activity.
10	stop	Halt a system or end an activity.
11	restart	Stop then start a system or activity.
14	cancel	Invalidate a previously issued action.
15	set	Change a value, configuration, or state of a managed entity.
16	update	Instruct a component to retrieve, install, process, and operate in accordance with a software update, reconfiguration, or other update.
18	redirect	Change the flow of traffic to a destination other than its original destination.
19	create	Add a new entity of a known type (e.g., data, files, directories).
20	delete	Remove an entity (e.g., data, files, flows).
22	detonate	Execute and observe the behavior of a target (e.g., file, hyperlink) in an isolated environment.
23	restore	Return a system to a previously known state.
28	copy	Duplicate a file or data flow.
30	investigate	Task the recipient to aggregate and report information as it pertains to a security event or incident.
32	remediate	Task the recipient to eliminate a vulnerability or attack point.

Target (Choice)

ID	Name	Type	Description
1	artifact	Artifact	An array of bytes representing a file-like object or a link to that object.
2	command	Command-ID	A reference to a previously issued OpenC2 command
3	device	Device	The properties of a hardware device
4	directory	Directory	The properties common to a file system directory
7	domain_name	Domain-Name	A network domain name
8	email_addr	Email-Addr	A single email address
9	email_message	Email-Message	An instance of an email message, corresponding to the internet message format described in RFC 5322 and related RFCs
10	file	File	Properties of a file
11	ip_addr	IP-Addr	The representation of one or more IP addresses (either version 4 or version 6) expressed using CIDR notation
13	mac_addr	Mac-Addr	A single Media Access Control (MAC) address
15	ip_connection	IP-Connection	A network connection that originates from a source and is addressed to a destination

16	openc2	OpenC2	A set of items used with the query action to determine an actuator's capabilities
17	process	Process	Common properties of an instance of a computer program as executed on an operating system
18	software	Software	High-level properties associated with software, including software products
23	windows_registry_key	Windows-Registry-Key	The properties of a Windows registry key
25	property	Property	Data attribute associated with an actuator.
1024	slpf	slpf:Target	Targets defined in the Stateless Packet Filter profile.

Actuator (Choice)

ID	Name	Type	Description
1	generic	Actuator-Specifiers	Generic actuator specifiers
1024	slpf	slpf:Specifiers	Actuator specifiers and options as defined in the Stateless Packet Filter profile, oasis-open.org/openc2/oc2ap-slpf/v1.0/csd01

Args (Map)

ID	Name	Type	#	Description
1	start_time	Date-Time	0..1	The specific date/time to initiate the action
2	stop_time	Date-Time	0..1	The specific date/time to terminate the action
3	duration	Duration	0..1	The length of time for an action to be in effect
4	response_requested	Response-Type	0..1	The type of response required for the action
1024	slpf	slpf:Args	0..1	Command arguments defined in the Stateless Packet Filter profile

OpenC2-Response (Record)

ID	Name	Type	#	Description
1	id	Command-ID	0..1	Id of the response
2	status	Status-Code	1	An integer status code
3	status_text	String	0..1	A free-form human-readable description of the response status
4	*	Results	1	Data or extended status information that was requested from an OpenC2 command
5	id_ref	Command-ID	1	Id of the command that induced this response.

Status-Code (Enumerated.ID)

ID	Description
102	Processing -- An interim response used to inform the client that the server has accepted the request but not yet completed it.
200	OK -- The request has succeeded.
301	Moved Permanently -- The target resource has been assigned a new permanent URI
400	Bad Request -- The server cannot process the request due to something that is perceived to be a client error (e.g., malformed request syntax.)
401	Unauthorized -- The request lacks valid authentication credentials for the target resources or authorization has been refused for the submitted credentials.
403	Forbidden -- The server understood the request but refuses to authorize it.
500	Server Error -- The server encountered an unexpected condition that prevented it from fulfilling the request.
501	Not Implemented -- The server does not support the functionality required to fulfill the request.

Artifact (Record)

ID	Name	Type	#	Description
1	mime_type	String	0..1	Permitted values specified in the IANA Media Types registry
2	*	Payload	0..1	choice of literal content or URL to obtain content
3	hashes	Hashes	0..1	Specifies a dictionary of hashes for the contents of the payload

Device (Map)

ID	Name	Type	#	Description
1	hostname	Hostname	1	A hostname that can be used to connect to this device over a network
2	description	String	0..1	A human-readable description of the purpose, relevance, and/or properties of the device
3	device_id	String	0..1	An identifier that refers to this device within an inventory or management system

Domain-Name

Name	Type	Description
Domain-Name	String (hostname)	Domain name, RFC 1034, section 3.5

Email-Addr

Name	Type	Description
Email-Addr	String (email)	Email address, RFC 5322, section 3.4.1

File (Map)

ID	Name	Type	#	Description
1	name	String	0..1	The name of the file as defined in the file system
2	path	String	0..1	The absolute path to the location of the file in the file system
3	hashes	Hashes	0..1	One or more cryptographic hash codes of the file contents

IP-Addr

Name	Type	Description
IP-Addr	String (ip)	IPv4 or IPv6 address per RFC 2673 section 3.2, and RFC 4291 section 2.2

IP-Connection (Record)

ID	Name	Type	#	Description
1	src_addr	IP-Addr	0..1	source address
2	src_port	Port	0..1	source TCP/UDP port number
3	dst_addr	IP-Addr	0..1	destination address
4	dst_port	Port	0..1	destination TCP/UDP port number
5	layer4-protocol	L4-Protocol	0..1	Protocol (IPv4) / Next Header (IPv6)

OpenC2

Name	Type	Description
OpenC2	ArrayOf(Query-Item) ['max', 'min']	A target used to query Actuator for its supported capabilities

Process (Map)

ID	Name	Type	#	Description
1	pid	Integer	0..1	Process ID of the process
2	name	String	0..1	Name of the process
3	cwd	String	0..1	Current working directory of the process
4	executable	File	0..1	Executable that was executed to start the process
5	parent	Process	0..1	Process that spawned this one
6	command_line	String	0..1	The full command line invocation used to start this process, including all arguments

Property (Record)

ID	Name	Type	#	Description
1	name	String	0..1	The name that uniquely identifies a property of an actuator.
2	query_string	String	0..1	A query string that identifies a single property of an actuator. The syntax of the query string is defined in the actuator profile.

Command-ID

Name	Type	Description
Command-ID	String	Uniquely identifies a particular command – TBD syntax

Hashes (Map)

ID	Name	Type	#	Description
1	md5	String	0..1	Hex-encoded MD5 hash as defined in RFC3121
4	sha1	String	0..1	Hex-encoded SHA1 hash as defined in RFC3174
6	sha256	String	0..1	Hex-encoded SHA256 as defined in RFC6234

Hostname

Name	Type	Description
Hostname	String	A legal Internet host name as specified in RFC 1123

Identifier

Name	Type	Description
Identifier	String	command--UUIDv4 – An identifier universally and uniquely identifies an OpenC2 command. Value SHOULD be a UUID generated according to RFC 4122.

L4-Protocol (Enumerated)

ID	Name	Description
1	icmp	Internet Control Message Protocol – RFC 792
6	tcp	Transmission Control Protocol – RFC 793
17	udp	User Datagram Protocol – RFC 768
132	sctp	Stream Control Transmission Protocol – RFC 4960

Payload (Choice)

ID	Name	Type	Description
1	payload_bin	Binary	Specifies the data contained in the artifact.
2	url	URI	MUST be a valid URL that resolves to the un-encoded content

Port

Name	Type	Description
Port	String (port)	Service Name or Transport Protocol Port Number, RFC 6335

Query-Item (Enumerated)

ID	Name	Description
1	versions	OpenC2 language versions supported by this actuator
2	profiles	List of profiles supported by this actuator
3	schema	Definition of the command syntax supported by this actuator
4	pairs	List of supported actions and applicable targets

Response-Type (Enumerated)

ID	Name	Description
0	none	No response
1	ack	Respond when command received
2	complete	Respond when all aspects of command completed

Version

Name	Type	Description
Version	String	TBSL

Results (Map)

ID	Name	Type	#	Description
1	strings	String	0..n	Generic set of string values
2	ints	Integer	0..n	Generic set of integer values
3	kvs	KVP	0..n	Generic set of string values
4	versions	Version	0..n	Supported OpenC2 Language versions
5	profiles	jadn:Uname	0..n	Supported actuator profiles
6	schema	jadn:Schema	0..n	Schema supported by this actuator
7	actions	ActionTargets	0..n	List of targets applicable to each supported action
1024	slpf	slpf:Results	0..n	Results from Stateless Packet Filter profile

KVP (Array)

ID	Type	#	Description
1	Identifier	1	key -- name of this item
2	String	1	value -- string value of this item

ActionTargets (Array)

ID	Type	#	Description
1	Action	1	action -- An action supported by this actuator
2	Target.*	1..n	targets -- List of targets applicable to this action
