

AD Circus™ SLIX SLIX 2

Overview

Frequency Band

HF 13.56 MHz

Chip

NXP ICODE SLIX 2

Antenna Dimensions

Ø 18 mm / 0.71 in

International Standard

ISO 15693

Industry Segments

Industrial Applications

Applications

Product Authentication
Pharmaceutical and Healthcare
NFC

RoHS

EU Directive 2011/65/EU and
2015/863 Compliant

REACH

Regulation (EC) No 1907/2006



Smallest round HF inlay with best-in-class performance

Our AD Circus™ Slix and Slix 2 inlays and tags provide superior readability and best-in-class performance for item-level product authentication, pharmaceutical and brand protection applications. As the smallest available round HF inlay, Circus™ inlays and tags are ideal wherever small size and top performance are essential.

AD Circus™ Slix and Slix 2 are tiny and cost-effective inlay with best-in-class performance. The inlay comes with NXP ICODE SLIX provides 896-bit of user memory, while NXP ICODE SLIX2 boasts an extended user memory of 2,528-bit.

Our inlays and tags are compliant with ISO 9001:2015 Quality Management and ISO 14001:2015 Environmental Management. This ensures a reliable and state-of-the-art product that meets a variety of application needs, where high performance is a critical parameter.

Technical features

Chip	NXP ICODE SLIX	NXP ICODE SLIX	NXP ICODE SLIX 2
EPC and User Memory	896-bit	896-bit	2500-bit
Product Code	3003285 / IL-602803	3003286 / IL-610376	3006370 / IL-603074
Delivery Format	Wet inlay +	Label	Wet inlay +
Die-Cut Dimension	Ø 21 mm / 0.827 in	Ø 21 mm / 0.827 in	Ø 21 mm / 0.827 in
Inlay Substrate	PET	PET	PET
Face Sheet	Clear PET	White PET 50	Clear PET
Total Thickness	141 µm	172 µm	141 µm
Standard Pitch	27 mm / 1.063 in	27 mm / 1.063 in	27 mm / 1.063 in
Web Width	26 mm / 1.02 in	26 mm / 1.02 in	26 mm / 1.02 in
Core Size	76 mm / 3 in	76 mm / 3 in	76 mm / 3 in
Quantity / Reel	5000 pcs/reel 10000 pcs/box	5000 pcs/reel 10000 pcs/box	5000 pcs/reel 10000 pcs/box
Operating Temperature	-40 °C to 85 °C / -40 °F to 185 °F		

Contact information

rfid.averydennison.com/contact
+1-678-617-2359

Connect with us on:



© 2023 Avery Dennison Corp. All rights reserved. 170 Monarch Lane, Miamisburg, OH 45342, USA Third party trademarks and/or trade names used herein are the property of their respective owner(s). Some of the trademarks appear for identification purposes only.

Warranty: Please refer to Avery Dennison standard terms and conditions: rfid.averydennison.com/termsandconditions

Care and handling: RFID inlays are sensitive to ESD. Observe standard industry practices relating to electronics / RFID to keep environmental impact and static charge to a minimum.

Applications: This product should be tested by the customer / user thoroughly under end use conditions to ensure the product meets the particular requirements. Avery Dennison does not represent that this product is fit for any particular purpose or use. Avery Dennison reserves the right to modify, change, supplement or discontinue product offerings at any time without notice. The information contained herein is believed to be reliable but Avery Dennison makes no representation concerning the accuracy or correctness of the data.