NFL Players Analytics

Final Project Report

John Zhao · Ishaan Parikh · Victor Prosekov

techzjc@vt.edu · iparikh4@vt.edu · vprosekov@vt.edu

CS5614 Database Management Systems

Dr. Nizamani

Fall 2026

November 11, 2026

Table of Contents

1. Introduction to the Mini-verse.....3
1.1 Background.....3
1.2 Motivation.....3
1.3 Overview of the System.....3
2. User Support.....4
2.1 User Roles and Entities.....4
2.2 Authentication (Login System).....4
2.3 Security Measures.....11
3. Database Connection & Setup.....13
3.1 System Connection.....13
3.2 Setup Instructions.....14
3.3 Database Initialization.....14
3.4 Challenges & Lessons Learned.....15
4. System Design & Functionality.....16
4.1 Schema Design.....16
4.2 ER Diagram.....17
4.3 Tables & Keys.....22
4.4 Sample Data and Application Queries.....32
5. Reporting.....44
5.1 Team Season Comparison.....44
5.2 Player Season Comparison.....46
6. GUI / Interface.....47
6.1 CRUD Operations.....49
7. Reflection.....53
7.1 Individual Contributions.....53
7.2 Team Reflection.....54
8. Appendix.....55
8.1 Repository and Deliverables.....55
8.2 Evidence Method and Submission Notes.....55
8.3 Initial ER Diagram.....56
8.4 Review and Verification.....57

1. Introduction to the Mini-verse

1.1 Background

Sports analysis depends on relationships among leagues, seasons, teams, players, games, and recorded statistics. A score alone cannot explain who participated, which roster applied at the time, or how the result contributes to a season. NFL Players Analytics models those relationships in a relational database and presents them through a browser application. Although the project name refers to the NFL, the demonstration uses one fictional football league and synthetic people; it is not an official NFL data source.

1.2 Motivation

The project supports two main tasks: helping fans discover and compare teams or players, and helping an administrator maintain consistent sports records. Fans can follow teams using account-owned favorites, filter historical rosters, and compare recorded season statistics. Administrators can create users and maintain the shared dataset through forms with named selections, validation, and confirmations. These tasks make database design visible in everyday interactions without requiring users to know SQL or table identifiers.

1.3 Overview of the System

This CS5614 prototype combines a React TypeScript interface and Ant Design components with FastAPI, synchronous SQLAlchemy sessions, and SQLite. The final implementation includes role-based accounts, password changes, admin user creation, sports CRUD, a simulated game center, season filters, and two comparison reports. This report explains the 19-table design, setup, security boundaries, and observed application behavior. Evidence was collected on November 11, 2026 in a separate disposable database; the existing development database and the original core schema submission file were preserved.

2. User Support

2.1 User Roles and Entities

Table 1 distinguishes anonymous browsing from authenticated permissions. Fan and analyst currently share the same access level. Each request derives its user and current role from the database-backed session; hiding an admin menu is not the authorization boundary.

Table 1. Roles and allowed tasks

Role	Allowed tasks
Guest	Browse games, teams, players, standings, and comparisons. Favorites stay in that browser.
Fan or analyst	Guest tasks plus account-owned favorite teams and changing their own password.
Admin	Normal-user tasks plus creating users, editing shared sports records, and optional development SQL inspection.

The app_user table holds identity labels and roles. user_credential stores one Argon2 password hash per credentialed account. auth_session stores hashes of expiring opaque tokens; it never stores the cookie token itself. Seeded users are synthetic profile records without credentials. A role named admin in seed data does not provide a usable login.

2.2 Authentication (Login System)

Public signup always creates a fan and does not accept a role. The sign-in form is shared by all roles. Logout removes the current session and clears the cookie. Password change verifies the existing password, writes the new hash and revokes every previous session in one transaction, then issues a new session and CSRF token for the current browser. A conditional credential write coordinates concurrent logins with password changes, so a login cannot issue a session using a revoked hash.

Administrators are created through the local Python setup command, which prompts for a hidden password. Signed-in admins can create fan or analyst accounts through Account menu → Create a user; the API rejects administrator roles. That flow never overwrites an existing email and never switches the administrator into the new account. Figures 1–7 show the user-facing account flows; Table 2 records additional HTTP observations.

Listing 1. Create the first administrator from the repository root

```
uv run --directory backend --frozen python -m scripts.create_admin
```

Account signup

Figure 1 shows the signup form before submission. The password is masked, the form describes normal-user access, and all account details are synthetic. Successful signup opened the signed-in state shown in Figure 3.




Figure 1. Signup form with a masked password before creating Report Fan.

Account login

Figure 2 shows the login form used for the newly created account. The same screen supports administrators; there is no role selector on public login or signup.




Figure 2. Sign-in form with an existing synthetic account and masked password.

Account favorites and logout

Figure 3 shows Report Fan signed in with Alder Bay Foxes saved to the account and the Sign out action available. Figure 4 shows the guest state after sign-out. Guest favorites are separate from the account and are never silently imported.




Figure 3. Signed-in identity, account-owned favorite, and Sign out action.




Figure 4. Guest state after sign-out; favorites are browser-local.

Changing a password

Figure 5 shows the implemented password-change form. It requires the current password and matching new values of 12–128 characters. This is a form capture, not a screenshot of a completed password change; the successful change and session invalidation were verified through the API as summarized in Table 2.




Figure 5. Password-change form for a signed-in normal user.

Administrator user creation

Figure 6 shows the administrator preparing a normal user account. Only fan and analyst roles are offered in this admin flow; administrators are provisioned locally. The initial password is masked and is hashed before storage.




Figure 6. Admin form before creating the synthetic Report Scout account.

Administrator creation result

Figure 7 confirms that Report Scout was created and the administrator remained signed in. The form clears its input after success. A repeated email produces a readable conflict instead of replacing the account.




Figure 7. Successful in-app user creation with the admin session preserved.

2.3 Security Measures

Passwords use Argon2 hashing rather than plaintext or reversible storage. Cookie tokens are random and only their SHA-256 digests are persisted. Cookies are HttpOnly and SameSite=Lax, with a configurable fixed lifetime of 168 hours by default. The local HTTP demo leaves Secure disabled; an HTTPS deployment must enable it. Argon2 and password hashing are consistent with OWASP password-storage guidance [2].

Authenticated writes require a valid session and an X-CSRF-Token header. Account requests also require JSON and reject untrusted browser origins. The server requires admin authorization for shared-data writes and user creation. Favorite ownership comes from the session, never a supplied user ID. Account SQL uses a private engine with logging and request capture disabled, including when sports SQL debugging is enabled.

SQLAlchemy expressions pass values as bound parameters. User input is never concatenated into SQL or accepted as arbitrary SQL through the UI. Database constraints and cross-table validation remain active independently of the optional request guard. This follows the parameterized-query approach described by OWASP [1]. The guard adds signatures for obvious probes, body limits, peer-IP rate limits, and temporary bans; it is not a complete WAF or an installed Fail2ban daemon.

The manual checks in Table 2 were performed against synthetic accounts in the disposable database. They support the listed cases, not an exhaustive security claim. No automated test suite was added.

Table 2. Observed account and security checks

Action	Observed result
Wrong current password	422; readable “Your current password is incorrect.”
Password change without CSRF	403; asks the user to refresh before saving.
Valid password change	200; new cookie/CSRF issued; a previous session became anonymous.
Old / new password login	Old password: 401. New password: 200.
Normal user creates a user	403; administrator permission is required.
Admin creates analyst and fan	201; each newly created user could sign in.
Existing email	409; account is not overwritten.
SQL-like text in password fields	Accepted as a password, including slash-redirect routes; not scanned as SQL.
Terminal SQL enabled	No tested password, Argon2 hash, or credential-write SQL appeared in the log.

SQL injection demonstration

Figure 8 captures a controlled probe in the Teams search box. The request guard returned 403 with an ordinary-language explanation. No table modification was requested or performed. The normal-query route still binds its search value as data; a guard bypass would not turn that bound value into SQL syntax.




Figure 8. The application rejects a quoted boolean probe with a readable message.

Five detected probes or failed sign-ins within five minutes trigger a temporary block by default. Limits are per process and reset on restart. Vite makes local clients share a loopback peer-IP bucket. These limits can have false positives and do not provide distributed denial-of-service protection.

3. Database Connection & Setup

3.1 System Connection

Figure 9 follows a request from the browser to SQLite. React forms call the shared API client with JSON; Vite forwards /api, /docs/api, and /openapi.json to FastAPI. FastAPI applies the request guard, authentication, authorization, CSRF checks, and Pydantic validation before service logic executes parameterized SQLAlchemy statements. Successful writes commit; failed writes roll back and return an error envelope with a readable message.




Figure 9. Browser, API, and database connection paths; account queries use private sessions.

Sports and account engines use the same configured database. Both enable SQLite foreign keys on every connection. SQLite documents that this setting is connection-specific [3]. The browser never opens the database file directly. Source-of-truth records are accessed through the application; the read-only extracts in this report serve only as coursework evidence.

3.2 Setup Instructions

Use Git, Node.js 22.13+ LTS or 24+, npm, and uv. Setup installs the locked Python 3.12 environment and locked Node dependencies. Listing 2 is the fresh-clone sequence. Run it from the project root and stop older servers before setup or startup.

Listing 2. Fresh clone, safe setup, and shared development launcher

```
git clone https://github.com/g497813927/NFLPlayersAnalytics.git
cd NFLPlayersAnalytics
npm run setup
npm run dev
```

Open http://127.0.0.1:5173 for the interface and /docs/api for Swagger. The launcher starts FastAPI on 8000 and Vite on 5173 in one terminal, labels their output API/Web, and stops both with Ctrl+C or when either process exits. Vite fails on an occupied port instead of silently choosing another. Create the first admin using Listing 1, then use the in-app account menu.

Table 3 lists the main configuration values. Setup copies only missing .env files; shell environment variables override them. Local .env files and database files are ignored by Git. Restart the affected service after changing configuration. Never place credentials in VITE_ variables, which are exposed to the browser.

Table 3. Local configuration and debugging switches

Setting / file	Default and purpose
DATABASE_URL / backend/.env	sqlite:///data/prototype.db; relative paths resolve from backend/.
SQL_ECHO / backend/.env	true in new setup examples; prints actual sports SQL and separate parameters. Fallback if absent: false.
SQL_DEBUG_UI / backend/.env	false; enable only for development/admin request-scoped SQL inspection.
SESSION_COOKIE_SECURE	false for loopback HTTP; enable with HTTPS.
WAF_ENABLED	true; parameter binding and permissions still apply when false.
API_PROXY_TARGET / frontend/.env	http://127.0.0.1:8000; Vite development proxy target.

3.3 Database Initialization

Setup initializes and seeds an empty SQLite file, seeds a complete compatible empty schema, and skips populated application data. It rejects partial or unrelated schemas. For a compatible older 17-table database, the only automatic upgrade adds the two authentication tables. Startup itself never creates tables, resets data, or seeds records.

The ORM creation path and standalone SQL path are alternatives. Listing 3 shows the explicit SQL path for a fresh disposable database; it runs both db/schema.sql and db/auth_schema.sql. Using --method orm instead creates the same 19 tables from the imported ORM metadata. The deterministic Python seed program is shared by both paths.

Listing 3. Initialize and seed a fresh database using the SQL scripts

```
cd backend
uv run --frozen python -m scripts.init_db --method sql
uv run --frozen python -m scripts.seed
```

3.4 Challenges & Lessons Learned

Maintaining both ORM metadata and a submission SQL artifact made path handling and schema parity important. Initialization now resolves schema files independently of the working directory. The original 17-table db/schema.sql remains unchanged for submission; authentication is isolated in db/auth_schema.sql. This keeps a previously submitted artifact stable while making the extension explicit.

Adding accounts introduced a second tension: generated SQL is valuable evidence, but credential queries must never appear in it. A private account engine and request-capture exclusions preserve sports SQL debugging without exposing password hashes or session material. Password changes also require session rotation and a new CSRF token; changing only the stored hash would leave old sessions usable.

Season filters revealed why domain dates matter. A season can end in the following calendar year, so roster, membership, and statistic filters use the stored season relationship rather than extracting a calendar year from each date. Comparison calculations similarly honor each statistic definition instead of summing every value. These choices improved consistency between forms, queries, and charts.

4. System Design & Functionality

4.1 Schema Design

Table 4 maps the initial relational proposal to the implemented design. The Phase 2 ER diagram in Figure 27 shows 16 entities. The normalized core adds saved_comparison, producing 17 tables; user_credential and auth_session then bring the implemented total to 19. This update does not modify the core schema file; the new password-change and admin-create-user features reuse the existing authentication extension.

Table 4. Initial proposal to final implementation

Area	Implemented decision and reason
USER entity	Mapped to app_user to avoid a reserved or ambiguous SQL name; keeps email, display name, and role.
STANDING totals	Adds ties and derives points as wins + 0.5 × ties. Rank uses win percentage with dense ties.
Authentication and saved comparisons	Adds saved_comparison to the Phase 2 model, then user_credential and auth_session for credentials and expiring sessions.
Keys and uniqueness	Game participants use (game_id, team_id); one home/away role per game and one roster per team/season.
Optional subject/target fields	CHECK constraints require exactly one statistic subject or favorite target, and a valid distinct comparison pair.
Dates and numeric rules	Valid season/membership date ranges, nonnegative scores and standing counts; jersey numbers remain nullable strings.
References	Explicit CASCADE, SET NULL, or RESTRICT actions preserve the intended ownership/history behavior.

The initial diagram separates entities and relationships conceptually; the SQL model makes those references explicit as foreign keys. Membership gains start/end dates for historical rosters, and stat_definition uses calc_type for aggregation. Descriptive attributes belong to their own keys: a team name is stored on team, a sport name on sport, and a statistic definition on stat_definition. roster resolves the team–season relationship, membership resolves dated athlete–roster participation, and game_participant resolves team–game participation. These separations avoid repeating league names, athlete profiles, and statistic labels in every observation and follow the intended third-normal-form structure. This is a design explanation, not a formal proof of every functional dependency.

standing is an intentional stored summary, recalculated from completed games within the sports-write transaction. Favorite target columns and comparison pair columns preserve the original proposal with explicit CHECK constraints. saved_comparison and data_import have synthetic records but their full save/import workflows remain deferred; the current Compare page is read-only and does not write saved_comparison.

4.2 ER Diagram

Figures 10–14 present the final schema as five UML class views. Boxes show entities and their key attributes; Table 5 onward gives every column. Arrows run from the referenced parent to the referencing child. Association labels give parent multiplicity : child multiplicity; 1 is mandatory, 0..1 optional, and 0..* permits many. Repeated boxes are the same entity across views. Brackets beside FK fields mark optional references.

Figure 10 shows that each league belongs to one sport, each team and season to one league, and each roster to one team and one season. Membership belongs to one roster and one athlete. A parent can exist before its child rows, so parent participation is generally partial. The unique team/season roster key prevents duplicate rosters.




Figure 10. Final UML view: sports, leagues, teams, seasons, rosters, and memberships.

Game and statistic relationships

Figure 11 connects games to seasons, optional venues, participants, and performance rows. Each statistic belongs to one game and definition, with exactly one athlete or team subject. The database permits zero to two participant rows: the home/away CHECK and unique game/role key cap the count at two; application validation saves exactly one home and one away participant with each game and requires both scores for completed games. An athlete statistic also requires a qualifying membership on a participating team on the game date.




Figure 11. Final UML view: games, participants, statistics, definitions, and derived standings.

Account relationships

Figure 12 separates user profiles from credentials. A synthetic or not-yet-credentialed app_user may have no credential; a credential has exactly one user. An auth_session must reference a credential and is deleted with it. data_import can retain a record after its optional initiating user is removed because that FK uses SET NULL.




Figure 12. Final UML view: profiles, credentials, sessions, and import audit records.

Favorite ownership

Figure 13 shows mandatory favorite ownership and optional target references. A CHECK constraint permits exactly one target among sport, league, team, and athlete. The current account API exposes team favorites only, derives the owner from the session, and enforces uniqueness per user/target. Removing an owner or target cascades its associated favorite rows.




Figure 13. Final UML view: favorite ownership and alternative target associations.

Stored comparison design

Figure 14 documents the retained saved_comparison entity. Each record has one user and one sport. For object_type team, both distinct team IDs are required and athlete IDs must be NULL; athlete comparisons use the opposite rule. A and B are two independent associations with the same multiplicities. The implemented comparison reports read recorded performance data directly; account-backed saving remains future work.




Figure 14. Final UML view: saved comparison pairs, retained for a later save workflow.

4.3 Tables & Keys

Tables 5–23 describe all 19 entities and every mapped column. PK denotes a primary key, FK a foreign key, and NULL an optional value. All integer references match their integer parent keys. FK notes include the delete action. Named constraints and full SQLite DDL are retained in db/schema.sql and db/auth_schema.sql; ORM metadata is exposed through backend/app/models.py.

sport

Table 5 describes sport. Names the supported sport.

Table 5. sport entity and key dictionary

Column	SQL type	Keys, nullability, and references
sport_id	INTEGER	PK; NOT NULL
sport_name	VARCHAR(100)	NOT NULL

Unique combinations: sport_name.

Checks: length(trim(sport_name)) > 0.

league

Table 6 describes league. Groups teams and seasons under one sport.

Table 6. league entity and key dictionary

Column	SQL type	Keys, nullability, and references
league_id	INTEGER	PK; NOT NULL
league_name	VARCHAR(150)	NOT NULL
country	VARCHAR(100)	NOT NULL
sport_id	INTEGER	NOT NULL; FK → sport.sport_id; DELETE RESTRICT

Unique combinations: sport_id, league_name.

Checks: length(trim(league_name)) > 0 AND length(trim(country)) > 0.

team

Table 7 describes team. Stores a fictional team identity and city.

Table 7. team entity and key dictionary

Column	SQL type	Keys, nullability, and references
team_id	INTEGER	PK; NOT NULL
team_name	VARCHAR(150)	NOT NULL
city	VARCHAR(100)	NOT NULL
league_id	INTEGER	NOT NULL; FK → league.league_id; DELETE RESTRICT

Unique combinations: league_id, team_name.

Checks: length(trim(team_name)) > 0 AND length(trim(city)) > 0.

season

Table 8 describes season. Defines the date interval and league for a season.

Table 8. season entity and key dictionary

Column	SQL type	Keys, nullability, and references
season_id	INTEGER	PK; NOT NULL
season_name	VARCHAR(100)	NOT NULL
start_date	DATE	NOT NULL
end_date	DATE	NOT NULL
league_id	INTEGER	NOT NULL; FK → league.league_id; DELETE RESTRICT

Unique combinations: league_id, season_name.

Checks: end_date >= start_date; length(trim(season_name)) > 0.

venue

Table 9 describes venue. Stores a named location for scheduled games.

Table 9. venue entity and key dictionary

Column	SQL type	Keys, nullability, and references
venue_id	INTEGER	PK; NOT NULL
venue_name	VARCHAR(150)	NOT NULL
city	VARCHAR(100)	NOT NULL

Checks: length(trim(venue_name)) > 0 AND length(trim(city)) > 0.

athlete

Table 10 describes athlete. Stores a synthetic athlete profile.

Table 10. athlete entity and key dictionary

Column	SQL type	Keys, nullability, and references
athlete_id	INTEGER	PK; NOT NULL
first_name	VARCHAR(100)	NOT NULL
last_name	VARCHAR(100)	NOT NULL
nationality	VARCHAR(100)	NULL

Checks: length(trim(first_name)) > 0 AND length(trim(last_name)) > 0.

roster

Table 11 describes roster. Connects one team to one season.

Table 11. roster entity and key dictionary

Column	SQL type	Keys, nullability, and references
roster_id	INTEGER	PK; NOT NULL
team_id	INTEGER	NOT NULL; FK → team.team_id; DELETE RESTRICT
season_id	INTEGER	NOT NULL; FK → season.season_id; DELETE RESTRICT

Unique combinations: team_id, season_id.

membership

Table 12 describes membership. Records dated athlete participation on a roster.

Table 12. membership entity and key dictionary

Column	SQL type	Keys, nullability, and references
membership_id	INTEGER	PK; NOT NULL
roster_id	INTEGER	NOT NULL; FK → roster.roster_id; DELETE CASCADE
athlete_id	INTEGER	NOT NULL; FK → athlete.athlete_id; DELETE RESTRICT
position	VARCHAR(40)	NOT NULL
jersey_number	VARCHAR(10)	NULL
start_date	DATE	NOT NULL
end_date	DATE	NULL

Unique combinations: roster_id, athlete_id, start_date.

Checks: end_date IS NULL OR end_date >= start_date; length(trim(position)) > 0.

game

Table 13 describes game. Stores the schedule/status and links to season and optional venue.

Table 13. game entity and key dictionary

Column	SQL type	Keys, nullability, and references
game_id	INTEGER	PK; NOT NULL
game_time	DATETIME	NOT NULL
status	VARCHAR(20)	NOT NULL; Default scheduled
season_id	INTEGER	NOT NULL; FK → season.season_id; DELETE RESTRICT
venue_id	INTEGER	NULL; FK → venue.venue_id; DELETE SET NULL

Checks: status IN ('scheduled', 'in_progress', 'completed', 'cancelled').

game_participant

Table 14 describes game_participant. Stores a home or away team and optional score for a game.

Table 14. game_participant entity and key dictionary

Column	SQL type	Keys, nullability, and references
game_id	INTEGER	PK; NOT NULL; FK → game.game_id; DELETE CASCADE
team_id	INTEGER	PK; NOT NULL; FK → team.team_id; DELETE RESTRICT
participant_role	VARCHAR(10)	NOT NULL
score	INTEGER	NULL

Unique combinations: game_id, participant_role.

Checks: score IS NULL OR score >= 0; participant_role IN ('home', 'away').

stat_definition

Table 15 describes stat_definition. Defines a sport-specific metric and its aggregation rule.

Table 15. stat_definition entity and key dictionary

Column	SQL type	Keys, nullability, and references
stat_definition_id	INTEGER	PK; NOT NULL
stat_name	VARCHAR(100)	NOT NULL
abbreviation	VARCHAR(20)	NOT NULL
calc_type	VARCHAR(20)	NOT NULL
sport_id	INTEGER	NOT NULL; FK → sport.sport_id; DELETE RESTRICT

Unique combinations: sport_id, abbreviation.

Checks: length(trim(stat_name)) > 0 AND length(trim(abbreviation)) > 0; calc_type IN ('sum', 'average', 'min', 'max', 'last').

performance_statistic

Table 16 describes performance_statistic. Stores one metric for exactly one athlete or team in a game.

Table 16. performance_statistic entity and key dictionary

Column	SQL type	Keys, nullability, and references
performance_statistic_id	INTEGER	PK; NOT NULL
game_id	INTEGER	NOT NULL; FK → game.game_id; DELETE CASCADE
stat_definition_id	INTEGER	NOT NULL; FK → stat_definition.stat_definition_id; DELETE RESTRICT
athlete_id	INTEGER	NULL; FK → athlete.athlete_id; DELETE RESTRICT
team_id	INTEGER	NULL; FK → team.team_id; DELETE RESTRICT
stat_value	FLOAT	NOT NULL

Unique combinations: game_id, stat_definition_id, team_id; game_id, stat_definition_id, athlete_id.

Checks: Exactly one of athlete_id or team_id is non-NULL.

standing

Table 17 describes standing. Stores the recalculated team/season summary.

Table 17. standing entity and key dictionary

Column	SQL type	Keys, nullability, and references
standing_id	INTEGER	PK; NOT NULL
team_id	INTEGER	NOT NULL; FK → team.team_id; DELETE CASCADE
season_id	INTEGER	NOT NULL; FK → season.season_id; DELETE CASCADE
rank	INTEGER	NOT NULL
wins	INTEGER	NOT NULL; Default 0
losses	INTEGER	NOT NULL; Default 0
ties	INTEGER	NOT NULL; Default 0
points	FLOAT	NOT NULL; Default 0

Unique combinations: team_id, season_id.

Checks: rank > 0; points >= 0; wins >= 0 AND losses >= 0 AND ties >= 0.

app_user

Table 18 describes app_user. Stores display identity, email, and role.

Table 18. app_user entity and key dictionary

Column	SQL type	Keys, nullability, and references
user_id	INTEGER	PK; NOT NULL
email	VARCHAR(254)	NOT NULL
display_name	VARCHAR(100)	NOT NULL
role	VARCHAR(20)	NOT NULL; Default fan

Unique combinations: email.

Checks: role IN ('fan', 'analyst', 'admin'); length(trim(email)) > 0 AND length(trim(display_name)) > 0.

favorite

Table 19 describes favorite. Stores an account-owned favorite with exactly one target.

Table 19. favorite entity and key dictionary

Column	SQL type	Keys, nullability, and references
favorite_id	INTEGER	PK; NOT NULL
user_id	INTEGER	NOT NULL; FK → app_user.user_id; DELETE CASCADE
sport_id	INTEGER	NULL; FK → sport.sport_id; DELETE CASCADE
league_id	INTEGER	NULL; FK → league.league_id; DELETE CASCADE
team_id	INTEGER	NULL; FK → team.team_id; DELETE CASCADE
athlete_id	INTEGER	NULL; FK → athlete.athlete_id; DELETE CASCADE
created_at	DATETIME	NOT NULL; Default CURRENT_TIMESTAMP

Unique combinations: user_id, team_id; user_id, league_id; user_id, sport_id; user_id, athlete_id.

Checks: Exactly one target is non-NULL.

saved_comparison

Table 20 describes saved_comparison. Retains a valid pair for the proposed future save feature.

Table 20. saved_comparison entity and key dictionary

Column	SQL type	Keys, nullability, and references
comparison_id	INTEGER	PK; NOT NULL
user_id	INTEGER	NOT NULL; FK → app_user.user_id; DELETE CASCADE
sport_id	INTEGER	NOT NULL; FK → sport.sport_id; DELETE CASCADE
object_type	VARCHAR(20)	NOT NULL
athlete_a_id	INTEGER	NULL; FK → athlete.athlete_id; DELETE CASCADE
athlete_b_id	INTEGER	NULL; FK → athlete.athlete_id; DELETE CASCADE
team_a_id	INTEGER	NULL; FK → team.team_id; DELETE CASCADE
team_b_id	INTEGER	NULL; FK → team.team_id; DELETE CASCADE
title	VARCHAR(200)	NOT NULL
created_at	DATETIME	NOT NULL; Default CURRENT_TIMESTAMP

Checks: Exactly one distinct same-kind pair; title is nonblank.

data_import

Table 21 describes data_import. Retains synthetic import provenance; live importing is deferred.

Table 21. data_import entity and key dictionary

Column	SQL type	Keys, nullability, and references
import_id	INTEGER	PK; NOT NULL
source_name	VARCHAR(200)	NOT NULL
imported_at	DATETIME	NOT NULL; Default CURRENT_TIMESTAMP
status	VARCHAR(20)	NOT NULL; Default pending
run_by_user_id	INTEGER	NULL; FK → app_user.user_id; DELETE SET NULL

Checks: length(trim(source_name)) > 0; status IN ('completed', 'failed', 'pending').

user_credential

Table 22 describes user_credential. Stores the private password hash for a user.

Table 22. user_credential entity and key dictionary

Column	SQL type	Keys, nullability, and references
user_id	INTEGER	PK; NOT NULL; FK → app_user.user_id; DELETE CASCADE
password_hash	VARCHAR(255)	NOT NULL
created_at	DATETIME	NOT NULL; Default CURRENT_TIMESTAMP

auth_session

Table 23 describes auth_session. Stores a private expiring token digest for a credentialed user.

Table 23. auth_session entity and key dictionary

Column	SQL type	Keys, nullability, and references
token_hash	VARCHAR(64)	PK; NOT NULL
user_id	INTEGER	NOT NULL; FK → user_credential.user_id; DELETE CASCADE
expires_at	DATETIME	NOT NULL
created_at	DATETIME	NOT NULL; Default CURRENT_TIMESTAMP

4.4 Sample Data and Application Queries

The seed program uses fixed random seed 5614, fictional team/city/name lists, and deterministic schedules for 2022–2026. It creates 20 teams, 100 athletes, 100 games, and 1,260 performance rows. Additional synthetic credentialed users were created through the CLI and application. Report fixture setup also inserted four sport/league pairs through the existing SQLAlchemy models in the disposable database; catalog_fixtures.json records those inputs. They have no game data and do not change the normal football seed. Table 24 records the evidence counts. Authentication activity can change session counts after the snapshot; the sample is not a production export.

Table 24. Evidence snapshot row counts

Table	Rows	Table	Rows
sport	5	league	5
team	20	season	5
venue	10	athlete	100
roster	100	membership	500
game	100	game_participant	200
stat_definition	6	performance_statistic	1260
standing	100	app_user	10
favorite	21	saved_comparison	20
data_import	5	user_credential	5
auth_session	7	—	—

The following tables show five actual rows from every entity, with selected fields for readability. The normal seed uses one football league; the extra report-only catalog rows demonstrate that the schema can represent other sports. They are setup fixtures, not evidence of additional supported game visualizations. Password and token hashes are withheld, and no usable credentials are included.

Sample queries are shown in Listings 4–6. They illustrate the application’s parameterized SELECT behavior; the report does not require users to run SQL. League/team names and roster descriptions appear in the GUI instead of raw identifiers. The report’s one-time read-only sample extraction is separate from end-user workflows.

Listing 4. Read teams with a name filter and league label

```
SELECT t.team_name, t.city, l.league_name
FROM team AS t JOIN league AS l ON l.league_id = t.league_id
WHERE t.team_name LIKE :search
ORDER BY t.team_name;
-- Bound parameter: search = '%Alder%'
-- Result: Alder Bay Foxes | Alder Bay | Frontier Football League
```

Listing 5. Read a team roster for the selected stored season

```
SELECT a.first_name, a.last_name, m.position, m.jersey_number
FROM membership AS m
JOIN athlete AS a ON a.athlete_id = m.athlete_id
JOIN roster AS r ON r.roster_id = m.roster_id
WHERE r.team_id = :team_id AND r.season_id = :season_id
ORDER BY a.last_name, a.first_name;
-- Bound parameters: team_id = 1, season_id = 4 (2025)
```

sport sample

Table 25 shows five rows from sport; total snapshot rows: 5.

Table 25. sport sample rows (selected fields)

sport_id	sport_name
1	American Football
2	Basketball
3	Association Football
4	Baseball
5	Ice Hockey

league sample

Table 26 shows five rows from league; total snapshot rows: 5.

Table 26. league sample rows (selected fields)

league_id	league_name	country	sport_id
1	Frontier Football League	United States	1
2	Cedar Valley Basketball League	United States	2
3	Harbor District Soccer League	United States	3
4	Meadow County Baseball League	United States	4
5	Northlake Hockey League	United States	5

team sample

Table 27 shows five rows from team; total snapshot rows: 20.

Table 27. team sample rows (selected fields)

team_id	team_name	city	league_id
1	Alder Bay Foxes	Alder Bay	1
2	Briar Glen Owls	Briar Glen	1
3	Cedar Reach Bears	Cedar Reach	1
4	Dawn Harbor Falcons	Dawn Harbor	1
5	Elm Ridge Stags	Elm Ridge	1

season sample

Table 28 shows five rows from season; total snapshot rows: 5.

Table 28. season sample rows (selected fields)

season_id	season_name	start_date	end_date	league_id
1	2022	2022-08-01	2023-02-28	1
2	2023	2023-08-01	2024-02-28	1
3	2024	2024-08-01	2025-02-28	1
4	2025	2025-08-01	2026-02-28	1
5	2026	2026-08-01	2027-02-28	1

venue sample

Table 29 shows five rows from venue; total snapshot rows: 10.

Table 29. venue sample rows (selected fields)

venue_id	venue_name	city
1	Alder Bay Community Field	Alder Bay
2	Cedar Reach Community Field	Cedar Reach
3	Elm Ridge Community Field	Elm Ridge
4	Granite Cove Community Field	Granite Cove
5	Iron Meadow Community Field	Iron Meadow

athlete sample

Table 30 shows five rows from athlete; total snapshot rows: 100.

Table 30. athlete sample rows (selected fields)

athlete_id	first_name	last_name	nationality
1	Alden	Ashford	United States
2	Alden	Brookvale	United States
3	Alden	Crestwood	United States
4	Alden	Dunridge	United States
5	Alden	Evermere	United States

roster sample

Table 31 shows five rows from roster; total snapshot rows: 100.

Table 31. roster sample rows (selected fields)

roster_id	team_id	season_id
1	1	1
2	2	1
3	3	1
4	4	1
5	5	1

membership sample

Table 32 shows five rows from membership; total snapshot rows: 500.

Table 32. membership sample rows (selected fields)

membership_id	roster_id	athlete_id	position	jersey_number	start_date
1	1	1	QB	12	2022-08-01
2	1	2	RB	24	2022-08-01
3	1	3	WR	81	2022-08-01
4	1	4	LB	54	2022-08-01
5	1	5	DB	31	2022-08-01

The complete sample_rows.json also includes end_date. The string jersey_number preserves values such as 00.

game sample

Table 33 shows five rows from game; total snapshot rows: 100.

Table 33. game sample rows (selected fields)

game_id	game_time	status	season_id	venue_id
1	2022-09-13 17:00:00	completed	1	1
2	2022-09-13 17:00:00	completed	1	1
3	2022-09-13 17:00:00	completed	1	2
4	2022-09-13 17:00:00	completed	1	2
5	2022-09-13 17:00:00	completed	1	3

game_participant sample

Table 34 shows five rows from game_participant; total snapshot rows: 200.

Table 34. game_participant sample rows (selected fields)

game_id	team_id	participant_role	score
1	1	home	14
1	11	away	17
2	2	home	21
2	12	away	14
3	3	home	14

stat_definition sample

Table 35 shows five rows from stat_definition; total snapshot rows: 6.

Table 35. stat_definition sample rows (selected fields)

stat_definition_id	stat_name	abbreviation	calc_type	sport_id
1	Points scored	PTS	sum	1
2	Total offensive yards	YDS	sum	1
3	Turnovers	TO	sum	1
4	Passing yards	PASS_YDS	sum	1
5	Rushing yards	RUSH_YDS	sum	1

performance_statistic sample

Table 36 shows five rows from performance_statistic; total snapshot rows: 1260.

Table 36. performance_statistic sample rows (selected fields)

performance_statistic_id	game_id	stat_definition_id	athlete_id	team_id	stat_value
1	1	1	NULL	1	14.0
2	1	2	NULL	1	442.0
3	1	3	NULL	1	0.0
4	1	4	1	NULL	252.0
5	1	5	2	NULL	190.0

standing sample

Table 37 shows five rows from standing; total snapshot rows: 100.

Table 37. standing sample rows (selected fields)

standing_id	team_id	season_id	rank	wins	losses	ties	points
1	1	1	3	1	1	0	1.0
2	2	1	3	1	1	0	1.0
3	3	1	4	0	1	1	0.5
4	4	1	4	0	1	1	0.5
5	5	1	3	1	1	0	1.0

app_user sample

Table 38 shows five rows from app_user; total snapshot rows: 10.

Table 38. app_user sample rows (selected fields)

user_id	email	display_name	role
1	demo.fan@example.invalid	Demo Fan	fan
2	rowan.analyst@example.invalid	Rowan Analyst	analyst
3	avery.manager@example.invalid	Avery Manager	admin
4	morgan.scout@example.invalid	Morgan Scout	analyst
5	casey.supporter@example.invalid	Casey Supporter	fan

favorite sample

Table 39 shows five rows from favorite; total snapshot rows: 21.

Table 39. favorite sample rows (selected fields)

favorite_id	user_id	sport_id	league_id	team_id	athlete_id
1	1	1	NULL	NULL	NULL
2	1	NULL	1	NULL	NULL
3	1	NULL	NULL	1	NULL
4	1	NULL	NULL	NULL	1
5	2	1	NULL	NULL	NULL

saved_comparison sample

Table 40 shows five rows from saved_comparison; total snapshot rows: 20.

Table 40. saved_comparison sample rows (selected fields)

comparison_id	user_id	object_type	athlete_a_id	athlete_b_id	team_a_id	team_b_id
1	1	team	NULL	NULL	1	11
2	1	athlete	1	51	NULL	NULL
3	1	team	NULL	NULL	6	16
4	1	athlete	26	76	NULL	NULL
5	2	team	NULL	NULL	2	12

The complete sample also includes sport_id, title, and created_at. These seed rows do not imply an implemented save-comparison screen.

data_import sample

Table 41 shows five rows from data_import; total snapshot rows: 5.

Table 41. data_import sample rows (selected fields)

import_id	source_name	status	run_by_user_id
1	Seed 5614; 2022 season	completed	3
2	Seed 5614; 2023 season	completed	3
3	Seed 5614; 2024 season	completed	3
4	Seed 5614; 2025 season	completed	3
5	Seed 5614; 2026 season	completed	3

user_credential sample

Table 42 shows five rows from user_credential; total snapshot rows: 5.

Table 42. user_credential sample rows (selected fields)

user_id	password_hash	created_at
6	[withheld]	2026-11-11 16:19:40
7	[withheld]	2026-11-11 16:20:20
8	[withheld]	2026-11-11 16:22:37
9	[withheld]	2026-11-11 16:24:35
10	[withheld]	2026-11-11 16:24:35

Private hash values are deliberately withheld. These are real fixture rows created during account verification, not reusable credentials.

auth_session sample

Table 43 shows five rows from auth_session; total snapshot rows: 7.

Table 43. auth_session sample rows (selected fields)

token_hash	user_id	expires_at	created_at
[withheld]	7	2026-11-18 16:20:56.223609	2026-11-11 16:20:56
[withheld]	7	2026-11-18 16:20:56.284163	2026-11-11 16:20:56
[withheld]	6	2026-11-18 16:21:04.958540	2026-11-11 16:21:04
[withheld]	6	2026-11-18 16:24:35.104068	2026-11-11 16:24:35
[withheld]	7	2026-11-18 16:24:35.131366	2026-11-11 16:24:35

Private hash values are deliberately withheld. These are real fixture rows created during account verification, not reusable credentials.

5. Reporting

5.1 Team Season Comparison

Report 1 answers how two teams compare on saved performance in one season. On Compare, choose Teams, season 2025, Alder Bay Foxes, and Briar Glen Owls. The API joins performance_statistic with game and stat_definition, filters completed games, and groups by subject and metric. A CASE expression selects sum, average, minimum, maximum, or the latest recorded value according to calc_type. The latest rule uses a window function ordered by game time and stable IDs. Listing 6 is a readable equivalent of the aggregation; the exact emitted SQL and separate parameters are included in report_queries.json.

Listing 6. Comparison aggregation with a subquery, joins, grouping, and a window function

```
WITH recorded AS (
  SELECT ps.team_id AS subject_id, ps.stat_definition_id,
         ps.stat_value, g.game_id,
         ROW_NUMBER() OVER (
           PARTITION BY ps.team_id, ps.stat_definition_id
           ORDER BY g.game_time DESC, g.game_id DESC,
                    ps.performance_statistic_id DESC) AS recency
  FROM performance_statistic AS ps
  JOIN game AS g ON g.game_id = ps.game_id
  WHERE ps.team_id IN (:left_id, :right_id)
    AND g.season_id = :season_id AND g.status = :status
)
SELECT d.stat_name, d.calc_type, r.subject_id, COUNT(*) AS samples,
  CASE d.calc_type
    WHEN 'sum' THEN SUM(r.stat_value)
    WHEN 'average' THEN AVG(r.stat_value)
    WHEN 'min' THEN MIN(r.stat_value)
    WHEN 'max' THEN MAX(r.stat_value)
    WHEN 'last' THEN MAX(CASE WHEN r.recency = 1
                              THEN r.stat_value END)
  END AS value
FROM recorded AS r JOIN stat_definition AS d
  ON d.stat_definition_id = r.stat_definition_id
GROUP BY d.stat_definition_id, d.stat_name, d.calc_type, r.subject_id;
-- Team report: left_id=1, right_id=2, season_id=4, status='completed'
-- Player report: use athlete_id instead; left_id=1, right_id=11
```

Team report results

Figure 15 visualizes the observed team results, rechecked through the API on November 11. Table 44 lists the same values. Both sides have two completed games with two observations for each metric. Alder Bay scored three more points with fewer recorded offensive yards and fewer turnovers. These are descriptive comparisons of a small synthetic sample; more is not automatically better, especially for turnovers.




Figure 15. Report 1: 2025 team comparison with separate metric scales and sample counts.

Table 44. Report 1 observed team aggregates

Metric (sum)	Alder Bay Foxes	Briar Glen Owls	Samples each
Points scored	48.0	45.0	2
Total offensive yards	633.0	695.0	2
Turnovers	2.0	5.0	2

5.2 Player Season Comparison

Report 2 asks how two rostered players compare in the same season. Choose Players, 2025, Alden Ashford, and Bennett Ashford. The service uses the same joined/grouped calculation as Listing 6 with athlete_id as the subject column, independently of list pagination. Player selectors come from complete season memberships and show team/position context. Team totals are not reconstructed by adding athlete rows.

Figure 16 and Table 45 show passing yards of 488 and 421, a difference of 67. Each side has two saved observations from two completed games. A missing metric is displayed as a dash rather than zero; values from mock live replays never contribute. The chart supports comparison, not a claim about professional player ability.




Figure 16. Report 2: 2025 player passing-yard comparison from saved completed games.

Table 45. Report 2 observed player aggregates

Metric (sum)	Alden Ashford	Bennett Ashford	Samples each
Passing yards	488.0	421.0	2

Use GET /api/comparisons/options for valid selectors and GET /api/comparisons for the report. Both reports are read-only and unsaved. Invalid or repeated selections return 422.

6. GUI / Interface

Figure 17 shows the home page with named task links and a database-connected status. Navigation can collapse on any screen and expands to a full-screen menu on a phone. Pages include Teams, Players, Games, Statistics, Compare, Standings, and the admin workspace. Selection controls display names and context rather than asking users to type foreign-key IDs.




Figure 17. Home page with database connectivity and entry points to user tasks.

The Games page distinguishes a saved record from an explicitly scripted mock replay. Drive position, key events, and low-key impact explanations support exploration without writing simulated events into the database. Account favorites synchronize when devices use the same backend; separate local databases do not synchronize with one another.

Season filters

Figure 18 shows a team roster filtered by the stored 2025 season. Rosters, memberships, and statistics follow that season together, while each section retains its own pagination. The filter includes a season ending in 2026; it does not reinterpret the selection as a calendar-year-only date search.




Figure 18. Team detail filtered by season, with readable player and roster labels.

6.1 CRUD Operations

The following walkthrough uses a temporary synthetic team, Quarry Bay Comets, in the admin workspace. All four operations used the GUI and API in the disposable database. Figures 19–26 frame the relevant form/table region; original full captures remain in docs/screenshots/final-report/.

Figure 19 shows a search with no matching team before creation. Figure 20 shows the named league selector and completed add form. The relationship value submitted to the API is an ID selected from the database, even though the user sees Frontier Football League.




Figure 19. Create before: no Quarry Bay team exists.




Figure 20. Create form: new team values and a database-backed league selection.

Create result and update

Figure 21 confirms the saved team, with one matching record. Figure 22 shows the edit form loading its current values before changing the city from Quarry Bay to Quarry Heights. The update retains the team name and league.




Figure 21. Create after: Quarry Bay Comets is persisted and listed.




Figure 22. Update before: existing values are loaded into the form.

Update result and delete confirmation

Figure 23 shows the changed city in the saved row. Figure 24 shows the confirmation before deletion. This newly created team has no roster or game children, so deletion can complete. A referenced team would be protected by RESTRICT and the backend would return a readable conflict.




Figure 23. Update after: the saved city is Quarry Heights.




Figure 24. Delete before: confirmation explains that dependencies may block removal.

Delete result and read search

Figure 25 shows no matching record after confirmation, completing the delete evidence. Figure 26 demonstrates Read/Search: filtering Teams by Alder returns the named team and league. These results demonstrate the observed operations, not exhaustive coverage of every entity.




Figure 25. Delete after: the Quarry Bay search returns zero records.




Figure 26. Read/Search: the team list is filtered by a meaningful name.

The browser receives {error: {code, message, fields?}} on rejection. Validation keeps current form input where practical, failed transactions roll back, successful writes refresh affected lists, and unavailable-backend/empty states are explicit. The optional admin SQL inspector shows actual emitted SQL and bound parameters; it cannot execute arbitrary SQL.

7. Reflection

7.1 Individual Contributions

The individual contribution paragraphs below are intentionally left blank at the team's request. Each member should complete their paragraph before submission. No contribution has been inferred from Git author names or assigned by the assistant.

John Zhao (techzjc@vt.edu)

Ishaan Parikh (iparikh4@vt.edu)

Victor Prosekov (vprosekov@vt.edu)

AI-assisted work

Codex assisted with the prototype implementation and iterative refinements described in the project conversation, including component separation, readable formatting/CI, setup scripts, API documentation, the game-center UI, accounts and the request guard, comparisons, and season filters. For this report update, it implemented password change and admin user creation, performed targeted manual checks, captured screenshots in a disposable database, shortened README into linked guides, and prepared the schema/evidence documentation and report layout. This paragraph records assistance and does not replace the three members' individual reflections or human review.

7.2 Team Reflection

A feature worth highlighting is the separation between simulated play and persisted statistical evidence. The game center can tell a visual story with a drive tracker and small-impact explanations, while comparison reports remain grounded in completed games stored in the relational model. Clear labels and separate code paths prevent a visually convincing mock score from contaminating the analytical results. This connects interface design to database correctness rather than treating them as separate concerns.

An alternative would have been to build only a generic table editor. Task-focused pages made the schema easier to use: the user chooses a team by name, filters a stored season, or compares two players without entering numeric references. Keeping database constraints and server validation underneath those forms was still necessary, because a friendly UI alone cannot protect data. The same lesson applied to the SQL-probe guard: parameter binding remains essential even when a suspicious request is blocked early.

The prototype has limits. It has no automated test suite, production migration history, email verification, password recovery, or distributed rate limiter. The normal seed and game visualizations cover one football league; extra report catalog fixtures do not add other sports workflows. Saved comparisons are not connected to accounts, and import/export workflows are deferred. Future work should add representative tests for authorization, session rotation, cross-table integrity, and report aggregation; introduce deliberate migrations; and evaluate another RDBMS with its driver and compatibility requirements. Changing DATABASE_URL alone is not a complete migration strategy.

8. Appendix

8.1 Repository and Deliverables

The public repository is the source for the application, reproducible setup, database scripts, and supporting report materials. Its public visibility was checked while preparing this report. The existing folder layout is retained; no files were moved merely to match an example hierarchy.

Public project repository

Table 46 maps deliverables to their actual locations. The editable Word report and PDF contain all three team names in author metadata. The original core schema was verified unchanged with SHA-256 d1653c7c2f2c42049b8182fc0c917c8f777de4a5b18be2b0515c2a6bdead2bc1.

Table 46. Repository evidence map

Location	Content
README.md	Short project overview, screenshots, quick start, and guide links.
backend/ and frontend/	API, SQLAlchemy mappings, React/TSX task screens, and dependency lockfiles.
db/	Unchanged core schema.sql plus auth_schema.sql.
docs/ guides	Setup, user tasks, project structure, CI, security rules, and limitations.
docs/final-report/	Final PDF/DOCX, evidence index, schema metadata, sample rows, query captures, UML diagrams, and this report in text form.
docs/screenshots/	Original screenshot captures, including the final-report walkthrough.
Section 7.1 of this report	Reserved individual contribution paragraphs; intentionally blank.

8.2 Evidence Method and Submission Notes

Evidence uses source baseline baf2c23a8291dfecc2d4cd73e93c14b05f1c8a25 plus the account-completion changes accompanying this report. A new disposable SQLite file was initialized using the SQL scripts and deterministic seed; the developer's existing database was not reset. Browser captures show actual local application behavior. Team/player/roster screenshots from the preceding feature work were retained, and the two report result sets were rechecked through the current API. Figure captions identify form states rather than claiming an unobserved success.

The sample appendix is a read-only, sanitized snapshot. Credential hashes and session digests are withheld before publishing. Runtime verification consisted of the repository's format/lint/build/Python-syntax checks and targeted manual browser/API checks. These are not an automated test suite or a complete security assessment. The dated review snapshot in Section 8.4 records the reviewed revisions; the pull requests remain the live source for subsequent CI and review status.

8.3 Initial ER Diagram

Figure 27 reproduces the original diagram from page 9 of the team's Phase 2 submission. It contains 16 entity boxes, including stat_definition and game_participant, although the narrative separately describes 14 entities. Relationship lines express conceptual references; the later relational schema stores these as explicit foreign-key columns.




Figure 27. Original Phase 2 ER diagram, reproduced from the team-provided PDF, page 9.

Relative to this initial model, the normalized core adds saved_comparison, membership dates, an aggregation rule for each statistic definition, explicit foreign keys, and constraints. Authentication adds two more tables. The proposed import-to-record provenance linkage, CSV export, and account-saved comparison workflow remain deferred; their presence in the initial proposal does not imply an implemented feature.

8.4 Review and Verification

Table 47 records the review snapshot taken on November 11, 2026 at 17:16 UTC, before this addendum was committed. Both pull requests were open and unmerged, their Node/Python quality workflows had passed, and no unresolved review threads remained. Codex completed both reviews without unresolved findings. The saved review_snapshot.json includes the revisions and evidence links.

Table 47. Review snapshot before the report addendum

PR	Reviewed revision	CI	Copilot
11	e3579fd	Passed	Approval recommended; no open issues
12	755ad67	Passed	No open issues; human document review requested

Review corrections kept administrator provisioning local, coordinated login with password rotation, and queued browser account mutations so sign-out revokes the final session. The participant diagram now shows zero to two rows per game. The stand-alone Claude guide explicitly includes schema exports and admin authorization. A trailing-slash concern was resolved with the existing normalization and successful requests; a repeated login concern referred to an older revision.

Controlled verification covered both login/password-change orderings and successful or failed password changes followed by queued logout. Formatting, lint, type/build, and Python syntax checks passed. These checks supplement human review and do not replace a future functional test suite.

Figure 28 shows the reviewed fan/analyst role choices. This form was refilled only to capture the revised selector; the original successful creation is shown in Figure 7. Its masked example password was not submitted again.




Figure 28. Reviewed web role choices: fan and analyst; administrator provisioning remains local.

Copilot requested human verification of the Word/PDF layout and coursework requirements. The team must still review the rendered report and complete the reserved individual-contribution paragraphs before submission. Neither pull request was merged during the review loop.

PR 11 account changes

PR 12 report and documentation