


RS-WT Industrial tablet



Commercial Grade



All-in-One



Highly-expandible

Product overview

Ultron windows tablet Series is designed to be placed individually as a All-in-One kiosk. There are VESA mounting holes at the back of the tablet for easy installation.

Available in 10.1", 15.6", 21.5", 32" widescreen

The most common operating system

Easy deployments with various VESA mounting

Industrial Windows Tablet

		RS-WT 101	RS-WT156	RS-WT215
Screen size		10.1"	15.6"	21.5"
Panel info.	Resolution	1280 x 800	1920 x 1080	
	Brightness	350 cd/m²	220 cd/m²	220 cd/m²
	Contrast ratio	800:1	800:1	1000:1
	Aspect Ratio	16:10	16:9	
	Active Display Area	134.8 x 216.2 mm	344.16 x 193.59 mm	476.06 x 267.786 mm
	Viewing angle	H:170°/ V:170°	H:178°/ V:178°	H:170°/ V:170°
	Touch Tech.	10 point cap touch (6H semi-tempered glass)		
CPU & System	CPU	Intel Celeron J1900 (Quad Core)		
	Base Frequency	2.0 GHz		
	CPU Turbo Boost	2.42 GHz		
	CPU Cache	2MB		
	BIOS	AMI 8MB UEFI BIOS		
RAM	RAM	4GB DDR3L @1333 MHz (upgradable)		
ROM	Storage	32GB SSD (upgradable)		
Software	OS	Pre-installed Windows 10 IoT core (License is optional)		
GPU	GPU chipset	Intel HD Graphic (Bay Trail, 688 - 854 MHz)		
	VGA	Yes		
	Display Port	No		
	HDMI	Yes		
	# of display supported	2		
Audio	Codec	Realtek HD ALC662		
	I/O	Line-out x 1, Mic-in x 1		
	Speaker	5W x 2		
Ethernet	Controller	Realtek RTL8111F Gigabit LAN		
	Connector	2 x RJ45		
	Wake on LAN	Yes		
	vPro/ AMT	No		
Storage	Slot	1 x mSATA/ SATA 2.0; 1 x SATA2.0		
Housing	Material & color	Metal housing with Matte black paint		
I/O	USB 2.0	2		
	USB 3.0	1		
	Audio	Line-out x 1; Mic-in x 1		
	LAN	2		
	HDMI	1 (HDMI1.4)		
	Display port	0		
	VGA	1		
Upgradabl e I/O	USB2.0	4		
	RS232	6 (COM2 able to change to RS485) (Only COM2 & 4 with power supply)		
	RS485	1 (switch from COM2)		
	PS/2	1 (Keyboard or Mouse)		
	GPIO	8		
	LPT	1		
AV capability	Camera	Front Facing Camera 2/5 MP fixed focus (Optional)		
Hardware monitor	Sensor	CPU temperature sensor; Voltage sensor; Watchdog; Plug and Start		
	Included in Box	Ultron open frame tablet, Power Adaptor, Power cable		
	Consumption	TBC	TBC	TBC
	Power input	12V 5A		
	Operating	Operating: 32°F to 104°F (0°C to 40°C); Storage: -4°F to 122°F (-20°C to 50°C)		

	Environment	Operating: 20%-80%; Storage: 10%-95%		
	Certification	CE, FCC, ROHS		
	Language	Multi language		
	VESA	VESA 75		VESA 100
Dimension	Size (W x H x D)	250 x 170 x 50.3 mm	290 x 251 x 34.7 mm	534 x 322 x 48 mm
	Product Weight	2 KG	2.7KG	5KG
	Gift Box Size	385 x 222 x 80 mm	444 x 348 x 112 mm	580 x 420 x 110 mm
	Master Carton Size	470 x 400 x 355	462 x 375 x 356 mm	601 x 450 x 370 mm
	Master Carton Weight	24 KG	12 KG	19KG
	Unit/Master carton	8pcs	3pcs	3pcs

*see dimensional drawings for details

Options information

Option	Type	Remarks
3G/4G module	Mini-PCI-e add-on	WCDMA / HSDPA 2100 / 1900 / 850 (900) MHz GSM / GPRS / EDGE 850 / 900 / 1800 / 1900 MHz
Windows 10 IoT core license	/	/
RAM	Extra RAM	4/ 8GB
SSD	Mini-PCI-e add-on	64/ 128 GB
Front Camera	Extra PCB	2 Megapixel with Fixed Focus / 5Megapixel with Auto Focus
Barcode module	USB accessories	1D barcode/ 2D barcode
RFID / NFC module	USB accessories	ISO 14443 T=CL, T=CL, 1K/4K, ISO 18092
Printer	RS232/USB accessories	Receipt thermal printer

