



Printer Specifications	
Resolution	203DPI
Print Method	Direct Thermal
Memory	32 MB RAM / 16 MB Flash
Max.Print Width	4.25 in./108 mm
Max.Print Speed	Up to 6 ips (152 mm/s)
Media Sensors	Movable Black Mark Sensor / Fixed Gap Sensor
Emulation	TSPL, ZPL, EPL, DPL
Interface	USB, USB+Ethernet, Optional Wireless Connectivity: Bluetooth / Wi-Fi
Others	Optional RTC, Optional SD Card Slot
Media and Ribbon Characteristics	
Media Length	0.39 in.~70 in.(10 mm ~ 1778 mm)
Media Width	1 in.~4.56 in.(25.4 mm ~ 116 mm)
Media Roll Size	5 in./127 mm Outer Diameter/ Core Inner Diameter: 1 in. (25.4 mm) - 1.5in. (38.1mm)
Media Thickness	0.0023 in.(0.06 mm) Min.;0.01 in.(0.254 mm) Max.
Media Types	Continuous, Gap, Black mark, Fan-fold, Perforated Media

Environment Condition	
Operating Temp.	5~40°C(41~104°F)
Storage Temp.	-40~60°C(-40~140°F)
Operating Humidity	25 ~ 85% Non-Condensing
Storage Humidity	10 ~ 90% Non-Condensing
Fonts/Graphics/Symbologies	
1D Bar Codes	Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST, GS1 DataBar, Code 11
2D Bar Codes	PDF-417, Maxicode, DataMatrix, QR code, Aztec
Fonts and Graphics	Font 0 ~ Font 8
Software	
Driver	Windows /Linux /Mac / Android / Chrome OS
SDK	Windows/Linux / Android /iOS
Software	Bartender UltraLite / Mobile Label Design App
Accessories	
Standard Accessories	Power Adapter, Power Cord, USB Cable, User Manual, CD, Label spindle, Fixing tab
Factory Installed Options	Bluetooth Module, Wi-Fi Module, Peel-off Module, Cutter Module
User Options	8" External Paper Roll Holder
Product Warranty	
Printhead life	The earlier of 30 km usage or 1 year
Platen roller life	The earlier of 30 km usage or 1 year
Printer Warranty	1 Year
Physical Characteristics	
Dimension	220 mm x 178 mm x 158 mm(D*W*H)
Weight	1.3 Kg