



RScan 2D Scanner stationar 1210

2D Desktop scanner

RScan 2D Scanner stationar 1210

THE PERFORMANCE PARAMETERS

Model	XL-2310
Light Source	Red LED (Lighting) Color Temperature 650nm LED
CPU	32bit MIPS @1G Hz
Scan Mode	Continue scanning &Automatic induction
Image Size	1280x800 pix
Scanning speed	60 fps
Decoding Depth	5~250mm@(13mil UPC/EAN 100%,PCS=90%)
Mnimum Resolution	≥4mil
Scanning angle	Deflection 360° Inclination ±65° Rotation ±60°
Size	L × W × H:152×152×75(mm)
Weight	600g
Case Material	ABS+PC, Flame Retardant Material
Cable	Straight 2.0m
Mobile tolerance	1m/s
Compatible system	Compatible with Linux, Android, Windows XP/7/8/10/MAC OS
Input Voltage	DC 3.6V-5V
Working current	< 200mA
stand-by current	< 150mA
Indicator	Tone and Volume adjustable
Interface	USB-HID、USB-VCP、RS-232
Temperature (Operating)	0°C-50°C
Temperature (Storage)	-40°C-70°C
Humidity	5% to 95% (non-condensing)
Light Levels	0-5000Lux (fluorescence), 0-100,000 Lux (sunlight)
Decoding Capability	1D: UPC,EAN,Code 39 (with full ASCII),Codabar,Code 128,Code 93,Code 11, Interleaved 2 of 5,Industrial 2 of 5,Matrix 2 of 5, MSI Plessy,GS1 DataBar,etc 2D: PDF417,Data Matrix,QR Code,etc