

Scanner RSC 1105 2D

2D Embedded Image Scanner



- ⦿ Easy to be embedded in multiple kiosk applications.
- ⦿ 300000 pixels CMOS sensor for quick reading response.
- ⦿ Sensing scan in bright and dim environment.
- ⦿ Flexible to read barcodes from papers& electronic screens.



Light Source	White light,LED	Secondary Development	Available
Scan Pattern	Sensing Scan	Size	L x W x H: 65.1x61.6x33(mm)
Image Sensor	CMOS	Weight	105g±1g
Scan Resolution	640 × 480 pix	Voltage	5 VDC±5%
Decode Rate	30fps	Scan Mode	Automatic & Continuous
Scan Precision	≥4mil Precision	Operating Current	125mA(Typical value), 130mA(Max value)
Scan Depth of Field	EAN13: 20mm~130mm @13MIL PCS90%	Static Current	85mA
Scan Angle	Tilt ±40° Rotate 360° Deflection Angle ±300°	EMC	CE & FCC DOC compliance
Invoice Code	Support (Alipay, Bill Butler)	Operating Temperature	-20°C to 60°C
Paper Code	Support (paper bar code)	Storage Temperature	-40°C to 70°C
Screen Code	Support (mobile phone screen, PC screen, etc.)	Humidity	5% to 95% relative humidity, non-condensing
Support Interface	USB-HID,USB-VCP and RS232	Light Levels	Daylight, 0-100,000Lux
Decoding Capability	1D:EAN-13, EAN-8, UPC-A, UPC-E, ISSN, ISBN, Codabar, Code 128(FNC1/FNC2/FNC3), Code 93, ITF-6, ITF-14, Interleaved 2 of 5, Industrial 2 of 5, Standard 2 of 5, Matrix 2 of 5, GS1 Databar (RSS-Expand, RSS-Limited, RSS-14), Code 39(Code 39 FULL ASCII), Code 11, MSI-Plessey, Plessey , etc 2D:PDF417, Data Matrix, QR Code, etc		

Scanner RSC 1105 2D

Technical Parameters

Light Source	White light,LED
Scan Pattern	Induction Scan
Image Sensor	CMOS
Scan Resolution	640 × 480 pix
Decode Rate	30fps
Scan Precision	≥ 4mil Precision
Scan Depth of Field	EAN13: 20mm~130mm @13MIL PCS90%Tilt ± 40°
Scan Angle	Rotate 360° Deflection Angle ±300°
Invoice Code	Support (Alipay, Bill Butler)
Paper Code	Support (paper bar code)
Screen Code	Support (mobile phone screen, PC screen, etc.)
Support Interface	USB-HID,USB-VCP and RS232
Secondary Development	Available
Size	L x W x H: 65.1x61.6x33(mm)
Weight	105g±1g
Voltage	5 VDC±5%
Scan Mode	Automatic & Continuous
Operating Current	125mA(Typical value), 130mA(Max value)
Static Current	85mA
EMC	CE & FCC DOC compliance
Operating Temperature	-20°C to 60°C
Storage Temperature	-40°C to 70°C
Humidity	5% to 95% relative humidity, non-condensing
Light Levels	Daylight, 0-100,000Lux
Decoding Capability	1D:EAN-13,EAN-8,UPC-A,UPC-E,ISSN,ISBN,Codabar, Code 128(FNC1/FNC2/FNC3),Code 93,ITF-6,ITF-14, Interleaved 2 of 5,Industrial 2 of 5,Standard 2 of 5,Matrix 2 of 5, GS1 Databar(RSS-Expand,RSS-Limited,RSS-14),Code39 (Code 39 FULLASCII),Code 11,MSI-Plessey,Plessey,ect.

CMOS sensor, read fast barcode

The barcode of paper and electronic screen can be read

Easy to embed other applications



Scanner RSC 1105

2D Barcode scan Module