General Assembly

STUDY GUIDE

# STYLING TEXT WITH CSS

---

## Text Properties

### Color

To change the color of a bit of text, you can use:

- A word, for example, "red"
- A six-character **hex code**, for example, #f142a3 (every color has a unique hex code)
- A color's unique **RGB Value**, for example, rgb(226,28,35)

### Font Size

You can adjust a font's exact pixel size or its relative size.

- Pixel size
    - Indicate an exact pixel size, for example, 12px
- Relative size
    - Set the font size of one element, then change the size of other elements relative to that one using em.
    - Examples:
        - font-size: 0.5em will make the font half the size of other elements
        - font-size: 2em will make the font twice the size
- By default, some HTML elements are larger than others. <h1> is larger than <h2>, and so on, but you can still control the exact and relative size of those elements using the font-size property.

### Font Weight

Determines how thick the text is. You can alter this using one of two methods.

- font-weight: bold will make the text bold
- You can set the exact thickness by entering a number between 100 and 900 after font-weight.

### Font Style

font-style: italic will make text italic.

### Text Transform

- text-transform: uppercase sets all letters in a word to uppercase
- text-transform: lowercase sets all letters in a word to lowercase
- text-transform: capitalize will capitalize the first letter in each word

### Text Decoration

- text-decoration: underline will underline your text
- text-decoration: line-through will put a line through your text
- text-decoration: none will remove the default underline for hyperlinks

### Text Alignment

You can set the text-align property to left, right, or center.

### Lists

HTML lists come with default styling - ordered lists are numbered and unordered lists have solid round bullet points. To change these styles, use the list-style property.

- list-style: square will change the bullet points to squares
- list-style: circle will change bullet points to open circles
- list-style: none will remove the bullet points

### Fonts

#### Importing Fonts

- Fonts need to be imported from an external source.
- The external source will provide an import URL for each font.
- Paste the import URL at the top of your CSS style sheet, above all other rules. It should look like this: @import url('https://fonts.googleapis.com/css?family=Poiret+One');.
- You can import as many fonts as you like, but using multiple fonts may slow down your site.

#### Styling with Fonts

- To apply an imported font to an HTML element, use the font-family property, followed by the name of the font in quotes.
- Not all web browsers support all fonts. Always include a generic font family (serif or sans-serif) as a backup.

## Classes and IDs

You can apply style to individual elements using **IDs** (for example, just one <p> of many) or to groups of elements using **classes** (for example, all <h1> elements).

First, add IDs or classes in your HTML, then refer to them in your CSS style sheet. (You can give an element a class and an ID if you'd like.)

### IDs

- IDs must be unique - they can only be applied to one element.
- Use id in your HTML, refer to it in your CSS with a #.
    - Example: id="id-name" would be referred to as #id-name in CSS.

### Classes

- A class can be applied to several elements, which will be styled together.
- Use class in your HTML, then call it out in your CSS with a period.
    - Example: class="class-name" would be referred to as .class-name in CSS.