

Assignment 1: Detecting (Anti-)Patterns

Milan Lagae

Institution/University Name:

Faculty:

Course:

Vrije Universiteit Brussel

Sciences and Bioengineering Sciences

Software Quality Analysis

Contents

1	Intro	1
2	Discussion Point 1	2
2.1	Abstract & Extending	2
2.2	Checking methods	2
2.2.1	Abstract method	2
2.2.1.1	Method Body	2
2.2.1.2	Method Modifiers	2
2.2.2	Overriding method	3
2.2.2.1	Class	3
2.2.2.2	Method Body	3
2.2.2.3	Method Modifiers	3
2.2.3	Overrider & Template Method	3
2.2.3.1	Template Method	4
2.2.4	Algorithm Step	4
2.3	Results	5
3	Discussion Point 2	5
3.1	Comparison	5
3.2	Is Algorithm Step	5
4	Appendix	7
4.1	Discussion Point 1	7
	Bibliography	11

1 Intro

This report will discuss an implementation for the assignment “Assignment 3: Dataflow Analysis” for the course: Software Quality Analysis. The assigned pattern for this assignment is the Template Method pattern as described in [1] and [2]. All individual methods can be found in the Appendix section §4.

2 Discussion Point 1

This section will discuss the creating of a logic query in Ekeko for Discussion Point 1, executed on the DesignPatterns folder.

2.1 Abstract & Extending

The first step in the logic query is retrieving all abstract & extending classes (get-abstract-and-extending-classes), the complete method can be found in Listing 15.

The first step is retrieving all the ast nodes of type :TypeDeclaration and define this as the extending class. For each ast node, retrieve the type of the declaration and check if the ast-node is a class-type, shown in Listing 1.

```
1 (ast :TypeDeclaration ?extending)
2 (typedeclaration-type ?extending ?type)
3 (type|class ?type)
```

Listing 1: Extending class.

After the type of the ast-node is known to be a class-type, check that the extending class is not defined as an abstract class, Listing 2.

```
1 ; The extending class cannot both be abstract & have a super type
2 (has :modifiers ?extending ?modifiers-extending)
3 (modifier|abstract ?mod-abstract)
4 (fails (contains ?modifiers-extending ?mod-abstract))
```

Listing 2: Modifiers extending class.

2.2 Checking methods

The list of abstract and extending class, is refined by filtering the results based on methods defined on the pair of abstract & extending class. Filtering is performed on both classes, this action is done by the check-methods method, which can be found in full in Listing 16.

The core of the method is surrounded by the logic operations: one & all, declaring that one valid result is required and all operations must succeed for all declared. The list of method declarations in a class is retrieved by using the logic query: typedeclaration-method, it retrieves all the :bodyDeclarations (methods) in the body of the given class, it can be found in Listing 17

2.2.1 Abstract method

Validating the retrieved method is an abstract method is the next step in finding Template Method patterns, the complete method can be found in Listing 18.

2.2.1.1 Method Body

According to the pattern definition, the body of an abstract method must be empty. Java allows for multiple definitions of abstract methods as illustrated in Listing 3. Detecting these two different examples must be managed and are explained in Listing 4.

```
1 public abstract methodDefinition();
2 // or
3 public abstract methodDefinition() {};
```

Listing 3: Java method examples

The first type of empty body can be detected in a Ekeko logic query by checking if the body property of a method has the null type.

The other type of empty body declaration requires a bit more code. Starting with a fails check, the first case is excluded. Following that, the statements property is retrieved from the body of the method, which is the list of expressions inside the body of the method. The list of statements is transformed to its raw value using: value-raw. Finally, the list of statements is checked to be empty: (equals 0 (count ?raw)).

```
1 ; Get method body
2 (has :body ?abstract-method ?abstract-body)
3 ; Method body is null or has no statements
4 (conde
5   [(value|null ?abstract-body)]
6   [
7     (fails (value|null ?abstract-body))
8     (has :statements ?abstract-body ?stmts)
9     (value-raw ?stmts ?raw)
10    (equals 0 (count ?raw))])
11
```

Listing 4: Abstract body must be empty.

2.2.1.2 Method Modifiers

Continuing from the body of the methods, the next part is checking the list of modifiers on the respective methods in Listing 5. Following the pattern definition, there are two scenarios of possible modifier combinations for abstract methods:

- public & abstract
- protected.

The list of modifiers is retrieved, and the two scenarios are detected by using a conde.

```

1 ; Modifiers
2 (has :modifiers ?abstract-method ?modifiers)
3 ; Abstract method is public + abstract or protected
4 (conde
5 [
6 (modifier|public ?mod-public)
7 (contains ?modifiers ?mod-public)
8 (modifier|abstract ?mod-abstract)
9 (contains ?modifiers ?mod-abstract)])
10 [
11 (modifier|protected ?mod-protected)
12 (contains ?modifiers ?mod-protected)])
13

```

Listing 5: Abstract method, required modifiers.

That concludes the code required for checking if a method is an abstract method.

2.2.2 Overriding method

For each abstract method there is an associated overriding method, detecting such a method is done by the method: `is-overriding-method`, the full Implementation can be found in Listing 19.

Retrieving the connected overriding method with each abstract method is done by using the built Ekeko logic query: `(methoddeclaration-methoddeclaration|overrides ?abstract-method ?overriding-method)`. For either grounded value, Ekeko will retrieve the accompanying method, in this case the `overriding-method`.

2.2.2.1 Class

Each retrieved method is checked so that it belongs to the extending class found earlier. For this the `typedecclaration-method` defined earlier is reused, code can be found in Listing 6.

```

1 ; Get the overriding method from the abstract-method
2 (methoddeclaration-methoddeclaration|overrides ?abstract-
  method ?overriding-method)
3 ; Check if parent class is the same as the extending class of the
  abstract
4 (typedecclaration-method ?extending ?overriding-method)

```

Listing 6: Retrieving overriding method from abstract method.

2.2.2.2 Method Body

For each overriding method, it's body cannot be empty or null, the code for this can be found in Listing 7. Retrieve the body of the method using the `:body` property value. After the body is returned, check the body is not null by using a `fails`.

```

1 ; Overriding method body cannot be empty
2 (ast :MethodDeclaration ?overriding-method)
3 (has :body ?overriding-method ?overriding-body)
4 (fails (value|null ?overriding-body))

```

Listing 7: Checking body of overriding method.

2.2.2.3 Method Modifiers

The final check for the overriding method is checking the modifiers defined on the method, Listing 8. Retrieve the list of modifiers from the method using the `:modifiers` property value. Get the public modifier value from the `modifier|public` Ekeko built-in method. After that use `contains` to check for the presence of the public modifier in the list of modifiers.

```

1 ; Overriding method is public
2 (has :modifiers ?overriding-method ?modifiers)
3 (modifier|public ?mod-public)
4 (contains ?modifiers ?mod-public)

```

Listing 8: Checking list of modifiers on the overriding method.

2.2.3 Overriding & Template Method

This step checks if the `overriding-method` is present in the `template-method` of the `abstract-class`. Surround the query with a `one` for the `?template-method` value.

Retrieve a method declaration from the abstract class, first check if the name is not the same as the `abstract-method` retrieved earlier. This is done by retrieving the `:name` property on both respective methods. Proceed to check if comparison of name fails.

If that is the case, check if the method is a template method using `is-template-method`, the full code of the method can be found in Listing 21.

```

1 ; Check if the overrider method is present
2 ; in the template method of the abstract class
3 (one (fresh [?template-method]
4 (typedeclaration-method ?abstract ?template-method)
5 ; Template method does not equal abstract-method
6 (has :name ?template-method ?template-name)
7 (has :name ?abstract-method ?abstract-name)
8 (fails (name|simple-name|simple|same ?template-name ?
  abstract-name)))
9
10 ; Is template method
11 (is-template-method ?template-method ?template-body)
12
13 (is-algorithm-step ?template-body ?overrider-method)
14 ))

```

Listing 9: Validating template method & overrider method.

2.2.3.1 Template Method

The pattern definition declares a ‘Template Method’ to adhere to the following properties: must be a public method, no other modifiers are allowed; the body of the method must also not be empty. Since this is the method that defines the steps of the algorithm, which are the abstract methods defined earlier, and which are later overridden by methods in the extending class. The name of the implementation method is: `is-template-method` and can be found in full in Listing 21.

The first step of checking if a given method is a template method is by validating the list of modifiers, the method must be public and cannot contain any other modifiers, code can be found in Listing 10.

```

1 ; Public and non abstract
2 (has :modifiers ?template-method ?modifiers)
3
4 ; Public method
5 (modifier|public ?mod-public)
6 (contains ?modifiers ?mod-public)
7 ; Must be public method only
8 (value-raw ?modifiers ?raw)
9 (equals 1 (count ?raw))

```

Listing 10: Modifier check on the template method.

Retrieve the `:modifiers` property from the method using the `has` query. Retrieving a value for the public modifier using `modifier|public` to then check using `contains` if the value is present in the list of modifiers. The length of the list of modifiers is also checked to see if it’s length is 1, e.g: only contains the public modifier.

After the modifiers are checked, validating if the body of the method is not empty is in Listing 11.

```

1 ; Non empty body
2 (has :body ?template-method ?template-body)
3 (fails (value|null ?template-body))

```

Listing 11: Template method non-empty body.

Validating if a method is a template method in the sense is not complete without the next method named: `is-algorithm-step`.

2.2.4 Algorithm Step

Pattern definition declares that there must be at least one template method per pattern implementation [2]. Thus the purpose of this method named: `is-algorithm-step` which can be found in full in Listing 20, is to check the supposed template method for presence of each of the `abstract<=>overriding` method pair.

The method starts of with retrieving the name of the `overrider-method` method, the `:statements` property is also retrieved from the `template-body`, as illustrated in Listing 12.

```

1 ; Overrider method name
2 (has :name ?overrider-method ?overrider-name)
3 ; Extracts rhs method invocation from the body of the template
  method
4 (has :statements ?template-body ?stmts)

```

Listing 12: Method name & body statements.

Each statement in the list of statements is then iterated using `contains`, for each, the name of the invocation expression is compared with the name of the given `overrider-name`. The list of queries is surrounded with a `one`, indicating that at least one match for that particular method must be found in the body of the template method.

```

1 ; We need to at least have one match
2 (one (fresh [?stmt ?expression ?rhs ?inv-name]
3       ; Iterate each stmt
4       (contains ?stmts ?stmt)
5       ; Extract name
6       (has :expression ?stmt ?expression)
7       (has :rightHandSide ?expression ?rhs)
8       (has :name ?rhs ?inv-name)
9
10      ; 'Compare' with overrider method name
11      (name|simple-name|simple|same ?overrider-name ?inv-
12      name)
12 )

```

Listing 13: Comparing method name & invocation name in method body.

This completes the list of methods used for querying the Template Method pattern on the DesignPatterns folder.

2.3 Results

Executing the query as defined above, results in the following result defined in Figure 1.

Table	Columns	Tree
?abstract		?extending
DecoratedStringGenerator		FancyGenerator
DecoratedStringGenerator		SimpleGenerator

Figure 1: Discussion Point 1 - Result

All the expected results for the Template Method pattern in the DesignPatterns folder are present in the result of the query.

3 Discussion Point 2

Executing the query defined in Discussion Point 1, without modification on the JhotDraw folder, results in no results. To gather more results, part of the query was removed/ commented out.

3.1 Comparison

First start by removing the comparison query line in the is-algorithm-step method, namely: name|simple-name|simple|same, which can be found in Listing 14.

```

1 ; We need to at least have one match
2 (one (fresh [?stmt ?expression ?rhs ?inv-name]
3       (...))
4
5       ; 'Compare' with overrider method name
6       (name|simple-name|simple|same ?overrider-name ?inv-
7       name))

```

Listing 14: Comparing method name & invocation name in method body.

Executing the remaining query which this line removed results in the following as defined in Figure 2.

Table	Columns	Tree
?abstract		?extending
AbstractFigure		BorderDecorator
AbstractFigure		PertFigure
AbstractFigure		AnimationDecorator
AbstractFigure		PertDependency
AbstractFigure		RectangleFigure
AbstractFigure		PolygonFigure
AbstractFigure		PolyLineFigure
AbstractFigure		DecoratorFigure
AbstractFigure		TextFigure
AbstractFigure		LineFigure
AbstractFigure		NodeFigure
AbstractFigure		TriangleFigure
AbstractFigure		GroupFigure
AbstractFigure		StandardDrawing
AbstractFigure		EllipseFigure
AbstractFigure		ImageFigure
AbstractFigure		ElbowConnection
AbstractFigure		RoundRectangleFigure
AbstractFigure		LineConnection

Figure 2: Discussion Point 2 - Comparison Removed Result

The result already includes more of the expected patterns. When comparing with the expected results as defined in the xml file, all results regarding the: AttributeFigure are missing, and for the results regarding AbstractFigure, there is 1 false positive: DecoratorFigure and 3 missing implementations (DiamondFigure, NumberTextFigure, BouncingDrawing).

3.2 Is Algorithm Step

The purpose of the is-algorithm-step method was to check for the template-method in the abstract class of the pattern to

check for the overrider methods that are defined as the steps of the algorithm as explained in [2].

When removing the calling of the `is-algorithm-step` method from the logic query, more results are show, but include more false/positives. The results can be seen in Figure 3 & Figure 4.

Table	Columns	Tree
?abstract		?extending
Command		AlignCommand
ActionTool		BorderTool
AbstractFigure		BorderDecorator
Command		DeleteCommand
DecoratorFigure		AnimationDecorator
AbstractFigure		PertFigure
AbstractFigure		AnimationDecorator
AbstractFigure		PertDependency
AttributeFigure		RectangleFigure
AbstractFigure		RectangleFigure
AbstractFigure		PolygonFigure
AttributeFigure		PolygonFigure
Command		InsertImageCommand
Command		DuplicateCommand
AbstractFigure		PolyLineFigure
AbstractFigure		DecoratorFigure
Command		SendToBackCommand
AttributeFigure		TextFigure
AbstractFigure		TextFigure
Command		CopyCommand
AbstractHandle		ElbowHandle
PaletteButton		ToolButton
AbstractHandle		PolygonScaleHandle
AbstractFigure		LineFigure
AbstractHandle		RadiusHandle
Command		GroupCommand
AbstractFigure		NodeFigure
AbstractHandle		LocatorHandle

Figure 3: Discussion Point 2 - Result 1

Table	Columns	Tree
?abstract		?extending
AbstractHandle		ElbowHandle
PaletteButton		ToolButton
AbstractHandle		PolygonScaleHandle
AbstractFigure		LineFigure
AbstractHandle		RadiusHandle
Command		GroupCommand
AbstractFigure		NodeFigure
AbstractHandle		LocatorHandle
AbstractHandle		ChangeConnectionStartHandle
Command		ToggleGridCommand
AbstractHandle		TriangleRotationHandle
AbstractFigure		TriangleFigure
Command		PasteCommand
Command		CutCommand
Command		UngroupCommand
AbstractFigure		GroupFigure
AbstractFigure		StandardDrawing
AttributeFigure		EllipseFigure
AbstractFigure		EllipseFigure
AbstractFigure		ImageFigure
Command		ChangeAttributeCommand
Command		BringToFrontCommand
AbstractFigure		ElbowConnection
AttributeFigure		RoundRectangleFigure
AbstractFigure		RoundRectangleFigure
AbstractHandle		PolygonHandle
AbstractHandle		ChangeConnectionEndHandle
AbstractFigure		LineConnection

Figure 4: Discussion Point 2 - Result 2

Analysing the results when removing the method, is that more of the expected results are included, but also more false positives are included, mainly: `Command`, `AbstractHandle`, `PaletteButton` as the abstract classes, and their corresponding extending classes.

No further refined of the query was performed for discussion point 2.

4 Appendix

4.1 Discussion Point 1

clj

```
1 ; Abstract and extending classes
2 (defn get-abstract-and-extending-classes [?abstract ?extending]
3   (fresh [?type ?supertype ?modifiers-abstract ?mod-abstract ?modifiers-extending]
4
5     ; Intersection of abstract and extending class
6     (ast :TypeDeclaration ?extending)
7     (typeddeclaration-type ?extending ?type)
8     (type|class ?type)
9
10    ; The extending class cannot both be abstract & have a super type
11    (has :modifiers ?extending ?modifiers-extending)
12    (modifier|abstract ?mod-abstract)
13    (fails (contains ?modifiers-extending ?mod-abstract))
14
15    ; Get the supertype of the type
16    (type-type|super+ ?type ?supertype)
17
18    ; Abstract class
19    (type|class ?supertype)
20    (typeddeclaration-type ?abstract ?supertype)
21    (ast :TypeDeclaration ?abstract)
22
23    ; Abstract modifier
24    (has :modifiers ?abstract ?modifiers-abstract)
25    (contains ?modifiers-abstract ?mod-abstract)))
```

Listing 15: Method that retrieves a list of abstract and extending classes.

```

1 (defn check-methods [?abstract ?extending]
2   (fresh [?overrider-body ?overrider-method ?template-method ?abstract-method
3     ?template-body ?template-name ?abstract-name]
4
5     (one (all
6       ; Gets all the childs nodes of abstract class
7       (typedeclaration-method ?abstract ?abstract-method)
8       ; Abstract method
9       (is-abstract-method ?abstract-method)
10
11       ; Is overrider method?
12       (is-overriding-method ?abstract-method ?extending ?overrider-method)
13
14       ; Check if the overrider method is present
15       ; in the template method of the abstract class
16       (one (fresh [?template-method]
17         (typedeclaration-method ?abstract ?template-method)
18         ; Template method does not equal abstract-method
19         (has :name ?template-method ?template-name)
20         (has :name ?abstract-method ?abstract-name)
21         (fails (name|simple-name|simple|same ?template-name ?abstract-name))
22
23         ; Is template method
24         (is-template-method ?template-method ?template-body)
25
26         (is-algorithm-step ?template-body ?overrider-method)))))))

```

Listing 16: Method responsible for checking method declarations on the pair of abstract and extending class.

```

1 ; Method taken from WPO, get all method declarations
2 (defn typedeclaration-method [?class ?method]
3   (child :bodyDeclarations ?class ?method))

```

Listing 17: Retrieves all method declarations from a given class.


```

1  ; Is abstract method?
2  (defn is-abstract-method [?abstract-method]
3    (fresh [?abstract-body ?modifiers ?mod-abstract ?mod-public ?mod-protected ?stmts ?raw]
4      ; Method of the abstract class
5      (ast :MethodDeclaration ?abstract-method)
6
7      ; Get method body
8      (has :body ?abstract-method ?abstract-body)
9      ; Method body is null or has no statements
10     (conde
11       [(value|null ?abstract-body)]
12       [(fails (value|null ?abstract-body))
13        (has :statements ?abstract-body ?stmts)
14        (value-raw ?stmts ?raw)
15        (equals 0 (count ?raw))]))
16
17
18     ; Modifiers
19     (has :modifiers ?abstract-method ?modifiers)
20     ; Abstract method is public + abstract or protected
21     (conde
22       [(modifier|public ?mod-public)
23        (contains ?modifiers ?mod-public)
24        (modifier|abstract ?mod-abstract)
25        (contains ?modifiers ?mod-abstract)]
26       [(modifier|protected ?mod-protected)
27        (contains ?modifiers ?mod-protected)])))

```

Listing 18: Checks if the given method is an abstract method.

```

1  (defn is-overriding-method [?abstract-method ?extending ?overrider-method]
2    (fresh [?overrider-body ?abstract-body ?modifiers ?mod-public]
3      ; Get the overrider method from the abstract-method
4      (methoddeclaration-methoddeclaration|overrides ?abstract-method ?overrider-method)
5      ; Check if parent class is the same as the extending class of the abstract
6      (typeddeclaration-method ?extending ?overrider-method)
7
8      ; Overriding method body cannot be empty
9      (ast :MethodDeclaration ?overrider-method)
10     (has :body ?overrider-method ?overrider-body)
11     (fails (value|null ?overrider-body))
12
13     ; Overrider is public
14     (has :modifiers ?overrider-method ?modifiers)
15     (modifier|public ?mod-public)
16     (contains ?modifiers ?mod-public)))

```

Listing 19: Checks if the given method is an overriding method.

```

1 ; Check with algorithm step in template-body
2 (defn is-algorithm-step [?template-body ?overrider-method]
3   (fresh [?stmts ?overrider-name]
4
5     ; Overrider method name
6     (has :name ?overrider-method ?overrider-name)
7     ; Extracts rhs method invocation from the body of the template method
8     (has :statements ?template-body ?stmts)
9
10    ; We need to at least have one match
11    (one (fresh [?stmt ?expression ?rhs ?inv-name]
12              ; Iterate each stmt
13              (contains ?stmts ?stmt)
14              ; Extract name
15              (has :expression ?stmt ?expression)
16              (has :rightHandSide ?expression ?rhs)
17              (has :name ?rhs ?inv-name)
18
19              ; 'Compare' with overrider method name
20              (name|simple-name|simple|same ?overrider-name ?inv-name))))))

```

Listing 20: Checks the body of the template-method to see if the overrider method is invoked in the body of the method.

```

1 ; Is template method?
2 (defn is-template-method [?template-method ?template-body]
3   (fresh [?mod-abstract ?mod-public ?modifiers ?raw]
4     (ast :MethodDeclaration ?template-method)
5
6     ; Public and non abstract
7     (has :modifiers ?template-method ?modifiers)
8
9     ; Public method
10    (modifier|public ?mod-public)
11    (contains ?modifiers ?mod-public)
12    ; Must be public method only
13    (value-raw ?modifiers ?raw)
14    (equals 1 (count ?raw))
15
16    ; Non empty body
17    (has :body ?template-method ?template-body)
18    (fails (value|null ?template-body))))

```

Listing 21: Checks if the given body is a template method.

Bibliography

- [1] [Online]. Available: https://en.wikipedia.org/wiki/Template_method_pattern
- [2] R. J. J. V. Erich Gamma Richard Helm, *Design Patterns Elements of Reusable Object-Oriented Software*. Addison-Wesley, 1994.