To enable the user agent in the settings.py file for all requests and for the project:

```
# Crawl responsibly by identifying yourself (and your website) on the user-agent
USER_AGENT = "Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/148.0.0.0 Safari/537.36"
```

==========

To set **headers** and **other related scraping work**, we can use middleware.

==========

```
yield response.follow(
      book_url,
      callback=self.parse,
      headers = { "User-Agent": self.USER_AGENTS[random.randint(0, len(self.USER_AGENTS) - 1)]}
           )
```

==========

To create a specific feed for each spider, we can use **custom_settings**

In general, in the **settings.py** file, we can put:

```
FEEDS = {
    "booksdata.json": { 'format': 'json', 'overwrite': True }
}
```

==========

In web scraping projects, two main aspects to consider when making a request are cookie handling and headers.

==========

We can set the default headers for every request made in the scraper by setting the variable **DEFAULT_REQUEST_HEADERS** with a JSON that mimics real browser request headers.

==========

For cookie handling, Scrapy natively passes cookies from the initial request to the following ones, unless we explicitly set the value

```
COOKIES_ENABLED = False
```

always inside the **settings.py** file.

If we wish to monitor how cookies evolve from request to request, we can enable cookie debugging mode by adding to the same file also the variable

```
COOKIES_DEBUG = True
```

==========