

To use **Jest** when defining the type module in the **package.json** file:

1. Create the config file for the babel: **babel.config.cjs**
 - a. We can use any valid extension for the file.
2. Set the content of babel config file to:

```
module.exports = {  
  presets: [['@babel/preset-env', {targets: {node: 'current'}}]],  
};
```

3. Install the required modules for the **babel** with **Jest**:

```
{
  "name": "jobs-api-unit-testing",
  "version": "1.0.0",
  "type": "module",
  "description": "",
  "main": "app.js",
  "scripts": {
    "dev": "nodemon server.js",
    "test": "jest --watch",
    "coverage": "jest --coverage"
  },
  "author": "",
  "license": "ISC",
  "dependencies": {
    "aws-sdk": "^2.1253.0",
    "bcryptjs": "^2.4.3",
    "cookie-parser": "^1.4.6",
    "dotenv": "^16.0.3",
    "express": "^4.18.2",
    "express-fileupload": "^1.4.0",
    "jsonwebtoken": "^8.5.1",
    "mongoose": "^6.7.1",
    "nodemailer": "^6.8.0"
  },
  "devDependencies": {
    "@babel/core": "^7.29.0",
    "@babel/preset-env": "^7.29.2",
    "@types/jest": "^30.0.0",
    "babel-jest": "^30.3.0",
    "jest": "^30.3.0",
    "mongodb-memory-server": "^11.2.0",
    "nodemon": "^3.1.14",
    "supertest": "^7.2.2"
  }
}
```