

Week 5

on

Circular Linked List

Objective: In this lab, you will be working on problems related to a circular linked list. The objective is to create a circular single and double linked list and perform various operations such as **Insertion, Deletion, Traversal (displaying)**. You are required to implement the solutions using C language for the below questions.

Questions to be worked on in this lab:

1. Write a C program to perform the following operations on a circular single linked List:
 - a) **Insertion:** Create separate functions to **insert node at the beginning, middle, and the end of the circular single linked list.**
 - b) **Traverse:** Create a separate function to display the content of each node of the circular single linked list.

Solution:

Program1.c // This is the name of the c programming file

```
#include<stdio.h>
#include <stdlib.h>
struct node {
    int data;
    struct node *next;
};
struct node *head = NULL;
// Create a new node
struct node* CreateNode() {
    struct node *newNode = (struct node *)malloc(sizeof(struct node));
    if (newNode == NULL) {
        printf("Out of memory space\n");
        exit(0);
    }
    printf("Enter the value to be inserted: ");
    scanf("%d", &newNode->data);
    newNode->next = NULL;
    return newNode;
}
```

```

// Insert at beginning
void InsertAtBeginning() {
    struct node *newNode = CreateNode();
    if (head == NULL) {
        head = newNode;
        newNode->next = head;
    } else {
        struct node *temp = head;
        while (temp->next != head)
            temp = temp->next;
        newNode->next = head;
        temp->next = newNode;
        head = newNode;
    }
    printf("Node inserted at beginning.\n");
}

// Insert at end
void InsertAtEnd() {
    struct node *newNode = CreateNode();
    if (head == NULL) {
        head = newNode;
        newNode->next = head;
    } else {
        struct node *temp = head;
        while (temp->next != head)
            temp = temp->next;
        temp->next = newNode;
        newNode->next = head;
    }
    printf("Node inserted at end.\n");
}

// Insert at specific position
void InsertAtPosition(int pos) {
    int count = 1;
    struct node *newNode = CreateNode();
    if (pos == 1) {
        InsertAtBeginning();
        return;
    }
    struct node *temp = head;

```

```

while (count < pos - 1 && temp->next != head) {
    temp = temp->next;
    count++;
}
if (count == pos - 1) {
    newNode->next = temp->next;
    temp->next = newNode;
    printf("Node inserted at position %d.\n", pos);
} else {
    printf("Invalid position.\n");
    free(newNode);
}
}
// Display the list
void DisplayList() {
    if (head == NULL) {
        printf("List is empty.\n");
        return;
    }
    struct node *temp = head;
    printf("Circular Linked List contents:\n");
    do {
        printf(" %d ->", temp->data);
        temp = temp->next;
    } while (temp != head);
    printf(" (back to head)\n");
}
// Main function
int main() {
    int choice, pos;
    do {
        printf("\nMenu:\n");
        printf("1. Insert at Beginning\n");
        printf("2. Insert at End\n");
        printf("3. Insert at Position\n");
        printf("4. Display List\n");
        printf("5. Exit\n");
        printf("Enter your choice: ");
        scanf("%d", &choice);
        switch (choice) {

```

```

    case 1:
        InsertAtBeginning();
        break;
    case 2:
        InsertAtEnd();
        break;
    case 3:
        printf("Enter position to insert: ");
        scanf("%d", &pos);
        InsertAtPosition(pos);
        break;
    case 4:
        DisplayList();
        break;
    case 5:
        exit(0);
    default:
        printf("Invalid choice.\n");
}
} while (1);
return 0;
}

```

To Compile the above code, type below command as shown:

```
gccProgram1.c
```

To see the output, execute the following as shown:

```
./a.out
```

```
sivakumar@sivakumar:~/DS4$ gcc Program1.c
sivakumar@sivakumar:~/DS4$ ./a.out
```

Menu:

1. Insert at Beginning
2. Insert at End
3. Insert at Position
4. Display List
5. Exit

Enter your choice: 1

Enter the value to be inserted: 15

Node inserted at beginning.

Menu:

1. Insert at Beginning
2. Insert at End
3. Insert at Position
4. Display List
5. Exit

Enter your choice: 1

Enter the value to be inserted: 11

Node inserted at beginning.

Menu:

1. Insert at Beginning
2. Insert at End
3. Insert at Position
4. Display List
5. Exit

Enter your choice: 2

Enter the value to be inserted: 30

Node inserted at end.

Menu:

1. Insert at Beginning
2. Insert at End
3. Insert at Position
4. Display List
5. Exit

Enter your choice: 3

Enter position to insert: 2

Enter the value to be inserted: 22

Node inserted at position 2.

Menu:

1. Insert at Beginning
2. Insert at End
3. Insert at Position
4. Display List
5. Exit

Enter your choice: 4

Circular Linked List contents:

11 -> 15 -> 22 -> 30 -> (back to head)

Menu:

1. Insert at Beginning
2. Insert at End
3. Insert at Position
4. Display List
5. Exit

Enter your choice: 5

2. Write a C program to perform the following operations on double linked List. The below C Program is provided a insert function to insert as many nodes as the user wants. It also provided traverse function and the main function. Your task is to add a delete function to allow a user to delete a node from the beginning, middle and the end.

Solution:

Program2.c // This is the name of the c programming file

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
struct node {  
    int data;  
    struct node *next;  
};
```

```
struct node *head = NULL;
```

```
// Display the circular linked list
```

```
void DisplayList() {  
    struct node *temp = head;  
    if (head == NULL) {  
        printf("List is empty.\n");  
        return;  
    }
```

```
    struct node *start = head;  
    do {  
        printf(" %d\n", temp->data);  
        temp = temp->next;  
    } while (temp != start);  
}
```

```
// Create a circular linked list
```

```
void CreateList() {  
    char ch;
```

```

int i = 0;
struct node *nn, *last;

nn = (struct node *)malloc(sizeof(struct node));
if (nn == NULL) {
printf("No memory exists\n");
exit(0);
}

printf("Enter the value for node %d: ", i);
scanf("%d", &nn->data);
nn->next = nn;
head = nn;
last = nn;
i++;

printf("\nPress 'n' to quit or any other key to continue: ");
fflush(stdin);
ch = getchar();

while (ch != 'n') {
nn = (struct node *)malloc(sizeof(struct node));
if (nn == NULL) {
printf("No memory exists\n");
exit(0);
}

printf("Enter the value for node %d: ", i);
scanf("%d", &nn->data);
nn->next = head;
last->next = nn;
last = nn;
i++;

printf("\nPress 'n' to quit or any other key to continue: ");

```



```
fflush(stdin);
ch = getchar();
    }
}
```

```
// Delete from beginning
void DeleteBeginning() {
}
```

```
// Delete from end
void DeleteEnd() {
}
```

```
// Delete by position (middle)
void DeleteByPosition(int pos) {
}
```

```
int main() {
    int choice, val;
    CreateList();
```

```
    do {
        printf("\nMenu:\n");
        printf("1. Display List\n");
        printf("2. Delete from Beginning\n");
        printf("3. Delete from End\n");
        printf("4. Delete by Position\n");
        printf("5. Exit\n");
        printf("Enter your choice: ");
        scanf("%d", &choice);
```

```
        switch (choice) {
            case 1:
                DisplayList();
                break;
```

```

        case 2:
DeleteBeginning();
        break;
        case 3:
DeleteEnd();
        break;
        case 4:
printf("Enter position to delete: ");
scanf("%d", &val);
DeleteByPosition(val);
        break;
        case 5:
exit(0);
        default:
printf("Invalid choice.\n");
    }
} while (1);

return 0;
}

```

To Compile the above code, type below command as shown:

```
gccProgram1.c
```

To see the output, execute the following as shown after filling the code for deleting functions:

```
./a.out
```

Homework Problem for this week:

Note: Roll no and name is must for your solution sheet.

1. Write a C program to perform the following operations on a circular double linked List:
 - a) **Insertion:** Create separate functions to insert as many nodes as user wants and assign data (entered by a user) to these nodes.

- b) **Traverse:** Create a separate function to display the content of each node of the linked list.
- c) **Search:** Create separate function to search for a given value in the nodes of the list and display its position if it is found and else "Not Found".

Test Case:

1: Insert
2: Search
3: Traverse
4: Quit

Enter your choice: 1
Enter value: 55
Press 'n' to quit or any other key to continue: y
Enter value: 44
Press 'n' to quit or any other key to continue: y
Enter value: 66
Press 'n' to quit or any other key to continue: y
Enter value: 33
Press 'n' to quit or any other key to continue: n

1: Insert
2: Search
3: Traverse
4: Quit

Enter your choice: 3
Values of nodes in the linked list:
55 44 66 33

Enter your choice: 2
Enter value to search: 66
Value 66 found at position 3.

Enter your choice: 4

Note: Support each answer with an appropriate screenshot from your system. The above homework assignment will be evaluated for 2 marks.

Submission instructions and Deadline: Submit the source code along with the screenshots of output for the above two questions respectively in a single pdf document on G-Learn. The deadline for submission is **given on G-Learn**.