# DSLsofMath 2020: Assignment 1

Patrik Jansson and Sólrún Einardóttir and Víctor López Juan

# 1 DSLsofMath 2020: Assignment 1

In this assignment the focus is on the following three learning outcomes:

- organize areas of mathematics in DSL terms
- develop adequate notation for mathematical concepts
- discuss and compare different software implementations of mathematical concepts

## 1.1 DSLs, sets and von Neumann

In this assignment you will build up a domain-specific language (a DSL) for finite sets. The domain you should model is pure set theory where all members are sets.

Define a datatype  $TERM\ v$  for the abstract syntax of set expressions with variables of type v and a datatype  $PRED\ v$  for predicates over pure set expressions.

#### Part 1. TERM should have constructors for

- $\bullet$  the Empty set
- the one-element set constructor Singleton
- Union, and Intersection
  - you can also try *Powerset*
- set-valued variables ( $Var :: v \to TERM \ v$ )

PRED should have contructors for

- the two predicates *Elem*, *Subset*
- the logical connectives And, Or, Implies, Not

### Part 2. A possible semantic domain for pure sets is

```
newtype Set = S [Set]
```

Implement the evaluation functions

```
eval :: Eq \ v \Rightarrow Env \ v \ Set \rightarrow TERM \ v \rightarrow Set check :: Eq \ v \Rightarrow Env \ v \ Set \rightarrow PRED \ v \rightarrow Bool
```

**type**  $Env \ var \ dom = [(var, dom)]$ 

Note that the type parameter v to TERM is for the type of variables in the set expressions, not the type of elements of the sets. (You can think of pure set theory as "untyped" or "unityped".)

Part 3. The von Neumann encoding of natural numbers as sets is defined recursively as

```
vonNeumann\ 0 = Empty \\ vonNeumann\ (n+1) = Union\ (vonNeumann\ n) \\ (Singleton\ (vonNeumann\ n))
```

Implement vonNeumann and explore, explain and implement the following "pseudocode" claims as functions in Haskell:

```
\begin{array}{ll} \textit{claim1} \ \textit{n1} \ \textit{n2} = \{\text{- if } (\textit{n1} \leqslant \textit{n2}) \ \text{then } (\textit{n1} \subseteq \textit{n2}) \ \text{-} \} \\ \textit{claim2} \ \textit{n} &= \{\text{- } n = \{0,1,...,n-1\} \ \text{-} \} \end{array}
```

You need to insert some embeddings and types and you should use the eval and check functions. (For debugging it is useful to implement a show function for Set which uses numerals to show the von Neumann naturals.)

Admin:

- Submission: Assignments are to be submitted via Canvas
- Deadline: Tueday 2020-02-04
- Grading: Discussions with each of the teams during the slot 2020-02-10, 8.30-12 or 13.30-17

Note: The examination will be in English.