



ENGIN 604 INTRODUCTION TO PYTHON FOR FINANCE — FALL 2021

FINAL EXAM - SOLUTION

Due: 10:50am, Thursday, April 22

Submit to: engin604assignments@gmail.com

Maximum page limit: ∞ pages

Instructions

- The exam is **INDIVIDUAL**.
- You have from 9:30 am until 10:50 am (1 hour and 20 minutes) on Thursday, April 22, 2021 to work on and submit the exam.
- You must develop the exam in **A SINGLE Python SCRIPT** with extension **.py** and send it to engin604assignments@gmail.com before 10:50 am on Thursday, April 22, 2021. Any email sent after the deadline will be graded 1.0.
- The file name must be **Ex_RUT** without dots or hyphen.py. Example: if your RUT is 12.345.678-9, the file name must be **Ex_123456789.py**.
- The email subject must be **Final Exam + RUT** without dots or hyphen. Example: if your RUT is 12.345.678-9, the email subject must be **Final Exam 123456789**.
- Any question that involves a written answer must be answered as a comment in the **.py** file.
- If you have any doubt regarding the development of your exam, you may state your assumption as a comment in the **.py** file, whose relevance will be assessed at grading time. If you have any problem during the development of your exam, you may join the following Webex room: <https://fenuchile.webex.com/meet/gcabrerag>.
- **ONLY** the statements and solutions of the **GUIDES**, **HOMEWORK** and **TUTORIALS** may be used as support during the exam.
- Any sign of copying will be graded 1.0 and the actions stipulated in the **ZERO TOLERANCE FOR COPYING** rules of the Graduate School will be taken.

Questions

1. (10 points) A prime number is one that is only divisible by itself and the number 1. For example, the number 11 is a prime number because it is only divisible by 11 and by 1. In a list, show the prime numbers that exist between 1 and 100 (do not consider 1 as a prime number).

```
# list of numbers from 1 to 100
num1 = list(range(1,101))

# empty list
prime_numbers = []

# loop
for i in num1:
    if i > 1:
        num2 = []
        for j in range(2,i+1):
            if i % j == 0:
                num2.append(j)
        if len(num2) == 1:
            prime_numbers.append(i)
```

2. A bullet bond is one in which the issuer pays the bondholder coupons (interest payments) corresponding to each period and, at maturity (last period), the holder receives the coupon plus the principal (the face value of the bond). The mathematical formula would be:

$$P_B = \sum_{t=1}^{T-1} \frac{C}{(1+r)^t} + \frac{C + \text{Face Value}}{(1+r)^T}$$

Where P_B is the bond price, C the interest or coupon payment, T the number of periods and r the discount rate.

- a. (10 points) Generate an *array* containing a sequence of numbers from 0.02 to 0.4 (40 elements) where the distance between each number is 0.01.

```
# numpy is loaded
import numpy as np

# the array is created
num3 = np.array(list(range(2,41))) / 100
```

- b. (10 points) Using each element of the *array* generated in (a) as the discount rate (r), compute and store in a list the price of the bullet bond (P_B). Except for the discount rate (r), keep the following parameters constant:

Table 1: Bullet Bond Parameters

Parameter	Value
T	25 years
C	0.065
Face Value	100

The coupon payments are annual.

```
def bullet_bond_price(fv, t, cr, r):
    """
    Parameters
    -----
```

```

fv : Face value of the bullet bond (float).
t : Number of periods (float).
cr : Coupon interest rate (float).
r : Discount rate (float).
Returns
-----
Price of a bullet bond.
"""

pb = 0

for i in range(1,t+1):
    if i == t:
        pb += (fv * cr + fv) / (1 + r) ** i
    else:
        pb += (fv * cr) / (1 + r) ** i

return(pb)

# empty list
pb_k_list = []

# the bond price is computed and stored in a loop
for k in num3:
    pb_k = bullet_bond_price(100, 25, 0.065, k)
    pb_k_list.append(pb_k)

```

- c. (10 points) Plot the relationship between the bullet bond price (P_B) and the risk-free rate (r). What do you observe?


```

# pandas is loaded
import pandas as pd

# the DataFrame is created
df1 = pd.DataFrame(data = {'pb':pb_k_list}, index = num3)

# it is plotted
df1.plot(figsize=(8,3))

```



3. The monthly realized volatility of copper for month m is built as the square root of the sum of the squared daily log returns:

$$RV_t = \sqrt{\sum_{j=1}^{M_t} r_{j,t}^2}$$

Where M_t is the total number of business days in month m .

- a. (5 points) The file `copper_daily.xlsx` contains two sheets:
- `copper`: daily *spot* price of copper (`icopper`) from 2000-01-03 to 2019-12-31 (date).
 - `recession`: monthly business cycle of China (`chrec`) from 2000-01 to 2019-12 (year and month). 1 implies recession and 0 expansion.

Load the data into your workspace and compute the monthly realized volatility for copper. Remember to drop the NAs that arise when creating the log returns.

```
# loads the sheet with the daily price of copper in dollars
copper_daily = pd.read_excel('copper_daily.xlsx', sheet_name='copper')

# the date is added to the index
copper_daily.set_index('date', inplace=True)

# the log return is computed
copper_daily['logret'] = copper_daily.apply(lambda x: np.log(x / x.shift(1)))
# the na is dropped
copper_daily.dropna(inplace=True)

# the year column is created
copper_daily['year'] = copper_daily.index.year
# the month column is created
copper_daily['month'] = copper_daily.index.month

# the variable containing the copper price is dropped
copper_daily.drop(columns=['icopper'], axis=1, inplace=True)

# it is grouped by year and month, the squared return is computed and
# summed, creating one observation per month
copper_daily = copper_daily.groupby(['year', 'month'])['logret']. \
    apply(lambda x: np.sqrt(np.sum(x ** 2)))

# it is turned into a DataFrame and then the index (year and date)
# becomes a variable
rv_copper = copper_daily.to_frame().reset_index()

# the variable is renamed
rv_copper.rename(columns={'logret': 'log_rv_copper'}, inplace=True)
```

- b. (5 points) Merge the monthly realized volatility computed in (a) with the `rec` variable from the `recession` sheet.

```
# loads the sheet with the recessions
rec = pd.read_excel('copper_daily.xlsx', sheet_name='recession')

# the recession is merged with the price through a merge
rv_copper_with_rec = rv_copper.merge(rec, on=['year', 'month'])
```

- c. (10 points) Annualize¹ the monthly realized volatility created in (a) and then plot it, adding the 20-day rolling minimum and maximum (also of the annualized realized volatility). The expected result is the following:

```
# matplotlib is imported
import matplotlib.pyplot as plt

# variables are created
```


¹To annualize you must multiply by $\sqrt{12}$.

```

rv_copper_with_rec2 = rv_copper_with_rec.copy()
rv_copper_with_rec2['LogRV'] = rv_copper_with_rec2['log_rv_copper']. \
    apply(lambda x: x * np.sqrt(12) * 100)
rv_copper_with_rec2['Min'] = rv_copper_with_rec2['LogRV'].rolling(20).min()
rv_copper_with_rec2['Max'] = rv_copper_with_rec2['LogRV'].rolling(20).max()

# the annualized realized volatility is plotted
rv_copper_with_rec2.loc[:, ['Max', 'LogRV', 'Min']].plot(figsize=(8,3),
    style=['b:', 'r-', 'b:'])
plt.title("Annualized Copper Realized Volatility")
plt.ylabel("RV")

```



d. (10 points) Compute the descriptive statistics² of the monthly realized volatility for the periods where:

i. China was in recession (rec = 1)

```

# it is filtered by chrec == 0 and the descriptive statistics
# of the realized volatility are computed
rv_copper_with_rec[rv_copper_with_rec['chrec']==0].loc[:, 'log_rv_copper']. \
    describe()[['mean', 'std',
    'min', 'max']]

```

ii. China was in expansion (rec = 0)

```

# it is filtered by chrec == 1 and the descriptive statistics
# of the realized volatility are computed
rv_copper_with_rec[rv_copper_with_rec['chrec']==1].loc[:, 'log_rv_copper']. \
    describe()[['mean', 'std',
    'min', 'max']]

```

²You must only include mean, standard deviation, minimum value and maximum value.