

LISA Noise Curves - Consider Cornish and Robson arXiv 1803.01944v1 and Maggiore Chapter7

Bill Gabella 20180410

Refs:

Maggiore, *Gravitational Waves*, Chapter 7 Cornish and Robson, *The construction and use of LISA sensitivity curves*, arXiv 1803.01944v1




Some Points about our Exops


- Exop GW frequencies are low compared to either the round-trip time in a LISA arm (16.7 s) as a frequency, 60 mHz, or compared to f_star = c/(2pi L) which is 19.1 mHz.
 - Highest Exop GW frequency, see histogram in PrettyPlotsGWStrainEtc notebook, is XXXX
 - This puts us in the "LIGO Limit" where the LISA "signal response function of the instrument" (sky and polarization averaged) is the same at LIGO, \cal R = 1/5 per channel.
- Oh yeah, C&R say that there are two independent Michelson interferometer channels below f_star and three above f_star.
 - So you can multiply signal, usual \cal R, by 2 or 3.
 - That is Sky and Polarization averaged.
- Plot on following from GWStrainPlotsSNR notebook, currently last cell.



All Exop Modes and Cornish-Robson and Larson noise curves, 1 year and 4 year



All Exop Modes and Cornish-Robson 4 years



Questions

- Data presentation of histograms with a logarithmic x-scale...
 - is it cheating to make the histo evenly spaced in the log-x space?
- Cornish and Robson are very careful to re-write

$$\rho^2 = 4 \int \frac{|\tilde{h}(f)|^2}{P_n(f)} df$$

$$\rho^2 = 4 \int \frac{|\tilde{h}(f)|^2}{P_n(f)} df = 4 \int_{f=0}^{\infty} \frac{f |\tilde{h}(f)|^2}{P_n(f)} d(\ln f).$$
 (17)

coherently extract the signal. Rather than plotting the signal power directly (which often lies below the sensitivity curve), the convention is to plot $h_{\text{eff}}^2 = 16(2fT)S_h(f)/5$, to account for the boost we get from the coherent signal extraction.

C&R top page 7



Links


- Cornish and Robson, https://arxiv.org/abs/1803.01944
- aa



Backup



Gravitational Wave Spectrum





Strain from Exoplanets

Exoplanets RMS summed and LISA/eLISA Strain, 10 years strain

