Machine Design Homework 6

July 13, 2022

Gabe Morris

```
[1]:  # Notebook Preamble
      import sympy as sp
      import numpy as np
      import matplotlib.pyplot as plt

      plt.style.use('maroon_ipynb.mplstyle')
```

Contents

1 Problem 11-1

1.1 Given

Timken rates its bearings for 3000 hours at 500 rpm.

1.2 Find

Determine the catalog rating for a ball bearing running for 10,000 hours at 1800 rpm with a load of 2.75 kN with a reliability of 90%.

1.3 Solution

Use Eq. 11-3,

$$C_{10} = F_D \left(\frac{\mathcal{L}_D n_D 60}{\mathcal{L}_R n_R 60} \right)^{1/a}$$

```
[2]: FD = sp.S('2.75')
     nD = 1800
     LD = 10_000
     LR = 3_000
     nR = 500
     C10 = FD*(LD*nD*60/(LR*nR*60))**(1/sp.S(3))
     C10  # kN
```

[2]: 6.29592833404333

2 Problem 11-3

2.1 Given

An angular-contact, inner ring rotating, 02-series ball bearing is required for an application in which the life requirement is 40 kh at 520 rpm. The design radial load is 725 lbf. The application factor is 1.4. The reliability goal is 0.90.

2.2 Find

Find the multiple of rating life x_D required and the catalog rating C_{10} with which to enter Table 11–2. Choose a bearing and estimate the existing reliability in service.

2.3 Solution

With the assumed rating life (L_R) to be 10^6,

```
[3]: LD = 60*40_000*sp.S(520)
     LR = sp.S(1e6)
     xD = LD/LR
     xD
```

[3]:
1248.0

Use Eq. 11-9.

$$C_{10} = a_f F_D \left(\frac{x_D}{x_0 + (\theta - x_0)[\ln(1/R_D)]^{1/b}} \right)^{1/a}$$

```
[4]: # Weibull parameters
     x0, theta = sp.S('0.02'), sp.S('4.459')
     b = sp.S('1.483')

     a = sp.S(3)
     af = sp.S('1.4')
     FD = sp.S(725)
     RD = sp.S('0.9')
     c10 = af*FD*(xD/(x0 + (theta - x0)*(sp.log(1/RD))**(1/b)))**(1/a)
     c10  # lbf
```

[4]:
10952.2598806396

```
[5]: # Convert to kN
     C10_kN = c10*4.44822/1000
     C10_kN
```

[5]:

48.7180614462586

The bearing selection is the 02-60 mm bearing with $C_{10} = 55.9 \; kN$. The reliability may be estimated using Eq. 11-21.

$$R = \exp\left(-\left\{\frac{x_D \left(\frac{a_f F_D}{C_{10}}\right)^a - x_0}{\theta - x_0}\right\}^b\right)$$

[6]:
```python
# Getting the reliability
C10 = sp.S('55.9')
FD = FD*4.44822/1000
R = sp.exp(-((xD*(af*FD/C10)**a - x0)/(theta - x0))**b)
R
```

[6]: 0.945295510736457

3   Problem 11-9

3.1   Given

Two ball bearings from different manufacturers are being considered for a certain application. Bearing A has a catalog rating of 2.0 kN based on a catalog rating system of 3000 hours at 500 rpm. Bearing B has a catalog rating of 7.0 kN based on a catalog that rates at 10^6 cycles.

3.2   Find

For a given application, determine which bearing can carry the larger load.

3.3   Solution

We can calculate the catalog rating for bearing A based on a one million cycle load.

```
[7]:  FA = sp.S(2)
      LA = sp.S(3000)*sp.S(500)*60
      LR = sp.S(1e6)
      CA = (FA*(LA/LR)**sp.Rational(1, 3)).n()
      CA  # kN
```

[7]: 8.96280949311433

Bearing A is the better bearing because the catalog rating at one million revolutions is greater than the catalog rating of Bearing B, which is 7 kN.

4   Problem 11-15

4.1   Given