

Machine Design Homework 2

June 7, 2022

Gabe Morris

```
[1]: # Notebook Preamble
import sympy as sp
import numpy as np
import matplotlib.pyplot as plt
from IPython.display import display, Markdown


plt.style.use('maroon_ipynb.mplstyle')
```

Contents

1	Problem 3-39	3
1.1	Given	3
1.2	Find	3
1.3	Solution	3
2	Problem 62 Part A	6
2.1	Given	6
2.2	Find	6
2.3	Solution	6

1 Problem 3-39

1.1 Given




1.2 Find

For the beam above, find the maximum tensile stress due to M and the maximum shear stress due to V .

1.3 Solution

The free body diagram is,



```
[2]: # Getting reaction forces
Ay, By = sp.symbols('A_y B_y')
eq1 = sp.Eq(Ay + By, 1800)
eq2 = sp.Eq(200*Ay, 150*1800)

sol = sp.solve([eq1, eq2], dict=True)[0]
[display(eq) for eq in [eq1, eq2]]
```

```
display(Markdown('---'))

for key, value in sol.items():
    display(sp.Eq(key, value))
```


$$A_y + B_y = 1800$$

$$200A_y = 270000$$

$$A_y = 1350$$

$$B_y = 450$$

The shear and moment diagram is,



The maximum shear and tensile stress occur at $x = 100 \text{ mm}$.

```
[3]: # Calculating stress due to bending
M, c = 30_000, sp.S(0.025)
(M*c/(sp.pi/4*c**4)).n() # in Pa
```


```
[3]: 2444619925.89151
```

```
[4]: # Calculating the maximum shear stress
V = 750_000
(sp.Rational(4, 3)*V/(sp.pi*c**2)).n() # in Pa
```

```
[4]: 509295817.894065
```

2 Problem 62 Part A

2.1 Given



The tube is 36 *in* long.

2.2 Find

The maximum torque that can be applied and the corresponding angle of twist of the tube.

2.3 Solution

For thin-walled tubes,

$$\tau = \frac{T}{2A_m t}$$
$$\theta_1 = \frac{TL_m}{4GA_m^2 t}$$

See p. 129 for additional details of the above formulas.

```
[5]: # Calculating the maximum torque
tau_max = 12_000 # lbf in
t = sp.Rational(1, 16) # thickness in inches
Am = (1 - t)**2
T = tau_max*2*Am*t
T.n() # lbf in
```

[5]: 1318.359375

From table A-5, the modulus of rigidity is 11.5 *Mpsi*.

```
[6]: G = 11.5e6
      Lm = (1 - t)*4 # total length
      L = 36 # inches
      phi_1 = T*Lm/(4*G*Am**2*t)*L
      (phi_1*180/sp.pi).n() # in degrees
```

[6]: 4.59163394776145

The expression gets multiplied by L because θ_1 is the angle of twist per unit length.