

System Dynamics Homework 3

September 27, 2023

Gabe Morris

```
[1]: import control as ct
import matplotlib.pyplot as plt
import numpy as np
import sympy as sp
import pandas as pd


plt.style.use('../maroon_ipynb.mplstyle')
```

Contents

1	Problem 1	3
1.1	Given	3
1.2	Find	3
1.3	Solution	3
1.3.1	Part A	3
1.3.2	Part B	4
1.3.3	Part C	4
1.3.4	Part D	6
1.3.5	Part E	6

1 Problem 1

1.1 Given



$$m = 10 \text{ kg}$$

$$k_1 = 85 \text{ N/m}, k_2 = 30 \text{ N/m}$$

$$c_1 = 4 \text{ N} \cdot \text{s/m}, c_2 = 3 \text{ N} \cdot \text{s/m}$$

The input force $f(t)$ is in the `data.xlsx` file.

1.2 Find

Using the control package `tf()` function to get the forced response, find the following:

- The equation of motion for the system.
- The transfer function $X(s)/F(s)$.
- The forced response for the no noise data. Plot the input force and the response on separate axes.
- Repeat part c for the high frequency noise data.
- Repeat part c for the low frequency noise data.

1.3 Solution

1.3.1 Part A

```
[2]: t = sp.Symbol('t')
x = sp.Function('x')(t)
f = sp.Function('f')(t)

eq = sp.Eq(10*x.diff(t, 2), f - 85*x - 30*x - 4*x.diff() - 3*x.diff())
eq
```

[2]: $10 \frac{d^2}{dt^2} x(t) = f(t) - 115x(t) - 7 \frac{d}{dt} x(t)$

1.3.2 Part B

```
[3]: s = sp.Symbol('s')
eq_s = sp.Eq(
    sp.laplace_transform(eq.lhs, t, s)[0],
    sp.laplace_transform(eq.rhs, t, s)[0]
)
eq_s
```

[3]: $10s^2 \mathcal{L}_t[x(t)](s) - 10sx(0) - 10 \left. \frac{d}{dt} x(t) \right|_{t=0} = -7s \mathcal{L}_t[x(t)](s) + \mathcal{L}_t[f(t)](s) - 115 \mathcal{L}_t[x(t)](s) + 7x(0)$

```
[4]: eq_s = eq_s.subs([
    (x.subs(t, 0), 0),
    (x.diff().subs(t, 0), 0)
])
eq_s
```

[4]: $10s^2 \mathcal{L}_t[x(t)](s) = -7s \mathcal{L}_t[x(t)](s) + \mathcal{L}_t[f(t)](s) - 115 \mathcal{L}_t[x(t)](s)$

```
[5]: X = sp.solve(eq_s, sp.laplace_transform(x, t, s)[0])[0]
X
```

[5]: $\frac{\mathcal{L}_t[f(t)](s)}{10s^2 + 7s + 115}$

```
[6]: # Transfer function
sys1 = ct.tf(1, [10, 7, 115])
sys1
```

[6]:
$$\frac{1}{10s^2 + 7s + 115}$$

1.3.3 Part C

```
[7]: data = pd.read_excel('data.xlsx', sheet_name='Input Force Data')
data
```

```
[7]:
```

	Time (s)	High (N)	Low (N)	No Noise (N)
0	0.00000	-4.849845	1.076581	0.000000
1	0.02004	-1.574263	1.076581	0.400802
2	0.04008	-2.771360	1.076581	0.801603
3	0.06012	2.071162	1.076581	1.202405
4	0.08016	3.660872	1.076581	1.603206
..
495	9.91984	95.248337	95.648604	100.000000
496	9.93988	101.726636	95.648604	100.000000

```

497  9.95992  95.527882  95.648604  100.000000
498  9.97996 102.458740  95.648604  100.000000
499 10.00000 102.326431  95.648604  100.000000

```

[500 rows x 4 columns]

```


[8]: t, f_high, f_low, f_none = np.array(data['Time (s)']), np.array(data['High_
      ↪(N)']), np.array(data['Low (N)']), np.array(data['No Noise (N)'])
      _, x_none = ct.forced_response(sys1, T=t, U=f_none)

fig, ax = plt.subplots(nrows=1, ncols=2)
ax[0].set_xlabel('$t$ ($s$)')
ax[1].set_xlabel('$t$ ($s$)')
ax[0].set_ylabel('$x(t)$ ($m$)')
ax[1].set_ylabel('$f(t)$ ($N$)')

ax[1].plot(t, f_none, label='Input Force Data', color='black')
ax[0].plot(t, x_none, label='No Noise Response')

ax[0].legend()
ax[1].legend()
plt.show()

```




1.3.4 Part D

```
[9]: _, x_high = ct.forced_response(sys1, T=t, U=f_high)

fig, ax = plt.subplots(nrows=1, ncols=2)
ax[0].set_xlabel('$t$ ($s$)')
ax[1].set_xlabel('$t$ ($s$)')
ax[0].set_ylabel('$x(t)$ ($m$)')
ax[1].set_ylabel('$f(t)$ ($N$)')

ax[1].plot(t, f_high, label='Input Force Data', color='black')
ax[0].plot(t, x_none, label='No Noise Response', ls='--')
ax[0].plot(t, x_high, label='High Frequency Response')

ax[0].legend()
ax[1].legend()
plt.show()
```



1.3.5 Part E

```
[10]: _, x_low = ct.forced_response(sys1, T=t, U=f_low)

fig, ax = plt.subplots(nrows=1, ncols=2)
ax[0].set_xlabel('$t$ ($s$)')
ax[1].set_xlabel('$t$ ($s$)')
ax[0].set_ylabel('$x(t)$ ($m$)')
```

```

ax[1].set_ylabel('$f(t)$ ($N$)')

ax[1].plot(t, f_low, label='Input Force Data', color='black')
ax[0].plot(t, x_none, label='No Noise Response', ls='--')
ax[0].plot(t, x_low, label='Low Frequency Response')

ax[0].legend()
ax[1].legend()
plt.show()

```

