Buildroot

BASC2020 seminar

Giacomo Longo

University of Genoa

Q4 2020

BuildRoot



Official website: https://buildroot.org

- Born in 2005
- Entirely based on makefiles and kconfig
- Only one goal: *producing root file system images* for *100% custom Linux systems*

BuildRoot users

The most prominent users of BuildRoot are using it for building:

- IoT devices
- Automated factory controllers
- Point of sale devices
- Car multimedia units

Why BuildRoot

- Each buildroot is a 100% custom Linux "mini-distro"
- Buildroot images can be less than 100MB or even 10MB
- Complete customization of target architecture and build flags
- Multiple compiler / libc / system layout choices
- Updated every 3 months current version is 2020.08.1
- Easily extendable

Why BuildRoot: architecture support

$\approx$ 20 architectures supported

- ARC LE & BE
- **ARM** LE & BE
- AArch64 LE & BE
- csky
- **i386**
- Microblaze AXI & Non-AXI
- MIPS LE & BE
- MIPS64 LE & BE
- nds32
- Nios II
- PowerPC
- PowerPC64 LE & BE
- RISCV
- SuperH
- SPARC
- **x86_64**
- Xtensa

The BuildRoot process

What the user sees

1. Create a configuration file
2. Start the build
3. Flash the image on the device

What BuildRoot does

1. Build a cross compiler on our machine
2. Resolve the configuration dependencies
3. Compile from source the requested packages
4. Assemble an image

Prerequisites

Packages for an ARM BuildRoot

Ubuntu 20.04

```
sudo apt-get update
sudo apt-get install -y \
  curl tar \
  make \
  gcc g++ \
  libncurses-dev libssl-dev \
  qemu-user-static \
  qemu-system-arm
```

Others

Binaries needed

- Downloaders: curl & wget
- Extractor: tar
- Compilers: gcc & g++
- Libraries: ncurses & openssl
- Execution: QEMU system for ARM & QEMU static

Preparing our BuildRoot working directory

1. Clone the repository at
   `https://github.com/gabibbo97/basc-buildroot`
2. Enter the directory
3. Run `sh ./seminar-scripts/get-buildroot.sh`

Please use the provided script

The script downloads BuildRoot 2020.08.1 but also applies two required patches that we need for today's seminar

Creating an ARM cross compiler

Initial setup

1. `cd buildroot-2020.08.1`
2. `cp ../scripts/gef-python.sh ./gef-python.sh`
3. `chmod +x *.sh`
4. `make distclean`
5. `make defconfig`

Creating an ARM cross compiler

Configuration options: 1/2

`make menuconfig`

- Target options
  - Target Architecture = ARM (little endian)
  - Target Architecture Variant = cortex-A7
  - Floating point strategy = VFPv4-D16
- Build options
  - ☒ Enable compiler cache
  - ☒ build packages with debugging symbols
  - gcc debug level = debug level 3
  - ☐ strip target binaries
  - gcc optimization level = optimize for debugging

Creating an ARM cross compiler

Configuration options: 2/2

- Toolchain
  - C library = glibc
  - ☒ Enable C++ support
  - ☒ Build cross gdb for the host
  - ☒ TUI support
  - Python support = Python3
- System configuration
  - Custom scripts to run before creating filesystem images = ./gef-python.sh
- Filesystem images
  - ☐ tar the root filesystem
- Host utilities
  - host python3
  - ssl

Creating an ARM cross compiler

Performing the build

1. Save the configuration to the default `.config` path
2. Download sources with `make source`
3. Start the build with `make sdk`

Creating an ARM root filesystem

Initial setup

1. `cd buildroot-2020.08.1`
2. `cp ../scripts/gef-python.sh ./gef-python.sh`
3. `chmod +x *.sh`
4. `make distclean`
5. `make defconfig`

Creating an ARM root filesystem

Configuration options: 1/3

`make menuconfig`

- Target options
  - Target Architecture = ARM (little endian)
  - Target Architecture Variant = cortex-A7
  - Floating point strategy = VFPv4-D16
- Build options
  - ☒ Enable compiler cache
  - ☒ build packages with debugging symbols
  - gcc debug level = debug level 3
  - ☐ strip target binaries
  - gcc optimization level = optimize for debugging

Creating an ARM root filesystem

Configuration options: 2/3

- Toolchain
  - C library = glibc
  - ☒ Enable C++ support
  - ☒ Build cross gdb for the host
  - ☒ TUI support
  - Python support = Python3
- System configuration
  - Custom scripts to run before creating filesystem images = ./gef-python.sh
- Target packages
  - Debugging, profiling and benchmark
    - ☒ gdb
    - ☒ full debugger
    - ☒ gdbserver
    - ☒ TUI support

Creating an ARM root filesystem

Configuration options: 3/3

- Filesystem images
  - ☒ tar the root filesystem
- Host utilities
  - host python3
  - ssl

Creating an ARM root filesystem

Performing the build

1. Save the configuration to the default `.config` path
2. Download sources with `make source`
3. Start the build with `make`

1. `cd buildroot-2020.08.1`
2. `cp ../kconfigs/virtio.kconfig ./virtio.kconfig`
3. `cp ../scripts/gef-python.sh ./gef-python.sh`
4. `cp ../scripts/enable-ssh-root-login.sh ./enable-ssh-root-login.sh`
5. `chmod +x *.sh`
6. `make distclean`
7. `make defconfig`

Creating a bootable ARM root filesystem

Configuration options: 1/3

`make menuconfig`

- Target options
  - Target Architecture = ARM (little endian)
  - Target Architecture Variant = cortex-A7
  - Floating point strategy = VFPv4-D16
- Build options
  - ☒ Enable compiler cache
  - ☒ build packages with debugging symbols
  - gcc debug level = debug level 3
  - ☐ strip target binaries
  - gcc optimization level = optimize for debugging

Creating a bootable ARM root filesystem

Configuration options: 2/3

- Toolchain
  - C library = glibc
  - ☒ Enable C++ support
  - ☒ Build cross gdb for the host
  - ☒ TUI support
  - Python support = Python3
- System configuration
  - System hostname = BASC2020
  - System banner = Welcome to BASC2020 Buildroot
  - Root password = BASC2020
  - Network interface to configure through DHCP = eth0
  - Custom scripts to run before creating filesystem images = ./enable-ssh-root-login.sh ./gef-python.sh

Creating a bootable ARM root filesystem

Configuration options: 3/3

- Target packages
  - Debugging, profiling and benchmark
    - ☒ gdb
    - ☒ full debugger
    - ☒ gdbserver
    - ☒ TUI support
    - ☒ ltrace
    - ☒ strace
    - ☒ valgrind
  - Networking applications
    - ☒ openssh
    - ☐ client
    - ☒ key utilities
- Filesystem images
  - ☒ ext2/3/4 root filesystem
    - exact size = 512M
  - ☐ tar the root filesystem
- Host utilities
  - host python3
  - ssl

Creating an ARM root filesystem

Performing the build

1. Save the configuration to the default `.config` path
2. Download sources with `make source`
3. Start the build with `make`

Customizing our images

Build time overlay

- Create a directory
- Add `BR2_ROOTFS_OVERLAY=my-overlay` to `.config`
- Rebuild using `make`
- The structure of `my-overlay` will be copied to the rootfs

How to specify multiple overlays

Multiple overlays can be specified by separating them with spaces in the `BR2_ROOTFS_OVERLAY` directive

Customizing our images

Build time script

Add `BR2_ROOTFS_POST_BUILD_SCRIPT=my-script.sh` to `.config`
Available environment variables inside:

`BR2_CONFIG`	path of `.config`
`HOST_DIR`	path of `output/host`
`STAGING_DIR`	path of `output/staging`
`TARGET_DIR`	path of `output/target`
`BUILD_DIR`	path of `output/build`
`BINARIES_DIR`	path of `output/images`
`BASE_DIR`	path of `output`

How to specify multiple scripts

Multiple scripts can be specified by separating them with spaces in the `BR2_ROOTFS_POST_BUILD_SCRIPT` directive

Customizing our images

Editing the target directory

1. Add your files to the `output/target` directory
2. Rebuild using `make`

Warning

Your files might be rewritten / deleted by buildroot

Customizing our images

D.I.Y. approach

1. Unpack your rootfs (with `tar -xzf` for instance)
2. Perform your modifications
3. Repack your rootfs (with `tar -cf` for instance)

Using the cross-compiler

1. Extract the cross-compiler
2. Run `relocate-sdk.sh`
3. Edit your `$PATH` variable: `export PATH="$PATH:$PWD/bin"`
4. You can invoke your cross compiler with commands like `arm-buildroot-linux-gnueabihf-<COMMAND NAME>`
   Notable entries
   - `arm-buildroot-linux-gnueabihf-gcc`
   - `arm-buildroot-linux-gnueabihf-gdb`
   - `arm-buildroot-linux-gnueabihf-nm`

Improving gdb with library simbols

See the section ▸ Using gdb

Running dynamic executables in Docker

```
sudo docker import rootfs.tar basc-buildroot
sudo docker run --rm -it \
  --volume "$(which qemu-arm-static):/bin/qemu-arm-static" \
  --volume "${PWD}/:/host" \
  --entrypoint /bin/qemu-arm-static \
  --workdir "/host" \
  basc-buildroot \
  /bin/sh
```

Running dynamic executables with systemd-nspawn

```
mkdir -p basc-rootfs
tar -xf rootfs.tar -C basc-rootfs
cp -f "$(which qemu-arm-static)" \
  basc-rootfs/bin/qemu-arm-static
sudo systemd-nspawn \
  --register=no \
  -D basc-rootfs \
  /bin/qemu-arm-static /bin/sh
```

Package needed

You might need to install the package `systemd-container`

Booting the rootfs

```
qemu-system-arm \
  -machine virt \
  -cpu cortex-a7 \
  -smp 4 -m 4096 \
  -kernel zImage \
  -device virtio-blk-device,drive=rootfs \
  -drive file=rootfs.ext2,if=none,format=raw,id=rootfs \
  -append "console=ttyAMA0,115200 rootwait root=/dev/vda" \
  -netdev user,id=user0,hostfwd=tcp::2222-:22,hostfwd=tcp::1234-:1234 \
  -device virtio-net-device,netdev=user0 \
  -serial stdio \
  -display none
```

Opening an SSH session

```
ssh \
  -o UserKnownHostsFile=/dev/null \
  -o StrictHostKeyChecking=no \
  -p 2222 root@localhost
```

Sharing a folder

```
mkdir -p guest-os-ssh
sshfs root@localhost:/ ./guest-os-ssh \
  -f \
  -o port=2222 \
  -o reconnect \
  -o UserKnownHostsFile=/dev/null \
  -o StrictHostKeyChecking=no
```

Using {l,s,uf}trace

What did you expect?

- {l,s,uf}trace do work as expected
- Can only be performed on QEMU **system** emulation

Note that *ltrace* has a bug with unwinding of DWARF tables on ARM and will show limited information.

Using gdb

On the guest

`gdbserver :1234` *command to debug*

On the host (*From the cross-compiler extracted folder*)

```
bin/arm-buildroot-linux-gnueabihf-gdb \
  -x arm-buildroot-linux-gnueabihf/sysroot/usr/share/buildroot/gdbinit \
  executable name
```

On the host gdb shell attach with `target remote localhost:1234`