

Singleton services



Contents >

Providing a singleton service

Using providedIn

NgModule providers array

...

A singleton service is a service for which only one instance exists in an app.

For a sample app using the app-wide singleton service that this page describes, see the [live example](#) / [download example](#) showcasing all the documented features of NgModules.

Providing a singleton service

There are two ways to make a service a singleton in Angular:

- Set the `providedIn` property of the `@Injectable()` to "root".
- Include the service in the `AppModule` or in a module that is only imported by the `AppModule`

Using providedIn

Beginning with Angular 6.0, the preferred way to create a singleton service is to set `providedIn` to `root` on the service's `@Injectable()` decorator. This tells Angular to provide the service in the application root.

src/app/user.service.ts

```
import { Injectable } from '@angular/core';

@Injectable({
  providedIn: 'root',
})
export class UserService {
}
```



For more detailed information on services, see the [Services](#) chapter of the [Tour of Heroes tutorial](#).

NgModule providers array

In apps built with Angular versions prior to 6.0, services are registered NgModule providers arrays as follows:

```
@NgModule({
```



```
...
providers: [UserService],
...
})
```

If this NgModule were the root AppModule, the UserService would be a singleton and available throughout the app. Though you may see it coded this way, using the `providedIn` property of the `@Injectable()` decorator on the service itself is preferable as of Angular 6.0 as it makes your services tree-shakable.

The `forRoot()` pattern

Generally, you'll only need `providedIn` for providing services and `forRoot()/forChild()` for routing. However, understanding how `forRoot()` works to make sure a service is a singleton will inform your development at a deeper level.

If a module defines both providers and declarations (components, directives, pipes), then loading the module in multiple feature modules would duplicate the registration of the service. This could result in multiple service instances and the service would no longer behave as a singleton.

There are multiple ways to prevent this:

- Use the `providedIn` [syntax](#) instead of registering the service in the module.
- Separate your services into their own module.
- Define `forRoot()` and `forChild()` methods in the module.

Note: There are two example apps where you can see this scenario; the more advanced [NgModules live example](#), which contains `forRoot()` and `forChild()` in the routing modules and the `GreetingModule`, and the simpler [Lazy Loading live example](#). For an introductory explanation see the [Lazy Loading Feature Modules](#) guide.

Use `forRoot()` to separate providers from a module so you can import that module into the root module with `providers` and child modules without `providers`.

1. Create a static method `forRoot()` on the module.
2. Place the providers into the `forRoot()` method.

src/app/greeting/greeting.module.ts

```
static forRoot(config: UserServiceConfig): ModuleWithProviders<GreetingModule> {
  return {
    ngModule: GreetingModule,
    providers: [
      {provide: UserServiceConfig, useValue: config }
    ]
  }
}
```



```
};  
}
```

forRoot() and the Router

RouterModule provides the Router service, as well as router directives, such as RouterOutlet and routerLink. The root application module imports RouterModule so that the application has a Router and the root application components can access the router directives. Any feature modules must also import RouterModule so that their components can place router directives into their templates.

If the RouterModule didn't have forRoot() then each feature module would instantiate a new Router instance, which would break the application as there can only be one Router. By using the forRoot() method, the root application module imports RouterModule.forRoot(...) and gets a Router, and all feature modules import RouterModule.forChild(...) which does not instantiate another Router.

Note: If you have a module which has both providers and declarations, you *can* use this technique to separate them out and you may see this pattern in legacy apps. However, since Angular 6.0, the best practice for providing services is with the @Injectable() providedIn property.

How forRoot() works

forRoot() takes a service configuration object and returns a [ModuleWithProviders](#), which is a simple object with the following properties:

- ngModule: in this example, the GreetingModule class
- providers: the configured providers

In the [live example](#) / [download example](#) the root AppModule imports the GreetingModule and adds the providers to the AppModule providers. Specifically, Angular accumulates all imported providers before appending the items listed in @NgModule.providers. This sequence ensures that whatever you add explicitly to the AppModule providers takes precedence over the providers of imported modules.

The sample app imports GreetingModule and uses its forRoot() method one time, in AppModule. Registering it once like this prevents multiple instances.

You can also add a forRoot() method in the GreetingModule that configures the greeting UserService.

In the following example, the optional, injected UserServiceConfig extends the greeting UserService. If a UserServiceConfig exists, the UserService sets the user name from that config.

src/app/greeting/user.service.ts (constructor)

```
constructor(@Optional() config?: UserServiceConfig) {  
  if (config) { this._userName = config.userName; }  
}
```



Here's `forRoot()` that takes a `UserServiceConfig` object:

src/app/greeting/greeting.module.ts (forRoot)

```
static forRoot(config: UserServiceConfig): ModuleWithProviders<GreetingModule> {  
  return {  
    ngModule: GreetingModule,  
    providers: [  
      {provide: UserServiceConfig, useValue: config }  
    ]  
  };  
}
```

Lastly, call it within the `imports` list of the `AppModule`. In the following snippet, other parts of the file are left out. For the complete file, see the [live example](#) / [download example](#), or continue to the next section of this document.

src/app/app.module.ts (imports)

```
import { GreetingModule } from '../greeting/greeting.module';  
@NgModule({  
  imports: [  
    GreetingModule.forRoot({userName: 'Miss Marple'}),  
  ],  
})
```

The app displays "Miss Marple" as the user instead of the default "Sherlock Holmes".

Remember to import `GreetingModule` as a Javascript import at the top of the file and don't add it to more than one `@NgModule imports` list.

Prevent reimport of the GreetingModule

Only the root `AppModule` should import the `GreetingModule`. If a lazy-loaded module imports it too, the app can generate [multiple instances](#) of a service.

To guard against a lazy loaded module re-importing `GreetingModule`, add the following `GreetingModule` constructor.

src/app/greeting/greeting.module.ts

```
constructor(@Optional() @SkipSelf() parentModule?: GreetingModule) {  
  if (parentModule) {  
    throw new Error(  
      'GreetingModule is already loaded. Import it in the AppModule only');  
  }  
}
```

The constructor tells Angular to inject the `GreetingModule` into itself. The injection would be circular if Angular looked for `GreetingModule` in the *current* injector, but the `@SkipSelf()` decorator means "look for `GreetingModule` in an ancestor injector, above me in the injector hierarchy."

By default, the injector throws an error when it can't find a requested provider. The `@Optional()` decorator means not finding the service is OK. The injector returns `null`, the `parentModule` parameter is `null`, and the constructor concludes uneventfully.

It's a different story if you improperly import `GreetingModule` into a lazy loaded module such as `CustomersModule`.

Angular creates a lazy loaded module with its own injector, a child of the root injector. `@SkipSelf()` causes Angular to look for a `GreetingModule` in the parent injector, which this time is the root injector. Of course it finds the instance imported by the root `AppModule`. Now `parentModule` exists and the constructor throws the error.

Here are the two files in their entirety for reference:

app.module.ts

greeting.module.ts

```
import { BrowserModule } from '@angular/platform-browser';
import { NgModule } from '@angular/core';

/* App Root */
import { AppComponent } from './app.component';

/* Feature Modules */
import { ContactModule } from './contact/contact.module';
import { GreetingModule } from './greeting/greeting.module';

/* Routing Module */
import { AppRoutingModuleModule } from './app-routing.module';

@NgModule({
  imports: [
    BrowserModule,
    ContactModule,
    GreetingModule.forRoot({userName: 'Miss Marple'}),
    AppRoutingModuleModule
  ],
  declarations: [
    AppComponent
  ],
  bootstrap: [AppComponent]
})
export class AppModule { }
```

You may also be interested in:

- [Sharing Modules](#), which elaborates on the concepts covered on this page.
- [Lazy Loading Modules](#).
- [NgModule FAQ](#).

RESOURCES

[About](#)

[Resource Listing](#)

[Press Kit](#)

[Blog](#)

[Usage Analytics](#)

HELP

[Stack Overflow](#)

[Gitter](#)

[Report Issues](#)

[Code of Conduct](#)

COMMUNITY

[Events](#)

[Meetups](#)

[Twitter](#)

[GitHub](#)

[Contribute](#)

LANGUAGES

[简体中文版](#)

[正體中文版](#)

[日本語版](#)

[한국어](#)

Super-powered by Google ©2010-2020. Code licensed under an MIT-style License. Documentation licensed under CC BY 4.0.

Version 10.0.10-local+sha.84d1ba792b.