


```
ng update [options]
```



```
ng update @angular/cli @angular/core
```

To update from one major version to another, use the format `ng update @angular/cli@^<major_version> @angular/core@^<major_version>`.

```
ng update @angular/cli@^9 @angular/core@^9
```

Options

OPTION	DESCRIPTION
<code>--all=true false</code>	Whether to update all packages in package.json. Default: <code>false</code>
<code>--allowDirty=true false</code>	Whether to allow updating when the repository contains modified or untracked files.
<code>--createCommits=true false</code>	Create source control commits for updates and migrations. Default: <code>false</code> Aliases: <code>-C</code>
<code>--force=true false</code>	If false, will error out if installed packages are incompatible with the update. Default: <code>false</code>
<code>--from=from</code>	Version from which to migrate from. Only available with a single package being updated, and only on migration only.
<code>--help=true false json JSON</code>	Shows a help message for this command in the console. Default: <code>false</code>
<code>--migrateOnly=true false</code>	Only perform a migration, does not update the installed version.
<code>--next=true false</code>	Use the prerelease version, including beta and RCs. Default: <code>false</code>
<code>--packages</code>	The names of package(s) to update.
<code>--to=to</code>	Version up to which to apply migrations. Only available with a single package being updated, and only on migrations only. Requires from to be specified. Default to the installed version detected.
<code>--verbose=true false</code>	Display additional details about internal operations during execution. Default: <code>false</code>