

English is a STEM subject

tinyurl.com/SigmaCFG

Normative grammar is lame

- Normative grammar is concerned with the rules that make sentences “right” or “wrong”, developing a uniform “standard” language.
- These rules often don’t match spoken language varieties.
 - *Bob and me played Pokemon yesterday.
 - Bob and I played Pokemon yesterday.
 - *There’s a lot of people here.
 - There are a lot of people here.
 - The cat that the dog that the man fed chased meowed


Descriptive grammar doesn't make rules (kind of)

- Descriptive grammar aims at describing how a language actually behaves, and how speakers perceive sentences as ill-formed or not.
- Linguists are often concerned with descriptive grammars.
 - Yous are going to the party?
 - *Yous are went to the party?
 - There's a lot of people here.
 - *A lot are of people here.
 - *The cat that the dog that the man fed chased meowed.

Rules seem to be natural to language

- Speakers still perceive some new sentences as ill-formed. Why?
 - *This sentence ill-formed.
- Speakers can say novel, well-formed sentences. How?
 - This sentence is well-formed.
- The number of well-formed sentences is seemingly infinite. How?
 - This well-formed sentence was made for Sigma Camp 2025.
 - This well-formed sentence was made for Sigma Camp 2026.
 - This well-formed sentence was made for Sigma Camp 2027.
- → Generative grammar rules the structure (syntax) of sentences


Grammar is seemingly natural and biological




- Average Joe can learn a language, but his dog can't.
- Children learn languages despite a poverty of stimulus.
- Languages are seemingly too complex to be learned so quickly
- → (simple) Universal grammar

Summary: normative vs generative grammar


Normative grammar



Generative grammar



Comprehensive generative grammars can become weird...



HSPG feature structure by Lizmarie, Public domain,
via Wikimedia Commons

Context-free grammars


Lexicon is the dictionary, grammar is the rule

- A context-free grammar is composed of
 - A lexicon corresponding to a set of words with their classes
 - E.g. Noun → “dog”
 - A grammar consisting of rules of substitution, with start symbol S
 - E.g. Noun phrase → Article Adjective Noun
- Any sentence that can be generated (or parsed) by the grammar is well-formed with respect to it, and ill-formed otherwise.

(Parsing means to show how a sentence can be predicted by the rules)


Example: brackets

- Lexicon: $\{ [,] \}$
- Grammar:
 - $S \rightarrow S^+ S$
 - $S \rightarrow [(S)]$
- Example sentences:
 - $[]$
 - $[] []$
 - $[] [] [] []$
 - $*[] [] [] [] [] [$
 - $[] [] [] [] [] [] [] []$




Sisters side-by-side, parent dominates

- If a symbol X is directly above Y, then:
 - Y is the *daughter* of X
 - X *dominates* Y
 - X is the *parent* of Y
- Two symbols with the same parent are *sisters*



Example: brackets // ambiguity

- CFGs can be complex enough to convey ambiguity!
- Ambiguity shows up as different tree structures parsing the same sentence.
- Real languages are ambiguous, so this really is an advantage.



Example: brackets // the code

- As you can imagine, CFG sentence generation can easily be implemented by code
- Parsing is a slightly harder problem, and may need the rules to be re-written in simpler terms at the expense of conciseness
- [Python code](#) for generating well-formed bracket sentences:


```
def bracket(depth):  
    S = ""  
    if depth == 0:  
        return "[ ]"  
    if randint(0,1) % 2 == 0:  
        #first rule  
        length = randint(2, 3)  
        for i in range(length):  
            S += bracket(depth - 1)  
    else:  
        #second rule  
        S = " [ " + bracket(depth - 1) + " ] "  
    return S
```

Example: English

- Before jumping into English CFGs, we need to decide which types of words and phrases exist.
- It is useful to separate things into nonterminal and terminal symbols



Abstract classes:
NP \rightarrow Article + Noun



Lexical entries:
“dog”, “see”, “an”

Example: English // terminal symbols

- Terminal symbols can be grouped into standard grammatical classes
 - Noun = N \rightarrow “cat” | “woman” | “telescope” | “house”
 - Adjective = Adj \rightarrow “quick” | “slow”
 - Article = Art \rightarrow “the” | “a”
 - Preposition = Pr \rightarrow “with” | “in”
 - Verb = V \rightarrow “loves” | “sees” | “runs” | “walks”
 - Adverb = Adv \rightarrow “quickly” | “slowly”
 - Conjunction = Conj \rightarrow “and”

Example: English // nonterminal symbols

- Nonterminal symbols are less trivial. One can think of them as more complex, compound versions of the terminal symbols.
 - Noun phrase = NP \rightarrow Art Adj* N
 - Verb phrase = VP \rightarrow V (NP) (Adv)
 - Prepositional phrase = PP \rightarrow Pr NP
- They can also refer to each other
 - VP \rightarrow V PP
 - NP \rightarrow NP PP
 - NP \rightarrow NP Conj NP
 - S \rightarrow NP VP

a slow woman runs a quick house slowly

- $N \rightarrow \text{"cat"} \mid \text{"woman"} \mid \text{"telescope"} \mid \text{"house"}$
- $\text{Adj} \rightarrow \text{"quick"} \mid \text{"slow"}$
- $\text{Art} \rightarrow \text{"the"} \mid \text{"a"}$
- $\text{Pr} \rightarrow \text{"with"} \mid \text{"in"}$
- $V \rightarrow \text{"loves"} \mid \text{"sees"} \mid \text{"runs"} \mid \text{"walks"}$
- $\text{Adv} \rightarrow \text{"quickly"} \mid \text{"slowly"}$
- $\text{Conj} \rightarrow \text{"and"}$
- $\text{NP} \rightarrow \text{Art Adj}^* N$
- $\text{NP} \rightarrow \text{NP PP}$
- $\text{NP} \rightarrow \text{NP Conj NP}$
- $\text{VP} \rightarrow V (\text{NP}) (\text{PP}) (\text{Adv})$
- $\text{PP} \rightarrow \text{Pr NP}$

Example: English // code

- The code for our grammar is a bit long, but can also be easily implemented to generate “valid” sentences!
- [Python code](#)

```
from random import randint
lexicon = {"N":("cat ", "woman ", "telescope ", "house "), "Adj":("quick ", "slow "), "Art":("the ", "a
def sel(c):
    return lexicon[c][randint(0,len(lexicon[c])-1)]
def PP(depth):
    if depth == 0:
        return ""
    return sel("Pr") + NP(depth - 1)
def NP(depth):
    rule = randint(0, 2)
    if rule == 0 or depth == 0:
        return sel("Art") + randint(0,1)*sel("Adj") + randint(0, 1)*sel("Adj") + sel("N")
    elif rule == 1:
        return NP(depth - 1) + PP(depth-1)
    elif rule == 2:
        return NP(depth - 1) + sel("Conj") + NP(depth - 1)
def VP(depth):
    return sel("V") + randint(0,1)*NP(depth-1) + randint(0,1)*PP(depth - 1) + randint(0, 1)*sel("Adv")
def S(depth):
    return NP(depth - 1) + VP(depth - 1)
print(S(3))
```


Example: English // sample nice phrases

- A cat walks quickly
- The slow cat runs quickly
- The quick cat runs quickly
- The woman with the telescope loves the cat
- The woman walks in the telescope
- The woman walks the quick cat and the slow cat in the house

- $N \rightarrow \text{"cat"} \mid \text{"woman"} \mid \text{"telescope"} \mid \text{"house"}$
- $\text{Adj} \rightarrow \text{"quick"} \mid \text{"slow"}$
- $\text{Art} \rightarrow \text{"the"} \mid \text{"a"}$
- $\text{Pr} \rightarrow \text{"with"} \mid \text{"in"}$
- $\text{V} \rightarrow \text{"loves"} \mid \text{"sees"} \mid \text{"runs"} \mid \text{"walks"}$
- $\text{Adv} \rightarrow \text{"quickly"} \mid \text{"slowly"}$
- $\text{Conj} \rightarrow \text{"and"}$

- $\text{NP} \rightarrow \text{Art Adj}^* \text{N}$
- $\text{NP} \rightarrow \text{NP PP}$
- $\text{NP} \rightarrow \text{NP Conj NP}$
- $\text{VP} \rightarrow \text{V (NP) (PP) (Adv)}$
- $\text{PP} \rightarrow \text{Pr NP}$
- $\text{S} \rightarrow \text{NP VP}$


Example: English // ambiguity



- “With the telescope” is a daughter of VP
- The cat sees the woman *through* the telescope

- $NP \rightarrow \text{Art Adj}^* N$
- $NP \rightarrow NP PP$
- $NP \rightarrow NP \text{ Conj } NP$
- $VP \rightarrow V (NP) (PP) (\text{Adv})$
- $PP \rightarrow \text{Pr } NP$
- $S \rightarrow NP VP$

Example: English // ambiguity



- “With the telescope” is a daughter of NP
- The cat sees the woman, *who is* with the telescope

- $NP \rightarrow \text{Art Adj}^* N$
- $NP \rightarrow NP PP$
- $NP \rightarrow NP \text{ Conj } NP$
- $VP \rightarrow V (NP) (PP) (\text{Adv})$
- $PP \rightarrow \text{Pr } NP$
- $S \rightarrow NP VP$

Example: English // sample wrong phrases

- *The slow cat
- *Cat walks quickly
- *The woman sees the cat the telescope
- *The cat slowly loves the woman and the telescope
- *The woman walks quickly in the house

- $N \rightarrow \text{"cat"} \mid \text{"woman"} \mid \text{"telescope"} \mid \text{"house"}$
- $Adj \rightarrow \text{"quick"} \mid \text{"slow"}$
- $Art \rightarrow \text{"the"} \mid \text{"a"}$
- $Pr \rightarrow \text{"with"} \mid \text{"in"}$
- $V \rightarrow \text{"loves"} \mid \text{"sees"} \mid \text{"runs"} \mid \text{"walks"}$
- $Adv \rightarrow \text{"quickly"} \mid \text{"slowly"}$
- $Conj \rightarrow \text{"and"}$

- $NP \rightarrow Art\ Adj^* N$
- $NP \rightarrow NP\ PP$
- $NP \rightarrow NP\ Conj\ NP$
- $VP \rightarrow V\ (NP)\ (PP)\ (Adv)$
- $PP \rightarrow Pr\ NP$
- $S \rightarrow NP\ VP$

Example: English // our grammar is imperfect :(


- *Cat walks quickly
- The woman loves
- The woman and the cat walks slowly
- *The slow cat walks slowly and the quick cat runs quickly
- *The cats love the telescope

- $N \rightarrow \text{"cat"} \mid \text{"woman"} \mid \text{"telescope"} \mid \text{"house"}$
- $\text{Adj} \rightarrow \text{"quick"} \mid \text{"slow"}$
- $\text{Art} \rightarrow \text{"the"} \mid \text{"a"}$
- $\text{Pr} \rightarrow \text{"with"} \mid \text{"in"}$
- $\text{V} \rightarrow \text{"loves"} \mid \text{"sees"} \mid \text{"runs"} \mid \text{"walks"}$
- $\text{Adv} \rightarrow \text{"quickly"} \mid \text{"slowly"}$
- $\text{Conj} \rightarrow \text{"and"}$

- $\text{NP} \rightarrow \text{Art Adj}^* \text{N}$
- $\text{NP} \rightarrow \text{NP PP}$
- $\text{NP} \rightarrow \text{NP Conj NP}$
- $\text{VP} \rightarrow \text{V (NP) (PP) (Adv)}$
- $\text{PP} \rightarrow \text{Pr NP}$
- $\text{S} \rightarrow \text{NP VP}$

CFGs are insufficient for linguistics

- An attempt to make CFGs match natural languages soon makes them exceedingly convoluted and redundant
- More advanced theories are needed to model them well
 - Example: Head-driven phrase structure grammars (HSPGs)



Computer science can be helped by linguistics

- Linguistic insight can help with natural language processing (both generation and parsing)
- Generative grammars are also mathematical objects that can be studied on their own right, without reference to human languages
 - Often, the design of a programming language and of its compiler goes through many linguistic considerations.
 - For example, it is useful to design a language that avoids ambiguity.
 - It is also useful to design a compiler that “solves” the ambiguity!

Your turn!

Write a CFG capable of generating valid haikus

A valid haiku has three lines, with syllables following the 5-7-5 pattern.

Example:

An old silent pond . . .

A frog jumps into the pond,

splash! Silence again.