```
--
-- V1600D.my
-- MIB generated by MG-SOFT Visual MIB Builder Version 6.0  Build 88
-- Tuesday, September 01, 2015 at 08:41:32
--

      V1600D DEFINITIONS ::= BEGIN

            IMPORTS
                  enterprises, IpAddress, Integer32, Unsigned32, Gauge32,
                  Counter32, Counter64, OBJECT-TYPE, NOTIFICATION-TYPE
                        FROM SNMPv2-SMI

            RowStatus, TEXTUAL-CONVENTION
                  FROM SNMPv2-TC;


--
-- Node definitions
--

            -- 1.3.6.1.4.1.37950
            vsolution OBJECT IDENTIFIER ::= { enterprises 37950 }


            -- 1.3.6.1.4.1.37950.1
            business OBJECT IDENTIFIER ::= { vsolution 1 }


            -- 1.3.6.1.4.1.37950.1.1
            devices OBJECT IDENTIFIER ::= { business 1 }


            -- 1.3.6.1.4.1.37950.1.1.5
            v1600d OBJECT IDENTIFIER ::= { devices 5 }


            -- 1.3.6.1.4.1.37950.1.1.5.10
            v1600dSwitch OBJECT IDENTIFIER ::= { v1600d 10 }


            -- 1.3.6.1.4.1.37950.1.1.5.10.1
            v1600dPort OBJECT IDENTIFIER ::= { v1600dSwitch 1 }


            -- 1.3.6.1.4.1.37950.1.1.5.10.1.1
            upLinkPort OBJECT IDENTIFIER ::= { v1600dPort 1 }


            -- 1.3.6.1.4.1.37950.1.1.5.10.1.1.1
            uplinkPortConfigTable OBJECT-TYPE
                  SYNTAX SEQUENCE OF UplinkPortConfigEntry
                  MAX-ACCESS not-accessible
                  STATUS current
                  DESCRIPTION
                        "Description."
                  ::= { upLinkPort 1 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.1.1
uplinkPortConfigEntry OBJECT-TYPE
      SYNTAX UplinkPortConfigEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { upLinkPortIndex }
      ::= { uplinkPortConfigTable 1 }


UplinkPortConfigEntry ::=
      SEQUENCE {
            upLinkPortIndex
                  INTEGER,
            upLinkPortDescr
                  OCTET STRING,
            upLinkPortType
                  INTEGER,
            upLinkPortAdminStatus
                  INTEGER,
            upLinkPortAutoNegotiation
                  INTEGER,
            upLinkPortSpeed
                  INTEGER,
            upLinkPortDuplex
                  INTEGER,
            upLinkPortFlowControl
                  INTEGER,
            upLinkPortMacLearnEn
                  INTEGER,
            upLinkPortPriEn
                  INTEGER,
            upLinkPortPriValue
                  Integer32,
            upLinkPortIngressRate
                  INTEGER,
            upLinkPortEgressRate
                  INTEGER,
            upLinkPortBCStromCtrl
                  INTEGER,
            upLinkPortMCStromCtrl
                  INTEGER,
            upLinkPortUCStromCtrl
                  INTEGER,
            upLinkPortIsolate
                  INTEGER,
            upLinkPortPvid
                  INTEGER,
            uplinkPortJumboFrameEn
                  INTEGER,
            upLinkPortDescr2
                  OCTET STRING,
            uplinkPortHardwareSpeed
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.1.1.1
upLinkPortIndex OBJECT-TYPE
```

```
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortConfigEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.1.1.2
upLinkPortDescr OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortConfigEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.1.1.3
upLinkPortType OBJECT-TYPE
      SYNTAX INTEGER
            {
            fiber(0),
            copper(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortConfigEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.1.1.4
upLinkPortAdminStatus OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortConfigEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.1.1.5
upLinkPortAutoNegotiation OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortConfigEntry 5 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.1.1.6
upLinkPortSpeed OBJECT-TYPE
      SYNTAX INTEGER
            {
            auto(1),
            s10M(2),
            s100M(3),
            s1000M(4)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      DEFVAL { 1 }
      ::= { uplinkPortConfigEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.1.1.7
upLinkPortDuplex OBJECT-TYPE
      SYNTAX INTEGER
            {
            auto(1),
            full(2),
            half(3)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      DEFVAL { 1 }
      ::= { uplinkPortConfigEntry 7 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.1.1.8
upLinkPortFlowControl OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortConfigEntry 8 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.1.1.9
upLinkPortMacLearnEn OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { uplinkPortConfigEntry 9 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.1.1.10
upLinkPortPriEn OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortConfigEntry 10 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.1.1.11
upLinkPortPriValue OBJECT-TYPE
      SYNTAX Integer32 (0..7)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortConfigEntry 11 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.1.1.12
upLinkPortIngressRate OBJECT-TYPE
      SYNTAX INTEGER (0 | 64..1000000)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      DEFVAL { 0 }
      ::= { uplinkPortConfigEntry 12 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.1.1.13
upLinkPortEgressRate OBJECT-TYPE
      SYNTAX INTEGER (0 | 64..1000000)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      DEFVAL { 0 }
      ::= { uplinkPortConfigEntry 13 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.1.1.14
upLinkPortBCStromCtrl OBJECT-TYPE
      SYNTAX INTEGER (0 | 64..1000000)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortConfigEntry 14 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.1.1.15
upLinkPortMCStromCtrl OBJECT-TYPE
      SYNTAX INTEGER (0 | 64..1000000)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortConfigEntry 15 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.1.1.16
upLinkPortUCStromCtrl OBJECT-TYPE
      SYNTAX INTEGER (0 | 64..1000000)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortConfigEntry 16 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.1.1.17
upLinkPortIsolate OBJECT-TYPE
      SYNTAX INTEGER
            {
            no_isolate(0),
            isolate(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortConfigEntry 17 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.1.1.18
upLinkPortPvid OBJECT-TYPE
      SYNTAX INTEGER (1..4096)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortConfigEntry 18 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.1.1.19
uplinkPortJumboFrameEn OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortConfigEntry 19 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.1.1.20
```

```
upLinkPortDescr2 OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortConfigEntry 20 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.1.1.21
uplinkPortHardwareSpeed OBJECT-TYPE
      SYNTAX INTEGER
            {
            GE(0),
            GE10(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortConfigEntry 21 }

-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.2
uplinkPortPerformanceDataTable OBJECT-TYPE
      SYNTAX SEQUENCE OF UplinkPortPerformanceDataEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { upLinkPort 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.2.1
uplinkPortPerformanceDataEntry OBJECT-TYPE
      SYNTAX UplinkPortPerformanceDataEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { upLinkPIndex }
      ::= { uplinkPortPerformanceDataTable 1 }


UplinkPortPerformanceDataEntry ::=
      SEQUENCE {
            upLinkPIndex
                  INTEGER,
            upLinkPortDownOctets
                  Counter32,
            upLinkDownSpeed
                  Counter32,
            upLinkPortDownMaxBand
                  Counter32,
            upLinkPortDownProportion
                  Counter32,
            upLinkPortDownUcastPkts
                  Counter32,
            upLinkPortDownMulicastPkts
                  Counter32,
```

```
upLinkPortDownBrocastPkts
      Counter32,
upLinkPortDownPackets
      Counter32,
upLinkPortDownNormalOctets
      Counter32,
upLinkPortDownErrOctets
      Counter32,
upLinkPortDownPausePkts
      Counter32,
upLinkPortUpOctets
      Counter32,
upLinkPortUpSpeed
      Counter32,
upLinkPortUpMaxBand
      Counter32,
upLinkPortUpProportion
      Counter32,
upLinkPortUpUcastPkts
      Counter32,
upLinkPortUpMulicastPkts
      Counter32,
upLinkPortUpBrocastPkts
      Counter32,
upLinkPortUpPackets
      Counter32,
upLinkPortUpNormalOctets
      Counter32,
upLinkPortUpErrOctets
      Counter32,
upLinkPortUpPausePkts
      Counter32,
upLinkPortDroppedPkts
      Counter32,
upLinkPortCrcError
      Counter32,
upLinkPortJabber
      Counter32,
upLinkPortOverSize
      Counter32,
upLinkPortUnderSize
      Counter32,
upLinkPortCollision
      Counter32,
upLinkPort64OctetFrames
      Counter32,
upLinkPort65To127OctetFrames
      Counter32,
upLinkPort128To255OctetFrames
      Counter32,
upLinkPort256To511OctetFrames
      Counter32,
upLinkPort512To1023OctetFrames
      Counter32,
upLinkPortOver1024OctetFrames
      Counter32,
uplinkPortDownBytes
      Counter64,
uplinkPortUpBytes
```

```
                  Counter64
       }

-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.2.1.1
upLinkPIndex OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortPerformanceDataEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.2.1.2
upLinkPortDownOctets OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortPerformanceDataEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.2.1.3
upLinkDownSpeed OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortPerformanceDataEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.2.1.4
upLinkPortDownMaxBand OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortPerformanceDataEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.2.1.5
upLinkPortDownProportion OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortPerformanceDataEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.2.1.6
upLinkPortDownUcastPkts OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
```

```
            "Description."
      ::= { uplinkPortPerformanceDataEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.2.1.7
upLinkPortDownMulicastPkts OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortPerformanceDataEntry 7 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.2.1.8
upLinkPortDownBrocastPkts OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortPerformanceDataEntry 8 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.2.1.9
upLinkPortDownPackets OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortPerformanceDataEntry 9 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.2.1.10
upLinkPortDownNormalOctets OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortPerformanceDataEntry 10 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.2.1.11
upLinkPortDownErrOctets OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortPerformanceDataEntry 11 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.2.1.12
upLinkPortDownPausePkts OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
```

```
      DESCRIPTION
            "Description."
      ::= { uplinkPortPerformanceDataEntry 12 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.2.1.13
upLinkPortUpOctets OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortPerformanceDataEntry 13 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.2.1.14
upLinkPortUpSpeed OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortPerformanceDataEntry 14 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.2.1.15
upLinkPortUpMaxBand OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortPerformanceDataEntry 15 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.2.1.16
upLinkPortUpProportion OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortPerformanceDataEntry 16 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.2.1.17
upLinkPortUpUcastPkts OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortPerformanceDataEntry 17 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.2.1.18
upLinkPortUpMulicastPkts OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
```

```
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortPerformanceDataEntry 18 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.2.1.19
upLinkPortUpBrocastPkts OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortPerformanceDataEntry 19 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.2.1.20
upLinkPortUpPackets OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortPerformanceDataEntry 20 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.2.1.21
upLinkPortUpNormalOctets OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortPerformanceDataEntry 21 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.2.1.22
upLinkPortUpErrOctets OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortPerformanceDataEntry 22 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.2.1.23
upLinkPortUpPausePkts OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortPerformanceDataEntry 23 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.2.1.24
upLinkPortDroppedPkts OBJECT-TYPE
      SYNTAX Counter32
```

```
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortPerformanceDataEntry 24 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.2.1.25
upLinkPortCrcError OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortPerformanceDataEntry 25 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.2.1.26
upLinkPortJabber OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortPerformanceDataEntry 26 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.2.1.27
upLinkPortOverSize OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortPerformanceDataEntry 27 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.2.1.28
upLinkPortUnderSize OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortPerformanceDataEntry 28 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.2.1.29
upLinkPortCollision OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortPerformanceDataEntry 29 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.2.1.30
upLinkPort64OctetFrames OBJECT-TYPE
```

```
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortPerformanceDataEntry 30 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.2.1.31
upLinkPort65To127OctetFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortPerformanceDataEntry 31 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.2.1.32
upLinkPort128To255OctetFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortPerformanceDataEntry 32 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.2.1.33
upLinkPort256To511OctetFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortPerformanceDataEntry 33 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.2.1.34
upLinkPort512To1023OctetFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortPerformanceDataEntry 34 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.2.1.35
upLinkPortOver1024OctetFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortPerformanceDataEntry 35 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.2.1.36
```

```
uplinkPortDownBytes OBJECT-TYPE
      SYNTAX Counter64
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortPerformanceDataEntry 36 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.2.1.37
uplinkPortUpBytes OBJECT-TYPE
      SYNTAX Counter64
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortPerformanceDataEntry 37 }

-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.3
uplinkPortLinkTable OBJECT-TYPE
      SYNTAX SEQUENCE OF UplinkPortLinkEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { upLinkPort 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.3.1
uplinkPortLinkEntry OBJECT-TYPE
      SYNTAX UplinkPortLinkEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { portNumIndex }
      ::= { uplinkPortLinkTable 1 }


UplinkPortLinkEntry ::=
      SEQUENCE {
            portNumIndex
                  INTEGER,
            portLinkStatus
                  INTEGER,
            uplinkPortLinkSpeed
                  OCTET STRING
       }

-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.3.1.1
portNumIndex OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortLinkEntry 1 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.3.1.2
portLinkStatus OBJECT-TYPE
      SYNTAX INTEGER
            {
            down(0),
            up(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortLinkEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.3.1.3
uplinkPortLinkSpeed OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortLinkEntry 3 }

-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.4
uplinkPortPerfThresholdTable OBJECT-TYPE
      SYNTAX SEQUENCE OF UplinkPortPerfThresholdEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { upLinkPort 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.4.1
uplinkPortPerfThresholdEntry OBJECT-TYPE
      SYNTAX UplinkPortPerfThresholdEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { porIndex }
      ::= { uplinkPortPerfThresholdTable 1 }


UplinkPortPerfThresholdEntry ::=
      SEQUENCE {
            porIndex
                  INTEGER,
            uplinkPortCRCThreshold
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.4.1.1
porIndex OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { uplinkPortPerfThresholdEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.1.4.1.2
uplinkPortCRCThreshold OBJECT-TYPE
      SYNTAX INTEGER
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uplinkPortPerfThresholdEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2
ponPort OBJECT IDENTIFIER ::= { v1600dPort 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.1
ponPortConfigTable OBJECT-TYPE
      SYNTAX SEQUENCE OF PonPortConfigEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPort 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.1.1
ponPortConfigEntry OBJECT-TYPE
      SYNTAX PonPortConfigEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { ponPortIndex }
      ::= { ponPortConfigTable 1 }


PonPortConfigEntry ::=
      SEQUENCE {
            ponPortIndex
                  INTEGER,
            ponPortDescr
                  OCTET STRING,
            ponPortAdminStatus
                  INTEGER,
            ponPortFlowControl
                  INTEGER,
            ponPortIngressRate
                  INTEGER,
            ponPortEgressRate
                  INTEGER,
            ponPortBCStormCtrl
                  INTEGER,
            ponPortMCStromCtrl
                  INTEGER,
            ponPortUCStromCtrl
                  INTEGER,
            ponPortPriValue
```

```
                  Integer32,
            ponPortPvid
                  INTEGER,
            ponPortIsolate
                  INTEGER,
            ponPortJumboFrameEn
                  INTEGER,
            ponPortDescr2
                  OCTET STRING
       }

-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.1.1.1
ponPortIndex OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortConfigEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.1.1.2
ponPortDescr OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortConfigEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.1.1.3
ponPortAdminStatus OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortConfigEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.1.1.4
ponPortFlowControl OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortConfigEntry 4 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.1.1.5
ponPortIngressRate OBJECT-TYPE
      SYNTAX INTEGER (0 | 64..1000000)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortConfigEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.1.1.6
ponPortEgressRate OBJECT-TYPE
      SYNTAX INTEGER (0 | 64..1000000)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortConfigEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.1.1.7
ponPortBCStormCtrl OBJECT-TYPE
      SYNTAX INTEGER (0 | 64..1000000)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortConfigEntry 7 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.1.1.8
ponPortMCStromCtrl OBJECT-TYPE
      SYNTAX INTEGER (0 | 64..1000000)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortConfigEntry 8 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.1.1.9
ponPortUCStromCtrl OBJECT-TYPE
      SYNTAX INTEGER (0 | 64..1000000)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortConfigEntry 9 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.1.1.10
ponPortPriValue OBJECT-TYPE
      SYNTAX Integer32 (0..7)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortConfigEntry 10 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.1.1.11
ponPortPvid OBJECT-TYPE
      SYNTAX INTEGER (1..4096)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortConfigEntry 11 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.1.1.12
ponPortIsolate OBJECT-TYPE
      SYNTAX INTEGER
            {
            no_isolate(0),
            isolate(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortConfigEntry 12 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.1.1.13
ponPortJumboFrameEn OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortConfigEntry 13 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.1.1.14
ponPortDescr2 OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortConfigEntry 14 }

-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.2
ponPortPerformanceDataTable OBJECT-TYPE
      SYNTAX SEQUENCE OF PonPortPerformanceDataEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPort 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.2.1
```

```
ponPortPerformanceDataEntry OBJECT-TYPE
      SYNTAX PonPortPerformanceDataEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { ponPIndex }
      ::= { ponPortPerformanceDataTable 1 }


PonPortPerformanceDataEntry ::=
      SEQUENCE {
            ponPIndex
                  INTEGER,
            ponPortUpOctets
                  Counter32,
            ponPortUpSpeed
                  Counter32,
            ponPortUpMaxBand
                  Counter32,
            ponPortUpProportion
                  Counter32,
            ponPortUpMPCP
                  Counter32,
            ponPortTotalFrames
                  Counter32,
            ponPortUpUnicastFrames
                  Counter32,
            ponPortUpBroadcastFrames
                  Counter32,
            ponPortUpMulticastFrames
                  Counter32,
            ponPortUpCrc32Errors
                  Counter32,
            ponPortUpUndersizeFrames
                  Counter32,
            ponPortUpOversizeFrames
                  Counter32,
            ponPortUpCollisions
                  Counter32,
            ponPortUpFramesDropped
                  Counter32,
            ponPortUp64OctetFrames
                  Counter32,
            ponPortUp65To127OctetFrames
                  Counter32,
            ponPortUp128To255OctetFrames
                  Counter32,
            ponPortUp256To511OctetFrames
                  Counter32,
            ponPortUp512To1023OctetFrames
                  Counter32,
            ponPortUp1024To1518OctetFrames
                  Counter32,
            ponPortUpOver1519OctetFrames
                  Counter32,
            ponPortDownOctets
                  Counter32,
            ponPortDownSpeed
```

```
                Counter32,
            ponPortDownMaxband
                Counter32,
            ponPortDownproportion
                Counter32,
            ponPortDownMPCP
                Counter32,
            ponPortDownTotalFrames
                Counter32,
            ponPortDownUnicastFrames
                Counter32,
            ponPortDownBroadcastFrames
                Counter32,
            ponPortDownMulticastFrames
                Counter32,
            ponPortDownCrc32Errors
                Counter32,
            ponPortDownUndersizeFrames
                Counter32,
            ponPortDownOversizeFrames
                Counter32,
            ponPortDownCollisions
                Counter32,
            ponPortDownFramesDropped
                Counter32,
            ponPortDown64OctetFrames
                Counter32,
            ponPortDown65To127OctetFrames
                Counter32,
            ponPortDown128To255OctetFrames
                Counter32,
            ponPortDown256To511OctetFrames
                Counter32,
            ponPortDown512To1023OctetFrames
                Counter32,
            ponPortDown1024To1518OctetFrames
                Counter32,
            ponPortDownOver1519OctetFrames
                Counter32,
            ponPortDownBytes
                Counter64,
            ponPortUpBytes
                Counter64
        }

-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.2.1.1
ponPIndex OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortPerformanceDataEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.2.1.2
ponPortUpOctets OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
```

```
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortPerformanceDataEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.2.1.3
ponPortUpSpeed OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortPerformanceDataEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.2.1.4
ponPortUpMaxBand OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortPerformanceDataEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.2.1.5
ponPortUpProportion OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortPerformanceDataEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.2.1.6
ponPortUpMPCP OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortPerformanceDataEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.2.1.7
ponPortTotalFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortPerformanceDataEntry 7 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.2.1.8
ponPortUpUnicastFrames OBJECT-TYPE
      SYNTAX Counter32
```

```
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortPerformanceDataEntry 8 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.2.1.9
ponPortUpBroadcastFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortPerformanceDataEntry 9 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.2.1.10
ponPortUpMulticastFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortPerformanceDataEntry 10 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.2.1.11
ponPortUpCrc32Errors OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortPerformanceDataEntry 11 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.2.1.12
ponPortUpUndersizeFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortPerformanceDataEntry 12 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.2.1.13
ponPortUpOversizeFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortPerformanceDataEntry 13 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.2.1.14
ponPortUpCollisions OBJECT-TYPE
```

```
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortPerformanceDataEntry 14 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.2.1.15
ponPortUpFramesDropped OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortPerformanceDataEntry 15 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.2.1.16
ponPortUp64OctetFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortPerformanceDataEntry 16 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.2.1.17
ponPortUp65To127OctetFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortPerformanceDataEntry 17 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.2.1.18
ponPortUp128To255OctetFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortPerformanceDataEntry 18 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.2.1.19
ponPortUp256To511OctetFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortPerformanceDataEntry 19 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.2.1.20
```

```
ponPortUp512To1023OctetFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortPerformanceDataEntry 20 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.2.1.21
ponPortUp1024To1518OctetFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortPerformanceDataEntry 21 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.2.1.22
ponPortUpOver1519OctetFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortPerformanceDataEntry 22 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.2.1.23
ponPortDownOctets OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortPerformanceDataEntry 23 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.2.1.24
ponPortDownSpeed OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortPerformanceDataEntry 24 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.2.1.25
ponPortDownMaxband OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortPerformanceDataEntry 25 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.2.1.26
ponPortDownproportion OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortPerformanceDataEntry 26 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.2.1.27
ponPortDownMPCP OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortPerformanceDataEntry 27 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.2.1.28
ponPortDownTotalFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortPerformanceDataEntry 28 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.2.1.29
ponPortDownUnicastFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortPerformanceDataEntry 29 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.2.1.30
ponPortDownBroadcastFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortPerformanceDataEntry 30 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.2.1.31
ponPortDownMulticastFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortPerformanceDataEntry 31 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.2.1.32
ponPortDownCrc32Errors OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortPerformanceDataEntry 32 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.2.1.33
ponPortDownUndersizeFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortPerformanceDataEntry 33 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.2.1.34
ponPortDownOversizeFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortPerformanceDataEntry 34 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.2.1.35
ponPortDownCollisions OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortPerformanceDataEntry 35 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.2.1.36
ponPortDownFramesDropped OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortPerformanceDataEntry 36 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.2.1.37
ponPortDown64OctetFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortPerformanceDataEntry 37 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.2.1.38
ponPortDown65To127OctetFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortPerformanceDataEntry 38 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.2.1.39
ponPortDown128To255OctetFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortPerformanceDataEntry 39 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.2.1.40
ponPortDown256To511OctetFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortPerformanceDataEntry 40 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.2.1.41
ponPortDown512To1023OctetFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortPerformanceDataEntry 41 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.2.1.42
ponPortDown1024To1518OctetFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortPerformanceDataEntry 42 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.2.1.43
ponPortDownOver1519OctetFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { ponPortPerformanceDataEntry 43 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.2.1.44
ponPortDownBytes OBJECT-TYPE
      SYNTAX Counter64
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortPerformanceDataEntry 44 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.2.1.45
ponPortUpBytes OBJECT-TYPE
      SYNTAX Counter64
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortPerformanceDataEntry 45 }

-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.3
ponPortLinkTable OBJECT-TYPE
      SYNTAX SEQUENCE OF PonPortLinkEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPort 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.3.1
ponPortLinkEntry OBJECT-TYPE
      SYNTAX PonPortLinkEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { ponPortLinkIndex }
      ::= { ponPortLinkTable 1 }


PonPortLinkEntry ::=
      SEQUENCE {
            ponPortLinkIndex
                  INTEGER,
            ponPortLinkStatus
                  INTEGER,
            ponPortLinkSpeed
                  OCTET STRING
       }

-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.3.1.1
ponPortLinkIndex OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
```

```
            "Description."
      ::= { ponPortLinkEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.3.1.2
ponPortLinkStatus OBJECT-TYPE
      SYNTAX INTEGER
            {
            down(0),
            up(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortLinkEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.3.1.3
ponPortLinkSpeed OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPortLinkEntry 3 }

-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.4
ponConfigTable OBJECT-TYPE
      SYNTAX SEQUENCE OF PonConfigEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPort 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.4.1
ponConfigEntry OBJECT-TYPE
      SYNTAX PonConfigEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { ponIndex }
      ::= { ponConfigTable 1 }


PonConfigEntry ::=
      SEQUENCE {
            ponIndex
                  INTEGER,
            ponStauts
                  INTEGER,
            ponEncrytionTime
                  INTEGER,
            ponMaxRtt
                  INTEGER,
            ponP2pEnable
```

```
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.4.1.1
ponIndex OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponConfigEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.4.1.2
ponStauts OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponConfigEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.4.1.3
ponEncrytionTime OBJECT-TYPE
      SYNTAX INTEGER (0 | 774..786426)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponConfigEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.4.1.4
ponMaxRtt OBJECT-TYPE
      SYNTAX INTEGER (2000..32000)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponConfigEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.2.4.1.5
ponP2pEnable OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponConfigEntry 5 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.10.1.3
portMirror OBJECT IDENTIFIER ::= { v1600dPort 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.3.1
mirrorSession OBJECT-TYPE
      SYNTAX INTEGER (1..4)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portMirror 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.3.2
mirrorDstPort OBJECT-TYPE
      SYNTAX INTEGER (1..28)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portMirror 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.3.3
mirrorSrcPort OBJECT-TYPE
      SYNTAX INTEGER (1..28)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portMirror 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.3.4
mirrorType OBJECT-TYPE
      SYNTAX INTEGER
            {
            both(1),
            rx(2),
            tx(3)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portMirror 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.3.5
mirrorAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            delete(2),
            clear(3),
            clearAll(4)
            }
```

```
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portMirror 5 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.4
portMirrorTable OBJECT-TYPE
      SYNTAX SEQUENCE OF PortMirrorEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { v1600dPort 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.4.1
portMirrorEntry OBJECT-TYPE
      SYNTAX PortMirrorEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { portMirrorIndex }
      ::= { portMirrorTable 1 }


PortMirrorEntry ::=
      SEQUENCE {
            portMirrorIndex
                  INTEGER,
            portMirrorsession
                  INTEGER,
            portMirrorDstPort
                  Integer32,
            portMirrorSrcPort
                  Integer32,
            portMirrorType
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.10.1.4.1.1
portMirrorIndex OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portMirrorEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.4.1.2
portMirrorsession OBJECT-TYPE
      SYNTAX INTEGER (1..4)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { portMirrorEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.4.1.3
portMirrorDstPort OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portMirrorEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.4.1.4
portMirrorSrcPort OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portMirrorEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.4.1.5
portMirrorType OBJECT-TYPE
      SYNTAX INTEGER
            {
            both(1),
            rx(2),
            tx(3)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portMirrorEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.5
portCountersClear OBJECT-TYPE
      SYNTAX INTEGER { clear(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { v1600dPort 5 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.6
portLookbackDetect OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { v1600dPort 6 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.7
portChannelGroup OBJECT IDENTIFIER ::= { v1600dPort 7 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.7.1
portChannelGroupCfg OBJECT IDENTIFIER ::= { portChannelGroup 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.7.1.1
portChannelGroupIndex OBJECT-TYPE
      SYNTAX Integer32 (1..4)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portChannelGroupCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.7.1.2
portChannelLoadBalance OBJECT-TYPE
      SYNTAX INTEGER
            {
            smac(1),
            dmac(2),
            sdmac(3),
            sip(4),
            dip(5),
            sdip(6)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portChannelGroupCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.7.1.3
portChannelPortId1 OBJECT-TYPE
      SYNTAX INTEGER (0..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      DEFVAL { 0 }
      ::= { portChannelGroupCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.7.1.4
portChannelPortId2 OBJECT-TYPE
      SYNTAX INTEGER (0..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      DEFVAL { 0 }
      ::= { portChannelGroupCfg 4 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.10.1.7.1.5
portChannelPortId3 OBJECT-TYPE
      SYNTAX INTEGER (0..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      DEFVAL { 0 }
      ::= { portChannelGroupCfg 5 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.7.1.6
portChannelPortId4 OBJECT-TYPE
      SYNTAX INTEGER (0..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      DEFVAL { 0 }
      ::= { portChannelGroupCfg 6 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.7.1.7
portChannelAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            create(1),
            delete(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portChannelGroupCfg 7 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.7.2
portChannelGroupTable OBJECT-TYPE
      SYNTAX SEQUENCE OF PortChannelGroupEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portChannelGroup 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.7.2.1
portChannelGroupEntry OBJECT-TYPE
      SYNTAX PortChannelGroupEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { portChannelGroupId }
      ::= { portChannelGroupTable 1 }
```

```
PortChannelGroupEntry ::=
      SEQUENCE {
            portChannelGroupId
                  Integer32,
            portChannelGroupLoadBalance
                  INTEGER,
            portChannelGroupPortIdx1
                  Integer32,
            portChannelGroupPortIdx2
                  INTEGER,
            portChannelGroupPortIdx3
                  INTEGER,
            portChannelGroupPortIdx4
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.10.1.7.2.1.1
portChannelGroupId OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portChannelGroupEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.7.2.1.2
portChannelGroupLoadBalance OBJECT-TYPE
      SYNTAX INTEGER
            {
            smac(1),
            dmac(2),
            sdmac(3),
            sip(4),
            dip(5),
            sdip(6)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portChannelGroupEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.7.2.1.3
portChannelGroupPortIdx1 OBJECT-TYPE
      SYNTAX Integer32 (0..16)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portChannelGroupEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.7.2.1.4
portChannelGroupPortIdx2 OBJECT-TYPE
      SYNTAX INTEGER (0..16)
      MAX-ACCESS read-only
      STATUS current
```

```
      DESCRIPTION
            "Description."
      ::= { portChannelGroupEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.7.2.1.5
portChannelGroupPortIdx3 OBJECT-TYPE
      SYNTAX INTEGER (0..16)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portChannelGroupEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.7.2.1.6
portChannelGroupPortIdx4 OBJECT-TYPE
      SYNTAX INTEGER (0..16)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portChannelGroupEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.8
portCountersClean OBJECT IDENTIFIER ::= { v1600dPort 8 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.8.1
portCountersCleanIndex OBJECT-TYPE
      SYNTAX INTEGER (1..28)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portCountersClean 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.1.8.2
portCountersCleanAction OBJECT-TYPE
      SYNTAX INTEGER { clear(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portCountersClean 2 }

-- 1.3.6.1.4.1.37950.1.1.5.10.2
v1600dVLAN OBJECT IDENTIFIER ::= { v1600dSwitch 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.2.1
vlanCfg OBJECT IDENTIFIER ::= { v1600dVLAN 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.2.1.1
vlanCfgItem OBJECT-TYPE
      SYNTAX INTEGER
```

```
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { vlanCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.2.1.2
serviceName OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { vlanCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.2.1.3
startVid OBJECT-TYPE
      SYNTAX INTEGER (1..4094)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { vlanCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.2.1.4
endVid OBJECT-TYPE
      SYNTAX INTEGER (1..4094)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { vlanCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.2.1.5
upLinkPortNo OBJECT-TYPE
      SYNTAX INTEGER (1..28)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { vlanCfg 5 }


-- 1.3.6.1.4.1.37950.1.1.5.10.2.1.6
vlanTag OBJECT-TYPE
      SYNTAX INTEGER
            {
            untagged(0),
            tagged(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { vlanCfg 6 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.10.2.1.7
vlanAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            delete(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { vlanCfg 7 }


-- 1.3.6.1.4.1.37950.1.1.5.10.2.2
vlanCfgTable OBJECT-TYPE
      SYNTAX SEQUENCE OF VlanCfgEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { v1600dVLAN 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.2.2.1
vlanCfgEntry OBJECT-TYPE
      SYNTAX VlanCfgEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { vlanConfigIndex }
      ::= { vlanCfgTable 1 }


VlanCfgEntry ::=
      SEQUENCE {
            vlanConfigIndex
                  INTEGER,
            vlanCfgServiceName
                  OCTET STRING,
            vlanCfgStartVid
                  INTEGER,
            vlanCfgEndVid
                  INTEGER,
            vlanCfgUplinkPortNo
                  INTEGER,
            vlanCfgTagMode
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.10.2.2.1.1
vlanConfigIndex OBJECT-TYPE
      SYNTAX INTEGER (1..4094)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
```

```
            "Description."
      ::= { vlanCfgEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.2.2.1.2
vlanCfgServiceName OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { vlanCfgEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.2.2.1.3
vlanCfgStartVid OBJECT-TYPE
      SYNTAX INTEGER (1..4094)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { vlanCfgEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.2.2.1.4
vlanCfgEndVid OBJECT-TYPE
      SYNTAX INTEGER (1..4094)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { vlanCfgEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.2.2.1.5
vlanCfgUplinkPortNo OBJECT-TYPE
      SYNTAX INTEGER (1..28)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { vlanCfgEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.10.2.2.1.6
vlanCfgTagMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            untagged(0),
            tagged(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { vlanCfgEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.10.2.3
```

```
vlanIPCfg OBJECT IDENTIFIER ::= { v1600dVLAN 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.2.3.1
vlanId OBJECT-TYPE
      SYNTAX INTEGER (1..4094)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { vlanIPCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.2.3.2
vlanIP OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { vlanIPCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.2.3.3
vlanIPMask OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { vlanIPCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.2.3.4
vlanIPAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            delete(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { vlanIPCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.2.4
vlanIPTable OBJECT-TYPE
      SYNTAX SEQUENCE OF VlanIPEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { v1600dVLAN 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.2.4.1
vlanIPEntry OBJECT-TYPE
```

```
      SYNTAX VlanIPEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { vlanIdIndex }
      ::= { vlanIPTable 1 }


VlanIPEntry ::=
      SEQUENCE {
            vlanIdIndex
                  Integer32,
            vlanIPAddr
                  IpAddress,
            vlanIPMaskAddr
                  IpAddress
       }

-- 1.3.6.1.4.1.37950.1.1.5.10.2.4.1.1
vlanIdIndex OBJECT-TYPE
      SYNTAX Integer32 (1..4094)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { vlanIPEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.2.4.1.2
vlanIPAddr OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { vlanIPEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.2.4.1.3
vlanIPMaskAddr OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { vlanIPEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.2.5
vlanQinq OBJECT IDENTIFIER ::= { v1600dVLAN 5 }


-- 1.3.6.1.4.1.37950.1.1.5.10.2.5.1
vlanQinqEn OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
```

```
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { vlanQinq 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.2.5.2
vlanQinqSetting OBJECT IDENTIFIER ::= { vlanQinq 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.2.5.2.1
qinqPortId OBJECT-TYPE
      SYNTAX INTEGER (1..28)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { vlanQinqSetting 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.2.5.2.2
qinqCVlanId OBJECT-TYPE
      SYNTAX Integer32 (1..4094)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { vlanQinqSetting 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.2.5.2.3
qinqSVlanId OBJECT-TYPE
      SYNTAX Integer32 (1..4094)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { vlanQinqSetting 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.2.5.2.4
qinqModeSelect OBJECT-TYPE
      SYNTAX INTEGER
            {
            translation(1),
            qinq(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { vlanQinqSetting 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.2.5.2.5
qinqAction OBJECT-TYPE
      SYNTAX INTEGER
```

```
            {
            add(1),
            delete(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { vlanQinqSetting 5 }


-- 1.3.6.1.4.1.37950.1.1.5.10.2.5.3
vlanQinqTable OBJECT-TYPE
      SYNTAX SEQUENCE OF VlanQinqEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { vlanQinq 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.2.5.3.1
vlanQinqEntry OBJECT-TYPE
      SYNTAX VlanQinqEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { qinqIndex }
      ::= { vlanQinqTable 1 }


VlanQinqEntry ::=
      SEQUENCE {
            qinqIndex
                  Integer32,
            qinqPortIndex
                  Integer32,
            qinqCVlanIndex
                  Integer32,
            qinqSVlanIndex
                  Integer32,
            qinqMode
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.10.2.5.3.1.1
qinqIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { vlanQinqEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.2.5.3.1.2
qinqPortIndex OBJECT-TYPE
      SYNTAX Integer32
```

```
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { vlanQinqEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.2.5.3.1.3
qinqCVlanIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { vlanQinqEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.2.5.3.1.4
qinqSVlanIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { vlanQinqEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.2.5.3.1.5
qinqMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            translation(1),
            qinq(2)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { vlanQinqEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.10.2.6
vlanTable OBJECT-TYPE
      SYNTAX SEQUENCE OF VlanEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { v1600dVLAN 6 }


-- 1.3.6.1.4.1.37950.1.1.5.10.2.6.1
vlanEntry OBJECT-TYPE
      SYNTAX VlanEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { vlanVid }
```

```
      ::= { vlanTable 1 }


VlanEntry ::=
      SEQUENCE {
            vlanVid
                  Gauge32,
            vlanName
                  OCTET STRING,
            vlanTagPort
                  OCTET STRING,
            vlanUntagPort
                  OCTET STRING,
            vlanRowStatus
                  RowStatus,
            vlanDescr
                  OCTET STRING
       }

-- 1.3.6.1.4.1.37950.1.1.5.10.2.6.1.1
vlanVid OBJECT-TYPE
      SYNTAX Gauge32 (1..4094)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { vlanEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.2.6.1.2
vlanName OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { vlanEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.2.6.1.3
vlanTagPort OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { vlanEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.2.6.1.4
vlanUntagPort OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { vlanEntry 4 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.10.2.6.1.5
vlanRowStatus OBJECT-TYPE
      SYNTAX RowStatus
      MAX-ACCESS read-create
      STATUS current
      DESCRIPTION
            "Description."
      ::= { vlanEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.10.2.6.1.6
vlanDescr OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { vlanEntry 6 }

-- 1.3.6.1.4.1.37950.1.1.5.10.3
v1600dMacAddr OBJECT IDENTIFIER ::= { v1600dSwitch 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.3.1
agingTimer OBJECT-TYPE
      SYNTAX INTEGER (0 | 10..1000000)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { v1600dMacAddr 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.3.2
macAddrTable OBJECT-TYPE
      SYNTAX SEQUENCE OF MacAddrEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { v1600dMacAddr 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.3.2.1
macAddrEntry OBJECT-TYPE
      SYNTAX MacAddrEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { macAddrIndex }
      ::= { macAddrTable 1 }


MacAddrEntry ::=
      SEQUENCE {
            macAddrIndex
                  Integer32,
            macVlanId
```

```
                Integer32,
            macAddr
                OCTET STRING,
            macType
                INTEGER,
            macPortId
                OCTET STRING
        }

-- 1.3.6.1.4.1.37950.1.1.5.10.3.2.1.1
macAddrIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { macAddrEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.3.2.1.2
macVlanId OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { macAddrEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.3.2.1.3
macAddr OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { macAddrEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.3.2.1.4
macType OBJECT-TYPE
      SYNTAX INTEGER
            {
            static(0),
            dynamic(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { macAddrEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.3.2.1.5
macPortId OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
```

```
            "Description."
      ::= { macAddrEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.10.3.3
portMacAddrLimitTable OBJECT-TYPE
      SYNTAX SEQUENCE OF PortMacAddrLimitEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { v1600dMacAddr 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.3.3.1
portMacAddrLimitEntry OBJECT-TYPE
      SYNTAX PortMacAddrLimitEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { portMacLimitIdx }
      ::= { portMacAddrLimitTable 1 }


PortMacAddrLimitEntry ::=
      SEQUENCE {
            portMacLimitIdx
                  INTEGER,
            portMacAddrLimit
                  Integer32
       }

-- 1.3.6.1.4.1.37950.1.1.5.10.3.3.1.1
portMacLimitIdx OBJECT-TYPE
      SYNTAX INTEGER (1..28)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portMacAddrLimitEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.3.3.1.2
portMacAddrLimit OBJECT-TYPE
      SYNTAX Integer32 (0..16384)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portMacAddrLimitEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.4
v1600dQos OBJECT IDENTIFIER ::= { v1600dSwitch 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.4.1
qosQueueScheduler OBJECT-TYPE
```

```
      SYNTAX INTEGER
            {
            strict-priority(1),
            wrr(2),
            sp-wrr(3)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { v1600dQos 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.4.2
wrrTable OBJECT-TYPE
      SYNTAX SEQUENCE OF WrrEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { v1600dQos 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.4.2.1
wrrEntry OBJECT-TYPE
      SYNTAX WrrEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { wrrQueue }
      ::= { wrrTable 1 }


WrrEntry ::=
      SEQUENCE {
            wrrQueue
                  Gauge32,
            wrrWeight
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.10.4.2.1.1
wrrQueue OBJECT-TYPE
      SYNTAX Gauge32 (0..7)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { wrrEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.4.2.1.2
wrrWeight OBJECT-TYPE
      SYNTAX INTEGER (1..127)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { wrrEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.4.3
spWrrTable OBJECT-TYPE
      SYNTAX SEQUENCE OF SpWrrEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { v1600dQos 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.4.3.1
spWrrEntry OBJECT-TYPE
      SYNTAX SpWrrEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { spWrrQueue }
      ::= { spWrrTable 1 }


SpWrrEntry ::=
      SEQUENCE {
            spWrrQueue
                  INTEGER,
            spWrrWeight
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.10.4.3.1.1
spWrrQueue OBJECT-TYPE
      SYNTAX INTEGER (0..7)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { spWrrEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.4.3.1.2
spWrrWeight OBJECT-TYPE
      SYNTAX INTEGER (0..127)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { spWrrEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.5
v1600dIgmpsnooping OBJECT IDENTIFIER ::= { v1600dSwitch 5 }


-- 1.3.6.1.4.1.37950.1.1.5.10.5.1
igmpSnoopingEn OBJECT-TYPE
      SYNTAX INTEGER
```

```
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { v1600dIgmpsnooping 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.5.2
igmpMrouterPortCfg OBJECT IDENTIFIER ::= { v1600dIgmpsnooping 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.5.2.1
mrouterPort OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { igmpMrouterPortCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.5.2.2
mrouterVlan OBJECT-TYPE
      SYNTAX INTEGER (1..4094)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { igmpMrouterPortCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.5.2.3
mrouterAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            delete(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { igmpMrouterPortCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.5.3
igmpMrouterPortTable OBJECT-TYPE
      SYNTAX SEQUENCE OF IgmpMrouterPortEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { v1600dIgmpsnooping 3 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.10.5.3.1
igmpMrouterPortEntry OBJECT-TYPE
      SYNTAX IgmpMrouterPortEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { igmpMrouterItem }
      ::= { igmpMrouterPortTable 1 }


IgmpMrouterPortEntry ::=
      SEQUENCE {
            igmpMrouterItem
                  Integer32,
            igmpMrouterPort
                  INTEGER,
            igmpMrouterVlan
                  Integer32
       }

-- 1.3.6.1.4.1.37950.1.1.5.10.5.3.1.1
igmpMrouterItem OBJECT-TYPE
      SYNTAX Integer32 (1..24)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { igmpMrouterPortEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.5.3.1.2
igmpMrouterPort OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { igmpMrouterPortEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.5.3.1.3
igmpMrouterVlan OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { igmpMrouterPortEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.5.4
igmpPortTable OBJECT-TYPE
      SYNTAX SEQUENCE OF IgmpPortEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { v1600dIgmpsnooping 4 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.10.5.4.1
igmpPortEntry OBJECT-TYPE
      SYNTAX IgmpPortEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { igmpPortIndex }
      ::= { igmpPortTable 1 }


IgmpPortEntry ::=
      SEQUENCE {
            igmpPortIndex
                  Integer32,
            groupCount
                  Integer32,
            tagstrip
                  INTEGER,
            fastLeave
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.10.5.4.1.1
igmpPortIndex OBJECT-TYPE
      SYNTAX Integer32 (1..28)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { igmpPortEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.5.4.1.2
groupCount OBJECT-TYPE
      SYNTAX Integer32 (0..1024)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { igmpPortEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.5.4.1.3
tagstrip OBJECT-TYPE
      SYNTAX INTEGER
            {
            no_tagstrip(0),
            tagstrip(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { igmpPortEntry 3 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.10.5.4.1.4
fastLeave OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { igmpPortEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.5.5
userVlanConfig OBJECT IDENTIFIER ::= { v1600dIgmpsnooping 5 }


-- 1.3.6.1.4.1.37950.1.1.5.10.5.5.1
userPort OBJECT-TYPE
      SYNTAX Integer32 (1..28)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { userVlanConfig 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.5.5.2
userVlanId OBJECT-TYPE
      SYNTAX Integer32 (1..4094)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { userVlanConfig 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.5.5.3
groupVlanId OBJECT-TYPE
      SYNTAX Integer32 (1..4094)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { userVlanConfig 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.5.5.4
userAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            delete(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { userVlanConfig 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.5.6
userVlanTable OBJECT-TYPE
      SYNTAX SEQUENCE OF UserVlanEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { v1600dIgmpsnooping 6 }


-- 1.3.6.1.4.1.37950.1.1.5.10.5.6.1
userVlanEntry OBJECT-TYPE
      SYNTAX UserVlanEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { userVlanIndex }
      ::= { userVlanTable 1 }


UserVlanEntry ::=
      SEQUENCE {
            userVlanIndex
                  Integer32,
            userVlanPortIndex
                  Integer32,
            userVlanIdIndex
                  Integer32,
            groupVlanIdIndex
                  Integer32
       }

-- 1.3.6.1.4.1.37950.1.1.5.10.5.6.1.1
userVlanIndex OBJECT-TYPE
      SYNTAX Integer32 (1..4094)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { userVlanEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.5.6.1.2
userVlanPortIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { userVlanEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.5.6.1.3
userVlanIdIndex OBJECT-TYPE
      SYNTAX Integer32
```

```
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { userVlanEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.5.6.1.4
groupVlanIdIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { userVlanEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.5.7
igmpStaticGroupCfg OBJECT IDENTIFIER ::= { v1600dIgmpsnooping 7 }


-- 1.3.6.1.4.1.37950.1.1.5.10.5.7.1
staticGroupPort OBJECT-TYPE
      SYNTAX Integer32 (1..28)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { igmpStaticGroupCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.5.7.2
staticGroupIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { igmpStaticGroupCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.5.7.3
staticGroupVlan OBJECT-TYPE
      SYNTAX Integer32 (1..4094)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { igmpStaticGroupCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.5.7.4
staticGroupAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            delete(2)
            }
      MAX-ACCESS read-write
```

```
      STATUS current
      DESCRIPTION
            "Description."
      ::= { igmpStaticGroupCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.5.8
igmpStaticGroupTable OBJECT-TYPE
      SYNTAX SEQUENCE OF IgmpStaticGroupEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { v1600dIgmpsnooping 8 }


-- 1.3.6.1.4.1.37950.1.1.5.10.5.8.1
igmpStaticGroupEntry OBJECT-TYPE
      SYNTAX IgmpStaticGroupEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { igmpStaticItem }
      ::= { igmpStaticGroupTable 1 }


IgmpStaticGroupEntry ::=
      SEQUENCE {
            igmpStaticItem
                  Integer32,
            igmpStaticPort
                  Integer32,
            igmpStaticGroupIp
                  IpAddress,
            igmpStaticGroupVlan
                  Integer32
       }

-- 1.3.6.1.4.1.37950.1.1.5.10.5.8.1.1
igmpStaticItem OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { igmpStaticGroupEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.5.8.1.2
igmpStaticPort OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { igmpStaticGroupEntry 2 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.10.5.8.1.3
igmpStaticGroupIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { igmpStaticGroupEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.5.8.1.4
igmpStaticGroupVlan OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { igmpStaticGroupEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.5.9
igmplastmemberCfg OBJECT IDENTIFIER ::= { v1600dIgmpsnooping 9 }


-- 1.3.6.1.4.1.37950.1.1.5.10.5.9.1
querycount OBJECT-TYPE
      SYNTAX Integer32 (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { igmplastmemberCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.5.9.2
queryinterval OBJECT-TYPE
      SYNTAX Integer32 (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { igmplastmemberCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.5.9.3
queryresponse OBJECT-TYPE
      SYNTAX Integer32 (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { igmplastmemberCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.5.10
igmpGeneralCfg OBJECT IDENTIFIER ::= { v1600dIgmpsnooping 10 }


-- 1.3.6.1.4.1.37950.1.1.5.10.5.10.1
```

```
queryPacket OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { igmpGeneralCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.5.10.2
queryTime OBJECT-TYPE
      SYNTAX Integer32 (10..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { igmpGeneralCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.5.11
igmpSourceIpCfg OBJECT IDENTIFIER ::= { v1600dIgmpsnooping 11 }


-- 1.3.6.1.4.1.37950.1.1.5.10.5.11.1
sourceip OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { igmpSourceIpCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.5.12
igmpGroupMemberTable OBJECT-TYPE
      SYNTAX SEQUENCE OF IgmpGroupMemberEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { v1600dIgmpsnooping 12 }


-- 1.3.6.1.4.1.37950.1.1.5.10.5.12.1
igmpGroupMemberEntry OBJECT-TYPE
      SYNTAX IgmpGroupMemberEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { igmpGroupMemberItem }
      ::= { igmpGroupMemberTable 1 }


IgmpGroupMemberEntry ::=
```

```
      SEQUENCE {
            igmpGroupMemberItem
                  Integer32,
            igmpGroupMemberGVlan
                  INTEGER,
            igmpGroupMemberIp
                  IpAddress,
            igmpGroupMemberPort
                  OCTET STRING,
            igmpGroupMembeType
                  INTEGER,
            igmpGroupMemberUserVlan
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.10.5.12.1.1
igmpGroupMemberItem OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { igmpGroupMemberEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.5.12.1.2
igmpGroupMemberGVlan OBJECT-TYPE
      SYNTAX INTEGER (1..4094)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { igmpGroupMemberEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.5.12.1.3
igmpGroupMemberIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { igmpGroupMemberEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.5.12.1.4
igmpGroupMemberPort OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { igmpGroupMemberEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.5.12.1.5
igmpGroupMembeType OBJECT-TYPE
      SYNTAX INTEGER
            {
```

```
            static(1),
            router(2),
            dynamic(3)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { igmpGroupMemberEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.10.5.12.1.6
igmpGroupMemberUserVlan OBJECT-TYPE
      SYNTAX INTEGER (1..4094)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { igmpGroupMemberEntry 6 }
-- 1.3.6.1.4.1.37950.1.1.5.10.6
v1600dARPProxy OBJECT IDENTIFIER ::= { v1600dSwitch 6 }


-- 1.3.6.1.4.1.37950.1.1.5.10.6.1
arpProxyCfg OBJECT IDENTIFIER ::= { v1600dARPProxy 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.6.1.1
arpProxyVlan OBJECT-TYPE
      SYNTAX Integer32 (1..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { arpProxyCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.6.1.2
arpProxyConfig OBJECT-TYPE
      SYNTAX INTEGER
            {
            enable(1),
            disable(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { arpProxyCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.6.2
arpProxyTable OBJECT-TYPE
      SYNTAX SEQUENCE OF ArpProxyEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { v1600dARPProxy 2 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.10.6.2.1
arpProxyEntry OBJECT-TYPE
      SYNTAX ArpProxyEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { arpProxyVlanId }
      ::= { arpProxyTable 1 }


ArpProxyEntry ::=
      SEQUENCE {
            arpProxyVlanId
                  Integer32,
            arpProxyState
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.10.6.2.1.1
arpProxyVlanId OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { arpProxyEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.6.2.1.2
arpProxyState OBJECT-TYPE
      SYNTAX INTEGER
            {
            enable(1),
            disable(2)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { arpProxyEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7
v1600dDHCP OBJECT IDENTIFIER ::= { v1600dSwitch 7 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.1
dhcpServer OBJECT IDENTIFIER ::= { v1600dDHCP 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.1.1
dhcpCurrentState OBJECT-TYPE
      SYNTAX INTEGER
            {
            enable(1),
            disable(2)
```

```
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { dhcpServer 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.1.2
dhcpStartIP OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { dhcpServer 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.1.3
dhcpEndIP OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { dhcpServer 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.1.4
dhcpSubNetMask OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { dhcpServer 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.1.5
dhcpGateWay OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { dhcpServer 5 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.1.6
dhcpDNS1 OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { dhcpServer 6 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.1.7
```

```
dhcpDNS2 OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { dhcpServer 7 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.1.8
dhcpDNS3 OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { dhcpServer 8 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.1.9
dhcpWins OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { dhcpServer 9 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.1.10
dhcpLeaseTime OBJECT-TYPE
      SYNTAX Integer32 (60..864000)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { dhcpServer 10 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.1.11
dhcpInterfaceVlan OBJECT-TYPE
      SYNTAX Integer32 (1..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { dhcpServer 11 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.1.12
dhcpControl OBJECT-TYPE
      SYNTAX INTEGER
            {
            enable(1),
            disable(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
```

```
            "Description."
      ::= { dhcpServer 12 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.1.13
dhcpCommit OBJECT-TYPE
      SYNTAX INTEGER { Commit(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { dhcpServer 13 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.1.14
dhcpLeaseTable OBJECT-TYPE
      SYNTAX SEQUENCE OF DhcpLeaseEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { dhcpServer 14 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.1.14.1
dhcpLeaseEntry OBJECT-TYPE
      SYNTAX DhcpLeaseEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { dhcpLeaseIndex }
      ::= { dhcpLeaseTable 1 }


DhcpLeaseEntry ::=
      SEQUENCE {
            dhcpLeaseIndex
                  Integer32,
            dhcpLeaseIP
                  IpAddress,
            dhcpLeaseMACAddr
                  OCTET STRING,
            dhcpLeaseTimeValue
                  Integer32
       }

-- 1.3.6.1.4.1.37950.1.1.5.10.7.1.14.1.1
dhcpLeaseIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { dhcpLeaseEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.1.14.1.2
dhcpLeaseIP OBJECT-TYPE
```

```
      SYNTAX IpAddress
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { dhcpLeaseEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.1.14.1.3
dhcpLeaseMACAddr OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { dhcpLeaseEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.1.14.1.4
dhcpLeaseTimeValue OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { dhcpLeaseEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.2
dhcpRelay OBJECT IDENTIFIER ::= { v1600dDHCP 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.2.1
relayServerConfig OBJECT IDENTIFIER ::= { dhcpRelay 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.2.1.1
relayVlan OBJECT-TYPE
      SYNTAX Integer32 (1..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { relayServerConfig 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.2.1.2
relayServerIP OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { relayServerConfig 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.2.1.3
relayServerAction OBJECT-TYPE
      SYNTAX INTEGER
```

```
            {
            Add(1),
            Delete(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { relayServerConfig 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.2.2
relayServerTable OBJECT-TYPE
      SYNTAX SEQUENCE OF RelayServerEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { dhcpRelay 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.2.2.1
relayServerEntry OBJECT-TYPE
      SYNTAX RelayServerEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { relayServerVlan }
      ::= { relayServerTable 1 }


RelayServerEntry ::=
      SEQUENCE {
            relayServerVlan
                  Integer32,
            relayServerIPAddrList
                  OCTET STRING
       }

-- 1.3.6.1.4.1.37950.1.1.5.10.7.2.2.1.1
relayServerVlan OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { relayServerEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.2.2.1.2
relayServerIPAddrList OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { relayServerEntry 2 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.10.7.3
dhcpSnooping OBJECT IDENTIFIER ::= { v1600dDHCP 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.3.1
dhcpSNControl OBJECT-TYPE
      SYNTAX INTEGER
            {
            Enable(1),
            Disable(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { dhcpSnooping 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.3.2
dhcpSNVlan OBJECT IDENTIFIER ::= { dhcpSnooping 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.3.2.1
dhcpSNVlanId OBJECT-TYPE
      SYNTAX Integer32 (1..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { dhcpSNVlan 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.3.2.2
dhcpSNVlanAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            Add(1),
            Delete(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { dhcpSNVlan 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.3.2.3
dhcpSNVlanList OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { dhcpSNVlan 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.3.3
dhcpSNOption82 OBJECT IDENTIFIER ::= { dhcpSnooping 3 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.10.7.3.3.1
snOption82Control OBJECT-TYPE
      SYNTAX INTEGER
            {
            Enable(1),
            Disable(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { dhcpSNOption82 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.3.3.2
snOption82Strategy OBJECT-TYPE
      SYNTAX INTEGER
            {
            Drop(0),
            Keep(1),
            Replace(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { dhcpSNOption82 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.3.4
dhcpSNPortCfgTable OBJECT-TYPE
      SYNTAX SEQUENCE OF DhcpSNPortCfgEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { dhcpSnooping 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.3.4.1
dhcpSNPortCfgEntry OBJECT-TYPE
      SYNTAX DhcpSNPortCfgEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { snPortIndex }
      ::= { dhcpSNPortCfgTable 1 }


DhcpSNPortCfgEntry ::=
      SEQUENCE {
            snPortIndex
                  Integer32,
            snPortType
                  INTEGER,
            snPortUserCircuitID
```

```
                  OCTET STRING,
            snPortUserRemoteID
                  OCTET STRING,
            snPortRateLimit
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.10.7.3.4.1.1
snPortIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { dhcpSNPortCfgEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.3.4.1.2
snPortType OBJECT-TYPE
      SYNTAX INTEGER
            {
            Trust(1),
            Untrust(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { dhcpSNPortCfgEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.3.4.1.3
snPortUserCircuitID OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { dhcpSNPortCfgEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.3.4.1.4
snPortUserRemoteID OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { dhcpSNPortCfgEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.3.4.1.5
snPortRateLimit OBJECT-TYPE
      SYNTAX INTEGER (0..4096)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { dhcpSNPortCfgEntry 5 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.10.7.3.5
dhcpSNErrorRecovery OBJECT-TYPE
      SYNTAX INTEGER
            {
            Enable(1),
            Disable(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { dhcpSnooping 5 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.3.6
dhcpSNErrorRecoveryInterval OBJECT-TYPE
      SYNTAX INTEGER (3..3600)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { dhcpSnooping 6 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.3.7
dhcpSNBinding OBJECT IDENTIFIER ::= { dhcpSnooping 7 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.3.7.1
snBindingConfig OBJECT IDENTIFIER ::= { dhcpSNBinding 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.3.7.1.1
snBindMAC OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { snBindingConfig 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.3.7.1.2
snBindVlan OBJECT-TYPE
      SYNTAX Integer32 (1..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { snBindingConfig 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.3.7.1.3
snBindIP OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
```

```
      DESCRIPTION
            "Description."
      ::= { snBindingConfig 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.3.7.1.4
snBindPortIndex OBJECT-TYPE
      SYNTAX Integer32 (1..28)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { snBindingConfig 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.3.7.1.5
snBindLease OBJECT-TYPE
      SYNTAX Integer32 (60..1000000)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { snBindingConfig 5 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.3.7.1.6
snBindAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            AddStatic(1),
            DeleteByMac(2),
            FlushAll(3),
            FlushStatic(4),
            FlushDynamic(5)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { snBindingConfig 6 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.3.7.2
snBindingTable OBJECT-TYPE
      SYNTAX SEQUENCE OF SnBindingEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { dhcpSNBinding 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.3.7.2.1
snBindingEntry OBJECT-TYPE
      SYNTAX SnBindingEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
```

```
      INDEX { snBindingid }
      ::= { snBindingTable 1 }


SnBindingEntry ::=
      SEQUENCE {
            snBindingid
                  Integer32,
            snBindingMAC
                  OCTET STRING,
            snBindingIP
                  IpAddress,
            snBindingLease
                  Integer32,
            snBindingType
                  INTEGER,
            snBindingVlan
                  Integer32,
            snBindingPortIndex
                  Integer32
       }

-- 1.3.6.1.4.1.37950.1.1.5.10.7.3.7.2.1.1
snBindingid OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { snBindingEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.3.7.2.1.2
snBindingMAC OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { snBindingEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.3.7.2.1.3
snBindingIP OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { snBindingEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.3.7.2.1.4
snBindingLease OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { snBindingEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.3.7.2.1.5
snBindingType OBJECT-TYPE
      SYNTAX INTEGER
            {
            Static(1),
            Dynamic(2)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { snBindingEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.3.7.2.1.6
snBindingVlan OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { snBindingEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.3.7.2.1.7
snBindingPortIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { snBindingEntry 7 }


-- 1.3.6.1.4.1.37950.1.1.5.10.7.3.7.3
snBindingDeleteTime OBJECT-TYPE
      SYNTAX Integer32 (1..3600)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { dhcpSNBinding 3 }

-- 1.3.6.1.4.1.37950.1.1.5.10.8
v1600dStormControlCfg OBJECT IDENTIFIER ::= { v1600dSwitch 8 }


-- 1.3.6.1.4.1.37950.1.1.5.10.8.1
stormCtrPid OBJECT-TYPE
      SYNTAX Integer32 (1..24)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { v1600dStormControlCfg 1 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.10.8.2
broadcastStormCtrEn OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { v1600dStormControlCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.8.3
multicastStormCtrEn OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { v1600dStormControlCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.8.4
unknownStormCtrEn OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { v1600dStormControlCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.8.5
broadcastSpeed OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { v1600dStormControlCfg 5 }


-- 1.3.6.1.4.1.37950.1.1.5.10.8.6
multicastSpeed OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
```

```
            "Description."
      ::= { v1600dStormControlCfg 6 }


-- 1.3.6.1.4.1.37950.1.1.5.10.8.7
unknownSpeed OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { v1600dStormControlCfg 7 }


-- 1.3.6.1.4.1.37950.1.1.5.10.8.8
stormCtrAction OBJECT-TYPE
      SYNTAX INTEGER { commit(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { v1600dStormControlCfg 8 }


-- 1.3.6.1.4.1.37950.1.1.5.10.9
v1600dRstp OBJECT IDENTIFIER ::= { v1600dSwitch 9 }


-- 1.3.6.1.4.1.37950.1.1.5.10.9.1
rstpEn OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { v1600dRstp 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.9.2
rstpCfg OBJECT IDENTIFIER ::= { v1600dRstp 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.9.2.1
maxAge OBJECT-TYPE
      SYNTAX Integer32 (6..40)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { rstpCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.9.2.2
bridgePriority OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
```

```
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { rstpCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.9.2.3
bridgeMac OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { rstpCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.9.2.4
helloTime OBJECT-TYPE
      SYNTAX Integer32 (1..10)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { rstpCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.9.2.5
forwardDelay OBJECT-TYPE
      SYNTAX Integer32 (4..30)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { rstpCfg 5 }


-- 1.3.6.1.4.1.37950.1.1.5.10.9.3
rstpPortCfgTable OBJECT-TYPE
      SYNTAX SEQUENCE OF RstpPortCfgEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { v1600dRstp 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.9.3.1
rstpPortCfgEntry OBJECT-TYPE
      SYNTAX RstpPortCfgEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { rstpPortId }
      ::= { rstpPortCfgTable 1 }


RstpPortCfgEntry ::=
```

```
      SEQUENCE {
            rstpPortId
                  Integer32,
            rstpPortAdminStatus
                  INTEGER,
            rstpPortPrioritySet
                  Integer32,
            rstpPortCostSet
                  Unsigned32,
            rstpPortOperEdgeSet
                  INTEGER,
            rstpPortP2PSet
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.10.9.3.1.1
rstpPortId OBJECT-TYPE
      SYNTAX Integer32 (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { rstpPortCfgEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.9.3.1.2
rstpPortAdminStatus OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { rstpPortCfgEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.9.3.1.3
rstpPortPrioritySet OBJECT-TYPE
      SYNTAX Integer32 (0..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { rstpPortCfgEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.9.3.1.4
rstpPortCostSet OBJECT-TYPE
      SYNTAX Unsigned32 (1..200000000)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { rstpPortCfgEntry 4 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.10.9.3.1.5
rstpPortOperEdgeSet OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { rstpPortCfgEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.10.9.3.1.6
rstpPortP2PSet OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { rstpPortCfgEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.10.9.4
rstpInfo OBJECT IDENTIFIER ::= { v1600dRstp 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.9.4.1
rstpRootBridgeInfo OBJECT IDENTIFIER ::= { rstpInfo 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.9.4.1.1
pathCostToRootBridge OBJECT-TYPE
      SYNTAX Unsigned32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { rstpRootBridgeInfo 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.9.4.1.2
rootPort OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { rstpRootBridgeInfo 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.9.4.1.3
rootBridgePriority OBJECT-TYPE
      SYNTAX Integer32
```

```
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { rstpRootBridgeInfo 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.9.4.1.4
rootBridgeMac OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { rstpRootBridgeInfo 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.9.4.1.5
rootBridgeHelloTime OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { rstpRootBridgeInfo 5 }


-- 1.3.6.1.4.1.37950.1.1.5.10.9.4.1.6
rootBridgeMaxAge OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { rstpRootBridgeInfo 6 }


-- 1.3.6.1.4.1.37950.1.1.5.10.9.4.1.7
rootBridgeForwardDelay OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { rstpRootBridgeInfo 7 }


-- 1.3.6.1.4.1.37950.1.1.5.10.9.4.2
rstpPortStatusTable OBJECT-TYPE
      SYNTAX SEQUENCE OF RstpPortStatusEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { rstpInfo 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.9.4.2.1
rstpPortStatusEntry OBJECT-TYPE
```

```
      SYNTAX RstpPortStatusEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { rstpPortIndex }
      ::= { rstpPortStatusTable 1 }


RstpPortStatusEntry ::=
      SEQUENCE {
            rstpPortIndex
                  Integer32,
            rstpPortRole
                  INTEGER,
            rstpPortStatus
                  INTEGER,
            rstpPortCost
                  Integer32,
            rstpPortPriority
                  Integer32,
            rstpPortP2P
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.10.9.4.2.1.1
rstpPortIndex OBJECT-TYPE
      SYNTAX Integer32 (1..24)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { rstpPortStatusEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.9.4.2.1.2
rstpPortRole OBJECT-TYPE
      SYNTAX INTEGER
            {
            root(1),
            backup(2),
            design(3),
            alternat(4),
            disable(5),
            unkown(6)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { rstpPortStatusEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.9.4.2.1.3
rstpPortStatus OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            discarding(1),
```

```
            learning(2),
            forwarding(3),
            unkown(4)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { rstpPortStatusEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.9.4.2.1.4
rstpPortCost OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { rstpPortStatusEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.9.4.2.1.5
rstpPortPriority OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { rstpPortStatusEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.10.9.4.2.1.6
rstpPortP2P OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { rstpPortStatusEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10
v1600dAcl OBJECT IDENTIFIER ::= { v1600dSwitch 10 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1
aclCfg OBJECT IDENTIFIER ::= { v1600dAcl 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.1
stdIPFilterCfg OBJECT IDENTIFIER ::= { aclCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.1.1
stdIpFilterId OBJECT-TYPE
```

```
      SYNTAX INTEGER (0..999)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { stdIPFilterCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.1.2
stdIpFilterSrcIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { stdIPFilterCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.1.3
stdIpFilterSrcMask OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { stdIPFilterCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.1.4
stdIpFilterMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            permit(1),
            deny(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { stdIPFilterCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.1.5
stdIpFilterAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            delete(2),
            clear(3)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { stdIPFilterCfg 5 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.2
extIPFilterCfg OBJECT IDENTIFIER ::= { aclCfg 2 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.2.1
extIpFilterId OBJECT-TYPE
      SYNTAX INTEGER (1000..1999)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { extIPFilterCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.2.2
extIpFilterProtocol OBJECT-TYPE
      SYNTAX INTEGER (-1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { extIPFilterCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.2.3
extIpFilterSrcIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { extIPFilterCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.2.4
extIpFilterSrcMask OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { extIPFilterCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.2.5
extIpFilterSrcPort OBJECT-TYPE
      SYNTAX INTEGER (-1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { extIPFilterCfg 5 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.2.6
extIpFilterDstIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { extIPFilterCfg 6 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.2.7
extIpFilterDstMask OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { extIPFilterCfg 7 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.2.8
extIpFilterDstPort OBJECT-TYPE
      SYNTAX INTEGER (-1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { extIPFilterCfg 8 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.2.9
extIpFilterDscp OBJECT-TYPE
      SYNTAX INTEGER (-1..63)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { extIPFilterCfg 9 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.2.10
extIpFilterMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            permit(1),
            deny(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { extIPFilterCfg 10 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.2.11
extIpFilterAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            delete(2),
            clear(3)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { extIPFilterCfg 11 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.3
macFilterCfg OBJECT IDENTIFIER ::= { aclCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.3.1
macFilterId OBJECT-TYPE
      SYNTAX INTEGER (2000..2999)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { macFilterCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.3.2
macFilterSrcMac OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { macFilterCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.3.3
macFilterSrcMacMask OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { macFilterCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.3.4
macFilterDstMac OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { macFilterCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.3.5
macFilterDstMacMask OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { macFilterCfg 5 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.3.6
macFilterVlanId OBJECT-TYPE
```

```
      SYNTAX INTEGER (0..4094)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { macFilterCfg 6 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.3.7
macFilterCos OBJECT-TYPE
      SYNTAX INTEGER (-1..7)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { macFilterCfg 7 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.3.8
macFilterEthType OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { macFilterCfg 8 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.3.9
macFilterEthTypeMask OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { macFilterCfg 9 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.3.10
macFilterMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            permit(1),
            deny(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { macFilterCfg 10 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.3.11
macFilterAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            delete(2),
            clear(3)
```

```
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { macFilterCfg 11 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.4
portBaseAclCfg OBJECT IDENTIFIER ::= { aclCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.4.1
portBaseAclId OBJECT-TYPE
      SYNTAX Integer32 (5000..5999)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portBaseAclCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.4.2
portBaseFltMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            permit(1),
            deny(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portBaseAclCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.4.3
portBaseSrcMac OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portBaseAclCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.4.4
portBaseSrcMacMask OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portBaseAclCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.4.5
portBaseDstMac OBJECT-TYPE
      SYNTAX OCTET STRING
```

```
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portBaseAclCfg 5 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.4.6
portBaseDstMacMask OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portBaseAclCfg 6 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.4.7
portBaseVlan OBJECT-TYPE
      SYNTAX INTEGER (0..4094)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portBaseAclCfg 7 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.4.8
portBaseVlanMask OBJECT-TYPE
      SYNTAX INTEGER (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portBaseAclCfg 8 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.4.9
portBaseCos OBJECT-TYPE
      SYNTAX INTEGER (-1..7)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portBaseAclCfg 9 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.4.10
portBaseEthernetType OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portBaseAclCfg 10 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.4.11
portBaseSrcIp OBJECT-TYPE
```

```
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portBaseAclCfg 11 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.4.12
portBaseSrcIpMask OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portBaseAclCfg 12 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.4.13
portBaseDstIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portBaseAclCfg 13 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.4.14
portBaseDstIpMask OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portBaseAclCfg 14 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.4.15
portBaseProtocol OBJECT-TYPE
      SYNTAX INTEGER (-1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portBaseAclCfg 15 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.4.16
portBaseProtocolMask OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portBaseAclCfg 16 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.4.17
```

```
portBaseTosDscp OBJECT-TYPE
      SYNTAX INTEGER (-1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portBaseAclCfg 17 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.4.18
portBaseTosDscpMask OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portBaseAclCfg 18 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.4.19
portBaseSrcPort OBJECT-TYPE
      SYNTAX INTEGER (-1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portBaseAclCfg 19 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.4.20
portBaseSrcPortMask OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portBaseAclCfg 20 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.4.21
portBaseDstPort OBJECT-TYPE
      SYNTAX INTEGER (-1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portBaseAclCfg 21 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.4.22
portBaseDstPortMask OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portBaseAclCfg 22 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.4.23
portBaseAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            delete(2),
            clear(3)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portBaseAclCfg 23 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.5
qosBaseAclCfg OBJECT IDENTIFIER ::= { aclCfg 5 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.5.1
qosBaseAclId OBJECT-TYPE
      SYNTAX INTEGER (6000..6999)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { qosBaseAclCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.5.2
qosBaseOutPacketPri OBJECT-TYPE
      SYNTAX INTEGER (0..8)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { qosBaseAclCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.5.3
qosBaseHwTransQueue OBJECT-TYPE
      SYNTAX INTEGER (0..7)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { qosBaseAclCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.5.4
qosBaseRulePri OBJECT-TYPE
      SYNTAX INTEGER (1..12)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { qosBaseAclCfg 4 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.5.5
qosBaseSrcMac OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { qosBaseAclCfg 5 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.5.6
qosBaseSrcMacMask OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { qosBaseAclCfg 6 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.5.7
qosBaseDstMac OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { qosBaseAclCfg 7 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.5.8
qosBaseDstMacMask OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { qosBaseAclCfg 8 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.5.9
qosBaseVlan OBJECT-TYPE
      SYNTAX INTEGER (0..4094)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { qosBaseAclCfg 9 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.5.10
qosBaseVlanMask OBJECT-TYPE
      SYNTAX INTEGER (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { qosBaseAclCfg 10 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.5.11
qosBaseCos OBJECT-TYPE
      SYNTAX INTEGER (-1..7)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { qosBaseAclCfg 11 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.5.12
qosEthernetType OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { qosBaseAclCfg 12 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.5.13
qosBaseSrcIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { qosBaseAclCfg 13 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.5.14
qosBaseSrcIpMask OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { qosBaseAclCfg 14 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.5.15
qosBaseDstIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { qosBaseAclCfg 15 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.5.16
qosBaseDstIpMask OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { qosBaseAclCfg 16 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.5.17
qosBaseProtocol OBJECT-TYPE
      SYNTAX INTEGER (-1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { qosBaseAclCfg 17 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.5.18
qosBaseProtocolMask OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { qosBaseAclCfg 18 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.5.19
qosBaseTosDscp OBJECT-TYPE
      SYNTAX INTEGER (-1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { qosBaseAclCfg 19 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.5.20
qosBaseTosDscpMask OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { qosBaseAclCfg 20 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.5.21
qosBaseSrcPort OBJECT-TYPE
      SYNTAX INTEGER (-1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { qosBaseAclCfg 21 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.5.22
qosBaseSrcPortMask OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { qosBaseAclCfg 22 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.5.23
qosBaseDstPort OBJECT-TYPE
      SYNTAX INTEGER (-1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { qosBaseAclCfg 23 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.5.24
qosBaseDstPortMask OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { qosBaseAclCfg 24 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.1.5.25
qosBaseAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            delete(2),
            clear(3)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { qosBaseAclCfg 25 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2
aclTable OBJECT IDENTIFIER ::= { v1600dAcl 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.1
stdIpFilterTable OBJECT-TYPE
      SYNTAX SEQUENCE OF StdIpFilterEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { aclTable 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.1.1
stdIpFilterEntry OBJECT-TYPE
      SYNTAX StdIpFilterEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
```

```
      INDEX { stdIpFltId }
      ::= { stdIpFilterTable 1 }


StdIpFilterEntry ::=
      SEQUENCE {
            stdIpFltId
                  INTEGER,
            stdIpFltSrcIp
                  IpAddress,
            stdIpFltSrcMask
                  IpAddress,
            stdIpFltMode
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.1.1.1
stdIpFltId OBJECT-TYPE
      SYNTAX INTEGER (0..999)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { stdIpFilterEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.1.1.2
stdIpFltSrcIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { stdIpFilterEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.1.1.3
stdIpFltSrcMask OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { stdIpFilterEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.1.1.4
stdIpFltMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            permit(1),
            deny(2)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { stdIpFilterEntry 4 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.2
extIpFilterTable OBJECT-TYPE
      SYNTAX SEQUENCE OF ExtIpFilterEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { aclTable 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.2.1
extIpFilterEntry OBJECT-TYPE
      SYNTAX ExtIpFilterEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { extIpFltId }
      ::= { extIpFilterTable 1 }


ExtIpFilterEntry ::=
      SEQUENCE {
            extIpFltId
                  INTEGER,
            extIpFltProtocol
                  INTEGER,
            extIpFltSrcIp
                  IpAddress,
            extIpFltSrcMask
                  IpAddress,
            extIpFltSrcPort
                  INTEGER,
            extIpFltDstIp
                  IpAddress,
            extIpFltDstMask
                  IpAddress,
            extIpFltDstPort
                  INTEGER,
            extIpFltDscp
                  INTEGER,
            extIpFltMode
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.2.1.1
extIpFltId OBJECT-TYPE
      SYNTAX INTEGER (1000..1999)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { extIpFilterEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.2.1.2
extIpFltProtocol OBJECT-TYPE
      SYNTAX INTEGER (-1..255)
```

```
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { extIpFilterEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.2.1.3
extIpFltSrcIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { extIpFilterEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.2.1.4
extIpFltSrcMask OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { extIpFilterEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.2.1.5
extIpFltSrcPort OBJECT-TYPE
      SYNTAX INTEGER (-1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { extIpFilterEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.2.1.6
extIpFltDstIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { extIpFilterEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.2.1.7
extIpFltDstMask OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { extIpFilterEntry 7 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.2.1.8
extIpFltDstPort OBJECT-TYPE
```

```
      SYNTAX INTEGER (-1..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { extIpFilterEntry 8 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.2.1.9
extIpFltDscp OBJECT-TYPE
      SYNTAX INTEGER (-1..63)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { extIpFilterEntry 9 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.2.1.10
extIpFltMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            permit(1),
            deny(2)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { extIpFilterEntry 10 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.3
macFilterTable OBJECT-TYPE
      SYNTAX SEQUENCE OF MacFilterEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { aclTable 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.3.1
macFilterEntry OBJECT-TYPE
      SYNTAX MacFilterEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { macFltId }
      ::= { macFilterTable 1 }


MacFilterEntry ::=
      SEQUENCE {
            macFltId
                  INTEGER,
            macFltSrcMac
                  OCTET STRING,
```

```
            macFltSrcMacMask
                  OCTET STRING,
            macFltDstMac
                  OCTET STRING,
            macFltDstMacMask
                  OCTET STRING,
            macFltVlanId
                  INTEGER,
            macFltCos
                  INTEGER,
            macFltEthType
                  OCTET STRING,
            macFltEthTypeMask
                  OCTET STRING,
            macFltMode
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.3.1.1
macFltId OBJECT-TYPE
      SYNTAX INTEGER (2000..2999)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { macFilterEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.3.1.2
macFltSrcMac OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { macFilterEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.3.1.3
macFltSrcMacMask OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { macFilterEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.3.1.4
macFltDstMac OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { macFilterEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.3.1.5
```

```
macFltDstMacMask OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { macFilterEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.3.1.6
macFltVlanId OBJECT-TYPE
      SYNTAX INTEGER (0..4094)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { macFilterEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.3.1.7
macFltCos OBJECT-TYPE
      SYNTAX INTEGER (-1..7)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { macFilterEntry 7 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.3.1.8
macFltEthType OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { macFilterEntry 8 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.3.1.9
macFltEthTypeMask OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { macFilterEntry 9 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.3.1.10
macFltMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            permit(1),
            deny(2)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
```

```
            "Description."
      ::= { macFilterEntry 10 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.4
portBaseAclTable OBJECT-TYPE
      SYNTAX SEQUENCE OF PortBaseAclEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { aclTable 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.4.1
portBaseAclEntry OBJECT-TYPE
      SYNTAX PortBaseAclEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { portBaseAclIndex }
      ::= { portBaseAclTable 1 }


PortBaseAclEntry ::=
      SEQUENCE {
            portBaseAclIndex
                  Integer32,
            portBaseAclFltMode
                  INTEGER,
            portBaseAclSrcMac
                  OCTET STRING,
            portBaseAclSrcMacMask
                  OCTET STRING,
            portBaseAclDstMac
                  OCTET STRING,
            portBaseAclDstMacMask
                  OCTET STRING,
            portBaseAclVlan
                  INTEGER,
            portBaseAclVlanMask
                  INTEGER,
            portBaseAclCos
                  INTEGER,
            portBaseAclEthernetType
                  OCTET STRING,
            portBaseAclSrcIp
                  IpAddress,
            portBaseAclSrcIpMask
                  IpAddress,
            portBaseAclDstIp
                  IpAddress,
            portBaseAclDstIpMask
                  IpAddress,
            portBaseAclProtocol
                  INTEGER,
            portBaseAclProtocolMask
                  INTEGER,
```

```
            portBaseAclTosDscp
                  INTEGER,
            portBaseAclTosDscpMask
                  INTEGER,
            portBaseAclSrcPort
                  INTEGER,
            portBaseAclSrcPortMask
                  OCTET STRING,
            portBaseAclDstPort
                  INTEGER,
            portBaseAclDstPortMask
                  OCTET STRING
       }

-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.4.1.1
portBaseAclIndex OBJECT-TYPE
      SYNTAX Integer32 (5000..5999)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portBaseAclEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.4.1.2
portBaseAclFltMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            permit(1),
            deny(2)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portBaseAclEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.4.1.3
portBaseAclSrcMac OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portBaseAclEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.4.1.4
portBaseAclSrcMacMask OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portBaseAclEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.4.1.5
```

```
portBaseAclDstMac OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portBaseAclEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.4.1.6
portBaseAclDstMacMask OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portBaseAclEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.4.1.7
portBaseAclVlan OBJECT-TYPE
      SYNTAX INTEGER (0..4094)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portBaseAclEntry 7 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.4.1.8
portBaseAclVlanMask OBJECT-TYPE
      SYNTAX INTEGER (0..4095)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portBaseAclEntry 8 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.4.1.9
portBaseAclCos OBJECT-TYPE
      SYNTAX INTEGER (-1..7)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portBaseAclEntry 9 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.4.1.10
portBaseAclEthernetType OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portBaseAclEntry 10 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.4.1.11
portBaseAclSrcIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portBaseAclEntry 11 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.4.1.12
portBaseAclSrcIpMask OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portBaseAclEntry 12 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.4.1.13
portBaseAclDstIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portBaseAclEntry 13 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.4.1.14
portBaseAclDstIpMask OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portBaseAclEntry 14 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.4.1.15
portBaseAclProtocol OBJECT-TYPE
      SYNTAX INTEGER (-1..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portBaseAclEntry 15 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.4.1.16
portBaseAclProtocolMask OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portBaseAclEntry 16 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.4.1.17
portBaseAclTosDscp OBJECT-TYPE
      SYNTAX INTEGER (-1..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portBaseAclEntry 17 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.4.1.18
portBaseAclTosDscpMask OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portBaseAclEntry 18 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.4.1.19
portBaseAclSrcPort OBJECT-TYPE
      SYNTAX INTEGER (-1..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portBaseAclEntry 19 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.4.1.20
portBaseAclSrcPortMask OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portBaseAclEntry 20 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.4.1.21
portBaseAclDstPort OBJECT-TYPE
      SYNTAX INTEGER (-1..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portBaseAclEntry 21 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.4.1.22
portBaseAclDstPortMask OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portBaseAclEntry 22 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.5
qosBaseAclTable OBJECT-TYPE
      SYNTAX SEQUENCE OF QosBaseAclEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { aclTable 5 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.5.1
qosBaseAclEntry OBJECT-TYPE
      SYNTAX QosBaseAclEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { qosBaseAclIndex }
      ::= { qosBaseAclTable 1 }


QosBaseAclEntry ::=
      SEQUENCE {
            qosBaseAclIndex
                  Integer32,
            qosBaseAclOutPacketPri
                  INTEGER,
            qosBaseAclHwTransQueue
                  INTEGER,
            qosBaseAclRulePri
                  INTEGER,
            qosBaseAclSrcMac
                  OCTET STRING,
            qosBaseAclSrcMacMask
                  OCTET STRING,
            qosBaseAclDstMac
                  OCTET STRING,
            qosBaseAclDstMacMask
                  OCTET STRING,
            qosBaseAclVlan
                  INTEGER,
            qosBaseAclVlanMask
                  INTEGER,
            qosBaseAclCos
                  INTEGER,
            qosBaseAclEthernetType
                  OCTET STRING,
            qosBaseAclSrcIp
                  IpAddress,
            qosBaseAclSrcIpMask
                  IpAddress,
            qosBaseAclDstIp
                  IpAddress,
            qosBaseAclDstIpMask
                  IpAddress,
            qosBaseAclProtocol
                  INTEGER,
```

```
            qosBaseAclProtocolMask
                  INTEGER,
            qosBaseAclTosDscp
                  INTEGER,
            qosBaseAclTosDscpMask
                  INTEGER,
            qosBaseAclSrcPort
                  INTEGER,
            qosBaseAclSrcPortMask
                  OCTET STRING,
            qosBaseAclDstPort
                  INTEGER,
            qosBaseAclDstPortMask
                  OCTET STRING
       }

-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.5.1.1
qosBaseAclIndex OBJECT-TYPE
      SYNTAX Integer32 (6000..6999)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { qosBaseAclEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.5.1.2
qosBaseAclOutPacketPri OBJECT-TYPE
      SYNTAX INTEGER (0..8)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { qosBaseAclEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.5.1.3
qosBaseAclHwTransQueue OBJECT-TYPE
      SYNTAX INTEGER (0..7)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { qosBaseAclEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.5.1.4
qosBaseAclRulePri OBJECT-TYPE
      SYNTAX INTEGER (1..12)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { qosBaseAclEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.5.1.5
qosBaseAclSrcMac OBJECT-TYPE
      SYNTAX OCTET STRING
```

```
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { qosBaseAclEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.5.1.6
qosBaseAclSrcMacMask OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { qosBaseAclEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.5.1.7
qosBaseAclDstMac OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { qosBaseAclEntry 7 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.5.1.8
qosBaseAclDstMacMask OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { qosBaseAclEntry 8 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.5.1.9
qosBaseAclVlan OBJECT-TYPE
      SYNTAX INTEGER (0..4094)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { qosBaseAclEntry 9 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.5.1.10
qosBaseAclVlanMask OBJECT-TYPE
      SYNTAX INTEGER (0..4095)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { qosBaseAclEntry 10 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.5.1.11
qosBaseAclCos OBJECT-TYPE
```

```
      SYNTAX INTEGER (-1..7)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { qosBaseAclEntry 11 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.5.1.12
qosBaseAclEthernetType OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { qosBaseAclEntry 12 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.5.1.13
qosBaseAclSrcIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { qosBaseAclEntry 13 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.5.1.14
qosBaseAclSrcIpMask OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { qosBaseAclEntry 14 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.5.1.15
qosBaseAclDstIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { qosBaseAclEntry 15 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.5.1.16
qosBaseAclDstIpMask OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { qosBaseAclEntry 16 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.5.1.17
```

```
qosBaseAclProtocol OBJECT-TYPE
      SYNTAX INTEGER (-1..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { qosBaseAclEntry 17 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.5.1.18
qosBaseAclProtocolMask OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { qosBaseAclEntry 18 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.5.1.19
qosBaseAclTosDscp OBJECT-TYPE
      SYNTAX INTEGER (-1..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { qosBaseAclEntry 19 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.5.1.20
qosBaseAclTosDscpMask OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { qosBaseAclEntry 20 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.5.1.21
qosBaseAclSrcPort OBJECT-TYPE
      SYNTAX INTEGER (-1..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { qosBaseAclEntry 21 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.5.1.22
qosBaseAclSrcPortMask OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { qosBaseAclEntry 22 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.5.1.23
qosBaseAclDstPort OBJECT-TYPE
      SYNTAX INTEGER (-1..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { qosBaseAclEntry 23 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.2.5.1.24
qosBaseAclDstPortMask OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { qosBaseAclEntry 24 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.3
aclEffectTable OBJECT-TYPE
      SYNTAX SEQUENCE OF AclEffectEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { v1600dAcl 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.10.3.1
aclEffectEntry OBJECT-TYPE
      SYNTAX AclEffectEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { aclIndex }
      ::= { aclEffectTable 1 }


AclEffectEntry ::=
      SEQUENCE {
            aclIndex
                  Integer32,
            aclPortList
                  OCTET STRING
       }

-- 1.3.6.1.4.1.37950.1.1.5.10.10.3.1.1
aclIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { aclEffectEntry 1 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.10.10.3.1.2
aclPortList OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { aclEffectEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.11
v1600dStaticRoute OBJECT IDENTIFIER ::= { v1600dSwitch 11 }


-- 1.3.6.1.4.1.37950.1.1.5.10.11.1
staticRouteCfg OBJECT IDENTIFIER ::= { v1600dStaticRoute 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.11.1.1
staticRouteIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { staticRouteCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.11.1.2
staticRouteIpMask OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { staticRouteCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.11.1.3
staticRouteIpGw OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { staticRouteCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.11.1.4
staticRouteAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            delete(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { staticRouteCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.11.2
staticRouteTable OBJECT-TYPE
      SYNTAX SEQUENCE OF StaticRouteEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { v1600dStaticRoute 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.11.2.1
staticRouteEntry OBJECT-TYPE
      SYNTAX StaticRouteEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { staticRouteItem }
      ::= { staticRouteTable 1 }


StaticRouteEntry ::=
      SEQUENCE {
            staticRouteItem
                  INTEGER,
            staticRouteIpAddr
                  IpAddress,
            staticRouteMask
                  IpAddress,
            staticRouteGw
                  IpAddress
       }

-- 1.3.6.1.4.1.37950.1.1.5.10.11.2.1.1
staticRouteItem OBJECT-TYPE
      SYNTAX INTEGER (1..512)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { staticRouteEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.11.2.1.2
staticRouteIpAddr OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { staticRouteEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.11.2.1.3
staticRouteMask OBJECT-TYPE
      SYNTAX IpAddress
```

```
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { staticRouteEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.11.2.1.4
staticRouteGw OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { staticRouteEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12
v1600dSysCfg OBJECT IDENTIFIER ::= { v1600dSwitch 12 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.1
restartSystem OBJECT-TYPE
      SYNTAX INTEGER { enable(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { v1600dSysCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.2
pingIP OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { v1600dSysCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.3
cpuLoad OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { v1600dSysCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.4
memoryLoad OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { v1600dSysCfg 4 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.10.12.5
systemInfo OBJECT IDENTIFIER ::= { v1600dSysCfg 5 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.5.1
sysHostName OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { systemInfo 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.5.2
sysContact OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { systemInfo 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.5.3
sysLocation OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { systemInfo 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.5.4
sysFirmVersion OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { systemInfo 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.5.5
sysHardVersion OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { systemInfo 5 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.5.6
mibSup OBJECT-TYPE
      SYNTAX OCTET STRING
```

```
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { systemInfo 6 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.5.7
sysMac OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { systemInfo 7 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.5.8
sysRunningTime OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { systemInfo 8 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.5.9
sysTemperature OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { systemInfo 9 }

-- 1.3.6.1.4.1.37950.1.1.5.10.12.6
arpTable OBJECT-TYPE
      SYNTAX SEQUENCE OF ArpEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { v1600dSysCfg 6 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.6.1
arpEntry OBJECT-TYPE
      SYNTAX ArpEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { arpIndex }
      ::= { arpTable 1 }


ArpEntry ::=
      SEQUENCE {
```

```
            arpIndex
                  Integer32,
            arpmacAddr
                  OCTET STRING,
            arpIPAddr
                  IpAddress,
            arpType
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.10.12.6.1.1
arpIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { arpEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.6.1.2
arpmacAddr OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { arpEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.6.1.3
arpIPAddr OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { arpEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.6.1.4
arpType OBJECT-TYPE
      SYNTAX INTEGER
            {
            static(0),
            dynamic(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { arpEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.7
snmpCfg OBJECT IDENTIFIER ::= { v1600dSysCfg 7 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.7.1
```

```
snmpv1v2Config OBJECT IDENTIFIER ::= { snmpCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.7.1.1
communityNameSetting OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { snmpv1v2Config 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.7.1.2
accessRightSetting OBJECT-TYPE
      SYNTAX INTEGER
            {
            read-only(1),
            read-write(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { snmpv1v2Config 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.7.1.3
communitycommit OBJECT-TYPE
      SYNTAX INTEGER
            {
            commit(1),
            delete(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { snmpv1v2Config 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.7.2
communityTable OBJECT-TYPE
      SYNTAX SEQUENCE OF CommunityEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { snmpCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.7.2.1
communityEntry OBJECT-TYPE
      SYNTAX CommunityEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { communityIndex }
```

```
      ::= { communityTable 1 }


CommunityEntry ::=
      SEQUENCE {
            communityIndex
                  Integer32,
            communityName
                  OCTET STRING,
            accessRight
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.10.12.7.2.1.1
communityIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { communityEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.7.2.1.2
communityName OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { communityEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.7.2.1.3
accessRight OBJECT-TYPE
      SYNTAX INTEGER
            {
            read-only(1),
            read-write(2)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { communityEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.7.3
snmpv1v2TrapConfig OBJECT IDENTIFIER ::= { snmpCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.7.3.1
trapHostIpSetting OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { snmpv1v2TrapConfig 1 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.10.12.7.3.2
trapUdpPortSetting OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { snmpv1v2TrapConfig 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.7.3.3
trapCommunityNameSetting OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { snmpv1v2TrapConfig 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.7.3.4
trapVersionSetting OBJECT-TYPE
      SYNTAX INTEGER
            {
            snmp-v1(1),
            snmp-v2c(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { snmpv1v2TrapConfig 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.7.3.5
trapAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            delete(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { snmpv1v2TrapConfig 5 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.7.4
snmpv1v2TrapTable OBJECT-TYPE
      SYNTAX SEQUENCE OF Snmpv1v2TrapEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { snmpCfg 4 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.10.12.7.4.1
snmpv1v2TrapEntry OBJECT-TYPE
      SYNTAX Snmpv1v2TrapEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { trapIndex }
      ::= { snmpv1v2TrapTable 1 }


Snmpv1v2TrapEntry ::=
      SEQUENCE {
            trapIndex
                  Integer32,
            trapHostIp
                  IpAddress,
            trapUdpPort
                  Integer32,
            trapCommunityName
                  OCTET STRING,
            trapVersion
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.10.12.7.4.1.1
trapIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { snmpv1v2TrapEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.7.4.1.2
trapHostIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { snmpv1v2TrapEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.7.4.1.3
trapUdpPort OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { snmpv1v2TrapEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.7.4.1.4
trapCommunityName OBJECT-TYPE
      SYNTAX OCTET STRING
```

```
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { snmpv1v2TrapEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.7.4.1.5
trapVersion OBJECT-TYPE
      SYNTAX INTEGER
            {
            snmp-v1(1),
            snmp-v2c(2)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { snmpv1v2TrapEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.8
configFile OBJECT IDENTIFIER ::= { v1600dSysCfg 8 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.8.1
restoreConfiguration OBJECT-TYPE
      SYNTAX INTEGER { enable(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { configFile 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.8.2
saveConfiguration OBJECT-TYPE
      SYNTAX INTEGER { enable(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { configFile 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.8.3
uploadDownloadCfgFile OBJECT IDENTIFIER ::= { configFile 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.8.3.1
cfgFileName OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uploadDownloadCfgFile 1 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.10.12.8.3.2
tftpServerIPAddr OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uploadDownloadCfgFile 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.8.3.3
cfgFileAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            upload(1),
            download(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uploadDownloadCfgFile 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.9
systemUpgrade OBJECT IDENTIFIER ::= { v1600dSysCfg 9 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.9.1
tftpServerIP OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { systemUpgrade 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.9.2
fileType OBJECT-TYPE
      SYNTAX INTEGER
            {
            bld(1),
            kernel(2),
            rootfs(3)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { systemUpgrade 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.9.3
fileName OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
```

```
            "Description."
      ::= { systemUpgrade 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.9.4
upgradeCommit OBJECT-TYPE
      SYNTAX INTEGER { commit(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { systemUpgrade 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.10
auxPortCfg OBJECT IDENTIFIER ::= { v1600dSysCfg 10 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.10.1
auxIP OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { auxPortCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.10.2
auxIPMask OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { auxPortCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.10.3
auxIPAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            edit(1),
            delete(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { auxPortCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.11
fanCfg OBJECT IDENTIFIER ::= { v1600dSysCfg 11 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.11.1
fanMode OBJECT-TYPE
      SYNTAX INTEGER
```

```
            {
            open(1),
            close(2),
            auto(3)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { fanCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.11.2
fanOpenTemperature OBJECT-TYPE
      SYNTAX INTEGER (20..80)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { fanCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.12
rtcCfg OBJECT IDENTIFIER ::= { v1600dSysCfg 12 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.12.1
year OBJECT-TYPE
      SYNTAX INTEGER (2000..2099)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { rtcCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.12.2
month OBJECT-TYPE
      SYNTAX INTEGER (1..12)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { rtcCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.12.3
day OBJECT-TYPE
      SYNTAX INTEGER (1..31)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { rtcCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.12.4
hour OBJECT-TYPE
      SYNTAX INTEGER (0..23)
```

```
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { rtcCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.12.5
minute OBJECT-TYPE
      SYNTAX INTEGER (0..59)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { rtcCfg 5 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.12.6
second OBJECT-TYPE
      SYNTAX INTEGER (0..59)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { rtcCfg 6 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.12.7
rtcAction OBJECT-TYPE
      SYNTAX INTEGER { commit(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { rtcCfg 7 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.13
syslogcfg OBJECT IDENTIFIER ::= { v1600dSysCfg 13 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.13.1
syslogServerIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { syslogcfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.13.2
syslogServerPort OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { syslogcfg 2 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.10.12.13.3
syslogFlashLevel OBJECT-TYPE
      SYNTAX INTEGER
            {
            debug(0),
            info(1),
            notice(2),
            warning(3),
            major(4),
            critical(5),
            alert(6),
            emerg(7)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { syslogcfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.13.4
restoreSyslog OBJECT-TYPE
      SYNTAX INTEGER { commit(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { syslogcfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.13.5
saveSyslog OBJECT-TYPE
      SYNTAX INTEGER { commit(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { syslogcfg 5 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.13.6
uploadSyslog OBJECT IDENTIFIER ::= { syslogcfg 6 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.13.6.1
uploadSyslogName OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uploadSyslog 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.13.6.2
tftpSeverSyslog OBJECT-TYPE
      SYNTAX IpAddress
```

```
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uploadSyslog 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.13.6.3
uploadAction OBJECT-TYPE
      SYNTAX INTEGER { commit(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { uploadSyslog 3 }

-- 1.3.6.1.4.1.37950.1.1.5.10.12.14
timeParam OBJECT IDENTIFIER ::= { v1600dSysCfg 14 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.14.1
timeZone OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { timeParam 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.14.2
ntpServer OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { timeParam 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.15
dasParam OBJECT IDENTIFIER ::= { v1600dSysCfg 15 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.15.1
primaryDNS OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { dasParam 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.15.2
secondDNS OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
```

```
      DESCRIPTION
            "Description."
      ::= { dasParam 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.15.3
commit OBJECT-TYPE
      SYNTAX INTEGER { commit(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { dasParam 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.16
loginAccessList OBJECT IDENTIFIER ::= { v1600dSysCfg 16 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.16.1
loginAccessListEn OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1),
            clear(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { loginAccessList 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.16.2
loginAccessListCfg OBJECT IDENTIFIER ::= { loginAccessList 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.16.2.1
filterAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            deny(0),
            permit(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { loginAccessListCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.16.2.2
protocol OBJECT-TYPE
      SYNTAX INTEGER
            {
            telnet(0),
            web(1),
            snmp(2)
```

```
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { loginAccessListCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.16.2.3
sourceIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { loginAccessListCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.16.2.4
ipMask OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { loginAccessListCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.16.2.5
action OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            del(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { loginAccessListCfg 5 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.16.3
loginAccessListTable OBJECT-TYPE
      SYNTAX SEQUENCE OF LoginAccessListEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { loginAccessList 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.16.3.1
loginAccessListEntry OBJECT-TYPE
      SYNTAX LoginAccessListEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
```

```
      INDEX { filterActionS, protocolS, sourceIpS, ipMaskS }
      ::= { loginAccessListTable 1 }


LoginAccessListEntry ::=
      SEQUENCE {
            filterActionS
                  INTEGER,
            protocolS
                  INTEGER,
            sourceIpS
                  IpAddress,
            ipMaskS
                  IpAddress
       }

-- 1.3.6.1.4.1.37950.1.1.5.10.12.16.3.1.1
filterActionS OBJECT-TYPE
      SYNTAX INTEGER
            {
            deny(1),
            permit(2)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { loginAccessListEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.16.3.1.2
protocolS OBJECT-TYPE
      SYNTAX INTEGER
            {
            telnet(1),
            web(2),
            snmp(3)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { loginAccessListEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.16.3.1.3
sourceIpS OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { loginAccessListEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.12.16.3.1.4
ipMaskS OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
```

```
      STATUS current
      DESCRIPTION
            "Description."
      ::= { loginAccessListEntry 4 }

-- 1.3.6.1.4.1.37950.1.1.5.10.13
v1600dAlarm OBJECT IDENTIFIER ::= { v1600dSwitch 13 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.1
ponTransceiverTable OBJECT-TYPE
      SYNTAX SEQUENCE OF PonTransceiverEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { v1600dAlarm 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.1.1
ponTransceiverEntry OBJECT-TYPE
      SYNTAX PonTransceiverEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { transceiverPonIndex }
      ::= { ponTransceiverTable 1 }


PonTransceiverEntry ::=
      SEQUENCE {
            transceiverPonIndex
                  INTEGER,
            tempperature
                  OCTET STRING,
            voltage
                  OCTET STRING,
            biasCurrent
                  OCTET STRING,
            transmitPower
                  OCTET STRING
       }

-- 1.3.6.1.4.1.37950.1.1.5.10.13.1.1.1
transceiverPonIndex OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponTransceiverEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.1.1.2
tempperature OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
```

```
      DESCRIPTION
            "Description."
      ::= { ponTransceiverEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.1.1.3
voltage OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponTransceiverEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.1.1.4
biasCurrent OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponTransceiverEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.1.1.5
transmitPower OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponTransceiverEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.2
alarmMsg OBJECT IDENTIFIER ::= { v1600dAlarm 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.2.1
dataUpLinkPort OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmMsg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.2.2
dataPon OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmMsg 2 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.10.13.2.3
dataOnu OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmMsg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.2.4
dataOnuPort OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmMsg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.2.5
dataTrapOID OBJECT-TYPE
      SYNTAX OBJECT IDENTIFIER
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmMsg 5 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.2.6
dataTrapClass OBJECT-TYPE
      SYNTAX INTEGER
            {
            clear_alarm(0),
            raised_alarm(1),
            no_clear_alarm(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmMsg 6 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.2.7
dataMac OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmMsg 7 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.2.8
dataTime OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
```

```
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmMsg 8 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.2.9
dateAlarmLevel OBJECT-TYPE
      SYNTAX INTEGER
            {
            debug(0),
            info(1),
            notice(2),
            warning(3),
            major(4),
            criterr(5),
            alert(6),
            emerg(7)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmMsg 9 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.2.10
dataValue OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmMsg 10 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.2.11
dataAlarmType OBJECT-TYPE
      SYNTAX INTEGER
            {
            equipment(0),
            process(1),
            communit(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmMsg 11 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.2.12
dataSynOID OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmMsg 12 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.10.13.3
ponOpticalAlarmControl OBJECT IDENTIFIER ::= { v1600dAlarm 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.3.1
ponOpticalAlarmDisCfg OBJECT IDENTIFIER ::= { ponOpticalAlarmControl
1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.3.1.1
ponAlarmPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponOpticalAlarmDisCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.3.1.2
ponOpticalType OBJECT-TYPE
      SYNTAX INTEGER
            {
            txPowerHighAlarm(1),
            txPowerLowAlarm(2),
            txBiasHighAlarm(3),
            txBiasLowAlarm(4),
            vccHighAlarm(5),
            vccLowAlarm(6),
            tempHighAlarm(7),
            tempLowAlarm(8)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponOpticalAlarmDisCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.3.1.3
ponOpticalAlarmDis OBJECT-TYPE
      SYNTAX INTEGER { disable(0) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponOpticalAlarmDisCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.3.1.4
ponOpticalDisAction OBJECT-TYPE
      SYNTAX INTEGER { commit(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponOpticalAlarmDisCfg 4 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.10.13.3.2
ponOpticalAlarmEnCfg OBJECT IDENTIFIER ::= { ponOpticalAlarmControl 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.3.2.1
ponOpticalAlarmPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponOpticalAlarmEnCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.3.2.2
ponOpticalAlarmType OBJECT-TYPE
      SYNTAX INTEGER
            {
            txPowerHighAlarm(1),
            txPowerLowAlarm(2),
            txBiasHighAlarm(3),
            txBiasLowAlarm(4),
            vccHighAlarm(5),
            vccLowAlarm(6),
            tempHighAlarm(7),
            tempLowAlarm(8)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponOpticalAlarmEnCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.3.2.3
ponOpticalAlarmEn OBJECT-TYPE
      SYNTAX INTEGER { enable(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponOpticalAlarmEnCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.3.2.4
ponOpticalAlarmThld OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponOpticalAlarmEnCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.3.2.5
ponOpticalClearThld OBJECT-TYPE
      SYNTAX OCTET STRING
```

```
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponOpticalAlarmEnCfg 5 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.3.2.6
ponOpticalAlarmEnAction OBJECT-TYPE
      SYNTAX INTEGER { commit(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponOpticalAlarmEnCfg 6 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.3.3
ponOpticalAlarmTable OBJECT-TYPE
      SYNTAX SEQUENCE OF PonOpticalAlarmEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponOpticalAlarmControl 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.3.3.1
ponOpticalAlarmEntry OBJECT-TYPE
      SYNTAX PonOpticalAlarmEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { ponAlarmPonIndex, ponAlarmType }
      ::= { ponOpticalAlarmTable 1 }


PonOpticalAlarmEntry ::=
      SEQUENCE {
            ponAlarmPonIndex
                  Integer32,
            ponAlarmType
                  INTEGER,
            ponOpticalAlarmStatus
                  INTEGER,
            ponOpticalAlarmThldVal
                  OCTET STRING,
            ponOpticalClearThldVal
                  OCTET STRING
       }

-- 1.3.6.1.4.1.37950.1.1.5.10.13.3.3.1.1
ponAlarmPonIndex OBJECT-TYPE
      SYNTAX Integer32 (1..16)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { ponOpticalAlarmEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.3.3.1.2
ponAlarmType OBJECT-TYPE
      SYNTAX INTEGER
            {
            txPowerHighAlarm(1),
            txPowerLowAlarm(2),
            txBiasHighAlarm(3),
            txBiasLowAlarm(4),
            vccHighAlarm(5),
            vccLowAlarm(6),
            tempHighAlarm(7),
            tempLowAlarm(8)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponOpticalAlarmEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.3.3.1.3
ponOpticalAlarmStatus OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponOpticalAlarmEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.3.3.1.4
ponOpticalAlarmThldVal OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponOpticalAlarmEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.3.3.1.5
ponOpticalClearThldVal OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponOpticalAlarmEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.4
alarmCtrl OBJECT IDENTIFIER ::= { v1600dAlarm 4 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.10.13.4.1
alarmControlCfg OBJECT IDENTIFIER ::= { alarmCtrl 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.4.1.1
alarmControlType OBJECT-TYPE
      SYNTAX INTEGER
            {
            fan(1),
            download-file-failed(2),
            upload-file-failed(3),
            upgrade-file-failed(4),
            port-updown(5),
            port-loopback(6),
            pon-deregister(7),
            pon-register-failed(8),
            pon-disable(9),
            pon-txpower-high(10),
            pon-txpower-low(11),
            pon-txbias-high(12),
            pon-txbias-low(13),
            pon-vcc-high(14),
            pon-vcc-low(15),
            pon-temp-high(16),
            pon-temp-low(17),
            pon-los(18),
            onu-deregister(19),
            onu-link-lost(20),
            onu-illegal-register(21),
            onu-auth-failed (22),
            onu-mac-conflict(23),
            onu-loid-conflict(24),
            onu-critical-event(25),
            onu-dying-gasp(26),
            onu-link-fault(27),
            onu-link-event(28),
            onu-event-notific(29),
            reset(30),
            config-save(31),
            config-erase(32),
            download-file-success(33),
            upload-file-success(34),
            upgrade-file-success(35),
            pon-register(36),
            pon-enable(37),
            pon-los-recovery(38),
            onu-register(39),
            onu-link-discover(40),
            onu-auth-success(41),
            onu-deauth-success(42),
            onu-pon-rxpower-high(43),
            onu-pon-rxpower-low(44),
            onu-pon-txpower-high(45),
            onu-pon-txpower-low(46),
            onu-pon-txbias-high(47),
            onu-pon-txbias-low(48),
            onu-pon-vcc-high(49),
```

```
            onu-pon-vcc-low (50),
            onu-pon-temp-high (51),
            onu-pon-temp-low(52),
            onu-port-autoneg-failure(53),
            onu-port-los(54),
            onu-port-failure(55),
            onu-port-loopback(56),
            onu-pots-failure(57)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmControlCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.4.1.2
alarmOutputType OBJECT-TYPE
      SYNTAX INTEGER
            {
            print(0),
            record(1),
            trap(2),
            remote(3),
            all(4)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmControlCfg 2 }
-- 1.3.6.1.4.1.37950.1.1.5.10.13.4.1.3
alarmControlEnable OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmControlCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.4.1.4
alarmControlAction OBJECT-TYPE
      SYNTAX INTEGER { commit(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmControlCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.4.2
alarmControlTable OBJECT-TYPE
      SYNTAX SEQUENCE OF AlarmControlEntry
      MAX-ACCESS not-accessible
```

```
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmCtrl 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.4.2.1
alarmControlEntry OBJECT-TYPE
      SYNTAX AlarmControlEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { alarmControlId }
      ::= { alarmControlTable 1 }


AlarmControlEntry ::=
      SEQUENCE {
            alarmControlId
                  Integer32,
            alarmControlTypeS
                  OCTET STRING,
            alarmPrintStatus
                  INTEGER,
            alarmRecordStatus
                  INTEGER,
            alarmTrapStatus
                  INTEGER,
            alarmRemoteStatus
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.10.13.4.2.1.1
alarmControlId OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmControlEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.4.2.1.2
alarmControlTypeS OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmControlEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.4.2.1.3
alarmPrintStatus OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
```

```
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmControlEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.4.2.1.4
alarmRecordStatus OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmControlEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.4.2.1.5
alarmTrapStatus OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmControlEntry 5 }

-- 1.3.6.1.4.1.37950.1.1.5.10.13.4.2.1.6
alarmRemoteStatus OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmControlEntry 6 }

-- 1.3.6.1.4.1.37950.1.1.5.10.13.4.3
alarmControlThldCfg OBJECT IDENTIFIER ::= { alarmCtrl 3 }

-- 1.3.6.1.4.1.37950.1.1.5.10.13.4.3.1
alarmControlThldType OBJECT-TYPE
      SYNTAX INTEGER
            {
            temp-high(1),
            temp-low(2),
            cpu-usage-high(3),
            mem-usage-high(4)
```

```
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmControlThldCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.4.3.2
alarmOutputThldType OBJECT-TYPE
      SYNTAX INTEGER
            {
            print(0),
            record(1),
            trap(2),
            remote(3),
            all(4)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmControlThldCfg 2 }

-- 1.3.6.1.4.1.37950.1.1.5.10.13.4.3.3
alarmControlThldEnable OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enablel(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmControlThldCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.4.3.4
alarmControlThldAlarm OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmControlThldCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.4.3.5
alarmControlThldClear OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmControlThldCfg 5 }

alarmControlThldAction OBJECT-TYPE
      SYNTAX INTEGER { commit(1) }
```

```
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmControlThldCfg 6 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.4.4
alarmControlThldTable OBJECT-TYPE
      SYNTAX SEQUENCE OF AlarmControlThldEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmCtrl 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.4.4.1
alarmControlThldEntry OBJECT-TYPE
      SYNTAX AlarmControlThldEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { alarmCtrlThldId }
      ::= { alarmControlThldTable 1 }


AlarmControlThldEntry ::=
      SEQUENCE {
            alarmCtrlThldId
                  Integer32,
            alarmCtrlThldType
                  INTEGER,
            alarmPrintThldStatus
                  INTEGER,
            alarmRecordThldStatus
                  INTEGER,
            alarmTrapThldStatus
                  INTEGER,
            alarmRemoteThldStatus
                  INTEGER,
            alarmCtrlThldAlarm
                  OCTET STRING,
            alarmCtrlThldClear
                  OCTET STRING
       }

-- 1.3.6.1.4.1.37950.1.1.5.10.13.4.4.1.1
alarmCtrlThldId OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmControlThldEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.4.4.1.2
```

```
alarmCtrlThldType OBJECT-TYPE
      SYNTAX INTEGER
            {
            temp-high(1),
            temp-low(2),
            cpu-usage-high(3),
            mem-usage-high(4)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmControlThldEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.4.4.1.3
alarmPrintThldStatus OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmControlThldEntry 3 }

-- 1.3.6.1.4.1.37950.1.1.5.10.13.4.4.1.4
alarmRecordThldStatus OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmControlThldEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.4.4.1.5
alarmTrapThldStatus OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmControlThldEntry 5 }

-- 1.3.6.1.4.1.37950.1.1.5.10.13.4.4.1.6
alarmRemoteThldStatus OBJECT-TYPE
      SYNTAX INTEGER
            {
```

```
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmControlThldEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.4.4.1.7
alarmCtrlThldAlarm OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmControlThldEntry 7 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.4.4.1.8
alarmCtrlThldClear OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmControlThldEntry 8 }



-- 1.3.6.1.4.1.37950.1.1.5.10.13.5
alarmOID OBJECT IDENTIFIER ::= { v1600dAlarm 5 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.1
tempHigh OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.2
tempLow OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.3
cpuUsageHigh OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
```

```
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.4
memUsageHigh OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 4 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.5
fan OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 5 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.6
downloadFileFailed OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 6 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.7
uploadFileFailed OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 7 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.8
upgradeFileFailled OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 8 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.9
portUpdown OBJECT-TYPE
      SYNTAX Integer32
```

```
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 9 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.10
portLoopback OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 10 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.11
ponDeregister OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 11 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.12
ponRegisterFailed OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 12 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.13
ponDisable OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 13 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.14
ponTxPowerHigh OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 14 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.15
ponTxPowerLow OBJECT-TYPE
```

```
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 15 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.16
ponTxBisaHigh OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 16 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.17
ponTxbiasLow OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 17 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.18
ponVccHigh OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 18 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.19
ponVccLow OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 19 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.20
ponTempHigh OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 20 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.21
```

```
ponTempLow OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 21 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.22
ponLos OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 22 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.23
onuDeregister OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 23 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.24
onuLinkLost OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 24 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.25
onuIllegalRegister OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 25 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.26
onuAuthFailed OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 26 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.27
onuMacConflict OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 27 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.28
onuLoidConflict OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 28 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.29
onuCriticalEvent OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 29 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.30
onuDyingGasp OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 30 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.31
onuLinkFault OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 31 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.32
onuLinkEvent OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 32 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.33
onuEventNotific OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 33 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.34
onuOmLaoDetect OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 34 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.35
onuOmLolDetect OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 35 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.36
alarmMax OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 36 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.37
reset OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 37 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.38
configSave OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 38 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.39
configErase OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 39 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.40
dnLoadFileSuccess OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 40 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.41
uploadFileSuccess OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 41 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.42
upgradeFileSuccess OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 42 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.43
ponRegister OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 43 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.44
ponEnable OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { alarmOID 44 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.45
ponLosRecovery OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 45 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.46
onuRegister OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 46 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.47
onuLinkDiscover OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 47 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.48
onuAuthSuccess OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 48 }

-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.49
onuDeauthSuccess OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 49 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.50
onuUpgradeOver OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { alarmOID 50 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.51
onuFinish OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 51 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.52
onuPonRxPowerHigh OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 52 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.53
onuPonRxPowerLow OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 53 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.54
onuPonTxPowerHigh OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 54 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.55
onuPonTxPowerLow OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 55 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.56
onuPonTxBiasHigh OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
```

```
            "Description."
      ::= { alarmOID 56 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.57
onuPonTxBiasLow OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 57 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.58
onuPonVccHigh OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 58 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.59
onuPonVccLow OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 59 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.60
onuPonTempHigh OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 60 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.61
onuPonTempLow OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOID 61 }


-- 1.3.6.1.4.1.37950.1.1.5.10.13.5.62
onuPortAutoNegFailure OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
```

```
            DESCRIPTION
                  "Description."
            ::= { alarmOID 62 }


      -- 1.3.6.1.4.1.37950.1.1.5.10.13.5.63
      onuPortLos OBJECT-TYPE
            SYNTAX Integer32
            MAX-ACCESS read-write
            STATUS current
            DESCRIPTION
                  "Description."
            ::= { alarmOID 63 }


      -- 1.3.6.1.4.1.37950.1.1.5.10.13.5.64
      onuPortFailure OBJECT-TYPE
            SYNTAX Integer32
            MAX-ACCESS read-write
            STATUS current
            DESCRIPTION
                  "Description."
            ::= { alarmOID 64 }


      -- 1.3.6.1.4.1.37950.1.1.5.10.13.5.65
      onuPortLoopback OBJECT-TYPE
            SYNTAX Integer32
            MAX-ACCESS read-write
            STATUS current
            DESCRIPTION
                  "Description."
            ::= { alarmOID 65 }


      -- 1.3.6.1.4.1.37950.1.1.5.10.13.5.66
      onuPotsFailure OBJECT-TYPE
            SYNTAX Integer32
            MAX-ACCESS read-write
            STATUS current
            DESCRIPTION
                  "Description."
            ::= { alarmOID 66 }


      -- 1.3.6.1.4.1.37950.1.1.5.10.13.6
      alarmTrap OBJECT IDENTIFIER ::= { v1600dAlarm 6 }


      -- 1.3.6.1.4.1.37950.1.1.5.10.13.6.1
      dataAlarmTrap NOTIFICATION-TYPE
            OBJECTS { dataUpLinkPort, dataPon, dataOnu, dataOnuPort,
dataTrapOID,
                  dataTrapClass, dataMac, dataTime, dateAlarmLevel,
dataValue,
                  dataAlarmType, dataSynOID }
            STATUS current
            DESCRIPTION
                  "Description."
```

```
      ::= { alarmTrap 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.14
v1600dOltType OBJECT IDENTIFIER ::= { v1600dSwitch 14 }


-- 1.3.6.1.4.1.37950.1.1.5.10.14.1
oltType OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { v1600dOltType 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.15
v1600dLoopback OBJECT IDENTIFIER ::= { v1600dSwitch 15 }


-- 1.3.6.1.4.1.37950.1.1.5.10.15.1
loopbackEn OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { v1600dLoopback 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.15.2
loopbackCfg OBJECT IDENTIFIER ::= { v1600dLoopback 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.15.2.1
mode OBJECT-TYPE
      SYNTAX INTEGER
            {
            onlyAlarm(1),
            manualRecovery(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { loopbackCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.15.2.2
agingTime OBJECT-TYPE
      SYNTAX Integer32 (30..3600)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
```

```
            "Description."
      ::= { loopbackCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.10.15.3
loopbackTable OBJECT-TYPE
      SYNTAX SEQUENCE OF LoopbackEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { v1600dLoopback 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.15.3.1
loopbackEntry OBJECT-TYPE
      SYNTAX LoopbackEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { interfaceS }
      ::= { loopbackTable 1 }


LoopbackEntry ::=
      SEQUENCE {
            interfaceS
                  OCTET STRING,
            modeS
                  INTEGER,
            timeS
                  Integer32,
            srcInterface
                  OCTET STRING
       }

-- 1.3.6.1.4.1.37950.1.1.5.10.15.3.1.1
interfaceS OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { loopbackEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.10.15.3.1.2
modeS OBJECT-TYPE
      SYNTAX INTEGER
            {
            noShutdown(0),
            shutdown(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { loopbackEntry 2 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.10.15.3.1.3
timeS OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { loopbackEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.10.15.3.1.4
srcInterface OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { loopbackEntry 4 }

-- 1.3.6.1.4.1.37950.1.1.5.12
v1600dOnuMgmt OBJECT IDENTIFIER ::= { v1600d 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1
onuAuth OBJECT IDENTIFIER ::= { v1600dOnuMgmt 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.1
authModeTable OBJECT-TYPE
      SYNTAX SEQUENCE OF AuthModeEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAuth 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.1.1
authModeEntry OBJECT-TYPE
      SYNTAX AuthModeEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { onuAuthPonNo }
      ::= { authModeTable 1 }


AuthModeEntry ::=
      SEQUENCE {
            onuAuthPonNo
                  INTEGER,
            onuAuthMode
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.1.1.1.1
```

```
onuAuthPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { authModeEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.1.1.2
onuAuthMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            mac(1),
            loid(2),
            hybrid(3)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { authModeEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.2
whiteMaclistCfg OBJECT IDENTIFIER ::= { onuAuth 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.2.1
whiteMacPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { whiteMaclistCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.2.2
whiteMacValue OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { whiteMaclistCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.2.3
whiteMacAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            delete(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
```

```
            "Description."
      ::= { whiteMaclistCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.3
whiteMaclistTable OBJECT-TYPE
      SYNTAX SEQUENCE OF WhiteMaclistEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAuth 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.3.1
whiteMaclistEntry OBJECT-TYPE
      SYNTAX WhiteMaclistEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { whiteMacIndex }
      ::= { whiteMaclistTable 1 }


WhiteMaclistEntry ::=
      SEQUENCE {
            whiteMacIndex
                  Integer32,
            whiteMaclistPonNo
                  Integer32,
            whiteMaclistValue
                  OCTET STRING
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.1.3.1.1
whiteMacIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { whiteMaclistEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.3.1.2
whiteMaclistPonNo OBJECT-TYPE
      SYNTAX Integer32 (1..16)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { whiteMaclistEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.3.1.3
whiteMaclistValue OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
```

```
      STATUS current
      DESCRIPTION
            "Description."
      ::= { whiteMaclistEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.4
blackMaclistCfg OBJECT IDENTIFIER ::= { onuAuth 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.4.1
blackMacPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { blackMaclistCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.4.2
blackMacValue OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { blackMaclistCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.4.3
blackMacAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            delete(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { blackMaclistCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.5
blackMaclistTable OBJECT-TYPE
      SYNTAX SEQUENCE OF BlackMaclistEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAuth 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.5.1
blackMaclistEntry OBJECT-TYPE
      SYNTAX BlackMaclistEntry
      MAX-ACCESS not-accessible
      STATUS current
```

```
      DESCRIPTION
            "Description."
      INDEX { blackMacIndex }
      ::= { blackMaclistTable 1 }


BlackMaclistEntry ::=
      SEQUENCE {
            blackMacIndex
                  Integer32,
            blackMaclistPonNo
                  Integer32,
            blackMaclistValue
                  OCTET STRING
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.1.5.1.1
blackMacIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { blackMaclistEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.5.1.2
blackMaclistPonNo OBJECT-TYPE
      SYNTAX Integer32 (1..16)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { blackMaclistEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.5.1.3
blackMaclistValue OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { blackMaclistEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.6
loidListCfg OBJECT IDENTIFIER ::= { onuAuth 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.6.1
loidPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { loidListCfg 1 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.1.6.2
loid OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { loidListCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.6.3
loidpw OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { loidListCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.6.4
loidAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            delete(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { loidListCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.7
loidListTable OBJECT-TYPE
      SYNTAX SEQUENCE OF LoidListEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAuth 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.7.1
loidListEntry OBJECT-TYPE
      SYNTAX LoidListEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { loidIndex }
      ::= { loidListTable 1 }


LoidListEntry ::=
      SEQUENCE {
            loidIndex
```

```
                Integer32,
            loidListPonNo
                Integer32,
            loidValue
                OCTET STRING,
            loidpwValue
                OCTET STRING
        }

-- 1.3.6.1.4.1.37950.1.1.5.12.1.7.1.1
loidIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { loidListEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.7.1.2
loidListPonNo OBJECT-TYPE
      SYNTAX Integer32 (1..16)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { loidListEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.7.1.3
loidValue OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { loidListEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.7.1.4
loidpwValue OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { loidListEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.8
noAuthOnu OBJECT IDENTIFIER ::= { onuAuth 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.8.1
ponNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
```

```
            "Description."
      ::= { noAuthOnu 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.8.2
noAuthOnuId OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { noAuthOnu 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.9
onuListTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuListEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAuth 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.9.1
onuListEntry OBJECT-TYPE
      SYNTAX OnuListEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { onuIndex }
      ::= { onuListTable 1 }


OnuListEntry ::=
      SEQUENCE {
            onuIndex
                  Integer32,
            ponId
                  Integer32,
            llid
                  Integer32,
            status
                  OCTET STRING,
            macAddress
                  OCTET STRING
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.1.9.1.1
onuIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuListEntry 1 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.1.9.1.2
ponId OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuListEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.9.1.3
llid OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuListEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.9.1.4
status OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuListEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.9.1.5
macAddress OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuListEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.10
onuTypeCfg OBJECT IDENTIFIER ::= { onuAuth 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.10.1
onuVerdorId OBJECT-TYPE
      SYNTAX OCTET STRING (SIZE (4))
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuTypeCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.10.2
onuModelId OBJECT-TYPE
      SYNTAX OCTET STRING (SIZE (4))
      MAX-ACCESS read-write
      STATUS current
```

```
      DESCRIPTION
            "Description."
      ::= { onuTypeCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.10.3
onuTpyeLanPortNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuTypeCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.10.4
onuTypeValue OBJECT-TYPE
      SYNTAX OCTET STRING (SIZE (1..16))
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuTypeCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.10.5
onuTypeAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            delete(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuTypeCfg 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.11
onuTypeTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuTypeEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAuth 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.11.1
onuTypeEntry OBJECT-TYPE
      SYNTAX OnuTypeEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { onuTypeIndex }
      ::= { onuTypeTable 1 }
```

```
OnuTypeEntry ::=
      SEQUENCE {
            onuTypeIndex
                  Integer32,
            onuVerdorID
                  OCTET STRING,
            onuModelID
                  OCTET STRING,
            onuTypeLanPortVal
                  Integer32,
            onuTypeVal
                  OCTET STRING
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.1.11.1.1
onuTypeIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuTypeEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.11.1.2
onuVerdorID OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuTypeEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.11.1.3
onuModelID OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuTypeEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.11.1.4
onuTypeLanPortVal OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuTypeEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.11.1.5
onuTypeVal OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
```

```
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuTypeEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.12
onuAuthInfoTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuAuthInfoEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAuth 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.12.1
onuAuthInfoEntry OBJECT-TYPE
      SYNTAX OnuAuthInfoEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { authInfoIndex }
      ::= { onuAuthInfoTable 1 }


OnuAuthInfoEntry ::=
      SEQUENCE {
            authInfoIndex
                  Integer32,
            authInfoPonNo
                  Integer32,
            authInfoOnuNo
                  Integer32,
            authInfoLlid
                  Integer32,
            lineStatus
                  INTEGER,
            onuMacAddr
                  OCTET STRING,
            onutype
                  OCTET STRING,
            exchange
                  INTEGER,
            authMode
                  INTEGER,
            onuAuthInfoDescription
                  OCTET STRING,
            onuAuthInfoLoid
                  OCTET STRING,
            onuAuthInfoLoidPwd
                  OCTET STRING,
            onuAuthInfoRtt
                  INTEGER,
            onuType2
                  OCTET STRING
       }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.1.12.1.1
authInfoIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAuthInfoEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.12.1.2
authInfoPonNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAuthInfoEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.12.1.3
authInfoOnuNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAuthInfoEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.12.1.4
authInfoLlid OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAuthInfoEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.12.1.5
lineStatus OBJECT-TYPE
      SYNTAX INTEGER
            {
            offline(0),
            online(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAuthInfoEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.12.1.6
onuMacAddr OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
```

```
      DESCRIPTION
            "Description."
      ::= { onuAuthInfoEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.12.1.7
onutype OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAuthInfoEntry 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.12.1.8
exchange OBJECT-TYPE
      SYNTAX INTEGER
            {
            idle(1),
            busy(2)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAuthInfoEntry 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.12.1.9
authMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            none(0),
            macAuth(1),
            loidAuth(2)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAuthInfoEntry 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.12.1.10
onuAuthInfoDescription OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAuthInfoEntry 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.12.1.11
onuAuthInfoLoid OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
```

```
      DESCRIPTION
            "Description."
      ::= { onuAuthInfoEntry 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.12.1.12
onuAuthInfoLoidPwd OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAuthInfoEntry 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.12.1.13
onuAuthInfoRtt OBJECT-TYPE
      SYNTAX INTEGER
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAuthInfoEntry 13 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.12.1.14
onuType2 OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAuthInfoEntry 14 }

-- 1.3.6.1.4.1.37950.1.1.5.12.1.13
onuAutoFindTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuAutoFindEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAuth 13 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.13.1
onuAutoFindEntry OBJECT-TYPE
      SYNTAX OnuAutoFindEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { onuAutoFindIndex }
      ::= { onuAutoFindTable 1 }


OnuAutoFindEntry ::=
      SEQUENCE {
            onuAutoFindIndex
                  Integer32,
```

```
            onuAutoFindPon
                  INTEGER,
            onuAutoFindMac
                  OCTET STRING,
            onuAutoFindTimeout
                  Integer32,
            onuAutoFindLoid
                  OCTET STRING,
            onuAutoFindLoidPwd
                  OCTET STRING
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.1.13.1.1
onuAutoFindIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAutoFindEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.13.1.2
onuAutoFindPon OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAutoFindEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.13.1.3
onuAutoFindMac OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAutoFindEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.13.1.4
onuAutoFindTimeout OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAutoFindEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.13.1.5
onuAutoFindLoid OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { onuAutoFindEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.13.1.6
onuAutoFindLoidPwd OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAutoFindEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.14
deregisterOnu OBJECT IDENTIFIER ::= { onuAuth 14 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.14.1
deregisterOnuPonIndex OBJECT-TYPE
      SYNTAX Integer32 (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { deregisterOnu 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.14.2
deregisterOnuIndex OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { deregisterOnu 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.15
resetOnu OBJECT IDENTIFIER ::= { onuAuth 15 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.15.1
resetOnuPonIndex OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { resetOnu 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.15.2
resetOnuIndex OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { resetOnu 2 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.1.16
onuDescription OBJECT IDENTIFIER ::= { onuAuth 16 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.16.1
onuDescriptionPon OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuDescription 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.16.2
onuDescriptionOnu OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuDescription 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.16.3
onuDescriptionStr OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuDescription 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.16.4
onuDescriptionAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            commit(1),
            delete(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuDescription 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.17
onuRttTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuRttEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAuth 17 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.1.17.1
onuRttEntry OBJECT-TYPE
      SYNTAX OnuRttEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { onuRttPon, onuRttOnu }
      ::= { onuRttTable 1 }


OnuRttEntry ::=
      SEQUENCE {
            onuRttPon
                  INTEGER,
            onuRttOnu
                  INTEGER,
            onuRttValue
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.1.17.1.1
onuRttPon OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuRttEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.17.1.2
onuRttOnu OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuRttEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.17.1.3
onuRttValue OBJECT-TYPE
      SYNTAX INTEGER
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuRttEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.18
onuEncryption OBJECT IDENTIFIER ::= { onuAuth 18 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.18.1
onuEncryptionPon OBJECT-TYPE
      SYNTAX INTEGER (1..16)
```

```
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuEncryption 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.18.2
onuEncryptionOnu OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuEncryption 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.18.3
onuEncryptionEnable OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuEncryption 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.18.4
onuEncryptionAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            commit(1),
            delete(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuEncryption 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.19
onuEncryptionTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuEncryptionEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAuth 19 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.19.1
onuEncryptionEntry OBJECT-TYPE
      SYNTAX OnuEncryptionEntry
      MAX-ACCESS not-accessible
```

```
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { onuEncryptionPonS, onuEncryptionOnuS }
      ::= { onuEncryptionTable 1 }


OnuEncryptionEntry ::=
      SEQUENCE {
            onuEncryptionPonS
                  INTEGER,
            onuEncryptionOnuS
                  INTEGER,
            onuEncryptionEnableS
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.1.19.1.1
onuEncryptionPonS OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuEncryptionEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.19.1.2
onuEncryptionOnuS OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuEncryptionEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.19.1.3
onuEncryptionEnableS OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuEncryptionEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.20
onuStatisticsTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuStatisticsEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAuth 20 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.1.20.1
onuStatisticsEntry OBJECT-TYPE
      SYNTAX OnuStatisticsEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { onuStatisticsPon, onuStatisticsOnu }
      ::= { onuStatisticsTable 1 }


OnuStatisticsEntry ::=
      SEQUENCE {
            onuStatisticsPon
                  INTEGER,
            onuStatisticsOnu
                  INTEGER,
            statRxGoodOctets
                  Counter64,
            statRxUcastFrames
                  Unsigned32,
            statRxMcastFrames
                  Unsigned32,
            statRxBcastFrames
                  Unsigned32,
            statRxRegreqFrames
                  Unsigned32,
            statRxRegackFrames
                  Unsigned32,
            statRxReportFrames
                  Unsigned32,
            statTxGoodOctets
                  Counter64,
            statTxUcastFrames
                  Unsigned32,
            statTxMcastFrames
                  Unsigned32,
            statTxBcastFrames
                  Unsigned32,
            statTxGateFrames
                  Unsigned32,
            statTxRegFrames
                  Unsigned32,
            statTxOamFrames
                  Unsigned32,
            statRxGoodOpi
                  Unsigned32,
            statRxBadCrc32
                  Unsigned32,
            statRxOamFrames
                  Unsigned32
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.1.20.1.1
onuStatisticsPon OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-only
```

```
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuStatisticsEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.20.1.2
onuStatisticsOnu OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuStatisticsEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.20.1.3
statRxGoodOctets OBJECT-TYPE
      SYNTAX Counter64
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuStatisticsEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.20.1.4
statRxUcastFrames OBJECT-TYPE
      SYNTAX Unsigned32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuStatisticsEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.20.1.5
statRxMcastFrames OBJECT-TYPE
      SYNTAX Unsigned32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuStatisticsEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.20.1.6
statRxBcastFrames OBJECT-TYPE
      SYNTAX Unsigned32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuStatisticsEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.20.1.7
statRxRegreqFrames OBJECT-TYPE
      SYNTAX Unsigned32
```

```
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuStatisticsEntry 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.20.1.8
statRxRegackFrames OBJECT-TYPE
      SYNTAX Unsigned32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuStatisticsEntry 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.20.1.9
statRxReportFrames OBJECT-TYPE
      SYNTAX Unsigned32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuStatisticsEntry 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.20.1.10
statTxGoodOctets OBJECT-TYPE
      SYNTAX Counter64
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuStatisticsEntry 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.20.1.11
statTxUcastFrames OBJECT-TYPE
      SYNTAX Unsigned32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuStatisticsEntry 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.20.1.12
statTxMcastFrames OBJECT-TYPE
      SYNTAX Unsigned32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuStatisticsEntry 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.20.1.13
statTxBcastFrames OBJECT-TYPE
```

```
      SYNTAX Unsigned32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuStatisticsEntry 13 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.20.1.14
statTxGateFrames OBJECT-TYPE
      SYNTAX Unsigned32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuStatisticsEntry 14 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.20.1.15
statTxRegFrames OBJECT-TYPE
      SYNTAX Unsigned32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuStatisticsEntry 15 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.20.1.16
statTxOamFrames OBJECT-TYPE
      SYNTAX Unsigned32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuStatisticsEntry 16 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.20.1.17
statRxGoodOpi OBJECT-TYPE
      SYNTAX Unsigned32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuStatisticsEntry 17 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.20.1.18
statRxBadCrc32 OBJECT-TYPE
      SYNTAX Unsigned32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuStatisticsEntry 18 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.20.1.19
```

```
statRxOamFrames OBJECT-TYPE
      SYNTAX Unsigned32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuStatisticsEntry 19 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.21
onuUpstream OBJECT IDENTIFIER ::= { onuAuth 21 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.21.1
onuUpstreamPon OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuUpstream 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.21.2
onuUpstreamOnu OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuUpstream 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.21.3
onuUpstreamFir OBJECT-TYPE
      SYNTAX INTEGER (0..950000)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuUpstream 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.21.4
onuUpstreamCir OBJECT-TYPE
      SYNTAX INTEGER (1..950000)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuUpstream 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.21.5
onuUpstreamPir OBJECT-TYPE
      SYNTAX INTEGER (512..1000000)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
```

```
            "Description."
      ::= { onuUpstream 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.21.6
onuUpstreamWeight OBJECT-TYPE
      SYNTAX INTEGER (1..20)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuUpstream 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.21.7
onuUpstreamAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            commit(1),
            delete(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuUpstream 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.22
onuUpstreamTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuUpstreamEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAuth 22 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.22.1
onuUpstreamEntry OBJECT-TYPE
      SYNTAX OnuUpstreamEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { onuUpstreamPonS, onuUpstreamOnuS }
      ::= { onuUpstreamTable 1 }


OnuUpstreamEntry ::=
      SEQUENCE {
            onuUpstreamPonS
                  INTEGER,
            onuUpstreamOnuS
                  INTEGER,
            onuUpstreamFirS
                  INTEGER,
            onuUpstreamCirS
                  INTEGER,
```

```
            onuUpstreamPirS
                  INTEGER,
            onuUpstreamWeightS
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.1.22.1.1
onuUpstreamPonS OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuUpstreamEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.22.1.2
onuUpstreamOnuS OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuUpstreamEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.22.1.3
onuUpstreamFirS OBJECT-TYPE
      SYNTAX INTEGER (0..950000)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuUpstreamEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.22.1.4
onuUpstreamCirS OBJECT-TYPE
      SYNTAX INTEGER (1..950000)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuUpstreamEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.22.1.5
onuUpstreamPirS OBJECT-TYPE
      SYNTAX INTEGER (512..1000000)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuUpstreamEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.22.1.6
onuUpstreamWeightS OBJECT-TYPE
      SYNTAX INTEGER (1..20)
```

```
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuUpstreamEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.23
onuDownsteam OBJECT IDENTIFIER ::= { onuAuth 23 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.23.1
onuDownsteamPon OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuDownsteam 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.23.2
onuDownsteamOnu OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuDownsteam 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.23.3
onuDownsteamPir OBJECT-TYPE
      SYNTAX INTEGER (0..1000000)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuDownsteam 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.23.4
onuDownsteamWeight OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuDownsteam 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.23.5
onuDownsteamAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            commit(1),
            delete(2)
            }
      MAX-ACCESS read-write
```

```
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuDownsteam 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.24
onuDownsteamTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuDownsteamEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAuth 24 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.24.1
onuDownsteamEntry OBJECT-TYPE
      SYNTAX OnuDownsteamEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { onuDownsteamPonS, onuDownsteamOnuS }
      ::= { onuDownsteamTable 1 }


OnuDownsteamEntry ::=
      SEQUENCE {
            onuDownsteamPonS
                  INTEGER,
            onuDownsteamOnuS
                  INTEGER,
            onuDownsteamPirS
                  INTEGER,
            onuDownsteamWeightS
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.1.24.1.1
onuDownsteamPonS OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuDownsteamEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.24.1.2
onuDownsteamOnuS OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuDownsteamEntry 2 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.1.24.1.3
onuDownsteamPirS OBJECT-TYPE
      SYNTAX INTEGER (0..1000000)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuDownsteamEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.24.1.4
onuDownsteamWeightS OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuDownsteamEntry 4 }

-- 1.3.6.1.4.1.37950.1.1.5.12.1.25
onuAuthInfo2Table OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuAuthInfo2Entry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAuth 25 }

-- 1.3.6.1.4.1.37950.1.1.5.12.1.25.1
onuAuthInfo2Entry OBJECT-TYPE
      SYNTAX OnuAuthInfo2Entry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { authInfoPonNo2, authInfoOnuNo2 }
      ::= { onuAuthInfo2Table 1 }


OnuAuthInfo2Entry ::=
      SEQUENCE {
            authInfoPonNo2
                  Integer32,
            authInfoOnuNo2
                  Integer32,
            authInfoLlid2
                  Integer32,
            lineStatus2
                  INTEGER,
            onuMacAddr2
                  OCTET STRING,
            onutype2
                  OCTET STRING,
            exchange2
                  INTEGER,
            authMode2
                  INTEGER,
            onuAuthInfoDescription2
                  OCTET STRING,
```

```
            onuAuthInfoLoid2
                  OCTET STRING,
            onuAuthInfoLoidPwd2
                  OCTET STRING,
            onuAuthInfoRtt2
                  INTEGER,
            onutype22
                  OCTET STRING,
            onuAuthInfoStatus2
                  INTEGER,
            onuAuthInfo2DeregReason
                  INTEGER,
            onuAuthInfo2PriSupport
                  Unsigned32,
            onuAuthInfoDistance2
                  Unsigned32,
            onuAuthInfoLastRegTime
                  OCTET STRING,
            onuAuthInfoLastDeregTime
                  OCTET STRING,
            onuAuthInfoAliveTime
                  OCTET STRING
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.1.25.1.1
authInfoPonNo2 OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAuthInfo2Entry 1 }

-- 1.3.6.1.4.1.37950.1.1.5.12.1.25.1.2
authInfoOnuNo2 OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAuthInfo2Entry 2 }

-- 1.3.6.1.4.1.37950.1.1.5.12.1.25.1.3
authInfoLlid2 OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAuthInfo2Entry 3 }

-- 1.3.6.1.4.1.37950.1.1.5.12.1.25.1.4
lineStatus2 OBJECT-TYPE
      SYNTAX INTEGER
            {
            offline(0),
            online(1)
            }
      MAX-ACCESS read-only
```

```
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAuthInfo2Entry 4 }

-- 1.3.6.1.4.1.37950.1.1.5.12.1.25.1.5
onuMacAddr2 OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAuthInfo2Entry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.25.1.6
onutype2 OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAuthInfo2Entry 6 }

-- 1.3.6.1.4.1.37950.1.1.5.12.1.25.1.7
exchange2 OBJECT-TYPE
      SYNTAX INTEGER
            {
            idle(1),
            busy(2)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAuthInfo2Entry 7 }

-- 1.3.6.1.4.1.37950.1.1.5.12.1.25.1.8
authMode2 OBJECT-TYPE
      SYNTAX INTEGER
            {
            none(0),
            macAuth(1),
            loidAuth(2)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAuthInfo2Entry 8 }
-- 1.3.6.1.4.1.37950.1.1.5.12.1.25.1.9
onuAuthInfoDescription2 OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAuthInfo2Entry 9 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.1.25.1.10
onuAuthInfoLoid2 OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAuthInfo2Entry 10 }

-- 1.3.6.1.4.1.37950.1.1.5.12.1.25.1.11
onuAuthInfoLoidPwd2 OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAuthInfo2Entry 11 }

-- 1.3.6.1.4.1.37950.1.1.5.12.1.25.1.12
onuAuthInfoRtt2 OBJECT-TYPE
      SYNTAX INTEGER
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAuthInfo2Entry 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.25.1.13
onutype22 OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAuthInfo2Entry 13 }

-- 1.3.6.1.4.1.37950.1.1.5.12.1.25.1.14
onuAuthInfoStatus2 OBJECT-TYPE
      SYNTAX INTEGER
            {
            unfinish(0),
            finish(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAuthInfo2Entry 14 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.25.1.15
onuAuthInfo2DeregReason OBJECT-TYPE
      SYNTAX INTEGER
            {
            wire_down(0),
            power_off(1)
            }
      MAX-ACCESS read-write
```

```
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAuthInfo2Entry 15 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.25.1.16
onuAuthInfo2PriSupport OBJECT-TYPE
      SYNTAX Unsigned32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAuthInfo2Entry 16 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.25.1.17
onuAuthInfoDistance2 OBJECT-TYPE
      SYNTAX Unsigned32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAuthInfo2Entry 17 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.25.1.18
onuAuthInfoLastRegTime OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAuthInfo2Entry 18 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.25.1.19
onuAuthInfoLastDeregTime OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAuthInfo2Entry 19 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.25.1.20
onuAuthInfoAliveTime OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAuthInfo2Entry 20 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.26
onuMacTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuMacEntry
```

```
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAuth 26 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.26.1
onuMacEntry OBJECT-TYPE
      SYNTAX OnuMacEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { onuMacPon, onuMacOnuId, onuMacNum }
      ::= { onuMacTable 1 }


OnuMacEntry ::=
      SEQUENCE {
            onuMacPon
                  Integer32,
            onuMacOnuId
                  Integer32,
            onuMacNum
                  Integer32,
            onuMacVlan
                  Integer32,
            onuMacAddress
                  OCTET STRING,
            onuMacAge
                  Integer32
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.1.26.1.1
onuMacPon OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuMacEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.26.1.2
onuMacOnuId OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuMacEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.26.1.3
onuMacNum OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
```

```
      DESCRIPTION
            "Description."
      ::= { onuMacEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.26.1.4
onuMacVlan OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuMacEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.26.1.5
onuMacAddress OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuMacEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.26.1.6
onuMacAge OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuMacEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.27
onuNumberTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuNumberEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAuth 27 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.27.1
onuNumberEntry OBJECT-TYPE
      SYNTAX OnuNumberEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { onuNumberPon }
      ::= { onuNumberTable 1 }


OnuNumberEntry ::=
      SEQUENCE {
            onuNumberPon
```

```
                  Integer32,
            onuNumberAll
                  Integer32,
            onuNumberOnline
                  Integer32
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.1.27.1.1
onuNumberPon OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuNumberEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.27.1.2
onuNumberAll OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuNumberEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.1.27.1.3
onuNumberOnline OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuNumberEntry 3 }

-- 1.3.6.1.4.1.37950.1.1.5.12.2
onuGlobalCfg OBJECT IDENTIFIER ::= { v1600dOnuMgmt 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1
onuInfo OBJECT IDENTIFIER ::= { onuGlobalCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.1
onuCtcInfoTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuCtcInfoEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuInfo 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.1.1
onuCtcInfoEntry OBJECT-TYPE
      SYNTAX OnuCtcInfoEntry
      MAX-ACCESS not-accessible
      STATUS current
```

```
      DESCRIPTION
            "Description."
      INDEX { onuCtcInfoPonIndex, onuCtcInfoOnuIndex }
      ::= { onuCtcInfoTable 1 }


OnuCtcInfoEntry ::=
      SEQUENCE {
            onuCtcInfoPonIndex
                  Integer32,
            onuCtcInfoOnuIndex
                  Integer32,
            onuOamVersion
                  OCTET STRING,
            onuOamOUI
                  OCTET STRING
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.1.1.1
onuCtcInfoPonIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuCtcInfoEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.1.1.2
onuCtcInfoOnuIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuCtcInfoEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.1.1.3
onuOamVersion OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuCtcInfoEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.1.1.4
onuOamOUI OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuCtcInfoEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.2
```

```
onuSnInfoTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuSnInfoEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuInfo 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.2.1
onuSnInfoEntry OBJECT-TYPE
      SYNTAX OnuSnInfoEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { onuSnInfoPonIndex, onuSnInfoOnuIndex }
      ::= { onuSnInfoTable 1 }


OnuSnInfoEntry ::=
      SEQUENCE {
            onuSnInfoPonIndex
                  Integer32,
            onuSnInfoOnuIndex
                  Integer32,
            onuVendorId
                  OCTET STRING,
            onuModel
                  OCTET STRING,
            onuID
                  OCTET STRING,
            onuHardwareVersion
                  OCTET STRING,
            onuSoftwareVersion
                  OCTET STRING
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.2.1.1
onuSnInfoPonIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSnInfoEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.2.1.2
onuSnInfoOnuIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSnInfoEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.2.1.3
```

```
onuVendorId OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSnInfoEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.2.1.4
onuModel OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSnInfoEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.2.1.5
onuID OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSnInfoEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.2.1.6
onuHardwareVersion OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSnInfoEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.2.1.7
onuSoftwareVersion OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSnInfoEntry 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.3
fwVersionInfoTable OBJECT-TYPE
      SYNTAX SEQUENCE OF FwVersionInfoEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuInfo 3 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.3.1
fwVersionInfoEntry OBJECT-TYPE
      SYNTAX FwVersionInfoEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { fwVersionInfoPonIndex, fwVersionInfoOnuIndex }
      ::= { fwVersionInfoTable 1 }


FwVersionInfoEntry ::=
      SEQUENCE {
            fwVersionInfoPonIndex
                  Integer32,
            fwVersionInfoOnuIndex
                  Integer32,
            fwVersion
                  OCTET STRING
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.3.1.1
fwVersionInfoPonIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { fwVersionInfoEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.3.1.2
fwVersionInfoOnuIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { fwVersionInfoEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.3.1.3
fwVersion OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { fwVersionInfoEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.4
chipIdInfoTable OBJECT-TYPE
      SYNTAX SEQUENCE OF ChipIdInfoEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuInfo 4 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.4.1
chipIdInfoEntry OBJECT-TYPE
      SYNTAX ChipIdInfoEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { chipIdInfoPonIndex, chipIdInfoOnuIndex }
      ::= { chipIdInfoTable 1 }


ChipIdInfoEntry ::=
      SEQUENCE {
            chipIdInfoPonIndex
                  Integer32,
            chipIdInfoOnuIndex
                  Integer32,
            verderId
                  OCTET STRING,
            chipModel
                  OCTET STRING,
            date
                  OCTET STRING
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.4.1.1
chipIdInfoPonIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { chipIdInfoEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.4.1.2
chipIdInfoOnuIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { chipIdInfoEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.4.1.3
verderId OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { chipIdInfoEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.4.1.4
chipModel OBJECT-TYPE
```

```
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { chipIdInfoEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.4.1.5
date OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { chipIdInfoEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.5
cap1InfoTable OBJECT-TYPE
      SYNTAX SEQUENCE OF Cap1InfoEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuInfo 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.5.1
cap1InfoEntry OBJECT-TYPE
      SYNTAX Cap1InfoEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { cap1InfoPonIndex, cap1InfoOnuIndex }
      ::= { cap1InfoTable 1 }


Cap1InfoEntry ::=
      SEQUENCE {
            cap1InfoPonIndex
                  Integer32,
            cap1InfoOnuIndex
                  Integer32,
            serviceSupported
                  OCTET STRING,
            numGEPorts
                  INTEGER,
            geBitMap
                  OCTET STRING,
            numFEPorts
                  INTEGER,
            feBitMap
                  OCTET STRING,
            numPOTSPorts
                  INTEGER,
            numE1Ports
                  INTEGER,
```

```
            numUSQueues
                  INTEGER,
            maxQueueUSPort
                  INTEGER,
            numDSQueues
                  INTEGER,
            maxQueueDSPort
                  INTEGER,
            batteryBackup
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.5.1.1
cap1InfoPonIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { cap1InfoEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.5.1.2
cap1InfoOnuIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { cap1InfoEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.5.1.3
serviceSupported OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { cap1InfoEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.5.1.4
numGEPorts OBJECT-TYPE
      SYNTAX INTEGER
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { cap1InfoEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.5.1.5
geBitMap OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { cap1InfoEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.5.1.6
numFEPorts OBJECT-TYPE
      SYNTAX INTEGER
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { cap1InfoEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.5.1.7
feBitMap OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { cap1InfoEntry 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.5.1.8
numPOTSPorts OBJECT-TYPE
      SYNTAX INTEGER
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { cap1InfoEntry 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.5.1.9
numE1Ports OBJECT-TYPE
      SYNTAX INTEGER
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { cap1InfoEntry 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.5.1.10
numUSQueues OBJECT-TYPE
      SYNTAX INTEGER
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { cap1InfoEntry 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.5.1.11
maxQueueUSPort OBJECT-TYPE
      SYNTAX INTEGER
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
```

```
            "Description."
      ::= { cap1InfoEntry 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.5.1.12
numDSQueues OBJECT-TYPE
      SYNTAX INTEGER
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { cap1InfoEntry 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.5.1.13
maxQueueDSPort OBJECT-TYPE
      SYNTAX INTEGER
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { cap1InfoEntry 13 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.5.1.14
batteryBackup OBJECT-TYPE
      SYNTAX INTEGER
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { cap1InfoEntry 14 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.6
cap2InfoTable OBJECT-TYPE
      SYNTAX SEQUENCE OF Cap2InfoEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuInfo 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.6.1
cap2InfoEntry OBJECT-TYPE
      SYNTAX Cap2InfoEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { cap2InfoPonIndex, cap2InfoOnuIndex }
      ::= { cap2InfoTable 1 }


Cap2InfoEntry ::=
      SEQUENCE {
            cap2InfoPonIndex
                  Integer32,
```

```
            cap2InfoOnuIndex
                  Integer32,
            onuType
                  OCTET STRING,
            multiLLID
                  OCTET STRING,
            protectionType
                  OCTET STRING,
            numPONIf
                  INTEGER,
            numSlot
                  INTEGER,
            numInterfaceType
                  Integer32,
            interfaceTypePorts
                  OCTET STRING,
            batBackup
                  OCTET STRING
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.6.1.1
cap2InfoPonIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { cap2InfoEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.6.1.2
cap2InfoOnuIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { cap2InfoEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.6.1.3
onuType OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { cap2InfoEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.6.1.4
multiLLID OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { cap2InfoEntry 4 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.6.1.5
protectionType OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { cap2InfoEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.6.1.6
numPONIf OBJECT-TYPE
      SYNTAX INTEGER
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { cap2InfoEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.6.1.7
numSlot OBJECT-TYPE
      SYNTAX INTEGER
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { cap2InfoEntry 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.6.1.8
numInterfaceType OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { cap2InfoEntry 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.6.1.9
interfaceTypePorts OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { cap2InfoEntry 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.6.1.10
batBackup OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { cap2InfoEntry 10 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.7
cap3InfoTable OBJECT-TYPE
      SYNTAX SEQUENCE OF Cap3InfoEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuInfo 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.7.1
cap3InfoEntry OBJECT-TYPE
      SYNTAX Cap3InfoEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { cap3InfoPonIndex, cap3InfoOnuIndex }
      ::= { cap3InfoTable 1 }


Cap3InfoEntry ::=
      SEQUENCE {
            cap3InfoPonIndex
                  Integer32,
            cap3InfoOnuIndex
                  Integer32,
            ipv6Support
                  INTEGER,
            powerControl
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.7.1.1
cap3InfoPonIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { cap3InfoEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.7.1.2
cap3InfoOnuIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { cap3InfoEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.7.1.3
ipv6Support OBJECT-TYPE
      SYNTAX INTEGER
            {
```

```
            not_support(0),
            support(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { cap3InfoEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.7.1.4
powerControl OBJECT-TYPE
      SYNTAX INTEGER
            {
            not_support(0),
            support_onu_tx(1),
            support_onu_tx_and_rx(2)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { cap3InfoEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.8
opmDiagInfoTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OpmDiagInfoEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuInfo 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.8.1
opmDiagInfoEntry OBJECT-TYPE
      SYNTAX OpmDiagInfoEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { opmDiagInfoPonIndex, opmDiagInfoOnuIndex }
      ::= { opmDiagInfoTable 1 }


OpmDiagInfoEntry ::=
      SEQUENCE {
            opmDiagInfoPonIndex
                  Integer32,
            opmDiagInfoOnuIndex
                  Integer32,
            temperature
                  OCTET STRING,
            supplyVoltage
                  OCTET STRING,
            txBias
                  OCTET STRING,
            txPower
```

```
                  OCTET STRING,
            rxPower
                  OCTET STRING
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.8.1.1
opmDiagInfoPonIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { opmDiagInfoEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.8.1.2
opmDiagInfoOnuIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { opmDiagInfoEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.8.1.3
temperature OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { opmDiagInfoEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.8.1.4
supplyVoltage OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { opmDiagInfoEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.8.1.5
txBias OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { opmDiagInfoEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.8.1.6
txPower OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
```

```
      STATUS current
      DESCRIPTION
            "Description."
      ::= { opmDiagInfoEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.8.1.7
rxPower OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { opmDiagInfoEntry 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.9
fecAbilityTable OBJECT-TYPE
      SYNTAX SEQUENCE OF FecAbilityEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuInfo 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.9.1
fecAbilityEntry OBJECT-TYPE
      SYNTAX FecAbilityEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { fecAbilityPonIndex, fecAbilityOnuIndex }
      ::= { fecAbilityTable 1 }


FecAbilityEntry ::=
      SEQUENCE {
            fecAbilityPonIndex
                  Integer32,
            fecAbilityOnuIndex
                  Integer32,
            fecAbility
                  OCTET STRING,
            fecMode
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.9.1.1
fecAbilityPonIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { fecAbilityEntry 1 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.9.1.2
fecAbilityOnuIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { fecAbilityEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.9.1.3
fecAbility OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { fecAbilityEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.9.1.4
fecMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            Unknow(1),
            Enable(2),
            Disable(3)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { fecAbilityEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.10
powerSavingCapTable OBJECT-TYPE
      SYNTAX SEQUENCE OF PowerSavingCapEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuInfo 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.10.1
powerSavingCapEntry OBJECT-TYPE
      SYNTAX PowerSavingCapEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { powerSavingCapPonIndex, powerSavingCapOnuIndex }
      ::= { powerSavingCapTable 1 }


PowerSavingCapEntry ::=
      SEQUENCE {
            powerSavingCapPonIndex
```

```
                  Integer32,
            powerSavingCapOnuIndex
                  Integer32,
            sleepmode
                  OCTET STRING,
            earlywakeup
                  OCTET STRING
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.10.1.1
powerSavingCapPonIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { powerSavingCapEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.10.1.2
powerSavingCapOnuIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { powerSavingCapEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.10.1.3
sleepmode OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { powerSavingCapEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.10.1.4
earlywakeup OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { powerSavingCapEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.11
onuSnmpTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuSnmpEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuInfo 11 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.11.1
onuSnmpEntry OBJECT-TYPE
      SYNTAX OnuSnmpEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { snmpPonNo, snmpOnuNo }
      ::= { onuSnmpTable 1 }


OnuSnmpEntry ::=
      SEQUENCE {
            snmpPonNo
                  Integer32,
            snmpOnuNo
                  Integer32,
            snmpVer
                  INTEGER,
            snmpTrapIPaddr
                  IpAddress,
            snmpTrapPort
                  Integer32,
            snmpPort
                  Integer32,
            snmpSecuritName
                  OCTET STRING,
            snmpCommunityRead
                  OCTET STRING,
            snmpCommunityWrite
                  OCTET STRING
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.11.1.1
snmpPonNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSnmpEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.11.1.2
snmpOnuNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSnmpEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.11.1.3
snmpVer OBJECT-TYPE
      SYNTAX INTEGER
            {
            SNMP_V1(1),
            SNMP_V2(2),
```

```
            SNMP_V3(3)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSnmpEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.11.1.4
snmpTrapIPaddr OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSnmpEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.11.1.5
snmpTrapPort OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSnmpEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.11.1.6
snmpPort OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSnmpEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.11.1.7
snmpSecuritName OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSnmpEntry 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.11.1.8
snmpCommunityRead OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSnmpEntry 8 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.11.1.9
snmpCommunityWrite OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSnmpEntry 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.12
onuSlaTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuSlaEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuInfo 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.12.1
onuSlaEntry OBJECT-TYPE
      SYNTAX OnuSlaEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { slaPonNo, slaOnuNo }
      ::= { onuSlaTable 1 }


OnuSlaEntry ::=
      SEQUENCE {
            slaPonNo
                  Integer32,
            slaOnuNo
                  Integer32,
            slaOperActive
                  INTEGER,
            slaScheduleScheme
                  INTEGER,
            slaHPriorityBoundary
                  INTEGER,
            slaCycleLen
                  INTEGER,
            slaNumService
                  INTEGER,
            slaQueIdStr
                  OCTET STRING,
            slaFixPacketSizeStr
                  OCTET STRING,
            slaFixBandwidthStr
                  OCTET STRING,
            slaGuarantBwStr
                  OCTET STRING,
            slaBestEffortBWStr
                  OCTET STRING,
            slaWrrWeightStr
                  OCTET STRING
```

```
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.12.1.1
slaPonNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSlaEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.12.1.2
slaOnuNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSlaEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.12.1.3
slaOperActive OBJECT-TYPE
      SYNTAX INTEGER
            {
            Deactivate(0),
            Active(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSlaEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.12.1.4
slaScheduleScheme OBJECT-TYPE
      SYNTAX INTEGER
            {
            SP(0),
            WRR(1),
            SP_WRR(2)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSlaEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.12.1.5
slaHPriorityBoundary OBJECT-TYPE
      SYNTAX INTEGER
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSlaEntry 5 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.12.1.6
slaCycleLen OBJECT-TYPE
      SYNTAX INTEGER
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSlaEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.12.1.7
slaNumService OBJECT-TYPE
      SYNTAX INTEGER
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSlaEntry 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.12.1.8
slaQueIdStr OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSlaEntry 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.12.1.9
slaFixPacketSizeStr OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSlaEntry 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.12.1.10
slaFixBandwidthStr OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSlaEntry 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.12.1.11
slaGuarantBwStr OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { onuSlaEntry 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.12.1.12
slaBestEffortBWStr OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSlaEntry 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.1.12.1.13
slaWrrWeightStr OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSlaEntry 13 }

-- 1.3.6.1.4.1.37950.1.1.5.12.2.2
onuUpgrade OBJECT IDENTIFIER ::= { onuGlobalCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.2.1
tftpDownloadFile OBJECT IDENTIFIER ::= { onuUpgrade 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.2.1.1
filename OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { tftpDownloadFile 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.2.1.2
tftpServer OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { tftpDownloadFile 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.2.1.3
tftpAction OBJECT-TYPE
      SYNTAX INTEGER { commit(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { tftpDownloadFile 3 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.2.2.2
upgradeLoadOnuImg OBJECT IDENTIFIER ::= { onuUpgrade 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.2.2.1
filenameSet OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { upgradeLoadOnuImg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.2.2.2
loadAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            commit(1),
            clean(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { upgradeLoadOnuImg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.2.3
ctcUpgradeCfg OBJECT IDENTIFIER ::= { onuUpgrade 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.2.3.1
upgradePonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ctcUpgradeCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.2.3.2
upgradeOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ctcUpgradeCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.2.3.3
ctcUpgrade OBJECT-TYPE
      SYNTAX INTEGER
            {
            start(1),
            commit(2)
```

```
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ctcUpgradeCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.2.4
upgradeOnuImage OBJECT IDENTIFIER ::= { onuUpgrade 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.2.4.1
upgradeImage OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { upgradeOnuImage 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.2.4.2
upgradeIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { upgradeOnuImage 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.2.4.3
upgradeImageAction OBJECT-TYPE
      SYNTAX INTEGER { commit(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { upgradeOnuImage 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.2.5
upgradeOnuSelect OBJECT IDENTIFIER ::= { onuUpgrade 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.2.5.1
upgradePon OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { upgradeOnuSelect 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.2.5.2
upgradeOnu OBJECT-TYPE
      SYNTAX OCTET STRING
```

```
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { upgradeOnuSelect 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.2.5.3
upgradeSelectAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            delete(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { upgradeOnuSelect 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.2.6
upgradeOnuSelectTable OBJECT-TYPE
      SYNTAX SEQUENCE OF UpgradeOnuSelectEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuUpgrade 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.2.6.1
upgradeOnuSelectEntry OBJECT-TYPE
      SYNTAX UpgradeOnuSelectEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { upgradeOnuPonS }
      ::= { upgradeOnuSelectTable 1 }


UpgradeOnuSelectEntry ::=
      SEQUENCE {
            upgradeOnuPonS
                  INTEGER,
            upgradeOnuSelectS
                  OCTET STRING
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.2.2.6.1.1
upgradeOnuPonS OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { upgradeOnuSelectEntry 1 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.2.2.6.1.2
upgradeOnuSelectS OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { upgradeOnuSelectEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.2.7
upgreadOnuAction OBJECT IDENTIFIER ::= { onuUpgrade 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.2.7.1
upgreadAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            start(1),
            stop(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { upgreadOnuAction 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.2.7.2
upgradeOver OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { upgreadOnuAction 2 }

-- 1.3.6.1.4.1.37950.1.1.5.12.2.2.8
upgradeOnuStatusTable OBJECT-TYPE
      SYNTAX SEQUENCE OF UpgradeOnuStatusEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuUpgrade 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.2.8.1
upgradeOnuStatusEntry OBJECT-TYPE
      SYNTAX UpgradeOnuStatusEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { upgradeOnuStatusIndex }
      ::= { upgradeOnuStatusTable 1 }
```

```
UpgradeOnuStatusEntry ::=
      SEQUENCE {
            upgradeOnuStatusIndex
                  Integer32,
            upgreadeStatusPonS
                  Integer32,
            upgradeOnuLlid
                  Integer32,
            upgradeOnuStatusS
                  OCTET STRING,
            upgradeOnuStatusProcess
                  OCTET STRING
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.2.2.8.1.1
upgradeOnuStatusIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { upgradeOnuStatusEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.2.8.1.2
upgreadeStatusPonS OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { upgradeOnuStatusEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.2.8.1.3
upgradeOnuLlid OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { upgradeOnuStatusEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.2.8.1.4
upgradeOnuStatusS OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { upgradeOnuStatusEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.2.8.1.5
upgradeOnuStatusProcess OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
```

```
      DESCRIPTION
            "Description."
      ::= { upgradeOnuStatusEntry 5 }

-- 1.3.6.1.4.1.37950.1.1.5.12.2.3
onuManagementIp OBJECT IDENTIFIER ::= { onuGlobalCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.3.1
mgmtIpPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuManagementIp 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.3.2
mgmtIpOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuManagementIp 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.3.3
mgmtIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuManagementIp 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.3.4
mgmtIpMask OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuManagementIp 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.3.5
mgmtIpGw OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuManagementIp 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.3.6
```

```
mgmtIpCVlan OBJECT-TYPE
      SYNTAX INTEGER (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuManagementIp 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.3.7
mgmtIpSVlan OBJECT-TYPE
      SYNTAX INTEGER (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuManagementIp 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.3.8
mgmtIpPri OBJECT-TYPE
      SYNTAX INTEGER (0..7)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuManagementIp 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.3.9
mgmtIPAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            commit(1),
            delete(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuManagementIp 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.3.10
onuManagementIpTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuManagementIpEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuManagementIp 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.3.10.1
onuManagementIpEntry OBJECT-TYPE
      SYNTAX OnuManagementIpEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
```

```
            "Description."
      INDEX { mgmtIPPonNo, mgmtIPOnuNo }
      ::= { onuManagementIpTable 1 }


OnuManagementIpEntry ::=
      SEQUENCE {
            mgmtIPPonNo
                  Integer32,
            mgmtIPOnuNo
                  Integer32,
            mgmtIP
                  IpAddress,
            mgmtIPMask
                  IpAddress,
            mgmtIPGw
                  IpAddress,
            mgmtIPCvlan
                  Integer32,
            mgmtIPSvlan
                  Integer32,
            mgmtIPPri
                  Integer32
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.2.3.10.1.1
mgmtIPPonNo OBJECT-TYPE
      SYNTAX Integer32 (1..16)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuManagementIpEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.3.10.1.2
mgmtIPOnuNo OBJECT-TYPE
      SYNTAX Integer32 (1..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuManagementIpEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.3.10.1.3
mgmtIP OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuManagementIpEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.3.10.1.4
mgmtIPMask OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
```

```
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuManagementIpEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.3.10.1.5
mgmtIPGw OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuManagementIpEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.3.10.1.6
mgmtIPCvlan OBJECT-TYPE
      SYNTAX Integer32 (0..4095)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuManagementIpEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.3.10.1.7
mgmtIPSvlan OBJECT-TYPE
      SYNTAX Integer32 (0..4095)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuManagementIpEntry 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.3.10.1.8
mgmtIPPri OBJECT-TYPE
      SYNTAX Integer32 (0..7)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuManagementIpEntry 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.4
onuSnmpCfg OBJECT IDENTIFIER ::= { onuGlobalCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.4.1
onuSnmpPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSnmpCfg 1 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.2.4.2
onuSnmpOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSnmpCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.4.3
onuSnmpTrapHostIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSnmpCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.4.4
onuSnmpTrapUdpPort OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSnmpCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.4.5
onuSnmpPort OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSnmpCfg 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.4.6
onuCommunityName OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSnmpCfg 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.4.7
onuRoCommunityName OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSnmpCfg 7 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.2.4.8
onuRwCommunityName OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSnmpCfg 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.4.9
onuCommunityAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            delete(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSnmpCfg 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.5
onuMultiLlid OBJECT IDENTIFIER ::= { onuGlobalCfg 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.5.1
llidPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuMultiLlid 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.5.2
llidOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuMultiLlid 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.5.3
llidNo OBJECT-TYPE
      SYNTAX INTEGER (0..8)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuMultiLlid 3 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.2.6
onuMainPonCfg OBJECT IDENTIFIER ::= { onuGlobalCfg 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.6.1
ponNumber OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuMainPonCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.6.2
onuNumber OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuMainPonCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.6.3
onuMainPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..8)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuMainPonCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.7
onuFecCfg OBJECT IDENTIFIER ::= { onuGlobalCfg 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.7.1
onuFecPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuFecCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.7.2
onuFecOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuFecCfg 2 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.2.7.3
onuFecEn OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuFecCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.8
onuHoldoverCfg OBJECT IDENTIFIER ::= { onuGlobalCfg 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.8.1
holdoverPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuHoldoverCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.8.2
holdoverOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuHoldoverCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.8.3
holdover OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuHoldoverCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.9
onuSlaCfg OBJECT IDENTIFIER ::= { onuGlobalCfg 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.9.1
onuSlaPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { onuSlaCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.9.2
onuSlaOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSlaCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.9.3
onuSlaEn OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSlaCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.9.4
onuSlaMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            sp_basic(1),
            wrr(2),
            sp_wrr(3)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSlaCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.9.5
highPriBoundary OBJECT-TYPE
      SYNTAX Integer32 (0..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSlaCfg 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.9.6
cycleLength OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { onuSlaCfg 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.9.7
numServices OBJECT-TYPE
      SYNTAX Integer32 (1..8)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSlaCfg 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.9.8
queueIdListStr OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSlaCfg 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.9.9
fixPacketSizeListStr OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSlaCfg 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.9.10
queweightListStr OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSlaCfg 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.9.11
fixBandwidthListStr OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSlaCfg 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.9.12
guaranteedBandwidthListStr OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
```

```
            "Description."
      ::= { onuSlaCfg 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.9.13
besteffortBandwithListStr OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSlaCfg 13 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.9.56
slaAction OBJECT-TYPE
      SYNTAX INTEGER { commit(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSlaCfg 56 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.10
onuIgmpCfg OBJECT IDENTIFIER ::= { onuGlobalCfg 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.10.1
igmpMode OBJECT IDENTIFIER ::= { onuIgmpCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.10.1.1
igmpModePonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { igmpMode 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.10.1.2
igmpModeOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { igmpMode 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.10.1.3
onuIgmpMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            snooping(1),
            control(2)
            }
```

```
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { igmpMode 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.10.2
igmpFastLeave OBJECT IDENTIFIER ::= { onuIgmpCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.10.2.1
igmpFastPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { igmpFastLeave 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.10.2.2
igmpFastOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { igmpFastLeave 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.10.2.3
onuIgmpFastLeave OBJECT-TYPE
      SYNTAX INTEGER
            {
            Disable(1),
            Enable(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { igmpFastLeave 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.10.3
igmpCfgTable OBJECT-TYPE
      SYNTAX SEQUENCE OF IgmpCfgEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuIgmpCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.10.3.1
igmpCfgEntry OBJECT-TYPE
      SYNTAX IgmpCfgEntry
      MAX-ACCESS not-accessible
```

```
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { igmpCfgPonNo, igmpCfgOnuNo }
      ::= { igmpCfgTable 1 }


IgmpCfgEntry ::=
      SEQUENCE {
            igmpCfgPonNo
                  Integer32,
            igmpCfgOnuNo
                  Integer32,
            igmpCfgMode
                  INTEGER,
            igmpCfgFastLeave
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.2.10.3.1.1
igmpCfgPonNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { igmpCfgEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.10.3.1.2
igmpCfgOnuNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { igmpCfgEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.10.3.1.3
igmpCfgMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            Snooping(1),
            CTC(2)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { igmpCfgEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.10.3.1.4
igmpCfgFastLeave OBJECT-TYPE
      SYNTAX INTEGER
            {
            Enable(1),
            Disable(2)
```

```
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { igmpCfgEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.11
onuReset OBJECT IDENTIFIER ::= { onuGlobalCfg 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.11.1
onuResetPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuReset 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.11.2
onuResetOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuReset 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.11.3
onuResetAction OBJECT-TYPE
      SYNTAX INTEGER { enable(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuReset 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.12
onuPowerSavingCfg OBJECT IDENTIFIER ::= { onuGlobalCfg 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.12.1
onuPowerSavPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPowerSavingCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.12.2
onuPowerSavOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
```

```
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPowerSavingCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.12.3
earlyWakeupEn OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPowerSavingCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.12.4
sleepDurationMax OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPowerSavingCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.12.5
powerSavAction OBJECT-TYPE
      SYNTAX INTEGER { commit(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPowerSavingCfg 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.13
onuPowerSavParameter OBJECT IDENTIFIER ::= { onuGlobalCfg 13 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.13.1
onuPwSavPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPowerSavParameter 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.13.2
onuPwSavOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
```

```
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPowerSavParameter 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.13.3
sleepDuration OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPowerSavParameter 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.13.4
wakeDuration OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPowerSavParameter 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.13.5
sleepFlag OBJECT-TYPE
      SYNTAX INTEGER
            {
            off(1),
            on(2),
            change(3)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPowerSavParameter 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.13.6
sleepMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            none(1),
            txSleepOnly(2),
            txAndRxSleep(3)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPowerSavParameter 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.13.7
onuPwSaveAction OBJECT-TYPE
      SYNTAX INTEGER { commit(1) }
```

```
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPowerSavParameter 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.14
onuPonProtectCfg OBJECT IDENTIFIER ::= { onuGlobalCfg 14 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.14.1
ponProtectPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPonProtectCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.14.2
ponProtectOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPonProtectCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.14.3
losOptical OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPonProtectCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.14.4
losMpcp OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPonProtectCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.14.5
ponProtectAction OBJECT-TYPE
      SYNTAX INTEGER { commit(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPonProtectCfg 5 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.2.14.6
onuPonProtectTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuPonProtectEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPonProtectCfg 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.14.6.1
onuPonProtectEntry OBJECT-TYPE
      SYNTAX OnuPonProtectEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { protectPonNo, protectPonOnuNo }
      ::= { onuPonProtectTable 1 }


OnuPonProtectEntry ::=
      SEQUENCE {
            protectPonNo
                  Integer32,
            protectPonOnuNo
                  Integer32,
            protectLostOptical
                  Integer32,
            protectLostMpcp
                  Integer32
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.2.14.6.1.1
protectPonNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPonProtectEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.14.6.1.2
protectPonOnuNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPonProtectEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.14.6.1.3
protectLostOptical OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
```

```
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPonProtectEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.14.6.1.4
protectLostMpcp OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPonProtectEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.15
onuPonPowerOnOff OBJECT IDENTIFIER ::= { onuGlobalCfg 15 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.15.1
onOffPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPonPowerOnOff 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.15.2
onOffOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPonPowerOnOff 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.15.3
laserAction OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPonPowerOnOff 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.15.4
ponMac OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPonPowerOnOff 4 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.2.15.5
transmitter OBJECT-TYPE
      SYNTAX INTEGER
            {
            major(1),
            standby(2),
            both(3)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPonPowerOnOff 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.15.6
onOffAction OBJECT-TYPE
      SYNTAX INTEGER { commit(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPonPowerOnOff 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.16
onuMacAgingTime OBJECT IDENTIFIER ::= { onuGlobalCfg 16 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.16.1
agingTimePonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuMacAgingTime 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.16.2
agingTimeOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuMacAgingTime 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.16.3
macAgetime OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuMacAgingTime 3 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.2.17
onuInfoTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuInfoEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuGlobalCfg 17 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.17.1
onuInfoEntry OBJECT-TYPE
      SYNTAX OnuInfoEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { onuInfoPonNo, onuInfoOnuNo }
      ::= { onuInfoTable 1 }


OnuInfoEntry ::=
      SEQUENCE {
            onuInfoPonNo
                  Integer32,
            onuInfoOnuNo
                  Integer32,
            onuInfoMacAgingTime
                  Integer32,
            onuInfoHoldOver
                  Integer32,
            onuInfoMainPon
                  Integer32
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.2.17.1.1
onuInfoPonNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuInfoEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.17.1.2
onuInfoOnuNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuInfoEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.17.1.3
onuInfoMacAgingTime OBJECT-TYPE
      SYNTAX Integer32
```

```
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuInfoEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.17.1.4
onuInfoHoldOver OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuInfoEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.17.1.5
onuInfoMainPon OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuInfoEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.18
powerSavingTable OBJECT-TYPE
      SYNTAX SEQUENCE OF PowerSavingEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuGlobalCfg 18 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.18.1
powerSavingEntry OBJECT-TYPE
      SYNTAX PowerSavingEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { pSPonNo, pSOnuNo }
      ::= { powerSavingTable 1 }


PowerSavingEntry ::=
      SEQUENCE {
            pSPonNo
                  Integer32,
            pSOnuNo
                  Integer32,
            pSEarlyWakeupEn
                  INTEGER,
            pSSleepDurationMax
                  INTEGER
       }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.2.18.1.1
pSPonNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { powerSavingEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.18.1.2
pSOnuNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { powerSavingEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.18.1.3
pSEarlyWakeupEn OBJECT-TYPE
      SYNTAX INTEGER
            {
            enableWakeUp(0),
            disableWakeUp(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { powerSavingEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.18.1.4
pSSleepDurationMax OBJECT-TYPE
      SYNTAX INTEGER
            {
            enableWakeUp(0),
            disableWakeUp(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { powerSavingEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.19
onuSleepControlTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuSleepControlEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuGlobalCfg 19 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.2.19.1
onuSleepControlEntry OBJECT-TYPE
      SYNTAX OnuSleepControlEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { sleepCtlPonNo, sleepCtlOnuNo }
      ::= { onuSleepControlTable 1 }


OnuSleepControlEntry ::=
      SEQUENCE {
            sleepCtlPonNo
                  Integer32,
            sleepCtlOnuNo
                  Integer32,
            scSleepDuration
                  Integer32,
            scWakeDuration
                  Integer32,
            scSleepFlag
                  Integer32,
            scSleepMode
                  Integer32
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.2.19.1.1
sleepCtlPonNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSleepControlEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.19.1.2
sleepCtlOnuNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSleepControlEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.19.1.3
scSleepDuration OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSleepControlEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.19.1.4
scWakeDuration OBJECT-TYPE
```

```
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSleepControlEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.19.1.5
scSleepFlag OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSleepControlEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.2.19.1.6
scSleepMode OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSleepControlEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3
onuPriGlobal OBJECT IDENTIFIER ::= { v1600dOnuMgmt 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1
onuPriGlobalCfg OBJECT IDENTIFIER ::= { onuPriGlobal 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.1
onuPriIgmpAdmin OBJECT IDENTIFIER ::= { onuPriGlobalCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.1.1
priIgmpAdminPon OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriIgmpAdmin 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.1.2
priIgmpAdminOnu OBJECT-TYPE
      SYNTAX INTEGER (1..65565)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriIgmpAdmin 2 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.1.3
priIgmpAdmin OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriIgmpAdmin 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.1.4
priIgmpAdminAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            commit(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriIgmpAdmin 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.2
onuPriCatvEnable OBJECT IDENTIFIER ::= { onuPriGlobalCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.2.1
priCatvEnablePon OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriCatvEnable 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.2.2
priCatvEnableOnu OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriCatvEnable 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.2.3
priCatvEnable OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
```

```
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriCatvEnable 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.2.4
priCatvAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            commit(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriCatvEnable 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.3
onuPriCtcoamSkip OBJECT IDENTIFIER ::= { onuPriGlobalCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.3.1
priCtcoamSkipPon OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriCtcoamSkip 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.3.2
priCtcoamSkipOnu OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriCtcoamSkip 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.3.3
priCtcoamSkip OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriCtcoamSkip 3 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.3.4
priCtcoamSkipAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            commit(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriCtcoamSkip 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.4
onuPriWifiSwitch OBJECT IDENTIFIER ::= { onuPriGlobalCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.4.1
priWifiSwitchPon OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriWifiSwitch 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.4.2
priWifiSwitchOnu OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriWifiSwitch 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.4.3
priWifiApModule OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriWifiSwitch 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.4.4
priWifiContry OBJECT-TYPE
      SYNTAX INTEGER
            {
            ETSI(0),
            FCC(1)
```

```
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriWifiSwitch 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.4.5
priWifiChannel OBJECT-TYPE
      SYNTAX INTEGER (0..13)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriWifiSwitch 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.4.6
priWifiStandard OBJECT-TYPE
      SYNTAX INTEGER
            {
            s80211b(0),
            s80211g(1),
            s80211bg(2),
            s80211n(3),
            s80211bgn(4)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriWifiSwitch 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.4.7
priWifiPower OBJECT-TYPE
      SYNTAX INTEGER (0..20)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriWifiSwitch 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.4.8
priWifiSwitchAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            commit(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriWifiSwitch 8 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.5
onuPriWifiSsid OBJECT IDENTIFIER ::= { onuPriGlobalCfg 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.5.1
priSsidPon OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriWifiSsid 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.5.2
proSsidOnu OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriWifiSsid 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.5.3
priSsidId OBJECT-TYPE
      SYNTAX INTEGER (1..4)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriWifiSsid 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.5.4
priSsidName OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriWifiSsid 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.5.5
priSsidEnable OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriWifiSsid 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.5.6
```

```
priSsidHide OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriWifiSsid 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.5.7
priSsidAuthMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            open(1),
            shared(2),
            wepauto(3),
            wpapsk(4),
            wpa(5),
            wpa2psk(6),
            wpa2(7),
            wpa_wpa2(8),
            wpapsk_wpa2psk(9)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriWifiSsid 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.5.8
priSsidEncrypTpye OBJECT-TYPE
      SYNTAX INTEGER
            {
            none(1),
            wep(2),
            tkip(3),
            aes(4),
            tkipaes(5)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriWifiSsid 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.5.9
priSsidPresharedKey OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriWifiSsid 9 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.5.10
priSsidPrekeyInterval OBJECT-TYPE
      SYNTAX INTEGER (0..4194303)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriWifiSsid 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.5.11
priSsidRadiusSeripType OBJECT-TYPE
      SYNTAX INTEGER
            {
            ipv4(1),
            ipv6(2),
            ipv4z(3),
            ipv6z(4),
            dns(16)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriWifiSsid 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.5.12
priSsidRadiusSerip OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriWifiSsid 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.5.13
priSsidRadiusServipPrefixLen OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriWifiSsid 13 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.5.14
priSsidRadiusPort OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriWifiSsid 14 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.5.15
priSsidRadiusKey OBJECT-TYPE
      SYNTAX OCTET STRING (SIZE (0..32))
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriWifiSsid 15 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.5.16
priSsidWepEncrytionLevel OBJECT-TYPE
      SYNTAX INTEGER
            {
            s64bit(1),
            s128bit(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriWifiSsid 16 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.5.17
priSsidWepKeyIndex OBJECT-TYPE
      SYNTAX INTEGER (1..4)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriWifiSsid 17 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.5.18
priSsidWepKey1 OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriWifiSsid 18 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.5.19
priSsidWepKey2 OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriWifiSsid 19 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.5.20
priSsidWepKey3 OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
```

```
      DESCRIPTION
            "Description."
      ::= { onuPriWifiSsid 20 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.5.21
priSsidWepKey4 OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriWifiSsid 21 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.5.22
priSsidAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            commit(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriWifiSsid 22 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.6
onuPriWanConn OBJECT IDENTIFIER ::= { onuPriGlobalCfg 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.6.1
priWanConnAdd OBJECT IDENTIFIER ::= { onuPriWanConn 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.6.1.1
priWanAddPon OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnAdd 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.6.1.2
priWanAddOnu OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnAdd 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.6.1.3
priConnType OBJECT-TYPE
```

```
      SYNTAX INTEGER
            {
            bridge(0),
            route(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnAdd 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.6.1.4
priConnAddAction OBJECT-TYPE
      SYNTAX INTEGER { add(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnAdd 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.6.2
priWanConnDelete OBJECT IDENTIFIER ::= { onuPriWanConn 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.6.2.1
priWanDeletePon OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnDelete 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.6.2.2
priWanDeleteOnu OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnDelete 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.6.2.3
priConnIndexD OBJECT-TYPE
      SYNTAX Integer32 (1..8)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnDelete 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.6.2.4
priConnDeleteAction OBJECT-TYPE
      SYNTAX INTEGER { delete(1) }
```

```
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnDelete 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.6.3
priWanConnCfg OBJECT IDENTIFIER ::= { onuPriWanConn 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.6.3.1
priConnPon OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.6.3.2
priConnOnu OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.6.3.3
priConnIndex OBJECT-TYPE
      SYNTAX INTEGER (1..8)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.6.3.4
priConnBindLan OBJECT-TYPE
      SYNTAX INTEGER (0..15)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.6.3.5
priConnBindSsid OBJECT-TYPE
      SYNTAX INTEGER (0..15)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnCfg 5 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.6.3.6
priWanMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            internet(0),
            multicast(1),
            tr069(2),
            tr069_internet(3),
            tr069_voip(4),
            voip_internet(5),
            tr069_voip_internet(6),
            other(100)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnCfg 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.6.3.7
priConnTypeCfg OBJECT-TYPE
      SYNTAX INTEGER
            {
            bridge(0),
            route(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnCfg 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.6.3.8
priConnVlanId OBJECT-TYPE
      SYNTAX Integer32 (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnCfg 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.6.3.9
priConnCos OBJECT-TYPE
      SYNTAX INTEGER (0..7)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnCfg 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.6.3.10
priConnNatEnable OBJECT-TYPE
      SYNTAX INTEGER
```

```
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnCfg 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.6.3.11
priConnModeCfg OBJECT-TYPE
      SYNTAX INTEGER
            {
            dhcp(0),
            static(1),
            pppoe(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnCfg 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.6.3.12
priConnIpAddress OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnCfg 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.6.3.13
priConnIpMask OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnCfg 13 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.6.3.14
priConnGateway OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnCfg 14 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.6.3.15
priConnMasterDns OBJECT-TYPE
      SYNTAX IpAddress
```

```
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnCfg 15 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.6.3.16
priConnSlaveDns OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnCfg 16 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.6.3.17
priConnPppoeProxy OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnCfg 17 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.6.3.18
priConnPppoeUsername OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnCfg 18 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.6.3.19
priConnPppoePassword OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnCfg 19 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.6.3.20
priConnPppoeSerName OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnCfg 20 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.6.3.21
priConnPppoeMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            autoConnect(0),
            connecWhenPayload(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnCfg 21 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.6.3.22
priConnQosEnable OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnCfg 22 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.6.3.23
priConnVlanMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            tag(1),
            transparent(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnCfg 23 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.6.3.24
priConnTranslationEnable OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnCfg 24 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.6.3.25
priConnTranslationVlan OBJECT-TYPE
      SYNTAX INTEGER (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnCfg 25 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.6.3.26
priConnTranslationCos OBJECT-TYPE
      SYNTAX INTEGER (0..7)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnCfg 26 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.6.3.27
priConnQinqEnable OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnCfg 27 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.6.3.28
priConnQinqTpid OBJECT-TYPE
      SYNTAX Integer32 (0..65534)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnCfg 28 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.6.3.29
priConnWanSvlan OBJECT-TYPE
      SYNTAX INTEGER (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnCfg 29 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.6.3.30
priConnSvlanCos OBJECT-TYPE
      SYNTAX INTEGER (0..7)
      MAX-ACCESS read-write
      STATUS current
```

```
      DESCRIPTION
            "Description."
      ::= { priWanConnCfg 30 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.6.3.31
priConnCfgAction OBJECT-TYPE
      SYNTAX INTEGER { add(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnCfg 31 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.6.4
priWanConnCommit OBJECT IDENTIFIER ::= { onuPriWanConn 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.6.4.1
priConnCommitPon OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnCommit 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.6.4.2
priConnCommitOnu OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnCommit 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.6.4.3
priConnCommitAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            commit(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnCommit 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.7
onuPriPortIsolate OBJECT IDENTIFIER ::= { onuPriGlobalCfg 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.7.1
priPortIsolatePon OBJECT-TYPE
```

```
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriPortIsolate 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.7.2
priPortIsolateOnu OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriPortIsolate 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.7.3
priPortIsolate OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriPortIsolate 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.7.4
priPortIsolateAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            commit(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriPortIsolate 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.8
onuPriFactoryReset OBJECT IDENTIFIER ::= { onuPriGlobalCfg 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.8.1
priFactoryResetPon OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriFactoryReset 1 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.8.2
priFactoryResetOnu OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriFactoryReset 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.8.3
priFactoryReset OBJECT-TYPE
      SYNTAX INTEGER { commit(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriFactoryReset 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.9
onuPriMacClean OBJECT IDENTIFIER ::= { onuPriGlobalCfg 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.9.1
priMacCleanPon OBJECT-TYPE
      SYNTAX INTEGER (1..816)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriMacClean 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.9.2
priMacCleanOnu OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriMacClean 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.9.3
priMacClean OBJECT-TYPE
      SYNTAX INTEGER { commit(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriMacClean 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.10
onuPriSaveConfig OBJECT IDENTIFIER ::= { onuPriGlobalCfg 10 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.10.1
priSaveConfigPon OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriSaveConfig 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.10.2
priSaveConfigOnu OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriSaveConfig 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.10.3
priSaveConfig OBJECT-TYPE
      SYNTAX INTEGER { commit(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriSaveConfig 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.11
onuPriVoipTimer OBJECT IDENTIFIER ::= { onuPriGlobalCfg 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.11.1
onuPriVoipPon OBJECT-TYPE
      SYNTAX Integer32 (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriVoipTimer 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.11.2
onuPriVoipOnu OBJECT-TYPE
      SYNTAX Integer32 (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriVoipTimer 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.11.3
onuPriVoipWaitTime OBJECT-TYPE
      SYNTAX Integer32 (0..254)
      MAX-ACCESS read-write
      STATUS current
```

```
      DESCRIPTION
            "Description."
      ::= { onuPriVoipTimer 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.11.4
onuPriVoipStartTimer OBJECT-TYPE
      SYNTAX Integer32 (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriVoipTimer 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.11.5
onuPriVoipLongTimer OBJECT-TYPE
      SYNTAX Integer32 (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriVoipTimer 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.11.6
onuPriVoipShortTimer OBJECT-TYPE
      SYNTAX Integer32 (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriVoipTimer 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.11.7
onuPriVoipDigitmapNotify OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriVoipTimer 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.11.8
onuPriVoipAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            commit(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
```

```
            "Description."
      ::= { onuPriVoipTimer 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.12
onuPriDhcpServer OBJECT IDENTIFIER ::= { onuPriGlobalCfg 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.12.1
onuPriDhcpServerPon OBJECT-TYPE
      SYNTAX Integer32 (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriDhcpServer 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.12.2
onuPriDhcpServerOnu OBJECT-TYPE
      SYNTAX Integer32 (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriDhcpServer 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.12.3
onuPriDhcpLanIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriDhcpServer 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.12.4
onuPriDhcpLanMask OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriDhcpServer 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.12.5
onuPriDhcpEnable OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1),
            relay(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
```

```
            "Description."
      ::= { onuPriDhcpServer 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.12.6
onuPriDhcpLease OBJECT-TYPE
      SYNTAX Unsigned32 (0..4294967295)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriDhcpServer 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.12.7
onuPriDhcpBeginIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriDhcpServer 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.12.8
onuPriDhcpEndIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriDhcpServer 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.12.9
onuPriDhcpPoolType OBJECT-TYPE
      SYNTAX INTEGER
            {
            pc(0),
            camera(1),
            stb(2),
            ip_phone(3)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriDhcpServer 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.12.10
onuPriDhcpMasterDns OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriDhcpServer 10 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.12.11
onuPriDhcpSlaveDns OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriDhcpServer 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.12.12
onuPriDhcpGateway OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriDhcpServer 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.12.13
onuPriDhcpRelayIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriDhcpServer 13 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.12.14
onuPriDhcpAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            commit(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriDhcpServer 14 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.13
onuPriDhcpOption82 OBJECT IDENTIFIER ::= { onuPriGlobalCfg 13 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.13.1
onuPriDhcpOption82Pon OBJECT-TYPE
      SYNTAX Integer32 (1..8)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriDhcpOption82 1 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.13.2
onuPriDhcpOption82Onu OBJECT-TYPE
      SYNTAX Integer32 (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriDhcpOption82 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.13.3
onuPriDhcpOption82Enable OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriDhcpOption82 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.13.4
onuPriDhcpOption82Action OBJECT-TYPE
      SYNTAX INTEGER
            {
            commit(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriDhcpOption82 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.14
onuPriPPPoE OBJECT IDENTIFIER ::= { onuPriGlobalCfg 14 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.14.1
onuPriPPPoEPon OBJECT-TYPE
      SYNTAX Integer32 (1..8)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriPPPoE 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.14.2
onuPriPPPoEOnu OBJECT-TYPE
      SYNTAX Integer32 (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { onuPriPPPoE 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.14.3
onuPriPPPoEEnable OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriPPPoE 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.14.4
onuPriPPPoEAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            commit(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriPPPoE 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.15
onuPriDhcpV6 OBJECT IDENTIFIER ::= { onuPriGlobalCfg 15 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.15.1
onuPriDhcpV6Pon OBJECT-TYPE
      SYNTAX Integer32 (1..8)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriDhcpV6 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.15.2
onuPriDhcpV6Onu OBJECT-TYPE
      SYNTAX Integer32 (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriDhcpV6 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.15.3
onuPriDhcpV6Option18Enable OBJECT-TYPE
      SYNTAX INTEGER
            {
```

```
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriDhcpV6 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.15.4
onuPriDhcpV6Option37Enable OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriDhcpV6 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.15.5
onuPriDhcpV6Action OBJECT-TYPE
      SYNTAX INTEGER
            {
            commit(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriDhcpV6 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.16
onuPriVoipParam OBJECT IDENTIFIER ::= { onuPriGlobalCfg 16 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.16.1
priVoipParamPon OBJECT-TYPE
      SYNTAX Integer32 (1..8)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriVoipParam 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.16.2
priVoipParamOnu OBJECT-TYPE
      SYNTAX Integer32 (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { onuPriVoipParam 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.16.3
priIpMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            static(1),
            dhcp(2),
            pppoe(3)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriVoipParam 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.16.4
priIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriVoipParam 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.16.5
priMask OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriVoipParam 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.16.6
priGw OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriVoipParam 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.16.7
priRtpIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriVoipParam 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.16.8
```

```
priRtpMask OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriVoipParam 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.16.9
priRtpGw OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriVoipParam 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.16.10
priDnsMaster OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriVoipParam 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.16.11
priDnsSlave OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriVoipParam 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.16.12
priDhcpOption60Enable OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriVoipParam 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.16.13
priDhcpOption60Base OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
```

```
            "Description."
      ::= { onuPriVoipParam 13 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.16.14
priDhcpOption60Value OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriVoipParam 14 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.16.15
priPPPoEMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            auto(0),
            chap(1),
            pap(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriVoipParam 15 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.16.16
priPPPoEUsername OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriVoipParam 16 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.16.17
priPPPoEPassword OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriVoipParam 17 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.16.18
priSVlanTpid OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriVoipParam 18 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.16.19
priSVlanId OBJECT-TYPE
      SYNTAX Integer32 (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriVoipParam 19 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.16.20
priSVlanCos OBJECT-TYPE
      SYNTAX Integer32 (0..7)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriVoipParam 20 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.16.21
priCVlanTpid OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriVoipParam 21 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.16.22
priCVlanId OBJECT-TYPE
      SYNTAX Integer32 (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriVoipParam 22 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.16.23
priCVlanCos OBJECT-TYPE
      SYNTAX Integer32 (0..7)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriVoipParam 23 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.16.24
priRtpSVlanTpid OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriVoipParam 24 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.16.25
priRtpSVlanId OBJECT-TYPE
      SYNTAX Integer32 (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriVoipParam 25 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.16.26
priRtpSVlanCos OBJECT-TYPE
      SYNTAX Integer32 (0..7)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriVoipParam 26 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.16.27
priRtpCVlanTpid OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriVoipParam 27 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.16.28
priRtpCVlanId OBJECT-TYPE
      SYNTAX Integer32 (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriVoipParam 28 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.16.29
priRtpCVlanCos OBJECT-TYPE
      SYNTAX Integer32 (0..7)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriVoipParam 29 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.16.30
priVoipParamAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            commit(1),
            remove(2)
            }
      MAX-ACCESS read-write
```

```
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriVoipParam 30 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.17
onuPriSipParam OBJECT IDENTIFIER ::= { onuPriGlobalCfg 17 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.17.1
priSipParamPon OBJECT-TYPE
      SYNTAX Integer32 (1..8)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriSipParam 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.17.2
priSipParamOnu OBJECT-TYPE
      SYNTAX Integer32 (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriSipParam 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.17.3
priProxyServName OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriSipParam 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.17.4
priProxyServPort OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriSipParam 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.17.5
priBakProxyServName OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriSipParam 5 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.17.6
priBakProxyServPort OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriSipParam 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.17.7
priRegServName OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriSipParam 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.17.8
priRegServPort OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriSipParam 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.17.9
priBakRegServName OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriSipParam 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.17.10
priBakRegServPort OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriSipParam 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.17.11
priOutBndServName OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriSipParam 11 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.17.12
priOutBndServPort OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriSipParam 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.17.13
priSipParamMgPort OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriSipParam 13 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.17.14
priRegInterval OBJECT-TYPE
      SYNTAX Integer32 (0..10000000)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriSipParam 14 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.17.15
priHBeatCfg OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            active(1),
            passive(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriSipParam 15 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.17.16
priHBeatCycle OBJECT-TYPE
      SYNTAX Integer32 (1..65525)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriSipParam 16 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.17.17
priHBeatCount OBJECT-TYPE
```

```
      SYNTAX Integer32 (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriSipParam 17 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.1.17.18
priSipGloParamAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            commit(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriSipParam 18 }



-- 1.3.6.1.4.1.37950.1.1.5.12.3.2
onuPriGlobalInfo OBJECT IDENTIFIER ::= { onuPriGlobal 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.1
priIgmpAdminTable OBJECT-TYPE
      SYNTAX SEQUENCE OF PriIgmpAdminEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriGlobalInfo 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.1.1
priIgmpAdminEntry OBJECT-TYPE
      SYNTAX PriIgmpAdminEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { priIgmpAdminPonS, priIgmpAdminOnuS }
      ::= { priIgmpAdminTable 1 }


PriIgmpAdminEntry ::=
      SEQUENCE {
            priIgmpAdminPonS
                  INTEGER,
            priIgmpAdminOnuS
                  INTEGER,
            priIgmpAdminEnableS
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.1.1.1
```

```
priIgmpAdminPonS OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priIgmpAdminEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.1.1.2
priIgmpAdminOnuS OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priIgmpAdminEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.1.1.3
priIgmpAdminEnableS OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priIgmpAdminEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.2
priCatvStatusTable OBJECT-TYPE
      SYNTAX SEQUENCE OF PriCatvStatusEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriGlobalInfo 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.2.1
priCatvStatusEntry OBJECT-TYPE
      SYNTAX PriCatvStatusEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { priCatvStatusPonS, priCatvSatusOnuS }
      ::= { priCatvStatusTable 1 }


PriCatvStatusEntry ::=
      SEQUENCE {
            priCatvStatusPonS
                  INTEGER,
            priCatvSatusOnuS
```

```
                  INTEGER,
            priCatvStatusS
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.2.1.1
priCatvStatusPonS OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priCatvStatusEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.2.1.2
priCatvSatusOnuS OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priCatvStatusEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.2.1.3
priCatvStatusS OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priCatvStatusEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.3
priCtcoamSkipTable OBJECT-TYPE
      SYNTAX SEQUENCE OF PriCtcoamSkipEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriGlobalInfo 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.3.1
priCtcoamSkipEntry OBJECT-TYPE
      SYNTAX PriCtcoamSkipEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { priCtcoamSkipPonS, priCtcOamSkipOnuS }
      ::= { priCtcoamSkipTable 1 }
```

```
PriCtcoamSkipEntry ::=
      SEQUENCE {
            priCtcoamSkipPonS
                  INTEGER,
            priCtcOamSkipOnuS
                  INTEGER,
            priCtcoamSkipS
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.3.1.1
priCtcoamSkipPonS OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priCtcoamSkipEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.3.1.2
priCtcOamSkipOnuS OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priCtcoamSkipEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.3.1.3
priCtcoamSkipS OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priCtcoamSkipEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.4
priWifiSwichTable OBJECT-TYPE
      SYNTAX SEQUENCE OF PriWifiSwichEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriGlobalInfo 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.4.1
priWifiSwichEntry OBJECT-TYPE
      SYNTAX PriWifiSwichEntry
      MAX-ACCESS not-accessible
```

```
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { priWifiSwichPonS, priWifiSwichOnuS }
      ::= { priWifiSwichTable 1 }


PriWifiSwichEntry ::=
      SEQUENCE {
            priWifiSwichPonS
                  INTEGER,
            priWifiSwichOnuS
                  INTEGER,
            priWifiSwichAPModuleS
                  INTEGER,
            priWifiSwichCountry
                  INTEGER,
            priWifiSwichChannelS
                  INTEGER,
            priWifiSwichStandardS
                  INTEGER,
            priWifiSwitchPower
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.4.1.1
priWifiSwichPonS OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWifiSwichEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.4.1.2
priWifiSwichOnuS OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWifiSwichEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.4.1.3
priWifiSwichAPModuleS OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWifiSwichEntry 3 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.4.1.4
priWifiSwichCountry OBJECT-TYPE
      SYNTAX INTEGER
            {
            ETSI(0),
            FCC(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWifiSwichEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.4.1.5
priWifiSwichChannelS OBJECT-TYPE
      SYNTAX INTEGER (0..13)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWifiSwichEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.4.1.6
priWifiSwichStandardS OBJECT-TYPE
      SYNTAX INTEGER
            {
            s80211b(0),
            s80211g(1),
            s80211bg(2),
            s80211n(3),
            s80211bgn(4)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWifiSwichEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.4.1.7
priWifiSwitchPower OBJECT-TYPE
      SYNTAX INTEGER (0..20)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWifiSwichEntry 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.5
priWifiSsidTable OBJECT-TYPE
      SYNTAX SEQUENCE OF PriWifiSsidEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriGlobalInfo 5 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.5.1
priWifiSsidEntry OBJECT-TYPE
      SYNTAX PriWifiSsidEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { priWifiSsidPonS, priWifiSsidOnuS, priWifiSsidIdS }
      ::= { priWifiSsidTable 1 }


PriWifiSsidEntry ::=
      SEQUENCE {
            priWifiSsidPonS
                  INTEGER,
            priWifiSsidOnuS
                  INTEGER,
            priWifiSsidIdS
                  Integer32,
            priWifiSsidNameS
                  OCTET STRING,
            priWifiSsidEnableS
                  INTEGER,
            priWifiSsidHideS
                  INTEGER,
            priWifiSsidAuthMode
                  INTEGER,
            priWifiSsidEncryTpeS
                  INTEGER,
            priSsidPreshareKeyS
                  OCTET STRING,
            priSsidWpaRekeyIntervalS
                  INTEGER,
            priSsidRadiusServIpTypeS
                  INTEGER,
            priSsidRadiusServIp
                  OCTET STRING,
            priSsidRadiusServIpPrefixLenS
                  INTEGER,
            priSsidRadiusPortS
                  INTEGER,
            priSsidRadiusKeyS
                  OCTET STRING,
            priSsidWepEncryptionLevelS
                  INTEGER,
            priSsidWepKeyIndexS
                  INTEGER,
            priSsidWepKey1S
                  OCTET STRING,
            priSsidWepKey2S
                  OCTET STRING,
            priSsidWepKey3S
                  OCTET STRING,
            priSsidWepKey4S
                  OCTET STRING
       }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.5.1.1
priWifiSsidPonS OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWifiSsidEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.5.1.2
priWifiSsidOnuS OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWifiSsidEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.5.1.3
priWifiSsidIdS OBJECT-TYPE
      SYNTAX Integer32 (1..4)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWifiSsidEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.5.1.4
priWifiSsidNameS OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWifiSsidEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.5.1.5
priWifiSsidEnableS OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWifiSsidEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.5.1.6
priWifiSsidHideS OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
```

```
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWifiSsidEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.5.1.7
priWifiSsidAuthMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            open(1),
            shared(2),
            wepauto(3),
            wpapsk(4),
            wpa(5),
            wpa2psk(6),
            wpa2(7),
            wpa_wpa2(8),
            wpapsk_wpa2psk(9)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWifiSsidEntry 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.5.1.8
priWifiSsidEncryTpeS OBJECT-TYPE
      SYNTAX INTEGER
            {
            none(1),
            wep(2),
            tkip(3),
            aes(4),
            tkipaes(5)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWifiSsidEntry 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.5.1.9
priSsidPreshareKeyS OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWifiSsidEntry 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.5.1.10
priSsidWpaRekeyIntervalS OBJECT-TYPE
```

```
      SYNTAX INTEGER (0..4194303)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWifiSsidEntry 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.5.1.11
priSsidRadiusServIpTypeS OBJECT-TYPE
      SYNTAX INTEGER
            {
            unknown(0),
            ipv4(1),
            ipv6(2),
            ipv4z(3),
            ipv6z(4),
            dns(16)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWifiSsidEntry 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.5.1.12
priSsidRadiusServIp OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWifiSsidEntry 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.5.1.13
priSsidRadiusServIpPrefixLenS OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWifiSsidEntry 13 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.5.1.14
priSsidRadiusPortS OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWifiSsidEntry 14 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.5.1.15
priSsidRadiusKeyS OBJECT-TYPE
      SYNTAX OCTET STRING (SIZE (0..32))
```

```
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWifiSsidEntry 15 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.5.1.16
priSsidWepEncryptionLevelS OBJECT-TYPE
      SYNTAX INTEGER
            {
            s64bit(1),
            s128bit(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWifiSsidEntry 16 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.5.1.17
priSsidWepKeyIndexS OBJECT-TYPE
      SYNTAX INTEGER (1..4)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWifiSsidEntry 17 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.5.1.18
priSsidWepKey1S OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWifiSsidEntry 18 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.5.1.19
priSsidWepKey2S OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWifiSsidEntry 19 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.5.1.20
priSsidWepKey3S OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWifiSsidEntry 20 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.5.1.21
priSsidWepKey4S OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWifiSsidEntry 21 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.6
priWanConnTable OBJECT-TYPE
      SYNTAX SEQUENCE OF PriWanConnEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriGlobalInfo 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.6.1
priWanConnEntry OBJECT-TYPE
      SYNTAX PriWanConnEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { priWanConnPonS, priWanConnOnuS, priWanConnIndexS }
      ::= { priWanConnTable 1 }


PriWanConnEntry ::=
      SEQUENCE {
            priWanConnPonS
                  INTEGER,
            priWanConnOnuS
                  INTEGER,
            priWanConnIndexS
                  Integer32,
            priWanConnBindLanS
                  INTEGER,
            priWanConnBindSsidS
                  INTEGER,
            priWanModeS
                  INTEGER,
            priWanConnTypeS
                  INTEGER,
            priWanConnVlanIdS
                  INTEGER,
            priWanConnVlanCosS
                  INTEGER,
            priWanConnNatEnableS
                  INTEGER,
            priWanConnModeS
                  INTEGER,
            priWanConnIpAddressS
                  IpAddress,
```

```
            priWanConnIpMaskS
                  IpAddress,
            priWanConnGatewayS
                  IpAddress,
            priWanConnMasterDns
                  IpAddress,
            priWanConnSlaveDns
                  IpAddress,
            priWanConnPppoeProxyS
                  INTEGER,
            priWanConnPppoeUsernameS
                  OCTET STRING,
            priWanConnPppoePasswordS
                  OCTET STRING,
            priWanConnPppoeSerName
                  OCTET STRING,
            priWanConnPppoeModeS
                  INTEGER,
            priWanConnQosEnableS
                  INTEGER,
            priWanConnVlanModeS
                  INTEGER,
            priWanConnTranslationEnableS
                  INTEGER,
            priWanConnTranslationVlanS
                  INTEGER,
            priWanConnTranslationCosS
                  INTEGER,
            priWanConnQinqEnableS
                  INTEGER,
            priWanConnQinqTpidS
                  INTEGER,
            priWanConnSvlanIdS
                  INTEGER,
            priWanConnSvlanCosS
                  INTEGER,
            priWanConnName
                  OCTET STRING,
            priWanConnStatus
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.6.1.1
priWanConnPonS OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.6.1.2
priWanConnOnuS OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { priWanConnEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.6.1.3
priWanConnIndexS OBJECT-TYPE
      SYNTAX Integer32 (1..8)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.6.1.4
priWanConnBindLanS OBJECT-TYPE
      SYNTAX INTEGER (0..15)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.6.1.5
priWanConnBindSsidS OBJECT-TYPE
      SYNTAX INTEGER (0..15)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.6.1.6
priWanModeS OBJECT-TYPE
      SYNTAX INTEGER
            {
            internet(0),
            multicast(1),
            tr069(2),
            tr069_internet(3),
            tr069_voip(4),
            voip_internet(5),
            tr069_voip_internet(6),
            other(100)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.6.1.7
priWanConnTypeS OBJECT-TYPE
      SYNTAX INTEGER
            {
            bridge(0),
            route(1)
```

```
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnEntry 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.6.1.8
priWanConnVlanIdS OBJECT-TYPE
      SYNTAX INTEGER (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnEntry 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.6.1.9
priWanConnVlanCosS OBJECT-TYPE
      SYNTAX INTEGER (0..7)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnEntry 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.6.1.10
priWanConnNatEnableS OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnEntry 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.6.1.11
priWanConnModeS OBJECT-TYPE
      SYNTAX INTEGER
            {
            dhcp(0),
            static(1),
            pppoe(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnEntry 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.6.1.12
priWanConnIpAddressS OBJECT-TYPE
```

```
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnEntry 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.6.1.13
priWanConnIpMaskS OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnEntry 13 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.6.1.14
priWanConnGatewayS OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnEntry 14 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.6.1.15
priWanConnMasterDns OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnEntry 15 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.6.1.16
priWanConnSlaveDns OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnEntry 16 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.6.1.17
priWanConnPppoeProxyS OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { priWanConnEntry 17 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.6.1.18
priWanConnPppoeUsernameS OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnEntry 18 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.6.1.19
priWanConnPppoePasswordS OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnEntry 19 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.6.1.20
priWanConnPppoeSerName OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnEntry 20 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.6.1.21
priWanConnPppoeModeS OBJECT-TYPE
      SYNTAX INTEGER
            {
            autoConnect(0),
            connectWhenPayload(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnEntry 21 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.6.1.22
priWanConnQosEnableS OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnEntry 22 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.6.1.23
priWanConnVlanModeS OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            tag(1),
            transparent(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnEntry 23 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.6.1.24
priWanConnTranslationEnableS OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnEntry 24 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.6.1.25
priWanConnTranslationVlanS OBJECT-TYPE
      SYNTAX INTEGER (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnEntry 25 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.6.1.26
priWanConnTranslationCosS OBJECT-TYPE
      SYNTAX INTEGER (0..7)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnEntry 26 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.6.1.27
priWanConnQinqEnableS OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
```

```
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnEntry 27 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.6.1.28
priWanConnQinqTpidS OBJECT-TYPE
      SYNTAX INTEGER (0..65534)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnEntry 28 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.6.1.29
priWanConnSvlanIdS OBJECT-TYPE
      SYNTAX INTEGER (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnEntry 29 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.6.1.30
priWanConnSvlanCosS OBJECT-TYPE
      SYNTAX INTEGER (0..7)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnEntry 30 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.6.1.31
priWanConnName OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnEntry 31 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.6.1.32
priWanConnStatus OBJECT-TYPE
      SYNTAX INTEGER
            {
            disconnected(0),
            connected(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priWanConnEntry 32 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.7
priPortIsolateTable OBJECT-TYPE
      SYNTAX SEQUENCE OF PriPortIsolateEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriGlobalInfo 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.7.1
priPortIsolateEntry OBJECT-TYPE
      SYNTAX PriPortIsolateEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { priPortIsolatePonS, priPortIsolateOnuS }
      ::= { priPortIsolateTable 1 }


PriPortIsolateEntry ::=
      SEQUENCE {
            priPortIsolatePonS
                  INTEGER,
            priPortIsolateOnuS
                  INTEGER,
            priPortIsolateS
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.7.1.1
priPortIsolatePonS OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priPortIsolateEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.7.1.2
priPortIsolateOnuS OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priPortIsolateEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.7.1.3
priPortIsolateS OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
```

```
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priPortIsolateEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.8
priVoipTimerTable OBJECT-TYPE
      SYNTAX SEQUENCE OF PriVoipTimerEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriGlobalInfo 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.8.1
priVoipTimerEntry OBJECT-TYPE
      SYNTAX PriVoipTimerEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { priVoipTimerPon, priVoipTimerOnu }
      ::= { priVoipTimerTable 1 }


PriVoipTimerEntry ::=
      SEQUENCE {
            priVoipTimerPon
                  Integer32,
            priVoipTimerOnu
                  Integer32,
            priVoipTimerWaitTimer
                  Integer32,
            priVoipTimerStartTimer
                  Integer32,
            priVoipTimerLongTimer
                  Integer32,
            priVoipTimerShortTimer
                  Integer32,
            priVoipTimerDigitNotify
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.8.1.1
priVoipTimerPon OBJECT-TYPE
      SYNTAX Integer32 (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priVoipTimerEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.8.1.2
priVoipTimerOnu OBJECT-TYPE
      SYNTAX Integer32 (1..65535)
      MAX-ACCESS read-write
```

```
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priVoipTimerEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.8.1.3
priVoipTimerWaitTimer OBJECT-TYPE
      SYNTAX Integer32 (0..254)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priVoipTimerEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.8.1.4
priVoipTimerStartTimer OBJECT-TYPE
      SYNTAX Integer32 (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priVoipTimerEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.8.1.5
priVoipTimerLongTimer OBJECT-TYPE
      SYNTAX Integer32 (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priVoipTimerEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.8.1.6
priVoipTimerShortTimer OBJECT-TYPE
      SYNTAX Integer32 (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priVoipTimerEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.8.1.7
priVoipTimerDigitNotify OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priVoipTimerEntry 7 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.9
priDhcpServerTable OBJECT-TYPE
      SYNTAX SEQUENCE OF PriDhcpServerEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriGlobalInfo 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.9.1
priDhcpServerEntry OBJECT-TYPE
      SYNTAX PriDhcpServerEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { priDhcpServerPon, priDhcpServerOnu }
      ::= { priDhcpServerTable 1 }


PriDhcpServerEntry ::=
      SEQUENCE {
            priDhcpServerPon
                  Integer32,
            priDhcpServerOnu
                  Integer32,
            priDhcpLanIp
                  IpAddress,
            priDhcpLanMask
                  IpAddress,
            priDhcpEnable
                  INTEGER,
            priDhcpLease
                  Unsigned32,
            priDhcpBeginIp
                  IpAddress,
            priDhcpEndIp
                  IpAddress,
            priDhcpPoolType
                  INTEGER,
            priDhcpMasterDns
                  IpAddress,
            priDhcpSlaveDns
                  IpAddress,
            priDhcpGateway
                  IpAddress,
            priDhcpRelayIp
                  IpAddress
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.9.1.1
priDhcpServerPon OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { priDhcpServerEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.9.1.2
priDhcpServerOnu OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priDhcpServerEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.9.1.3
priDhcpLanIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priDhcpServerEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.9.1.4
priDhcpLanMask OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priDhcpServerEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.9.1.5
priDhcpEnable OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1),
            relay(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priDhcpServerEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.9.1.6
priDhcpLease OBJECT-TYPE
      SYNTAX Unsigned32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priDhcpServerEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.9.1.7
```

```
priDhcpBeginIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priDhcpServerEntry 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.9.1.8
priDhcpEndIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priDhcpServerEntry 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.9.1.9
priDhcpPoolType OBJECT-TYPE
      SYNTAX INTEGER
            {
            pc(0),
            camera(1),
            stb(2),
            ip_phone(3)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priDhcpServerEntry 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.9.1.10
priDhcpMasterDns OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priDhcpServerEntry 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.9.1.11
priDhcpSlaveDns OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priDhcpServerEntry 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.9.1.12
priDhcpGateway OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
```

```
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priDhcpServerEntry 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.9.1.13
priDhcpRelayIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priDhcpServerEntry 13 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.10
priDhcpOption82Table OBJECT-TYPE
      SYNTAX SEQUENCE OF PriDhcpOption82Entry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriGlobalInfo 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.10.1
priDhcpOption82Entry OBJECT-TYPE
      SYNTAX PriDhcpOption82Entry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { priDhcpOption82Pon, priDhcpOption82Onu }
      ::= { priDhcpOption82Table 1 }


PriDhcpOption82Entry ::=
      SEQUENCE {
            priDhcpOption82Pon
                  Integer32,
            priDhcpOption82Onu
                  Integer32,
            priDhcpOption82Enable
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.10.1.1
priDhcpOption82Pon OBJECT-TYPE
      SYNTAX Integer32 (1..8)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priDhcpOption82Entry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.10.1.2
priDhcpOption82Onu OBJECT-TYPE
```

```
      SYNTAX Integer32 (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priDhcpOption82Entry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.10.1.3
priDhcpOption82Enable OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priDhcpOption82Entry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.11
priPPPoETable OBJECT-TYPE
      SYNTAX SEQUENCE OF PriPPPoEEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriGlobalInfo 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.11.1
priPPPoEEntry OBJECT-TYPE
      SYNTAX PriPPPoEEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { priPPPoEPon, priPPPoEOnu }
      ::= { priPPPoETable 1 }


PriPPPoEEntry ::=
      SEQUENCE {
            priPPPoEPon
                  Integer32,
            priPPPoEOnu
                  Integer32,
            priPPPoEEnable
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.11.1.1
priPPPoEPon OBJECT-TYPE
      SYNTAX Integer32 (1..8)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
```

```
            "Description."
      ::= { priPPPoEEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.11.1.2
priPPPoEOnu OBJECT-TYPE
      SYNTAX Integer32 (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priPPPoEEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.11.1.3
priPPPoEEnable OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priPPPoEEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.12
priDhcpV6Table OBJECT-TYPE
      SYNTAX SEQUENCE OF PriDhcpV6Entry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriGlobalInfo 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.12.1
priDhcpV6Entry OBJECT-TYPE
      SYNTAX PriDhcpV6Entry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { priDhcpV6Pon, priDhcpV6Onu }
      ::= { priDhcpV6Table 1 }


PriDhcpV6Entry ::=
      SEQUENCE {
            priDhcpV6Pon
                  Integer32,
            priDhcpV6Onu
                  Integer32,
            priDhcpV6Option18Enable
                  INTEGER,
            priDhcpV6Option37Enable
                  INTEGER
```

```
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.12.1.1
priDhcpV6Pon OBJECT-TYPE
      SYNTAX Integer32 (1..8)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priDhcpV6Entry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.12.1.2
priDhcpV6Onu OBJECT-TYPE
      SYNTAX Integer32 (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priDhcpV6Entry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.12.1.3
priDhcpV6Option18Enable OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priDhcpV6Entry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.12.1.4
priDhcpV6Option37Enable OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priDhcpV6Entry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.13
priVoipParamTable OBJECT-TYPE
      SYNTAX SEQUENCE OF PriVoipParamEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriGlobalInfo 13 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.13.1
priVoipParamEntry OBJECT-TYPE
      SYNTAX PriVoipParamEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { voipPTPon, voipPTOnu }
      ::= { priVoipParamTable 1 }


PriVoipParamEntry ::=
      SEQUENCE {
            voipPTPon
                  Integer32,
            voipPTOnu
                  Integer32,
            voipPTIpMode
                  INTEGER,
            voipPTIp
                  IpAddress,
            voipPTMask
                  IpAddress,
            voipPTGw
                  IpAddress,
            voipPTRtpIp
                  IpAddress,
            voipPTRtpMask
                  IpAddress,
            voipPTRtpGw
                  IpAddress,
            voipPTDnsMaster
                  IpAddress,
            voipPTDnsSlave
                  IpAddress,
            voipPTDhcpOption60Enable
                  INTEGER,
            voipPTDhcpOption60Base
                  OCTET STRING,
            voipPTDhcpOption60Value
                  OCTET STRING,
            voipPTPPPoEMode
                  INTEGER,
            voipPTPPPoEUsername
                  OCTET STRING,
            voipPTPPPoEPassword
                  OCTET STRING,
            voipPTSVlanTpid
                  Integer32,
            voipPTSVlanId
                  Integer32,
            voipPTSVlanCos
                  Integer32,
            voipPTCVlanTpid
                  Integer32,
            voipPTCVlanId
                  Integer32,
            voipPTCVlanCos
```

```
                  Integer32,
            voipPTRtpSVlanTpid
                  Integer32,
            voipPTRtpSVlanId
                  Integer32,
            voipPTRtpSVlanCos
                  Integer32,
            voipPTRtpCVlanTpid
                  Integer32,
            voipPTRtpCVlanId
                  Integer32,
            voipPTRtpCVlanCos
                  Integer32
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.13.1.1
voipPTPon OBJECT-TYPE
      SYNTAX Integer32 (1..8)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priVoipParamEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.13.1.2
voipPTOnu OBJECT-TYPE
      SYNTAX Integer32 (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priVoipParamEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.13.1.3
voipPTIpMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            static(1),
            dhcp(2),
            pppoe(3)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priVoipParamEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.13.1.4
voipPTIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priVoipParamEntry 4 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.13.1.5
voipPTMask OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priVoipParamEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.13.1.6
voipPTGw OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priVoipParamEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.13.1.7
voipPTRtpIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priVoipParamEntry 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.13.1.8
voipPTRtpMask OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priVoipParamEntry 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.13.1.9
voipPTRtpGw OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priVoipParamEntry 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.13.1.10
voipPTDnsMaster OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priVoipParamEntry 10 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.13.1.11
voipPTDnsSlave OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priVoipParamEntry 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.13.1.12
voipPTDhcpOption60Enable OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priVoipParamEntry 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.13.1.13
voipPTDhcpOption60Base OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priVoipParamEntry 13 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.13.1.14
voipPTDhcpOption60Value OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priVoipParamEntry 14 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.13.1.15
voipPTPPPoEMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            auto(1),
            chap(2),
            pap(3)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priVoipParamEntry 15 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.13.1.16
voipPTPPPoEUsername OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priVoipParamEntry 16 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.13.1.17
voipPTPPPoEPassword OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priVoipParamEntry 17 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.13.1.18
voipPTSVlanTpid OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priVoipParamEntry 18 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.13.1.19
voipPTSVlanId OBJECT-TYPE
      SYNTAX Integer32 (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priVoipParamEntry 19 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.13.1.20
voipPTSVlanCos OBJECT-TYPE
      SYNTAX Integer32 (0..7)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priVoipParamEntry 20 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.13.1.21
voipPTCVlanTpid OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { priVoipParamEntry 21 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.13.1.22
voipPTCVlanId OBJECT-TYPE
      SYNTAX Integer32 (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priVoipParamEntry 22 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.13.1.23
voipPTCVlanCos OBJECT-TYPE
      SYNTAX Integer32 (0..7)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priVoipParamEntry 23 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.13.1.24
voipPTRtpSVlanTpid OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priVoipParamEntry 24 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.13.1.25
voipPTRtpSVlanId OBJECT-TYPE
      SYNTAX Integer32 (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priVoipParamEntry 25 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.13.1.26
voipPTRtpSVlanCos OBJECT-TYPE
      SYNTAX Integer32 (0..7)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priVoipParamEntry 26 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.13.1.27
voipPTRtpCVlanTpid OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
```

```
            "Description."
      ::= { priVoipParamEntry 27 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.13.1.28
voipPTRtpCVlanId OBJECT-TYPE
      SYNTAX Integer32 (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priVoipParamEntry 28 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.13.1.29
voipPTRtpCVlanCos OBJECT-TYPE
      SYNTAX Integer32 (0..7)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priVoipParamEntry 29 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.14
priSipParamTable OBJECT-TYPE
      SYNTAX SEQUENCE OF PriSipParamEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriGlobalInfo 14 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.14.1
priSipParamEntry OBJECT-TYPE
      SYNTAX PriSipParamEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { sipPTPon, sipPTOnu }
      ::= { priSipParamTable 1 }


PriSipParamEntry ::=
      SEQUENCE {
            sipPTPon
                  Integer32,
            sipPTOnu
                  Integer32,
            sipPTProxyServName
                  OCTET STRING,
            sipPTProxyServPort
                  Integer32,
            sipPTBakProxyServName
                  OCTET STRING,
            sipPTBakProxyServPort
                  Integer32,
```

```
            sipPTRegServName
                  OCTET STRING,
            sipPTRegServPort
                  Integer32,
            sipPTBakRegServName
                  OCTET STRING,
            sipPTBakRegServPort
                  Integer32,
            sipPTOutBndServName
                  OCTET STRING,
            sipPTOutBndServPort
                  Integer32,
            sipPTMgPort
                  Integer32,
            activeSipProxyServer
                  OCTET STRING,
            sipPTRegInterValue
                  Integer32,
            sipPTHBeatCfg
                  INTEGER,
            sipPTHBeatCycle
                  Integer32,
            sipPTHBeatCount
                  Integer32
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.14.1.1
sipPTPon OBJECT-TYPE
      SYNTAX Integer32 (1..8)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priSipParamEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.14.1.2
sipPTOnu OBJECT-TYPE
      SYNTAX Integer32 (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priSipParamEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.14.1.3
sipPTProxyServName OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priSipParamEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.14.1.4
sipPTProxyServPort OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
```

```
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priSipParamEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.14.1.5
sipPTBakProxyServName OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priSipParamEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.14.1.6
sipPTBakProxyServPort OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priSipParamEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.14.1.7
sipPTRegServName OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priSipParamEntry 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.14.1.8
sipPTRegServPort OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priSipParamEntry 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.14.1.9
sipPTBakRegServName OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priSipParamEntry 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.14.1.10
sipPTBakRegServPort OBJECT-TYPE
```

```
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priSipParamEntry 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.14.1.11
sipPTOutBndServName OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priSipParamEntry 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.14.1.12
sipPTOutBndServPort OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priSipParamEntry 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.14.1.13
sipPTMgPort OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priSipParamEntry 13 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.14.1.14
activeSipProxyServer OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priSipParamEntry 14 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.14.1.15
sipPTRegInterValue OBJECT-TYPE
      SYNTAX Integer32 (0..10000000)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priSipParamEntry 15 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.14.1.16
```

```
sipPTHBeatCfg OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            active(1),
            passive(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priSipParamEntry 16 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.14.1.17
sipPTHBeatCycle OBJECT-TYPE
      SYNTAX Integer32 (1..65525)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priSipParamEntry 17 }


-- 1.3.6.1.4.1.37950.1.1.5.12.3.2.14.1.18
sipPTHBeatCount OBJECT-TYPE
      SYNTAX Integer32 (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priSipParamEntry 18 }

-- 1.3.6.1.4.1.37950.1.1.5.12.4
onuPriPort OBJECT IDENTIFIER ::= { v1600dOnuMgmt 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.1
onuPriPortCfg OBJECT IDENTIFIER ::= { onuPriPort 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.1.1
onuPriPortMacLimit OBJECT IDENTIFIER ::= { onuPriPortCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.1.1.1
priMacLimitPon OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriPortMacLimit 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.1.1.2
priMacLimitOnu OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
```

```
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriPortMacLimit 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.1.1.3
priMacLimitEthNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriPortMacLimit 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.1.1.4
priMacLimit OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriPortMacLimit 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.1.1.5
priMacLimitAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriPortMacLimit 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.1.2
onuPriPortPkgSuppress OBJECT IDENTIFIER ::= { onuPriPortCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.1.2.1
priPkgSuppressPon OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriPortPkgSuppress 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.1.2.2
priPkgSuppressOnu OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
```

```
      DESCRIPTION
            "Description."
      ::= { onuPriPortPkgSuppress 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.1.2.3
priPkgSuppressEthNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriPortPkgSuppress 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.1.2.4
priPkgBroadcast OBJECT-TYPE
      SYNTAX INTEGER (0..1024000)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriPortPkgSuppress 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.1.2.5
priPkgMulticast OBJECT-TYPE
      SYNTAX INTEGER (0..1024000)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriPortPkgSuppress 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.1.2.6
priPkgUnknown OBJECT-TYPE
      SYNTAX INTEGER (0..1024000)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriPortPkgSuppress 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.1.2.7
priPkgSuppressAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriPortPkgSuppress 7 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.4.1.3
onuPriPortModeControl OBJECT IDENTIFIER ::= { onuPriPortCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.1.3.1
priModeControlPon OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriPortModeControl 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.1.3.2
priModeControlOnu OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriPortModeControl 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.1.3.3
priModeControlEthNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriPortModeControl 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.1.3.4
priModeControl OBJECT-TYPE
      SYNTAX INTEGER
            {
            s10hd(1),
            s10fd(2),
            s100hd(3),
            s100fd(4),
            s1000hd(5),
            s1000fd(6),
            s10000fd(7)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriPortModeControl 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.1.3.5
priModeControlAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            remove(2)
```

```
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriPortModeControl 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.1.4
onuPriPotsParameter OBJECT IDENTIFIER ::= { onuPriPortCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.1.4.1
priPotsParameterPon OBJECT-TYPE
      SYNTAX Integer32 (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriPotsParameter 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.1.4.2
priPotsParameterOnu OBJECT-TYPE
      SYNTAX Integer32 (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriPotsParameter 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.1.4.3
priPotsParameterPotsNo OBJECT-TYPE
      SYNTAX Integer32 (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriPotsParameter 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.1.4.4
priPotsParameterVar OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriPotsParameter 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.1.4.5
priPotsParameterEchoCancle OBJECT-TYPE
      SYNTAX INTEGER
```

```
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriPotsParameter 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.1.4.6
priPotsPtInutGain OBJECT-TYPE
      SYNTAX Integer32 (-32..32)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriPotsParameter 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.1.4.7
priPotsPtOutputGain OBJECT-TYPE
      SYNTAX Integer32 (-32..32)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriPotsParameter 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.1.4.8
priPotsPtDtmfMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            transparent(0),
            rfc2833(1),
            rfc2833_redundancy(2),
            outband(3)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriPotsParameter 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.1.4.9
priPotsPtAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            commit(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriPotsParameter 9 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.4.1.5
onuPriPotsAction OBJECT IDENTIFIER ::= { onuPriPortCfg 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.1.5.1
priPotsActionPon OBJECT-TYPE
      SYNTAX Integer32 (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriPotsAction 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.1.5.2
priPotsActionOnu OBJECT-TYPE
      SYNTAX Integer32 (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriPotsAction 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.1.5.3
priPotsActionPotsNo OBJECT-TYPE
      SYNTAX Integer32 (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriPotsAction 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.1.5.4
priPotsActionRegister OBJECT-TYPE
      SYNTAX INTEGER
            {
            unregister(0),
            register(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriPotsAction 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.1.5.5
priPotsActionAction OBJECT-TYPE
      SYNTAX INTEGER { commit(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriPotsAction 5 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.4.2
onuPriPortInfo OBJECT IDENTIFIER ::= { onuPriPort 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.2.1
priPortMacLimitTable OBJECT-TYPE
      SYNTAX SEQUENCE OF PriPortMacLimitEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriPortInfo 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.2.1.1
priPortMacLimitEntry OBJECT-TYPE
      SYNTAX PriPortMacLimitEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { priPortMacLimitPonS, priPortMacLimitOnuS,
priPortMacLimitEthNoS }
      ::= { priPortMacLimitTable 1 }


PriPortMacLimitEntry ::=
      SEQUENCE {
            priPortMacLimitPonS
                  INTEGER,
            priPortMacLimitOnuS
                  INTEGER,
            priPortMacLimitEthNoS
                  INTEGER,
            priPortMacLimitS
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.4.2.1.1.1
priPortMacLimitPonS OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priPortMacLimitEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.2.1.1.2
priPortMacLimitOnuS OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priPortMacLimitEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.2.1.1.3
```

```
            priPortMacLimitEthNoS OBJECT-TYPE
                  SYNTAX INTEGER (1..255)
                  MAX-ACCESS read-write
                  STATUS current
                  DESCRIPTION
                        "Description."
                  ::= { priPortMacLimitEntry 3 }


            -- 1.3.6.1.4.1.37950.1.1.5.12.4.2.1.1.4
            priPortMacLimitS OBJECT-TYPE
                  SYNTAX INTEGER (0..65535)
                  MAX-ACCESS read-write
                  STATUS current
                  DESCRIPTION
                        "Description."
                  ::= { priPortMacLimitEntry 4 }


            -- 1.3.6.1.4.1.37950.1.1.5.12.4.2.2
            priPortPkgSuppressTable OBJECT-TYPE
                  SYNTAX SEQUENCE OF PriPortPkgSuppressEntry
                  MAX-ACCESS not-accessible
                  STATUS current
                  DESCRIPTION
                        "Description."
                  ::= { onuPriPortInfo 2 }


            -- 1.3.6.1.4.1.37950.1.1.5.12.4.2.2.1
            priPortPkgSuppressEntry OBJECT-TYPE
                  SYNTAX PriPortPkgSuppressEntry
                  MAX-ACCESS not-accessible
                  STATUS current
                  DESCRIPTION
                        "Description."
                  INDEX { priPortPkgSuppressPonS, priPortPkgSuppressOnuS,
priPortPkgSuppressEthNoS }
                  ::= { priPortPkgSuppressTable 1 }


            PriPortPkgSuppressEntry ::=
                  SEQUENCE {
                        priPortPkgSuppressPonS
                              INTEGER,
                        priPortPkgSuppressOnuS
                              INTEGER,
                        priPortPkgSuppressEthNoS
                              INTEGER,
                        priPortPkgSuppressBroadcastS
                              INTEGER,
                        priPortPkgSuppressMulticastS
                              INTEGER,
                        priPortPkgSuppressUnkownS
                              INTEGER
                       }

            -- 1.3.6.1.4.1.37950.1.1.5.12.4.2.2.1.1
            priPortPkgSuppressPonS OBJECT-TYPE
```

```
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priPortPkgSuppressEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.2.2.1.2
priPortPkgSuppressOnuS OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priPortPkgSuppressEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.2.2.1.3
priPortPkgSuppressEthNoS OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priPortPkgSuppressEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.2.2.1.4
priPortPkgSuppressBroadcastS OBJECT-TYPE
      SYNTAX INTEGER (0..1024000)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priPortPkgSuppressEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.2.2.1.5
priPortPkgSuppressMulticastS OBJECT-TYPE
      SYNTAX INTEGER (0..1024000)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priPortPkgSuppressEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.2.2.1.6
priPortPkgSuppressUnkownS OBJECT-TYPE
      SYNTAX INTEGER (0..1024000)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priPortPkgSuppressEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.2.3
```

```
            priPortModeControlTable OBJECT-TYPE
                  SYNTAX SEQUENCE OF PriPortModeControlEntry
                  MAX-ACCESS not-accessible
                  STATUS current
                  DESCRIPTION
                        "Description."
                  ::= { onuPriPortInfo 3 }


            -- 1.3.6.1.4.1.37950.1.1.5.12.4.2.3.1
            priPortModeControlEntry OBJECT-TYPE
                  SYNTAX PriPortModeControlEntry
                  MAX-ACCESS not-accessible
                  STATUS current
                  DESCRIPTION
                        "Description."
                  INDEX { priPortModeControlPonS, priPortModeControlOnuS,
priPortModeControlEthNoS }
                  ::= { priPortModeControlTable 1 }


            PriPortModeControlEntry ::=
                  SEQUENCE {
                        priPortModeControlPonS
                              INTEGER,
                        priPortModeControlOnuS
                              INTEGER,
                        priPortModeControlEthNoS
                              Integer32,
                        priPortModeControlS
                              INTEGER
                   }

            -- 1.3.6.1.4.1.37950.1.1.5.12.4.2.3.1.1
            priPortModeControlPonS OBJECT-TYPE
                  SYNTAX INTEGER (1..16)
                  MAX-ACCESS read-write
                  STATUS current
                  DESCRIPTION
                        "Description."
                  ::= { priPortModeControlEntry 1 }


            -- 1.3.6.1.4.1.37950.1.1.5.12.4.2.3.1.2
            priPortModeControlOnuS OBJECT-TYPE
                  SYNTAX INTEGER (1..65535)
                  MAX-ACCESS read-write
                  STATUS current
                  DESCRIPTION
                        "Description."
                  ::= { priPortModeControlEntry 2 }


            -- 1.3.6.1.4.1.37950.1.1.5.12.4.2.3.1.3
            priPortModeControlEthNoS OBJECT-TYPE
                  SYNTAX Integer32
                  MAX-ACCESS read-write
                  STATUS current
                  DESCRIPTION
```

```
                "Description."
        ::= { priPortModeControlEntry 3 }


    -- 1.3.6.1.4.1.37950.1.1.5.12.4.2.3.1.4
    priPortModeControlS OBJECT-TYPE
        SYNTAX INTEGER
                {
                s10hd(1),
                s10fd(2),
                s100hd(3),
                s100fd(4),
                s1000hd(5),
                s1000fd(6),
                s10000fd(7)
                }
        MAX-ACCESS read-write
        STATUS current
        DESCRIPTION
                "Description."
        ::= { priPortModeControlEntry 4 }


    -- 1.3.6.1.4.1.37950.1.1.5.12.4.2.4
    priPortModeStatusTable OBJECT-TYPE
        SYNTAX SEQUENCE OF PriPortModeStatusEntry
        MAX-ACCESS not-accessible
        STATUS current
        DESCRIPTION
                "Description."
        ::= { onuPriPortInfo 4 }


    -- 1.3.6.1.4.1.37950.1.1.5.12.4.2.4.1
    priPortModeStatusEntry OBJECT-TYPE
        SYNTAX PriPortModeStatusEntry
        MAX-ACCESS not-accessible
        STATUS current
        DESCRIPTION
                "Description."
        INDEX { priPortModeStatusPonS, priPortModeStatusOnuS,
priPortModeStatusEthNoS }
        ::= { priPortModeStatusTable 1 }


    PriPortModeStatusEntry ::=
        SEQUENCE {
                priPortModeStatusPonS
                        INTEGER,
                priPortModeStatusOnuS
                        INTEGER,
                priPortModeStatusEthNoS
                        Integer32,
                priPortModeStatusS
                        INTEGER
         }

    -- 1.3.6.1.4.1.37950.1.1.5.12.4.2.4.1.1
    priPortModeStatusPonS OBJECT-TYPE
```

```
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priPortModeStatusEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.2.4.1.2
priPortModeStatusOnuS OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priPortModeStatusEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.2.4.1.3
priPortModeStatusEthNoS OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priPortModeStatusEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.2.4.1.4
priPortModeStatusS OBJECT-TYPE
      SYNTAX INTEGER
            {
            s10hd(1),
            s10fd(2),
            s100hd(3),
            s100fd(4),
            s1000hd(5),
            s1000fd(6),
            s10000fd(7)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priPortModeStatusEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.2.5
priPotsParameterTable OBJECT-TYPE
      SYNTAX SEQUENCE OF PriPotsParameterEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPriPortInfo 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.2.5.1
priPotsParameterEntry OBJECT-TYPE
```

```
      SYNTAX PriPotsParameterEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { priPortPtPonS, priPortPtOnuS, priPortPtPotsNoS }
      ::= { priPotsParameterTable 1 }


PriPotsParameterEntry ::=
      SEQUENCE {
            priPortPtPonS
                  Integer32,
            priPortPtOnuS
                  Integer32,
            priPortPtPotsNoS
                  Integer32,
            priPortPtVarS
                  INTEGER,
            priPortPtEchoCancleS
                  INTEGER,
            priPotsPtInputGainS
                  Integer32,
            priPotsPtOutputGainS
                  Integer32,
            priPotsPtDtmfModeS
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.4.2.5.1.1
priPortPtPonS OBJECT-TYPE
      SYNTAX Integer32 (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priPotsParameterEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.2.5.1.2
priPortPtOnuS OBJECT-TYPE
      SYNTAX Integer32 (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priPotsParameterEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.2.5.1.3
priPortPtPotsNoS OBJECT-TYPE
      SYNTAX Integer32 (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priPotsParameterEntry 3 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.4.2.5.1.4
priPortPtVarS OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priPotsParameterEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.2.5.1.5
priPortPtEchoCancleS OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priPotsParameterEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.2.5.1.6
priPotsPtInputGainS OBJECT-TYPE
      SYNTAX Integer32 (-32..32)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priPotsParameterEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.2.5.1.7
priPotsPtOutputGainS OBJECT-TYPE
      SYNTAX Integer32 (-32..32)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { priPotsParameterEntry 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.4.2.5.1.8
priPotsPtDtmfModeS OBJECT-TYPE
      SYNTAX INTEGER
            {
            transparent(0),
            rfc2833(1),
            rfc2833_redundancy(2),
            outband(3)
            }
      MAX-ACCESS read-write
      STATUS current
```

```
      DESCRIPTION
            "Description."
      ::= { priPotsParameterEntry 8 }

-- 1.3.6.1.4.1.37950.1.1.5.12.5
onuPort OBJECT IDENTIFIER ::= { v1600dOnuMgmt 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1
onuPortInfo OBJECT IDENTIFIER ::= { onuPort 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.1
onuPortInfoCfg OBJECT IDENTIFIER ::= { onuPortInfo 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.1.1
infoPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortInfoCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.1.2
infoOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortInfoCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.1.3
infoPortNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortInfoCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.1.4
infoAction OBJECT-TYPE
      SYNTAX INTEGER { commit(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortInfoCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.2
onuPortInfoDisplay OBJECT IDENTIFIER ::= { onuPortInfo 2 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.2.1
displayPortNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortInfoDisplay 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.2.2
linkState OBJECT-TYPE
      SYNTAX INTEGER
            {
            down(0),
            up(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortInfoDisplay 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.2.3
flowControl OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortInfoDisplay 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.2.4
policyState OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortInfoDisplay 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.2.5
policyCir OBJECT-TYPE
      SYNTAX INTEGER (0..1048576)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
```

```
            "Description."
      ::= { onuPortInfoDisplay 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.2.6
policyCbs OBJECT-TYPE
      SYNTAX INTEGER (0..10240)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortInfoDisplay 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.2.7
policyEbs OBJECT-TYPE
      SYNTAX INTEGER (0..10240)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortInfoDisplay 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.2.8
rateLimitState OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortInfoDisplay 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.2.9
rateLimitCir OBJECT-TYPE
      SYNTAX INTEGER (0..1048576)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortInfoDisplay 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.2.10
rateLimitPir OBJECT-TYPE
      SYNTAX INTEGER (0..1048576)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortInfoDisplay 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.3
```

```
onuPortAdminTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuPortAdminEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortInfo 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.3.1
onuPortAdminEntry OBJECT-TYPE
      SYNTAX OnuPortAdminEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { onuPortAdminPonIndex, onuPortAdminOnuIndex,
onuPortAdminPortIndex }
      ::= { onuPortAdminTable 1 }


OnuPortAdminEntry ::=
      SEQUENCE {
            onuPortAdminPonIndex
                  Integer32,
            onuPortAdminOnuIndex
                  Integer32,
            onuPortAdminPortIndex
                  Integer32,
            onuPortAdminVal
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.3.1.1
onuPortAdminPonIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortAdminEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.3.1.2
onuPortAdminOnuIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortAdminEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.3.1.3
onuPortAdminPortIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
```

```
                "Description."
        ::= { onuPortAdminEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.3.1.4
onuPortAdminVal OBJECT-TYPE
        SYNTAX INTEGER
                {
                disable(0),
                enable(1)
                }
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
                "Description."
        ::= { onuPortAdminEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.4
onuPortAutoNegTable OBJECT-TYPE
        SYNTAX SEQUENCE OF OnuPortAutoNegEntry
        MAX-ACCESS not-accessible
        STATUS current
        DESCRIPTION
                "Description."
        ::= { onuPortInfo 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.4.1
onuPortAutoNegEntry OBJECT-TYPE
        SYNTAX OnuPortAutoNegEntry
        MAX-ACCESS not-accessible
        STATUS current
        DESCRIPTION
                "Description."
        INDEX { onuPortAutoNegPonIndex, onuPortAutoNegOnuIndex,
onuPortAutoNegPortIndex }
        ::= { onuPortAutoNegTable 1 }


OnuPortAutoNegEntry ::=
        SEQUENCE {
                onuPortAutoNegPonIndex
                        Integer32,
                onuPortAutoNegOnuIndex
                        Integer32,
                onuPortAutoNegPortIndex
                        Integer32,
                onuPortAutoNegVal
                        INTEGER
         }

-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.4.1.1
onuPortAutoNegPonIndex OBJECT-TYPE
        SYNTAX Integer32
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
                "Description."
```

```
            ::= { onuPortAutoNegEntry 1 }


        -- 1.3.6.1.4.1.37950.1.1.5.12.5.1.4.1.2
        onuPortAutoNegOnuIndex OBJECT-TYPE
            SYNTAX Integer32
            MAX-ACCESS read-only
            STATUS current
            DESCRIPTION
                "Description."
            ::= { onuPortAutoNegEntry 2 }


        -- 1.3.6.1.4.1.37950.1.1.5.12.5.1.4.1.3
        onuPortAutoNegPortIndex OBJECT-TYPE
            SYNTAX Integer32
            MAX-ACCESS read-only
            STATUS current
            DESCRIPTION
                "Description."
            ::= { onuPortAutoNegEntry 3 }


        -- 1.3.6.1.4.1.37950.1.1.5.12.5.1.4.1.4
        onuPortAutoNegVal OBJECT-TYPE
            SYNTAX INTEGER
                {
                disable(0),
                enable(1)
                }
            MAX-ACCESS read-only
            STATUS current
            DESCRIPTION
                "Description."
            ::= { onuPortAutoNegEntry 4 }


        -- 1.3.6.1.4.1.37950.1.1.5.12.5.1.5
        onuPortFcTable OBJECT-TYPE
            SYNTAX SEQUENCE OF OnuPortFcEntry
            MAX-ACCESS not-accessible
            STATUS current
            DESCRIPTION
                "Description."
            ::= { onuPortInfo 5 }


        -- 1.3.6.1.4.1.37950.1.1.5.12.5.1.5.1
        onuPortFcEntry OBJECT-TYPE
            SYNTAX OnuPortFcEntry
            MAX-ACCESS not-accessible
            STATUS current
            DESCRIPTION
                "Description."
            INDEX { onuPortFcPonIndex, onuPortFcOnuIndex,
onuPortFcPortIndex }
            ::= { onuPortFcTable 1 }
```

```
OnuPortFcEntry ::=
      SEQUENCE {
            onuPortFcPonIndex
                  Integer32,
            onuPortFcOnuIndex
                  Integer32,
            onuPortFcPortIndex
                  Integer32,
            onuPortFcVal
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.5.1.1
onuPortFcPonIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortFcEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.5.1.2
onuPortFcOnuIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortFcEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.5.1.3
onuPortFcPortIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortFcEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.5.1.4
onuPortFcVal OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortFcEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.6
portLoopdetectTable OBJECT-TYPE
      SYNTAX SEQUENCE OF PortLoopdetectEntry
```

```
                MAX-ACCESS not-accessible
                STATUS current
                DESCRIPTION
                      "Description."
                ::= { onuPortInfo 6 }


          -- 1.3.6.1.4.1.37950.1.1.5.12.5.1.6.1
          portLoopdetectEntry OBJECT-TYPE
                SYNTAX PortLoopdetectEntry
                MAX-ACCESS not-accessible
                STATUS current
                DESCRIPTION
                      "Description."
                INDEX { portLoopdetectPonIndex, portLoopdetectOnuIndex,
portLoopdetectPortIndex }
                ::= { portLoopdetectTable 1 }


          PortLoopdetectEntry ::=
                SEQUENCE {
                      portLoopdetectPonIndex
                            Integer32,
                      portLoopdetectOnuIndex
                            Integer32,
                      portLoopdetectPortIndex
                            Integer32,
                      portLoopdetectVal
                            INTEGER
                 }

          -- 1.3.6.1.4.1.37950.1.1.5.12.5.1.6.1.1
          portLoopdetectPonIndex OBJECT-TYPE
                SYNTAX Integer32
                MAX-ACCESS read-only
                STATUS current
                DESCRIPTION
                      "Description."
                ::= { portLoopdetectEntry 1 }


          -- 1.3.6.1.4.1.37950.1.1.5.12.5.1.6.1.2
          portLoopdetectOnuIndex OBJECT-TYPE
                SYNTAX Integer32
                MAX-ACCESS read-only
                STATUS current
                DESCRIPTION
                      "Description."
                ::= { portLoopdetectEntry 2 }


          -- 1.3.6.1.4.1.37950.1.1.5.12.5.1.6.1.3
          portLoopdetectPortIndex OBJECT-TYPE
                SYNTAX Integer32
                MAX-ACCESS read-only
                STATUS current
                DESCRIPTION
                      "Description."
                ::= { portLoopdetectEntry 3 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.6.1.4
portLoopdetectVal OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portLoopdetectEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.7
onuPortUpstreamLimitTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuPortUpstreamLimitEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortInfo 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.7.1
onuPortUpstreamLimitEntry OBJECT-TYPE
      SYNTAX OnuPortUpstreamLimitEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { onuPortUpstreamLimitPonIndex,
onuPortUpstreamLimitOnuIndex, onuPortUpstreamLimitPortIndex }
      ::= { onuPortUpstreamLimitTable 1 }


OnuPortUpstreamLimitEntry ::=
      SEQUENCE {
            onuPortUpstreamLimitPonIndex
                  Integer32,
            onuPortUpstreamLimitOnuIndex
                  Integer32,
            onuPortUpstreamLimitPortIndex
                  Integer32,
            onuPortUpstreamLimitCir
                  Integer32,
            onuPortUpstreamLimitCbs
                  Integer32,
            onuPortUpstreamLimitEbs
                  Integer32
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.7.1.1
onuPortUpstreamLimitPonIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
```

```
      DESCRIPTION
            "Description."
      ::= { onuPortUpstreamLimitEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.7.1.2
onuPortUpstreamLimitOnuIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortUpstreamLimitEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.7.1.3
onuPortUpstreamLimitPortIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortUpstreamLimitEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.7.1.4
onuPortUpstreamLimitCir OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortUpstreamLimitEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.7.1.5
onuPortUpstreamLimitCbs OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortUpstreamLimitEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.7.1.6
onuPortUpstreamLimitEbs OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortUpstreamLimitEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.8
onuPortDownstreamLimitTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuPortDownstreamLimitEntry
      MAX-ACCESS not-accessible
```

```
                STATUS current
                DESCRIPTION
                      "Description."
                ::= { onuPortInfo 8 }


          -- 1.3.6.1.4.1.37950.1.1.5.12.5.1.8.1
          onuPortDownstreamLimitEntry OBJECT-TYPE
                SYNTAX OnuPortDownstreamLimitEntry
                MAX-ACCESS not-accessible
                STATUS current
                DESCRIPTION
                      "Description."
                INDEX { onuPortDownstreamLimitPonIndex,
onuPortDownstreamLimitOnuIndex, onuPortDownstreamLimitPortIndex }
                ::= { onuPortDownstreamLimitTable 1 }


          OnuPortDownstreamLimitEntry ::=
                SEQUENCE {
                      onuPortDownstreamLimitPonIndex
                            Integer32,
                      onuPortDownstreamLimitOnuIndex
                            Integer32,
                      onuPortDownstreamLimitPortIndex
                            Integer32,
                      onuPortDownstreamLimitCir
                            Integer32,
                      onuPortDownstreamLimitPir
                            Integer32
                 }

          -- 1.3.6.1.4.1.37950.1.1.5.12.5.1.8.1.1
          onuPortDownstreamLimitPonIndex OBJECT-TYPE
                SYNTAX Integer32
                MAX-ACCESS read-only
                STATUS current
                DESCRIPTION
                      "Description."
                ::= { onuPortDownstreamLimitEntry 1 }


          -- 1.3.6.1.4.1.37950.1.1.5.12.5.1.8.1.2
          onuPortDownstreamLimitOnuIndex OBJECT-TYPE
                SYNTAX Integer32
                MAX-ACCESS read-only
                STATUS current
                DESCRIPTION
                      "Description."
                ::= { onuPortDownstreamLimitEntry 2 }


          -- 1.3.6.1.4.1.37950.1.1.5.12.5.1.8.1.3
          onuPortDownstreamLimitPortIndex OBJECT-TYPE
                SYNTAX Integer32
                MAX-ACCESS read-only
                STATUS current
                DESCRIPTION
                      "Description."
```

```
            ::= { onuPortDownstreamLimitEntry 3 }


      -- 1.3.6.1.4.1.37950.1.1.5.12.5.1.8.1.4
      onuPortDownstreamLimitCir OBJECT-TYPE
            SYNTAX Integer32
            MAX-ACCESS read-only
            STATUS current
            DESCRIPTION
                  "Description."
            ::= { onuPortDownstreamLimitEntry 4 }


      -- 1.3.6.1.4.1.37950.1.1.5.12.5.1.8.1.5
      onuPortDownstreamLimitPir OBJECT-TYPE
            SYNTAX Integer32
            MAX-ACCESS read-only
            STATUS current
            DESCRIPTION
                  "Description."
            ::= { onuPortDownstreamLimitEntry 5 }


      -- 1.3.6.1.4.1.37950.1.1.5.12.5.1.9
      onuPortLinkstateTable OBJECT-TYPE
            SYNTAX SEQUENCE OF OnuPortLinkstateEntry
            MAX-ACCESS not-accessible
            STATUS current
            DESCRIPTION
                  "Description."
            ::= { onuPortInfo 9 }


      -- 1.3.6.1.4.1.37950.1.1.5.12.5.1.9.1
      onuPortLinkstateEntry OBJECT-TYPE
            SYNTAX OnuPortLinkstateEntry
            MAX-ACCESS not-accessible
            STATUS current
            DESCRIPTION
                  "Description."
            INDEX { onuPortLinkstatePonIndex, onuPortLinkstateOnuIndex,
onuPortLinkstatePortIndex }
            ::= { onuPortLinkstateTable 1 }


      OnuPortLinkstateEntry ::=
            SEQUENCE {
                  onuPortLinkstatePonIndex
                        Integer32,
                  onuPortLinkstateOnuIndex
                        Integer32,
                  onuPortLinkstatePortIndex
                        Integer32,
                  onuPortLinkstateVal
                        INTEGER
             }

      -- 1.3.6.1.4.1.37950.1.1.5.12.5.1.9.1.1
      onuPortLinkstatePonIndex OBJECT-TYPE
```

```
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortLinkstateEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.9.1.2
onuPortLinkstateOnuIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortLinkstateEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.9.1.3
onuPortLinkstatePortIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortLinkstateEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.9.1.4
onuPortLinkstateVal OBJECT-TYPE
      SYNTAX INTEGER
            {
            down(0),
            up(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortLinkstateEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.10
onuVlanPortTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuVlanPortEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortInfo 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.10.1
onuVlanPortEntry OBJECT-TYPE
      SYNTAX OnuVlanPortEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
```

```
      INDEX { onuVlanPonIndex, onuVlanOnuIndex, onuVlanPortIndex }
      ::= { onuVlanPortTable 1 }


OnuVlanPortEntry ::=
      SEQUENCE {
            onuVlanPonIndex
                  Integer32,
            onuVlanOnuIndex
                  Integer32,
            onuVlanPortIndex
                  Integer32,
            onuVlanPortMode
                  INTEGER,
            onuVlanPortPvid
                  INTEGER,
            onuVlanPortVlan
                  OCTET STRING
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.10.1.1
onuVlanPonIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuVlanPortEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.10.1.2
onuVlanOnuIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuVlanPortEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.10.1.3
onuVlanPortIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuVlanPortEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.10.1.4
onuVlanPortMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            transparent(0),
            tag(1),
            translation(2),
            aggregation(3),
            trunk(4)
```

```
                }
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
                "Description."
        ::= { onuVlanPortEntry 4 }


    -- 1.3.6.1.4.1.37950.1.1.5.12.5.1.10.1.5
    onuVlanPortPvid OBJECT-TYPE
        SYNTAX INTEGER
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
                "Description."
        ::= { onuVlanPortEntry 5 }


    -- 1.3.6.1.4.1.37950.1.1.5.12.5.1.10.1.6
    onuVlanPortVlan OBJECT-TYPE
        SYNTAX OCTET STRING
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
                "Description."
        ::= { onuVlanPortEntry 6 }


    -- 1.3.6.1.4.1.37950.1.1.5.12.5.1.11
    onuPortStatEnTable OBJECT-TYPE
        SYNTAX SEQUENCE OF OnuPortStatEnEntry
        MAX-ACCESS not-accessible
        STATUS current
        DESCRIPTION
                "Description."
        ::= { onuPortInfo 11 }


    -- 1.3.6.1.4.1.37950.1.1.5.12.5.1.11.1
    onuPortStatEnEntry OBJECT-TYPE
        SYNTAX OnuPortStatEnEntry
        MAX-ACCESS not-accessible
        STATUS current
        DESCRIPTION
                "Description."
        INDEX { onuPortStatEnPonIndex, onuPortStatEnOnuIndex,
onuPortStatEnPortIndex }
        ::= { onuPortStatEnTable 1 }


    OnuPortStatEnEntry ::=
        SEQUENCE {
                onuPortStatEnPonIndex
                        Integer32,
                onuPortStatEnOnuIndex
                        Integer32,
                onuPortStatEnPortIndex
                        Integer32,
                onuPortStatEn
```

```
                INTEGER,
            onuPortStatEnPeriod
                INTEGER
        }

-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.11.1.1
onuPortStatEnPonIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatEnEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.11.1.2
onuPortStatEnOnuIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatEnEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.11.1.3
onuPortStatEnPortIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatEnEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.11.1.4
onuPortStatEn OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatEnEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.11.1.5
onuPortStatEnPeriod OBJECT-TYPE
      SYNTAX INTEGER
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatEnEntry 5 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.12
onuPortStatTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuPortStatEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortInfo 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.12.1
onuPortStatEntry OBJECT-TYPE
      SYNTAX OnuPortStatEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { onuPortStatPonIndex, onuPortStatOnuIndex,
onuPortStatPortIndex }
      ::= { onuPortStatTable 1 }


OnuPortStatEntry ::=
      SEQUENCE {
            onuPortStatPonIndex
                  Integer32,
            onuPortStatOnuIndex
                  Integer32,
            onuPortStatPortIndex
                  Integer32,
            statDnDropEvents
                  Counter32,
            statUpDropEvents
                  Counter32,
            statDnOctets
                  Counter32,
            statUpOctets
                  Counter32,
            statDnFrames
                  Counter32,
            statUpFrames
                  Counter32,
            statDnBcFrames
                  Counter32,
            statUpBcFrames
                  Counter32,
            statDnMcFrames
                  Counter32,
            statUpMcFrames
                  Counter32,
            statDnCrcErrFrames
                  Counter32,
            statUpCrcErrFrames
                  Counter32,
            statDnUndersizeFrames
                  Counter32,
            statUpUndersizeFrames
                  Counter32,
            statDnOversizeFrames
```

```
                Counter32,
            statUpOversizeFrames
                Counter32,
            statDnFragments
                Counter32,
            statUpFragments
                Counter32,
            statDnJabbers
                Counter32,
            statUpJabbers
                Counter32,
            statDn64OctetsFrames
                Counter32,
            statDn65to127OctetsFrames
                Counter32,
            statDn128to255OctetsFrames
                Counter32,
            statDn256to511OctetsFrames
                Counter32,
            statDn512to1023OctetsFrames
                Counter32,
            statDn1024to1518OctetsFrames
                Counter32,
            statUp64OctetsFrames
                Counter32,
            statUp65to127OctetsFrames
                Counter32,
            statUp128to255OctetsFrames
                Counter32,
            statUp256to511OctetsFrames
                Counter32,
            statUp512to1023OctetsFrames
                Counter32,
            statUp1024to1518OctetsFrames
                Counter32,
            statDnDiscardFrames
                Counter32,
            statUpDiscardFrames
                Counter32,
            statDnErrFrames
                Counter32,
            statUpErrFrames
                Counter32,
            statStatusChangeTimes
                Counter32
        }

-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.12.1.1
onuPortStatPonIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.12.1.2
onuPortStatOnuIndex OBJECT-TYPE
```

```
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.12.1.3
onuPortStatPortIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.12.1.4
statDnDropEvents OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.12.1.5
statUpDropEvents OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.12.1.6
statDnOctets OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.12.1.7
statUpOctets OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatEntry 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.12.1.8
```

```
statDnFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatEntry 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.12.1.9
statUpFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatEntry 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.12.1.10
statDnBcFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatEntry 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.12.1.11
statUpBcFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatEntry 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.12.1.12
statDnMcFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatEntry 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.12.1.13
statUpMcFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatEntry 13 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.12.1.14
statDnCrcErrFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatEntry 14 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.12.1.15
statUpCrcErrFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatEntry 15 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.12.1.16
statDnUndersizeFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatEntry 16 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.12.1.17
statUpUndersizeFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatEntry 17 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.12.1.18
statDnOversizeFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatEntry 18 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.12.1.19
statUpOversizeFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatEntry 19 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.12.1.20
statDnFragments OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatEntry 20 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.12.1.21
statUpFragments OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatEntry 21 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.12.1.22
statDnJabbers OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatEntry 22 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.12.1.23
statUpJabbers OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatEntry 23 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.12.1.24
statDn64OctetsFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatEntry 24 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.12.1.25
statDn65to127OctetsFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatEntry 25 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.12.1.26
statDn128to255OctetsFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatEntry 26 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.12.1.27
statDn256to511OctetsFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatEntry 27 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.12.1.28
statDn512to1023OctetsFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatEntry 28 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.12.1.29
statDn1024to1518OctetsFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatEntry 29 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.12.1.30
statUp64OctetsFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatEntry 30 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.12.1.31
statUp65to127OctetsFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { onuPortStatEntry 31 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.12.1.32
statUp128to255OctetsFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatEntry 32 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.12.1.33
statUp256to511OctetsFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatEntry 33 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.12.1.34
statUp512to1023OctetsFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatEntry 34 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.12.1.35
statUp1024to1518OctetsFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatEntry 35 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.12.1.36
statDnDiscardFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatEntry 36 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.12.1.37
statUpDiscardFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
```

```
                "Description."
        ::= { onuPortStatEntry 37 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.12.1.38
statDnErrFrames OBJECT-TYPE
        SYNTAX Counter32
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
                "Description."
        ::= { onuPortStatEntry 38 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.12.1.39
statUpErrFrames OBJECT-TYPE
        SYNTAX Counter32
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
                "Description."
        ::= { onuPortStatEntry 39 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.12.1.40
statStatusChangeTimes OBJECT-TYPE
        SYNTAX Counter32
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
                "Description."
        ::= { onuPortStatEntry 40 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.13
onuPortBasicTable OBJECT-TYPE
        SYNTAX SEQUENCE OF OnuPortBasicEntry
        MAX-ACCESS not-accessible
        STATUS current
        DESCRIPTION
                "Description."
        ::= { onuPortInfo 13 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.13.1
onuPortBasicEntry OBJECT-TYPE
        SYNTAX OnuPortBasicEntry
        MAX-ACCESS not-accessible
        STATUS current
        DESCRIPTION
                "Description."
        INDEX { onuPortBasicPonIndex, onuPortBasicOnuIndex,
onuPortBasicPortIndex }
        ::= { onuPortBasicTable 1 }


OnuPortBasicEntry ::=
        SEQUENCE {
                onuPortBasicPonIndex
```

```
                Integer32,
            onuPortBasicOnuIndex
                Integer32,
            onuPortBasicPortIndex
                Integer32,
            onuPortBasicLinkStatus
                INTEGER,
            onuPortBasicAdminStatus
                INTEGER,
            onuPortBasicAutoNgt
                INTEGER,
            onuPortBasicFlowCtl
                INTEGER,
            onuPortBasicLoopback
                INTEGER,
            onuPortBasicPolicyState
                INTEGER,
            onuPortBasicPolicyCir
                Integer32,
            onuPortBasicPolicyCbs
                Integer32,
            onuPortBasicPolicyEbs
                Integer32,
            onuPortBasicRateState
                INTEGER,
            onuPortBasicRateCir
                Integer32,
            onuPortBasicRatePir
                Integer32
        }

-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.13.1.1
onuPortBasicPonIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortBasicEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.13.1.2
onuPortBasicOnuIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortBasicEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.13.1.3
onuPortBasicPortIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortBasicEntry 3 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.13.1.4
onuPortBasicLinkStatus OBJECT-TYPE
      SYNTAX INTEGER
            {
            down(0),
            up(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortBasicEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.13.1.5
onuPortBasicAdminStatus OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortBasicEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.13.1.6
onuPortBasicAutoNgt OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortBasicEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.13.1.7
onuPortBasicFlowCtl OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortBasicEntry 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.13.1.8
```

```
onuPortBasicLoopback OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortBasicEntry 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.13.1.9
onuPortBasicPolicyState OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortBasicEntry 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.13.1.10
onuPortBasicPolicyCir OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortBasicEntry 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.13.1.11
onuPortBasicPolicyCbs OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortBasicEntry 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.13.1.12
onuPortBasicPolicyEbs OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortBasicEntry 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.13.1.13
onuPortBasicRateState OBJECT-TYPE
```

```
            SYNTAX INTEGER
                  {
                  disable(0),
                  enable(1)
                  }
            MAX-ACCESS read-only
            STATUS current
            DESCRIPTION
                  "Description."
            ::= { onuPortBasicEntry 13 }


      -- 1.3.6.1.4.1.37950.1.1.5.12.5.1.13.1.14
      onuPortBasicRateCir OBJECT-TYPE
            SYNTAX Integer32
            MAX-ACCESS read-only
            STATUS current
            DESCRIPTION
                  "Description."
            ::= { onuPortBasicEntry 14 }


      -- 1.3.6.1.4.1.37950.1.1.5.12.5.1.13.1.15
      onuPortBasicRatePir OBJECT-TYPE
            SYNTAX Integer32
            MAX-ACCESS read-only
            STATUS current
            DESCRIPTION
                  "Description."
            ::= { onuPortBasicEntry 15 }


      -- 1.3.6.1.4.1.37950.1.1.5.12.5.1.14
      onuPortDisLoopTable OBJECT-TYPE
            SYNTAX SEQUENCE OF OnuPortDisLoopEntry
            MAX-ACCESS not-accessible
            STATUS current
            DESCRIPTION
                  "Description."
            ::= { onuPortInfo 14 }


      -- 1.3.6.1.4.1.37950.1.1.5.12.5.1.14.1
      onuPortDisLoopEntry OBJECT-TYPE
            SYNTAX OnuPortDisLoopEntry
            MAX-ACCESS not-accessible
            STATUS current
            DESCRIPTION
                  "Description."
            INDEX { onuPortDisLoopPon, onuPortDisLoopOnu,
onuPortDisLoopPort }
            ::= { onuPortDisLoopTable 1 }


      OnuPortDisLoopEntry ::=
            SEQUENCE {
                  onuPortDisLoopPon
                        INTEGER,
                  onuPortDisLoopOnu
```

```
                  INTEGER,
            onuPortDisLoopPort
                  Integer32,
            onuPortDisLoopEn
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.14.1.1
onuPortDisLoopPon OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortDisLoopEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.14.1.2
onuPortDisLoopOnu OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortDisLoopEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.14.1.3
onuPortDisLoopPort OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortDisLoopEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.1.14.1.4
onuPortDisLoopEn OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortDisLoopEntry 4 }

-- 1.3.6.1.4.1.37950.1.1.5.12.5.2
onuPortCfg OBJECT IDENTIFIER ::= { onuPort 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.1
onuPortAdminCfg OBJECT IDENTIFIER ::= { onuPortCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.1.1
```

```
portAdminPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortAdminCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.1.2
portAdminOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortAdminCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.1.3
portAdminPortNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortAdminCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.1.4
portAdmin OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortAdminCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.2
onuPortAutoNegCfg OBJECT IDENTIFIER ::= { onuPortCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.2.1
autoNegPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortAutoNegCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.2.2
autoNegOnuNo OBJECT-TYPE
```

```
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortAutoNegCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.2.3
autoNegPortNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortAutoNegCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.2.4
portAutoNeg OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortAutoNegCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.3
onuPortAutoNegRstCfg OBJECT IDENTIFIER ::= { onuPortCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.3.1
autoNegRstPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortAutoNegRstCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.3.2
autoNegRstOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortAutoNegRstCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.3.3
autoNegRstPortNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
```

```
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortAutoNegRstCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.3.4
portAutoNegRestart OBJECT-TYPE
      SYNTAX INTEGER { enable(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortAutoNegRstCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.4
onuPortFcCfg OBJECT IDENTIFIER ::= { onuPortCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.4.1
fcPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortFcCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.4.2
fcOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortFcCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.4.3
fcPortNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortFcCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.4.4
portFlowControl OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
```

```
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortFcCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.5
portLoopdetectCfg OBJECT IDENTIFIER ::= { onuPortCfg 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.5.1
loopPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portLoopdetectCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.5.2
loopOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portLoopdetectCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.5.3
loopPortNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portLoopdetectCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.5.4
portLoopdetect OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portLoopdetectCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.6
portDisLoopCfg OBJECT IDENTIFIER ::= { onuPortCfg 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.6.1
```

```
disLoopPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portDisLoopCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.6.2
disLoopOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portDisLoopCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.6.3
disLoopPortNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portDisLoopCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.6.4
portDisableLoopEn OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portDisLoopCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.8
onuPortUpstreamLimit OBJECT IDENTIFIER ::= { onuPortCfg 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.8.1
upLimitPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortUpstreamLimit 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.8.2
upLimitOnuNo OBJECT-TYPE
```

```
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortUpstreamLimit 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.8.3
upLimitPortNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortUpstreamLimit 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.8.4
upLimitCir OBJECT-TYPE
      SYNTAX INTEGER (0..1048576)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortUpstreamLimit 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.8.5
upLimitCbs OBJECT-TYPE
      SYNTAX INTEGER (0..10240)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortUpstreamLimit 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.8.6
upLimitEbs OBJECT-TYPE
      SYNTAX INTEGER (0..10240)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortUpstreamLimit 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.8.7
upLimitAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            delete(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { onuPortUpstreamLimit 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.9
onuPortDownstreamLimit OBJECT IDENTIFIER ::= { onuPortCfg 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.9.1
downLimitPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortDownstreamLimit 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.9.2
downLimitOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortDownstreamLimit 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.9.3
downLimitPortNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortDownstreamLimit 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.9.4
downLimitCir OBJECT-TYPE
      SYNTAX INTEGER (0..1048576)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortDownstreamLimit 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.9.5
downLimitPir OBJECT-TYPE
      SYNTAX INTEGER (0..1048576)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortDownstreamLimit 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.9.6
downLimitAction OBJECT-TYPE
```

```
      SYNTAX INTEGER
            {
            add(1),
            delete(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortDownstreamLimit 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10
onuPortVlan OBJECT IDENTIFIER ::= { onuPortCfg 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.1
onuPortVlanMode OBJECT IDENTIFIER ::= { onuPortVlan 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.1.1
vlanModePonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortVlanMode 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.1.2
vlanModeOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortVlanMode 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.1.3
vlanModePortNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortVlanMode 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.1.4
vlanMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            transparent(1),
            tag(2),
            translation(3),
            aggregation(4),
            trunk(5)
```

```
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortVlanMode 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.2
onuPortVlanPvid OBJECT IDENTIFIER ::= { onuPortVlan 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.2.1
portPvidPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortVlanPvid 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.2.2
portPvidOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortVlanPvid 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.2.3
portPvidPortNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortVlanPvid 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.2.4
portPvidValue OBJECT-TYPE
      SYNTAX INTEGER (1..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortVlanPvid 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.2.5
portPriValue OBJECT-TYPE
      SYNTAX INTEGER (0..7)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { onuPortVlanPvid 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.2.6
pvidAction OBJECT-TYPE
      SYNTAX INTEGER { commit(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortVlanPvid 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.3
onuPortVlanTranslate OBJECT IDENTIFIER ::= { onuPortVlan 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.3.1
translatePonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortVlanTranslate 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.3.2
translateOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortVlanTranslate 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.3.3
translatePortNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortVlanTranslate 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.3.4
translateOldVlan OBJECT-TYPE
      SYNTAX INTEGER (1..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortVlanTranslate 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.3.5
translateNewVlan OBJECT-TYPE
```

```
      SYNTAX INTEGER (1..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortVlanTranslate 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.3.6
translateAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            set(1),
            add(2),
            delete(3)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortVlanTranslate 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.4
onuPortVlanTransTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuPortVlanTransEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortVlan 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.4.1
onuPortVlanTransEntry OBJECT-TYPE
      SYNTAX OnuPortVlanTransEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { vlanTransItem }
      ::= { onuPortVlanTransTable 1 }


OnuPortVlanTransEntry ::=
      SEQUENCE {
            vlanTransItem
                  Integer32,
            vlanTransPonNo
                  INTEGER,
            vlanTransOnuNo
                  INTEGER,
            vlanTransPortNo
                  INTEGER,
            vlanTransOldVlan
                  INTEGER,
            vlanTransNewVlan
                  INTEGER
       }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.4.1.1
vlanTransItem OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortVlanTransEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.4.1.2
vlanTransPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortVlanTransEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.4.1.3
vlanTransOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortVlanTransEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.4.1.4
vlanTransPortNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortVlanTransEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.4.1.5
vlanTransOldVlan OBJECT-TYPE
      SYNTAX INTEGER (1..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortVlanTransEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.4.1.6
vlanTransNewVlan OBJECT-TYPE
      SYNTAX INTEGER (1..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortVlanTransEntry 6 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.5
onuPortVlanTrunk OBJECT IDENTIFIER ::= { onuPortVlan 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.5.1
trunkPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortVlanTrunk 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.5.2
trunkOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortVlanTrunk 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.5.3
trunkPortNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortVlanTrunk 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.5.4
trunkPortVid OBJECT-TYPE
      SYNTAX INTEGER (1..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortVlanTrunk 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.5.5
trunkPortVidAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            set(1),
            add(2),
            delete(3)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortVlanTrunk 5 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.6
onuPortVlanTrunkTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuPortVlanTrunkEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortVlan 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.6.1
onuPortVlanTrunkEntry OBJECT-TYPE
      SYNTAX OnuPortVlanTrunkEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { vlanTrunkItem }
      ::= { onuPortVlanTrunkTable 1 }


OnuPortVlanTrunkEntry ::=
      SEQUENCE {
            vlanTrunkItem
                  Integer32,
            vlanTrunkPonNo
                  INTEGER,
            vlanTrunkOnuNo
                  INTEGER,
            vlanTrunkPortNo
                  INTEGER,
            vlanTrunkVid
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.6.1.1
vlanTrunkItem OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortVlanTrunkEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.6.1.2
vlanTrunkPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortVlanTrunkEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.6.1.3
vlanTrunkOnuNo OBJECT-TYPE
```

```
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortVlanTrunkEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.6.1.4
vlanTrunkPortNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortVlanTrunkEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.6.1.5
vlanTrunkVid OBJECT-TYPE
      SYNTAX INTEGER (1..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortVlanTrunkEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.7
onuPortVlanAgg OBJECT IDENTIFIER ::= { onuPortVlan 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.7.1
onuVlanAggPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortVlanAgg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.7.2
onuVlanAggOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortVlanAgg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.7.3
onuVlanAggPortNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { onuPortVlanAgg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.7.4
onuAggNewVlan OBJECT-TYPE
      SYNTAX INTEGER (1..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortVlanAgg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.7.5
onuAggOldVlan1 OBJECT-TYPE
      SYNTAX INTEGER (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortVlanAgg 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.7.6
onuAggOldVlan2 OBJECT-TYPE
      SYNTAX INTEGER (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortVlanAgg 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.7.7
onuAggOldVlan3 OBJECT-TYPE
      SYNTAX INTEGER (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortVlanAgg 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.7.8
onuAggOldVlan4 OBJECT-TYPE
      SYNTAX INTEGER (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortVlanAgg 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.7.9
onuAggOldVlan5 OBJECT-TYPE
      SYNTAX INTEGER (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
```

```
            "Description."
      ::= { onuPortVlanAgg 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.7.10
onuAggOldVlan6 OBJECT-TYPE
      SYNTAX INTEGER (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortVlanAgg 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.7.11
onuAggOldVlan7 OBJECT-TYPE
      SYNTAX INTEGER (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortVlanAgg 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.7.12
onuAggOldVlan8 OBJECT-TYPE
      SYNTAX INTEGER (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortVlanAgg 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.10.7.13
onuAggAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            set(1),
            add(2),
            del(3)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortVlanAgg 13 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.11
onuPortClassifyCfg OBJECT IDENTIFIER ::= { onuPortCfg 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.11.1
classPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
```

```
            "Description."
      ::= { onuPortClassifyCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.11.2
classOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.11.3
classPortNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.11.4
classPrecedence OBJECT-TYPE
      SYNTAX INTEGER (1..8)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.11.5
classPri OBJECT-TYPE
      SYNTAX INTEGER (0..7)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyCfg 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.11.6
dstMacEqualSel OBJECT-TYPE
      SYNTAX INTEGER
            {
            invalid(0),
            equal(1),
            unequal(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyCfg 6 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.11.7
dstMacValue OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyCfg 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.11.8
srcMacEqualSel OBJECT-TYPE
      SYNTAX INTEGER
            {
            invalid(0),
            equal(1),
            unequal(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyCfg 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.11.9
srcMacValue OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyCfg 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.11.10
vlanEqualSel OBJECT-TYPE
      SYNTAX INTEGER
            {
            invalid(0),
            equal(1),
            unequal(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyCfg 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.11.11
vlanValue OBJECT-TYPE
      SYNTAX INTEGER (1..4094)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyCfg 11 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.11.12
cosEqualSel OBJECT-TYPE
      SYNTAX INTEGER
            {
            invalid(0),
            equal(1),
            unequal(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyCfg 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.11.13
cosValue OBJECT-TYPE
      SYNTAX INTEGER (0..7)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyCfg 13 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.11.14
ethTypeEqualSel OBJECT-TYPE
      SYNTAX INTEGER
            {
            invalid(0),
            equal(1),
            unequal(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyCfg 14 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.11.15
ethTypeValue OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyCfg 15 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.11.16
srcIpEqualSel OBJECT-TYPE
      SYNTAX INTEGER
            {
            invalid(0),
            equal(1),
            unequal(2)
            }
```

```
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyCfg 16 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.11.17
srcIpValue OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyCfg 17 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.11.18
destIpEqualSel OBJECT-TYPE
      SYNTAX INTEGER
            {
            invalid(0),
            equal(1),
            unequal(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyCfg 18 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.11.19
destIpValue OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyCfg 19 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.11.20
protocolEqualSel OBJECT-TYPE
      SYNTAX INTEGER
            {
            invalid(0),
            equal(1),
            unequal(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyCfg 20 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.11.21
protocolValue OBJECT-TYPE
```

```
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyCfg 21 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.11.22
tosDscpEuqalSel OBJECT-TYPE
      SYNTAX INTEGER
            {
            invalid(0),
            equal(1),
            unequal(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyCfg 22 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.11.23
tosDscpValue OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyCfg 23 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.11.24
srcPortEqualSel OBJECT-TYPE
      SYNTAX INTEGER
            {
            invalid(0),
            equal(1),
            unequal(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyCfg 24 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.11.25
srcPortValue OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyCfg 25 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.11.26
```

```
destPortEqualSel OBJECT-TYPE
      SYNTAX INTEGER
            {
            invalid(0),
            equal(1),
            unequal(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyCfg 26 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.11.27
destPortValue OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyCfg 27 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.11.28
classAction OBJECT-TYPE
      SYNTAX INTEGER { add(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyCfg 28 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.11.29
classQueue OBJECT-TYPE
      SYNTAX Integer32 (0..7)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyCfg 29 }

-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.12
onuPortClassifyDel OBJECT IDENTIFIER ::= { onuPortCfg 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.12.1
classDelPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyDel 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.12.2
classDelOnuNo OBJECT-TYPE
```

```
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyDel 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.12.3
classDelPortNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyDel 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.12.4
classDelPrecedence OBJECT-TYPE
      SYNTAX INTEGER (1..8)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyDel 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.12.5
classDelAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            delete(1),
            cleanAll(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyDel 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.13
onuPortClassifyTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuPortClassifyEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortCfg 13 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.13.1
onuPortClassifyEntry OBJECT-TYPE
      SYNTAX OnuPortClassifyEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
```

```
        INDEX { classifyItem }
        ::= { onuPortClassifyTable 1 }


OnuPortClassifyEntry ::=
        SEQUENCE {
                classifyItem
                        Integer32,
                classifyPonNo
                        INTEGER,
                classifyOnuNo
                        INTEGER,
                classifyPortNo
                        INTEGER,
                classifyPrecedence
                        INTEGER,
                classifyPri
                        INTEGER,
                dstMacEqual
                        INTEGER,
                dstMacVal
                        OCTET STRING,
                srcMacEqual
                        INTEGER,
                srcMacVal
                        OCTET STRING,
                vlanEqual
                        INTEGER,
                vlanVal
                        INTEGER,
                cosEqual
                        INTEGER,
                cosVal
                        INTEGER,
                ethTypeEqual
                        INTEGER,
                ethTypeVal
                        OCTET STRING,
                srcIpEqual
                        INTEGER,
                srcIpVal
                        IpAddress,
                destIpEqual
                        INTEGER,
                destIpVal
                        IpAddress,
                protocolEqual
                        INTEGER,
                protocolVal
                        INTEGER,
                tosDscpEuqal
                        INTEGER,
                tosDscpVal
                        INTEGER,
                srcPortEqual
                        INTEGER,
                srcPortVal
                        INTEGER,
                destPortEqual
```

```
                  INTEGER,
            destPortVal
                  INTEGER,
            classifyQueue
                  Integer32
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.13.1.1
classifyItem OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.13.1.2
classifyPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.13.1.3
classifyOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.13.1.4
classifyPortNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.13.1.5
classifyPrecedence OBJECT-TYPE
      SYNTAX INTEGER (1..8)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.13.1.6
classifyPri OBJECT-TYPE
```

```
      SYNTAX INTEGER (0..7)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.13.1.7
dstMacEqual OBJECT-TYPE
      SYNTAX INTEGER
            {
            invalid(0),
            equal(1),
            unequal(2)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyEntry 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.13.1.8
dstMacVal OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyEntry 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.13.1.9
srcMacEqual OBJECT-TYPE
      SYNTAX INTEGER
            {
            invalid(0),
            equal(1),
            unequal(2)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyEntry 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.13.1.10
srcMacVal OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyEntry 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.13.1.11
```

```
vlanEqual OBJECT-TYPE
      SYNTAX INTEGER
            {
            invalid(0),
            equal(1),
            unequal(2)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyEntry 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.13.1.12
vlanVal OBJECT-TYPE
      SYNTAX INTEGER (0..4094)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyEntry 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.13.1.13
cosEqual OBJECT-TYPE
      SYNTAX INTEGER
            {
            invalid(0),
            equal(1),
            unequal(2)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyEntry 13 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.13.1.14
cosVal OBJECT-TYPE
      SYNTAX INTEGER (-1..7)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyEntry 14 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.13.1.15
ethTypeEqual OBJECT-TYPE
      SYNTAX INTEGER
            {
            invalid(0),
            equal(1),
            unequal(2)
            }
      MAX-ACCESS read-only
      STATUS current
```

```
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyEntry 15 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.13.1.16
ethTypeVal OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyEntry 16 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.13.1.17
srcIpEqual OBJECT-TYPE
      SYNTAX INTEGER
            {
            invalid(0),
            equal(1),
            unequal(2)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyEntry 17 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.13.1.18
srcIpVal OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyEntry 18 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.13.1.19
destIpEqual OBJECT-TYPE
      SYNTAX INTEGER
            {
            invalid(0),
            equal(1),
            unequal(2)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyEntry 19 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.13.1.20
destIpVal OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
```

```
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyEntry 20 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.13.1.21
protocolEqual OBJECT-TYPE
      SYNTAX INTEGER
            {
            invalid(0),
            equal(1),
            unequal(2)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyEntry 21 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.13.1.22
protocolVal OBJECT-TYPE
      SYNTAX INTEGER (-1..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyEntry 22 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.13.1.23
tosDscpEuqal OBJECT-TYPE
      SYNTAX INTEGER
            {
            invalid(0),
            equal(1),
            unequal(2)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyEntry 23 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.13.1.24
tosDscpVal OBJECT-TYPE
      SYNTAX INTEGER (-1..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyEntry 24 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.13.1.25
srcPortEqual OBJECT-TYPE
      SYNTAX INTEGER
```

```
            {
            invalid(0),
            equal(1),
            unequal(2)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyEntry 25 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.13.1.26
srcPortVal OBJECT-TYPE
      SYNTAX INTEGER (-1..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyEntry 26 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.13.1.27
destPortEqual OBJECT-TYPE
      SYNTAX INTEGER
            {
            invalid(0),
            equal(1),
            unequal(2)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyEntry 27 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.13.1.28
destPortVal OBJECT-TYPE
      SYNTAX INTEGER (-1..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyEntry 28 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.13.1.29
classifyQueue OBJECT-TYPE
      SYNTAX Integer32 (0..7)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortClassifyEntry 29 }

-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14
onuPortIgmpCfg OBJECT IDENTIFIER ::= { onuPortCfg 14 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14.1
mcVlanCfg OBJECT IDENTIFIER ::= { onuPortIgmpCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14.1.1
mcVlanPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { mcVlanCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14.1.2
mcVlanOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { mcVlanCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14.1.3
mcVlanPortNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { mcVlanCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14.1.4
mcVlanVal OBJECT-TYPE
      SYNTAX INTEGER (1..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { mcVlanCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14.1.5
mcVlanAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            delete(2),
            clear(3)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { mcVlanCfg 5 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14.2
mcVlanTable OBJECT-TYPE
      SYNTAX SEQUENCE OF McVlanEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortIgmpCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14.2.1
mcVlanEntry OBJECT-TYPE
      SYNTAX McVlanEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { mVlanItem }
      ::= { mcVlanTable 1 }


McVlanEntry ::=
      SEQUENCE {
            mVlanItem
                  Integer32,
            mVlanPonNo
                  INTEGER,
            mVlanOnuNo
                  INTEGER,
            mVlanPortNo
                  INTEGER,
            mVlanVal
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14.2.1.1
mVlanItem OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { mcVlanEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14.2.1.2
mVlanPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { mcVlanEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14.2.1.3
mVlanOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
```

```
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { mcVlanEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14.2.1.4
mVlanPortNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { mcVlanEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14.2.1.5
mVlanVal OBJECT-TYPE
      SYNTAX INTEGER (1..4095)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { mcVlanEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14.3
mcMaxGroupCfg OBJECT IDENTIFIER ::= { onuPortIgmpCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14.3.1
maxgrpPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { mcMaxGroupCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14.3.2
maxgrpOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { mcMaxGroupCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14.3.3
maxgrpPortNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { mcMaxGroupCfg 3 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14.3.4
maxgrpVal OBJECT-TYPE
      SYNTAX INTEGER (0..4096)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { mcMaxGroupCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14.4
mcTagstrip OBJECT IDENTIFIER ::= { onuPortIgmpCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14.4.1
tagstripPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { mcTagstrip 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14.4.2
tagstripOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { mcTagstrip 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14.4.3
tagstripPortNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { mcTagstrip 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14.4.4
tagstripGroupVlan0 OBJECT-TYPE
      SYNTAX Integer32 (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { mcTagstrip 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14.4.5
tagstripUserVlan0 OBJECT-TYPE
      SYNTAX Integer32 (0..4095)
```

```
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { mcTagstrip 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14.4.6
tagstripGroupVlan1 OBJECT-TYPE
      SYNTAX Integer32 (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { mcTagstrip 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14.4.7
tagstripUserVlan1 OBJECT-TYPE
      SYNTAX Integer32 (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { mcTagstrip 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14.4.8
tagstripGroupVlan2 OBJECT-TYPE
      SYNTAX Integer32 (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { mcTagstrip 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14.4.9
tagstripUserVlan2 OBJECT-TYPE
      SYNTAX Integer32 (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { mcTagstrip 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14.4.10
tagstripGroupVlan3 OBJECT-TYPE
      SYNTAX Integer32 (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { mcTagstrip 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14.4.11
tagstripUserVlan3 OBJECT-TYPE
```

```
      SYNTAX Integer32 (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { mcTagstrip 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14.4.12
tagstripGroupVlan4 OBJECT-TYPE
      SYNTAX Integer32 (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { mcTagstrip 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14.4.13
tagstripUserVlan4 OBJECT-TYPE
      SYNTAX Integer32 (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { mcTagstrip 13 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14.4.14
tagstripGroupVlan5 OBJECT-TYPE
      SYNTAX Integer32 (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { mcTagstrip 14 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14.4.15
tagstripUserVlan5 OBJECT-TYPE
      SYNTAX Integer32 (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { mcTagstrip 15 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14.4.16
tagstripGroupVlan6 OBJECT-TYPE
      SYNTAX Integer32 (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { mcTagstrip 16 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14.4.17
```

```
tagstripUserVlan6 OBJECT-TYPE
      SYNTAX Integer32 (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { mcTagstrip 17 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14.4.18
tagstripGroupVlan7 OBJECT-TYPE
      SYNTAX Integer32 (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { mcTagstrip 18 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14.4.19
tagstripUserVlan7 OBJECT-TYPE
      SYNTAX Integer32 (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { mcTagstrip 19 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14.4.20
tagstripMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1),
            tagStrip(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { mcTagstrip 20 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14.5
mcVlanTagStripTable OBJECT-TYPE
      SYNTAX SEQUENCE OF McVlanTagStripEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortIgmpCfg 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14.5.1
mcVlanTagStripEntry OBJECT-TYPE
      SYNTAX McVlanTagStripEntry
      MAX-ACCESS not-accessible
      STATUS current
```

```
      DESCRIPTION
            "Description."
      INDEX { mVlanTagsPonNo, mVlanTagsOnuNo, mVlanTagsPortNo }
      ::= { mcVlanTagStripTable 1 }


McVlanTagStripEntry ::=
      SEQUENCE {
            mVlanTagsPonNo
                  INTEGER,
            mVlanTagsOnuNo
                  INTEGER,
            mVlanTagsPortNo
                  INTEGER,
            mVlanTagsMode
                  INTEGER,
            mVlanTagsVlanTrans
                  OCTET STRING
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14.5.1.1
mVlanTagsPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { mcVlanTagStripEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14.5.1.2
mVlanTagsOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { mcVlanTagStripEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14.5.1.3
mVlanTagsPortNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { mcVlanTagStripEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14.5.1.4
mVlanTagsMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            no_strip(0),
            strip(1),
            vlanTrans(2)
            }
      MAX-ACCESS read-only
```

```
      STATUS current
      DESCRIPTION
            "Description."
      ::= { mcVlanTagStripEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14.5.1.5
mVlanTagsVlanTrans OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { mcVlanTagStripEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14.6
mcMaxGroupTable OBJECT-TYPE
      SYNTAX SEQUENCE OF McMaxGroupEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortIgmpCfg 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14.6.1
mcMaxGroupEntry OBJECT-TYPE
      SYNTAX McMaxGroupEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { mcMaxGrpPonNo, mcMaxGrpOnuNo, mcMaxGrpPortNo }
      ::= { mcMaxGroupTable 1 }


McMaxGroupEntry ::=
      SEQUENCE {
            mcMaxGrpPonNo
                  Integer32,
            mcMaxGrpOnuNo
                  Integer32,
            mcMaxGrpPortNo
                  Integer32,
            mcMaxGrpVal
                  Integer32
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14.6.1.1
mcMaxGrpPonNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { mcMaxGroupEntry 1 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14.6.1.2
mcMaxGrpOnuNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { mcMaxGroupEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14.6.1.3
mcMaxGrpPortNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { mcMaxGroupEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.14.6.1.4
mcMaxGrpVal OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { mcMaxGroupEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.15
onuPortStatOnOff OBJECT IDENTIFIER ::= { onuPortCfg 15 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.15.1
statOnOffPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatOnOff 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.15.2
statOnOffOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatOnOff 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.15.3
statOnOffEthNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
```

```
      DESCRIPTION
            "Description."
      ::= { onuPortStatOnOff 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.15.4
monitorStatus OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatOnOff 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.15.5
statisticCycle OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatOnOff 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.15.6
statOnOffAction OBJECT-TYPE
      SYNTAX INTEGER { commit(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatOnOff 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.16
onuPortStat OBJECT IDENTIFIER ::= { onuPortCfg 16 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.16.1
onuPortStatClr OBJECT IDENTIFIER ::= { onuPortStat 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.16.1.1
clrStatPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatClr 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.16.1.2
clrStatOnuNo OBJECT-TYPE
```

```
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatClr 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.16.1.3
clrStatPortNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatClr 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.16.1.4
clrStatAction OBJECT-TYPE
      SYNTAX INTEGER { clear(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatClr 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.16.2
onuPortStatQueryMode OBJECT IDENTIFIER ::= { onuPortStat 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.16.2.1
queryPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatQueryMode 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.16.2.2
queryOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatQueryMode 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.16.2.3
queryPortNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { onuPortStatQueryMode 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.16.2.4
queryMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            monitor_current(1),
            monitor_history(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatQueryMode 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.16.2.5
queryAction OBJECT-TYPE
      SYNTAX INTEGER { commit(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatQueryMode 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.16.3
onuPortStatDisplay OBJECT IDENTIFIER ::= { onuPortStat 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.16.3.1
statDisplayPortNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatDisplay 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.16.3.2
dnDropEvents OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatDisplay 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.16.3.3
upDropEvents OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatDisplay 3 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.16.3.4
dnOctets OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatDisplay 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.16.3.5
upOctets OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatDisplay 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.16.3.6
dnFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatDisplay 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.16.3.7
upFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatDisplay 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.16.3.8
dnBcFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatDisplay 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.16.3.9
upBcFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { onuPortStatDisplay 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.16.3.10
dnMcFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatDisplay 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.16.3.11
upMcFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatDisplay 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.16.3.12
dnCrcErrFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatDisplay 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.16.3.13
upCrcErrFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatDisplay 13 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.16.3.14
dnUndersizeFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatDisplay 14 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.16.3.15
upUndersizeFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
```

```
            "Description."
      ::= { onuPortStatDisplay 15 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.16.3.16
dnOversizeFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatDisplay 16 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.16.3.17
upOversizeFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatDisplay 17 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.16.3.18
dnFragments OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatDisplay 18 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.16.3.19
upFragments OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatDisplay 19 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.16.3.20
dnJabbers OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatDisplay 20 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.16.3.21
upJabbers OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
```

```
      DESCRIPTION
            "Description."
      ::= { onuPortStatDisplay 21 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.16.3.22
dn64OctetsFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatDisplay 22 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.16.3.23
dn65to127OctetsFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatDisplay 23 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.16.3.24
dn128to255OctetsFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatDisplay 24 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.16.3.25
dn256to511OctetsFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatDisplay 25 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.16.3.26
dn512to1023OctetsFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatDisplay 26 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.16.3.27
dn1024to1518OctetsFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
```

```
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatDisplay 27 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.16.3.28
up64OctetsFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatDisplay 28 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.16.3.29
up65to127OctetsFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatDisplay 29 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.16.3.30
up128to255OctetsFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatDisplay 30 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.16.3.31
up256to511OctetsFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatDisplay 31 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.16.3.32
up512to1023OctetsFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatDisplay 32 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.16.3.33
up1024to1518OctetsFrames OBJECT-TYPE
      SYNTAX Counter32
```

```
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatDisplay 33 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.16.3.34
dnDiscardFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatDisplay 34 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.16.3.35
upDiscardFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatDisplay 35 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.16.3.36
dnErrFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatDisplay 36 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.16.3.37
upErrFrames OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatDisplay 37 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.2.16.3.38
statusChangeTimes OBJECT-TYPE
      SYNTAX Counter32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatDisplay 38 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.3
onuPortGlobalView OBJECT IDENTIFIER ::= { onuPort 3 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.5.3.1
globalViewPonNum OBJECT-TYPE
      SYNTAX Integer32 (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortGlobalView 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.3.2
globalViewOnuNum OBJECT-TYPE
      SYNTAX Integer32 (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortGlobalView 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.5.3.3
globalViewPortNum OBJECT-TYPE
      SYNTAX Integer32 (1..64)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortGlobalView 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6
onuVoipCfg OBJECT IDENTIFIER ::= { v1600dOnuMgmt 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1
voipInfo OBJECT IDENTIFIER ::= { onuVoipCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.2
voipGlobalInfo OBJECT IDENTIFIER ::= { voipInfo 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.2.1
voipGlobalIPTable OBJECT-TYPE
      SYNTAX SEQUENCE OF VoipGlobalIPEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipGlobalInfo 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.2.1.1
voipGlobalIPEntry OBJECT-TYPE
      SYNTAX VoipGlobalIPEntry
      MAX-ACCESS not-accessible
      STATUS current
```

```
      DESCRIPTION
            "Description."
      INDEX { voipGIPPonNo, voipGIPOnuNo }
      ::= { voipGlobalIPTable 1 }


VoipGlobalIPEntry ::=
      SEQUENCE {
            voipGIPPonNo
                  Integer32,
            voipGIPOnuNo
                  Integer32,
            voipGIPMode
                  INTEGER,
            voipGIPAddr
                  IpAddress,
            voipGIPMask
                  IpAddress,
            voipGIPGateway
                  IpAddress,
            voipGIPPPPoEMode
                  INTEGER,
            voipGIPPPPoEUserName
                  OCTET STRING,
            voipGIPPPPoEPasswd
                  OCTET STRING,
            voipGIPTagFlag
                  INTEGER,
            voipGIPCVlan
                  Integer32,
            voipGIPSVlan
                  Integer32,
            voipGIPPriority
                  Integer32
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.2.1.1.1
voipGIPPonNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipGlobalIPEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.2.1.1.2
voipGIPOnuNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipGlobalIPEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.2.1.1.3
voipGIPMode OBJECT-TYPE
      SYNTAX INTEGER
```

```
            {
            Static_IP(0),
            DHCP(1),
            PPPoE(2)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipGlobalIPEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.2.1.1.4
voipGIPAddr OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipGlobalIPEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.2.1.1.5
voipGIPMask OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipGlobalIPEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.2.1.1.6
voipGIPGateway OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipGlobalIPEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.2.1.1.7
voipGIPPPPoEMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            AUTO(0),
            CHAP(1),
            PAP(2)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipGlobalIPEntry 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.2.1.1.8
voipGIPPPPoEUserName OBJECT-TYPE
```

```
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipGlobalIPEntry 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.2.1.1.9
voipGIPPPPoEPasswd OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipGlobalIPEntry 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.2.1.1.10
voipGIPTagFlag OBJECT-TYPE
      SYNTAX INTEGER
            {
            Transparent(0),
            Tag(1),
            Vlan_Stacking(2)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipGlobalIPEntry 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.2.1.1.11
voipGIPCVlan OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipGlobalIPEntry 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.2.1.1.12
voipGIPSVlan OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipGlobalIPEntry 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.2.1.1.13
voipGIPPriority OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
```

```
            "Description."
      ::= { voipGlobalIPEntry 13 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.2.2
voipPortMngTable OBJECT-TYPE
      SYNTAX SEQUENCE OF VoipPortMngEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipGlobalInfo 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.2.2.1
voipPortMngEntry OBJECT-TYPE
      SYNTAX VoipPortMngEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { voipMngTPonNo, voipMngTOnuNo, voipMngTPotsNo }
      ::= { voipPortMngTable 1 }


VoipPortMngEntry ::=
      SEQUENCE {
            voipMngTPonNo
                  Integer32,
            voipMngTOnuNo
                  Integer32,
            voipMngTPotsNo
                  Integer32,
            voipMngTPortManage
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.2.2.1.1
voipMngTPonNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipPortMngEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.2.2.1.2
voipMngTOnuNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipPortMngEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.2.2.1.3
voipMngTPotsNo OBJECT-TYPE
```

```
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipPortMngEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.2.2.1.4
voipMngTPortManage OBJECT-TYPE
      SYNTAX INTEGER
            {
            Disactive(0),
            Active(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipPortMngEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.2.3
voipIADInfoTable OBJECT-TYPE
      SYNTAX SEQUENCE OF VoipIADInfoEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipGlobalInfo 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.2.3.1
voipIADInfoEntry OBJECT-TYPE
      SYNTAX VoipIADInfoEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { voipIADInfoPonNo, voipIADInfoOnuNo }
      ::= { voipIADInfoTable 1 }


VoipIADInfoEntry ::=
      SEQUENCE {
            voipIADInfoPonNo
                  Integer32,
            voipIADInfoOnuNo
                  Integer32,
            voipIADInfoMacAddr
                  OCTET STRING,
            voipIADInfoProtocolSupport
                  INTEGER,
            voipIADInfoSoftVersion
                  OCTET STRING,
            voipIADInfoSoftTime
                  OCTET STRING,
            voipIADInfoUserCount
                  Integer32
```

```
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.2.3.1.1
voipIADInfoPonNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipIADInfoEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.2.3.1.2
voipIADInfoOnuNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipIADInfoEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.2.3.1.3
voipIADInfoMacAddr OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipIADInfoEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.2.3.1.4
voipIADInfoProtocolSupport OBJECT-TYPE
      SYNTAX INTEGER
            {
            H248(0),
            SIP(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipIADInfoEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.2.3.1.5
voipIADInfoSoftVersion OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipIADInfoEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.2.3.1.6
voipIADInfoSoftTime OBJECT-TYPE
      SYNTAX OCTET STRING
```

```
            MAX-ACCESS read-only
            STATUS current
            DESCRIPTION
                  "Description."
            ::= { voipIADInfoEntry 6 }


      -- 1.3.6.1.4.1.37950.1.1.5.12.6.1.2.3.1.7
      voipIADInfoUserCount OBJECT-TYPE
            SYNTAX Integer32
            MAX-ACCESS read-only
            STATUS current
            DESCRIPTION
                  "Description."
            ::= { voipIADInfoEntry 7 }


      -- 1.3.6.1.4.1.37950.1.1.5.12.6.1.2.4
      voipPotsStatusTable OBJECT-TYPE
            SYNTAX SEQUENCE OF VoipPotsStatusEntry
            MAX-ACCESS not-accessible
            STATUS current
            DESCRIPTION
                  "Description."
            ::= { voipGlobalInfo 4 }


      -- 1.3.6.1.4.1.37950.1.1.5.12.6.1.2.4.1
      voipPotsStatusEntry OBJECT-TYPE
            SYNTAX VoipPotsStatusEntry
            MAX-ACCESS not-accessible
            STATUS current
            DESCRIPTION
                  "Description."
            INDEX { voipPostStatusPonNo, voipPostStatusOnuNo,
voipPostStatusPotsNo }
            ::= { voipPotsStatusTable 1 }


      VoipPotsStatusEntry ::=
            SEQUENCE {
                  voipPostStatusPonNo
                        Integer32,
                  voipPostStatusOnuNo
                        Integer32,
                  voipPostStatusPotsNo
                        Integer32,
                  voipPostStatusPortStatus
                        INTEGER,
                  voipPostStatusServicesState
                        INTEGER,
                  voipPostStatusCodecMode
                        INTEGER
             }

      -- 1.3.6.1.4.1.37950.1.1.5.12.6.1.2.4.1.1
      voipPostStatusPonNo OBJECT-TYPE
            SYNTAX Integer32
            MAX-ACCESS read-only
```

```
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipPotsStatusEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.2.4.1.2
voipPostStatusOnuNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipPotsStatusEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.2.4.1.3
voipPostStatusPotsNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipPotsStatusEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.2.4.1.4
voipPostStatusPortStatus OBJECT-TYPE
      SYNTAX INTEGER
            {
            Registering(0),
            Idle(1),
            Offhook(2),
            Dialing(3),
            Ringing(4),
            Ring_Back(5),
            Connecting(6),
            Connected(7),
            Release_connection(8),
            Register_fail(9),
            Inactive(10)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipPotsStatusEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.2.4.1.5
voipPostStatusServicesState OBJECT-TYPE
      SYNTAX INTEGER
            {
            Endlocal(0),
            EndRemote(1),
            EndAuto(2),
            EndNormal(3)
            }
      MAX-ACCESS read-only
```

```
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipPotsStatusEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.2.4.1.6
voipPostStatusCodecMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            G711A(0),
            G729(1),
            G711U(2),
            G723(3),
            G726(4),
            T38(5)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipPotsStatusEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.3
voipH248Info OBJECT IDENTIFIER ::= { voipInfo 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.3.1
h248IADStatusTable OBJECT-TYPE
      SYNTAX SEQUENCE OF H248IADStatusEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipH248Info 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.3.1.1
h248IADStatusEntry OBJECT-TYPE
      SYNTAX H248IADStatusEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { h248IADStatusPonNo, h248IADStatusOnuNo }
      ::= { h248IADStatusTable 1 }


H248IADStatusEntry ::=
      SEQUENCE {
            h248IADStatusPonNo
                  Integer32,
            h248IADStatusOnuNo
                  Integer32,
            h248IADOperStatus
                  INTEGER
       }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.3.1.1.1
h248IADStatusPonNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248IADStatusEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.3.1.1.2
h248IADStatusOnuNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248IADStatusEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.3.1.1.3
h248IADOperStatus OBJECT-TYPE
      SYNTAX INTEGER
            {
            Registering(0),
            Register_success(1),
            IAD_fault(2),
            Deregister(3),
            IAD_restarting(4)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248IADStatusEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.3.2
h248ParamTable OBJECT-TYPE
      SYNTAX SEQUENCE OF H248ParamEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipH248Info 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.3.2.1
h248ParamEntry OBJECT-TYPE
      SYNTAX H248ParamEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { h248ParamTPonNo, h248ParamTOnuNo }
      ::= { h248ParamTable 1 }


H248ParamEntry ::=
```

```
      SEQUENCE {
            h248ParamTPonNo
                  Integer32,
            h248ParamTOnuNo
                  Integer32,
            h248ParamTMGPortNo
                  Integer32,
            h248ParamTMGCIP
                  IpAddress,
            h248ParamTMgcComPortNo
                  Integer32,
            h248ParamTBackupMGCIP
                  IpAddress,
            h248ParamTBackupMgcComPortNo
                  Integer32,
            h248ParamTActiveMGC
                  INTEGER,
            h248ParamTRegMode
                  INTEGER,
            h248ParamTMID
                  OCTET STRING,
            h248ParamTHBMode
                  INTEGER,
            h248ParamTHBCycle
                  Integer32,
            h248ParamTHBCount
                  Integer32
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.3.2.1.1
h248ParamTPonNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248ParamEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.3.2.1.2
h248ParamTOnuNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248ParamEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.3.2.1.3
h248ParamTMGPortNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248ParamEntry 3 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.3.2.1.4
h248ParamTMGCIP OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248ParamEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.3.2.1.5
h248ParamTMgcComPortNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248ParamEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.3.2.1.6
h248ParamTBackupMGCIP OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248ParamEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.3.2.1.7
h248ParamTBackupMgcComPortNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248ParamEntry 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.3.2.1.8
h248ParamTActiveMGC OBJECT-TYPE
      SYNTAX INTEGER
            {
            BackupMGC(0),
            MainMGC(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248ParamEntry 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.3.2.1.9
h248ParamTRegMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            Ipaddr(0),
```

```
            Domain_name(1),
            Device_name(2)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248ParamEntry 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.3.2.1.10
h248ParamTMID OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248ParamEntry 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.3.2.1.11
h248ParamTHBMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            Disable(0),
            H248(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248ParamEntry 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.3.2.1.12
h248ParamTHBCycle OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248ParamEntry 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.3.2.1.13
h248ParamTHBCount OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248ParamEntry 13 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.3.3
h248UserTidTable OBJECT-TYPE
      SYNTAX SEQUENCE OF H248UserTidEntry
      MAX-ACCESS not-accessible
      STATUS current
```

```
      DESCRIPTION
            "Description."
      ::= { voipH248Info 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.3.3.1
h248UserTidEntry OBJECT-TYPE
      SYNTAX H248UserTidEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { h248UserTIDPonNo, h248UserTIDOnuNo, h248UserTIDPotsNo }
      ::= { h248UserTidTable 1 }


H248UserTidEntry ::=
      SEQUENCE {
            h248UserTIDPonNo
                  Integer32,
            h248UserTIDOnuNo
                  Integer32,
            h248UserTIDPotsNo
                  Integer32,
            h248UserTIDName
                  OCTET STRING
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.3.3.1.1
h248UserTIDPonNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248UserTidEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.3.3.1.2
h248UserTIDOnuNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248UserTidEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.3.3.1.3
h248UserTIDPotsNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248UserTidEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.3.3.1.4
```

```
h248UserTIDName OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248UserTidEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.3.4
h248RTPTIDTable OBJECT-TYPE
      SYNTAX SEQUENCE OF H248RTPTIDEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipH248Info 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.3.4.1
h248RTPTIDEntry OBJECT-TYPE
      SYNTAX H248RTPTIDEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { h248RTPTIDPonNo, h248RTPTIDOnuNo }
      ::= { h248RTPTIDTable 1 }


H248RTPTIDEntry ::=
      SEQUENCE {
            h248RTPTIDPonNo
                  Integer32,
            h248RTPTIDOnuNo
                  Integer32,
            h248RTPTIDNumber
                  Integer32,
            h248RTPTIDFirstName
                  OCTET STRING
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.3.4.1.1
h248RTPTIDPonNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248RTPTIDEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.3.4.1.2
h248RTPTIDOnuNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { h248RTPTIDEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.3.4.1.3
h248RTPTIDNumber OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248RTPTIDEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.3.4.1.4
h248RTPTIDFirstName OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248RTPTIDEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.4
voipSipInfo OBJECT IDENTIFIER ::= { voipInfo 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.4.1
sipParamTable OBJECT-TYPE
      SYNTAX SEQUENCE OF SipParamEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipSipInfo 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.4.1.1
sipParamEntry OBJECT-TYPE
      SYNTAX SipParamEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { sipPTPonNo, sipPTOnuNo }
      ::= { sipParamTable 1 }


SipParamEntry ::=
      SEQUENCE {
            sipPTPonNo
                  Integer32,
            sipPTOnuNo
                  Integer32,
            sipPTMGPortNo
                  Integer32,
            sipPTProxyServIp
                  IpAddress,
            sipPTPorxyServPortNo
```

```
                Integer32,
            sipPTBackupProxyServIp
                IpAddress,
            sipPTBackupPorxyServPortNo
                Integer32,
            sipPTActiveProxyServer
                IpAddress,
            sipPTRegServIp
                IpAddress,
            sipPTRegServPortNo
                Integer32,
            sipPTBackupRegServIp
                IpAddress,
            sipPTBackupRegServPortNo
                Integer32,
            sipPTOutBoundServIp
                IpAddress,
            sipPTOutBoundServPortNo
                Integer32,
            sipPTRegInterval
                Integer32,
            sipPTHeartbeatEn
                INTEGER,
            sipPTHeartbeatCycle
                INTEGER,
            sipPTHeartbeatCount
                INTEGER
        }

-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.4.1.1.1
sipPTPonNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipParamEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.4.1.1.2
sipPTOnuNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipParamEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.4.1.1.3
sipPTMGPortNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipParamEntry 3 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.4.1.1.4
sipPTProxyServIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipParamEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.4.1.1.5
sipPTPorxyServPortNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipParamEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.4.1.1.6
sipPTBackupProxyServIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipParamEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.4.1.1.7
sipPTBackupPorxyServPortNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipParamEntry 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.4.1.1.8
sipPTActiveProxyServer OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipParamEntry 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.4.1.1.9
sipPTRegServIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipParamEntry 9 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.4.1.1.10
sipPTRegServPortNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipParamEntry 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.4.1.1.11
sipPTBackupRegServIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipParamEntry 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.4.1.1.12
sipPTBackupRegServPortNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipParamEntry 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.4.1.1.13
sipPTOutBoundServIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipParamEntry 13 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.4.1.1.14
sipPTOutBoundServPortNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipParamEntry 14 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.4.1.1.15
sipPTRegInterval OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipParamEntry 15 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.4.1.1.16
sipPTHeartbeatEn OBJECT-TYPE
      SYNTAX INTEGER
            {
            Enable(0),
            Disable(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipParamEntry 16 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.4.1.1.17
sipPTHeartbeatCycle OBJECT-TYPE
      SYNTAX INTEGER
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipParamEntry 17 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.4.1.1.18
sipPTHeartbeatCount OBJECT-TYPE
      SYNTAX INTEGER
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipParamEntry 18 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.4.2
sipUserParamTable OBJECT-TYPE
      SYNTAX SEQUENCE OF SipUserParamEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipSipInfo 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.4.2.1
sipUserParamEntry OBJECT-TYPE
      SYNTAX SipUserParamEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { sipUserParamPonNo, sipUserParamOnuNo,
sipUserParamPotsNo }
      ::= { sipUserParamTable 1 }


SipUserParamEntry ::=
```

```
      SEQUENCE {
            sipUserParamPonNo
                  Integer32,
            sipUserParamOnuNo
                  Integer32,
            sipUserParamPotsNo
                  Integer32,
            sipUserParamUserAccount
                  OCTET STRING,
            sipUserParamUserName
                  OCTET STRING,
            sipUserParamUserPasswd
                  OCTET STRING
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.4.2.1.1
sipUserParamPonNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipUserParamEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.4.2.1.2
sipUserParamOnuNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipUserParamEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.4.2.1.3
sipUserParamPotsNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipUserParamEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.4.2.1.4
sipUserParamUserAccount OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipUserParamEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.4.2.1.5
sipUserParamUserName OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
```

```
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipUserParamEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.4.2.1.6
sipUserParamUserPasswd OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipUserParamEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.4.3
faxModemCfgTable OBJECT-TYPE
      SYNTAX SEQUENCE OF FaxModemCfgEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipSipInfo 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.4.3.1
faxModemCfgEntry OBJECT-TYPE
      SYNTAX FaxModemCfgEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { faxModemPonNo, faxModemOnuNo }
      ::= { faxModemCfgTable 1 }


FaxModemCfgEntry ::=
      SEQUENCE {
            faxModemPonNo
                  Integer32,
            faxModemOnuNo
                  Integer32,
            faxModemVoiceT38En
                  INTEGER,
            faxModemVoiceCtl
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.4.3.1.1
faxModemPonNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { faxModemCfgEntry 1 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.4.3.1.2
faxModemOnuNo OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { faxModemCfgEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.4.3.1.3
faxModemVoiceT38En OBJECT-TYPE
      SYNTAX INTEGER
            {
            T30(0),
            T38(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { faxModemCfgEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.1.4.3.1.4
faxModemVoiceCtl OBJECT-TYPE
      SYNTAX INTEGER
            {
            Negotiation(0),
            Auto_VBD(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { faxModemCfgEntry 4 }

-- 1.3.6.1.4.1.37950.1.1.5.12.6.2
voipGlobalCfg OBJECT IDENTIFIER ::= { onuVoipCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.2.1
voipGlobalIpCfg OBJECT IDENTIFIER ::= { voipGlobalCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.2.1.1
voipIpPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipGlobalIpCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.2.1.2
voipIpOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
```

```
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipGlobalIpCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.2.1.3
voipIpMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            Static_IP(0),
            DHCP(1),
            PPPoE(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipGlobalIpCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.2.1.4
voipStaticIpAddr OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipGlobalIpCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.2.1.5
voipStaticIpMask OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipGlobalIpCfg 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.2.1.6
voipStaticIpGw OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipGlobalIpCfg 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.2.1.7
voipPPPoEMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            AUTO(0),
            CHAP(1),
            PAP(2)
            }
```

```
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipGlobalIpCfg 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.2.1.8
voipPPPOEUserName OBJECT-TYPE
      SYNTAX OCTET STRING (SIZE (0..32))
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipGlobalIpCfg 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.2.1.9
voipPPPOEPasswd OBJECT-TYPE
      SYNTAX OCTET STRING (SIZE (0..32))
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipGlobalIpCfg 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.2.1.10
voipTagFlag OBJECT-TYPE
      SYNTAX INTEGER
            {
            Transparent(0),
            Tag(1),
            Vlan_Stacking(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipGlobalIpCfg 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.2.1.11
voipCVlan OBJECT-TYPE
      SYNTAX Integer32 (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipGlobalIpCfg 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.2.1.12
voipSVlan OBJECT-TYPE
      SYNTAX Integer32 (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { voipGlobalIpCfg 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.2.1.13
voipPriority OBJECT-TYPE
      SYNTAX Integer32 (0..7)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipGlobalIpCfg 13 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.2.1.14
staticIpAction OBJECT-TYPE
      SYNTAX INTEGER { commit(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipGlobalIpCfg 14 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.2.2
voipPortMng OBJECT IDENTIFIER ::= { voipGlobalCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.2.2.1
voipMngPonNo OBJECT-TYPE
      SYNTAX Integer32 (0..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipPortMng 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.2.2.2
voipMngOnuNo OBJECT-TYPE
      SYNTAX Integer32 (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipPortMng 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.2.2.3
voipMngPotsNo OBJECT-TYPE
      SYNTAX Integer32 (1..64)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipPortMng 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.2.2.4
voipPortManage OBJECT-TYPE
```

```
      SYNTAX INTEGER
            {
            Disable(0),
            Enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipPortMng 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.3
voipH248Cfg OBJECT IDENTIFIER ::= { onuVoipCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.1
h248ProParam OBJECT IDENTIFIER ::= { voipH248Cfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.1.1
ipRegModeCfg OBJECT IDENTIFIER ::= { h248ProParam 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.1.1.1
ipRegPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ipRegModeCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.1.1.2
ipRegOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ipRegModeCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.1.1.3
ipRegMode OBJECT-TYPE
      SYNTAX INTEGER { ip_addr(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ipRegModeCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.1.1.5
ipRegAction OBJECT-TYPE
      SYNTAX INTEGER { commit(1) }
      MAX-ACCESS read-write
      STATUS current
```

```
      DESCRIPTION
            "Description."
      ::= { ipRegModeCfg 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.1.2
nameCfg OBJECT IDENTIFIER ::= { h248ProParam 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.1.2.1
namePonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { nameCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.1.2.2
nameOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { nameCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.1.2.3
nameSel OBJECT-TYPE
      SYNTAX INTEGER
            {
            realmName(1),
            deviceName(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { nameCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.1.2.4
nameValue OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { nameCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.1.2.5
nameAction OBJECT-TYPE
      SYNTAX INTEGER { commit(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
```

```
            "Description."
      ::= { nameCfg 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.1.3
heartbeatCfg OBJECT IDENTIFIER ::= { h248ProParam 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.1.3.1
heartbeatPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { heartbeatCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.1.3.2
heartbeatOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { heartbeatCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.1.3.3
heartbeatMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            h248(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { heartbeatCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.1.3.4
heartbeatCycle OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { heartbeatCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.1.3.5
heartbeatCount OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { heartbeatCfg 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.1.3.6
heartbeatAction OBJECT-TYPE
      SYNTAX INTEGER { commit(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { heartbeatCfg 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.1.4
mgcCfg OBJECT IDENTIFIER ::= { h248ProParam 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.1.4.1
mgcPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { mgcCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.1.4.2
mgcOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { mgcCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.1.4.3
mgPort OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { mgcCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.1.4.4
mgcIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { mgcCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.1.4.5
mgcPort OBJECT-TYPE
```

```
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { mgcCfg 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.1.4.6
bakMgcIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { mgcCfg 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.1.4.7
bakMgcPort OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { mgcCfg 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.1.4.8
mgcAction OBJECT-TYPE
      SYNTAX INTEGER { commit(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { mgcCfg 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.1.5
h248ParamCfg OBJECT IDENTIFIER ::= { h248ProParam 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.1.5.1
h248ParamPonNo OBJECT-TYPE
      SYNTAX Integer32 (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248ParamCfg 1 }

-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.1.5.2
h248ParamOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248ParamCfg 2 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.1.5.3
h248ParamMGPortNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248ParamCfg 3 }

-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.1.5.4
h248ParamMGCIP OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248ParamCfg 4 }

-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.1.5.5
h248ParamMgcComPortNo OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248ParamCfg 5 }

-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.1.5.6
h248ParamBackupMGCIP OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248ParamCfg 6 }

-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.1.5.7
h248ParamBackupMgcComPortNo OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248ParamCfg 7 }

-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.1.5.8
h248ParamRegMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            IPAddr(0),
            Domain_name(1),
            Device_name(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248ParamCfg 8 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.1.5.9
h248ParamMID OBJECT-TYPE
      SYNTAX OCTET STRING (SIZE (0..64))
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248ParamCfg 9 }

-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.1.5.10
h248ParamHBMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            Disable(0),
            H248(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248ParamCfg 10 }

-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.1.5.11
h248ParamHBCycle OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248ParamCfg 11 }

-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.1.5.12
h248ParamHBCount OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248ParamCfg 12 }

-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.1.5.13
h248ParamAction OBJECT-TYPE
      SYNTAX INTEGER { Commit(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248ParamCfg 13 }

-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.2
h248UserTid OBJECT IDENTIFIER ::= { voipH248Cfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.2.1
userTidPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
```

```
      DESCRIPTION
            "Description."
      ::= { h248UserTid 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.2.2
userTidOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248UserTid 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.2.3
userTidPotsNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248UserTid 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.2.4
userTid OBJECT-TYPE
      SYNTAX OCTET STRING (SIZE (0..32))
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248UserTid 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.2.5
userTidAction OBJECT-TYPE
      SYNTAX INTEGER { commit(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248UserTid 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.4
h248RtpTid OBJECT IDENTIFIER ::= { voipH248Cfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.4.1
rtpTidPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248RtpTid 1 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.4.2
rtpTidOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248RtpTid 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.4.3
rtpTidNumber OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248RtpTid 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.4.4
rtpTidPrefix OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248RtpTid 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.4.5
digitBegin0 OBJECT-TYPE
      SYNTAX Unsigned32 (0..4294967295)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248RtpTid 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.4.6
digitBegin1 OBJECT-TYPE
      SYNTAX Unsigned32 (0..4294967295)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248RtpTid 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.4.7
rtpTidMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            align(1),
            unalign(2)
            }
      MAX-ACCESS read-write
      STATUS current
```

```
      DESCRIPTION
            "Description."
      ::= { h248RtpTid 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.4.8
digitLength OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248RtpTid 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.3.4.9
rtpTidAction OBJECT-TYPE
      SYNTAX INTEGER { commit(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248RtpTid 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4
voipSipCfg OBJECT IDENTIFIER ::= { onuVoipCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.1
sipProParam OBJECT IDENTIFIER ::= { voipSipCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.1.1
hbeatCfg OBJECT IDENTIFIER ::= { sipProParam 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.1.1.1
hbeatPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { hbeatCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.1.1.2
hbeatOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { hbeatCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.1.1.3
hbeartEn OBJECT-TYPE
```

```
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { hbeatCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.1.1.4
hbeatCycle OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { hbeatCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.1.1.5
hbeatCount OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { hbeatCfg 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.1.1.6
regInterVal OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { hbeatCfg 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.1.1.7
hbeatAction OBJECT-TYPE
      SYNTAX INTEGER { commit(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { hbeatCfg 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.1.2
servIpCfg OBJECT IDENTIFIER ::= { sipProParam 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.1.2.1
servIpPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
```

```
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { servIpCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.1.2.2
servIpOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { servIpCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.1.2.3
mgPortVal OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { servIpCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.1.2.4
servIpVal OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { servIpCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.1.2.5
servPortVal OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { servIpCfg 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.1.2.6
servIpAction OBJECT-TYPE
      SYNTAX INTEGER { commit(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { servIpCfg 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.1.3
proxyServCfg OBJECT IDENTIFIER ::= { sipProParam 3 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.1.3.1
proxySrvPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { proxyServCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.1.3.2
proxySrvOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { proxyServCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.1.3.3
proxySrv OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { proxyServCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.1.3.4
proxySrvPort OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { proxyServCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.1.3.5
bakProxySrv OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { proxyServCfg 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.1.3.6
bakProxySrvPort OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { proxyServCfg 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.1.3.7
proxySrvAction OBJECT-TYPE
      SYNTAX INTEGER { commit(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { proxyServCfg 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.1.4
regServCfg OBJECT IDENTIFIER ::= { sipProParam 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.1.4.1
regSrvPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { regServCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.1.4.2
regSrvOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { regServCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.1.4.3
regSrv OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { regServCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.1.4.4
regSrvPort OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { regServCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.1.4.5
bakRegSrv OBJECT-TYPE
```

```
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { regServCfg 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.1.4.6
bakRegSrvPort OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { regServCfg 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.1.4.7
regSrvAction OBJECT-TYPE
      SYNTAX INTEGER { commit(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { regServCfg 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.1.5
sipParamCfg OBJECT IDENTIFIER ::= { sipProParam 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.1.5.1
sipParamPonNo OBJECT-TYPE
      SYNTAX Integer32 (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipParamCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.1.5.2
sipParamOnuNo OBJECT-TYPE
      SYNTAX Integer32 (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipParamCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.1.5.3
sipParamMGPortNo OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { sipParamCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.1.5.4
sipParamSipProxyServIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipParamCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.1.5.5
sipParamSipProxyServPortNo OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipParamCfg 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.1.5.6
sipParamBackupSipProxyServIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipParamCfg 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.1.5.7
sipParamBackupSipProxyServPortNo OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipParamCfg 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.1.5.8
sipParamSipRegServIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipParamCfg 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.1.5.9
sipParamSipRegServPortNo OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
```

```
            "Description."
      ::= { sipParamCfg 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.1.5.10
sipParamBackupSipRegServIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipParamCfg 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.1.5.11
sipParamBackupSipRegServPortNo OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipParamCfg 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.1.5.12
sipParamOutBoundServIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipParamCfg 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.1.5.13
sipParamOutBoundServPortNo OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipParamCfg 13 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.1.5.14
sipParamRegInterval OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipParamCfg 14 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.1.5.15
sipParamHeartbeatEn OBJECT-TYPE
      SYNTAX INTEGER
            {
            Enable(0),
```

```
            Disable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipParamCfg 15 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.1.5.16
sipParamHeartbeatCycle OBJECT-TYPE
      SYNTAX Integer32 (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipParamCfg 16 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.1.5.17
sipParamHeartbeatCount OBJECT-TYPE
      SYNTAX Integer32 (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipParamCfg 17 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.1.5.18
sipParamAction OBJECT-TYPE
      SYNTAX INTEGER { Commit(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipParamCfg 18 }

-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.2
sipUserParam OBJECT IDENTIFIER ::= { voipSipCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.2.1
sipUserPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipUserParam 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.2.2
sipUserOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { sipUserParam 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.2.3
sipUserPotsNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipUserParam 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.2.4
sipUserAccount OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipUserParam 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.2.5
sipUserName OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipUserParam 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.2.6
sipUserPw OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipUserParam 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.2.7
sipUserAction OBJECT-TYPE
      SYNTAX INTEGER { commit(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipUserParam 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.3
faxModemCfg OBJECT IDENTIFIER ::= { voipSipCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.3.1
faxPonNo OBJECT-TYPE
```

```
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { faxModemCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.3.2
faxOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { faxModemCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.3.3
t38En OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { faxModemCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.3.4
control OBJECT-TYPE
      SYNTAX INTEGER
            {
            negotiation(1),
            autovbd(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { faxModemCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.3.5
faxModemAction OBJECT-TYPE
      SYNTAX INTEGER { commit(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { faxModemCfg 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.4
iadOperCfg OBJECT IDENTIFIER ::= { voipSipCfg 4 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.4.1
iadOperPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { iadOperCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.4.2
iadOperOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { iadOperCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.4.3
iadOperation OBJECT-TYPE
      SYNTAX INTEGER
            {
            reregister(1),
            deregister(2),
            reset(3)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { iadOperCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.4.4
iadOperAction OBJECT-TYPE
      SYNTAX INTEGER { commit(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { iadOperCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.5
sipDigitCfg OBJECT IDENTIFIER ::= { voipSipCfg 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.5.1
digitPonNo OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipDigitCfg 1 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.5.2
digitOnuNo OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipDigitCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.5.3
digBlockNum OBJECT-TYPE
      SYNTAX Integer32 (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipDigitCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.5.4
digMapId OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipDigitCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.5.5
digitMap OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipDigitCfg 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.6.4.5.6
sipDigitAction OBJECT-TYPE
      SYNTAX INTEGER { commit(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipDigitCfg 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.7
onuAlarmShow OBJECT IDENTIFIER ::= { v1600dOnuMgmt 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.7.1
onuAlarmPonTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuAlarmPonEntry
      MAX-ACCESS not-accessible
```

```
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAlarmShow 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.7.1.1
onuAlarmPonEntry OBJECT-TYPE
      SYNTAX OnuAlarmPonEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { onuAlarmPonIndex, onuAlarmPonOnuIndex, onuAlarmPonType }
      ::= { onuAlarmPonTable 1 }


OnuAlarmPonEntry ::=
      SEQUENCE {
            onuAlarmPonIndex
                  Integer32,
            onuAlarmPonOnuIndex
                  Integer32,
            onuAlarmPonType
                  INTEGER,
            onuAlarmPonEnable
                  INTEGER,
            onuAlarmPonAlarmThr
                  OCTET STRING,
            onuAlarmPonClearThr
                  OCTET STRING
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.7.1.1.1
onuAlarmPonIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAlarmPonEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.7.1.1.2
onuAlarmPonOnuIndex OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAlarmPonEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.7.1.1.3
onuAlarmPonType OBJECT-TYPE
      SYNTAX INTEGER
            {
            rxPowerHighAlarm(1),
            rxPowerLowAlarm(2),
```

```
            txPowerHighAlarm(3),
            txPowerLowAlarm(4),
            txBiasHighAlarm(5),
            txBiasLowAlarm(6),
            vccHighAlarm(7),
            vccLowAlarm(8),
            tempHighAlarm(9),
            tempLowAlarm(10),
            rxPowerHighWarn(11),
            rxPowerLowWarn(12),
            txPowerHighWarn(13),
            txPowerLowWarn(14),
            txBiasHighWarn(15),
            txBiasLowWarn(16),
            vccHighWarn(17),
            vccLowWarn(18),
            tempHighWarn(19),
            tempLowWarn(20)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAlarmPonEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.7.1.1.4
onuAlarmPonEnable OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAlarmPonEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.7.1.1.5
onuAlarmPonAlarmThr OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAlarmPonEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.7.1.1.6
onuAlarmPonClearThr OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAlarmPonEntry 6 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.7.2
onuAlarmPortTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuAlarmPortEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAlarmShow 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.7.2.1
onuAlarmPortEntry OBJECT-TYPE
      SYNTAX OnuAlarmPortEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { onuAlarmPortPon, onuAlarmPortOnu, onuAlarmPortPort }
      ::= { onuAlarmPortTable 1 }


OnuAlarmPortEntry ::=
      SEQUENCE {
            onuAlarmPortPon
                  Integer32,
            onuAlarmPortOnu
                  Integer32,
            onuAlarmPortPort
                  Integer32,
            onuAlarmPortAutoEnable
                  INTEGER,
            onuAlarmPortLosEnable
                  INTEGER,
            onuAlarmPortFailureEnable
                  INTEGER,
            onuAlarmPortLoopbackEnable
                  INTEGER,
            onuAlarmPortCongestEnable
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.7.2.1.1
onuAlarmPortPon OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAlarmPortEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.7.2.1.2
onuAlarmPortOnu OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { onuAlarmPortEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.7.2.1.3
onuAlarmPortPort OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAlarmPortEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.7.2.1.4
onuAlarmPortAutoEnable OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAlarmPortEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.7.2.1.5
onuAlarmPortLosEnable OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAlarmPortEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.7.2.1.6
onuAlarmPortFailureEnable OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAlarmPortEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.7.2.1.7
onuAlarmPortLoopbackEnable OBJECT-TYPE
      SYNTAX INTEGER
            {
```

```
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAlarmPortEntry 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.7.2.1.8
onuAlarmPortCongestEnable OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuAlarmPortEntry 8 }

-- 1.3.6.1.4.1.37950.1.1.5.12.8
onuProfileCfg OBJECT IDENTIFIER ::= { v1600dOnuMgmt 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.1
profileEdit OBJECT IDENTIFIER ::= { onuProfileCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.1.1
profileTpye OBJECT-TYPE
      SYNTAX INTEGER
            {
            dba(1),
            srv(2),
            voip(3),
            alarm(4)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { profileEdit 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.1.2
profileId OBJECT-TYPE
      SYNTAX INTEGER (1..32767)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { profileEdit 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.1.3
profileAction OBJECT-TYPE
```

```
      SYNTAX INTEGER
            {
            add(1),
            delete(2),
            commit(3)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { profileEdit 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.2
dbaProfileEdit OBJECT IDENTIFIER ::= { onuProfileCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.2.1
dbaProfileNo OBJECT-TYPE
      SYNTAX INTEGER (1..32767)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { dbaProfileEdit 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.2.2
upstreamCfg OBJECT IDENTIFIER ::= { dbaProfileEdit 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.2.2.1
upstreamFir OBJECT-TYPE
      SYNTAX INTEGER (0..950000)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { upstreamCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.2.2.2
upstreamCir OBJECT-TYPE
      SYNTAX INTEGER (1..950000)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { upstreamCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.2.2.3
upstreamPir OBJECT-TYPE
      SYNTAX INTEGER (512..1000000)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { upstreamCfg 3 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.8.2.2.4
upstreamWeight OBJECT-TYPE
      SYNTAX INTEGER (1..20)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { upstreamCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.2.2.5
upstreamAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            delete(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { upstreamCfg 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.2.3
dnstreamCfg OBJECT IDENTIFIER ::= { dbaProfileEdit 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.2.3.1
dnstreamPir OBJECT-TYPE
      SYNTAX INTEGER (0..1000000)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { dnstreamCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.2.3.2
dnstreamWeight OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { dnstreamCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.2.3.3
dnstreamAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            delete(2)
            }
      MAX-ACCESS read-write
      STATUS current
```

```
      DESCRIPTION
            "Description."
      ::= { dnstreamCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3
srvProfileEdit OBJECT IDENTIFIER ::= { onuProfileCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.1
srvProfileNo OBJECT-TYPE
      SYNTAX INTEGER (1..32767)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { srvProfileEdit 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.2
onuLanCountConfig OBJECT IDENTIFIER ::= { srvProfileEdit 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.2.1
lanCount OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuLanCountConfig 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.2.2
lanCountAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuLanCountConfig 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.3
onuFastLeaveConfig OBJECT IDENTIFIER ::= { srvProfileEdit 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.3.1
ctcFastLeave OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
```

```
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuFastLeaveConfig 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.3.2
ctcFastLeaveAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuFastLeaveConfig 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.4
onuFecModeConfig OBJECT IDENTIFIER ::= { srvProfileEdit 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.4.1
ctcFecMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuFecModeConfig 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.4.2
ctcFecModeAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuFecModeConfig 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.5
ctcMcModeConfig OBJECT IDENTIFIER ::= { srvProfileEdit 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.5.1
ctcMcMode OBJECT-TYPE
      SYNTAX INTEGER
```

```
            {
            snooping(1),
            control(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ctcMcModeConfig 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.5.2
ctcMcModeAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ctcMcModeConfig 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.6
ctcMultiLlidConfig OBJECT IDENTIFIER ::= { srvProfileEdit 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.6.1
ctcMultiLlid OBJECT-TYPE
      SYNTAX INTEGER (0..8)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ctcMultiLlidConfig 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.6.2
ctcMultiLlidAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ctcMultiLlidConfig 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.7
ctcActivePonConfig OBJECT IDENTIFIER ::= { srvProfileEdit 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.7.1
ctcActivePon OBJECT-TYPE
```

```
      SYNTAX INTEGER (0..8)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ctcActivePonConfig 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.7.2
ctcActivePonAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ctcActivePonConfig 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.8
ctcHoldoverConfig OBJECT IDENTIFIER ::= { srvProfileEdit 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.8.1
ctcHoldover OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ctcHoldoverConfig 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.8.2
ctcHoldoverAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ctcHoldoverConfig 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.9
onuMgmtIpCfg OBJECT IDENTIFIER ::= { srvProfileEdit 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.9.1
onuMgmtIpAddr OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
```

```
      DESCRIPTION
            "Description."
      ::= { onuMgmtIpCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.9.2
onuMgmtIpMask OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuMgmtIpCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.9.3
onuMgmtIpGw OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuMgmtIpCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.9.4
onuMgmtCvlan OBJECT-TYPE
      SYNTAX INTEGER (1..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuMgmtIpCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.9.5
onuMgmtSvlan OBJECT-TYPE
      SYNTAX INTEGER (1..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      DEFVAL { 0 }
      ::= { onuMgmtIpCfg 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.9.6
onuMgmtPri OBJECT-TYPE
      SYNTAX INTEGER (0..7)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuMgmtIpCfg 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.9.7
onuMgmtAction OBJECT-TYPE
      SYNTAX INTEGER
```

```
            {
            add(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuMgmtIpCfg 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.10
onuSnmpProParam OBJECT IDENTIFIER ::= { srvProfileEdit 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.10.1
ctcSnmpHost OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSnmpProParam 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.10.2
ctcSnmpTrapPort OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSnmpProParam 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.10.3
ctcSnmpPort OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSnmpProParam 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.10.4
ctcCommunityName OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSnmpProParam 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.10.5
ctcRoCommunityName OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
```

```
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSnmpProParam 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.10.6
ctcRwCommunityName OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSnmpProParam 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.10.7
ctcSnmpAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSnmpProParam 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.11
onuSlaConfig OBJECT IDENTIFIER ::= { srvProfileEdit 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.11.1
ctcSlaEn OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSlaConfig 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.11.2
ctcSlaMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            sp_basic(1),
            wrr(2),
            sp_wrr(3)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
```

```
            "Description."
      ::= { onuSlaConfig 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.11.3
ctcQueueId OBJECT-TYPE
      SYNTAX INTEGER (0..7)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSlaConfig 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.11.4
ctcQueweight OBJECT-TYPE
      SYNTAX INTEGER (0..100)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSlaConfig 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.11.5
ctcGuaranteedBandwidth OBJECT-TYPE
      SYNTAX INTEGER (1..1024)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSlaConfig 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.11.6
ctcBesteffortBandwith OBJECT-TYPE
      SYNTAX INTEGER (1..1024)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSlaConfig 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.11.7
ctcSlaAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSlaConfig 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.12
```

```
onuCtcPause OBJECT IDENTIFIER ::= { srvProfileEdit 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.12.1
pauseEthNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuCtcPause 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.12.2
ctcPauseEn OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuCtcPause 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.12.3
ctcPauseAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuCtcPause 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.13
onuCtcLoopdetect OBJECT IDENTIFIER ::= { srvProfileEdit 13 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.13.1
loopEthNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuCtcLoopdetect 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.13.2
ctcLoopdetectEn OBJECT-TYPE
      SYNTAX INTEGER
            {
```

```
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuCtcLoopdetect 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.13.3
ctcLoopdetectAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuCtcLoopdetect 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.14
onuMcTagstrip OBJECT IDENTIFIER ::= { srvProfileEdit 14 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.14.1
tagstripEthNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuMcTagstrip 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.14.2
ctcTagstripEn OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuMcTagstrip 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.14.3
tagstripAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            remove(2)
            }
```

```
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuMcTagstrip 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.15
onuMcVlanTrans OBJECT IDENTIFIER ::= { srvProfileEdit 15 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.15.1
mcVlanTransEthNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuMcVlanTrans 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.15.2
ctcMcTransVlanStr OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuMcVlanTrans 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.15.10
ctcMcTransAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuMcVlanTrans 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.16
onuPortPhyAdmin OBJECT IDENTIFIER ::= { srvProfileEdit 16 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.16.1
adminEthNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortPhyAdmin 1 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.16.2
ctcPortAdmin OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortPhyAdmin 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.16.3
ctcPortAdminAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            commit(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortPhyAdmin 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.17
onuPortAutoNegConfig OBJECT IDENTIFIER ::= { srvProfileEdit 17 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.17.1
autoNegEthNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortAutoNegConfig 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.17.2
ctcAutoNeg OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortAutoNegConfig 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.17.3
ctcAutoNegAction OBJECT-TYPE
      SYNTAX INTEGER
```

```
            {
            commit(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortAutoNegConfig 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.18
onuPortMaxIgmpGrp OBJECT IDENTIFIER ::= { srvProfileEdit 18 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.18.1
grpEthNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortMaxIgmpGrp 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.18.2
ctcMcMaxGrp OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortMaxIgmpGrp 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.18.3
mcMaxGrpAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            commit(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortMaxIgmpGrp 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.19
onuPortUpLimit OBJECT IDENTIFIER ::= { srvProfileEdit 19 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.19.1
upLimitEthNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
```

```
            "Description."
      ::= { onuPortUpLimit 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.19.2
ctcUpLimitCir OBJECT-TYPE
      SYNTAX INTEGER (0..1048576)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortUpLimit 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.19.3
ctcUpLimitCbs OBJECT-TYPE
      SYNTAX INTEGER (1..10240)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortUpLimit 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.19.4
ctcUpLimitEbs OBJECT-TYPE
      SYNTAX INTEGER (1..10240)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortUpLimit 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.19.5
ctcUpLimitAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            commit(1),
            delete(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortUpLimit 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.20
onuPortDownLimit OBJECT IDENTIFIER ::= { srvProfileEdit 20 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.20.1
downLimitEthNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { onuPortDownLimit 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.20.2
ctcDownLimitCir OBJECT-TYPE
      SYNTAX INTEGER (0..1048576)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortDownLimit 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.20.3
ctcDownLimitPir OBJECT-TYPE
      SYNTAX INTEGER (1..1048576)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortDownLimit 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.20.4
ctcDownLimitAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            commit(1),
            delete(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortDownLimit 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.21
onuPortVlanConfig OBJECT IDENTIFIER ::= { srvProfileEdit 21 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.21.1
portVlanMode OBJECT IDENTIFIER ::= { onuPortVlanConfig 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.21.1.1
vlanModeEthNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portVlanMode 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.21.1.2
ctcVlanMode OBJECT-TYPE
      SYNTAX INTEGER
            {
```

```
            transparent(1),
            tag(2),
            translation(3),
            aggregation(4),
            trunk(5)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portVlanMode 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.21.1.3
vlanModeAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            commit(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portVlanMode 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.21.2
portVlanPvid OBJECT IDENTIFIER ::= { onuPortVlanConfig 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.21.2.1
pvidEthNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portVlanPvid 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.21.2.2
ctcPvidVal OBJECT-TYPE
      SYNTAX INTEGER (1..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portVlanPvid 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.21.2.3
ctcTpidVal OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      DEFVAL { '0'b }
```

```
      ::= { portVlanPvid 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.21.2.4
ctcPvidAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            commit(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portVlanPvid 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.21.3
portVlanTranslate OBJECT IDENTIFIER ::= { onuPortVlanConfig 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.21.3.1
vlanTransEthNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portVlanTranslate 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.21.3.2
ctcTransVlanStr OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      DEFVAL { '0'b }
      ::= { portVlanTranslate 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.21.3.8
ctcTransAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portVlanTranslate 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.21.4
portVlanTrunk OBJECT IDENTIFIER ::= { onuPortVlanConfig 4 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.21.4.1
trunkEthNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portVlanTrunk 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.21.4.2
ctcTrunkVidStr OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      DEFVAL { '0'b }
      ::= { portVlanTrunk 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.21.4.3
ctcTrunkVidAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portVlanTrunk 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.21.5
portVlanAgg OBJECT IDENTIFIER ::= { onuPortVlanConfig 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.21.5.1
aggEthNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portVlanAgg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.21.5.2
ctcAggNewVlan OBJECT-TYPE
      SYNTAX INTEGER (1..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portVlanAgg 2 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.21.5.10
ctcAggVlanStr OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      DEFVAL { '0'b }
      ::= { portVlanAgg 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.21.5.11
ctcAggAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portVlanAgg 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.22
onuIgmpVlanConfig OBJECT IDENTIFIER ::= { srvProfileEdit 22 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.22.2
mcVlanEthNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuIgmpVlanConfig 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.22.3
ctcMcVlanStr OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      DEFVAL { '0'b }
      ::= { onuIgmpVlanConfig 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.22.4
ctcMcValnAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            remove(2)
            }
      MAX-ACCESS read-write
```

```
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuIgmpVlanConfig 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.23
onuClassifyConfig OBJECT IDENTIFIER ::= { srvProfileEdit 23 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.23.1
onuClassifyAdd OBJECT IDENTIFIER ::= { onuClassifyConfig 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.23.1.1
cfyEthNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyAdd 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.23.1.2
ctcPrecedence OBJECT-TYPE
      SYNTAX INTEGER (1..8)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyAdd 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.23.1.3
ctcPri OBJECT-TYPE
      SYNTAX INTEGER (0..7)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyAdd 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.23.1.4
ctcDstMacEqualSel OBJECT-TYPE
      SYNTAX INTEGER
            {
            init(0),
            equal(1),
            unequal(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyAdd 4 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.23.1.5
ctcDstMacValue OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyAdd 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.23.1.6
ctcSrcMacEqualSel OBJECT-TYPE
      SYNTAX INTEGER
            {
            init(0),
            equal(1),
            unequal(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyAdd 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.23.1.7
ctcSrcMacValue OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyAdd 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.23.1.8
ctcVlanEqualSel OBJECT-TYPE
      SYNTAX INTEGER
            {
            init(0),
            equal(1),
            unequal(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyAdd 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.23.1.9
ctcVlanValue OBJECT-TYPE
      SYNTAX INTEGER (0..4094)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyAdd 9 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.23.1.10
ctcCosEqualSel OBJECT-TYPE
      SYNTAX INTEGER
            {
            init(0),
            equal(1),
            unequal(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyAdd 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.23.1.11
ctcCosValue OBJECT-TYPE
      SYNTAX INTEGER (-1..7)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyAdd 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.23.1.12
ctcEthTypeEqualSel OBJECT-TYPE
      SYNTAX INTEGER
            {
            init(0),
            equal(1),
            unequal(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyAdd 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.23.1.13
ctcEthTypeValue OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyAdd 13 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.23.1.14
ctcSrcIpEqualSel OBJECT-TYPE
      SYNTAX INTEGER
            {
            init(0),
            equal(1),
            unequal(2)
            }
```

```
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyAdd 14 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.23.1.15
ctcSrcIpValue OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyAdd 15 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.23.1.16
ctcDestIpEqualSel OBJECT-TYPE
      SYNTAX INTEGER
            {
            init(0),
            equal(1),
            unequal(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyAdd 16 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.23.1.17
ctcDestIpValue OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyAdd 17 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.23.1.18
ctcProEqualSel OBJECT-TYPE
      SYNTAX INTEGER
            {
            init(0),
            equal(1),
            unequal(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyAdd 18 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.23.1.19
ctcProValue OBJECT-TYPE
```

```
      SYNTAX INTEGER (-1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyAdd 19 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.23.1.20
ctcTosDscpEuqalSel OBJECT-TYPE
      SYNTAX INTEGER
            {
            init(0),
            equal(1),
            unequal(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyAdd 20 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.23.1.21
ctcTosDscpValue OBJECT-TYPE
      SYNTAX INTEGER (-1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyAdd 21 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.23.1.22
ctcSrcPortEqualSel OBJECT-TYPE
      SYNTAX INTEGER
            {
            init(0),
            equal(1),
            unequal(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyAdd 22 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.23.1.23
ctcSrcPortValue OBJECT-TYPE
      SYNTAX INTEGER (-1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyAdd 23 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.23.1.24
```

```
ctcDestPortEqualSel OBJECT-TYPE
      SYNTAX INTEGER
            {
            init(0),
            equal(1),
            unequal(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyAdd 24 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.23.1.25
ctcDestPortValue OBJECT-TYPE
      SYNTAX INTEGER (-1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyAdd 25 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.23.1.26
ctcCfyAction OBJECT-TYPE
      SYNTAX INTEGER { add(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyAdd 26 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.23.1.27
ctcQueue OBJECT-TYPE
      SYNTAX Integer32 (0..7)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyAdd 27 }

-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.23.2
onuClassifyDel OBJECT IDENTIFIER ::= { onuClassifyConfig 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.23.2.1
cfyDelEthNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyDel 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.23.2.2
ctcDelPrecedence OBJECT-TYPE
```

```
      SYNTAX INTEGER (1..8)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyDel 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.23.2.3
ctcCfyDelAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            delete(1),
            clearAll(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyDel 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.24
onuMacAgetime OBJECT IDENTIFIER ::= { srvProfileEdit 24 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.24.1
ctcAgetime OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuMacAgetime 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.24.2
agetimeAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            commit(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuMacAgetime 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.25
onuPonProtect OBJECT IDENTIFIER ::= { srvProfileEdit 25 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.25.1
ctcLosOptical OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-write
      STATUS current
```

```
      DESCRIPTION
            "Description."
      ::= { onuPonProtect 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.25.2
ctcLosMpcp OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPonProtect 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.25.3
ctcPonProtectAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            commit(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPonProtect 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.26
onuPowerSaveConfig OBJECT IDENTIFIER ::= { srvProfileEdit 26 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.26.1
ctcEarlyWakeupEn OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPowerSaveConfig 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.26.2
ctcSleepDurationMax OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPowerSaveConfig 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.26.3
onuPowerSaveAction OBJECT-TYPE
```

```
      SYNTAX INTEGER
            {
            commit(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPowerSaveConfig 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.27
onuPwSavParameter OBJECT IDENTIFIER ::= { srvProfileEdit 27 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.27.1
ctcSleepDuration OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPwSavParameter 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.27.2
ctcWakeDuration OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPwSavParameter 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.27.3
ctcSleepFlag OBJECT-TYPE
      SYNTAX INTEGER
            {
            off(1),
            on(2),
            change(3)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPwSavParameter 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.27.4
ctcSleepMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            none(1),
            txSleepOnly(2),
            txAndRxSleep(3)
            }
```

```
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPwSavParameter 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.27.5
onuPwSavAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            commit(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPwSavParameter 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.28
onuDisableLoopConfig OBJECT IDENTIFIER ::= { srvProfileEdit 28 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.28.1
disLoopEthNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuDisableLoopConfig 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.28.2
disableLoopEn OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuDisableLoopConfig 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.28.3
disLoopEthAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            delete(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
```

```
            "Description."
      ::= { onuDisableLoopConfig 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.29
onuPortStatConfig OBJECT IDENTIFIER ::= { srvProfileEdit 29 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.29.1
portStatEthNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatConfig 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.29.2
ctcMonitorStatus OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatConfig 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.29.3
ctcStatCycle OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatConfig 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.29.4
portStatAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatConfig 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.30
onuPortStatClear OBJECT IDENTIFIER ::= { srvProfileEdit 30 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.30.1
ctcClearEthNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatClear 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.30.2
ctcClearAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatClear 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.31
onuIgmpAdmin OBJECT IDENTIFIER ::= { srvProfileEdit 31 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.31.1
igmpAdmin OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuIgmpAdmin 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.31.2
igmpAdminAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuIgmpAdmin 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.32
onuCatvEnable OBJECT IDENTIFIER ::= { srvProfileEdit 32 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.32.1
catvEnable OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuCatvEnable 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.32.2
catvEnableAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuCatvEnable 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.33
onuCtcoamSkip OBJECT IDENTIFIER ::= { srvProfileEdit 33 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.33.1
ctcoamSkip OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuCtcoamSkip 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.33.2
ctcoamSkipAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { onuCtcoamSkip 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.34
onuWifiSwich OBJECT IDENTIFIER ::= { srvProfileEdit 34 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.34.1
wlanApmoduleEnable OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWifiSwich 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.34.2
wlanCountry OBJECT-TYPE
      SYNTAX INTEGER
            {
            ETSI(0),
            FCC(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWifiSwich 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.34.3
wlanChannel OBJECT-TYPE
      SYNTAX INTEGER (0..13)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWifiSwich 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.34.4
wlanStandard OBJECT-TYPE
      SYNTAX INTEGER
            {
            s80211b(0),
            s80211g(1),
            s80211bg(2),
            s80211n(3),
            s80211bgn(4)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { onuWifiSwich 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.34.5
wlanPower OBJECT-TYPE
      SYNTAX INTEGER (0..20)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWifiSwich 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.34.6
wlanSwichAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWifiSwich 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.35
onuWifiSsid OBJECT IDENTIFIER ::= { srvProfileEdit 35 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.35.1
ssidId OBJECT-TYPE
      SYNTAX Integer32 (1..4)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWifiSsid 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.35.2
ssidName OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWifiSsid 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.35.3
ssidEnable OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
```

```
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWifiSsid 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.35.4
ssidHide OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWifiSsid 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.35.5
ssidAuthMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            open(1),
            shared(2),
            wepauto(3),
            wpapsk(4),
            wpa(5),
            wpa2psk(6),
            wpa2(7),
            wpa_wpa2(8),
            wpapsk_wpa2psk(9)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWifiSsid 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.35.6
ssidEncrypTpye OBJECT-TYPE
      SYNTAX INTEGER
            {
            none(1),
            wep(2),
            tkip(3),
            aes(4),
            tkipaes(5)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWifiSsid 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.35.7
```

```
ssidPresharedKey OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWifiSsid 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.35.8
ssidRekeyInterval OBJECT-TYPE
      SYNTAX Integer32 (0..4194303)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWifiSsid 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.35.9
ssidRadiusServIpType OBJECT-TYPE
      SYNTAX INTEGER
            {
            ipv4(1),
            ipv6(2),
            ipv4z(3),
            ipv6z(4),
            dns(16)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWifiSsid 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.35.10
ssidRadiusSerIp OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWifiSsid 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.35.11
ssidRadiusServIpPrefixLen OBJECT-TYPE
      SYNTAX Integer32 (0..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWifiSsid 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.35.12
ssidRadiusPort OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
```

```
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWifiSsid 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.35.13
ssidRadiusKey OBJECT-TYPE
      SYNTAX OCTET STRING (SIZE (0..32))
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWifiSsid 13 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.35.14
ssidWepEncryptionLevel OBJECT-TYPE
      SYNTAX INTEGER
            {
            s64bit(1),
            s128bit(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWifiSsid 14 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.35.15
ssidWepKeyIndex OBJECT-TYPE
      SYNTAX Integer32 (1..4)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWifiSsid 15 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.35.16
ssidWepKey1 OBJECT-TYPE
      SYNTAX OCTET STRING (SIZE (0..32))
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWifiSsid 16 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.35.17
ssidWepKey2 OBJECT-TYPE
      SYNTAX OCTET STRING (SIZE (0..32))
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWifiSsid 17 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.35.18
ssidWepKey3 OBJECT-TYPE
      SYNTAX OCTET STRING (SIZE (0..32))
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWifiSsid 18 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.35.19
ssidWepKey4 OBJECT-TYPE
      SYNTAX OCTET STRING (SIZE (0..32))
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWifiSsid 19 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.35.20
ssidAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWifiSsid 20 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.36
onuWanConn OBJECT IDENTIFIER ::= { srvProfileEdit 36 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.36.1
wanConnAdd OBJECT IDENTIFIER ::= { onuWanConn 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.36.1.1
connType OBJECT-TYPE
      SYNTAX INTEGER
            {
            bridge(0),
            route(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { wanConnAdd 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.36.1.2
```

```
connAddAction OBJECT-TYPE
      SYNTAX INTEGER { add(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { wanConnAdd 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.36.2
wanConnDelete OBJECT IDENTIFIER ::= { onuWanConn 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.36.2.1
connIndexD OBJECT-TYPE
      SYNTAX Integer32 (1..8)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { wanConnDelete 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.36.2.2
connDeleteAction OBJECT-TYPE
      SYNTAX INTEGER { delete(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { wanConnDelete 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.36.3
wanConnCfg OBJECT IDENTIFIER ::= { onuWanConn 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.36.3.1
connIndex OBJECT-TYPE
      SYNTAX INTEGER (1..8)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { wanConnCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.36.3.2
connBindLan OBJECT-TYPE
      SYNTAX INTEGER (0..15)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { wanConnCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.36.3.3
connBindSsid OBJECT-TYPE
```

```
      SYNTAX INTEGER (0..15)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { wanConnCfg 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.36.3.4
wanMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            internet(0),
            multicast(1),
            tr069(2),
            tr069_internet(3),
            tr069_voip(4),
            voip_internet(5),
            tr069_voip_internet(6),
            other(100)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { wanConnCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.36.3.5
connTypeCfg OBJECT-TYPE
      SYNTAX INTEGER
            {
            bridge(0),
            route(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { wanConnCfg 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.36.3.6
connVlanId OBJECT-TYPE
      SYNTAX Integer32 (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { wanConnCfg 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.36.3.7
connCos OBJECT-TYPE
      SYNTAX INTEGER (0..7)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { wanConnCfg 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.36.3.8
connNatEnable OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { wanConnCfg 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.36.3.9
connModeCfg OBJECT-TYPE
      SYNTAX INTEGER
            {
            dhcp(0),
            static(1),
            pppoe(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { wanConnCfg 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.36.3.10
connIpAddress OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { wanConnCfg 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.36.3.11
connIpMask OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { wanConnCfg 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.36.3.12
connGateway OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { wanConnCfg 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.36.3.13
connMasterDns OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { wanConnCfg 13 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.36.3.14
connSlaveDns OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { wanConnCfg 14 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.36.3.15
connPppoeProxy OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { wanConnCfg 15 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.36.3.16
connPppoeUsername OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { wanConnCfg 16 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.36.3.17
connPppoePassword OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { wanConnCfg 17 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.36.3.18
connPppoeSerName OBJECT-TYPE
```

```
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { wanConnCfg 18 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.36.3.19
connPppoeMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            autoConnect(0),
            connecWhenPayload(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { wanConnCfg 19 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.36.3.20
connQosEnable OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { wanConnCfg 20 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.36.3.21
connVlanMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            tag(1),
            transparent(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { wanConnCfg 21 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.36.3.22
connTranslationEnable OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
```

```
      STATUS current
      DESCRIPTION
            "Description."
      ::= { wanConnCfg 22 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.36.3.23
connTranslationVlan OBJECT-TYPE
      SYNTAX INTEGER (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { wanConnCfg 23 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.36.3.24
connTranslationCos OBJECT-TYPE
      SYNTAX INTEGER (0..7)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { wanConnCfg 24 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.36.3.25
connQinqEnable OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { wanConnCfg 25 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.36.3.26
connQinqTpid OBJECT-TYPE
      SYNTAX Integer32 (0..65534)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { wanConnCfg 26 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.36.3.27
connWanSvlan OBJECT-TYPE
      SYNTAX INTEGER (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { wanConnCfg 27 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.36.3.28
connSvlanCos OBJECT-TYPE
      SYNTAX INTEGER (0..7)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { wanConnCfg 28 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.36.3.29
connCfgAction OBJECT-TYPE
      SYNTAX INTEGER { add(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { wanConnCfg 29 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.36.4
wanConnCommit OBJECT IDENTIFIER ::= { onuWanConn 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.36.4.1
connCommitAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            commit(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { wanConnCommit 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.37
onuPortMacLimit OBJECT IDENTIFIER ::= { srvProfileEdit 37 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.37.1
macLimitEthNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortMacLimit 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.37.2
macLimit OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
```

```
            "Description."
      ::= { onuPortMacLimit 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.37.3
macLimitAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortMacLimit 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.38
onuPortPkgSuppress OBJECT IDENTIFIER ::= { srvProfileEdit 38 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.38.1
pkgSuppressEthNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortPkgSuppress 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.38.2
pkgBroadcast OBJECT-TYPE
      SYNTAX INTEGER (0..1024000)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortPkgSuppress 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.38.3
pkgMulticast OBJECT-TYPE
      SYNTAX INTEGER (0..1024000)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortPkgSuppress 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.38.4
pkgUnknown OBJECT-TYPE
      SYNTAX INTEGER (0..1024000)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { onuPortPkgSuppress 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.38.5
pkgSuppressAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortPkgSuppress 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.39
onuPortIsolateEnable OBJECT IDENTIFIER ::= { srvProfileEdit 39 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.39.1
portIsolateEnable OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortIsolateEnable 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.39.2
portIsolateAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortIsolateEnable 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.40
onuPortModeControl OBJECT IDENTIFIER ::= { srvProfileEdit 40 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.40.1
modeControlEthNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
```

```
            "Description."
      ::= { onuPortModeControl 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.40.2
modeControl OBJECT-TYPE
      SYNTAX INTEGER
            {
            s10hd(1),
            s10fd(2),
            s100hd(3),
            s100fd(4),
            s1000hd(5),
            s1000fd(6),
            s10000fd(7)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortModeControl 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.40.3
modeControlAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortModeControl 3 }

-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.41
onuDhcpServer OBJECT IDENTIFIER ::= { srvProfileEdit 41 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.41.1
dhcpLanip OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuDhcpServer 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.41.2
dhcplanMask OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuDhcpServer 2 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.41.3
dhcpServerEnable OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1),
            relay(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuDhcpServer 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.41.4
dhcpLease OBJECT-TYPE
      SYNTAX Unsigned32 (0..4294967295)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuDhcpServer 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.41.5
dhcpBeginIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuDhcpServer 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.41.6
dhcpEndIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuDhcpServer 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.41.7
dhcpPoolType OBJECT-TYPE
      SYNTAX INTEGER
            {
            pc(0),
            camera(1),
            stb(2),
            ip_phone(3)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { onuDhcpServer 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.41.8
dhcpMasterDns OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuDhcpServer 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.41.9
dhcpSlaveDns OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuDhcpServer 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.41.10
dhcpGateway OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuDhcpServer 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.41.11
dhcpRelayIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuDhcpServer 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.41.12
dhcpAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            commit(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuDhcpServer 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.42
onuDhcpOption82 OBJECT IDENTIFIER ::= { srvProfileEdit 42 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.42.1
dhcpOption82Enable OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuDhcpOption82 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.42.2
dhcpOption82Action OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuDhcpOption82 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.43
onuPPPoE OBJECT IDENTIFIER ::= { srvProfileEdit 43 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.43.1
pppoeEnable OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPPPoE 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.43.2
pppoeAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { onuPPPoE 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.44
onuDhcpV6 OBJECT IDENTIFIER ::= { srvProfileEdit 44 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.44.1
dhcpV6Option18Enable OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuDhcpV6 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.44.2
dhcpV6Option37Enable OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuDhcpV6 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.3.44.3
dhcpV6Action OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuDhcpV6 3 }



-- 1.3.6.1.4.1.37950.1.1.5.12.8.4
voipProfileEdit OBJECT IDENTIFIER ::= { onuProfileCfg 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.1
voipProfileNo OBJECT-TYPE
      SYNTAX INTEGER (1..32767)
      MAX-ACCESS read-write
      STATUS current
```

```
      DESCRIPTION
            "Description."
      ::= { voipProfileEdit 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.2
onuPotsCountConfig OBJECT IDENTIFIER ::= { voipProfileEdit 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.2.1
potsCount OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPotsCountConfig 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.2.2
potsCountAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            commit(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPotsCountConfig 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.3
voipGlobalConfig OBJECT IDENTIFIER ::= { voipProfileEdit 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.3.1
ctcIpMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            staticip(0),
            dhcp(1),
            pppoe(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipGlobalConfig 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.3.2
ctcStaticIpAddr OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { voipGlobalConfig 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.3.3
ctcStaticIpMask OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipGlobalConfig 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.3.4
ctcStaticIpGw OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipGlobalConfig 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.3.5
ctcPppoeMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            auto(1),
            chap(2),
            pap(3)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipGlobalConfig 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.3.6
ctcPppoeUsr OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipGlobalConfig 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.3.7
ctcPppoePw OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipGlobalConfig 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.3.8
```

```
voipVlanMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            transparent(1),
            tag(2),
            vlan_stacking(3)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipGlobalConfig 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.3.9
voipCvlan OBJECT-TYPE
      SYNTAX INTEGER (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipGlobalConfig 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.3.10
voipSvlan OBJECT-TYPE
      SYNTAX INTEGER (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      DEFVAL { 0 }
      ::= { voipGlobalConfig 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.3.11
voipPri OBJECT-TYPE
      SYNTAX INTEGER (0..7)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      DEFVAL { 5 }
      ::= { voipGlobalConfig 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.3.12
ctcVoipGlobalAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      DEFVAL { 1 }
      ::= { voipGlobalConfig 12 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.4
voipH248Config OBJECT IDENTIFIER ::= { voipProfileEdit 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.4.1
h248ProParamConfig OBJECT IDENTIFIER ::= { voipH248Config 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.4.1.1
ctcMgPort OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      DEFVAL { 2944 }
      ::= { h248ProParamConfig 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.4.1.2
ctcMgcIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248ProParamConfig 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.4.1.3
ctcMgComPort OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248ProParamConfig 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.4.1.4
ctcBakMgcIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248ProParamConfig 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.4.1.5
ctcBakMgcPort OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      DEFVAL { 0 }
```

```
      ::= { h248ProParamConfig 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.4.1.6
ctcRegMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            ip_addr(0),
            realm(1),
            device(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      DEFVAL { 0 }
      ::= { h248ProParamConfig 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.4.1.7
ctcMID OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248ProParamConfig 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.4.1.8
ctcHeartbeatMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            h248(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248ProParamConfig 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.4.1.9
ctcHeartbeatCycle OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      DEFVAL { 60 }
      ::= { h248ProParamConfig 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.4.1.10
ctcHeartbeatCount OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
```

```
      DESCRIPTION
            "Description."
      DEFVAL { 3 }
      ::= { h248ProParamConfig 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.4.1.11
ctcH248ProParamAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248ProParamConfig 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.4.2
h248RtpTidConfig OBJECT IDENTIFIER ::= { voipH248Config 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.4.2.1
ctcRtpTidNumber OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248RtpTidConfig 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.4.2.2
ctcRtpTidPrefix OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248RtpTidConfig 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.4.2.3
ctcDigitBegin0 OBJECT-TYPE
      SYNTAX Unsigned32 (0..4294967295)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248RtpTidConfig 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.4.2.4
ctcDigitBegin1 OBJECT-TYPE
      SYNTAX Unsigned32 (0..4294967295)
      MAX-ACCESS read-write
      STATUS current
```

```
      DESCRIPTION
            "Description."
      ::= { h248RtpTidConfig 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.4.2.5
ctcRtpTidMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            align(1),
            unalign(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248RtpTidConfig 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.4.2.6
ctcDigitLength OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248RtpTidConfig 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.4.2.7
ctcRtpTidAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248RtpTidConfig 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.4.3
h248UserTidConfig OBJECT IDENTIFIER ::= { voipH248Config 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.4.3.1
ctcUserTidPotsNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248UserTidConfig 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.4.3.2
ctcUserTid OBJECT-TYPE
```

```
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248UserTidConfig 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.4.3.3
ctcUserTidAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248UserTidConfig 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.5
voipSipConfig OBJECT IDENTIFIER ::= { voipProfileEdit 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.5.1
sipProParamConfig OBJECT IDENTIFIER ::= { voipSipConfig 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.5.1.1
ctcMgPortVal OBJECT-TYPE
      SYNTAX Integer32 (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipProParamConfig 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.5.1.2
ctcProxySrvIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipProParamConfig 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.5.1.3
ctcProxySrvPort OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipProParamConfig 3 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.5.1.4
ctcBakProxySrvIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipProParamConfig 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.5.1.5
ctcBakProxySrvPort OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      DEFVAL { 0 }
      ::= { sipProParamConfig 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.5.1.6
ctcRegSrvIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipProParamConfig 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.5.1.7
ctcRegSrvPort OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipProParamConfig 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.5.1.8
ctcBakRegSrvIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipProParamConfig 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.5.1.9
ctcBakRegSrvPort OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
```

```
      DEFVAL { 0 }
      ::= { sipProParamConfig 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.5.1.10
ctcOutBoundServIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipProParamConfig 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.5.1.11
ctcOutBoundServPort OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipProParamConfig 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.5.1.12
ctcRegInterVal OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      DEFVAL { 0 }
      ::= { sipProParamConfig 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.5.1.13
ctcHbeartEn OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipProParamConfig 13 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.5.1.14
ctcHbeatCycle OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      DEFVAL { 60 }
      ::= { sipProParamConfig 14 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.5.1.15
ctcHbeatCount OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      DEFVAL { 3 }
      ::= { sipProParamConfig 15 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.5.1.16
ctcRegSrvAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipProParamConfig 16 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.5.2
sipUserParamConfig OBJECT IDENTIFIER ::= { voipSipConfig 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.5.2.1
ctcUserPotsNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipUserParamConfig 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.5.2.2
ctcUserAccount OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipUserParamConfig 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.5.2.3
ctcUserName OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipUserParamConfig 3 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.5.2.4
ctcUserPw OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipUserParamConfig 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.5.2.5
ctcUserAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipUserParamConfig 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.5.3
sipDigitConfig OBJECT IDENTIFIER ::= { voipSipConfig 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.5.3.1
ctcDigitNum OBJECT-TYPE
      SYNTAX Integer32 (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipDigitConfig 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.5.3.2
ctcDigitNumBlock OBJECT-TYPE
      SYNTAX Integer32 (0..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipDigitConfig 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.5.3.3
ctcDigitMap OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipDigitConfig 3 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.5.3.4
ctcDigitMapAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            commit(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipDigitConfig 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.6
voipFaxModemCfg OBJECT IDENTIFIER ::= { voipProfileEdit 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.6.1
ctcT38En OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipFaxModemCfg 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.6.2
ctcControl OBJECT-TYPE
      SYNTAX INTEGER
            {
            negotiation(1),
            autovbd(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipFaxModemCfg 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.6.3
ctcFaxModemAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipFaxModemCfg 3 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.7
voipPotsManage OBJECT IDENTIFIER ::= { voipProfileEdit 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.7.1
ctcPotsNo OBJECT-TYPE
      SYNTAX Integer32 (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipPotsManage 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.7.2
ctcPotsEnable OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipPotsManage 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.7.3
ctcPotsMgAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipPotsManage 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.8
voipTimerConfig OBJECT IDENTIFIER ::= { voipProfileEdit 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.8.1
maxWaitTime OBJECT-TYPE
      SYNTAX Integer32 (0..254)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipTimerConfig 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.8.2
startTimer OBJECT-TYPE
```

```
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipTimerConfig 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.8.3
longTimer OBJECT-TYPE
      SYNTAX Integer32 (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipTimerConfig 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.8.4
shortTimer OBJECT-TYPE
      SYNTAX Integer32 (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipTimerConfig 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.8.5
digitmapNotify OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipTimerConfig 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.8.6
voipTimerAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipTimerConfig 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.9
voipPotsParameter OBJECT IDENTIFIER ::= { voipProfileEdit 9 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.9.1
priPotsPtNo OBJECT-TYPE
      SYNTAX Integer32 (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipPotsParameter 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.9.2
priVad OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipPotsParameter 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.9.3
priEchoCancel OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipPotsParameter 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.9.4
priInputGain OBJECT-TYPE
      SYNTAX Integer32 (-32..32)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipPotsParameter 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.9.5
priOutputGain OBJECT-TYPE
      SYNTAX Integer32 (-32..32)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipPotsParameter 5 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.9.6
priDtmfMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            transparent(0),
            rfc2833(1),
            rfc2833_redundancy(2),
            outband(3)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipPotsParameter 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.9.7
priPotsParameterAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipPotsParameter 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.10
onuVoipParam OBJECT IDENTIFIER ::= { voipProfileEdit 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.10.1
ipMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            static(1),
            dhcp(2),
            pppoe(3)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuVoipParam 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.10.2
ip OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuVoipParam 2 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.10.3
mask OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuVoipParam 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.10.4
gw OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuVoipParam 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.10.5
rtpIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuVoipParam 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.10.6
rtpMask OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuVoipParam 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.10.7
rtpGw OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuVoipParam 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.10.8
dnsMaster OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuVoipParam 8 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.10.9
dnsSlave OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuVoipParam 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.10.10
dhcpOption60Enable OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuVoipParam 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.10.11
dhcpOption60Base OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuVoipParam 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.10.12
dhcpOption60Value OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuVoipParam 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.10.13
pppoeMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            auto(0),
            chap(1),
            pap(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuVoipParam 13 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.10.14
pppoeUsername OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuVoipParam 14 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.10.15
pppoePassword OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuVoipParam 15 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.10.16
svlanTpid OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuVoipParam 16 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.10.17
svlanId OBJECT-TYPE
      SYNTAX Integer32 (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuVoipParam 17 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.10.18
svlanCos OBJECT-TYPE
      SYNTAX Integer32 (0..7)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuVoipParam 18 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.10.19
cvlanTpid OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuVoipParam 19 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.10.20
cvlanId OBJECT-TYPE
      SYNTAX Integer32 (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuVoipParam 20 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.10.21
cvlanCos OBJECT-TYPE
      SYNTAX Integer32 (0..7)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuVoipParam 21 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.10.22
rtpSVlanTpid OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuVoipParam 22 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.10.23
rtpSVlanId OBJECT-TYPE
      SYNTAX Integer32 (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuVoipParam 23 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.10.24
rtpSVlanCos OBJECT-TYPE
      SYNTAX Integer32 (0..7)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuVoipParam 24 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.10.25
rtpCVlanTpid OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { onuVoipParam 25 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.10.26
rtpCVlanId OBJECT-TYPE
      SYNTAX Integer32 (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuVoipParam 26 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.10.27
rtpCVlanCos OBJECT-TYPE
      SYNTAX Integer32 (0..7)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuVoipParam 27 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.10.28
voipParamAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            commit(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuVoipParam 28 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.11
onuSipParam OBJECT IDENTIFIER ::= { voipProfileEdit 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.11.1
proxyServName OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSipParam 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.11.2
proxyServPort OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSipParam 2 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.11.3
bakProxyServName OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSipParam 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.11.4
bakProxyServPort OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSipParam 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.11.5
regServName OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSipParam 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.11.6
regServPort OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSipParam 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.11.7
bakRegServName OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSipParam 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.11.8
bakRegServPort OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { onuSipParam 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.11.9
outBndServName OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSipParam 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.11.10
outBndServPort OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSipParam 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.11.11
sipParamMgPort OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSipParam 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.11.12
regInterval OBJECT-TYPE
      SYNTAX Integer32 (0..10000000)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSipParam 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.11.13
hBeatCfg OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            active(1),
            passive(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSipParam 13 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.11.14
```

```
hBeatCycle OBJECT-TYPE
      SYNTAX Integer32 (1..65525)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSipParam 14 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.11.15
hBeatCount OBJECT-TYPE
      SYNTAX Integer32 (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSipParam 15 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.4.11.16
sipGloParamAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            commit(1),
            remove(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSipParam 16 }



-- 1.3.6.1.4.1.37950.1.1.5.12.8.5
alarmProfileEdit OBJECT IDENTIFIER ::= { onuProfileCfg 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.2
alarmProfileNo OBJECT-TYPE
      SYNTAX INTEGER (1..32767)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmProfileEdit 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.3
alarmOnuConfig OBJECT IDENTIFIER ::= { alarmProfileEdit 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.3.1
alarmOnuTpye OBJECT-TYPE
      SYNTAX INTEGER
            {
            equipmemAlarm(1),
            powerAlarm(2),
            batteryMiss(3),
```

```
            batteryFail(4),
            physicalLntrusion(5),
            selfTestFail(6),
            iadConFail(7),
            ponIfSwitch(8),
            sleepStatusUpdate(9)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOnuConfig 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.3.2
alarmOnuEn OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOnuConfig 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.3.3
alarmOnuAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            commit(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOnuConfig 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.4
onuTempAlarm OBJECT IDENTIFIER ::= { alarmProfileEdit 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.4.1
onuTempAlarmType OBJECT-TYPE
      SYNTAX INTEGER
            {
            onuTempHighAarm(1),
            onuTempLowAlarm(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuTempAlarm 1 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.4.2
onuTempAlarmEn OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuTempAlarm 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.4.3
onuTempAlarmThld OBJECT-TYPE
      SYNTAX INTEGER (-1280..1280)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuTempAlarm 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.4.4
onuTempClearThld OBJECT-TYPE
      SYNTAX INTEGER (-1280..1280)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuTempAlarm 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.4.5
onuTempAlarmAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            commit(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuTempAlarm 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.5
onuVccLowAlarm OBJECT IDENTIFIER ::= { alarmProfileEdit 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.5.1
onuVccAlarmEn OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
```

```
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuVccLowAlarm 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.5.2
onuVccAlarmThld OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuVccLowAlarm 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.5.3
onuVccClearThld OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuVccLowAlarm 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.5.4
onuVccAlarmAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            delete(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuVccLowAlarm 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.6
ponVccAlarm OBJECT IDENTIFIER ::= { alarmProfileEdit 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.6.1
ponVccAlarmType OBJECT-TYPE
      SYNTAX INTEGER
            {
            vccHighAlarm(1),
            vccLowAlarm(2),
            vccHighWarn(3),
            vccLowWarn(4)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { ponVccAlarm 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.6.2
ponVccAlarmTypeEn OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponVccAlarm 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.6.3
ponVccAlarmThld OBJECT-TYPE
      SYNTAX INTEGER (0..65)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponVccAlarm 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.6.4
ponVccClearThld OBJECT-TYPE
      SYNTAX INTEGER (0..65)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponVccAlarm 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.6.5
ponVccAlarmAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            delete(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponVccAlarm 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.7
ponBiasAlarm OBJECT IDENTIFIER ::= { alarmProfileEdit 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.7.1
ponBiasAlarmType OBJECT-TYPE
      SYNTAX INTEGER
            {
```

```
            txBiasHighAlarm(1),
            txBiasLowAlarm(2),
            txBiasHighWarn(3),
            txBiasLowWarn(4)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponBiasAlarm 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.7.2
ponBiasAlarmTypeEn OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponBiasAlarm 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.7.3
ponBiasAlarmThld OBJECT-TYPE
      SYNTAX INTEGER (0..1310)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponBiasAlarm 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.7.4
ponBiasClearThld OBJECT-TYPE
      SYNTAX INTEGER (0..1310)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponBiasAlarm 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.7.5
ponBiasAlarmAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            delete(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponBiasAlarm 5 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.8
ponPowerAlarm OBJECT IDENTIFIER ::= { alarmProfileEdit 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.8.1
ponPowerAlarmType OBJECT-TYPE
      SYNTAX INTEGER
            {
            rxPowerHighAlarm(1),
            rxPowerLowAlarm(2),
            txPowerHighAlarm(3),
            txPowerLowAlarm(4),
            rxPowerHighWarn(5),
            rxPowerLowWarn(6),
            txPowerHighWarn(7),
            txPowerLowWarn(8)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPowerAlarm 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.8.2
ponPowerAlarmTypeEn OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPowerAlarm 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.8.3
ponPowerAlarmThld OBJECT-TYPE
      SYNTAX INTEGER (-400..82)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPowerAlarm 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.8.4
ponPowerClearThld OBJECT-TYPE
      SYNTAX INTEGER (-400..82)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPowerAlarm 4 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.8.5
ponPowerAlarmAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            delete(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponPowerAlarm 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.9
ponTempAlarm OBJECT IDENTIFIER ::= { alarmProfileEdit 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.9.1
ponTempAlarmType OBJECT-TYPE
      SYNTAX INTEGER
            {
            tempHighAlarm(1),
            tempLowAlarm(2),
            tempHighWarn(3),
            tempLowWarn(4)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponTempAlarm 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.9.2
ponTempAlarmTypeEn OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponTempAlarm 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.9.3
ponTempAlarmThld OBJECT-TYPE
      SYNTAX INTEGER (-1280..1280)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponTempAlarm 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.9.4
```

```
ponTempClearThld OBJECT-TYPE
      SYNTAX INTEGER (-1280..1280)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponTempAlarm 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.9.5
ponTempAlarmAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            delete(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponTempAlarm 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.10
ponStatAlarm OBJECT IDENTIFIER ::= { alarmProfileEdit 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.10.1
ponStatAlarmType OBJECT-TYPE
      SYNTAX INTEGER
            {
            downstreamDropEventsAlarm(1),
            upstreamDropEventsAlarm(2),
            downstreamCRCErrorFramesAlarm(3),
            upstreamCRCErrorFramesAlarm(4),
            downstreamUndersizeFramesAlarm(5),
            upstreamUndersizeFramesAlarm(6),
            downstreamOversizeFramesAlarm(7),
            upstreamOversizeFramesAlarm(8),
            downstreamFragmentsAlarm(9),
            upstreamFragmentsAlarm(10),
            downstreamJabbersAlarm(11),
            upstreamJabbersAlarm(12),
            downstreamDiscardsAlarm(13),
            upstreamDiscardsAlarm(14),
            downstreamErrorsAlarm(15),
            upstreamErrorsAlarm(16),
            downstreamDropEventsWarning(17),
            upstreamDropEventsWarning(18),
            downstreamCRCErrorFramesWarning(19),
            upstreamCRCErrorFramesWarning(20),
            downstreamUndersizeFramesWarning(21),
            upstreamUndersizeFramesWarning(22),
            downstreamOversizeFramesWarning(23),
            upstreamOversizeFramesWarning(24),
            downstreamFragmentsWarning(25),
            upstreamFragmentsWarning(26),
            downstreamJabbersWarning(27),
            upstreamJabbersWarning(28),
```

```
            downstreamDiscardsWarning(29),
            upstreamDiscardsWarning(30),
            downstreamErrorsWarning(31),
            upstreamErrorsWarning(32)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponStatAlarm 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.10.2
ponStatAlarmTypeEn OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponStatAlarm 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.10.3
ponStatAlarmThld OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponStatAlarm 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.10.4
ponStatAlarmAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            delete(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ponStatAlarm 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.11
portAlarmStatus OBJECT IDENTIFIER ::= { alarmProfileEdit 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.11.1
portAlarmEthNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
```

```
      DESCRIPTION
            "Description."
      ::= { portAlarmStatus 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.11.2
portAlarmStatusType OBJECT-TYPE
      SYNTAX INTEGER
            {
            ethPortAutoNegFailure(1),
            ethPortLos(2),
            ethPortFailure(3),
            ethPortLoopback(4),
            ethPortCongestion(5)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portAlarmStatus 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.11.3
portAlarmStatusEn OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portAlarmStatus 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.11.4
portAlarmStatusAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            delete(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portAlarmStatus 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.12
portStatAlarm OBJECT IDENTIFIER ::= { alarmProfileEdit 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.12.1
portStatAlarmEthNo OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
```

```
      DESCRIPTION
            "Description."
      ::= { portStatAlarm 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.12.2
portStatAlarmType OBJECT-TYPE
      SYNTAX INTEGER
            {
            downstreamDropEventsAlarm(1),
            upstreamDropEventsAlarm(2),
            downstreamCRCErrorFramesAlarm(3),
            upstreamCRCErrorFramesAlarm(4),
            downstreamUndersizeFramesAlarm(5),
            upstreamUndersizeFramesAlarm(6),
            downstreamOversizeFramesAlarm(7),
            upstreamOversizeFramesAlarm(8),
            downstreamFragmentsAlarm(9),
            upstreamFragmentsAlarm(10),
            downstreamJabbersAlarm(11),
            upstreamJabbersAlarm(12),
            downstreamDiscardsAlarm(13),
            upstreamDiscardsAlarm(14),
            downstreamErrorsAlarm(15),
            upstreamErrorsAlarm(16),
            statusChangeTimesAlarm(17),
            downstreamDropEventsWarning(18),
            upstreamDropEventsWarning(19),
            downstreamCRCErrorFramesWarning(20),
            upstreamCRCErrorFramesWarning(21),
            downstreamUndersizeFramesWarning(22),
            upstreamUndersizeFramesWarning(23),
            downstreamOversizeFramesWarning(24),
            upstreamOversizeFramesWarning(25),
            upstreamFragmentsWarning(27),
            downstreamJabbersWarning(28),
            upstreamJabbersWarning(29),
            downstreamDiscardsWarning(30),
            upstreamDiscardsWarning(31),
            downstreamErrorsWarning(32),
            upstreamErrorsWarning(33),
            statusChangeTimesWarning(34)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portStatAlarm 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.12.3
portStatAlarmTypeEn OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
```

```
      DESCRIPTION
            "Description."
      ::= { portStatAlarm 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.12.4
portStatAlarmTld OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portStatAlarm 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.12.5
portStatAlarmAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            delete(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portStatAlarm 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.13
potsAlarmStatus OBJECT IDENTIFIER ::= { alarmProfileEdit 13 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.13.1
potsAlarmPotsNo OBJECT-TYPE
      SYNTAX INTEGER (1..64)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { potsAlarmStatus 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.13.2
potsPortFailAlarmEn OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { potsAlarmStatus 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.13.3
potsAlarmStatusAction OBJECT-TYPE
```

```
      SYNTAX INTEGER
            {
            add(1),
            delete(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { potsAlarmStatus 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.14
e1AlarmStatus OBJECT IDENTIFIER ::= { alarmProfileEdit 14 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.14.1
e1AlarmE1No OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { e1AlarmStatus 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.14.2
e1AlarmType OBJECT-TYPE
      SYNTAX INTEGER
            {
            e1PortFailure(1),
            e1TimingUnlock(2),
            e1Los(3)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { e1AlarmStatus 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.14.3
e1AlarmTypeEn OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { e1AlarmStatus 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.5.14.4
e1AlarmStatusAction OBJECT-TYPE
      SYNTAX INTEGER
            {
```

```
            add(1),
            delete(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { e1AlarmStatus 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.6
profileManualBind OBJECT IDENTIFIER ::= { onuProfileCfg 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.6.1
profileBindTpye OBJECT-TYPE
      SYNTAX INTEGER
            {
            dba(1),
            srv(2),
            voip(3),
            alarm(4)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { profileManualBind 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.6.2
profileBindPon OBJECT-TYPE
      SYNTAX Integer32 (1..16)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { profileManualBind 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.6.3
profileBindOnu OBJECT-TYPE
      SYNTAX Integer32 (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { profileManualBind 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.6.4
profileBindId OBJECT-TYPE
      SYNTAX Integer32 (0..32767)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { profileManualBind 4 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.8.6.5
profileBindAction OBJECT-TYPE
      SYNTAX INTEGER { commit(1) }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { profileManualBind 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.7
profileAutoBind OBJECT IDENTIFIER ::= { onuProfileCfg 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.7.1
profileAutoBindDba OBJECT-TYPE
      SYNTAX Integer32 (0..32767)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { profileAutoBind 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.7.2
profileAutoBindSrv OBJECT-TYPE
      SYNTAX Integer32 (0..32767)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { profileAutoBind 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.7.3
profileAutoBindVoip OBJECT-TYPE
      SYNTAX Integer32 (0..32767)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { profileAutoBind 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.7.4
profileAutoBindAlarm OBJECT-TYPE
      SYNTAX Integer32 (0..32767)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { profileAutoBind 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.7.5
profileOnuType OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
```

```
      STATUS current
      DESCRIPTION
            "Description."
      ::= { profileAutoBind 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.7.6
profileAutoBindAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            add(1),
            delete(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { profileAutoBind 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.8
profileDescrEdit OBJECT IDENTIFIER ::= { onuProfileCfg 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.8.1
profileDescrType OBJECT-TYPE
      SYNTAX INTEGER
            {
            dba(1),
            srv(2),
            voip(3),
            alarm(4)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { profileDescrEdit 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.8.2
profileDescrId OBJECT-TYPE
      SYNTAX Integer32 (1..32767)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { profileDescrEdit 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.8.8.3
profileDescrStr OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { profileDescrEdit 3 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.8.8.4
profileDescrAction OBJECT-TYPE
      SYNTAX INTEGER
            {
            submit(1),
            delete(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { profileDescrEdit 4 }

-- 1.3.6.1.4.1.37950.1.1.5.12.9
onuProfileShow OBJECT IDENTIFIER ::= { v1600dOnuMgmt 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.1
dbaProfileShow OBJECT IDENTIFIER ::= { onuProfileShow 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.1.1
upsteamPFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF UpsteamPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { dbaProfileShow 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.1.1.1
upsteamPFEntry OBJECT-TYPE
      SYNTAX UpsteamPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { upstreamDbaId }
      ::= { upsteamPFTable 1 }


UpsteamPFEntry ::=
      SEQUENCE {
            upstreamDbaId
                  Integer32,
            upstreamFirS
                  Integer32,
            upstreamCirS
                  Integer32,
            upstreamPirS
                  Integer32,
            upstreamWeightS
                  Integer32
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.1.1.1.1
upstreamDbaId OBJECT-TYPE
```

```
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { upsteamPFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.1.1.1.2
upstreamFirS OBJECT-TYPE
      SYNTAX Integer32 (0..950000)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { upsteamPFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.1.1.1.3
upstreamCirS OBJECT-TYPE
      SYNTAX Integer32 (1..950000)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { upsteamPFEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.1.1.1.4
upstreamPirS OBJECT-TYPE
      SYNTAX Integer32 (512..1000000)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { upsteamPFEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.1.1.1.5
upstreamWeightS OBJECT-TYPE
      SYNTAX Integer32 (1..20)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { upsteamPFEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.1.2
dnstreamPFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF DnstreamPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { dbaProfileShow 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.1.2.1
```

```
dnstreamPFEntry OBJECT-TYPE
      SYNTAX DnstreamPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { dnstreamDbaId }
      ::= { dnstreamPFTable 1 }


DnstreamPFEntry ::=
      SEQUENCE {
            dnstreamDbaId
                  Integer32,
            dnstreamPirS
                  Integer32,
            dnstreamWeightS
                  Integer32
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.1.2.1.1
dnstreamDbaId OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { dnstreamPFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.1.2.1.2
dnstreamPirS OBJECT-TYPE
      SYNTAX Integer32 (0..1000000)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { dnstreamPFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.1.2.1.3
dnstreamWeightS OBJECT-TYPE
      SYNTAX Integer32 (1..16)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { dnstreamPFEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2
srvProfileShow OBJECT IDENTIFIER ::= { onuProfileShow 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.1
onuLanCountPFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuLanCountPFEntry
      MAX-ACCESS not-accessible
      STATUS current
```

```
      DESCRIPTION
            "Description."
      ::= { srvProfileShow 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.1.1
onuLanCountPFEntry OBJECT-TYPE
      SYNTAX OnuLanCountPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { onuLanCountSrvId }
      ::= { onuLanCountPFTable 1 }


OnuLanCountPFEntry ::=
      SEQUENCE {
            onuLanCountSrvId
                  Integer32,
            onuLanCountS
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.1.1.1
onuLanCountSrvId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuLanCountPFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.1.1.2
onuLanCountS OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuLanCountPFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.2
onuFastleavePFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuFastleavePFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { srvProfileShow 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.2.1
onuFastleavePFEntry OBJECT-TYPE
      SYNTAX OnuFastleavePFEntry
      MAX-ACCESS not-accessible
      STATUS current
```

```
      DESCRIPTION
            "Description."
      INDEX { onuFastleaveSrvId }
      ::= { onuFastleavePFTable 1 }


OnuFastleavePFEntry ::=
      SEQUENCE {
            onuFastleaveSrvId
                  Integer32,
            onuFastleaveEnableS
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.2.1.1
onuFastleaveSrvId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuFastleavePFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.2.1.2
onuFastleaveEnableS OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuFastleavePFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.3
onuFecModePFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuFecModePFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { srvProfileShow 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.3.1
onuFecModePFEntry OBJECT-TYPE
      SYNTAX OnuFecModePFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { onuFecModeSrvId }
      ::= { onuFecModePFTable 1 }
```

```
OnuFecModePFEntry ::=
      SEQUENCE {
            onuFecModeSrvId
                  Integer32,
            onuFecModeEnableS
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.3.1.1
onuFecModeSrvId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuFecModePFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.3.1.2
onuFecModeEnableS OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuFecModePFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.4
ctcMcModePFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF CtcMcModePFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { srvProfileShow 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.4.1
ctcMcModePFEntry OBJECT-TYPE
      SYNTAX CtcMcModePFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { ctcMcModeSrvId }
      ::= { ctcMcModePFTable 1 }


CtcMcModePFEntry ::=
      SEQUENCE {
            ctcMcModeSrvId
                  Integer32,
            ctcMcModeS
                  INTEGER
```

```
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.4.1.1
ctcMcModeSrvId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ctcMcModePFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.4.1.2
ctcMcModeS OBJECT-TYPE
      SYNTAX INTEGER
            {
            snooping(1),
            control(2)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ctcMcModePFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.5
ctcMultiLlidPFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF CtcMultiLlidPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { srvProfileShow 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.5.1
ctcMultiLlidPFEntry OBJECT-TYPE
      SYNTAX CtcMultiLlidPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { ctcMultiLlidSrvId }
      ::= { ctcMultiLlidPFTable 1 }


CtcMultiLlidPFEntry ::=
      SEQUENCE {
            ctcMultiLlidSrvId
                  Integer32,
            ctcMultiLlidS
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.5.1.1
ctcMultiLlidSrvId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-only
```

```
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ctcMultiLlidPFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.5.1.2
ctcMultiLlidS OBJECT-TYPE
      SYNTAX INTEGER (0..8)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ctcMultiLlidPFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.6
ctcActivePonPFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF CtcActivePonPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { srvProfileShow 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.6.1
ctcActivePonPFEntry OBJECT-TYPE
      SYNTAX CtcActivePonPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { ctcActivePonSrvId }
      ::= { ctcActivePonPFTable 1 }


CtcActivePonPFEntry ::=
      SEQUENCE {
            ctcActivePonSrvId
                  Integer32,
            ctcActivePonS
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.6.1.1
ctcActivePonSrvId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ctcActivePonPFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.6.1.2
ctcActivePonS OBJECT-TYPE
      SYNTAX INTEGER (0..8)
      MAX-ACCESS read-only
```

```
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ctcActivePonPFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.7
ctcHoldoverPFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF CtcHoldoverPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { srvProfileShow 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.7.1
ctcHoldoverPFEntry OBJECT-TYPE
      SYNTAX CtcHoldoverPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { ctcHoldoverSrvId }
      ::= { ctcHoldoverPFTable 1 }


CtcHoldoverPFEntry ::=
      SEQUENCE {
            ctcHoldoverSrvId
                  Integer32,
            ctcHoldoverS
                  Integer32
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.7.1.1
ctcHoldoverSrvId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ctcHoldoverPFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.7.1.2
ctcHoldoverS OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { ctcHoldoverPFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.8
onuMgmtIpPFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuMgmtIpPFEntry
      MAX-ACCESS not-accessible
```

```
      STATUS current
      DESCRIPTION
            "Description."
      ::= { srvProfileShow 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.8.1
onuMgmtIpPFEntry OBJECT-TYPE
      SYNTAX OnuMgmtIpPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { onuMgmtIpSrvId }
      ::= { onuMgmtIpPFTable 1 }


OnuMgmtIpPFEntry ::=
      SEQUENCE {
            onuMgmtIpSrvId
                  Integer32,
            onuMgmtIpAddrS
                  IpAddress,
            onuMgmtIpMaskS
                  IpAddress,
            onuMgmtIpGwS
                  IpAddress,
            onuMgmtIpCvlanS
                  INTEGER,
            onuMgmtIpSvlanS
                  INTEGER,
            onuMgmtIpPriS
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.8.1.1
onuMgmtIpSrvId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuMgmtIpPFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.8.1.2
onuMgmtIpAddrS OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuMgmtIpPFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.8.1.3
onuMgmtIpMaskS OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
```

```
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuMgmtIpPFEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.8.1.4
onuMgmtIpGwS OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuMgmtIpPFEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.8.1.5
onuMgmtIpCvlanS OBJECT-TYPE
      SYNTAX INTEGER (0..4095)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuMgmtIpPFEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.8.1.6
onuMgmtIpSvlanS OBJECT-TYPE
      SYNTAX INTEGER (0..4095)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuMgmtIpPFEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.8.1.7
onuMgmtIpPriS OBJECT-TYPE
      SYNTAX INTEGER (-1..7)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuMgmtIpPFEntry 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.9
onuSnmpProPFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuSnmpProPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { srvProfileShow 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.9.1
onuSnmpProPFEntry OBJECT-TYPE
      SYNTAX OnuSnmpProPFEntry
```

```
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { onuSnmpProSrvId }
      ::= { onuSnmpProPFTable 1 }


OnuSnmpProPFEntry ::=
      SEQUENCE {
            onuSnmpProSrvId
                  Integer32,
            onuSnmpProHostS
                  IpAddress,
            onuSnmpProTrapPortS
                  INTEGER,
            onuSnmpProPortS
                  INTEGER,
            onuSnmpProNameS
                  OCTET STRING,
            onuSnmpProComRdS
                  OCTET STRING,
            onuSnmpProComWrS
                  OCTET STRING
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.9.1.1
onuSnmpProSrvId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSnmpProPFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.9.1.2
onuSnmpProHostS OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSnmpProPFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.9.1.3
onuSnmpProTrapPortS OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSnmpProPFEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.9.1.4
onuSnmpProPortS OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
```

```
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSnmpProPFEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.9.1.5
onuSnmpProNameS OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSnmpProPFEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.9.1.6
onuSnmpProComRdS OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSnmpProPFEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.9.1.7
onuSnmpProComWrS OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSnmpProPFEntry 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.10
onuSlaPFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuSlaPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { srvProfileShow 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.10.1
onuSlaPFEntry OBJECT-TYPE
      SYNTAX OnuSlaPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { onuSlaSrvId }
      ::= { onuSlaPFTable 1 }


OnuSlaPFEntry ::=
```

```
      SEQUENCE {
            onuSlaSrvId
                  Integer32,
            onuSlaEnableS
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.10.1.1
onuSlaSrvId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSlaPFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.10.1.2
onuSlaEnableS OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSlaPFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.11
onuCtcPausePFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuCtcPausePFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { srvProfileShow 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.11.1
onuCtcPausePFEntry OBJECT-TYPE
      SYNTAX OnuCtcPausePFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { onuCtcPauseSrvId, pausePortIndexS }
      ::= { onuCtcPausePFTable 1 }


OnuCtcPausePFEntry ::=
      SEQUENCE {
            onuCtcPauseSrvId
                  Integer32,
            pausePortIndexS
                  INTEGER,
            onuCtcPauseEnS
```

```
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.11.1.1
onuCtcPauseSrvId OBJECT-TYPE
      SYNTAX Integer32 (0..65536)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuCtcPausePFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.11.1.2
pausePortIndexS OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuCtcPausePFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.11.1.3
onuCtcPauseEnS OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuCtcPausePFEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.12
onuCtcLoopdetectPFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuCtcLoopdetectPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { srvProfileShow 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.12.1
onuCtcLoopdetectPFEntry OBJECT-TYPE
      SYNTAX OnuCtcLoopdetectPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { onuCtcLoopdetectSrvId, loopdetectPortIndexS }
      ::= { onuCtcLoopdetectPFTable 1 }


OnuCtcLoopdetectPFEntry ::=
```

```
      SEQUENCE {
            onuCtcLoopdetectSrvId
                  Integer32,
            loopdetectPortIndexS
                  INTEGER,
            onuCtcLoopdetectEnS
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.12.1.1
onuCtcLoopdetectSrvId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuCtcLoopdetectPFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.12.1.2
loopdetectPortIndexS OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuCtcLoopdetectPFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.12.1.3
onuCtcLoopdetectEnS OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuCtcLoopdetectPFEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.13
onuMcTagstripPFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuMcTagstripPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { srvProfileShow 13 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.13.1
onuMcTagstripPFEntry OBJECT-TYPE
      SYNTAX OnuMcTagstripPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
```

```
            "Description."
      INDEX { onuMcTagstripSrvId, tagstripPortIndexS }
      ::= { onuMcTagstripPFTable 1 }


OnuMcTagstripPFEntry ::=
      SEQUENCE {
            onuMcTagstripSrvId
                  Integer32,
            tagstripPortIndexS
                  INTEGER,
            onuMcTagstripEnS
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.13.1.1
onuMcTagstripSrvId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuMcTagstripPFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.13.1.2
tagstripPortIndexS OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuMcTagstripPFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.13.1.3
onuMcTagstripEnS OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuMcTagstripPFEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.14
onuMcVlanTransPFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuMcVlanTransPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { srvProfileShow 14 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.14.1
onuMcVlanTransPFEntry OBJECT-TYPE
      SYNTAX OnuMcVlanTransPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { onuMcVlanTransnSrvId, mcVlanTransPortIndexS }
      ::= { onuMcVlanTransPFTable 1 }


OnuMcVlanTransPFEntry ::=
      SEQUENCE {
            onuMcVlanTransnSrvId
                  Integer32,
            mcVlanTransPortIndexS
                  INTEGER,
            onuMcVlanTransVlanStrS
                  OCTET STRING
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.14.1.1
onuMcVlanTransnSrvId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuMcVlanTransPFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.14.1.2
mcVlanTransPortIndexS OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuMcVlanTransPFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.14.1.3
onuMcVlanTransVlanStrS OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuMcVlanTransPFEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.15
onuPortPhyAdminPFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuPortPhyAdminPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { srvProfileShow 15 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.15.1
onuPortPhyAdminPFEntry OBJECT-TYPE
      SYNTAX OnuPortPhyAdminPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { onuPortPhyAdminSrvId, adminPortIndexS }
      ::= { onuPortPhyAdminPFTable 1 }


OnuPortPhyAdminPFEntry ::=
      SEQUENCE {
            onuPortPhyAdminSrvId
                  Integer32,
            adminPortIndexS
                  INTEGER,
            onuPortPhyAdminEnS
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.15.1.1
onuPortPhyAdminSrvId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortPhyAdminPFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.15.1.2
adminPortIndexS OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortPhyAdminPFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.15.1.3
onuPortPhyAdminEnS OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortPhyAdminPFEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.16
portAutoNegPFTable OBJECT-TYPE
```

```
      SYNTAX SEQUENCE OF PortAutoNegPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { srvProfileShow 16 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.16.1
portAutoNegPFEntry OBJECT-TYPE
      SYNTAX PortAutoNegPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { portAutoNegSrvId, autoNegPortIndexS }
      ::= { portAutoNegPFTable 1 }


PortAutoNegPFEntry ::=
      SEQUENCE {
            portAutoNegSrvId
                  Integer32,
            autoNegPortIndexS
                  INTEGER,
            portAutoNegEnS
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.16.1.1
portAutoNegSrvId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portAutoNegPFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.16.1.2
autoNegPortIndexS OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portAutoNegPFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.16.1.3
portAutoNegEnS OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
```

```
            "Description."
      ::= { portAutoNegPFEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.17
maxIgmpGrpPFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF MaxIgmpGrpPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { srvProfileShow 17 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.17.1
maxIgmpGrpPFEntry OBJECT-TYPE
      SYNTAX MaxIgmpGrpPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { maxIgmpGrpSrvId, maxIgmpPortIndexS }
      ::= { maxIgmpGrpPFTable 1 }


MaxIgmpGrpPFEntry ::=
      SEQUENCE {
            maxIgmpGrpSrvId
                  Integer32,
            maxIgmpPortIndexS
                  INTEGER,
            maxIgmpGrpS
                  Integer32
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.17.1.1
maxIgmpGrpSrvId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { maxIgmpGrpPFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.17.1.2
maxIgmpPortIndexS OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { maxIgmpGrpPFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.17.1.3
maxIgmpGrpS OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
```

```
      STATUS current
      DESCRIPTION
            "Description."
      ::= { maxIgmpGrpPFEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.18
onuPortUpLimitPFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuPortUpLimitPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { srvProfileShow 18 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.18.1
onuPortUpLimitPFEntry OBJECT-TYPE
      SYNTAX OnuPortUpLimitPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { onuPortUpLimitSrvId, upLimitPortIndexS }
      ::= { onuPortUpLimitPFTable 1 }


OnuPortUpLimitPFEntry ::=
      SEQUENCE {
            onuPortUpLimitSrvId
                  Integer32,
            upLimitPortIndexS
                  INTEGER,
            onuPortUpLimitCirS
                  Integer32,
            onuPortUpLimitCbsS
                  Integer32,
            onuPortUpLimitEbsS
                  Integer32
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.18.1.1
onuPortUpLimitSrvId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortUpLimitPFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.18.1.2
upLimitPortIndexS OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortUpLimitPFEntry 2 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.18.1.3
onuPortUpLimitCirS OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortUpLimitPFEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.18.1.4
onuPortUpLimitCbsS OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortUpLimitPFEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.18.1.5
onuPortUpLimitEbsS OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortUpLimitPFEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.19
onuPortDownLimitPFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuPortDownLimitPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { srvProfileShow 19 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.19.1
onuPortDownLimitPFEntry OBJECT-TYPE
      SYNTAX OnuPortDownLimitPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { onuPortDownLimitSrvId, downLimitPortIndexS }
      ::= { onuPortDownLimitPFTable 1 }


OnuPortDownLimitPFEntry ::=
      SEQUENCE {
            onuPortDownLimitSrvId
                  Integer32,
            downLimitPortIndexS
                  INTEGER,
```

```
            onuPortDownLimitCirS
                  Integer32,
            onuPortDownLimitPirS
                  Integer32
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.19.1.1
onuPortDownLimitSrvId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortDownLimitPFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.19.1.2
downLimitPortIndexS OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortDownLimitPFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.19.1.3
onuPortDownLimitCirS OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortDownLimitPFEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.19.1.4
onuPortDownLimitPirS OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortDownLimitPFEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.20
portVlanModePFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF PortVlanModePFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { srvProfileShow 20 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.20.1
portVlanModePFEntry OBJECT-TYPE
      SYNTAX PortVlanModePFEntry
```

```
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { portVlanModeSrvId, vlanModePortIndexS }
      ::= { portVlanModePFTable 1 }


PortVlanModePFEntry ::=
      SEQUENCE {
            portVlanModeSrvId
                  Integer32,
            vlanModePortIndexS
                  INTEGER,
            onuCtcPortVlanModeS
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.20.1.1
portVlanModeSrvId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portVlanModePFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.20.1.2
vlanModePortIndexS OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portVlanModePFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.20.1.3
onuCtcPortVlanModeS OBJECT-TYPE
      SYNTAX INTEGER
            {
            transparent(1),
            tag(2),
            translation(3),
            aggregation(4),
            trunk(5)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portVlanModePFEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.21
portVlanPvidPFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF PortVlanPvidPFEntry
      MAX-ACCESS not-accessible
```

```
      STATUS current
      DESCRIPTION
            "Description."
      ::= { srvProfileShow 21 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.21.1
portVlanPvidPFEntry OBJECT-TYPE
      SYNTAX PortVlanPvidPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { portVlanPvidSrvId, vlanPvidPortIndexS }
      ::= { portVlanPvidPFTable 1 }


PortVlanPvidPFEntry ::=
      SEQUENCE {
            portVlanPvidSrvId
                  Integer32,
            vlanPvidPortIndexS
                  INTEGER,
            vlanPvidS
                  Integer32,
            vlanTpidS
                  OCTET STRING
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.21.1.1
portVlanPvidSrvId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portVlanPvidPFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.21.1.2
vlanPvidPortIndexS OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portVlanPvidPFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.21.1.3
vlanPvidS OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portVlanPvidPFEntry 3 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.21.1.4
vlanTpidS OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portVlanPvidPFEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.22
portVlanTranslatePFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF PortVlanTranslatePFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { srvProfileShow 22 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.22.1
portVlanTranslatePFEntry OBJECT-TYPE
      SYNTAX PortVlanTranslatePFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { portVlanTranslateSrvId, vlanTransPortIndexS }
      ::= { portVlanTranslatePFTable 1 }


PortVlanTranslatePFEntry ::=
      SEQUENCE {
            portVlanTranslateSrvId
                  Integer32,
            vlanTransPortIndexS
                  INTEGER,
            portVlanTransVlanStrS
                  OCTET STRING
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.22.1.1
portVlanTranslateSrvId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portVlanTranslatePFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.22.1.2
vlanTransPortIndexS OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portVlanTranslatePFEntry 2 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.22.1.3
portVlanTransVlanStrS OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portVlanTranslatePFEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.23
portVlanTrunkPFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF PortVlanTrunkPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { srvProfileShow 23 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.23.1
portVlanTrunkPFEntry OBJECT-TYPE
      SYNTAX PortVlanTrunkPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { portVlanTrunkSrvId, trunkPortIndexS }
      ::= { portVlanTrunkPFTable 1 }


PortVlanTrunkPFEntry ::=
      SEQUENCE {
            portVlanTrunkSrvId
                  Integer32,
            trunkPortIndexS
                  INTEGER,
            portVlanTrunkVidStrS
                  OCTET STRING
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.23.1.1
portVlanTrunkSrvId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portVlanTrunkPFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.23.1.2
trunkPortIndexS OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
```

```
            "Description."
      ::= { portVlanTrunkPFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.23.1.3
portVlanTrunkVidStrS OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portVlanTrunkPFEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.24
portVlanAggPFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF PortVlanAggPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { srvProfileShow 24 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.24.1
portVlanAggPFEntry OBJECT-TYPE
      SYNTAX PortVlanAggPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { portVlanAggSrvId, vlanAggPortIndexS }
      ::= { portVlanAggPFTable 1 }


PortVlanAggPFEntry ::=
      SEQUENCE {
            portVlanAggSrvId
                  Integer32,
            vlanAggPortIndexS
                  INTEGER,
            portVlanAggNewVlanS
                  Integer32,
            portVlanAggOldVlanStrS
                  OCTET STRING
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.24.1.1
portVlanAggSrvId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portVlanAggPFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.24.1.2
vlanAggPortIndexS OBJECT-TYPE
```

```
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portVlanAggPFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.24.1.3
portVlanAggNewVlanS OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portVlanAggPFEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.24.1.4
portVlanAggOldVlanStrS OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portVlanAggPFEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.25
portMcVlanPFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF PortMcVlanPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { srvProfileShow 25 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.25.1
portMcVlanPFEntry OBJECT-TYPE
      SYNTAX PortMcVlanPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { portMcVlanSrvId, mcVlanPortIndexS }
      ::= { portMcVlanPFTable 1 }


PortMcVlanPFEntry ::=
      SEQUENCE {
            portMcVlanSrvId
                  Integer32,
            mcVlanPortIndexS
                  INTEGER,
            portMcVlanStrS
                  OCTET STRING
       }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.25.1.1
portMcVlanSrvId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portMcVlanPFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.25.1.2
mcVlanPortIndexS OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portMcVlanPFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.25.1.3
portMcVlanStrS OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portMcVlanPFEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.26
onuClassifyPFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuClassifyPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { srvProfileShow 26 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.26.1
onuClassifyPFEntry OBJECT-TYPE
      SYNTAX OnuClassifyPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { onuClassifySrvId, cfyPortIndexS, ctcCfyPrecedenceS }
      ::= { onuClassifyPFTable 1 }


OnuClassifyPFEntry ::=
      SEQUENCE {
            onuClassifySrvId
                  Integer32,
            cfyPortIndexS
                  INTEGER,
            ctcCfyPrecedenceS
                  Integer32,
```

```
            ctcCfyPriS
                  Integer32,
            ctcCfyDstMacEqualS
                  INTEGER,
            ctcCfyDstMacValueS
                  OCTET STRING,
            ctcCfySrcMacEqualS
                  INTEGER,
            ctcCfySrcMacValueS
                  OCTET STRING,
            ctcCfyVlanEqualS
                  INTEGER,
            ctcCfyVlanValueS
                  INTEGER,
            ctcCfyCosEqualS
                  INTEGER,
            ctcCfyCosValueS
                  INTEGER,
            ctcCfyEthTypeEqualS
                  INTEGER,
            ctcCfyEthTypeValueS
                  OCTET STRING,
            ctcCfySrcIpEqualS
                  INTEGER,
            ctcCfySrcIpValueS
                  IpAddress,
            ctcCfyDestIpEqualS
                  INTEGER,
            ctcCfyDestIpValueS
                  IpAddress,
            ctcCfyProEqualS
                  INTEGER,
            ctcCfyProValueS
                  INTEGER,
            ctcCfyTosDscpEuqalS
                  INTEGER,
            ctcCfyTosDscpValueS
                  INTEGER,
            ctcCfySrcPortEqualS
                  INTEGER,
            ctcCfySrcPortValueS
                  INTEGER,
            ctcCfyDestPortEqualS
                  INTEGER,
            ctcCfyDestPortValueS
                  INTEGER,
            onuCfyQueueS
                  Integer32
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.26.1.1
onuClassifySrvId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyPFEntry 1 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.26.1.2
cfyPortIndexS OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyPFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.26.1.3
ctcCfyPrecedenceS OBJECT-TYPE
      SYNTAX Integer32 (1..8)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyPFEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.26.1.4
ctcCfyPriS OBJECT-TYPE
      SYNTAX Integer32 (0..7)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyPFEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.26.1.5
ctcCfyDstMacEqualS OBJECT-TYPE
      SYNTAX INTEGER
            {
            init(0),
            equal(1),
            unequal(2)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyPFEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.26.1.6
ctcCfyDstMacValueS OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyPFEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.26.1.7
ctcCfySrcMacEqualS OBJECT-TYPE
      SYNTAX INTEGER
```

```
            {
            init(0),
            equal(1),
            unequal(2)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyPFEntry 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.26.1.8
ctcCfySrcMacValueS OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyPFEntry 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.26.1.9
ctcCfyVlanEqualS OBJECT-TYPE
      SYNTAX INTEGER
            {
            init(0),
            equal(1),
            unequal(2)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyPFEntry 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.26.1.10
ctcCfyVlanValueS OBJECT-TYPE
      SYNTAX INTEGER (0..4094)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyPFEntry 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.26.1.11
ctcCfyCosEqualS OBJECT-TYPE
      SYNTAX INTEGER
            {
            init(0),
            equal(1),
            unequal(2)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { onuClassifyPFEntry 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.26.1.12
ctcCfyCosValueS OBJECT-TYPE
      SYNTAX INTEGER (-1..7)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyPFEntry 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.26.1.13
ctcCfyEthTypeEqualS OBJECT-TYPE
      SYNTAX INTEGER
            {
            init(0),
            equal(1),
            unequal(2)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyPFEntry 13 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.26.1.14
ctcCfyEthTypeValueS OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyPFEntry 14 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.26.1.15
ctcCfySrcIpEqualS OBJECT-TYPE
      SYNTAX INTEGER
            {
            init(0),
            equal(1),
            unequal(2)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyPFEntry 15 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.26.1.16
ctcCfySrcIpValueS OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
```

```
            "Description."
      ::= { onuClassifyPFEntry 16 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.26.1.17
ctcCfyDestIpEqualS OBJECT-TYPE
      SYNTAX INTEGER
            {
            init(0),
            equal(1),
            unequal(2)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyPFEntry 17 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.26.1.18
ctcCfyDestIpValueS OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyPFEntry 18 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.26.1.19
ctcCfyProEqualS OBJECT-TYPE
      SYNTAX INTEGER
            {
            init(0),
            equal(1),
            unequal(2)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyPFEntry 19 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.26.1.20
ctcCfyProValueS OBJECT-TYPE
      SYNTAX INTEGER (-1..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyPFEntry 20 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.26.1.21
ctcCfyTosDscpEuqalS OBJECT-TYPE
      SYNTAX INTEGER
            {
            init(0),
```

```
            equal(1),
            unequal(2)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyPFEntry 21 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.26.1.22
ctcCfyTosDscpValueS OBJECT-TYPE
      SYNTAX INTEGER (-1..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyPFEntry 22 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.26.1.23
ctcCfySrcPortEqualS OBJECT-TYPE
      SYNTAX INTEGER
            {
            init(0),
            equal(1),
            unequal(2)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyPFEntry 23 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.26.1.24
ctcCfySrcPortValueS OBJECT-TYPE
      SYNTAX INTEGER (-1..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyPFEntry 24 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.26.1.25
ctcCfyDestPortEqualS OBJECT-TYPE
      SYNTAX INTEGER
            {
            init(0),
            equal(1),
            unequal(2)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyPFEntry 25 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.26.1.26
ctcCfyDestPortValueS OBJECT-TYPE
      SYNTAX INTEGER (-1..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyPFEntry 26 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.26.1.27
onuCfyQueueS OBJECT-TYPE
      SYNTAX Integer32 (0..7)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuClassifyPFEntry 27 }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.27
onuMacAgetimePFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuMacAgetimePFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { srvProfileShow 27 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.27.1
onuMacAgetimePFEntry OBJECT-TYPE
      SYNTAX OnuMacAgetimePFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { onuMacAgetimeSrvId }
      ::= { onuMacAgetimePFTable 1 }


OnuMacAgetimePFEntry ::=
      SEQUENCE {
            onuMacAgetimeSrvId
                  Integer32,
            onuMacAgetimeS
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.27.1.1
onuMacAgetimeSrvId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuMacAgetimePFEntry 1 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.27.1.2
onuMacAgetimeS OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuMacAgetimePFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.28
onuPonProtectPFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuPonProtectPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { srvProfileShow 28 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.28.1
onuPonProtectPFEntry OBJECT-TYPE
      SYNTAX OnuPonProtectPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { onuPonProtectSrvId }
      ::= { onuPonProtectPFTable 1 }


OnuPonProtectPFEntry ::=
      SEQUENCE {
            onuPonProtectSrvId
                  Integer32,
            onuPonProtectLosOpS
                  INTEGER,
            onuPonProtectLosMpcpS
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.28.1.1
onuPonProtectSrvId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPonProtectPFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.28.1.2
onuPonProtectLosOpS OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPonProtectPFEntry 2 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.28.1.3
onuPonProtectLosMpcpS OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPonProtectPFEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.29
onuPowerSavePFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuPowerSavePFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { srvProfileShow 29 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.29.1
onuPowerSavePFEntry OBJECT-TYPE
      SYNTAX OnuPowerSavePFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { onuPowerSaveSrvId }
      ::= { onuPowerSavePFTable 1 }


OnuPowerSavePFEntry ::=
      SEQUENCE {
            onuPowerSaveSrvId
                  Integer32,
            onuPSEarlyWakeupS
                  INTEGER,
            onuPSSleepDurationMaxS
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.29.1.1
onuPowerSaveSrvId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPowerSavePFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.29.1.2
onuPSEarlyWakeupS OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
```

```
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPowerSavePFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.29.1.3
onuPSSleepDurationMaxS OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPowerSavePFEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.30
onuSleepPFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuSleepPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { srvProfileShow 30 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.30.1
onuSleepPFEntry OBJECT-TYPE
      SYNTAX OnuSleepPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { onuSleepSrvId }
      ::= { onuSleepPFTable 1 }


OnuSleepPFEntry ::=
      SEQUENCE {
            onuSleepSrvId
                  Integer32,
            onuSleepDurationS
                  INTEGER,
            onuWakeDurationS
                  INTEGER,
            onuSleepFlagS
                  INTEGER,
            onuSleepModeS
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.30.1.1
onuSleepSrvId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
```

```
            "Description."
      ::= { onuSleepPFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.30.1.2
onuSleepDurationS OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSleepPFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.30.1.3
onuWakeDurationS OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSleepPFEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.30.1.4
onuSleepFlagS OBJECT-TYPE
      SYNTAX INTEGER
            {
            off(1),
            add(2),
            change(3)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSleepPFEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.30.1.5
onuSleepModeS OBJECT-TYPE
      SYNTAX INTEGER
            {
            none(1),
            tx_sleep_only(2),
            tx_and_rx_sleep(3)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuSleepPFEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.31
onuDisableLoopPFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuDisableLoopPFEntry
      MAX-ACCESS not-accessible
      STATUS current
```

```
      DESCRIPTION
            "Description."
      ::= { srvProfileShow 31 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.31.1
onuDisableLoopPFEntry OBJECT-TYPE
      SYNTAX OnuDisableLoopPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { onuDisableLoopSrvId, disableLoopPortIndexS }
      ::= { onuDisableLoopPFTable 1 }


OnuDisableLoopPFEntry ::=
      SEQUENCE {
            onuDisableLoopSrvId
                  Integer32,
            disableLoopPortIndexS
                  INTEGER,
            onuDisableLoopS
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.31.1.1
onuDisableLoopSrvId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuDisableLoopPFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.31.1.2
disableLoopPortIndexS OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuDisableLoopPFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.31.1.3
onuDisableLoopS OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuDisableLoopPFEntry 3 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.32
onuPortStatPFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuPortStatPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { srvProfileShow 32 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.32.1
onuPortStatPFEntry OBJECT-TYPE
      SYNTAX OnuPortStatPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { onuPortStatSrvId, onuPortStatPortIdS }
      ::= { onuPortStatPFTable 1 }


OnuPortStatPFEntry ::=
      SEQUENCE {
            onuPortStatSrvId
                  Integer32,
            onuPortStatPortIdS
                  INTEGER,
            onuPortStatStatusS
                  INTEGER,
            onuPortStatCountS
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.32.1.1
onuPortStatSrvId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatPFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.32.1.2
onuPortStatPortIdS OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatPFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.32.1.3
onuPortStatStatusS OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
```

```
            enable(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatPFEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.32.1.4
onuPortStatCountS OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatPFEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.33
onuPortStatClearPFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuPortStatClearPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { srvProfileShow 33 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.33.1
onuPortStatClearPFEntry OBJECT-TYPE
      SYNTAX OnuPortStatClearPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { onuPortStatClearSrvId, onuPortStatClearPortIdS }
      ::= { onuPortStatClearPFTable 1 }


OnuPortStatClearPFEntry ::=
      SEQUENCE {
            onuPortStatClearSrvId
                  Integer32,
            onuPortStatClearPortIdS
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.33.1.1
onuPortStatClearSrvId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatClearPFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.33.1.2
```

```
onuPortStatClearPortIdS OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPortStatClearPFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.34
onuIgmpAdminPFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuIgmpAdminPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { srvProfileShow 34 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.34.1
onuIgmpAdminPFEntry OBJECT-TYPE
      SYNTAX OnuIgmpAdminPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { onuIgmpAdminSrvID }
      ::= { onuIgmpAdminPFTable 1 }


OnuIgmpAdminPFEntry ::=
      SEQUENCE {
            onuIgmpAdminSrvID
                  INTEGER,
            onuIgmpAdminEnableS
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.34.1.1
onuIgmpAdminSrvID OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuIgmpAdminPFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.34.1.2
onuIgmpAdminEnableS OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { onuIgmpAdminPFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.35
onuCatvStatusPFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuCatvStatusPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { srvProfileShow 35 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.35.1
onuCatvStatusPFEntry OBJECT-TYPE
      SYNTAX OnuCatvStatusPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { onuCatvSatusSrvId }
      ::= { onuCatvStatusPFTable 1 }


OnuCatvStatusPFEntry ::=
      SEQUENCE {
            onuCatvSatusSrvId
                  INTEGER,
            onuCatvStatusS
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.35.1.1
onuCatvSatusSrvId OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuCatvStatusPFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.35.1.2
onuCatvStatusS OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuCatvStatusPFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.36
onuCtcoamSkipPFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuCtcoamSkipPFEntry
```

```
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { srvProfileShow 36 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.36.1
onuCtcoamSkipPFEntry OBJECT-TYPE
      SYNTAX OnuCtcoamSkipPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { onuCtcOamSkipSrvId }
      ::= { onuCtcoamSkipPFTable 1 }


OnuCtcoamSkipPFEntry ::=
      SEQUENCE {
            onuCtcOamSkipSrvId
                  INTEGER,
            onuCtcoamSkipS
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.36.1.1
onuCtcOamSkipSrvId OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuCtcoamSkipPFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.36.1.2
onuCtcoamSkipS OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuCtcoamSkipPFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.37
onuWifiSwichPFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuWifiSwichPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { srvProfileShow 37 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.37.1
onuWifiSwichPFEntry OBJECT-TYPE
      SYNTAX OnuWifiSwichPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { onuWifiSwichSrvId }
      ::= { onuWifiSwichPFTable 1 }


OnuWifiSwichPFEntry ::=
      SEQUENCE {
            onuWifiSwichSrvId
                  INTEGER,
            onuWifiSwichAPModuleS
                  INTEGER,
            onuWifiSwichCountry
                  INTEGER,
            onuWifiSwichChannelS
                  INTEGER,
            onuWifiSwichStandardS
                  INTEGER,
            onuWifiSwitchPower
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.37.1.1
onuWifiSwichSrvId OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWifiSwichPFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.37.1.2
onuWifiSwichAPModuleS OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWifiSwichPFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.37.1.3
onuWifiSwichCountry OBJECT-TYPE
      SYNTAX INTEGER
            {
            ETSI(0),
            FCC(1)
            }
```

```
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWifiSwichPFEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.37.1.4
onuWifiSwichChannelS OBJECT-TYPE
      SYNTAX INTEGER (0..13)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWifiSwichPFEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.37.1.5
onuWifiSwichStandardS OBJECT-TYPE
      SYNTAX INTEGER
            {
            s80211b(0),
            s80211g(1),
            s80211bg(2),
            s80211n(3),
            s80211bgn(4)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWifiSwichPFEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.37.1.6
onuWifiSwitchPower OBJECT-TYPE
      SYNTAX INTEGER (0..20)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWifiSwichPFEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.38
onuWifiSsidPFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuWifiSsidPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { srvProfileShow 38 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.38.1
onuWifiSsidPFEntry OBJECT-TYPE
      SYNTAX OnuWifiSsidPFEntry
      MAX-ACCESS not-accessible
      STATUS current
```

```
      DESCRIPTION
            "Description."
      INDEX { onuWifiSsidSrvId, onuWifiSsidIdS }
      ::= { onuWifiSsidPFTable 1 }


OnuWifiSsidPFEntry ::=
      SEQUENCE {
            onuWifiSsidSrvId
                  INTEGER,
            onuWifiSsidIdS
                  Integer32,
            onuWifiSsidNameS
                  OCTET STRING,
            onuWifiSsidEnableS
                  INTEGER,
            onuWifiSsidHideS
                  INTEGER,
            onuWifiSsidAuthMode
                  INTEGER,
            onuWifiSsidEncryTpeS
                  INTEGER,
            ssidPreshareKeyS
                  OCTET STRING,
            ssidWpaRekeyIntervalS
                  INTEGER,
            ssidRadiusServIpTypeS
                  INTEGER,
            ssidRadiusServIp
                  OCTET STRING,
            ssidRadiusServIpPrefixLenS
                  INTEGER,
            ssidRadiusPortS
                  INTEGER,
            ssidRadiusKeyS
                  OCTET STRING,
            ssidWepEncryptionLevelS
                  INTEGER,
            ssidWepKeyIndexS
                  INTEGER,
            ssidWepKey1S
                  OCTET STRING,
            ssidWepKey2S
                  OCTET STRING,
            ssidWepKey3S
                  OCTET STRING,
            ssidWepKey4S
                  OCTET STRING
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.38.1.1
onuWifiSsidSrvId OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWifiSsidPFEntry 1 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.38.1.2
onuWifiSsidIdS OBJECT-TYPE
      SYNTAX Integer32 (1..4)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWifiSsidPFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.38.1.3
onuWifiSsidNameS OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWifiSsidPFEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.38.1.4
onuWifiSsidEnableS OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWifiSsidPFEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.38.1.5
onuWifiSsidHideS OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWifiSsidPFEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.38.1.6
onuWifiSsidAuthMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            open(1),
            shared(2),
            wepauto(3),
            wpapsk(4),
            wpa(5),
            wpa2psk(6),
```

```
            wpa2(7),
            wpa_wpa2(8),
            wpapsk_wpa2psk(9)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWifiSsidPFEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.38.1.7
onuWifiSsidEncryTpeS OBJECT-TYPE
      SYNTAX INTEGER
            {
            none(1),
            wep(2),
            tkip(3),
            aes(4),
            tkipaes(5)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWifiSsidPFEntry 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.38.1.8
ssidPreshareKeyS OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWifiSsidPFEntry 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.38.1.9
ssidWpaRekeyIntervalS OBJECT-TYPE
      SYNTAX INTEGER (0..4194303)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWifiSsidPFEntry 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.38.1.10
ssidRadiusServIpTypeS OBJECT-TYPE
      SYNTAX INTEGER
            {
            unknown(0),
            ipv4(1),
            ipv6(2),
            ipv4z(3),
            ipv6z(4),
            dns(16)
            }
```

```
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWifiSsidPFEntry 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.38.1.11
ssidRadiusServIp OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWifiSsidPFEntry 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.38.1.12
ssidRadiusServIpPrefixLenS OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWifiSsidPFEntry 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.38.1.13
ssidRadiusPortS OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWifiSsidPFEntry 13 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.38.1.14
ssidRadiusKeyS OBJECT-TYPE
      SYNTAX OCTET STRING (SIZE (0..32))
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWifiSsidPFEntry 14 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.38.1.15
ssidWepEncryptionLevelS OBJECT-TYPE
      SYNTAX INTEGER
            {
            s64bit(1),
            s128bit(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWifiSsidPFEntry 15 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.38.1.16
ssidWepKeyIndexS OBJECT-TYPE
      SYNTAX INTEGER (1..4)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWifiSsidPFEntry 16 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.38.1.17
ssidWepKey1S OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWifiSsidPFEntry 17 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.38.1.18
ssidWepKey2S OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWifiSsidPFEntry 18 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.38.1.19
ssidWepKey3S OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWifiSsidPFEntry 19 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.38.1.20
ssidWepKey4S OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWifiSsidPFEntry 20 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.39
onuWanConnPFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuWanConnPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { srvProfileShow 39 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.39.1
onuWanConnPFEntry OBJECT-TYPE
      SYNTAX OnuWanConnPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { wanConnSrvId, wanConnIndexS }
      ::= { onuWanConnPFTable 1 }


OnuWanConnPFEntry ::=
      SEQUENCE {
            wanConnSrvId
                  INTEGER,
            wanConnIndexS
                  Integer32,
            wanConnBindLanS
                  INTEGER,
            wanConnBindSsidS
                  INTEGER,
            wanModeS
                  INTEGER,
            wanConnTypeS
                  INTEGER,
            wanConnVlanIdS
                  INTEGER,
            wanConnVlanCosS
                  INTEGER,
            wanConnNatEnableS
                  INTEGER,
            wanConnModeS
                  INTEGER,
            wanConnIpAddressS
                  IpAddress,
            wanConnIpMaskS
                  IpAddress,
            wanConnGatewayS
                  IpAddress,
            wanConnMasterDns
                  IpAddress,
            wanConnSlaveDns
                  IpAddress,
            wanConnPppoeProxyS
                  INTEGER,
            wanConnPppoeUsernameS
                  OCTET STRING,
            wanConnPppoePasswordS
                  OCTET STRING,
            wanConnPppoeSerName
                  OCTET STRING,
            wanConnPppoeModeS
                  INTEGER,
            wanConnQosEnableS
                  INTEGER,
            wanConnVlanModeS
```

```
                INTEGER,
          wanConnTranslationEnableS
                INTEGER,
          wanConnTranslationVlanS
                INTEGER,
          wanConnTranslationCosS
                INTEGER,
          wanConnQinqEnableS
                INTEGER,
          wanConnQinqTpidS
                INTEGER,
          wanConnSvlanIdS
                INTEGER,
          wanConnSvlanCosS
                INTEGER
     }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.39.1.1
wanConnSrvId OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWanConnPFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.39.1.2
wanConnIndexS OBJECT-TYPE
      SYNTAX Integer32 (1..8)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWanConnPFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.39.1.3
wanConnBindLanS OBJECT-TYPE
      SYNTAX INTEGER (0..15)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWanConnPFEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.39.1.4
wanConnBindSsidS OBJECT-TYPE
      SYNTAX INTEGER (0..15)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWanConnPFEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.39.1.5
wanModeS OBJECT-TYPE
```

```
      SYNTAX INTEGER
            {
            internet(0),
            multicast(1),
            tr069(2),
            tr069_internet(3),
            tr069_voip(4),
            voip_internet(5),
            tr069_voip_internet(6),
            other(100)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWanConnPFEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.39.1.6
wanConnTypeS OBJECT-TYPE
      SYNTAX INTEGER
            {
            bridge(0),
            route(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWanConnPFEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.39.1.7
wanConnVlanIdS OBJECT-TYPE
      SYNTAX INTEGER (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWanConnPFEntry 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.39.1.8
wanConnVlanCosS OBJECT-TYPE
      SYNTAX INTEGER (0..7)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWanConnPFEntry 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.39.1.9
wanConnNatEnableS OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
```

```
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWanConnPFEntry 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.39.1.10
wanConnModeS OBJECT-TYPE
      SYNTAX INTEGER
            {
            dhcp(0),
            static(1),
            pppoe(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWanConnPFEntry 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.39.1.11
wanConnIpAddressS OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWanConnPFEntry 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.39.1.12
wanConnIpMaskS OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWanConnPFEntry 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.39.1.13
wanConnGatewayS OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWanConnPFEntry 13 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.39.1.14
wanConnMasterDns OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { onuWanConnPFEntry 14 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.39.1.15
wanConnSlaveDns OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWanConnPFEntry 15 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.39.1.16
wanConnPppoeProxyS OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWanConnPFEntry 16 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.39.1.17
wanConnPppoeUsernameS OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWanConnPFEntry 17 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.39.1.18
wanConnPppoePasswordS OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWanConnPFEntry 18 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.39.1.19
wanConnPppoeSerName OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWanConnPFEntry 19 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.39.1.20
wanConnPppoeModeS OBJECT-TYPE
```

```
      SYNTAX INTEGER
            {
            autoConnect(0),
            connectWhenPayload(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWanConnPFEntry 20 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.39.1.21
wanConnQosEnableS OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWanConnPFEntry 21 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.39.1.22
wanConnVlanModeS OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            tag(1),
            transparent(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWanConnPFEntry 22 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.39.1.23
wanConnTranslationEnableS OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWanConnPFEntry 23 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.39.1.24
wanConnTranslationVlanS OBJECT-TYPE
      SYNTAX INTEGER (0..4095)
      MAX-ACCESS read-write
```

```
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWanConnPFEntry 24 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.39.1.25
wanConnTranslationCosS OBJECT-TYPE
      SYNTAX INTEGER (0..7)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWanConnPFEntry 25 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.39.1.26
wanConnQinqEnableS OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWanConnPFEntry 26 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.39.1.27
wanConnQinqTpidS OBJECT-TYPE
      SYNTAX INTEGER (0..65534)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWanConnPFEntry 27 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.39.1.28
wanConnSvlanIdS OBJECT-TYPE
      SYNTAX INTEGER (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWanConnPFEntry 28 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.39.1.29
wanConnSvlanCosS OBJECT-TYPE
      SYNTAX INTEGER (0..7)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuWanConnPFEntry 29 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.40
portMacLimitPFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF PortMacLimitPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { srvProfileShow 40 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.40.1
portMacLimitPFEntry OBJECT-TYPE
      SYNTAX PortMacLimitPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { portMacLimitSrvId, portMacLimitEthNoS }
      ::= { portMacLimitPFTable 1 }


PortMacLimitPFEntry ::=
      SEQUENCE {
            portMacLimitSrvId
                  INTEGER,
            portMacLimitEthNoS
                  INTEGER,
            portMacLimitS
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.40.1.1
portMacLimitSrvId OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portMacLimitPFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.40.1.2
portMacLimitEthNoS OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portMacLimitPFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.40.1.3
portMacLimitS OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { portMacLimitPFEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.41
portPkgSuppressPFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF PortPkgSuppressPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { srvProfileShow 41 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.41.1
portPkgSuppressPFEntry OBJECT-TYPE
      SYNTAX PortPkgSuppressPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { portPkgSuppressSrvId, portPkgSuppressEthNoS }
      ::= { portPkgSuppressPFTable 1 }


PortPkgSuppressPFEntry ::=
      SEQUENCE {
            portPkgSuppressSrvId
                  INTEGER,
            portPkgSuppressEthNoS
                  INTEGER,
            portPkgSuppressBroadcastS
                  INTEGER,
            portPkgSuppressMulticastS
                  INTEGER,
            portPkgSuppressUnkownS
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.41.1.1
portPkgSuppressSrvId OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portPkgSuppressPFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.41.1.2
portPkgSuppressEthNoS OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portPkgSuppressPFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.41.1.3
```

```
portPkgSuppressBroadcastS OBJECT-TYPE
      SYNTAX INTEGER (0..1024000)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portPkgSuppressPFEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.41.1.4
portPkgSuppressMulticastS OBJECT-TYPE
      SYNTAX INTEGER (0..1024000)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portPkgSuppressPFEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.41.1.5
portPkgSuppressUnkownS OBJECT-TYPE
      SYNTAX INTEGER (0..1024000)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portPkgSuppressPFEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.42
portIsolateTable OBJECT-TYPE
      SYNTAX SEQUENCE OF PortIsolateEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { srvProfileShow 42 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.42.1
portIsolateEntry OBJECT-TYPE
      SYNTAX PortIsolateEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { portIsolateSrvId }
      ::= { portIsolateTable 1 }


PortIsolateEntry ::=
      SEQUENCE {
            portIsolateSrvId
                  INTEGER,
            portIsolateS
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.42.1.1
```

```
portIsolateSrvId OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portIsolateEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.42.1.2
portIsolateS OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portIsolateEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.43
portModeControlTable OBJECT-TYPE
      SYNTAX SEQUENCE OF PortModeControlEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { srvProfileShow 43 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.43.1
portModeControlEntry OBJECT-TYPE
      SYNTAX PortModeControlEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { portModeControlSrvId, portModeControlEthNoS }
      ::= { portModeControlTable 1 }


PortModeControlEntry ::=
      SEQUENCE {
            portModeControlSrvId
                  Integer32,
            portModeControlEthNoS
                  Integer32,
            portModeControlS
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.43.1.1
portModeControlSrvId OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
```

```
      DESCRIPTION
            "Description."
      ::= { portModeControlEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.43.1.2
portModeControlEthNoS OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portModeControlEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.43.1.3
portModeControlS OBJECT-TYPE
      SYNTAX INTEGER
            {
            s10hd(1),
            s10fd(2),
            s100hd(3),
            s100fd(4),
            s1000hd(5),
            s1000fd(6),
            s10000fd(7)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { portModeControlEntry 3 }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.44
onuDhcpServerTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuDhcpServerEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { srvProfileShow 44 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.44.1
onuDhcpServerEntry OBJECT-TYPE
      SYNTAX OnuDhcpServerEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { onuDhcpSrvId }
      ::= { onuDhcpServerTable 1 }


OnuDhcpServerEntry ::=
      SEQUENCE {
            onuDhcpSrvId
                  Integer32,
            onuDhcpLanIp
```

```
                IpAddress,
            onuDhcpMask
                IpAddress,
            onuDhcpServerEable
                INTEGER,
            onuDhcpLease
                Unsigned32,
            onuDhcpBeginIp
                IpAddress,
            onuDhcpEndIp
                IpAddress,
            onuDhcpPoolType
                INTEGER,
            onuDhcpMasterDns
                IpAddress,
            onuDhcpSlaveDns
                IpAddress,
            onuDhcpGateway
                IpAddress,
            onuDhcpRelayIp
                IpAddress
        }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.44.1.1
onuDhcpSrvId OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuDhcpServerEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.44.1.2
onuDhcpLanIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuDhcpServerEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.44.1.3
onuDhcpMask OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuDhcpServerEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.44.1.4
onuDhcpServerEable OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1),
```

```
            relay(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuDhcpServerEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.44.1.5
onuDhcpLease OBJECT-TYPE
      SYNTAX Unsigned32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuDhcpServerEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.44.1.6
onuDhcpBeginIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuDhcpServerEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.44.1.7
onuDhcpEndIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuDhcpServerEntry 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.44.1.8
onuDhcpPoolType OBJECT-TYPE
      SYNTAX INTEGER
            {
            pc(0),
            camera(1),
            stb(2),
            ip_phone(3)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuDhcpServerEntry 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.44.1.9
onuDhcpMasterDns OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
```

```
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuDhcpServerEntry 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.44.1.10
onuDhcpSlaveDns OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuDhcpServerEntry 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.44.1.11
onuDhcpGateway OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuDhcpServerEntry 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.44.1.12
onuDhcpRelayIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuDhcpServerEntry 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.45
onuDhcpOption82Table OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuDhcpOption82Entry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { srvProfileShow 45 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.45.1
onuDhcpOption82Entry OBJECT-TYPE
      SYNTAX OnuDhcpOption82Entry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { onuDhcpOption82SrvId }
      ::= { onuDhcpOption82Table 1 }


OnuDhcpOption82Entry ::=
      SEQUENCE {
```

```
            onuDhcpOption82SrvId
                  Integer32,
            onuDhcpOption82Enable
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.45.1.1
onuDhcpOption82SrvId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuDhcpOption82Entry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.45.1.2
onuDhcpOption82Enable OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuDhcpOption82Entry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.46
onuPPPoETable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuPPPoEEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { srvProfileShow 46 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.46.1
onuPPPoEEntry OBJECT-TYPE
      SYNTAX OnuPPPoEEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { onuPPPoESrvId }
      ::= { onuPPPoETable 1 }


OnuPPPoEEntry ::=
      SEQUENCE {
            onuPPPoESrvId
                  Integer32,
            onuPPPoEEnable
                  INTEGER
       }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.46.1.1
onuPPPoESrvId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPPPoEEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.46.1.2
onuPPPoEEnable OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPPPoEEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.47
onuDhcpV6Table OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuDhcpV6Entry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { srvProfileShow 47 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.47.1
onuDhcpV6Entry OBJECT-TYPE
      SYNTAX OnuDhcpV6Entry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { onuDhcpV6SrvId }
      ::= { onuDhcpV6Table 1 }


OnuDhcpV6Entry ::=
      SEQUENCE {
            onuDhcpV6SrvId
                  Integer32,
            onuDhcpV6Option18Enable
                  INTEGER,
            onuDhcpV6Option37Enable
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.47.1.1
onuDhcpV6SrvId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-write
```

```
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuDhcpV6Entry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.47.1.2
onuDhcpV6Option18Enable OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuDhcpV6Entry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.2.47.1.3
onuDhcpV6Option37Enable OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuDhcpV6Entry 3 }



-- 1.3.6.1.4.1.37950.1.1.5.12.9.3
voipProfileShow OBJECT IDENTIFIER ::= { onuProfileShow 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.1
onuPotsCountPFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF OnuPotsCountPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipProfileShow 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.1.1
onuPotsCountPFEntry OBJECT-TYPE
      SYNTAX OnuPotsCountPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { onuPotsCountVoipId }
      ::= { onuPotsCountPFTable 1 }
```

```
OnuPotsCountPFEntry ::=
      SEQUENCE {
            onuPotsCountVoipId
                  Integer32,
            onuPotsCountS
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.1.1.1
onuPotsCountVoipId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPotsCountPFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.1.1.2
onuPotsCountS OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { onuPotsCountPFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.2
voipGlobalPFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF VoipGlobalPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipProfileShow 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.2.1
voipGlobalPFEntry OBJECT-TYPE
      SYNTAX VoipGlobalPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { voipGlobalVoipId }
      ::= { voipGlobalPFTable 1 }


VoipGlobalPFEntry ::=
      SEQUENCE {
            voipGlobalVoipId
                  Integer32,
            voipGlobalIpModeS
                  INTEGER,
            voipGlobalIpAddrS
                  IpAddress,
            voipGlobalIpMaskS
```

```
                IpAddress,
            voipGlobalIpGwS
                IpAddress,
            voipGlobalPppoeModeS
                INTEGER,
            voipGlobalPppoeUsrS
                OCTET STRING,
            voipGlobalPppoePwS
                OCTET STRING,
            voipGlobalModeS
                INTEGER,
            voipGlobalCvlanS
                INTEGER,
            voipGlobalSvlanS
                INTEGER,
            voipGlobalPriS
                INTEGER
        }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.2.1.1
voipGlobalVoipId OBJECT-TYPE
      SYNTAX Integer32 (0..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipGlobalPFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.2.1.2
voipGlobalIpModeS OBJECT-TYPE
      SYNTAX INTEGER
            {
            staticip(0),
            dhcp(1),
            pppoe(2)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipGlobalPFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.2.1.3
voipGlobalIpAddrS OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipGlobalPFEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.2.1.4
voipGlobalIpMaskS OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
      STATUS current
```

```
      DESCRIPTION
            "Description."
      ::= { voipGlobalPFEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.2.1.5
voipGlobalIpGwS OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipGlobalPFEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.2.1.6
voipGlobalPppoeModeS OBJECT-TYPE
      SYNTAX INTEGER
            {
            auto(1),
            chap(2),
            pap(3)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipGlobalPFEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.2.1.7
voipGlobalPppoeUsrS OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipGlobalPFEntry 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.2.1.8
voipGlobalPppoePwS OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipGlobalPFEntry 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.2.1.9
voipGlobalModeS OBJECT-TYPE
      SYNTAX INTEGER
            {
            transparent(1),
            tag(2),
            vlan_stacking(3)
            }
      MAX-ACCESS read-only
```

```
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipGlobalPFEntry 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.2.1.10
voipGlobalCvlanS OBJECT-TYPE
      SYNTAX INTEGER (0..4095)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipGlobalPFEntry 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.2.1.11
voipGlobalSvlanS OBJECT-TYPE
      SYNTAX INTEGER (0..4095)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipGlobalPFEntry 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.2.1.12
voipGlobalPriS OBJECT-TYPE
      SYNTAX INTEGER (0..7)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipGlobalPFEntry 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.3
h248ProPFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF H248ProPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipProfileShow 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.3.1
h248ProPFEntry OBJECT-TYPE
      SYNTAX H248ProPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { h248ProVoipId }
      ::= { h248ProPFTable 1 }


H248ProPFEntry ::=
      SEQUENCE {
```

```
            h248ProVoipId
                  Integer32,
            h248ProMgPortS
                  INTEGER,
            h248ProMgcIpS
                  IpAddress,
            h248ProMgComPortS
                  INTEGER,
            h248ProBakMgcIpS
                  IpAddress,
            h248ProBakMgcPortS
                  INTEGER,
            h248ProRegModeS
                  INTEGER,
            h248ProMIDS
                  OCTET STRING,
            h248ProHBModeS
                  INTEGER,
            h248ProHBCycleS
                  INTEGER,
            h248ProHBCountS
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.3.1.1
h248ProVoipId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248ProPFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.3.1.2
h248ProMgPortS OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248ProPFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.3.1.3
h248ProMgcIpS OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248ProPFEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.3.1.4
h248ProMgComPortS OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-only
      STATUS current
```

```
      DESCRIPTION
            "Description."
      ::= { h248ProPFEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.3.1.5
h248ProBakMgcIpS OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248ProPFEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.3.1.6
h248ProBakMgcPortS OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248ProPFEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.3.1.7
h248ProRegModeS OBJECT-TYPE
      SYNTAX INTEGER
            {
            ip_addr(0),
            realm_name(1),
            device_name(2)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248ProPFEntry 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.3.1.8
h248ProMIDS OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248ProPFEntry 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.3.1.9
h248ProHBModeS OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            h248(1)
            }
      MAX-ACCESS read-only
      STATUS current
```

```
      DESCRIPTION
            "Description."
      ::= { h248ProPFEntry 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.3.1.10
h248ProHBCycleS OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248ProPFEntry 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.3.1.11
h248ProHBCountS OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248ProPFEntry 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.4
h248RtpTidPFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF H248RtpTidPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipProfileShow 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.4.1
h248RtpTidPFEntry OBJECT-TYPE
      SYNTAX H248RtpTidPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { h248RtpTidVoipId }
      ::= { h248RtpTidPFTable 1 }


H248RtpTidPFEntry ::=
      SEQUENCE {
            h248RtpTidVoipId
                  Integer32,
            h248RtpTidNumberS
                  INTEGER,
            h248RtpTidPrefixS
                  OCTET STRING,
            h248RtpTidBegin0S
                  Unsigned32,
            h248RtpTidBegin1S
                  Unsigned32,
            h248RtpTidModeS
```

```
                INTEGER,
            h248RtpTidDGLengthS
                INTEGER
        }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.4.1.1
h248RtpTidVoipId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248RtpTidPFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.4.1.2
h248RtpTidNumberS OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248RtpTidPFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.4.1.3
h248RtpTidPrefixS OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248RtpTidPFEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.4.1.4
h248RtpTidBegin0S OBJECT-TYPE
      SYNTAX Unsigned32 (0..4294967295)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248RtpTidPFEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.4.1.5
h248RtpTidBegin1S OBJECT-TYPE
      SYNTAX Unsigned32 (0..4294967295)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248RtpTidPFEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.4.1.6
h248RtpTidModeS OBJECT-TYPE
      SYNTAX INTEGER
            {
```

```
            align(1),
            unalign(2)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248RtpTidPFEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.4.1.7
h248RtpTidDGLengthS OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248RtpTidPFEntry 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.5
h248UserTidPFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF H248UserTidPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipProfileShow 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.5.1
h248UserTidPFEntry OBJECT-TYPE
      SYNTAX H248UserTidPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { h248UserTidVoipId, h248UserTidPotsNoS }
      ::= { h248UserTidPFTable 1 }


H248UserTidPFEntry ::=
      SEQUENCE {
            h248UserTidVoipId
                  Integer32,
            h248UserTidPotsNoS
                  INTEGER,
            h248UserTidS
                  OCTET STRING
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.5.1.1
h248UserTidVoipId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248UserTidPFEntry 1 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.5.1.2
h248UserTidPotsNoS OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248UserTidPFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.5.1.3
h248UserTidS OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { h248UserTidPFEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.6
sipProPFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF SipProPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipProfileShow 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.6.1
sipProPFEntry OBJECT-TYPE
      SYNTAX SipProPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { sipProVoipId }
      ::= { sipProPFTable 1 }


SipProPFEntry ::=
      SEQUENCE {
            sipProVoipId
                  Integer32,
            sipProMgPortS
                  INTEGER,
            sipProProxySrvIpS
                  IpAddress,
            sipProProxySrvPortS
                  INTEGER,
            sipProBKProxySrvIpS
                  IpAddress,
            sipProBKProxySrvPortS
                  INTEGER,
            sipProRegSrvIpS
                  OCTET STRING,
```

```
            sipProRegSrvPortS
                  INTEGER,
            sipProBKRegSrvIpS
                  IpAddress,
            sipProBKRegSrvPortS
                  INTEGER,
            sipProOutBoundServIpS
                  IpAddress,
            sipProOutBoundServPortS
                  INTEGER,
            sipProRegInterS
                  INTEGER,
            sipProHBEnableS
                  INTEGER,
            sipProHBCycleS
                  INTEGER,
            sipProHBCountS
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.6.1.1
sipProVoipId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipProPFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.6.1.2
sipProMgPortS OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipProPFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.6.1.3
sipProProxySrvIpS OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipProPFEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.6.1.4
sipProProxySrvPortS OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipProPFEntry 4 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.6.1.5
sipProBKProxySrvIpS OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipProPFEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.6.1.6
sipProBKProxySrvPortS OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipProPFEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.6.1.7
sipProRegSrvIpS OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipProPFEntry 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.6.1.8
sipProRegSrvPortS OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipProPFEntry 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.6.1.9
sipProBKRegSrvIpS OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipProPFEntry 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.6.1.10
sipProBKRegSrvPortS OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipProPFEntry 10 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.6.1.11
sipProOutBoundServIpS OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipProPFEntry 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.6.1.12
sipProOutBoundServPortS OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipProPFEntry 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.6.1.13
sipProRegInterS OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipProPFEntry 13 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.6.1.14
sipProHBEnableS OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipProPFEntry 14 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.6.1.15
sipProHBCycleS OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipProPFEntry 15 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.6.1.16
sipProHBCountS OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
```

```
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipProPFEntry 16 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.7
sipUserPFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF SipUserPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipProfileShow 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.7.1
sipUserPFEntry OBJECT-TYPE
      SYNTAX SipUserPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { sipUserVoipId, sipUserPotsNoS }
      ::= { sipUserPFTable 1 }


SipUserPFEntry ::=
      SEQUENCE {
            sipUserVoipId
                  Integer32,
            sipUserPotsNoS
                  INTEGER,
            sipUserAccountS
                  OCTET STRING,
            sipUserNameS
                  OCTET STRING,
            sipUserPwS
                  OCTET STRING
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.7.1.1
sipUserVoipId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipUserPFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.7.1.2
sipUserPotsNoS OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { sipUserPFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.7.1.3
sipUserAccountS OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipUserPFEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.7.1.4
sipUserNameS OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipUserPFEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.7.1.5
sipUserPwS OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipUserPFEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.8
sipDigitPFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF SipDigitPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipProfileShow 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.8.1
sipDigitPFEntry OBJECT-TYPE
      SYNTAX SipDigitPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { sipDigitVoipID }
      ::= { sipDigitPFTable 1 }


SipDigitPFEntry ::=
      SEQUENCE {
            sipDigitVoipID
                  Integer32,
            sipDigitNumS
```

```
                  INTEGER,
            sipDigitNumBlockS
                  INTEGER,
            sipDigitMapS
                  OCTET STRING
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.8.1.1
sipDigitVoipID OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipDigitPFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.8.1.2
sipDigitNumS OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipDigitPFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.8.1.3
sipDigitNumBlockS OBJECT-TYPE
      SYNTAX INTEGER (0..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipDigitPFEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.8.1.4
sipDigitMapS OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { sipDigitPFEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.9
voipFaxModemPFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF VoipFaxModemPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipProfileShow 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.9.1
voipFaxModemPFEntry OBJECT-TYPE
```

```
      SYNTAX VoipFaxModemPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { voipFaxModemVoipId }
      ::= { voipFaxModemPFTable 1 }


VoipFaxModemPFEntry ::=
      SEQUENCE {
            voipFaxModemVoipId
                  Integer32,
            voipFaxModemT38EnS
                  INTEGER,
            voipFaxModemControlS
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.9.1.1
voipFaxModemVoipId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipFaxModemPFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.9.1.2
voipFaxModemT38EnS OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipFaxModemPFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.9.1.3
voipFaxModemControlS OBJECT-TYPE
      SYNTAX INTEGER
            {
            negotiation(1),
            auto_vbd(2)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipFaxModemPFEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.10
voipPotsManagePFTable OBJECT-TYPE
```

```
      SYNTAX SEQUENCE OF VoipPotsManagePFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipProfileShow 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.10.1
voipPotsManagePFEntry OBJECT-TYPE
      SYNTAX VoipPotsManagePFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { voipPotsManageVoipId, voipPotsManagNoS }
      ::= { voipPotsManagePFTable 1 }


VoipPotsManagePFEntry ::=
      SEQUENCE {
            voipPotsManageVoipId
                  Integer32,
            voipPotsManagNoS
                  INTEGER,
            voipPotsManageEnableS
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.10.1.1
voipPotsManageVoipId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipPotsManagePFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.10.1.2
voipPotsManagNoS OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipPotsManagePFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.10.1.3
voipPotsManageEnableS OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
```

```
            "Description."
      ::= { voipPotsManagePFEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.11
voipTimerTable OBJECT-TYPE
      SYNTAX SEQUENCE OF VoipTimerEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipProfileShow 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.11.1
voipTimerEntry OBJECT-TYPE
      SYNTAX VoipTimerEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { voipTimerPfId }
      ::= { voipTimerTable 1 }


VoipTimerEntry ::=
      SEQUENCE {
            voipTimerPfId
                  Integer32,
            voipMaxWaitTime
                  Integer32,
            voipStartTimer
                  Integer32,
            voipLongTimer
                  Integer32,
            voipShortTimer
                  Integer32,
            voipDigitMapNotify
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.11.1.1
voipTimerPfId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipTimerEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.11.1.2
voipMaxWaitTime OBJECT-TYPE
      SYNTAX Integer32 (0..254)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipTimerEntry 2 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.11.1.3
voipStartTimer OBJECT-TYPE
      SYNTAX Integer32 (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipTimerEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.11.1.4
voipLongTimer OBJECT-TYPE
      SYNTAX Integer32 (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipTimerEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.11.1.5
voipShortTimer OBJECT-TYPE
      SYNTAX Integer32 (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipTimerEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.11.1.6
voipDigitMapNotify OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipTimerEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.12
potsParamterTable OBJECT-TYPE
      SYNTAX SEQUENCE OF PotsParamterEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipProfileShow 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.12.1
potsParamterEntry OBJECT-TYPE
      SYNTAX PotsParamterEntry
```

```
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { potsPtPfId, potsPtPotsNo }
      ::= { potsParamterTable 1 }


PotsParamterEntry ::=
      SEQUENCE {
            potsPtPfId
                  Integer32,
            potsPtPotsNo
                  Integer32,
            potsPtVad
                  INTEGER,
            potsPtEchoCancel
                  INTEGER,
            potsPtInputGain
                  Integer32,
            potsPtOutputGain
                  Integer32,
            potsPtDtmfMode
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.12.1.1
potsPtPfId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { potsParamterEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.12.1.2
potsPtPotsNo OBJECT-TYPE
      SYNTAX Integer32 (1..255)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { potsParamterEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.12.1.3
potsPtVad OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { potsParamterEntry 3 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.12.1.4
potsPtEchoCancel OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { potsParamterEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.12.1.5
potsPtInputGain OBJECT-TYPE
      SYNTAX Integer32 (-32..32)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { potsParamterEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.12.1.6
potsPtOutputGain OBJECT-TYPE
      SYNTAX Integer32 (-32..32)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { potsParamterEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.12.1.7
potsPtDtmfMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            transparent(0),
            rfc2833(1),
            rfc2833_redundancy(2),
            outband(3)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { potsParamterEntry 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.13
voipParamTable OBJECT-TYPE
      SYNTAX SEQUENCE OF VoipParamEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipProfileShow 13 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.13.1
voipParamEntry OBJECT-TYPE
      SYNTAX VoipParamEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { voipParamVoipId }
      ::= { voipParamTable 1 }


VoipParamEntry ::=
      SEQUENCE {
            voipParamVoipId
                  Integer32,
            voipParamIpMode
                  INTEGER,
            voipParamIp
                  IpAddress,
            voipParamMask
                  IpAddress,
            voipParamGw
                  IpAddress,
            voipRtpIp
                  IpAddress,
            voipRtpMask
                  IpAddress,
            voipRtpGw
                  IpAddress,
            voipDnsMaster
                  IpAddress,
            voipDnsSlave
                  IpAddress,
            voipDhcpOption60En
                  INTEGER,
            voipDhcpOption60Base
                  OCTET STRING,
            voipDhcpOption60Val
                  OCTET STRING,
            voipParamPPPoEMode
                  INTEGER,
            voipPPPoEUsername
                  OCTET STRING,
            voipPPPoEPassword
                  OCTET STRING,
            voipSVlanTpid
                  Integer32,
            voipSVlanId
                  Integer32,
            voipSVlanCos
                  Integer32,
            voipCVlanTpid
                  Integer32,
            voipCVlanId
                  Integer32,
            voipCVlanCos
                  Integer32,
```

```
            voipRtpSVlanTpid
                  Integer32,
            voipRtpSVlanId
                  Integer32,
            voipRtpSVlanCos
                  Integer32,
            voipRtpCVlanTpid
                  Integer32,
            voipRtpCVlanId
                  Integer32,
            voipRtpCVlanCos
                  Integer32
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.13.1.1
voipParamVoipId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipParamEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.13.1.2
voipParamIpMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            static(1),
            dhcp(2),
            pppoe(3)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipParamEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.13.1.3
voipParamIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipParamEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.13.1.4
voipParamMask OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipParamEntry 4 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.13.1.5
voipParamGw OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipParamEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.13.1.6
voipRtpIp OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipParamEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.13.1.7
voipRtpMask OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipParamEntry 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.13.1.8
voipRtpGw OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipParamEntry 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.13.1.9
voipDnsMaster OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipParamEntry 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.13.1.10
voipDnsSlave OBJECT-TYPE
      SYNTAX IpAddress
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipParamEntry 10 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.13.1.11
voipDhcpOption60En OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipParamEntry 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.13.1.12
voipDhcpOption60Base OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipParamEntry 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.13.1.13
voipDhcpOption60Val OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipParamEntry 13 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.13.1.14
voipParamPPPoEMode OBJECT-TYPE
      SYNTAX INTEGER
            {
            auto(1),
            chap(2),
            pap(3)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipParamEntry 14 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.13.1.15
voipPPPoEUsername OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipParamEntry 15 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.13.1.16
voipPPPoEPassword OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipParamEntry 16 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.13.1.17
voipSVlanTpid OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipParamEntry 17 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.13.1.18
voipSVlanId OBJECT-TYPE
      SYNTAX Integer32 (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipParamEntry 18 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.13.1.19
voipSVlanCos OBJECT-TYPE
      SYNTAX Integer32 (0..7)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipParamEntry 19 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.13.1.20
voipCVlanTpid OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipParamEntry 20 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.13.1.21
voipCVlanId OBJECT-TYPE
      SYNTAX Integer32 (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipParamEntry 21 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.13.1.22
voipCVlanCos OBJECT-TYPE
      SYNTAX Integer32 (0..7)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipParamEntry 22 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.13.1.23
voipRtpSVlanTpid OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipParamEntry 23 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.13.1.24
voipRtpSVlanId OBJECT-TYPE
      SYNTAX Integer32 (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipParamEntry 24 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.13.1.25
voipRtpSVlanCos OBJECT-TYPE
      SYNTAX Integer32 (0..7)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipParamEntry 25 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.13.1.26
voipRtpCVlanTpid OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipParamEntry 26 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.13.1.27
voipRtpCVlanId OBJECT-TYPE
      SYNTAX Integer32 (0..4095)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { voipParamEntry 27 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.13.1.28
voipRtpCVlanCos OBJECT-TYPE
      SYNTAX Integer32 (0..7)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipParamEntry 28 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.14
voipSipParamTable OBJECT-TYPE
      SYNTAX SEQUENCE OF VoipSipParamEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipProfileShow 14 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.14.1
voipSipParamEntry OBJECT-TYPE
      SYNTAX VoipSipParamEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { sipVoipId }
      ::= { voipSipParamTable 1 }


VoipSipParamEntry ::=
      SEQUENCE {
            sipVoipId
                  Integer32,
            sipProxyServName
                  OCTET STRING,
            sipProxyServPort
                  Integer32,
            sipBakProxyServName
                  OCTET STRING,
            sipBakProxyServPort
                  Integer32,
            sipRegServName
                  OCTET STRING,
            sipRegServPort
                  Integer32,
            sipBakRegServName
                  OCTET STRING,
            sipBakRegServPort
                  Integer32,
            sipOutBndServName
                  OCTET STRING,
            sipOutBndServPort
                  Integer32,
            sipMgPort
```

```
                Integer32,
          sipRegInterValue
                Integer32,
          sipHBeatCfg
                INTEGER,
          sipHBeatCycle
                Integer32,
          sipHBeatCount
                Integer32
     }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.14.1.1
sipVoipId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipSipParamEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.14.1.2
sipProxyServName OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipSipParamEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.14.1.3
sipProxyServPort OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipSipParamEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.14.1.4
sipBakProxyServName OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipSipParamEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.14.1.5
sipBakProxyServPort OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipSipParamEntry 5 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.14.1.6
sipRegServName OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipSipParamEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.14.1.7
sipRegServPort OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipSipParamEntry 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.14.1.8
sipBakRegServName OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipSipParamEntry 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.14.1.9
sipBakRegServPort OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipSipParamEntry 9 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.14.1.10
sipOutBndServName OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipSipParamEntry 10 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.14.1.11
sipOutBndServPort OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
```

```
      ::= { voipSipParamEntry 11 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.14.1.12
sipMgPort OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipSipParamEntry 12 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.14.1.13
sipRegInterValue OBJECT-TYPE
      SYNTAX Integer32 (0..10000000)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipSipParamEntry 13 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.14.1.14
sipHBeatCfg OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            active(1),
            passive(2)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipSipParamEntry 14 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.14.1.15
sipHBeatCycle OBJECT-TYPE
      SYNTAX Integer32 (1..65525)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipSipParamEntry 15 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.3.14.1.16
sipHBeatCount OBJECT-TYPE
      SYNTAX Integer32 (1..65535)
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { voipSipParamEntry 16 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.9.4
alarmProfileShow OBJECT IDENTIFIER ::= { onuProfileShow 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.4.1
alarmOnuPFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF AlarmOnuPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmProfileShow 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.4.1.1
alarmOnuPFEntry OBJECT-TYPE
      SYNTAX AlarmOnuPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { alarmOnuAlarmId, alarmOnunTypeS }
      ::= { alarmOnuPFTable 1 }


AlarmOnuPFEntry ::=
      SEQUENCE {
            alarmOnuAlarmId
                  Integer32,
            alarmOnunTypeS
                  INTEGER,
            alarmOnuEnableS
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.4.1.1.1
alarmOnuAlarmId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOnuPFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.4.1.1.2
alarmOnunTypeS OBJECT-TYPE
      SYNTAX INTEGER
            {
            equipmentAlarm(1),
            powerAlarm(2),
            batteryMissing(3),
            batteryFailure(4),
            physicalIntrusion(5),
            onuSelfTestFailure(6),
            iadConnectionFailure(7),
            ponIfSwitch(8),
            sleepStatusUpdate(9)
            }
```

```
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOnuPFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.4.1.1.3
alarmOnuEnableS OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOnuPFEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.4.2
alarmOnuThrPFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF AlarmOnuThrPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmProfileShow 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.4.2.1
alarmOnuThrPFEntry OBJECT-TYPE
      SYNTAX AlarmOnuThrPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { alarmOnuThrAlarmId, alarmOnuThrTypeS }
      ::= { alarmOnuThrPFTable 1 }


AlarmOnuThrPFEntry ::=
      SEQUENCE {
            alarmOnuThrAlarmId
                  Integer32,
            alarmOnuThrTypeS
                  INTEGER,
            alarmOnuThrEnS
                  INTEGER,
            alarmOnuThrAlarmS
                  INTEGER,
            alarmOnuThrClearS
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.4.2.1.1
alarmOnuThrAlarmId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
```

```
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOnuThrPFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.4.2.1.2
alarmOnuThrTypeS OBJECT-TYPE
      SYNTAX INTEGER
            {
            onuTempHighAlarm(1),
            onuTempLowAlarm(2),
            batteryVoltLow(3)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOnuThrPFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.4.2.1.3
alarmOnuThrEnS OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOnuThrPFEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.4.2.1.4
alarmOnuThrAlarmS OBJECT-TYPE
      SYNTAX INTEGER
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOnuThrPFEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.4.2.1.5
alarmOnuThrClearS OBJECT-TYPE
      SYNTAX INTEGER
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmOnuThrPFEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.4.3
alarmPonPFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF AlarmPonPFEntry
```

```
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmProfileShow 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.4.3.1
alarmPonPFEntry OBJECT-TYPE
      SYNTAX AlarmPonPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { alarmPonAlarmId, alarmPonTypeS }
      ::= { alarmPonPFTable 1 }


AlarmPonPFEntry ::=
      SEQUENCE {
            alarmPonAlarmId
                  Integer32,
            alarmPonTypeS
                  INTEGER,
            alarmPonEnableS
                  INTEGER,
            alarmPonAlarmS
                  INTEGER,
            alarmPonClearS
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.4.3.1.1
alarmPonAlarmId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmPonPFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.4.3.1.2
alarmPonTypeS OBJECT-TYPE
      SYNTAX INTEGER
            {
            rxPowerHighAlarm(1),
            rxPowerLowAlarm(2),
            txPowerHighAlarm(3),
            txPowerLowAlarm(4),
            txBiasHighAlarm(5),
            txBiasLowAlarm(6),
            vccHighAlarm(7),
            vccLowAlarm(8),
            tempHighAlarm(9),
            tempLowAlarm(10),
            rxPowerHighWarn(11),
            rxPowerLowWarn(12),
            txPowerHighWarn(13),
```

```
            txPowerLowWarn(14),
            txBiasHighWarn(15),
            txBiasLowWarn(16),
            vccHighWarn(17),
            vccLowWarn(18),
            tempHighWarn(19),
            tempLowWarn(20)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmPonPFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.4.3.1.3
alarmPonEnableS OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmPonPFEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.4.3.1.4
alarmPonAlarmS OBJECT-TYPE
      SYNTAX INTEGER
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmPonPFEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.4.3.1.5
alarmPonClearS OBJECT-TYPE
      SYNTAX INTEGER
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmPonPFEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.4.4
alarmPonStatPFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF AlarmPonStatPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmProfileShow 4 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.9.4.4.1
alarmPonStatPFEntry OBJECT-TYPE
      SYNTAX AlarmPonStatPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { alarmPonStatAlarmId, alarmPonStatTypeS }
      ::= { alarmPonStatPFTable 1 }


AlarmPonStatPFEntry ::=
      SEQUENCE {
            alarmPonStatAlarmId
                  Integer32,
            alarmPonStatTypeS
                  INTEGER,
            alarmPonStatEnableS
                  INTEGER,
            alarmPonStatThldS
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.4.4.1.1
alarmPonStatAlarmId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmPonStatPFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.4.4.1.2
alarmPonStatTypeS OBJECT-TYPE
      SYNTAX INTEGER
            {
            downstreamDropEventsAlarm(1),
            upstreamDropEventsAlarm(2),
            downstreamCRCErrorFramesAlarm(3),
            upstreamCRCErrorFramesAlarm(4),
            downstreamUndersizeFramesAlarm(5),
            upstreamUndersizeFramesAlarm(6),
            downstreamOversizeFramesAlarm(7),
            upstreamOversizeFramesAlarm(8),
            downstreamFragmentsAlarm(9),
            upstreamFragmentsAlarm(10),
            downstreamJabbersAlarm(11),
            upstreamJabbersAlarm(12),
            downstreamDiscardsAlarm(13),
            upstreamDiscardsAlarm(14),
            downstreamErrorsAlarm(15),
            upstreamErrorsAlarm(16),
            downstreamDropEventsWarning(17),
            upstreamDropEventsWarning(18),
            downstreamCRCErrorFramesWarning(19),
            upstreamCRCErrorFramesWarning(20),
            downstreamUndersizeFramesWarning(21),
            upstreamUndersizeFramesWarning(22),
```

```
            downstreamOversizeFramesWarning(23),
            upstreamOversizeFramesWarning(24),
            downstreamFragmentsWarning(25),
            upstreamFragmentsWarning(26),
            downstreamJabbersWarning(27),
            upstreamJabbersWarning(28),
            downstreamDiscardsWarning(29),
            upstreamDiscardsWarning(30),
            downstreamErrorsWarning(31),
            upstreamErrorsWarning(32)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmPonStatPFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.4.4.1.3
alarmPonStatEnableS OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmPonStatPFEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.4.4.1.4
alarmPonStatThldS OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmPonStatPFEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.4.5
alarmPortPFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF AlarmPortPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmProfileShow 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.4.5.1
alarmPortPFEntry OBJECT-TYPE
      SYNTAX AlarmPortPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
```

```
      INDEX { alarmPortAlarmId, alarmPortNoS, alarmPortTpyeS }
      ::= { alarmPortPFTable 1 }


AlarmPortPFEntry ::=
      SEQUENCE {
            alarmPortAlarmId
                  Integer32,
            alarmPortNoS
                  INTEGER,
            alarmPortTpyeS
                  INTEGER,
            alarmPortEnableS
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.4.5.1.1
alarmPortAlarmId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmPortPFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.4.5.1.2
alarmPortNoS OBJECT-TYPE
      SYNTAX INTEGER (1..255)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmPortPFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.4.5.1.3
alarmPortTpyeS OBJECT-TYPE
      SYNTAX INTEGER
            {
            ethPortAutoNegFailure(1),
            ethPortLos(2),
            ethPortFailure(3),
            ethPortLoopback(4),
            ethPortCongestion(5)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmPortPFEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.4.5.1.4
alarmPortEnableS OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
```

```
                }
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
                "Description."
        ::= { alarmPortPFEntry 4 }


    -- 1.3.6.1.4.1.37950.1.1.5.12.9.4.6
    alarmPortStatPFTable OBJECT-TYPE
        SYNTAX SEQUENCE OF AlarmPortStatPFEntry
        MAX-ACCESS not-accessible
        STATUS current
        DESCRIPTION
                "Description."
        ::= { alarmProfileShow 6 }


    -- 1.3.6.1.4.1.37950.1.1.5.12.9.4.6.1
    alarmPortStatPFEntry OBJECT-TYPE
        SYNTAX AlarmPortStatPFEntry
        MAX-ACCESS not-accessible
        STATUS current
        DESCRIPTION
                "Description."
        INDEX { alarmPortStatAlarmID, alarmPortStatEthNoS,
alarmPortStatTypeS }
        ::= { alarmPortStatPFTable 1 }


    AlarmPortStatPFEntry ::=
        SEQUENCE {
                alarmPortStatAlarmID
                        Integer32,
                alarmPortStatEthNoS
                        INTEGER,
                alarmPortStatTypeS
                        INTEGER,
                alarmPortStatEnableS
                        INTEGER,
                alarmPortStatTrldS
                        INTEGER
         }

    -- 1.3.6.1.4.1.37950.1.1.5.12.9.4.6.1.1
    alarmPortStatAlarmID OBJECT-TYPE
        SYNTAX Integer32 (0..65535)
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
                "Description."
        ::= { alarmPortStatPFEntry 1 }


    -- 1.3.6.1.4.1.37950.1.1.5.12.9.4.6.1.2
    alarmPortStatEthNoS OBJECT-TYPE
        SYNTAX INTEGER (1..255)
        MAX-ACCESS read-only
        STATUS current
```

```
      DESCRIPTION
            "Description."
      ::= { alarmPortStatPFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.4.6.1.3
alarmPortStatTypeS OBJECT-TYPE
      SYNTAX INTEGER
            {
            downstreamDropEventsAlarm(1),
            upstreamDropEventsAlarm(2),
            downstreamCRCErrorFramesAlarm(3),
            upstreamCRCErrorFramesAlarm(4),
            downstreamUndersizeFramesAlarm(5),
            upstreamUndersizeFramesAlarm(6),
            downstreamOversizeFramesAlarm(7),
            upstreamOversizeFramesAlarm(8),
            downstreamFragmentsAlarm(9),
            upstreamFragmentsAlarm(10),
            downstreamJabbersAlarm(11),
            upstreamJabbersAlarm(12),
            downstreamDiscardsAlarm(13),
            upstreamDiscardsAlarm(14),
            downstreamErrorsAlarm(15),
            upstreamErrorsAlarm(16),
            statusChangeTimesAlarm(17),
            downstreamDropEventsWarning(18),
            upstreamDropEventsWarning(19),
            downstreamCRCErrorFramesWarning(20),
            upstreamCRCErrorFramesWarning(21),
            downstreamUndersizeFramesWarning(22),
            upstreamUndersizeFramesWarning(23),
            downstreamOversizeFramesWarning(24),
            upstreamOversizeFramesWarning(25),
            downstreamFragmentsWarning(26),
            upstreamFragmentsWarning(27),
            downstreamJabbersWarning(28),
            upstreamJabbersWarning(29),
            downstreamDiscardsWarning(30),
            upstreamDiscardsWarning(31),
            downstreamErrorsWarning(32),
            upstreamErrorsWarning(33),
            statusChangeTimesWarning(34)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmPortStatPFEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.4.6.1.4
alarmPortStatEnableS OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-only
```

```
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmPortStatPFEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.4.6.1.5
alarmPortStatTrldS OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmPortStatPFEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.4.7
alarmPotsPFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF AlarmPotsPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmProfileShow 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.4.7.1
alarmPotsPFEntry OBJECT-TYPE
      SYNTAX AlarmPotsPFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { alarmPotsAlarmId, alarmPotsNoS }
      ::= { alarmPotsPFTable 1 }


AlarmPotsPFEntry ::=
      SEQUENCE {
            alarmPotsAlarmId
                  Integer32,
            alarmPotsNoS
                  INTEGER,
            alarmPotsFailEnableS
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.4.7.1.1
alarmPotsAlarmId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmPotsPFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.4.7.1.2
alarmPotsNoS OBJECT-TYPE
```

```
      SYNTAX INTEGER (1..64)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmPotsPFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.4.7.1.3
alarmPotsFailEnableS OBJECT-TYPE
      SYNTAX INTEGER
            {
            disable(0),
            enable(1)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmPotsPFEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.4.8
alarmE1PFTable OBJECT-TYPE
      SYNTAX SEQUENCE OF AlarmE1PFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmProfileShow 8 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.4.8.1
alarmE1PFEntry OBJECT-TYPE
      SYNTAX AlarmE1PFEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { alarmE1AlarmId, alarmE1NoS, alarmE1TypeS }
      ::= { alarmE1PFTable 1 }


AlarmE1PFEntry ::=
      SEQUENCE {
            alarmE1AlarmId
                  Integer32,
            alarmE1NoS
                  INTEGER,
            alarmE1TypeS
                  INTEGER,
            alarmE1EnableS
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.4.8.1.1
alarmE1AlarmId OBJECT-TYPE
      SYNTAX Integer32 (0..65535)
      MAX-ACCESS read-only
```

```
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmE1PFEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.4.8.1.2
alarmE1NoS OBJECT-TYPE
      SYNTAX INTEGER (1..16)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmE1PFEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.4.8.1.3
alarmE1TypeS OBJECT-TYPE
      SYNTAX INTEGER
            {
            e1PortFailure(1),
            e1TimingUnlock(2),
            e1Los(3)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmE1PFEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.4.8.1.4
alarmE1EnableS OBJECT-TYPE
      SYNTAX INTEGER
            {
            enable(1),
            disable(2)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { alarmE1PFEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.5
profileManualBindShow OBJECT IDENTIFIER ::= { onuProfileShow 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.5.1
profileBindTable OBJECT-TYPE
      SYNTAX SEQUENCE OF ProfileBindEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { profileManualBindShow 1 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.9.5.1.1
profileBindEntry OBJECT-TYPE
      SYNTAX ProfileBindEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { profileBindPonS, profileBindOnuS, profileBindTypeS }
      ::= { profileBindTable 1 }


ProfileBindEntry ::=
      SEQUENCE {
            profileBindPonS
                  Integer32,
            profileBindOnuS
                  INTEGER,
            profileBindTypeS
                  INTEGER,
            profileBindIdS
                  INTEGER
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.5.1.1.1
profileBindPonS OBJECT-TYPE
      SYNTAX Integer32 (1..16)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { profileBindEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.5.1.1.2
profileBindOnuS OBJECT-TYPE
      SYNTAX INTEGER (1..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { profileBindEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.5.1.1.3
profileBindTypeS OBJECT-TYPE
      SYNTAX INTEGER
            {
            dba(1),
            srv(2),
            voip(3),
            alarm(4)
            }
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { profileBindEntry 3 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.9.5.1.1.4
profileBindIdS OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { profileBindEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.6
profileAutoBindShow OBJECT IDENTIFIER ::= { onuProfileShow 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.6.1
profileAutoBindTable OBJECT-TYPE
      SYNTAX SEQUENCE OF ProfileAutoBindEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { profileAutoBindShow 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.6.1.1
profileAutoBindEntry OBJECT-TYPE
      SYNTAX ProfileAutoBindEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { profileAutoBindId }
      ::= { profileAutoBindTable 1 }


ProfileAutoBindEntry ::=
      SEQUENCE {
            profileAutoBindId
                  INTEGER,
            profileAutoBindDbaS
                  INTEGER,
            profileAutoBindSrvS
                  INTEGER,
            profileAutoBindVoipS
                  INTEGER,
            profileAutoBindAlarmS
                  INTEGER,
            profileOnuTypeS
                  OCTET STRING
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.6.1.1.1
profileAutoBindId OBJECT-TYPE
      SYNTAX INTEGER
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { profileAutoBindEntry 1 }
```

```
-- 1.3.6.1.4.1.37950.1.1.5.12.9.6.1.1.2
profileAutoBindDbaS OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { profileAutoBindEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.6.1.1.3
profileAutoBindSrvS OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { profileAutoBindEntry 3 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.6.1.1.4
profileAutoBindVoipS OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { profileAutoBindEntry 4 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.6.1.1.5
profileAutoBindAlarmS OBJECT-TYPE
      SYNTAX INTEGER (0..65535)
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { profileAutoBindEntry 5 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.6.1.1.6
profileOnuTypeS OBJECT-TYPE
      SYNTAX OCTET STRING
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
            "Description."
      ::= { profileAutoBindEntry 6 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.7
profileShow OBJECT IDENTIFIER ::= { onuProfileShow 7 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.7.1
profileTable OBJECT-TYPE
      SYNTAX SEQUENCE OF ProfileEntry
```

```
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      ::= { profileShow 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.7.1.1
profileEntry OBJECT-TYPE
      SYNTAX ProfileEntry
      MAX-ACCESS not-accessible
      STATUS current
      DESCRIPTION
            "Description."
      INDEX { profileIdexShow }
      ::= { profileTable 1 }


ProfileEntry ::=
      SEQUENCE {
            profileIdexShow
                  Integer32,
            profileTypeShow
                  INTEGER,
            profileIdShow
                  Integer32,
            profileIdDescr
                  OCTET STRING
       }

-- 1.3.6.1.4.1.37950.1.1.5.12.9.7.1.1.1
profileIdexShow OBJECT-TYPE
      SYNTAX Integer32
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { profileEntry 1 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.7.1.1.2
profileTypeShow OBJECT-TYPE
      SYNTAX INTEGER
            {
            dba(1),
            srv(2),
            voip(3),
            alarm(4)
            }
      MAX-ACCESS read-write
      STATUS current
      DESCRIPTION
            "Description."
      ::= { profileEntry 2 }


-- 1.3.6.1.4.1.37950.1.1.5.12.9.7.1.1.3
profileIdShow OBJECT-TYPE
      SYNTAX Integer32 (1..32767)
```

```
                MAX-ACCESS read-write
                STATUS current
                DESCRIPTION
                      "Description."
                ::= { profileEntry 3 }


          -- 1.3.6.1.4.1.37950.1.1.5.12.9.7.1.1.4
          profileIdDescr OBJECT-TYPE
                SYNTAX OCTET STRING
                MAX-ACCESS read-write
                STATUS current
                DESCRIPTION
                      "Description."
                ::= { profileEntry 4 }



      END

--
-- V1600D.my
--
```