



[www.internet2.edu](http://www.internet2.edu)

# DCN Software Suite v0.4.0 Alpha: OSCARS Inter-Domain Controller (IDC) Installation Guide



# Table of Contents

<a href="#">1 Overview.....</a>	<a href="#">1</a>
<a href="#">1.1 About this Document.....</a>	<a href="#">1</a>
<a href="#">1.2 Hardware and Software Requirements.....</a>	<a href="#">1</a>
<a href="#">1.2.1 System Requirements.....</a>	<a href="#">1</a>
<a href="#">1.2.2 Network Requirements.....</a>	<a href="#">1</a>
<a href="#">1.2.3 Firewall Requirements.....</a>	<a href="#">1</a>
<a href="#">1.2.4 Third-Party Library and Package Requirements.....</a>	<a href="#">1</a>
<a href="#">1.3 Downloading the IDC software .....</a>	<a href="#">2</a>
<a href="#">2 Preparing your Environment.....</a>	<a href="#">3</a>
<a href="#">2.1 MySQL.....</a>	<a href="#">3</a>
<a href="#">2.1.1 Install Option 1: Manual Installation.....</a>	<a href="#">3</a>
<a href="#">2.1.2 Install Option 2: Automatic Installation with a Package Manager.....</a>	<a href="#">3</a>
<a href="#">2.2 Java Development Kit (JDK).....</a>	<a href="#">4</a>
<a href="#">2.2.1 Do I already have the right version of Java?.....</a>	<a href="#">4</a>
<a href="#">2.2.2 Download and Installation.....</a>	<a href="#">4</a>
<a href="#">2.2.3 Setting the JAVA_HOME Environment Variable.....</a>	<a href="#">5</a>
<a href="#">2.2.4 Optional: Adding JAVA_HOME/bin To Your PATH Variable.....</a>	<a href="#">5</a>
<a href="#">2.3 Tomcat.....</a>	<a href="#">5</a>
<a href="#">2.3.1 Download and Installation.....</a>	<a href="#">5</a>
<a href="#">2.3.2 Setting the CATALINA_HOME Environment Variable.....</a>	<a href="#">6</a>
<a href="#">2.3.3 Starting/Stopping the Tomcat Server.....</a>	<a href="#">6</a>
<a href="#">2.3.4 Verifying a Successful Installation.....</a>	<a href="#">6</a>
<a href="#">2.3.5 Configuring SSL.....</a>	<a href="#">7</a>

2.4 Ant.....	7
2.4.1 Download and Installation.....	7
2.4.2 Setting the ANT_HOME Environment Variable.....	7
2.4.3 Adding ANT_HOME/bin to Your PATH Variable.....	7
2.5 Java Transaction API (JTA).....	8
2.6 SMTP Server.....	8
3 Installing the Inter-Domain Controller (IDC) Software.....	8
3.1 Installing the IDC for the First Time.....	8
3.2 Upgrading an Existing IDC from Version 0.3.X.....	11
3.3 Installing the TERCE.....	16
3.4 Creating the First User Account.....	17
3.5 Changing Keystore Passwords.....	18
3.6 Verifying the Web Service API Installation.....	19
3.7 Verifying the Web User Interface (WBUI) Installation.....	19
4 Creating and Managing User Accounts.....	19
4.1 Adding Users to the Database.....	20
4.1.1 Creating New User Accounts.....	20
4.1.2 Modifying Users.....	20
4.1.3 Deleting Users.....	21
4.2 Managing X.509 Certificates from Users and Other IDCs.....	21
4.2.1 Trusted Certificate Authorities.....	21
4.2.2 Associating an X.509 Certificate with a User Account.....	24
5 Describing Your Network Topology.....	25
5.1 Generating an XML Topology Description.....	25
5.1.1 Example XML files.....	25

5.1.2 Domains, Nodes, Ports and Links.....	25
5.1.3 Fully-Qualified Identifiers.....	26
5.1.4 <topology> Element.....	27
5.1.5 <domain> Element.....	27
5.1.6 <node> element.....	27
5.1.7 <port> Element.....	28
5.1.8 <link> Element.....	29
5.1.9 <switchingCapabilityDescriptors> Element.....	30
5.1.10 <switchingCapabilitySpecificInfo> Element.....	30
5.2 Configuring the terce-ws.properties file.....	30
5.3 Populating the Scheduling Database.....	31
5.3.1 Defining Your Local Domain.....	31
5.3.2 Run updateTopology.sh.....	32
5.4 Registering with a Topology Service.....	32
6 Verifying that You Can Build Local Circuits.....	33
7 Inter-Domain Configuration.....	33
7.1 Generating an IDC Certificate for Sending Inter-Domain Requests.....	33
7.1.1 Creating a Certificate and Private Key.....	33
7.1.2 Getting the IDC Certificate Signed.....	35
7.2 Making your IDC Aware of Other Domains.....	37
7.3 Activating Notifications.....	39
7.4 Trusting SSL Certificates of Other IDCs Running HTTPS.....	40
8 Appendix A: oscars.properties.....	41
8.1.1 General.....	41
8.1.2 MySQL Database Properties.....	42

8.1.3 Authentication, Authorization, and Accounting (AAA) Properties.....	42
8.1.4 Topology Exchange and Pathfinding Properties.....	43
8.1.5 Path Setup Properties.....	44
8.1.6 Notifications.....	46
8.1.7 External Services.....	48
8.1.8 Miscellaneous Properties.....	49
9 Appendix B: Using Hostnames Instead of URNs in Requests.....	51
10 Appendix C: Manually Installing Axis2.....	51
10.1.1 Download and Installation.....	51
10.1.2 Setting the AXIS2_HOME Environment Variable.....	52
10.1.3 Verifying a Successful Installation.....	52
10.2 Manually Installing Rampart.....	52
10.2.1 Download and Installation.....	52
10.2.2 Verifying a Successful Installation.....	53
11 Appendix D: Becoming a Certificate Authority (CA).....	53
11.1.1 Generating Your Own CA Certificate.....	53
11.1.2 Signing User ‘Certificate Signing Requests’ (CSRs).....	54
12 Appendix E: Static Path Calculation.....	54
12.1 Creating a Static List of Local Paths.....	54
12.2 Building Your Inter-Domain Routing Table.....	55
12.2.1 Populating the <remoteLinkId> fields in tedb-intra.xml and tedb-inter.xml.....	56
12.2.2 Defining a Default Route.....	56
12.2.3 Defining a Path with Only an Egress.....	57
12.2.4 Defining a Path with Multiple Hops.....	58







# 1 Overview

## 1.1 About this Document

This document is intended to be a guide for installing the OSCARS Inter-Domain Controller (IDC) as part of the DCN Software Suite. It specifically targets those interested in installing an IDC on a network running the DRAGON software (also included in the DCN Software Suite). The document assumes basic familiarity with DRAGON and experience with a Unix-like operating system. It does not assume experience with XML or building Java software but such experience may be useful.

## 1.2 Hardware and Software Requirements

### 1.2.1 System Requirements

The OSCARS IDC software requires a single PC that will act as a web server for processing requests. Most modern PCs should be suitable for running the software. The following specifications are the minimum requirements for most installations:

- 1Ghz Processor (preferably X86 architecture), 1GB memory
- Linux/Unix Operating System
- Basic Internet connectivity
- System clock running the Network Time Protocol (NTP)

Requirements may be greater for systems running the OSCARS IDC concurrently on the same machine as other components of the DCN Software Suite.

### 1.2.2 Network Requirements

A network running the DRAGON control plane software is required for this installation. See the DRAGON documentation for more information. See **Section 1.3** for information on obtaining DRAGON.

### 1.2.3 Firewall Requirements

The IDC runs on port 8080 and port 8443 by default.

### 1.2.4 Third-Party Library and Package Requirements

Installing and running the OSCARS IDC requires the following software packages:

Name	Supported Version	Download Location
MySQL	4.1+	<a href="http://dev.mysql.com/downloads/mysql/">http://dev.mysql.com/downloads/mysql/</a>
Java Development Kit (JDK)	5.0	<a href="http://java.sun.com/javase/downloads/index_jdk5.jsp">http://java.sun.com/javase/downloads/index_jdk5.jsp</a>
Tomcat	5.5	<a href="http://tomcat.apache.org/download-55.cgi">http://tomcat.apache.org/download-55.cgi</a>
Axis2	1.3	<a href="http://ws.apache.org/axis2/download/1_3/download.cgi">http://ws.apache.org/axis2/download/1_3/download.cgi</a>
Rampart	1.3	<a href="http://www.apache.org/dyn/mirrors/mirrors.cgi/ws/rampart/1_3/rampart-1.3.zip">http://www.apache.org/dyn/mirrors/mirrors.cgi/ws/rampart/1_3/rampart-1.3.zip</a>
Ant	1.7	<a href="http://ant.apache.org/bindownload.cgi">http://ant.apache.org/bindownload.cgi</a>
Java Transaction API (JTA) <sup>1</sup>	1.0.1b	<a href="http://sourceforge.net/project/showfiles.php?group_id=40712&amp;package_id=127784&amp;release_id=529023">http://sourceforge.net/project/showfiles.php?group_id=40712&amp;package_id=127784&amp;release_id=529023</a>

### 1.3 Downloading the IDC software

The IDC software is part of the DCN Software Suite. It can be downloaded at:

- <https://wiki.internet2.edu/confluence/display/DCNSS>

After downloading the DCN software suite, you may unpack it with the following commands:

```
% gunzip dcn-software-suite-0.4.tar.gz
% tar -xvf dcn-software-suite-0.4.tar
```

This will create a directory called `dcn-software-suite-0.4`. The IDC software, called OSCARS, is located in the subdirectory `dcn-software-suite-0.4/idc`. The TERCE software is located in `dcn-software-suite-0.4/terce`. This document describes the installation of both the IDC and TERCE. The DRAGON software is located in the subdirectory `dcn-software-suite-0.4/dragon`. DRAGON software installation instructions are located in `dcn-software-suite-0.4/dragon/docs/DRAGON-INSTALL-0.3.pdf`. The remainder of this document will focus on the IDC installation.

---

<sup>1</sup> The link given is to a library called Hibernate that contains JTA. This is currently the easiest way to obtain the library.

## 2 Preparing your Environment

This section details how to install and configure prerequisite software on the machine that will be running the IDC. The following prerequisite steps are detailed:

1. Install MySQL
2. Install the Java Development Kit and set the JAVA\_HOME environment variable
3. Install the Tomcat web server and set the CATALINA\_HOME environment variable
4. Install Ant and add it to your PATH environment variable
5. Install the Java Transaction API (JTA)

In addition the Axis2 and Rampart libraries from Apache must be installed. This will be done automatically by the OSCARS installation script as described in Section 3. If you would like to perform this installation manually please see section .

### 2.1 MySQL

MySQL is the database used to maintain user accounts and track reservations. You may install MySQL in one of two ways: manually, by installing a package downloaded from the MySQL web site OR automatically, using your operating system's package manager:

#### 2.1.1 Install Option 1: Manual Installation

Download the MySQL package from the MySQL web site at:

- <http://dev.mysql.com/downloads/mysql>

Installing MySQL in this manner is beyond the scope of this document but (English) installation instructions may be found at:

- <http://dev.mysql.com/doc>

#### 2.1.2 Install Option 2: Automatic Installation with a Package Manager

Download and install MySQL through a package manager if your operating system runs such a service. A few common package managers are up2date (RedHat), apt-get (Debian), and yum. You may install MySQL using a command such as:

```
% up2date mysql-server
```

Consult specific package managers for the exact command and package name.

## 2.2 Java Development Kit (JDK)

Java is the programming language in which the OSCARS IDC software was created and provides the environment in which it runs. In addition to running the software, the JDK also contains utilities required for compiling the source code and generating user certificates. This section details installation and configuration related to this package.

### 2.2.1 Do I already have the right version of Java?

Many systems come pre-installed with Java. To install the IDC, your system must not only have Java Runtime Environment (JRE) version 5 but also the various compilers and utilities. To verify that you have the necessary Java environment, issue the following command:

```
% javac -version
```

If the first line of output reads `javac 1.5.0_X`, you should not need to install the Java Development Kit and may skip to section **2.2.3 Setting the JAVA\_HOME Environment Variable**. If you get “command not found” or the version number is less than 1.5, you may need to install JDK 5.0 and should proceed to **2.2.2 Download and Installation**.

**NOTE: If you are not running the SUN distribution of Java you may encounter issues. The GNU and IBM versions of Java are not fully tested and some users have reported problems. It is recommended you run the SUN distribution of Java.**

### 2.2.2 Download and Installation

You may download JDK 5.0 from Sun’s web site at:

- [http://java.sun.com/javase/downloads/index\\_jdk5.jsp](http://java.sun.com/javase/downloads/index_jdk5.jsp)

It is recommended that you download the latest update of **JDK Version 5**. Choose the package most suitable for your operating system.

Once downloaded, unpack the file; this should create a new folder named something similar to “jdk1.5.0\_X”. The final step of installation is to move this folder to an easily accessible place. We recommend renaming the folder to java5 in /usr/local with the following command:

```
% sudo mv jdk1.5.0_X /usr/local/java5
```

The location may be anywhere you choose – just make sure you note the location as it is required for setting the JAVA\_HOME environment variable in the next section.

### 2.2.3 Setting the JAVA\_HOME Environment Variable

Once Java is installed, you need to set the JAVA\_HOME environment variable with its location. This variable is required by the Tomcat web server (see section **2.3 Tomcat**) to run. To set this environment variable, issue these commands:

```
% JAVA_HOME=/usr/local/java5
% export JAVA_HOME
```

You may permanently set this variable (recommended) by adding the above commands to the profile file in your home directory (i.e. .bash\_profile or .profile).

### 2.2.4 Optional: Adding JAVA\_HOME/bin To Your PATH Variable

This step is optional but may make issuing commands easier in later steps. You should add the folder JAVA\_HOME/bin to your PATH environment variable so that you can easily access the `keytool` command for issuing certificates. To update your PATH variable, issue these commands:

```
% PATH=$PATH:$JAVA_HOME/bin
% export PATH
```

You may permanently set this variable (recommended) by adding the above commands to the profile file in your home directory (i.e. .bash\_profile or .profile).

## 2.3 Tomcat

Tomcat is a Java-based application container in which the OSCARS IDC software runs. This section details installation and basic configuration of Tomcat.

### 2.3.1 Download and Installation

You may download Tomcat from the project's web site at:

- <http://tomcat.apache.org/download-55.cgi>

It is recommended you download **Tomcat Version 5.5**.

**NOTE: Tomcat 6.0 is NOT currently supported by the software.**

Once downloaded, unpack the downloaded file; this should create a new folder named something similar to “apache-tomcat-5.5.X”. The final step of installation is to move this folder to an easily accessible place. We recommend renaming the folder to tomcat in /usr/local with the following command:

```
% sudo mv apache-tomcat-5.5.X /usr/local/tomcat
```

The location may be anywhere you choose – just make sure you note the location as it is required for setting the CATALINA\_HOME environment variable in the next section.

**NOTE: It is NOT RECOMMENDED that you download Tomcat with a package manager such as up2date, yum, or apt-get. Many users have reported difficulty with this method. If you install Tomcat using this method be aware that some of the environment variables and other settings may vary from what is contained within this document.**

### 2.3.2 Setting the CATALINA\_HOME Environment Variable

Once Tomcat is installed, you need to set the CATALINA\_HOME environment variable with its location. This variable is required by the Tomcat web server to run. To set this environment variable, issue these commands:

```
% CATALINA_HOME=/usr/local/tomcat
% export CATALINA_HOME
```

You may permanently set this variable (recommended) by adding the above commands to the profile file in your home directory (i.e. .bash\_profile or .profile).

### 2.3.3 Starting/Stopping the Tomcat Server

You may start Tomcat with the following command:

```
% $CATALINA_HOME/bin/startup.sh
```

You shutdown the Tomcat server with the following command:

```
% $CATALINA_HOME/bin/shutdown.sh
```

### 2.3.4 Verifying a Successful Installation

To verify installation was successful, startup the Tomcat server with the following command:

```
% $CATALINA_HOME/bin/startup.sh
```

After starting the server, point a web browser to port 8080 of the machine on which you installed Tomcat with the following URL:

- <http://your-machine-name:8080>

If installation was successful, a web page will load with the Tomcat logo and a message that reads “If you're seeing this page via a web browser, it means you've setup Tomcat successfully. Congratulations!”

### 2.3.5 Configuring SSL

You may configure Tomcat to use SSL so that all requests and responses to the server are encrypted. This is not required but highly recommended. Information on this process can be found at:

- <http://tomcat.apache.org/tomcat-5.5-doc/ssl-howto.html>

## 2.4 Ant

Ant is a tool that is used to build the IDC code and deploy various configuration files (think of it as “make” for Java). This section details how to install and configure Ant.

### 2.4.1 Download and Installation

Download Ant from the project’s web site at:

- <http://ant.apache.org/bindownload.cgi>

Most IDC testing has been done with **Version 1.7**. Unpack and install Ant with the following commands:

```
% unzip apache-ant-1.7.0-bin.zip
% sudo mv apache-ant-1.7.0 /usr/local/ant
```

You are not required to install the downloaded folder in /usr/local/ant but you should note where it is installed as this information is needed in later steps.

### 2.4.2 Setting the ANT\_HOME Environment Variable

Once Ant is installed, you need to set the ANT\_HOME environment variable with Ant’s location. To set this environment variable, issue these commands:

```
% ANT_HOME=/usr/local/ant
% export ANT_HOME
```

You may permanently set this variable (recommended) by adding the above commands to the profile file in your home directory (i.e. .bash\_profile or .profile).

### 2.4.3 Adding ANT\_HOME/bin to Your PATH Variable

It is recommended you add the Ant bin directory to your PATH environment variable. This will allow ant command-line tools to be found when you type-in the command name. To set this environment variable, issue these commands:

```
% PATH=$PATH:$ANT_HOME/bin
% export PATH
```

You may permanently set this variable (recommended) by adding the above commands to the profile file in your home directory (i.e. `.bash_profile` or `.profile`).

## 2.5 Java Transaction API (JTA)

The Java Transaction API (JTA) is a library used for managing database connections in the IDC. It is a single JAR file but its license restricts distribution with the DCN Software Suite. The easiest way to obtain this library is to download another package called Hibernate and extract the appropriate JAR. The steps for obtaining and installing JTA are:

1. Download and unpack the DCN Software Suite (see section **1.3 Downloading the IDC software**)
2. Download the Hibernate-Core library at:
  - [http://sourceforge.net/project/showfiles.php?group\\_id=40712&package\\_id=127784&release\\_id=529023](http://sourceforge.net/project/showfiles.php?group_id=40712&package_id=127784&release_id=529023)

3. Unpack the downloaded files with the following command:

```
% unzip hibernate-3.2.5.ga.zip
```

4. Copy the `jta.jar` file to the lib directory of downloaded IDC software. The command to do this is:

```
% cp hibernate-3.2/lib/jta.jar dcn-software-suite-0.4/idc/lib
```

## 2.6 SMTP Server

You may **optionally** install an SMTP server on the same machine as the IDC and it will send email notification of circuit activity. A standard installation of `sendmail` should be suitable for the IDC's purposes. The IDC sends mail by transmitting SMTP packets to localhost so it is not dependent on the underlying software. Installing such software is beyond the scope of this document.

## 3 Installing the Inter-Domain Controller (IDC) Software

This section details how to install the OSCARS IDC Software. It assumes you have installed all the prerequisites as described in the previous section, Preparing your Environment. This section will cover installing an IDC for the first time, upgrading from a previous version of the IDC, and installing the TERCE component.

### 3.1 Installing the IDC for the First Time

This section describes how to install OSCARS on a machine that does not have another version of the software already running. **If you have a previous version of the OSCARS IDC installed**



**that you wish to upgrade, please proceed to the next section of this document.** The steps in this section will install both the OSCARS web page interface for human users and the web service interface for applications. To install OSCARS for the first time run the `do_build.sh` script followed by `do_install.sh`. These two scripts will compile the code, build the necessary MySQL database tables, and copy configuration files to the appropriate locations. Below is a detailed description of their use.

First run `do_build.sh` and you should see the following:

```
$ ./do_build.sh

--- Checking prerequisites...
    We seem to be in the correct directory
    Found ant
    Environment variable CATALINA_HOME is set to
    /usr/local/tomcat
    Environment variable DOMAIN_HOME is not set. Continuing
    without it.
    Found jta.jar under lib
    Axis2 library not found.
    Rampart library not found.
```

If you do not see the above output verify that you have installed all the prerequisites described in **2 Preparing your Environment**. You should answer ‘y’ to the next two questions and proceed as shown below:

```
- Axis2 installation not detected. Should I build it for you
y/n? y
    OK, will build Axis2 for you.

- Axis2 is not deployed. Should I do this for you y/n? y
    OK, will deploy Axis2 for you.
--- Downloading Axis2...
```

You should then see output of Axis2 and the module Rampart downloading. The script will then restart your Tomcat server. The output for the Axis2/Rampart download and the Tomcat restart is not shown in this document as it is rather lengthy. You should know that if your Tomcat server is not running you may see a harmless “Connection refused” exception. This only displays because the script first tries to shutdown the Tomcat server, which it can only do if Tomcat is running. This exception should not affect your installation so please ignore it if it appears. After restarting Tomcat you should see the following:

```
--- Your kit looks good.
- Input the hostname for this IDC. Leave blank for "your-
server.com":
```

If the host name displayed is not correct for your machine then enter the correct one, otherwise you may just hit the return key. You will then be asked if you would like to setup your MySQL

database. You should answer 'y' to the questions and provide information for an account capable of creating and granting privileges on databases as shown below:

- Install databases y/n? **y**  
     OK, will install databases.  
     Found mysql client at /usr/bin/mysql
- Input the MySQL server hostname. Leave blank for localhost:  
     Using localhost .
- Input a privileged MySQL username on that host. Leave blank for root:  
     Using root .
- Input the password for the privileged account:  
     Privileged account access verified.

The next of questions will ask for information on the MySQL user that will be used by the IDC to connect to the database. Please remember the information you specify for later as it will be important when configuring your IDC. Example output is shown below:

- Input a MySQL username the IDC will use to connect to the databases.  
     -- This name and password must match the  
     hibernate.connection.username and password specified in  
     oscars.properties.  
     Leave blank for "oscars":  
     Using oscar .
- Input the password for the IDC account:  
     IDC account access verified.
- Got all information. Press return to create the databases...  
     Creating databases bss, aaa, notify, testbss, testaaa  
     Databases created...  
     Initializing databases...  
     Databases initialized...  
     Granting privileges to IDC account...  
     IDC account authorized.  
     Modifying conf/server/aaa.cfg.xml ...  
     Modifying conf/server/bss.cfg.xml ...

You are now ready to build your IDC as indicated by the following output:

- Press return to build IDC...

As the last line indicates pressing return will build (compile) the IDC. You will know the build was successful when you see the following output:

```
BUILD SUCCESSFUL
Total time: 30 seconds
--- IDC built.
```

At this point you have successfully built the IDC. The next step is to deploy the software on your system with `do_install.sh`. The script will start by stopping your Tomcat server and prompting you to tell it if it should copy the OSCARS configuration files to their proper locations:

```
% ./do_install.sh
--- Checking prerequisites...
    We seem to be in the correct directory
    CATALINA_HOME is set to /usr/local/tomcat

--- Stopping Tomcat...
Using CATALINA_BASE:  /usr/local/tomcat
Using CATALINA_HOME:  /usr/local/tomcat
Using CATALINA_TMPDIR: /usr/local/tomcat/temp
Using JRE_HOME:       /usr/local/java5

Do you wish to copy key files and oscars configuration files
to Tomcat now? [y/n] y
```

You should answer ‘y’ and what follows is a long stream of output that moves the OSCARS software and configuration files to their correct locations. You will know installation was successful when you see the following:

```
IDC deployed, server configured
```

A final prompt will appear asking if you would like to build the IDC tools. You should answer ‘y’ to this prompt. It will compile a number of utilities important for configuring and running your IDC. This includes commands for managing certificates and the database. Below is a snippet of the output you will see:

```
Should I build the OSCARS tools for you y/n?y
...
--- Tools built.
```

You are now ready to install the TERCE component and begin configuring the OSCARS software. Proceed to **3.3 Installing the TERCE** to continue installation.

## 3.2 Upgrading an Existing IDC from Version 0.3.X

Upgrading an existing IDC that is running version 0.3.0 or 0.3.1 of the DCN Software Suite requires you to run the `do_upgrade.sh` script followed by the `do_install.sh` script. There are also a few additional steps required for inter-domain reservations to work properly with the new version of the software that are detailed in this section. **If you are running a version of the software prior to 0.3 it is recommended that you first upgrade to version 0.3 or 0.3.1 before trying these steps.**

The first step is to run the `do_upgrade.sh` script. The commands to do this and subsequent output are as follows (NOTE: The output you see may vary depending on your installation as it checks if any steps have already been completed. This will be especially true if you run this script multiple times):

```
% cd dcn-software-suite-0.4/idc
% ./do_upgrade.sh

--- Checking prerequisites...
    We seem to be in the correct directory
    CATALINA_HOME is set to /usr/local/tomcat

Would you like to upgrade your bss MySQL tables y/n? y
Please enter your mysql user name: oscars
--- mysql tables upgraded
Would you like to upgrade your aaa database y/n? y
Please enter your mysql user name: oscars
--- mysql tables upgraded
```

The first set of prompts upgrade the structure of the aaa database with user information and the bss database with scheduling/topology information. If this is your first time running this script you MUST answer 'y' to both of the above prompts.

```
Would you like to create the notify database y/n? y
NOTE: This action requires you to specify a privileged
MySQL user account such as 'root'
Please input a privileged mysql user (i.e. root): root
Please input password for privileged mysql user:
"Please enter the mysql user name OSCARS uses (i.e.
oscars): oscars
Please enter the password for the mysql user name OSCARS
uses:
--- mysql tables upgraded
```

The next set of prompts creates a new database called 'notify' that is used to track where notifications of IDC activity should be sent. It requires the login and password of a privileged MySQL user so that a new table can be created and access to that new table can be created to the database user used by OSCARS (as indicated by the `hibernate.connection.username` property in `oscars.properties`).

```
Would you like to update your topology description to
match the latest schema version y/n? y
```

This version of OSCARS uses a newer version of the NMWG control plane topology schema than previous versions of the software. Answering 'y' to this prompt will bring current topology

descriptions (such as those in your tedb-intra.xml and tedb-inter.xml files) up-to-date automatically.

```
- Updating oscars.properties...
Enter your IDC's URL: https://your-
idc.net:8443/axis2/services/OSCARS
-- Adding default topology service URL
-- Adding IDC PEP to notification broker
```

The above prompt adds the idc.url and the notify.broker.ws.url properties to oscars.properties.

```
Would you like to use the new perfsonar pathfinder? [y/n]
y
```

The above configures OSCARS to use the new “perfsonar” pathfinder which automatically queries other domain's topology from an external topology service and calculates a path. It is recommended you answer 'y' at this step. Answering 'y' also requires the name answer when prompted later if you'd like to register with the topology service.

```
Would you like to activate WS-Notifications? [y/n] y
```

The above is required to do interdomain provisioning. It tells the IDC to send notification messages.

```
Would you like to subscribe to other IDCs notifications?
[y/n] y
```

The above is required to do interdomain provisioning. It tells the IDC to subscribe to other IDC's notification messages.

```
Would you like to register the local topology with the
topology service? [y/n] y
```

The above is required to if you are suing the perfsonar pathfinder. It tells the IDC to register the local topology with an external topology service. The default topology service provided by Internet2 is used if you answer 'y'. You can change this by altering the perfsonar.topology\_url property in oscars.properties.

```
May this script copy jdom.jar to
$CATALINA_HOME/webapps/axis2/WEB-INF/lib/? [y/n] y
```

The above is required to run the topology registration. It resolves a library dependency that doesn't exist otherwise.

```
--- Upgrade changes complete
```

```
#####
#####
```

## UPGRADE NOTES

You may now run `./do_install.sh` to complete your upgrade.

You also need to complete the following steps:

1. Create a user account for the local domain as described in section '7.3 Activation Notifications' of the DCNSS install document

2. Add the URL of each neighboring domain's NotificationBroker by running `tools/utls/idc-serviceadd` as described at the end of section '7.2 Making your IDC Aware of Other Domains' of the DCNSS install document

3. Associate each neighboring domain with an Institution by running `tools/utls/idc-siteadd`

```
#####
#####
```

When the script is complete the above prompt displays. As it indicates you may now run `do_install.sh` to complete the installation. The additional steps it indicates are also described in this section. Running `do_install.sh` looks like the following:

```
% ./do_install.sh

--- Checking prerequisites...
    We seem to be in the correct directory
    CATALINA_HOME is set to /usr/local/tomcat

--- Stopping Tomcat...
Using CATALINA_BASE:  /usr/local/tomcat
Using CATALINA_HOME:  /usr/local/tomcat
Using CATALINA_TMPDIR: /usr/local/tomcat/temp
Using JRE_HOME:       /usr/local/java5

Do you wish to copy key files and oscars configuration
files to Tomcat now? [y/n]
n
--- Deploying IDC...
...
...
BUILD SUCCESSFUL
Total time: 39 seconds
```

```

--- Restarting Tomcat...
Using CATALINA_BASE:   /usr/local/tomcat
Using CATALINA_HOME:   /usr/local/tomcat
Using CATALINA_TMPDIR: /usr/local/tomcat/temp
Using JRE_HOME:        /usr/local/java5

```

IDC deployed

The above means that the new IDC software is deployed. Finally an optional prompt will be displayed as shown below:

```

Should I build the OSCARS tools for you y/n?y

--- Building tools...
Buildfile: build.xml

prepare:

compile:

idcutil:

all:

BUILD SUCCESSFUL
Total time: 3 seconds

--- Tools built.

```

It is highly recommended you answer 'y' as these are very useful for managing the IDC. After this prompt the script is complete.

There are a few final steps you must complete before finishing the upgrade. First, you must create a user account for the local IDC if you have not already done so. The steps for this (including a screenshot of the WBUI “Add User” form with required fields populated) is described in section **7.3 Activating Notifications**.

You must also add the URL of each of your neighboring IDC's “NotificationBrokers” to the OSCARS database. The NotificationBroker is a new service that comes installed with OSCARS by default and runs at the same URL as OSCARS expects it ends with OSCARSNotify. An example of the commands required to add a NotificationBroker URL for a domain are as follows:

```
% cd dcn-software-suite-0.4/idc/tools/utils
% ./idc-serviceadd

1. blue.pod.lan
2. red.pod.lan
Select the service's domain (by number): 2
Choose service type:
    1. NotificationBroker
    2. Other...
Enter Choice*: 1
Service URL*: https://their-
machine:8443/axis2/services/OSCARSNotify
New 'NB' service at 'https://their-
machine:8443/axis2/services/OSCARS' added.
```

Finally, you will need to associate each domain with an organization so that neighboring IDCs can be properly authorized to see notifications about events that their network. You can do this using the `idc-siteadd` command as follows:

```
% cd dcn-software-suite-0.4/idc/tools/utils
% ./idc-siteadd
1. blue.pod.lan
2. red.pod.lan
Select the service's domain (by number): 2

1. Energy Sciences Network
2. Internet2
3. MY ORGANIZATION
4. New...
Select the organization associated with this domain (by
number): 4
Organization Name*: Red Organization
New site created that associates domain 'red.pod.lan'
with organization 'Red Organization'
```

After completing the above your software should be completely upgraded and ready to use.

### 3.3 Installing the TERCE

The TERCE stores XML topology and the static list of local routes used by the IDC. Currently these components are kept in manually generated XML files, but in the future they will be automatically generated. You must install the TERCE to run OSCARS. The TERCE is included in the DCN Software Suite and can only be installed after Axis2 is installed (i.e. after you run `do_build.sh`). The installation can be done by running the following commands:

```
% cd dcn-software-suite-0.4/terce
% ./do_install.sh
```



Configuring the TERCE is detailed in section **5 Describing Your Network Topology**. If this is your first time installing the software then continue to section **3.4 Creating the First User Account**.

### 3.4 Creating the First User Account

You need to create a user account so you can login to the OSCARS web page, called the web user interface (WBUI), and verify your installation. You must create the first account with a provided command-line script but additional users can also be created from the WBUI. The tools to create a user can be found in the `tool/utils` directory. You must first change to this directory with the following command:

```
% cd dcn-software-suite-0.4/idc/tools/utils
```

Before creating the user account, you must first add your local organization to the OSCARS database. To do this, run the following commands:

```
% ./idc-orgadd
Organization Name*: MY ORGANIZATION
New organization 'MY ORGANIZATION' added.
```

The commands to create the first user are as follows:

```
% ./idc-useradd
* indicates a required field
Login*: oscars-admin
Password*:
Confirm Password*:
First Name*: John
Last Name*: Smith
Cert Subject:
Cert Issuer:

1. Energy Sciences Network
2. Internet2
3. MY ORGANIZATION
Select the user's organization (by number): 3

1. OSCARS-user
2. OSCARS-engineer
3. OSCARS-administrator
4. OSCARS-service
5. OSCARS-operator
6. OSCARS-site-administrator
7. OSCARS-publisher
8. OSCARS-may-specify-path
Select the user's role(s) (numbers separated by spaces): 2 3
Personal Description:
Email(Primary)*: myemail@mydomain.net
Email(Secondary):
Phone(Primary)*: 5555555555
Phone(Secondary):
```

The fields with a \* are required. It is recommended at this time you just fill-in the minimum requirements. You can always modify this information later when you log-in to the WBUI. It's important to note that the user you create should have at least **OSCARS-administrator** privileges so it can create new users. You may also want to give it **OSCARS-engineer** privileges so you can view and manage all circuits. After creating this user you are almost ready to test your installation. The final step before testing your installation is to change your keystore passwords as described in the next section (*NOTE: At this point you have enough configuration done to complete the steps in sections 3.6 and 3.7 but you will run into conflicts later if you do not complete 3.5*).

### 3.5 Changing Keystore Passwords

Keystores are special files that act as a database of X.509 certificate and private keys for your IDC. It is important to keep the information in these keystores protected so you **MUST** change the default passwords. There `idc-kspasswd` command can be used to change the passwords. There are two keystores you must modify, `sec-client.jks` and `sec-server.jks`, so you will need to run the command twice. These keystores are described in more detail in sections 7.1 and 4.2.1 respectively. You may run the command to change `sec-client.jks` as follows (*NOTE: the default "old" password for keystore is password*):

```
% cd dcn-software-suite-0.4/idc/tools/utils
% ./idc-kspasswd
Choose the keystore with the password you'd like to change:
    1. sec-client.jks - stores the private key and certificate
    used to send messages to other IDCs
    2. sec-server.jks - stores certificates trusted to sign
    incoming messages
Enter choice: 1
Enter the old keystore password:
Enter the new keystore password:
Re-enter the new keystore password:
-- Password changed
```

You need to run the command again and change the password for `sec-server.jks` (*Note: the default "old" password is password*):

```
% ./idc-kspasswd
Choose the keystore with the password you'd like to change:
    1. sec-client.jks - stores the private key and certificate
    used to send messages to other IDCs
    2. sec-server.jks - stores certificates trusted to sign
    incoming messages
Enter choice: 2
Enter the old keystore password:
Enter the new keystore password:
Re-enter the new keystore password:
-- Password changed
```

After changing the keystore passwords you are ready to test your installation. If this is your first time installing the software then continue to section **3.6 Verifying the Web Service API Installation**.

### 3.6 Verifying the Web Service API Installation

You may verify that the web service API deployed correctly through the Axis2 administrator interface by doing the following:

1. Open <http://your-machine:8080/axis2/axis2-admin/> in your browser
2. Log- in to the page that loads (default user: **admin**, default password: **axis2**)
3. Click “Available Services” on the left-hand side of the screen

You should see an entry for “OSCARS” and “OSCARSNotify” on the page that loads, followed by a list of web service calls. This indicates that installation was successful. If you do not see it, try re-installing the IDC.

### 3.7 Verifying the Web User Interface (WBUI) Installation

The Web User Interface (WBUI) is a set of web pages provided with OSCARS for managing reservations and users. To verify that the WBUI installed correctly visit the following URL:

- <http://your-machine:8080/OSCARS>

A login page should appear. You can login using the account you created in section **3.4 Creating the First User Account**. Once logged-in a blank page should load (reservations will be listed on this page once you begin actively using OSCARS). At this time you cannot create circuits until you do more configurations but you can manage users (see section **4 Creating and Managing User Accounts** for more information).

**NOTE: Web User Interface DOES NOT work with INTERNET EXPLORER. Mozilla-based browsers such as Firefox or Safari are the most thoroughly tested.**

## 4 Creating and Managing User Accounts

The OSCARS IDC has a built-in system for authenticating and authorizing requests. User information is kept in the MySQL *aaa* database. The WBUI associates a username and password with accounts kept in this database. In contrast, web service requests are authenticated using X.509 certificates that are associated with the accounts in the database. Creating user accounts can be done via the WBUI as described in section **4.1**. When you are ready to begin accepting requests from other IDCs or applications using the web service API read section **4.2** on what is required to accept X.509 certificates.

## 4.1 Adding Users to the Database

Users and permissions are stored in a MySQL database. This section details how to add users to the database and assign them permissions.

### 4.1.1 Creating New User Accounts

You can create new users from the OSCARS web page called the web user interface (WBUI). The five steps for creating a new user via this method are:

1. Visit <http://your-server:8080/OSCARS> – where *your-server* is the name of the server on which the WBUI is running
2. Login with a user account that has administrator privileges (such as the one you created in **3.4 Creating the First User Account**)
3. Click the **Users** tab on the top of the page that loads
4. Click the **Add User** button
5. Complete all the fields outlined in green. Most of the fields are self-explanatory but a few are worth mentioning:
  - *X.509 Subject Name* – Use this field to associate an X.509 certificate with a particular user. This field is not required to allow the user to provision via the WBUI. It is required if the entity associated with this account will send requests using the web service API (such as another IDC). See section **4.2.2 Associating an X.509 Certificate with a User Account** for more information on how to use this field.
  - *X.509 issuer name* – Generally the X.509 Subject Name is enough but you may also use this field to indicate the issuer of the certificate. In most cases you do not need to use this field.
  - *Choose Role(s)* – These determine what permissions users have. More complicated permissions are beyond the scope of this document.
6. Click the **Add** button on the top of the screen

### 4.1.2 Modifying Users

You may modify user accounts via the WBUI under the **Users** tab. Clicking on the users last name will display a form for editing the user's profile. The form should be self-explanatory as it is similar to the add users form.

### 4.1.3 Deleting Users

You may delete user accounts via the WBUI under the **Users** tab. Clicking on DELETE will remove the user after a confirmation.

## 4.2 Managing X.509 Certificates from Users and Other IDCs

X.509 certificates are passed in web service messages to your IDC as a means to authenticate users and other IDCs sending requests. **You do not need to create any X.509 certificates to setup circuits on the local domain via the WBUI. You may skip this section until you are ready to begin accepting requests from applications using the web service API or accepting requests from other IDCs.** Each certificate you accept needs to be signed by a certificate authority (CA) that your server trusts. The X.509 subject of the certificate must also be associated with a user account on your IDC. This section describes the information you need from users or other IDCs to **accept** requests. Instructions for generating a certificate your IDC inserts in messages it sends to other IDCs is described in section 7 **Inter-Domain Configuration**.

### 4.2.1 Trusted Certificate Authorities

X.509 certificates included in requests to your IDC must be issued by a certificate authority (CA) that your IDC trusts. This is important for the IDC to verify a particular request is from who the sender actually claims to be. The CAs trusted is determined by which CA certificates are stored in the \$CATALINA\_HOME/shared/classes/server/sec-server.jks keystore. A keystore is a file that acts as a database for storing certificates and their associated keys. By default a number of CA certificates are already installed in OSCARS (including those for Internet2's test CA and ESnet). You may view the certificates already installed by running the provided `idc-certview` script as follows:

```
% cd dcn-software-suite-0.4/idc/tools/utils
% ./idc-certview
Choose the keystore with the certificate you'd like to view:
    1. sec-client.jks - stores the private key and certificate
    used to send messages to other IDCs
    2. sec-server.jks - stores certificates trusted to sign
    incoming messages
    3. ssl-keystore.jks - stores SSL certificates of other
    IDCs running HTTPS
    4. Open certificate file...
Enter choice: 2
```

As previously mentioned, the keystore named `sec-server.jks` maintains the CA certificates trusted to sign incoming messages. For this reason you should choose option 2 when you wish to look at the certificates already installed for this purpose. Options 1 and 3 are described in sections 7.1

and 7.4 respectively. Option 4 is described in section 4.2.2. After choosing option 2 then output similar to the following displays:

```
Choose the certificate you wish to view:
  1. oasistestca
  2. oasistestrootca
  3. esnetroot
  4. doe gridsca
  5. geant
  6. dcsca
  7. nortel
Enter choice: 6
```

This set of output is the list of certificates currently installed in your keystore. Your output may look slightly different depending on what you have installed. If you wish to view the details of one of the certificates then enter the number next to it and hit ‘return’. Output such as the following will display:

```
-- Certificate details

Alias name: dcsca
Creation date: Mar 29, 2007
Entry type: trustedCertEntry

Owner: CN=DCSTest, OU=DCS Test, O=DCS Test, L=Ann Arbor,
ST=Michigan, C=US
Issuer: CN=DCSTest, OU=DCS Test, O=DCS Test, L=Ann Arbor,
ST=Michigan, C=US
Serial number: 0
Valid from: Thu Mar 29 11:14:29 EDT 2007 until: Sun Mar 26
11:14:29 EDT 2017
Certificate fingerprints:
    MD5:  92:21:D8:26:10:73:0A:CE:36:56:7D:F8:6C:65:9E:C6
    SHA1:
05:25:DF:20:69:78:EC:89:40:12:E7:70:01:B3:FB:D7:9E:44:9C:FF
```

If you wish to accept a request that is signed by a CA other than those currently in the keystore then you can import a new CA certificate using the provided `idc-certadd` script. **You do not need to worry about this if you only plan to accept requests from certificates signed by one of the default CAs and may progress to the next section.** Assuming you do want to add a new CA, the CA must first send you their certificate (via email, download it from a web site, etc) and you must then save it in a file. Assuming you saved it in a file called “ca.cer” you may use the following commands to import it:

```
% cd dcn-software-suite-0.4/idc/tools/utils
% ./idc-certadd What would you like to do?
  1. Create a new certificate my IDC will use in outgoing
messages to other IDCs
```

```

    2. Import a certificate created using choice 1 that was
    signed by a CA
    3. Trust a CA or another IDC's certificate
Enter choice: 3

```

When you run `idc-certadd` it will prompt you for the operation to perform. Since you would like trust an incoming certificate you should choose option 3. If you're interested, options 1 and 2 are described in section **7.1 Generating an IDC Certificate for Sending Inter-Domain Requests**. After choosing option 3 the following prompts are displayed:

```

-- You have chosen to import a trusted certificate.

Enter certificate filename: ca.cer
Enter certificate alias (This value is used to reference the
certificate in some configuration files. It may be any valid
string.): caname

```

The first prompt asks for the filename of the certificate to be imported. The second prompt asks for a certificate "alias". The alias is only used as a reference to the certificate entry in the keystore so it may be any value that helps you remember the CA to which the certificate belongs. You will see the alias again in commands such as `idc-certview` so make sure it is something that will help you remember the certificate. After specifying these values you will see the following output:

```

OSCARS will trust this certificate when it's used to sign...
...an incoming request y/n? y
...the SSL certificate of another IDC's web server y/n? n

```

Answer 'y' to the first question so that you will trust incoming requests with the certificate or another certificate signed by it. For the second question asked by the script about trusting "the SSL certificate of another IDC's web server" you may want to answer 'y' if you plan to connect to another IDC running HTTPS with an SSL certificate signed by the CA. More information on this is provided in section **7.4 Trusting SSL Certificates of Other IDCs Running HTTPS**. If you are not sure at this time, then you may answer 'n' and add the certificate later by running the script again if needed. These prompts lead to the final set of output:

```

-- Using keystore password from
/Library/Tomcat/shared/classes/server/sec-server.properties
...CERTIFICATE OUTPUT HERE...

-- Certificate imported into
/Library/Tomcat/shared/classes/server/sec-server.jks. Messages
containing this certificate or another certificate issued by
the CA it represents will now be trusted.

-- Complete

```

The output above indicates you have successfully installed the certificate. You should now trust messages signed with this certificates signed by the new CA. If you ever need to delete a certificate from `sec-server.jks` you may do so by running `idc-certdel`. The use of this command is very similar to that of `idc-certview`. After installing the new certificate, the next step is to associate specific certificates with user accounts. This is described in the next section.

## 4.2.2 Associating an X.509 Certificate with a User Account

When a user or another IDC sends your IDC a request it needs to be able to associate the certificate in that request with an OSCARS user account. Creating user accounts via the WBUI is described in section **4.1.1 Creating New User Accounts** and modifying existing accounts is described in section **4.1.2 Modifying Users**. Copying the “subject” of the certificate being sent in the *X.509 Subject Name* field of the WBUI will associate a certificate with a user account. You may obtain the X.509 subject in a few ways. First, the user may be able to send you the subject of their certificate. If they cannot, have them send you their certificate (i.e. via email) and use `idc-certview` to extract the subject. You may use `idc-certview` to extract the subject as follows:

```
Choose the keystore or file with the certificate you'd like to
view:
    1. sec-client.jks - stores the private key and certificate
    used to send messages to other IDCs
    2. sec-server.jks - stores certificates trusted to sign
    incoming messages
    3. ssl-keystore.jks - stores SSL certificates of other
    IDCs running HTTPS
    4. Open certificate file...
Enter choice: 4
Enter the certificate filename: /home/oscars/usercert.cer
-- Certificate Details
--- NOTE: The 'Owner' field is the X.509 subject name
[CERTIFICATE OUTPUT DISPLAYS HERE]
```

When you `idc-certview` you will be prompted for the location of the certificate. Since the certificate is in a file that the user gave you choose option **4**. You will then be prompted for the certificate filename and once provided the certificate in the file prints. As noted in the output, the *X.509 subject name* is the same as the *Owner* field that displays. Copy the value of the *Owner* field into the WBUI as previously described and your IDC will correctly associate the certificate containing the given subject and the user account you choose.



## 5 Describing Your Network Topology

### 5.1 Generating an XML Topology Description

OSCARS currently requires you to manually generate an XML file that describes your network's topology in the Open Grid Forum (OGF) Network Measurement Working Group (NMWG) control plane topology schema<sup>2</sup>. The topology description you generate describes what is *possible* on your network. For example, it is not concerned with what VLANs are currently provisioned on a network, rather the possible VLANs that could be provisioned on the network.

You can generate both an inter-domain topology description and an intra-domain topology description. The inter-domain topology description will be advertised to other networks, and the intra-domain topology description will be used for internal purposes. Currently, it is recommended you use the same topology for both. Generating the XML topology description is currently one of the most time-consuming portions of the install process.

#### 5.1.1 Example XML files

The easiest way to generate this file is to start from the two examples provided with the DCN Software Suite. Both files describe the same topology of the “blue pod” used in Internet2 DCN workshops<sup>3</sup>. You can find the example XML files in the following locations on your system:

- `$CATALINA_HOME/shared/classes/terce.conf/tedb-inter.xml`
- `$CATALINA_HOME/shared/classes/terce.conf/tedb-intra.xml`

Both contain the same topology so either will be fine. You may edit them directly or edit a copy in another location on your system. You will need to point the TERCE to the final copy of your files. You may do this by modifying the following file:

- `$CATALINA_HOME/shared/classes/terce.conf/terce-ws.properties`

Edit the `tedb.static.db.interdomain` and `tedb.static.db.intradomain` properties to point to the location of each file.

#### 5.1.2 Domains, Nodes, Ports and Links

The NMWG topology schema consists of a hierarchy of domains, nodes, ports, and links. The table below describes each of these elements.

Element	Child Element	Description
---------	---------------	-------------

<sup>2</sup> <http://anonsvn.internet2.edu/svn/nmwg/trunk/nmwg/schema/>

<sup>3</sup> <http://events.internet2.edu/2007/DCN/>

<b>domain</b>	node	Represents an administratively-similar set of devices.
<b>node</b>	port	Represents a network device. For this installation, it represents a VLSR
<b>port</b>	link	Represent a physical or virtual port on the network. Corresponds to a physical port number and/or DRAGON local-id for this installation.
<b>link</b>	-	Represents a connection between two ports. For the purposes of this installation, you will likely have one port per link.

### 5.1.3 Fully-Qualified Identifiers

Every element in the domain-node-port-link hierarchy has an “id” attribute. The ID takes the value of a Uniform Resource Name (URN) that contains not only an ID for the element defining it, but also its parent elements. This type of identifier is referred to as a fully-qualified identifier. These IDs always begin with the prefix “urn:ogf:network:”. This prefix is followed by a colon-delimited list of identifiers appropriate for that hierarchical level. For example, a fully-qualified port ID contains a domain ID, a node ID, and the port ID. The hierarchical level of each portion is indicated by either a “domain=”, “node=”, “port=”, or “link=” prefix. Examples of different fully-qualified link ID types from the example topology files that come with the software are shown below:

Type	Fully-Qualified Identifier
<b>domain ID</b>	urn:ogf:network:domain=blue.pod.lan
<b>node ID</b>	urn:ogf:network:domain=blue.pod.lan:node=vlsr1
<b>port ID</b>	urn:ogf:network:domain=blue.pod.lan:node=vlsr1:port=3
<b>link ID</b>	urn:ogf:network:domain=blue.pod.lan:node=vlsr1:port=3:link=11.2.1.2

### 5.1.4 <topology> Element

The <topology> element is the top-level element of the XML description. It contains the following important attributes and values.

Element/Attribute	Example	Description
<i>Id</i>	blue-topology	An identifier for this element. It has no significance currently and may be any string.
<idcId>	https://idc.blue.pod.lan:8443/axis2/services/OSCARS	The URL to the IDC advertising this topology. In most cases, you will only need to replace 'idc.blue.pod.lan' with the host on which you have installed the IDC.

### 5.1.5 <domain> Element

The <domain> element contains a set of commonly administered nodes. In addition to < node >, <domain> contains the following attributes and children elements:

Element/Attribute	Example	Description
<i>Id</i>	urn:ogf.network:domain=blue.pod.lan	A URN representing the domain's ID. The portion after "domain=" MUST be globally unique and SHOULD take the form of a DNS name.

### 5.1.6 <node> element

The <node> element represents a VLSR. In addition to a list of < port > elements, <domain> contains the following attributes and children elements:

Element/Attribute	Example	Description
<i>Id</i>	urn:ogf.network:domain=blue.pod.lan:node=vlsr1	A URN representing the node's ID. The portion after "node=" may be any valid string and is not required by the IDC to have any specific value.
<address>	192.168.2.4	An IP address that corresponds to the "router-id" field in the VLSR's ospfd.conf file. See DRAGON install

documents for more info about router-id's and ospfd.conf.

### 5.1.7 <port> Element

The <port> element represents a connection point between VLSRs. **The ID of this element must be set a specific way for OSCARS to correctly provision circuits.** The ID field corresponds to a physical port and/or local-ID controlled by DRAGON. The ID attribute's format is different depending on the network devices being controlled.

Element/Attribute	Example	Description
<i>id</i>	urn:ogf.network:domain=blue.pod.lan:node=vlsr1:port=3	This type of ID maps directly to the local-ID or physical port of an Ethernet switch.
<i>Id</i>	urn:ogf.network:domain=anna.internet2.edu:node=vlsr1:port=1-2-1	This type of ID maps to a port on an Ethernet switch. The format is (chassis+shelf)-slot-subport
<i>Id</i>	urn:ogf.network:domain=dcn.internet2.edu:node=CHIC:port=S23647	This type of ID map is applied to ports on an ESLM card in a Ciena CoreDirector. The format is S(Subnet Interface ID). See DRAGON documentation for more information about subnet interface IDs.
<i>Id</i>	urn:ogf.network:domain=dcn.internet2.edu:node=CHIC:port=DTL1	This type of IDC maps to internal SONET links between CienaCoreDirectors. The DTL values map to those in the DRAGON configuration files.
<capacity>	1000000000	Maximum capacity of the port in bits per second
<maximumReservableCapacity>	1000000000	Maximum amount of capacity that can be reserved on a link in bits per second. It MUST be <= capacity
<minimumReservableCapacity>	100000000	Minimum amount of capacity that can be reserved on a link in bits per second. It MUST be <=

		maximumReservableCapacity
<granularity>	100000000	The minimum increment in which bandwidth can be reserved.

### 5.1.8 <link> Element

Element/Attribute	Example	Description
<i>id</i>	urn:ogf:network:domain=blue.pod.lan:node=vlsr1:port=3:link=11.2.1.2	The link portion of this ID MUST map to the TE address used in the DRAGON ospfd.conf files. <b>For Ethernet interfaces on the edge of your network the link-id is only used as a label and may be any value you wish(i.e. 1, *, myport, etc)</b>
<remoteLinkId>	urn:ogf:network:domain=*.node=*.port=*.link=*	The remote link to which the link is connected. Values may all be "*" if connected to an end-host or domain without a topology description.
<trafficEngineeringMetric>	1000000000	A metric associated with this link
<capacity>	1000000000	Maximum capacity of the link in bits per second. Must be <= the parent <port> capacity
<maximumReservableCapacity>	1000000000	Maximum amount of capacity that can be reserved on a link in bits per second. It MUST be <= capacity
<minimumReservableCapacity>	100000000	Minimum amount of capacity that can be reserved on a link in bits per second. It MUST be <= maximumReservableCapacity
<granularity>	100000000	The minimum increment in which bandwidth can be reserved.

### 5.1.9 <switchingCapabilityDescriptors> Element

This element is a child of link and contains information about its parent's switching capability. This information can be derived from DRAGON's ospfd.conf or narb.conf.

Element/Attribute	Example	Description
<switchingcapType>	l2sc	"l2sc" for Ethernet links and "tdm" for SDH/SONET links
<encodingType>	ethernet	"Ethernet" for Ethernet links and "sdh" for SDH/SONET links

### 5.1.10 <switchingCapabilitySpecficInfo> Element

This element is a child of <switchingCapabilityDescriptors> and contains information specific to the switching capability type. Currently, only elements for l2sc links are defined.

Element/Attribute	Example	Description
< interfaceMTU >	9000	The maximum transmission unit (MTU) of this link
< vlanRangeAvailability >	0, 3000-3100, 3150-3200	The range of VLANs available for provisioning on a link. Use a "-" to separate continuous ranges and a "," to separate discontinuous ranges. <b>A value of 0 indicates that untagged interfaces are allowed on the interface represented by this link. Untagged interfaces will not be allowed if a value of 0 is not in the range.</b>

## 5.2 Configuring the terce-ws.properties file

**NOTE:** You may skip this section if your static-routes.xml, tedb-intra.xml, and tedb-inter.xml file are in \$CATALINA\_HOME/shared/classes/terce.conf.

The TERCE is a web service that acts as the topology exchange and route computation element for OSCARS. In the future, it will act as the intermediary between OSCARS and the NARB, but only static topology description and route files are supported in this release. To ensure the TERCE properties file can locate the static topology and route file you have generated, it must be edited as follows:

1. Open \$CATALINA\_HOME/shared/classes/terce.conf/terce-ws.properties in a text editor

2. Change the properties file to look like the following (where *location-of-your-topology-file* is replaced with the custom path to your topology file and likewise for *location-of-your-static-routes-file*)

```
#static tedb properties
tedb.type=static
tedb.static.db.interdomain=location-of-your-topology-file
tedb.static.db.intradomain=location-of-your-topology-file

#static rce properties
rce.type=static
rce.static.file=location-of-your-static-routes-file
```

## 5.3 Populating the Scheduling Database

The final step is to import the topology information from your XML file into the OSCARS scheduling database so that it can keep track of which resources are used on the network. This is done by defining your local domain in the database and running `updateTopology.sh`.

### 5.3.1 Defining Your Local Domain

You must define your local domain so that OSCARS know which links are on your network. This information is stored in MySQL under the `bss.domains` table but you add it using the `idc-domainadd` script. You may run this script with the following commands:

```
% cd dcn-software-suite-0.4/idc/tools/utils/
% ./idc-domainadd
Topology Identifier (i.e. mydomain.net)*: blue.pod.lan
IDC URL*: https://your-machine:8443/axis2/services/OSCARS
Descriptive Name (for display purposes)*: Blue Pod
Abbreviated Name (for display purposes)*: blue

1. Energy Sciences Network
2. Internet2
3. MY ORGANIZATION
4. New...
Select the organization associated with this domain (by
number): 3
Is this your IDC's local domain? [y/n] y
```

The first field, Topology Identifier, MUST match the domain ID you use in your URNs. Also, make sure you select the organization that represents your local domain. You should have defined this value in 3.4 Creating the First User Account. If not you may create it by selecting “New...” from the menu of choices. the above commands should result in a message indicating the domain was added.

### 5.3.2 Run `updateTopology.sh`

The `updateTopology.sh` script syncs the database with your Intra-Domain topology file. The three steps for running this script are:

1. Verify Tomcat is running
2. Change your current directory to `dcn-software-suite-0.4/idc/tools/updatedbterce`

```
% cd dcn-software-suite-0.4/idc/tools/updatedbterce
```
3. Finally, run the `updateTopology.sh` script and point it to your TERCE service:
 

```
% ./updateTopology.sh
```

If no errors are returned, your database is now populated with the appropriate topology information.

## 5.4 Registering with a Topology Service

OSCARS can register the topology of your local domain with an external service so that other domains can consume the data. It also make it easily accessible to other tools such as those used for network monitoring. OSCARS also provides a pathfinding module that can consume your local information as well as other domain's topology information and use that to automatically calculate paths. It is **HIGHLY RECOMMENDED** that you enable topology registraion although it is not required unless you plan to use the above module (which is used by default). If you do not plan to register you topology with an external service please see 12.1 Creating a Static List of Local Paths.

Registering your topology with the external topology service is done by modifying values in the `oscars.properties` file. More information is provided on this file in section 8 Appendix A: `oscars.properties`. The change that you need to make to register your topology are as follows:

1. Open `$CATALINA_HOME/shared/classes/server/oscars.properties` in a text editor
2. Find the line `"#external.service.2=topology"` and remove the `"#"` symbol at the beginning of the line.
3. By default Internet2 provides a topology service located at the URL specified for the `perfsnar.topology_url` property. If you are running your own topology service you may change this property, otherwise you can proceed to the next step
4. Restart Tomcat with the following commands to complete this task:



```
% $CATALINA_HOME/bin/shutdown.sh
% $CATALINA_HOME/bin/startup.sh
```

## 6 Verifying that You Can Build Local Circuits

If you have completed all the previous steps in this document you may now try provisioning a local circuit via the WBUI. The following steps will allow you to do this:

1. Open a browser and go to <https://your-server:8443/OSCARS> (or port 8080 if SSL is not installed)
2. Login using a user account you created
3. Click the “Create Reservation” tab
4. Enter the following value into the form (at a minimum):
  - a. Source – a fully qualified link-id or lookup service name of one edge of your network
  - b. Destination - a fully qualified link-id or lookup service name of another edge of your network
  - c. Bandwidth – the amount of bandwidth to reserve
  - d. Description – a brief description of your reservation
5. Click the “Reserve Bandwidth” button.

Assuming everything works correctly, you should see a page indicating the reservation was made. Click the “Refresh” button until you see the status of “ACTIVE” indicating that the scheduler built the circuit. Once you see ACTIVE you may begin using your circuit.

## 7 Inter-Domain Configuration

This section details the steps required to configure your IDC to communicate with other IDCs. The basic process involves generating an X.509 certificate for communication with other IDCs, adding neighboring domains to the OSCARS database, and activating notifications. Once completing this section you will be able to request circuits that span across multiple domains.

### 7.1 Generating an IDC Certificate for Sending Inter-Domain Requests

#### 7.1.1 Creating a Certificate and Private Key

You must generate a certificate and private key that your domain will use to sign messages passed to other domains. This certificate and associated key are stored in the following keystore file:

- `$CATALINA_HOME/shared/classes/repo/sec-client.jks`.

You may generate a new certificate and private key for your IDC using the `idc-certadd` script provided with OSCARS. An example of an `idc-certadd` session is shown below:

```
% cd dcn-software-suite-0.4/idc/tools/utils
% ./idc-certadd
What would you like to do?
    1. Create a new certificate my IDC will use in outgoing
messages to other IDCs
    2. Import a certificate created using choice 1 that was
signed by a CA
    3. Trust a CA or another IDC's certificate
Enter choice: 1
```

At this point you want to create a new certificate for your IDC so you should select option 1. This results in the following output:

```
-- You have chosen to create a new certificate for sending
messages to other IDCs.

Enter an alias for this certificate: idccert
How many days will this certificate be valid?: 3650
```

You will be prompted for the “alias” and the number of days the certificate will be valid. The alias is an identifier used for reference purposes. It has no real meaning so choose a value that allows you to easily remember what certificate this is. The second value determines when the certificate will expire. When the certificate expires you either need to renew your current certificate or create a new one. In the example the value of 3650 indicates the certificate will not expire for about 10 years. If you are not sure what value to specify then something like 3650 is adequate. After these prompts the following output appears:

```
-- Using keystore password from
/usr/local/tomcat/shared/classes/repo/sec-client.properties
What is your first and last name?
[Unknown]: youridc.yourdomain.net
What is the name of your organizational unit?
[Unknown]: Networking
What is the name of your organization?
[Unknown]: Your Organization
What is the name of your City or Locality?
[Unknown]: Ann Arbor
What is the name of your State or Province?
[Unknown]: MI
What is the two-letter country code for this unit?
[Unknown]: US
```

When it asks for your first and last name you don’t actually have to add a first and last name. You should add a unique identifier that represents this IDC. It’s your decision what this value is, but using your IDC’s hostname is common. The values for the fields that follow may matter if your CA has restrictions on them. Check with your CA if you have questions about these fields (*NOTE: The Internet2 test CA allows these fields to be any value*). After entering these values the following output displays:

```
Is CN=youridc.yourdomain.net, OU=Networking, O=Your
Organization, L=Ann Arbor, ST=MI, C=US correct?
[no]: yes

-- Certificate created.
```

You will need to confirm that the values you entered are correct. If they are not then you may respond ‘no’ and re-enter the values.

```
Would you like to generate a Certificate Signing Request (CSR)
y/n? y
What filename should I give the CSR?: myidc.csr
Enter key password for <alias>password
```

The final two prompts ask if you’d like to create a certificate signing request (CSR). You need to do this if your certificate is going to be signed by a CA. If you answer ‘y’ then you will be prompted for a file in which to save the request (*Note: If you answer ‘n’ you may generate a CSR later by running the `idc-certsignreq` command*). You will also be prompted for the key password which is ALWAYS the value **password** in current OSCARS implementations. After your certificate signing request is generated the following output appears:

```
-- Certificate Signing Request saved in file myidc.csr
--- Please send myidc.csr to your CA for signing.
--- You may then import your signed certificate by running
idc-certadd and choosing option 2.
--- Send the following X.509 subject to your neighboring IDCs:
CN=youridc.yourdomain.net, OU=Networking, O=Your Organization,
L=Ann Arbor, ST=MI, C=US
```

These lines indicate that the certificate was successfully created and a CSR generated. If no CSR was generated then you will see output similar to the above (but indicating the lack of CSR). Most useful from this output is probably the last line that prints your certificate subject. You may send that to other IDCs and they can use it to map your IDC’s user account to your IDC’s certificate. If you ever need to view the certificates subject again then run `idc-certview`, select “sec-client.jks”, and select your certificate. The subject will be displayed in the *Owner* field. If you are not going to get your certificate signed then you are done with this section and may progress to another section. If you are going to get your certificate signed then you should continue to **7.1.2 Getting the IDC Certificate Signed**.

## 7.1.2 Getting the IDC Certificate Signed

The first step to getting your certificate signed is to send a certificate signing request (CSR) to a certificate authority (CA). This will be done via email or some other mechanism. You may have generated the CSR when you ran `idc-certadd` or you may generate it by running `idc-certsignreq`. After your CA responds to the request and gives you a signed certificate file you may import it with `idc-certadd`. An example session is shown below:

```
% cd dcn-software-suite-0.4/idc/tools/utils
% ./idc-certadd
What would you like to do?
    1. Create a new certificate my IDC will use in outgoing
messages to other IDCs
    2. Import a certificate created using choice 1 that was
signed by a CA
    3. Trust a CA or another IDC's certificate
Enter choice: 2
```

When you run the `idc-certadd` script you are given the choice of what operation you'd like to perform. You want to import a signed version of the previously created certificate so choose option 2. This leads to the following output:

```
-- You have chosen to import a signed certificate for talking
to other domains.

Enter the filename of your signed certificate:
/home/oscars/idccert.cer
```

You will then be prompted to provide the filename of the signed certificate. After specifying the filename, the script verifies a copy of the certificate belonging to the CA that signed your certificate is in `sec-client.jks`. If it is not (which is likely if this is your first time creating a certificate) then you will need to import it (*NOTE: If it is then you will not see the next couple sections of output*). The CA will be able to provide you with their certificate. Example output of the situation where you need to import the CA certificate is shown below:

```
-- Using keystore password from
/usr/local/tomcat/shared/classes/repo/sec-client.properties
-- Using certificate with the alias idccert
--- If this is not the correct alias please exit (Ctrl-C) and
modify the <user> tag in axis2.xml
-- You need to import the root certificate of the CA that
signed your certificate.
--- Your CA should have given you this file. If they did not
then they can provide it.
--- The CA certificate will have the subject 'CN=DCSTest,
OU=DCS Test, O=DCS Test, L=Ann Arbor, ST=Michigan, C=US'
Enter the filename of your CA's certificate:
/home/oscars/dcn_ca.cer
Enter an alias for your CA's certificate: i2dcnca
```

The prompts ask you for the filename of the CA certificate and the alias to identify it. The certificate alias may be any value that helps you remember it belongs to the CA. After providing these values you will see something like the following:

```
Owner: CN=DCSTest, OU=DCS Test, O=DCS Test, L=Ann Arbor,
ST=Michigan, C=US
```

```

Issuer: CN=DCSTest, OU=DCS Test, O=DCS Test, L=Ann Arbor,
ST=Michigan, C=US
Serial number: 0
Valid from: Thu Mar 29 11:14:29 EDT 2007 until: Sun Mar 26
11:14:29 EDT 2017
Certificate fingerprints:
    MD5: 92:21:D8:26:10:73:0A:CE:36:56:7D:F8:6C:65:9E:C6
    SHA1:
05:25:DF:20:69:78:EC:89:40:12:E7:70:01:B3:FB:D7:9E:44:9C:FF
Trust this certificate? [no]: yes
Certificate was added to keystore
-- CA certificate imported

```

The top output is the CA certificate and you must verify that you want to install it. After answering 'yes' your CA certificate will be installed and you should see the following output(NOTE: If prompted for a password literally enter the string 'password'):

```

Enter key password for <idccert>password
Certificate reply was installed in keystore
-- Signed certificate imported
--- Send the following X.509 subject to your neighboring IDCs:
CN=youridc.yourdomain.net, OU=Networking, O=Your Organization,
L=Ann Arbor, ST=MI, C=US

```

This indicates that you have successfully installed a signed certificate for use by your domain.

## 7.2 Making your IDC Aware of Other Domains

You must add an entry for each domain to the bss.domains table in MySQL. An entry is needed for both direct neighbors and downstream domains with which dynamic circuit requests may traverse. This is can be done using the idc-domainadd script and the following commands:

```

% cd dcn-software-suite-0.4/idc/tools/utils/
% ./idc-domainadd
Topology Identifier (i.e. mydomain.net)*: red.pod.lan
IDC URL*: https://their-machine:8443/axis2/services/OSCARS
Descriptive Name (for display purposes)*: Red Pod
Abbreviated Name (for display purposes)*: red

1. Energy Sciences Network
2. Internet2
3. MY ORGANIZATION
4. New...
Select the organization associated with this domain (by
number): 4
Organization Name*: Red Domain Inc
New organization 'Red Domain Inc' added.
Is this your IDC's local domain? [y/n] n

```

Replace 'red.pod.lan' with the local part of the full-qualified domain-id URN (i.e. the part after "domain="), 'Red Pod' and 'red' with easily recognizable strings(can be anything), and add the URL of their IDC (NOTE: you may enter 'Unknown' if the domain is not a direct neighbor). Also, please associate the domain with an organization. If you have not already created an organization for this domain choose the "New..." option, otherwise select an existing organization. The organization is important in allowing neighbors to retrieve information from your local IDC about reservations that cross their domain. In general, every domain should be associated with a unique organization.

You will also need to point to your neighbor's *notification broker* service. This is the service that distributes notifications about IDC activity. If your neighbor is also running OSCARS (as opposed to another flavor of IDC), the URL will be the same as the IDC URL except with the last part containing OSCARSNotify instead of OSCARS. The commands to add this service are as follows (assuming you are in the directory dcn-software-suite-0.4/idc/tools/utils/):

```
% ./idc-serviceadd

1. blue.pod.lan
2. red.pod.lan
Select the service's domain (by number): 2
Choose service type:
    1. NotificationBroker
    2. Other...
Enter Choice*: 1
Service URL*: https://their-
machine:8443/axis2/services/OSCARSNotify
New 'NB' service at 'https://their-
machine:8443/axis2/services/OSCARS' added.
```

You will also need to create a user account for each neighboring domain using the process described in section 4 *Creating and Managing User Accounts*. The most important piece is that the certSubject field matches the X.509 certificate subject they have provided.

The final step is to update your topology description and import it into the OSCARS scheduling database. To do this open your tedb-intra.xml file (found in the directory \$CATALINA\_HOME/shared/classes/terce.conf unless you did a special configuration) and update the appropriate *remoteLinkId* field(s) with the URN(s) of your neighbor. After updating and saving the file run the following commands:

```
% cd dcn-software-suite-0.4/idc/tools/updatedbterce
% ./updateTopology.sh
```

### 7.3 Activating Notifications

IDCs communicate by sending notifications between each other as important events occur. These notifications are distributed by a *notification broker* service that is installed with OSCARS by default. The IDC service must authenticate itself to the notification broker service even though they run on the same machine so that not just anyone can send notifications for distribution. This means you must create a user account for the local IDC through the WBUI or the `idc-useradd` script. In both cases you will need to set the “X.509 Subject Name” to the subject of the local IDCs certificate that was created in section **7.1 Generating an IDC Certificate for Sending Inter-Domain Requests**. You will also need to give it the “OSCARS-service” and “OSCARS-publisher” roles. An example screenshot of the WBUI “Add User” form is shown below:

Required fields are outlined in green.

Add User

Reset form fields

Login Name

localidc

Password (Enter twice)

.....

Password Confirmation

.....

First Name

LOCAL

Last Name

IDC

X.509 subject name

CN=youridc.yourdomain.net, OU=Networ

X.509 issuer name

Organization

MY ORGANIZATION

Choose Roles

[Documentation](#)

None  
OSCARS-user -> make reservations  
OSCARS-engineer -> manage all reservations, view and update topology  
OSCARS-administrator -> manage all users  
OSCARS-service -> make reservations and view topology  
OSCARS-publisher -> publish events to external services  
OSCARS-may-specify-path -> an add-on attribute to allow specification of path elements  
OSCARS-operator -> view all reservations  
OSCARS-site-administrator -> manage all reservations starting or ending at site

Personal Description

E-mail (Primary)

admin@yourdomain.net

E-mail (Secondary)

Phone Number (Primary)

5555555555

Phone Number (Secondary)

After adding the new user you need to modify the `oscars.properties` to indicate that notifications should be sent. You may do this with the following steps:

1. Open `$CATALINA_HOME/shared/classes/server/oscars.properties` in a text editor
2. Remove the '#' symbol from the line `#notify.observer.2=net.es.oscars.notify.WSObserver` (or add the line “`notify.observer.2=net.es.oscars.notify.WSObserver`” if it does not contain the aforementioned line)
3. Finally, restart Tomcat with the following commands:

```
% $CATALINA_HOME/bin/shutdown.sh
% $CATALINA_HOME/bin/startup.sh
```

## 7.4 Trusting SSL Certificates of Other IDCs Running HTTPS

Many IDCs run HTTP over SSL (HTTPS) on their servers. This means that when you connect to their IDC to forward a request to them that you must trust the SSL certificate to establish the connection. Essentially, this verifies to your IDC that the remote IDC is who they say they are. Your IDC trusts the SSL certificate they give you if it is signed by a certificate authority (CA) installed in the following keystore:

- `$CATALINA_HOME/shared/classes/repo/ssl-keystore.jks`

By default certificates such as the Internet2 test CA and those from ESnet are installed. If you would like to trust SSL certificates signed by other CAs you may run `idc-certadd` to install their certificates. An example of an `idc-certadd` session to insert this type of certificate is shown below:

```
% cd dcn-software-suite-0.4/idc/tools/utlis
% ./idc-certadd
What would you like to do?
    1. Create a new certificate my IDC will use in outgoing
    messages to other IDCs
    2. Import a certificate created using choice 1 that was
    signed by a CA
    3. Trust a CA or another IDC's certificate
Enter choice: 3
```

The script prompts you for the operation you'd like to perform. Choose option 3 since you'd like to import a new trusted certificate. The following output then displays:

```
-- You have chosen to import a trusted certificate.

Enter certificate filename: ca.cer
```



```
Enter certificate alias (This value is used to reference the
certificate in some configuration files. It may be any valid
string.): caname
```

You are then prompted for the file name of the ca certificate and an alias. Give the filename of the certificate from your CA that you wish to install. The alias can be any value that helps you remember to which CA the certificate belongs. After providing the requested values the following output is shown:

```
OSCARS will trust this certificate when it's used to sign...
...an incoming request y/n? n
...the SSL certificate of another IDC's web server y/n? y
```

You are asked which situations in which you want to trust a certificate signed by the CA. You MUST answer 'y' to the second prompt for the certificate to be installed in the correct keystore. You may also answer 'y' to the first question if you want to trust incoming requests that have certificates signed by the CA (see section **4.2.1 Trusted Certificate Authorities** for more information on when to answer 'y' to the first question). After answering these prompts the following output will appear (more will appear if you answered 'y' to both).

```
-- Using keystore password from
/usr/local/tomcat/shared/classes/server/sec-server.properties
Certificate was added to keystore

-- Certificate imported into
/usr/local/tomcat/shared/classes/repo/ssl-keystore.jks. HTTPS
servers using this certificate or another certificate issued
by the CA it represents will now be trusted.

-- Complete
```

The above output indicates that the certificate was successfully installed.

## 8 Appendix A: **oscars.properties**

The `oscars.properties` file is the main area in which the OSCARS IDC retrieves installation-specific settings. These include settings for accessing the MySQL database, AAA, the perfSONAR Lookup Service, interacting with DRAGON, and more. The `oscars.properties` file is located on your system at:

- `$CATALINA_HOME/shared/classes/server/oscars.properties`

Your installation comes with a default `oscars.properties` file. This subsection details the properties required for an installation of the OSCARS IDC on a DRAGON-controlled network.

### 8.1.1 General

Property	Example Value	Description
<b>idc.url</b>	http://your-idc:8443/axis2/services/OSCARS	The URL of the local IDC. If not specified then OSCARS will default to the first hostname found on the current machine and assume https is running on port 8443.

### 8.1.2 MySQL Database Properties

The required properties related to the MySQL database are:

Property	Example Value	Description
<b>hibernate.connection.username</b>	oscars	The MySQL username the OSCARS IDC uses to access the database
<b>hibernate.connection.password</b>	mypass	The MySQL password the OSCARS IDC uses to access the database

*(Note: Hibernate is the name of the library used to manage database connections.)*

### 8.1.3 Authentication, Authorization, and Accounting (AAA) Properties

The required properties related to AAA are:

Property	Example Value	Description
<b>aaa.salt</b>	os	The value with which encrypted passwords are salted. A value of 'os' means a password could be generated with <code>crypt('password','os')</code>
<b>aaa.userName</b>	oscars	The username for accessing a secure cookie. Required if running the WBUI. It may be any valid string value.
<b>aaa.sessionName</b>	oscarssess	The session name for a secure cookie. Required if running the WBUI. It may be any valid string value.
<b>aaa.secureCookie</b>	1	If set to 1 it will require users to use SSL to access the WBUI. For ease of installation this defaults to 0 but <b>it</b>

		<b>is recommended you change this value to 1 after setting-up SSL.</b>
<b>aaa.useSignalTokens</b>	1	If set to 1 then signaling tokens will be generated for each createReservation request. Signaling tokens can be transferred between a user who sends a createReservation request and another who wants to send the createPath. <b>Note: If you running the IDC on a PowerPC you MUST set this property to 0.</b>
<b>aaa.guestLogin</b>	guest	The value of this optional property is a username that can be used to assign a guest login to the WBUI. The difference between a guest and a regular user is that a guest can login to the WBUI from multiple machines. In the example given the user “guest” has this ability. <b>An IDC administrator should be very careful about what permissions it gives a guest account as it is NOT secure.</b>

#### 8.1.4 Topology Exchange and Pathfinding Properties

The required properties related to topology exchange and pathfinding are:

Property	Example Value	Description
<b>pathfinder.findPath</b>	1	In general, always set to 1. If set to 0, the user must always provide the path.
<b>pathfinder.pathMethod</b>	perfsonar,terce	This property indicates the pathfinding component to use. If a comma-separated list then it will try each pathfinder until an inter-domain path is found. Set to perfsonar if want automatic path calculation using an external topology service. Set to terce for static path calculation.
<b>tedb.tedbMethod</b>	terce	Always set to ‘terce’ for DRAGON

		installations. This property indicates the traffic engineering database type (i.e. where to get topology info).
<b>terce.url</b>	http://127.0.0.1:8080/axis2/services/TERCE	The URL to the TERCE service. In most cases, the example URL can be used exactly as shown.
<b>topo.defaultSwcapType</b>	tdm	Defaults to tdm if not specified. Indicates the default switching capability type for non-ethernet links.
<b>topo.defaultEncodingType</b>	sdh/sonet	Defaults to sdh/sonet if not specified. Indicates the default switching capability type for non-ethernet links.

### 8.1.5 Path Setup Properties

The required properties related to path setup are:

Property	Example Value	Description
<b>pss.method</b>	dragon	The method for setting up circuits. A value of 'dragon' means that the IDC will try to use DRAGON to create the path. A value of 'stub' simulates circuit setup but does not perform any action.
<b>pss.dragon.password</b>	dragon	The telnet password used to access the dragon VLSR.
<b>pss.dragon.ssh.portForward</b>	1	Sends telnet traffic over an SSH tunnel if set to 1. If 0, telnet traffic is sent directly to VLSR.
<b>pss.dragon.setERO</b>	0	Explicitly sets every link on the local path if set to 1. This is highly

		recommended as it ensures DRAGON uses exactly the same path reserved in OSCARS. <b>You can only set this value to 1 if you are running the version of DRAGON in DCNSS 0.3 or later.</b>
<b>pss.dragon.tunnelMode</b>	0	Optional property that will cause untagged circuits on Ciena CoreDirectors to be setup in tunnel mode if equals 1. Tunnel-mode means that an interface will accept any Ethernet packet (tagged or untagged) whereas a regular untagged circuit only accepts untagged packets.
<b>pss.dragon.ssh.user</b>	oscars	Required if pss.dragon.ssh.portForward= 1. The SSH user must be the same for all VLSR machines.
<b>pss.dragon.ssh.key</b>	/home/oscars/.ssh/id_rsa	Required if pss.dragon.ssh.portForward= 1. The public key used for SSH login must be the same for all VLSR machines. See ssh-keygen man pages for more information.
<b>pss.dragon.remotePort</b>	2611	The telnet port on which the DRAGON CLI is running. Most DRAGON installations will use 2611.
<b>pss.dragon.nodeId<sup>4</sup></b>	127.0.0.1	The address used by telnet to access the VLSR with <i>nodeId</i> . If pss.dragon.ssh.portForward= 1, you should set this to 127.0.0.1.

---

<sup>4</sup> Not required if pss.dragon.ssh.portForward= 0 AND the nodeAddress field in the XML topology description is a routable address that can be used by telnet.

<b>pss.dragon.<i>nodeId</i>.ssh</b>	192.168.2.4	Required if pss.dragon.ssh.portForward= 1. The SSH address to access a VLSR with the given <i>nodeId</i> .
<b>pss.dragon.<i>nodeId</i>.ssh.port</b>	22	Optional. Defaults to 22. Indicates the SSH port number used to access the VLSR represented by <i>nodeId</i> via SSH. Use this property if SSH runs on a non-standard port number.
<b>pss.dragon.promptPattern</b>	vlsr	Optional. Defaults to “vlsr”. This value is a string that will be used in the telnet prompt of all the VLSRs. You will get a large hexdump in your logs if this property is not set properly.
<b>pss.dragon.hasNarb</b>	1	Optional. Defaults to 1. Indicates whether the domain is running a NARB. If set to 0 it causes OSCARS to use tunnel-id/lsp-id local-ids when sending commands to the VLSR.
<b>pss.dragon.delay</b>	30	The number of seconds between setup/teardown operations on a VLSR

### 8.1.6 Notifications

Property	Example Value	Description
<b>notify.observer.<i>N</i></b>	net.es.oscars.notify.EmailObserver	Sets a notification component. Current valid componets include one for send Email messages (net.es.oscars.notify.EmailObser ver) and another for sending WS- Notification messages(net.es.oscars.notify.W

		SObserver). The latter must be included for an IDC to support inter-domain messaging. The value $N$ is a number starting at 1.
<b>notify.ws.broker.url</b>	https://your-idc.net:8443/axis2/services/OSCAR SNotify	The URL of the local IDC's NotificationBroker
<b>notify.ws.broker.registerRetryAttempts</b>	10	The number of times to try registering with the IDC before failing. The default is 10.
<b>notify.ws.broker.secondsBetweenRegistrationRetries</b>	60	The number of seconds between retry attempts of registering with the local notification broker
<b>notifybroker.subscriptions.maxExpireTime</b>	3600	The maximum amount of time a subscription can remain active without expiring in the notification broker
<b>notifybroker.publishers.maxExpireTime</b>	3600	The maximum amount of time a publisher registration can remain active without expiring in the notification broker
<b>notifybroker.pep.N</b>	net.es.oscars.notify.ws.policy.IDCEventPEP	The type of “policy enforcement point” to use. The PEP controls who can receive what notifications. If inactive any user can receive any notification. The only valid value is currently “net.es.oscars.notify.ws.policy.IDCEventPEP”
<b>mail.webmaster</b>	webmaster@blue.pod.lan	Email address of OSCARS administrator who will receive

		notifications from the server
<b>mail.recipients</b>	user1@my.net:user2@my.net	A colon delimited list of recipients of email notifications from OSCARS

### 8.1.7 External Services

Property	Example Value	Description
<b>external.service.N</b>	subscribe	Tells OSCARS to use an external service of some type. Valid values are subscribe and topology. Subscribe tells it to subscribe to other IDC's notifications and topology tells it to register with the topology service. <i>N</i> is a value starting at 1.
<b>perfsonar.topology_url</b>	http://packrat.internet2.edu:8012/perfSONAR_PS/services/topology	The URL of the topology service with which to register and to pull data from to calculate a path
<b>lookup.hints</b>	http://www.perfsonar.net/gls.root.hints	A URL to a hints file containing a list of global lookup services.
<b>lookup.global.N</b>	http://ndb1.internet2.edu:9990/perfSONAR_PS/services/gLS	A URL to a global lookup service. <i>N</i> is a number starting at 1.
<b>lookup.home.N</b>	http://ndb1.internet2.edu:8005/perfSONAR_PS/services/hLS	A url to a home lookup service to use for lookups if lookup.useGlobal is set to 0. <i>N</i> is a number that starts at 1.
<b>lookup.useGlobal</b>	1	If 1 then any lookup requests to will first try to discover the home lookup service with the data by contacting a global lookup



		service (as found in the hints file or set with lookup.global.N). If 0 then it will only contact the hope lookup services specified by lookup.home.N.
<b>external.service.subscribe.termTimeWindow</b>	.2	The window of time as a percent of the total time that the IDC should renew a subscribe message. (i.e. a value of .2 means that a subscription that expires in 60 minutes will be renewed 12 minutes (.2 * 60 minutes) before the expiration time. Default is .2.
<b>external.service.subscribe.retryInterval</b>	1800	The number of seconds to wait before retrying a subscribe message to another IDC. Default is 30 minutes
<b>external.service.subscribe.topics</b>	idc:IDC	The topics to subscribe to from other IDCs Default is idc:IDC.
<b>external.service.topology.renewTime</b>	1800	The number of seconds between topology registration messages. Default is 1800 (30 minutes).

### 8.1.8 Miscellaneous Properties

Other various properties are:

Property	Example Value	Description
<b>logging.rsvlogdir</b>	/usr/local/tomcat/logs	Location to keep log information on individual reservations.
<b>timeout.default</b>	600	The default number of seconds to wait for a notification from another IDC in response to a

		request. May be overridden by any of the other timeout properties.
<b>timeout.[create  modify  cancel]Resv.confirm</b>	600	The number of seconds to wait for a createReservation, modifyReservation, or cancel reservation confirm notification before timing out. (i.e. timeout.createResv.confirm=600)
<b>timeout.[create  modify  cancel]Resv.complete</b>	600	The number of seconds to wait for a createReservation, modifyReservation, or cancel reservation complete message before timing out. (i.e. timeout.createResv.confirm=600)
<b>timeout.[create  teardown]Path.confir m</b>	600	The number of seconds to wait for a createPath or teardownPath confirm notification before timing out. (i.e. timeout.createPath.confirm=600)
<b>timeout.[create  teardown]Path.retry Attempts</b>	10	The number of times to try to update the status of a reservation in response to a createPath or teardownPath event received from another IDC. This property is useful for domains that have clocks slightly out of sync and one may send notification of a create/teardown before the other is ready.
<b>timeout.[create  teardown]Path.retry Wait</b>	30	The number of seconds to wait before trying to update the status of a reservation in response to a confirm or complete event. This property is useful for domains

		that have clocks slightly out of sync and one may send notification of a create/teardown before the local IDC is ready.
<b>policy.vlanFilter.scope</b>	node	Defines the scope to which a VLAN must be unique. May be domain, node, port, or link. Default is node.
<b>rmi.serverPort</b>	1098	The port on which to run the RMI server. Default is 0 (0 means an arbitrary port).
<b>rmi.registryPort</b>	1099	The port on which to run the RMI registry. Default is 1099.

## 9 Appendix B: Using Hostnames Instead of URNs in Requests

An optional step that will make provisioning easier is to generate hostnames for the URNs on the edge of your network. This will prevent users from having to enter long URNs into requests for circuits on your network. Currently this functionality is provided by a **Lookup Service**. The Lookup Service is analogous to DNS in the IP world. You may run your own instance of the Lookup Service or you may use an instance Internet2 has running. To add lookup service names to the lookup service please email [deploy-dcn@internet2.edu](mailto:deploy-dcn@internet2.edu) with the list of names and URNs you would like added to the Lookup Service maintained by Internet2.

## 10 Appendix C: Manually Installing Axis2

Axis2 provides the IDC with a web service framework. It is installed in Tomcat as its own web application. This section details installation and configuration of Axis2.

### 10.1.1 Download and Installation

Download Axis2 from the project's web site at:

- [http://ws.apache.org/axis2/download/1\\_3/download.cgi](http://ws.apache.org/axis2/download/1_3/download.cgi)

You only need to download the **WAR (Web Archive) Distribution** of the software. **You MUST download version 1.3 for the IDC to function properly.**

Unpack and install the downloaded components with the following commands:

```
% unzip -d axis2-1 axis2-1.3-war.zip
% mv axis2-1/axis2.war $CATALINA_HOME/webapps
```

After moving the WAR file to the correct location, restart the Tomcat server:

```
% $CATALINA_HOME/bin/shutdown.sh
% $CATALINA_HOME/bin/startup.sh
```

### 10.1.2 Setting the AXIS2\_HOME Environment Variable

Once Axis2 is installed, you need to set the AXIS2\_HOME environment variable with its location. To set this environment variable, issue these commands:

```
% AXIS2_HOME=$CATALINA_HOME/webapps/axis2/WEB-INF
% export AXIS2_HOME
```

You may permanently set this variable (recommended) by adding the above commands to the profile file in your home directory (i.e. .bash\_profile or .profile).

### 10.1.3 Verifying a Successful Installation

Validate that installation was successful by pointing your web browser to the following URL:

- <http://your-machine-name:8080/axis2> OR
- <https://your-machine-name:8443/axis2> (if SSL is configured – see section 2.3.5 Configuring SSL)

On the page that loads, click **Validate**. A page will appear that indicates the status of your Axis2 installation. If you see a message that reads “The core axis2 libraries are present.” Your installation was successful.

## 10.2 Manually Installing Rampart

Rampart is an Axis2 module that provides a number of the IDC’s security features. This section details its installation.

### 10.2.1 Download and Installation

Download the Rampart module from the project’s web site at:

- [http://www.apache.org/dyn/mirrors/mirrors.cgi/ws/rampart/1\\_3/rampart-1.3.zip](http://www.apache.org/dyn/mirrors/mirrors.cgi/ws/rampart/1_3/rampart-1.3.zip)

Unpack and install rampart with the following commands:

```
% unzip rampart.zip
% cp rampart-1.3/rampart-1.3.mar $AXIS2_HOME/modules/
% cp rampart-1.3/lib/*.jar $AXIS2_HOME/lib/
```

After installing Rampart, you must restart the Tomcat server with the following commands:

```
% $CATALINA_HOME/bin/shutdown.sh
% $CATALINA_HOME/bin/startup.sh
```

## 10.2.2 Verifying a Successful Installation

You may verify that Rampart was installed correctly through the Axis2 administrator interface. To use this interface point a web browser to the following URL:

- <http://your-machine-name:8080/axis2/axis2-admin/>

You may login using the default username and password (**user: admin, password: axis2**). Click on the **Available Modules** link on the left side of the screen after logging-in. If installation was successful, you will see Rampart in the list that loads.

# 11 Appendix D: Becoming a Certificate Authority (CA)

It's possible to act as a certificate authority (CA) and sign user certificates. Currently, there are no recommendations regarding who should become a CA as a true dynamic circuit authentication and authorization (AA) infrastructure is yet to exist. This section is intended to be a reference for some of the commands needed when running your own CA.

## 11.1.1 Generating Your Own CA Certificate

You may generate your own CA certificate. This is optional and requires the OpenSSL library. There are various issues with safeguarding root certificates that are beyond the scope of this document. The five basic steps to allow you to generate a root certificate are:

1. Create a directory for your CA certificates

```
% mkdir ca_certs
```

2. Create an openssl.conf file in the new directory (search the Internet for examples)

3. Create files for tracking created certificates in directory created in step 1

```
% touch certindex.txt
% echo '100001' > serial
```

4. Create a private key

```
% openssl genrsa -des3 -out ca_private.key 1024
```

## 5. Create a public key certificate from the private key

```
% openssl req -new -x509 -days 3650 -key ca_private.key -out ca.cer
```

### 11.1.2 Signing User ‘Certificate Signing Requests’ (CSRs)

If you do decide to run your own CA certificate, you will be responsible for signing user Certificate Signing Requests (CSRs). This requires the **user** to run the following commands:

```
% keytool -genkey -alias user1 -keystore sec-client.jks -storepass
password -validity 3650
% keytool -certreq -alias user1 -keystore sec-client.jks -file
~/oscars_certs/dcstest_ca/requests/user1.csr
```

Then, the user sends you the CSR file (`user1.csr`). You can then sign the CSR and convert it to an X.509 certificate with the following commands:

```
% openssl ca -config openssl.conf -cert ca.cer -in
requests/user1.csr -keyfile ca_private.key -days 3650 -out
signed_certs/user1.cer
% openssl x509 -in signed_certs/user1.cer -out signed_certs/user1-
X509.cer
```

Afterwards, you can send the user the signed certificate and they can import it **into the same keystore they used to generate the CSR** with the following command:

```
% keytool -import -keystore sec-client.jks -alias user1 -file user1-
X509.cer
```

## 12 Appendix E: Static Path Calculation

### 12.1 Creating a Static List of Local Paths

The current version of the OSCARS IDC requires you to statically generate intra-domain paths in an XML file. You only need to define those paths that are between the edges of your network. Defining inter-domain paths that extend beyond the local network are discussed in section **7 Inter-Domain Configuration**. An example of the static paths file can be found at the following location on your system:

- `$CATALINA_HOME/shared/classes/terce.conf/static-routes.xml`

**NOTE:** *If your network only runs one VLSR then you do not need to generate a static-routes.xml file and may skip this section. This file is NOT used to calculate the path from edge to edge of the same node. For this reason, you also do not need to define local paths that start and terminate on the same node.*

You may edit this file directly or make a copy. You will need to point the TERCE to the final copy of this file. You may do this by modifying the following file:

- `$CATALINA_HOME/shared/classes/terce.conf/terce-ws.properties`

Edit the `rce.static.file` property to point to the location of `static-routes.xml`.

Here are some helpful guidelines when populating this file:

- `<staticPathEntry>` elements contain the paths. You will need a `<staticPathEntry>` for every source/destination combination you wish to use (including separate paths for the forward and reverse direction).
- `<srcEndpoint>` and `<destEndpoint>` elements contain **fully-qualified link-IDs**. Every time these link-IDs are seen, the associated path will be returned. If a lookup service name is used, it will get converted to a fully-qualified link-ID before making the path calculation.
- The `<path>` element carries the path to be returned when the associated source and destination are given by the user or as the ingress and egress to your network. The `<path>` contains a list of `<hop>` elements. Each of these `<hop>` elements contains a `<linkIdRef>`, which is a fully-qualified link ID.
- Each local hop in a path should be followed by the link to which it is connected. Every local hop should be indicated in the path.

*NOTE: Previous versions of OSCARS required both intra-domain and inter-domain paths to be specified in `static-routes.xml`. You can no longer define inter-domain paths in `static-routes.xml`, see section **12.2 Building Your Inter-Domain Routing Table** for information on defining inter-domain routes.*

## 12.2 Building Your Inter-Domain Routing Table

Currently OSCARS maintains static routing tables that determine the path a circuit will take to reach another domain. You can build these routing tables using the `idc-route` command found in the “tools/utils” directory. The command allows you to indicate a destination in another domain and the “path” you will use to reach that destination. A destination may be a domain, node, port or link URN. The path to your destination may be as simple as the egress link from your domain (a *loose* inter-domain path) or it may be as specific as every ingress and egress in the path to the destination (a *strict* interdomain-path). The types of routes you enter depend on the needs of your network. Every IDC administrator should read **Section 12.2.1** and then use the list below to help decide which other sections to read and what types of routes to add:

1. If your IDC is going to manage a regional network, campus, or lab with a **single** connection to another domain running the DCN Software Suite 0.3+ (i.e. Internet2 DCN) see **12.2.2 Defining a Default Route**.

2. If your IDC is managing a network with **multiple** connections to other domains running the DCN Software Suite 0.3+ see **12.2.3 Defining a Path with Only an Egress**.
3. If your IDC is managing a network with one or more connections to domains running a version of the DCN Software Suite older than 0.2 or are running their own version of an IDC see **12.2.4 Defining a Path with Multiple Hops**.

*NOTE: In previous versions of OSCARS static-routes.xml maintained inter-domain paths as well as intra-domain path. It still maintains intra-domain paths but it does not maintain inter-domain paths. This means that you will need to add routes as indicated in this section when upgrading to 0.3 from a previous version. This new method does NOT require you to specify the exact path to every domain so this will hopefully be much easier than building your static-routes.xml table.*

### 12.2.1 Populating the <remoteLinkId> fields in `tedb-intra.xml` and `tedb-inter.xml`

The first step to adding inter-domain routes is to update your topology description with your neighboring domains' *remoteLinkIds*. You do not need to add them all at once, you can add them as you get them and the steps will be the same. First, to obtain the *remoteLinkIds* you must contact the IDC administrator of your neighboring domain (via phone, email, etc) and exchange this information. You will need to give them the fully-qualified link-id that represents the interface on your network that connects to their network. They will do the same for you and you will add the information they give you to the *remoteLinkId* field in `tedb-intra.xml` and `tedb-inter.xml` of the link you gave them. You will then run `updateTopology.sh` to update your database with this new information. The commands for this are as follows:

```
% cd dcn-software-suite-0.4/idc/tools/updatedbterce
% ./updateTopology.sh
http://127.0.0.1:8080/axis2/services/TERCE
```

### 12.2.2 Defining a Default Route

A default route is an inter-domain route that will be taken when a destination does not match any other entries in the routing tables. If the default route is the only route in the table then it will ALWAYS be used. This may be desirable when your IDC manages a network that only has a connection to one other network. Below is an example of how you may add a default route to the OSCARS routing tables:

```
% cd dcn-software-suite-0.4/idc/tools/utlis
% ./idc-route add -default -loose -egress
urn:ogf:network:domain=blue.pod.lan:node=vlsr1:port=6:link=11.
1.11.2
```



The above command states that if someone requests a circuit in another domain it will exit the network on *urn:ogf:network:domain=blue.pod.lan:node=vlsr1:port=6:link=11.1.11.2* if no other entry matches. The `-loose` option indicates that there may be other hops between the egress and the destination and that it will be the responsibility of other IDCs to fill-in the missing values. If this is the only entry made to the routing tables ALL requests with a destination outside the domain will exit using the specified egress. Assuming this is the only entry, by looking at the example topology provided with the TERCE we see that this means requests will always be forwarded to the “red.pod.lan” domain. This can be seen by looking at the *remoteLinkId* field in the definition of the link is *tedb-intra.xml*. Issue the above command and replace the value given to egress with a link-id on your network to create a default route.

### 12.2.3 Defining a Path with Only an Egress

You should define this type of path if you have multiple connections to other networks capable of accepting loose inter-domain paths (LIDP). A LIDP is one that does not contain the ingress and egress link of every domain in a path. You may define an LIDP containing only the egress of your network to use. The path passed to the next domain will include this egress but it will be the responsibility of the next domain to fill in any additional inter-domain hops between itself and the destination. All domains running version 0.3 or greater of the DCN Software Suite have this capability. Below is an example of a command used to create this type of route:

```
% cd dcn-software-suite-0.4/idc/tools/utils
% ./idc-route add -dest urn:ogf:network:domain=red.pod.lan -
egress
urn:ogf:network:domain=blue.pod.lan:node=vlsr1:port=6:link=11.
1.11.2
```

The above command states that any destination with a domain id of *red.pod.lan* will be routed to the next domain on the given egress link. **If the destination is not in a directly adjacent domain then you will want to specify the `-loose` option for this type of route.** Notice that the destination is a domain-id as opposed to a link-id. This means that any link-id that contains “domain= red.pod.lan ” will match this entry. For example, *urn:ogf:network:domain=red.pod.lan:node=vlsr1:port=5:link=11.1.11.3* would match this entry if given as a destination. The destination field in the routing table may be a domain-id (as shown), node-id, port-id, or link-id. Destinations in requests will match the route for which there is the most specific definition. In other words, if one route matches at the node level and another matches at the domain level, then the node level match will be used. You may want to match at levels more specific than domain-d if you have multiple ways to get to a domain and it makes more geographic sense to take a particular egress when going to one node, port, or link than others. You may also make the routing decision based on the source in your domain. **Run `./idc-route -help` for more information.**

### 12.2.4 Defining a Path with Multiple Hops

You may define a route that indicates more than one inter-domain hop used to get to a destination. You should use this type of entry when talking to an IDC that requires a strict inter-domain path (SIDP). A SIDP is a path with the ingress and egress hop for each domain. In some cases you may also define a loose inter-domain path with multiple hops, but that does not necessarily contain every hop in the path. Below is an example of a command used to define an SIDP:

```
% cd dcn-software-suite-0.4/idc/tools/utils
% ./idc-route add -dest urn:ogf:network:domain=green.pod.lan -
multi
Enter local egress:
urn:ogf:network:domain=blue.pod.lan:node=vlsr1:port=6:link=11.
1.11.2
Enter hop URN or type 'end' to complete:
urn:ogf:network:domain=red.pod.lan:node=vlsr3:port=6:link=11.1
.11.1
Enter hop URN or type 'end' to complete:
urn:ogf:network:domain=red.pod.lan:node=vlsr1:port=5:link=11.1
.11.3
Enter hop URN or type 'end' to complete:
urn:ogf:network:domain=green.pod.lan:node=vlsr1:port=5:link=11
.1.11.4
Enter hop URN or type 'end' to complete: end
Route Added
```

In the above example a SIDP is defined to *green.pod.lan*. The first element specified is the egress from the local domain (*blue.pod.lan*). The next link is the ingress to an intermediate domain (*red.pod.lan*). This link MUST be the same as that defined in the *remoteLinkId* field of your topology description (in *tedb-inta.xml*). The third link defined is the egress of *red.pod.lan* to *green.pod.lan*. The final hop is the ingress to *green.pod.lan*. Notice you do not need to define the egress in *green.pod.lan*. This is because the egress will be the destination in the user's request.

*This is the basic way in which you define a path with multiple hops. There are more advanced uses of this functionality, including LIDPs that include domain, node, or port identifiers (as opposed to link identifiers) but this is saved for a more advanced document on inter-domain routing in OSCARS.*