

Rotor and adapter compatibility

Halvard calipers, 2026 catalogue

Read the row for the caliper you are fitting and the position it is going in. Front and rear adapters are not interchangeable, and an adapter that bolts up is not the same as an adapter with the right offset. Where the note column says to see a workshop bulletin, the bulletin is binding and this table is a summary.

Caliper	Position	Frame mount	Rotor	Adapter	Bolt	Note
BRK-2200 R4	front	post 160 mm	160 mm	none	22 mm	direct fit
BRK-2200 R4	front	post 160 mm	180 mm	ADP-3308	30 mm	universal adapter
BRK-2200 R4	front	flat mount	160 mm	ADP-3308	30 mm	check fork clearance
BRK-2200 R4	rear	post 160 mm	180 mm	see bulletin	30 mm	offset differs from front; see workshop bulletin 2026-04 before ordering an adapter
BRK-2204 R2	front	post 160 mm	160 mm	none	22 mm	direct fit
BRK-2204 R2	front	post 160 mm	180 mm	ADP-3308	30 mm	BRK-1174 superseded
BRK-2204 R2	rear	post 140 mm	160 mm	none	22 mm	BRK-1188 discontinued
BRK-2190 R2	front	post 160 mm	180 mm	ADP-3308	30 mm	2019 body, new olive needed

Rotor thickness is 1.8 mm new across the range and 1.5 mm at the wear limit. Bolt lengths above are the lengths supplied with the adapter, not the caliper bolts.