

Speculative Parallelization of a Randomized Incremental Convex Hull Algorithm

M. Cintra (i), D. Llanos (ii), **B. Palop (ii)**

(i) School of Informatics, U. Edinburgh, UK

(ii) Dpt. of Computer Science, U. Valladolid, Spain

Keywords

“Convex Hull”, “Speculative Parallelization”,
“Randomized Incremental Algorithm”

- Why the Convex hull?
- Why Speculative Parallelization?
- Why Randomized Algorithms?

Keywords

“Convex Hull”, “Speculative Parallelization”,
“Randomized Incremental Algorithm”

- **Why the Convex hull?**

Frequently used simple structure whose computation is bottleneck for many others

- **Why Speculative Parallelization?**

- **Why Randomized Algorithms?**

Keywords

“Convex Hull”, “Speculative Parallelization”,
“Randomized Incremental Algorithm”

- **Why the Convex hull?**

Frequently used simple structure whose computation is bottleneck for many others

- **Why Speculative Parallelization?**

No need to design specific parallel algorithms

- **Why Randomized Algorithms?**

Keywords

“Convex Hull”, “Speculative Parallelization”,
“Randomized Incremental Algorithm”

- **Why the Convex hull?**

Frequently used simple structure whose computation is bottleneck for many others

- **Why Speculative Parallelization?**


No need to design specific parallel algorithms

- **Why Randomized Algorithms?**

Lower time bounds are expected in most cases


Convex Hull of a set of points

- Definition: Given a set S of points in the plane, $CH(S)$ is the smallest convex set containing S .




Convex Hull of a set of points

- Definition: Given a set S of points in the plane, $CH(S)$ is the smallest convex set containing S .
- Construction:




Convex Hull of a set of points

- Definition: Given a set S of points in the plane, $CH(S)$ is the smallest convex set containing S .
- Construction: Divide and conquer




Convex Hull of a set of points

- Definition: Given a set S of points in the plane, $CH(S)$ is the smallest convex set containing S .
- Construction: Divide and conquer, Sweep line




Convex Hull of a set of points

- Definition: Given a set S of points in the plane, $CH(S)$ is the smallest convex set containing S .
- Construction: Divide and conquer, Sweep line, Incremental



Convex Hull of a set of points

- Definition: Given a set S of points in the plane, $CH(S)$ is the smallest convex set containing S .
- Construction: Divide and conquer, Sweep line, Incremental, Graham Scan, etc.




Parallelization

- By hand: Developing specialized algorithms for each problem and architecture.
- Automatic: Rely on the compiler to obtain a parallel version of the incremental sequential algorithm.

Speculative Parallelization


- Optimistic parallel execution of an iterative algorithm



Points inside the current solution. No dependencies found.

Speculative Parallelization


- Optimistic parallel execution of an iterative algorithm



One point inside, one point outside. No dependencies found.

Speculative Parallelization

- Optimistic parallel execution of an iterative algorithm
- Squashes are produced when dependencies are found at runtime



Points outside the current solution. Dependencies found!

Speculative Parallelization vs. the Convex Hull

Why being optimistic on a parallel execution of the Convex Hull?

- Output structure depends usually on a small portion of input points

Speculative Parallelization vs. the Convex Hull

Why being optimistic on a parallel execution of the Convex Hull?

- Output structure depends usually on a small portion of input points
- Given the solution, ALL other input points could be processed in parallel


Speculative Parallelization vs. the Convex Hull

Why being optimistic on a parallel execution of the Convex Hull?

- Output structure depends usually on a small portion of input points
- Given the solution, ALL other input points could be processed in parallel
- Iterative algorithms with a lot of inherent parallelism are excellent candidates for speculative parallelization


Convex Hull of a set of points (II)

- Construction: Divide and conquer




Convex Hull of a set of points (II)

- Construction: Divide and conquer, Sweep line




Convex Hull of a set of points (II)

- Construction: Divide and conquer, Sweep line, Graham Scan




Convex Hull of a set of points (II)

- Construction: Divide and conquer, Sweep line, Graham Scan, Incremental




Clarkson's Incremental Randomized Algorithm (I)

- **First three points build first triangle**
- Locate next point in existing structure
- If inside, process next point
- If outside, connect to structure and process next point




Clarkson's Incremental Randomized Algorithm (I)

- First three points build first triangle
- **Locate next point in existing structure**
- If inside, process next point
- If outside, connect to structure and process next point




Clarkson's Incremental Randomized Algorithm (I)

- First three points build first triangle
- Locate next point in existing structure
- **If inside, process next point**
- If outside, connect to structure and process next point




Clarkson's Incremental Randomized Algorithm (I)

- First three points build first triangle
- **Locate next point in existing structure**
- If inside, process next point
- If outside, connect to structure and process next point




Clarkson's Incremental Randomized Algorithm (I)

- First three points build first triangle
- Locate next point in existing structure
- If inside, process next point
- **If outside, connect to structure and process next point**




Clarkson's Incremental Randomized Algorithm (I)

- First three points build first triangle
- **Locate next point in existing structure**
- If inside, process next point
- If outside, connect to structure and process next point




Clarkson's Incremental Randomized Algorithm (I)

- First three points build first triangle
- Locate next point in existing structure
- If inside, process next point
- **If outside, connect to structure and process next point**




Clarkson's Incremental Randomized Algorithm (I)

- First three points build first triangle
- **Locate next point in existing structure**
- If inside, process next point
- If outside, connect to structure and process next point



Clarkson's Incremental Randomized Algorithm (I)

- First three points build first triangle
- Locate next point in existing structure
- If inside, process next point
- **If outside, connect to structure and process next point**



Clarkson's Incremental Randomized Algorithm (II)

- First three points build first triangle $\in O(1)$
- **Locate next point in existing structure**
- If inside, process next point $\in O(1)$
- If outside, connect to structure and process next point $\in O(1)$

The expected number of edges that see point p_{r+1} is in $O \log(r)$.

Clarkson's Incremental Randomized Algorithm (II)

- First three points build first triangle $\in O(1)$
- Locate next point in existing structure $\in O(\log n)$
- If inside, process next point $\in O(1)$
- If outside, connect to structure and process next point $\in O(1)$

The expected running time is $O(n \log n)$

Setup: Input Sets and System

Input sets

- CGAL 2.4 random point generator and shuffle functions with integer coordinates
- 10 and 40 Million points in a square
- 10 and 40 Million points in a disk

Setup: Input Sets and System

Input sets


- CGAL 2.4 random point generator and shuffle functions with integer coordinates
- 10 and 40 Million points in a square
- 10 and 40 Million points in a disk

System

- Sun Fire 15K symmetric multiprocessor (SMP) with SunOS 5.8
- 900MHz UltraSparc-III processors with 1 GByte of shared memory each
- Forte Developer 7 Fortran 95 compiler


Obtained speedups

- *Small* input set, with 10 MP




Obtained speedups

- *Small* input set, with 10 MP
- *Big* input set, with 40 MP




Results

- Overhead grows with the number of processors




Results

- Overhead grows with the number of processors
- Bigger sets obtain better speedups



Results

- Overhead grows with the number of processors
- Bigger sets obtain better speedups
- Performance also depends on the block size



Conclusions

- Speculative parallelization is a valid technique to extract inherent parallelism from randomized iterative algorithms

Conclusions


- Speculative parallelization is a valid technique to extract inherent parallelism from randomized iterative algorithms
- No manual parallelization is needed: speculative calls may be inserted automatically

Conclusions

- Speculative parallelization is a valid technique to extract inherent parallelism from randomized iterative algorithms
- No manual parallelization is needed: speculative calls may be inserted automatically
- Low-cost technique: No need of hardware changes to the processor and/or memory hierarchy

Ongoing and future work

- Squash graphics show the *hot spots* where many dependencies are found



Ongoing and future work

- Squash graphics show the *hot spots* where many dependencies are found
- Dynamic scheduling can be applied to decrease the number of dependencies and reexecutions of big blocks

