

**Nome: Gabriel Wagner e Glaucus Rossini**

**Link do repositório:**

<https://github.com/gabrielhwagner/aps-bd>

As instruções para o rodar o projeto está no arquivo anotacoes.md

**Banco criado e utilizado através do mysql workbench**

BANCO DE DADOS HOTEL (Banco criado na disciplina de DB 1)

```
CREATE DATABASE IF NOT EXISTS `hotel` /*!40100 DEFAULT CHARACTER SET
utf8mb4 COLLATE utf8mb4_0900_ai_ci */ /*!80016 DEFAULT ENCRYPTION='N' */;
```

```
USE `hotel`;
```

```
-- MySQL dump 10.13 Distrib 8.0.20, for Linux (x86_64)
```

```
--
```

```
-- Host: localhost Database: hotel
```

```
-- -----
```

```
-- Server version 8.0.20-0ubuntu0.19.10.1
```

```
/*!40101 SET @OLD_CHARACTER_SET_CLIENT=@@CHARACTER_SET_CLIENT */;
```

```
/*!40101 SET @OLD_CHARACTER_SET_RESULTS=@@CHARACTER_SET_RESULTS
*/;
```

```
/*!40101 SET @OLD_COLLATION_CONNECTION=@@COLLATION_CONNECTION */;
```

```
/*!50503 SET NAMES utf8 */;
```

```
/*!40103 SET @OLD_TIME_ZONE=@@TIME_ZONE */;
```

```
/*!40103 SET TIME_ZONE='+00:00' */;
```

```
/*!40014 SET @OLD_UNIQUE_CHECKS=@@UNIQUE_CHECKS, UNIQUE_CHECKS=0
*/;
```

```
/*!40014 SET @OLD_FOREIGN_KEY_CHECKS=@@FOREIGN_KEY_CHECKS,
FOREIGN_KEY_CHECKS=0 */;
```

```
/*!40101 SET @OLD_SQL_MODE=@@SQL_MODE,  
SQL_MODE='NO_AUTO_VALUE_ON_ZERO' */;
```

```
/*!40111 SET @OLD_SQL_NOTES=@@SQL_NOTES, SQL_NOTES=0 */;
```

```
--
```

```
-- Table structure for table `categoria`
```

```
--
```

```
DROP TABLE IF EXISTS `categoria`;
```

```
/*!40101 SET @saved_cs_client = @@character_set_client */;
```

```
/*!50503 SET character_set_client = utf8mb4 */;
```

```
CREATE TABLE `categoria` (
```

```
  `id` int NOT NULL AUTO_INCREMENT,
```

```
  `nome` varchar(45) NOT NULL,
```

```
  `descricao` varchar(45) NOT NULL,
```

```
  PRIMARY KEY (`id`)
```

```
) ENGINE=InnoDB AUTO_INCREMENT=5 DEFAULT CHARSET=utf8;
```

```
/*!40101 SET character_set_client = @saved_cs_client */;
```

```
--
```

```
-- Dumping data for table `categoria`
```

```
--
```

```
LOCK TABLES `categoria` WRITE;
```

```
/*!40000 ALTER TABLE `categoria` DISABLE KEYS */;
```

```
INSERT INTO `categoria` VALUES (1,'Luxo','Quarto de luxo com tudo que tem direito'),(2,'Básico','Para uma noite de conforto'),(3,'Presidencial','Quarto com banheira de hidromassagem'),(4,'Harry Potter','Decoração totalmente inspirada na saga');
```

```
/*!40000 ALTER TABLE `categoria` ENABLE KEYS */;
```

```
UNLOCK TABLES;
```

```
--
```

```
-- Table structure for table `cidade`
```

```
--
```

```
DROP TABLE IF EXISTS `cidade`;
```

```
/*!40101 SET @saved_cs_client = @@character_set_client */;
```

```
/*!50503 SET character_set_client = utf8mb4 */;
```

```
CREATE TABLE `cidade` (
```

```
  `id` int NOT NULL AUTO_INCREMENT,
```

```
  `nome` varchar(45) NOT NULL,
```

```
  `uf_uf` char(2) NOT NULL,
```

```
  PRIMARY KEY (`id`),
```

```
  KEY `fk_cidade_uf1_idx` (`uf_uf`),
```

```
  CONSTRAINT `fk_cidade_uf1` FOREIGN KEY (`uf_uf`) REFERENCES `uf` (`uf`)
```

```
) ENGINE=InnoDB AUTO_INCREMENT=12 DEFAULT CHARSET=utf8;
```

```
/*!40101 SET character_set_client = @saved_cs_client */;
```

--

-- Dumping data for table `cidade`

--

LOCK TABLES `cidade` WRITE;

/\*!40000 ALTER TABLE `cidade` DISABLE KEYS \*/;

INSERT INTO `cidade` VALUES (1,'Abadia de Goiás','GO'),(2,'São Paulo','SP'),(3,'Teófilo Otoni','MG'),(4,'Tabuleiro', 'MG'),(5,'Jequitinhonha','MG'),(6,'Jenipapo dos Vieiras','MA'),(7,'Jaú do \nTocantins','TO'),(8,'Juazeirinho','PB'),(9,'Chorozinho','CE'),(10,'Clevelândia','MG'),(11,'Cupar aque','MG');

/\*!40000 ALTER TABLE `cidade` ENABLE KEYS \*/;

UNLOCK TABLES;

--

-- Table structure for table `consumo`

--

DROP TABLE IF EXISTS `consumo`;

/\*!40101 SET @saved\_cs\_client = @@character\_set\_client \*/;

/\*!50503 SET character\_set\_client = utf8mb4 \*/;

CREATE TABLE `consumo` (

  `id` int NOT NULL AUTO\_INCREMENT,

  `observacao` varchar(150) DEFAULT NULL,

  PRIMARY KEY (`id`)

```
) ENGINE=InnoDB AUTO_INCREMENT=6 DEFAULT CHARSET=utf8;
```

```
/*!40101 SET character_set_client = @saved_cs_client */;
```

```
--
```

```
-- Dumping data for table `consumo`
```

```
--
```

```
LOCK TABLES `consumo` WRITE;
```

```
/*!40000 ALTER TABLE `consumo` DISABLE KEYS */;
```

```
INSERT INTO `consumo` VALUES (1,'Nenhuma'),(2,'Quebrou  
\ngarrafa'),(3,NULL),(4,NULL),(5,NULL);
```

```
/*!40000 ALTER TABLE `consumo` ENABLE KEYS */;
```

```
UNLOCK TABLES;
```

```
--
```

```
-- Table structure for table `consumo_produto`
```

```
--
```

```
DROP TABLE IF EXISTS `consumo_produto`;
```

```
/*!40101 SET @saved_cs_client = @@character_set_client */;
```

```
/*!50503 SET character_set_client = utf8mb4 */;
```

```
CREATE TABLE `consumo_produto` (
```

```
  `consumo_id` int NOT NULL,
```

```
  `produto_id` int NOT NULL,
```

```

`quantidade` int NOT NULL,

`data` datetime NOT NULL,

PRIMARY KEY (`consumo_id`,`produto_id`),

KEY `fk_consumo_has_produto_produto1_idx` (`produto_id`),

KEY `fk_consumo_has_produto_consumo1_idx` (`consumo_id`),

CONSTRAINT `fk_consumo_has_produto_consumo1` FOREIGN KEY (`consumo_id`)
REFERENCES `consumo` (`id`),

CONSTRAINT `fk_consumo_has_produto_produto1` FOREIGN KEY (`produto_id`)
REFERENCES `produto` (`id`)

) ENGINE=InnoDB DEFAULT CHARSET=utf8;

/*!40101 SET character_set_client = @saved_cs_client */;

--

-- Dumping data for table `consumo_produto`

--

LOCK TABLES `consumo_produto` WRITE;

/*!40000 ALTER TABLE `consumo_produto` DISABLE KEYS */;

INSERT INTO `consumo_produto` VALUES (1,2,4,'2019-02-20
10:10:10'),(2,2,2,'2019-03-30 22:10:10'),(3,1,1,'2019-05-01
08:10:10'),(3,3,5,'2019-02-09 10:10:10'),(3,4,3,'2019-02-10
14:10:10'),(3,5,6,'2019-02-10 18:10:10'),(4,2,4,'2019-02-10
10:10:10'),(4,5,5,'2019-02-08 14:10:10');

/*!40000 ALTER TABLE `consumo_produto` ENABLE KEYS */;

UNLOCK TABLES;

```

```

--

-- Table structure for table `endereco`

--

DROP TABLE IF EXISTS `endereco`;

/*!40101 SET @saved_cs_client = @@character_set_client */;

/*!50503 SET character_set_client = utf8mb4 */;

CREATE TABLE `endereco` (

  `id` int NOT NULL AUTO_INCREMENT,

  `cep` char(8) NOT NULL,

  `rua` varchar(45) NOT NULL,

  `numero` int NOT NULL,

  `complemento` varchar(45) NOT NULL,

  `logradouro` varchar(45) NOT NULL,

  `cidade_id` int NOT NULL,

  PRIMARY KEY (`id`),

  KEY `fk_endereco_cidade1_idx` (`cidade_id`),

  CONSTRAINT `fk_endereco_cidade1` FOREIGN KEY (`cidade_id`) REFERENCES

`cidade` (`id`)

) ENGINE=InnoDB AUTO_INCREMENT=12 DEFAULT CHARSET=utf8;

/*!40101 SET character_set_client = @saved_cs_client */;

--

-- Dumping data for table `endereco`

```

--

LOCK TABLES `endereco` WRITE;

/\*!40000 ALTER TABLE `endereco` DISABLE KEYS \*/;

INSERT INTO `endereco` VALUES (1,'90050161','Menina do  
\nInterior',147,'405','Avenida',2),(2,'90050000','Andradas',1000,'2','Estação',1),(3,'9005  
0301','Carlos Gomes',30,'8','Vila',5),(4,'90052223','Lima e  
Silva',2,'1','Campo',7),(5,'90050444','Nilo  
Peçanha',2,'55','Condomínio',1),(6,'90050444','Rua do  
\nZé',3000,'2','Condomínio',1),(7,'90700000','Alameda dos  
\nAnjos',6,'3','Alameda',8),(8,'90050666','Crista  
Lake',666,'666','Lago',9),(9,'90050666','Elm  
Street',999,'999','Rua',5),(10,'90161000','Orfanotrófio',169,'3','Rua',3),(11,'90050111','An  
dré da Rocha',22,'3','Avenida',11);

/\*!40000 ALTER TABLE `endereco` ENABLE KEYS \*/;

UNLOCK TABLES;

--

-- Table structure for table `funcionario`

--

DROP TABLE IF EXISTS `funcionario`;

/\*!40101 SET @saved\_cs\_client = @@character\_set\_client \*/;

/\*!50503 SET character\_set\_client = utf8mb4 \*/;

CREATE TABLE `funcionario` (  
 `codigo` int NOT NULL AUTO\_INCREMENT,  
 `funcao` varchar(45) NOT NULL,  
 `pessoa\_cpf` char(11) NOT NULL,



```

PRIMARY KEY (`codigo`),

KEY `fk_funcionario_pessoa1_idx` (`pessoa_cpf`),

CONSTRAINT `fk_funcionario_pessoa1` FOREIGN KEY (`pessoa_cpf`) REFERENCES
`pessoa` (`cpf`)

) ENGINE=InnoDB AUTO_INCREMENT=5 DEFAULT CHARSET=utf8;

/*!40101 SET character_set_client = @saved_cs_client */;

--

-- Dumping data for table `funcionario`

--

LOCK TABLES `funcionario` WRITE;

/*!40000 ALTER TABLE `funcionario` DISABLE KEYS */;

INSERT INTO `funcionario` VALUES
(1,'Faxineiro(a)','59012873045'),(2,'Faxineiro(a)','07541928062'),(3,'Faxineiro(a)','5086
04540 1'),(4,'Faxineiro(a)','34903868095');

/*!40000 ALTER TABLE `funcionario` ENABLE KEYS */;

UNLOCK TABLES;

--

-- Temporary view structure for view `funcionarios`

--

DROP TABLE IF EXISTS `funcionarios`;

/*!50001 DROP VIEW IF EXISTS `funcionarios`*/;

```

```
SET @saved_cs_client = @@character_set_client;
```

```
/*!50503 SET character_set_client = utf8mb4 */;
```

```
/*!50001 CREATE VIEW `funcionarios` AS SELECT
```

```
1 AS `codigo`,
```

```
1 AS `funcao`,
```

```
1 AS `pessoa_cpf`,
```

```
1 AS `cpf`,
```

```
1 AS `rg`,
```

```
1 AS `nome`,
```

```
1 AS `data_nascimento`,
```

```
1 AS `ddd`,
```

```
1 AS `telefone`,
```

```
1 AS `endereco_id`*/;
```

```
SET character_set_client = @saved_cs_client;
```

```
--
```

```
-- Table structure for table `hospede`
```

```
--
```

```
DROP TABLE IF EXISTS `hospede`;
```

```
/*!40101 SET @saved_cs_client = @@character_set_client */;
```

```
/*!50503 SET character_set_client = utf8mb4 */;
```

```
CREATE TABLE `hospede` (
```

```

`numero_registro` int NOT NULL AUTO_INCREMENT,

`pessoa_cpf` char(11) NOT NULL,

PRIMARY KEY (`numero_registro`),

KEY `fk_hospede_pessoa1_idx` (`pessoa_cpf`),

CONSTRAINT `fk_hospede_pessoa1` FOREIGN KEY (`pessoa_cpf`) REFERENCES
`pessoa` (`cpf`)

) ENGINE=InnoDB AUTO_INCREMENT=10 DEFAULT CHARSET=utf8;

/*!40101 SET character_set_client = @saved_cs_client */;

--

-- Dumping data for table `hospede`

--

LOCK TABLES `hospede` WRITE;

/*!40000 ALTER TABLE `hospede` DISABLE KEYS */;

INSERT INTO `hospede` VALUES
(3,'00748701060'),(7,'06622402000'),(4,'16371689002'),(1,'28866323098'),(9,'299014
61057'),(6,'62470326095'),(8,'63249363090'),(2,'72571488058'),(5,'80692559000');

/*!40000 ALTER TABLE `hospede` ENABLE KEYS */;

UNLOCK TABLES;

--

-- Table structure for table `pessoa`

--

```

```
DROP TABLE IF EXISTS `pessoa`;

/*!40101 SET @saved_cs_client = @@character_set_client */;

/*!50503 SET character_set_client = utf8mb4 */;

CREATE TABLE `pessoa` (
  `cpf` char(11) NOT NULL,
  `rg` varchar(45) NOT NULL,
  `nome` varchar(90) NOT NULL,
  `data_nascimento` date NOT NULL,
  `ddd` char(2) NOT NULL,
  `telefone` varchar(9) NOT NULL,
  `endereco_id` int NOT NULL,
  PRIMARY KEY (`cpf`),
  KEY `fk_pessoa_endereco1_idx` (`endereco_id`),
  CONSTRAINT `fk_pessoa_endereco1` FOREIGN KEY (`endereco_id`) REFERENCES
`endereco` (`id`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8;

/*!40101 SET character_set_client = @saved_cs_client */;

--

-- Dumping data for table `pessoa`

--

LOCK TABLES `pessoa` WRITE;

/*!40000 ALTER TABLE `pessoa` DISABLE KEYS */;
```

```
INSERT INTO `pessoa` VALUES ('00748701060','392282719','Kevinson
Junior','1994-10-20','16','888888888',7),('06622402000','433691268','Wladimir Paraná
do Brasil','1975-10-20','55','333333333',11),('07541928062','374311729','Berta
Rachou','1945-04-11','11','254852145',2),('16371689002','328036432','Luís
Merenda','1978-07-04','18','999999999',8),('28866323098','349264636','Generosa\nFa
rias','1975-10-20','14','784545478',5),('29901461057','477463083','Urano
Magalhães','1999-08-20','14','555555555',5),('34903868095','442467497','Eva Gina
Melo','1988-02-20','13','658785457',4),('50860454010','236904346','Espere em Deus
Mateus','2000-01-20','12','485458214',3),('59012873045','451230863','Oceano
Atlantico da Silveira e
Souza','1999-10-20','51','915235874',1),('62470326095','109994036','Washington Luis
Moço','1999-05-28','51','222222222',10),('63249363090','254624662','Virtuosa
Doutora dos
Anjos','1999-10-20','53','444444444',2),('72571488058','345255653','Isabel Ignorada
Campos','1958-06-01','15','574845687',6),('80692559000','237991913','Zitelman José
dos Santos','1963-08-10','19','111111111',9);
```

```
/*!40000 ALTER TABLE `pessoa` ENABLE KEYS */;
```

```
UNLOCK TABLES;
```

```
--
```

```
-- Table structure for table `produto`
```

```
--
```

```
DROP TABLE IF EXISTS `produto`;
```

```
/*!40101 SET @saved_cs_client = @@character_set_client */;
```

```
/*!50503 SET character_set_client = utf8mb4 */;
```

```
CREATE TABLE `produto` (
```

```
  `id` int NOT NULL AUTO_INCREMENT,
```

```
  `nome` varchar(45) NOT NULL,
```

```
  `valor` decimal(12,2) NOT NULL,
```

```
  PRIMARY KEY (`id`)
```

```

) ENGINE=InnoDB AUTO_INCREMENT=7 DEFAULT CHARSET=utf8;

/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table `produto`
--

LOCK TABLES `produto` WRITE;

/*!40000 ALTER TABLE `produto` DISABLE KEYS */;

INSERT INTO `produto` VALUES (1,'Pastel',6.00),(2,'Refri
\nlata',5.00),(3,'Alaminuta',20.00),(4,'Chocolate',5.00),(5,'Agua',3.00),(6,'Suco
natural',10.00);

/*!40000 ALTER TABLE `produto` ENABLE KEYS */;

UNLOCK TABLES;

--
-- Table structure for table `quarto`
--

DROP TABLE IF EXISTS `quarto`;

/*!40101 SET @saved_cs_client = @@character_set_client */;

/*!50503 SET character_set_client = utf8mb4 */;

CREATE TABLE `quarto` (
  `numero` int NOT NULL,

```

```

`valor` decimal(12,2) NOT NULL,

`acomodacoes` varchar(45) DEFAULT NULL,

`categoria_id` int NOT NULL,

PRIMARY KEY (`numero`),

KEY `fk_quarto_categoria_idx` (`categoria_id`),

CONSTRAINT `fk_quarto_categoria` FOREIGN KEY (`categoria_id`) REFERENCES
`categoria` (`id`)

) ENGINE=InnoDB DEFAULT CHARSET=utf8;

/*!40101 SET character_set_client = @saved_cs_client */;

--

-- Dumping data for table `quarto`

--

LOCK TABLES `quarto` WRITE;

/*!40000 ALTER TABLE `quarto` DISABLE KEYS */;

INSERT INTO `quarto` VALUES
(100,50.00,'1',2),(101,50.00,'1',2),(105,100.00,'3',1),(108,300.00,'2',3),(200,100.00,'4',1),
(220,300.00,'2',3),(320,450.00,'4',4),(400,450.00,'4',4);

/*!40000 ALTER TABLE `quarto` ENABLE KEYS */;

UNLOCK TABLES;

--

-- Table structure for table `reserva`

--

```

```
DROP TABLE IF EXISTS `reserva`;
```

```
/*!40101 SET @saved_cs_client = @@character_set_client */;
```

```
/*!50503 SET character_set_client = utf8mb4 */;
```

```
CREATE TABLE `reserva` (
```

```
  `numero_reserva` int NOT NULL AUTO_INCREMENT,
```

```
  `data_entrada` date NOT NULL,
```

```
  `data_saida` date NOT NULL,
```

```
  `quarto_numero` int NOT NULL,
```

```
  `checkin` datetime DEFAULT NULL,
```

```
  `checkout` datetime DEFAULT NULL,
```

```
  `hospede_numero_registro` int NOT NULL,
```

```
  `funcionario_codigo` int NOT NULL,
```

```
  `consumo_id` int NOT NULL,
```

```
  PRIMARY KEY (`numero_reserva`),
```

```
  KEY `fk_reserva_quarto1_idx` (`quarto_numero`),
```

```
  KEY `fk_reserva_hospede1_idx` (`hospede_numero_registro`),
```

```
  KEY `fk_reserva_funcionario1_idx` (`funcionario_codigo`),
```

```
  KEY `fk_reserva_consumo1_idx` (`consumo_id`),
```

```
  CONSTRAINT `fk_reserva_consumo1` FOREIGN KEY (`consumo_id`) REFERENCES  
  `consumo` (`id`),
```

```
  CONSTRAINT `fk_reserva_funcionario1` FOREIGN KEY (`funcionario_codigo`)  
  REFERENCES `funcionario` (`codigo`),
```

```
  CONSTRAINT `fk_reserva_hospede1` FOREIGN KEY (`hospede_numero_registro`)  
  REFERENCES `hospede` (`numero_registro`),
```



```
CONSTRAINT `fk_reserva_quarto1` FOREIGN KEY (`quarto_numero`) REFERENCES  
`quarto` (`numero`)
```

```
) ENGINE=InnoDB AUTO_INCREMENT=20 DEFAULT CHARSET=utf8;
```

```
/*!40101 SET character_set_client = @saved_cs_client */;
```

```
--
```

```
-- Dumping data for table `reserva`
```

```
--
```

```
LOCK TABLES `reserva` WRITE;
```

```
/*!40000 ALTER TABLE `reserva` DISABLE KEYS */;
```

```
INSERT INTO `reserva` VALUES (1,'2019-10-20','2019-10-22',100,'2019-10-20  
00:00:00','2019-10-22 00:00:00',1,2,1),(2,'2019-10-21','2019-10-22',101,'2019-10-22  
00:00:00','2019-10-22 00:00:00',2,2,2),(3,'2019-10-22','2019-10-24',200,'2019-10-22  
00:00:00','2019-10-23 00:00:00',3,3,3),(4,'2019-10-25','2019-10-26',320,'2019-10-25  
00:00:00','2019-10-26 00:00:00',4,3,4),(5,'2019-10-27','2019-10-29',400,'2019-10-27  
00:00:00','2019-10-29 00:00:00',5,2,5),(6,'2019-11-01','2019-11-10',105,'2019-11-01  
00:00:00','2019-11-09 00:00:00',6,2,1),(7,'2019-11-05','2019-11-15',108,'2019-11-05  
00:00:00','2019-11-15 00:00:00',7,3,2),(8,'2019-11-18','2019-11-20',100,'2019-11-18  
00:00:00','2019-11-20 00:00:00',8,3,3),(9,'2019-11-18','2019-11-20',105,'2019-11-18  
00:00:00','2019-11-20 00:00:00',9,2,4),(10,'2019-11-28','2019-11-30',220,'2019-11-28  
00:00:00','2019-11-30 00:00:00',1,3,5),(11,'2019-12-01','2019-12-02',105,'2019-12-01  
00:00:00','2019-12-02 00:00:00',4,2,1),(12,'2019-12-02','2019-12-04',320,'2019-12-02  
00:00:00','2019-12-04 00:00:00',8,3,2),(13,'2019-12-06','2019-12-10',100,'2019-12-06  
00:00:00','2019-12-10 00:00:00',2,2,3),(14,'2019-12-08','2019-12-15',108,'2019-12-08  
00:00:00','2019-12-15 00:00:00',3,3,4),(15,'2019-12-10','2019-10-20',400,'2019-12-10  
00:00:00','2019-12-20 00:00:00',5,2,5),(16,'2020-02-10','2020-02-20',400,'2020-01-10  
00:00:00',NULL,9,1,5),(17,'2020-01-10','2020-02-20',220,'2020-01-10  
00:00:00',NULL,5,2,2),(18,'2020-10-25','2020-10-30',400,NULL,NULL,7,3,1),(19,'2020-10  
-25','2020-10-30',320,NULL,NULL,8,4,3);
```

```
/*!40000 ALTER TABLE `reserva` ENABLE KEYS */;
```

```
UNLOCK TABLES;
```

--

-- Table structure for table `uf`

--

DROP TABLE IF EXISTS `uf`;

/\*!40101 SET @saved\_cs\_client = @@character\_set\_client \*/;

/\*!50503 SET character\_set\_client = utf8mb4 \*/;

CREATE TABLE `uf` (

`uf` char(2) NOT NULL,

`descricao` varchar(45) NOT NULL,

PRIMARY KEY (`uf`)

) ENGINE=InnoDB DEFAULT CHARSET=utf8;

/\*!40101 SET character\_set\_client = @saved\_cs\_client \*/;

--

-- Dumping data for table `uf`

--

LOCK TABLES `uf` WRITE;

/\*!40000 ALTER TABLE `uf` DISABLE KEYS \*/;

INSERT INTO `uf` VALUES

('AC','Acre'),('AL','Alagoas'),('AM','Amazonas'),('AP','Amapá'),('BA','Bahia'),('CE','Ceará'),('DF','Distrito Federal'),('ES','Espírito Santo'),('GO','Goiás'),('MA','Maranhão'),('MG','Minas Gerais'),('MS','Mato Grosso do Sul'),('MT','Mato Grosso'),('PA','Pará'),('PB','Paraíba'),('PE','Pernambuco'),('PI','Piauí'),('PR','Paraná'),('RJ','Rio de Janeiro'),('RN','Rio Grande do

```
Norte'),('RO','Rondônia'),('RR','Roraima'),('RS','Rio Grande do Sul'),('SC','Santa
Catarina'),('SE','Sergipe'),('SP','São Paulo'),('TO','Tocantins');
```

```
/*!40000 ALTER TABLE `uf` ENABLE KEYS */;
```

```
UNLOCK TABLES;
```

```
--
```

```
-- Final view structure for view `funcionarios`
```

```
--
```

```
/*!50001 DROP VIEW IF EXISTS `funcionarios`*/;
```

```
/*!50001 SET @saved_cs_client      = @@character_set_client */;
```

```
/*!50001 SET @saved_cs_results     = @@character_set_results */;
```

```
/*!50001 SET @saved_col_connection = @@collation_connection */;
```

```
/*!50001 SET character_set_client  = utf8mb4 */;
```

```
/*!50001 SET character_set_results = utf8mb4 */;
```

```
/*!50001 SET collation_connection  = utf8mb4_0900_ai_ci */;
```

```
/*!50001 CREATE ALGORITHM=UNDEFINED */
```

```
/*!50013 DEFINER=`root`@`localhost` SQL SECURITY DEFINER */
```

```
/*!50001 VIEW `funcionarios` AS select `f`.`codigo` AS `codigo`,`f`.`funcao` AS
`funcao`,`f`.`pessoa_cpf` AS `pessoa_cpf`,`p`.`cpf` AS `cpf`,`p`.`rg` AS `rg`,`p`.`nome`
AS `nome`,`p`.`data_nascimento` AS `data_nascimento`,`p`.`ddd` AS
`ddd`,`p`.`telefone` AS `telefone`,`p`.`endereco_id` AS `endereco_id` from
(`funcionario` `f` join `pessoa` `p` on((`p`.`cpf` = `f`.`pessoa_cpf`))) */;
```

```
/*!50001 SET character_set_client  = @saved_cs_client */;
```

```
/*!50001 SET character_set_results = @saved_cs_results */;
```

```
/*!50001 SET collation_connection  = @saved_col_connection */;
```

/\*!40103 SET TIME\_ZONE=@OLD\_TIME\_ZONE \*/;

/\*!40101 SET SQL\_MODE=@OLD\_SQL\_MODE \*/;

/\*!40014 SET FOREIGN\_KEY\_CHECKS=@OLD\_FOREIGN\_KEY\_CHECKS \*/;

/\*!40014 SET UNIQUE\_CHECKS=@OLD\_UNIQUE\_CHECKS \*/;

/\*!40101 SET CHARACTER\_SET\_CLIENT=@OLD\_CHARACTER\_SET\_CLIENT \*/;

/\*!40101 SET CHARACTER\_SET\_RESULTS=@OLD\_CHARACTER\_SET\_RESULTS \*/;

/\*!40101 SET COLLATION\_CONNECTION=@OLD\_COLLATION\_CONNECTION \*/;

/\*!40111 SET SQL\_NOTES=@OLD\_SQL\_NOTES \*/;

-- Dump completed on 2020-09-25 23:51:38