

PRECISA SER
BOOLEAN PERO
RETORNO

```
1) public static void existeNovetor (int[] u, int tamU, int valor) {  
    for (int i = 0; i < tamU; i++) {  
        if (u[i] == valor) {  
            return true;  
        }  
    }  
    return false;  
}
```

```
public static int uniao (int[] a, int tamA, int[] b, int tamB, int  
    int tamU = 0;  
    for (int i = 0; i < tamA; i++) {  
        if (!existeNovetor (u, tamU, a[i])) {  
            u[tamU] = a[i];  
            tamU++;  
        }  
    }  
    for (int i = 0; i < tamB; i++) {  
        if (!existeNovetor (u, tamU, b[i])) {  
            u[tamU] = b[i];  
            tamU++;  
        }  
    }  
    return tamU;  
}
```

2.0


```

public static void ordenar (int [] v, int n) {
    for (int i = 0; i < n; i++) {
        int chave = v[i];
        int j = i - 1;
        while (j >= 0 && v[j] > chave) {
            v[j+1] = v[j];
            j--;
        }
    }

```

$v[j+1] = \text{chave}$

}

b) 2, 0 (RODA OK)

```

public static int gerarVetorSemRepeticao (int [] v, int tamV,
int [] vsr) {
    int tamVSR = 0;
    for (int i = 0; i < tamV; i++) {
        if (!existeNoVetor(vsr, tamVSR, v[i])) {
            vsr[tamVSR] = v[i];
            tamVSR++;
        }
    }

```

return tamVSR;

}

c) 2, 5 (RODA OK)

}

```

public static void rotacionar (int [] v, int tam, int k) {
    if (k < 0) {
        k = tam + k;
    }

```

```

    for (int j = 0; j < k; j++) {

```

int primeiro = v[0];

```

    for (int i = 0; i < tam - 1; i++) {

```

v[i] = v[i+1];

d) 0, 7

$v[j+1] = \text{primeiro}$ → IRIA RODAR ERRADO

OUROU: 02h:48min.

pois $v[tam-1] = \text{primeiro}$