

IMPERATIVE PROGRAMMING HT2018

SHEET 6

GABRIEL MOISE

Question 1

```
/*
```

We can replace each bucket in our hash table with a binary search tree, which will be balanced if we add another hash function which is completely independent from the initial one. Thus, we can maintain a balanced binary search tree, so we can add data in $O(\log_2(N))$ time and also search in $O(\log_2(N))$. We should maintain the property $\text{hash2}(\text{leftchild}) < \text{hash2}(\text{parent}) < \text{hash2}(\text{rightchild})$ in every binary search tree we create.

```
*/
```

Question 2

```
/*
```

Each item has a probability of $1/N$ to go in any specific bucket because their hash functions are uniform on $[0..N)$. Therefore, the distribution of the number of items that go into a specific bucket is $\text{Bin}(n, 1/N)$, and the mean of this is n/N . For an unsuccessful search, we compare the item with every item from the bucket, so the distribution of the number of comparisons for an unsuccessful search is the same, with the expected number of comparisons n/N . For a successful search, let's suppose that we have k keys to retrieve and the number of operations needed to retrieve all of them is $1 + 2 + \dots + k = k(k+1)/2$. So, if the number of items is X , which is a random variable, the expectation for this is: $E = \sum_k k(k+1)/2 \cdot P(X = k)$. Since X has binomial distribution $\text{Bin}(n, 1/N)$, we get: $E = 1/2 \cdot (E(X^2) + E(X)) = n/N \cdot ((n-1)/2 \cdot N - 1)$. So, if we want to get the mean cost per key retrieved we divide by n and to obtain the total expected cost we multiply by N to get: $E = (n-1)/2 \cdot N - 1$.

```
*/
```

Question 3

```
// A hash table, representing a bag of words; i.e., for each word we record how many times the word is stored.
```

```
object ArrayBag{
```

```
  private class Node (val word : String, var count : Int)
```

```
}
```

```
// DTI : table(hash(word)) = Node(word,count) if it was null when we added the word, or table(pos) = Node(word,count) where pos is the first null position found starting from hash(word) and wrapping around at MAX && there are size_ words in the table and size_ <= MAX. So, basically we have between hash(word) and pos all places non-null. Also, a node containing word can only appear once in table!
```

```
class ArrayBag{
```

```
  // The hash function we will use
```

```
  private def hash(word: String) : Int = {
```

```
    def f(e: Int, c: Char) = (e*41 + c.toInt) % MAX
```

```
    word.foldLeft(1)(f)
```

```
}
```

```
private val MAX = 100
```

```
private var size_ = 0 // # distinct words stored
```

```
private val table = new Array[ArrayBag.Node](MAX)
```

// Given a word and h = hash(word), this function finds the index in table where word is or if it is not, the first empty place to put the word in (if we find an empty space, then after it there cannot be any appearance of the word we are looking for as that word would have been placed in the first empty space found the previous time). We can also find a place where table(n).count = 0, meaning there was a number of appearances of a specific string which got deleted until count became 0, so we can reuse that space.

```
private def find (word: String, h : Int) : Int =
```

```
{  
    var n = h  
  
    while ((table(n) != null) && (table(n).word != word) && (table(n).count != 0)) n = (n+1) % MAX  
  
    n  
}
```

```
/** Add an occurrence of word to the table */
```

```
def add(word: String) = {  
    val h = hash(word)  
    var n = find(word, h)  
  
    if ((table(n) == null) || (table(n).count == 0)) table(n) = new ArrayBag.Node (word, 1) // word was not in table or got deleted  
    else table(n).count += 1 // word was already in table  
  
    size_ += 1  
}
```

```
/** The count stored for a particular word */
```

```
def count(word: String) : Int = {  
    val h = hash(word)  
    val n = find(word, h)  
  
    if (table(n) != null) return table(n).count  
    else return 0  
}
```

```
// return the size
```

```
def size = size_
```

```
/** Deletes word if it is in the bag and returns true if the word was found in the bag and false otherwise*/
```

```
def delete(word: String) : Boolean=  
{
```

```

val h = hash(word)

var n = find(word,h)

if ((table(n) != null) && (table(n).count > 0))
{
    table(n).count -= 1

    return true
}

else return false

}

}

```

Question 4

object Question4

```

{

case class Tree (var word: String, var left: Tree, var right: Tree)

```

// (a)

```
def printTreeRec (t : Tree, height : Int) : Unit=
```

```

{

    var str = ". " * height

    if (t != null)

    {

        println(str + t.word)

        printTreeRec(t.left,height+1)

        printTreeRec(t.right,height+1)

    }

    else println(str + "null")

}

```

// (b)

// Implementing a Stack with linked lists:

object Stack // I received a warning message when I tried to use the Stack from scala.collection, so I created one for myself

```

{

    class Node (var tree : Tree, var height: Int, var next : Node)

}

class Stack

{

```

```
var stack = new Stack.Node (null, 0, null)
```

```
// we add at the front of the stack
```

```
// Post : stack = (t,h) : stack_0
```

```
def push (t : Tree, h: Int) =
```

```
{  
    var n1 = new Stack.Node(t, h, stack.next)  
    stack.next = n1  
}
```

```
// We get an element from the stack from the front and we delete it from the stack
```

```
// Pre : stack is not empty
```

```
// Post : stack = tail(stack_0) && and returns head(stack_0)
```

```
def pop : (Tree,Int) =
```

```
{  
    require(stack.next != null)  
    var (t,h) = (stack.next.tree, stack.next.height)  
    stack.next = stack.next.next  
    return (t,h)  
}
```

```
// Checks if the stack is empty or not
```

```
def isEmpty : Boolean = (stack.next == null)
```

```
}
```

```
def printTreeStack (t: Tree, height : Int) : Unit =
```

```
{  
    var st = new Stack  
    st.push(t, 0)  
    while (st.isEmpty == false)  
    {  
        var (t,h) = st.pop  
        if (t == null)  
        {  
            var str = ". " * h  
            println(str + "null")  
        }  
    }
```

```

else
{
    st.push(t.right, h+1) // first we print the left and then the right subtree
    st.push(t.left, h+1)
    var str = ". " * h
    println(str + t.word)
}
}
}

def main (args: Array[String]) =
{
    var tr = Tree("three", Tree("four", Tree("five",null,null), Tree("six", Tree("seven",
        Tree("one",null,null), null), null)), Tree("two",null,null))
    printTreeStack(tr,0)
}
}

```

Question 5

object Question5

```

{
    case class Tree (var word : String, var left : Tree, var right : Tree)

    /** Function that destructively flips the tree t, exchanging left and right throughout */
    // tree.word remains the same, (t.left,t.right) becomes (t.right,t.left) and we recursively flip the two subtrees
    def flip(t: Tree) : Unit =
    {
        if (t != null)
        {
            var leftTree = t.left
            var rightTree = t.right
            t.right = leftTree
            t.left = rightTree
            flip (t.left)
            flip (t.right)
        }
    }
}

```

```
}
```

Question 6

```
object BinaryTreeBag
```

```
{
```

```
  private class Tree(var word: String, var count: Int, var left: Tree, var right: Tree)
```

// I implemented the Stack as for question 4 too, because I get an error when I tried to use the scala.collection.mutable.Stack: warning: class Stack in package mutable is deprecated (since 2.12.0): Stack is an inelegant and potentially poorly-performing wrapper around List. Use a List assigned to a var instead.

```
  private class Stack
```

```
  {
```

```
    case class Node (var tree : BinaryTreeBag.Tree, var next : Node)
```

```
    var stack = new Node (null, null)
```

```
    def push (t : BinaryTreeBag.Tree) =
```

```
    {
```

```
      var n1 = new Node(t,stack.next)
```

```
      stack.next = n1
```

```
    }
```

```
    def pop : BinaryTreeBag.Tree =
```

```
    {
```

```
      require(stack.next != null)
```

```
      var t = stack.next.tree
```

```
      stack.next = stack.next.next
```

```
      return t
```

```
    }
```

```
    def isEmpty : Boolean = (stack.next == null)
```

```
  }
```

```
}
```

```
class BinaryTreeBag
```

```
{
```

```
  private type Tree = BinaryTreeBag.Tree
```

```
  private def Tree(word: String, count: Int, left: Tree, right: Tree) = new BinaryTreeBag.Tree(word, count, left, right)
```

```
private var root : Tree = null
```

```
// (a) Recursive definition for the function size, which adds the count fields of all the nodes from the tree
```

```
private def sizeRec(t: Tree) : Int =  
  
  {  
  
    if (t != null) return t.count + sizeRec(t.left) + sizeRec(t.right)  
    else return 0  
  
  }
```

```
// (b) Iterative version of the function size, using a stack to keep track of the parts of the tree still to be considered
```

```
private def sizelter (t: Tree) : Int =  
  
  {  
  
    var size = 0  
  
    val stack = new BinaryTreeBag.Stack  
  
    stack.push(t)  
  
    // Invariant : We still need to add the count fields of the current node and of its nodes from the left and right subtrees and of the right child (if  
the current node is the left child of a node)  
  
    while(stack.isEmpty == false)  
  
    {  
  
      var tr = stack.pop  
  
      if (tr != null) {size += tr.count; stack.push(tr.left); stack.push(tr.right)}  
  
      else {}  
  
    }  
  
    size  
  
  }  
  
}
```

Question 7

```
object BinaryTreeBag  
  
{  
  
  private class Tree(var word: String, var count: Int, var left: Tree, var right: Tree)  
  
  
  private class Stack  
  
  {  
  
    case class Node (var tree : BinaryTreeBag.Tree, var depth : Int, var next : Node)  
  
  
    var stack = new Node (null, 0, null)
```

```
def push (t : BinaryTreeBag.Tree, d: Int) =  
  {  
    var n1 = new Node(t,d,stack.next)  
    stack.next = n1  
  }
```

```
def pop : (BinaryTreeBag.Tree, Int) =  
  {  
    require(stack.next != null)  
    var (t,d) = (stack.next.tree,stack.next.depth)  
    stack.next = stack.next.next  
    return (t,d)  
  }
```

```
def isEmpty : Boolean = (stack.next == null)  
}  
}
```

```
class BinaryTreeBag
```

```
{  
  private type Tree = BinaryTreeBag.Tree  
  private def Tree(word: String, count: Int, left: Tree, right: Tree) = new BinaryTreeBag.Tree(word, count, left, right)  
  
  private var root : Tree = null
```

```
// We want to calculate the minimum and the maximum depth of the tree, at any given point
```

```
// (a) Using a recursive function
```

```
private def depthRec (t: Tree) : (Int,Int) =  
  {  
    if (t == null) return (0,0)  
    else  
    {  
      var (minLeft,maxLeft) = depthRec(t.left)
```



```

    var (minRight,maxRight) = depthRec(t.right)

    var min = 0

    if (minLeft < minRight) min = minLeft
        else min = minRight

    var max = 0

    if (maxLeft < maxRight) max = maxRight
        else max = maxLeft

    return (min+1,max+1)

}

}

```

// (b) Using an iterative function, and making use of a Stack

```

private def depthIter (t: Tree) : (Int,Int) =
{
    var min = 10000000

    var max = 0

    val stack = new BinaryTreeBag.Stack

    stack.push(t,0)

    while (stack.isEmpty == false)
    {
        var (tr,depth) = stack.pop

        if (tr == null) //we reached a leaf
        {
            if (depth < min) min = depth

            if (depth > max) max = depth
        }

        else {stack.push(t.left,depth+1); stack.push(t.right,depth+1)}
    }

    return (min,max)
}
}

```

Question 8

```

class AnagramsDictionary(fname: String){

    /** An array holding the pairs of the order permutations with the words*/

```

```
var words = new Array [(String,String)] (120000) // the maximum number of words from knuth_words
```

```
var count = 0
```

```
/** Initialise anagrammatical dictionary from fname */
```

```
private def initDict(fname: String) = {
```

```
    val allWords = scala.io.Source.fromFile(fname).getLines
```

```
    def include(w:String) = w.forall(_isLower)
```

```
    for(w <- allWords; if include(w)) {words(count) = (w.sorted,w) ; count += 1}
```

```
}
```

```
initDict(fname)
```

```
var anagrams = new Array [(String,String)] (count) // we create a new array with no empty cells so that we can sort it
```

```
for (i<-0 until count) anagrams(i) = words(i)
```

```
// we sort the anagrammatical dictionary
```

```
anagrams = anagrams.sorted
```

```
}
```

```
object Question8
```

```
{
```

```
    var dict = new Dictionary("knuth_words.txt")
```

```
// (a) The program is very slow on long strings because the time complexity is  $O(n^n)$  and the memory  $O(n!)$  for the list
```

```
class List
```

```
{
```

```
    case class Node (var word : String, var next : Node)
```

```
    var list = new Node ("?", null)
```

```
    var end = list
```

```
// We add a new node at the end of the list
```

```
def add (word : String) =
```

```

{
    var n1 = new Node(word,null)

    end.next = n1

    end = n1
}

// We get a word from the head of the list, deleting its node
// Pre : the list is not empty
def get : String =
{
    var word = list.next.word

    if (list.next == end) {list.next = null; end = list} // we only change end if the list consisted of one element which was removed

    else list.next = list.next.next

    word
}

override def toString : String =
{
    var str = "{"

    var current = list.next

    while (current != null)
    {
        if (current.next != null) str = str + current.word + ", "

        else str = str+current.word

        current = current.next
    }

    str = str + "}"

    str
}

}

def permutations (word : String) : List =
{
    // In perm, we start with the last letter of the word and then we add a new letter to all the words we created so far (in all the positions) of
    length ln-1, which will be 2 at the first while-loop step, and add them at the end. Then we repeat until we are left with a list consisting of all the
    permutations of length word.length

    var N = word.length

    var perm = new List

```

```

var pos = N-1 // the current position of the letter we add to all the words in perm

perm.add(word.drop(N-1))

var ln = 1

// Invariant : perm contains all the possible permutations of word[(N-ln)..N]

while (ln < N)

{

    ln += 1

    var ch = word(N-ln)

    // We get nodes from the list, we put ch in each position to form new sub-permutations and we add them to perm, until we get to a node with
length ln (one that was added during this while iteration)

    while (perm.list.next.word.length == ln - 1)

    {

        var subword = perm.get

        // We insert ch in every position (we form ln words)

        for (i<-0 until ln) {var newWord = subword.take(i) + ch + subword.drop(i); perm.add(newWord)}

    }

}

// Now we have in perm all the permutations of the initial word

perm

}

```

// Given a list of words, it returns the list containing all the words from the list that are in the dictionary

```

def spell_check (perm : List) : List =

{

    var wordsDict = new List // the list that will the correct words (from our dictionary)

    var current = perm.list.next

    while (current != null)

    {

        if (dict.isWord(current.word)) wordsDict.add(current.word)

        current = current.next

    }

    wordsDict

}

```

// (b)

```

var anagramsDict = new AnagramsDictionary("knuth_words.txt")

```

```
val sizeDict = anagramsDict.anagrams.size
```

```
// We search the sorted permutation of the given word in the array (we consider a to be the array consisting of only the first entry of each tuple from our initial array)
```

```
def search(x: String) : Int = {  
  // invariant I: a[0..i) < x <= a[j..sizeDict) && 0 <= i <= j <= sizeDict  
  var i = 0; var j = sizeDict  
  while(i < j){  
    val m = (i+j)/2 // i <= m < j  
    if(anagramsDict.anagrams(m)._1 < x) i = m+1 else j = m  
  }  
  // I && i = j, so a[0..i) < x <= a[i..N)  
  i  
}
```

```
val value = 18 // by searching for anagrams in the anagramDict.anagrams array we found the the max length is 18, so we print those with length 18
```

```
def main (args: Array[String]) =  
  {  
    val word = scala.io.StdIn.readLine  
    // (a)  
    println(spell_check(permutations(word)).toString)  
  
    // (b)  
    var pos = search(word.sorted)  
    print("{ "+ anagramsDict.anagrams(pos)._2 + " ", "  
    // From pos+1 we search for the anagrams of word  
    var j = pos + 1  
    while (anagramsDict.anagrams(j)._1 == anagramsDict.anagrams(pos)._1)  
    {  
      if (anagramsDict.anagrams(j+1)._1 == anagramsDict.anagrams(pos)._1) print(anagramsDict.anagrams(j)._2 + " ", "  
      else print(anagramsDict.anagrams(j)._2)  
      j = j + 1  
    }  
    println("")
```

```

/* Finding the longest anagrams from the knuth dictionary:

var i = 0

while (i < sizeDict)
{
    if ((i < sizeDict - 1) && (anagramsDict.anagrams(i)._1 == anagramsDict.anagrams(i+1)._1))
    {
        if (anagramsDict.anagrams(i)._2.size == value) print(anagramsDict.anagrams(i)._2+" ")
        while ((i < sizeDict - 1) && (anagramsDict.anagrams(i)._1 == anagramsDict.anagrams(i+1)._1))
        {
            if (anagramsDict.anagrams(i)._2.size == value) print(anagramsDict.anagrams(i+1)._2+" ")
            i = i + 1
        }
        if (anagramsDict.anagrams(i)._2.size == value) println()
    }
    else i = i + 1
}

*/

// It turns out that the anagrams of length 18 from knuth_words are pathophysiological and physiopathological.
// It also turns out that the longest set of anagrams is:
// {least, setal, slate, stale, steal, stela, tales, teals, tesla}
// which has 9 anagrams.

}
}

```