


University of Padua

DEPARTMENT OF MATHEMATICS “TULLIO LEVI-CIVITA”

MASTER DEGREE IN COMPUTER SCIENCE



**Designing an accessibility learning toolkit: bridging
the gap between guidelines and implementation**

Master's Thesis

Supervisor

Prof. Ombretta Gaggi

Candidate

Gabriel Rovesti

ID Number: 2103389

ACADEMIC YEAR 2024-2025

© Gabriel Rovesti, July 2025. All rights reserved. Master's Thesis: "*Designing an accessibility learning toolkit: bridging the gap between guidelines and implementation*", University of Padua, Department of Mathematics "Tullio Levi-Civita".

“We don’t read and write poetry because it’s cute. We read and write poetry because we are members of the human race. And the human race is filled with passion. And medicine, law, business, engineering, these are noble pursuits and necessary to sustain life. But poetry, beauty, romance, love, these are what we stay alive for.”

— N.H. Kleinbaum, Dead Poets Society

Acknowledgements

First and foremost, I would like to express my gratitude to Prof. Gaggi, given her support throughout two paths of thesis, both in bachelor and master degrees, for valuable knowledge and support throughout these academic years, both humanly and academically.

I would like to thank my mom, the only person who supported me practically throughout these years and gave me many life lessons, maybe not in the right way, but her love was always present for me. For the same reason, my life has been very dense of things, but I promised myself I would have always been able to make it. And I did it always on my own, in ways I would have never imagined since I had no guidance, but I was always everyone guidance. Not arrogance, simply human nature. I hope after this huge step to conquer the long awaited peace of spirit and soul.

A special thank you to the few real friends I have (particularly Matilde, Andrea and Antonella), because they helped me do many things up until now and I would not live a day without them.

Padova, July 2025

Gabriel Rovesti

Abstract

This thesis presents a systematic comparative analysis of accessibility implementation approaches in mobile application development frameworks, specifically React Native and Flutter. Building upon previous research focused on Flutter's accessibility capabilities, this study extends the investigation to provide a comprehensive examination of how both frameworks enable developers to create accessible mobile user interfaces.

The research methodology encompasses the development of *AccessibleHub*—an educational toolkit application that serves as both a research vehicle and practical resource for developers. Through this implementation, the study identifies specific patterns, similarities, differences, and potential improvements in accessibility implementation between the frameworks. The analysis examines implementation complexity, developer experience, and compliance with Web Content Accessibility Guidelines (WCAG) 2.2 standards, providing quantitative metrics for framework comparison.

A core contribution of this work is the translation of abstract accessibility guidelines into concrete implementation patterns, bridging the gap between theoretical requirements and practical code. The research demonstrates that while both frameworks can achieve equivalent accessibility outcomes, they differ significantly in their architectural approaches and implementation overhead. React Native employs a property-based model that typically requires less code but offers less explicit semantic control, while Flutter's widget-based semantic system provides more granular accessibility management at the cost of increased implementation complexity.

Accessibility represents not merely a compliance requirement but a fundamental aspect of both user experience and developer mindset. By expanding product usability across diverse user populations regardless of capabilities, properly implemented accessibility features ensure seamless interaction across components and devices. This research provides evidence-based guidance for framework selection and implementation strategies, contributing to the advancement of accessible mobile application development as technology continues to evolve.

Table of contents

List of listings	xvi
Acronyms and abbreviations	xix
Glossary	xx
1 Introduction	1
1.1 Mobile accessibility: context & foundations	1
1.2 Thesis structure	6
2 Mobile accessibility: guidelines, standards and related works	8
2.1 Accessibility legislative frameworks	8
2.2 Accessibility standard guidelines	10
2.2.1 Web Content Accessibility Guidelines (WCAG)	11
2.2.2 Mobile Content Accessibility Guidelines (MCAG)	12
2.2.3 Mobile-specific accessibility considerations	12
2.3 State of research and literature review	13
2.3.1 Users and developers accessibility studies	14
2.3.2 User categories and development approaches	16
2.3.3 Testing methodologies and evaluation frameworks	17
2.3.4 Framework implementation approaches	18
2.3.5 Accessibility tools and extensions	19
3 AccessibleHub: Transforming mobile accessibility guidelines into code	22
3.1 Introduction	22
3.1.1 Challenges in implementing accessibility guidelines	22

TABLE OF CONTENTS

3.1.2	The need for practical developer education	23
3.1.3	Research objectives and methodology	26
3.2	React Native Overview	27
3.2.1	Core architecture and features	28
3.2.2	Accessibility in React Native	29
3.2.3	Advantages and developer benefits	30
3.2.4	Differences from native iOS/Android and web development	31
3.3	AccessibleHub: An Interactive Learning Toolkit	31
3.3.1	Core architecture and design principles	31
3.3.2	Educational framework design	34
3.3.3	From guidelines to implementation: a screen-based methodology	57
3.4	Accessibility implementation guidelines	58
3.4.1	Home screen	58
3.4.1.1	Component inventory and WCAG/MCAG mapping	59
3.4.1.2	Formal metrics calculation methodology	62
3.4.1.2.1	Component accessibility score	67
3.4.1.2.2	WCAG compliance score	68
3.4.1.2.3	Screen reader testing score	70
3.4.1.2.4	Overall accessibility score	72
3.4.1.3	Technical implementation analysis	73
3.4.1.4	Screen reader support analysis	75
3.4.1.5	Implementation overhead analysis	77
3.4.1.6	WCAG conformance by principle	78
3.4.1.7	Mobile-specific considerations	80
3.4.1.8	Beyond WCAG: metrics-driven accessibility guidelines	81
3.4.2	Accessible components main screen	82
3.4.2.1	Component inventory and WCAG/MCAG mapping	83
3.4.2.2	Navigation and orientation analysis	86
3.4.2.2.1	Breadcrumb implementation	86

TABLE OF CONTENTS

3.4.2.2.2	Drawer navigation	88
3.4.2.2.3	Component cards	89
3.4.2.3	Technical implementation analysis	89
3.4.2.4	Screen reader support analysis	91
3.4.2.5	Implementation overhead analysis	94
3.4.2.6	WCAG conformance by principle	95
3.4.2.7	Mobile-specific considerations	96
3.4.2.8	Breadcrumb implementation analysis	97
3.4.2.8.1	Implementation considerations	98
3.4.2.9	Beyond WCAG: component categorization guidelines	98
3.4.3	Accessible components section summary	99
3.4.3.1	Implementation overhead analysis	100
3.4.3.2	Implementation overhead comparison	102
3.4.4	Best practices section summary	103
3.4.4.1	Implementation overhead analysis	103
3.4.4.2	WCAG criteria implementation	104
3.4.4.3	Screen reader compatibility analysis	106
3.4.4.4	Implementation techniques comparison	107
3.4.5	Best practices main screen summary	108
3.4.5.1	Implementation overhead analysis	108
3.4.5.2	WCAG criteria implementation	109
3.4.5.3	Screen reader compatibility analysis	111
3.4.5.4	Mobile-specific considerations	112
3.4.6	Accessibility tools screen summary	113
3.4.6.1	Implementation overhead analysis	113
3.4.6.2	WCAG criteria implementation	114
3.4.6.3	Screen reader support analysis	116
3.4.6.4	Mobile-specific implementation considerations	117
3.4.7	Instruction and community screen summary	118

TABLE OF CONTENTS

3.4.7.1	Implementation overhead analysis	118
3.4.7.2	WCAG criteria implementation	119
3.4.7.3	Screen reader compatibility analysis	121
3.4.7.4	Mobile-specific accessibility considerations	122
3.4.8	Settings screen summary	123
3.4.8.1	Implementation overhead analysis	123
3.4.8.2	WCAG criteria implementation	124
3.4.8.3	Screen reader compatibility analysis	125
3.4.8.4	Mobile-specific accessibility considerations	126
3.4.8.5	Self-adapting interface principles	126
4	Accessibility analysis: framework comparison and implementation patterns	128
4.1	Research methodology	128
4.1.1	Research questions and objectives	129
4.1.2	Testing approach and criteria	129
4.1.3	Evaluation metrics and quantification methods	130
4.1.4	Metric calculation methodologies	131
4.1.4.1	Component Accessibility Score methodology	131
4.1.4.2	Implementation Overhead methodology	132
4.1.4.3	Complexity Impact Factor methodology	133
4.1.4.4	Screen Reader Support Score methodology	135
4.1.4.5	WCAG Compliance Ratio methodology	136
4.1.4.6	Developer Time Estimation methodology	137
4.1.5	Component selection methodology	137
4.2	Flutter overview	141
4.2.1	Core architecture and widget system	141
4.2.2	Accessibility in Flutter	142
4.2.3	Development workflow and advantages	144
4.2.4	Platform integration and accessibility capabilities	145

TABLE OF CONTENTS

4.3	Framework architecture and accessibility approach	145
4.3.1	Flutter accessibility model	146
4.3.2	Architectural differences affecting implementation	147
4.3.2.1	Mental model and developer workflow	147
4.3.2.2	Code organization and implementation overhead	147
4.3.2.3	Platform integration approach	148
4.3.3	Framework architecture comparison	149
4.3.3.1	Mental model and developer workflow	149
4.3.3.2	Code organization and implementation overhead	150
4.3.3.3	Platform integration approach	150
4.4	Framework comparison screen: a detailed analysis	150
4.4.0.1	Component inventory and WCAG/MCAG mapping	152
4.4.0.2	Formal methodology system implementation	155
4.4.0.3	Academic reference implementation	157
4.4.0.4	Framework data structure	160
4.4.0.5	Implementation complexity analysis	162
4.4.0.6	Specific accessibility feature comparison	165
4.4.0.7	Modal dialog accessibility implementation	167
4.4.0.8	Screen reader support analysis	169
4.4.0.9	Implementation overhead analysis	171
4.4.0.10	WCAG conformance by principle	172
4.4.0.11	Mobile-specific considerations	174
4.4.0.12	Beyond WCAG: evidence-based accessibility evaluation guidelines	175
4.4.0.13	Screen reader support comparison methodology	176
4.4.0.14	Implementation complexity calculation methodology	178
4.4.0.15	Feature-specific implementation comparison	179
4.5	Accessibility implementation patterns	180
4.5.1	Property-based vs widget-based implementation patterns	180

TABLE OF CONTENTS

4.5.2	State communication patterns	183
4.5.3	Navigation order and focus management patterns	185
4.5.4	Dynamic content announcement patterns	188
4.5.5	Hiding elements from accessibility tree	192
4.5.6	Interactive elements	193
4.5.6.1	Buttons and touchable elements	193
4.5.6.2	Form controls	196
4.5.6.3	Custom gesture handlers	199
4.5.7	Navigation components	202
4.5.7.1	Navigation hierarchy	202
4.5.7.2	Focus management	204
4.6	Quantitative comparison of implementation overhead	206
4.6.1	Lines of code analysis	206
4.6.2	Complexity factor calculation	207
4.6.3	Screen reader compatibility metrics	208
4.7	Framework-specific optimization patterns	209
4.7.1	React Native optimization techniques	210
4.7.2	Flutter optimization techniques	211
4.7.3	Cross-framework best practices	214
5	Conclusions and future research	216
5.1	Results and discussion	216
5.1.1	Default accessibility comparison	218
5.1.2	Implementation feasibility analysis	218
5.1.3	Development effort evaluation	219
5.1.4	Mitigating implementation overhead	220
5.1.5	Practical guidelines for framework selection	223
5.2	Implications for mobile developers	224
5.3	Conclusion and critical thoughts	224
5.4	Limitations of the research	224

TABLE OF CONTENTS

5.5 Directions for future research	224
Bibliography	225

List of figures

3.1	React Native logo	28
3.2	The Home screen of <i>AccessibleHub</i>	35
3.3	The Components screen of <i>AccessibleHub</i>	36
3.4	Side-by-side view of the two Button and Touchables screen parts	37
3.5	Side-by-side view of the two Form screen parts	38
3.6	Side-by-side view of the two Media screen parts	39
3.7	Side-by-side view of the two Dialog screen parts	40
3.8	Side-by-side view of the first two Advanced screen parts	41
3.9	Side-by-side view of the second two Advanced screen parts	42
3.10	The Best Practices screen of <i>AccessibleHub</i>	43
3.11	Side-by-side view of the Gestures Tutorial screen sections	44
3.12	Side-by-side view of the Semantic Structure screen sections	45
3.13	Side-by-side view of the Logical navigation screen sections	46
3.14	Side-by-side view of the Screen reader support screen sections	47
3.15	Side-by-side view of the WCAG Guidelines screen sections	49
3.16	The Framework comparison screen of <i>AccessibleHub</i>	50
3.17	The Tools screen of <i>AccessibleHub</i>	51
3.18	The Settings screen of <i>AccessibleHub</i>	53
3.19	Settings screen with different accessibility modes enabled	54
3.20	Visual notifications when accessibility settings are toggled	55
3.21	The Instruction and community screen of <i>AccessibleHub</i>	56
3.22	Side-by-side view of the two Home sections, with metrics and navigation buttons	59
3.23	Modal dialogs showing WCAG compliance metrics	63
3.24	Modal dialogs showing component accessibility metrics	64

3.25	Modal dialogs showing screen reader testing metrics	65
3.26	Modal dialogs showing methodology and references	66
3.27	Side-by-side view of the Components screen sections, showing component categories	83
3.28	Drawer navigation showing breadcrumb implementation in header	87
4.1	Flutter logo	141
4.2	Framework comparison screen showing overview information for both frameworks	152
4.3	Methodology tabs of Framework comparison screen	156
4.4	Academic references implementation with formal citation structure	158
4.5	References tab showing formatted citations with complete bibliographic information	160
4.6	Framework selection interface showing structured framework data	161
4.7	Implementation complexity analysis with detailed metrics	163
4.8	Implementation details showing feature-level comparison and code examples	165
4.9	Language modals of Framework comparison screen	166
4.10	Modal dialogs for the Implementation Tab	168
4.11	Screen reader support comparison methodology and calculation approach	177
4.12	Formal calculation methodology for implementation complexity	178

List of tables

3.1	Home screen component-criteria mapping	60
3.2	Home screen screen reader testing results	75
3.3	Accessibility implementation overhead	77

LIST OF TABLES

3.4	WCAG compliance analysis by principle	78
3.5	Components screen component-criteria mapping	84
3.6	Components screen screen reader testing results	92
3.7	Components screen accessibility implementation overhead	94
3.8	Components screen WCAG compliance analysis by principle	95
3.9	Buttons screen accessibility implementation overhead	100
3.10	WCAG criteria implementation by component type	101
3.11	Legend for WCAG criteria implementation colors	101
3.12	Accessibility implementation overhead by component type	102
3.13	Best practices screens accessibility implementation overhead	104
3.14	WCAG criteria implementation by best practices screen type	105
3.15	Legend for WCAG criteria implementation colors	106
3.16	Best practices screens screen reader testing highlights	106
3.17	Implementation techniques comparison across best practices screens	107
3.18	Best practices screen accessibility implementation overhead	109
3.19	Best practices screen WCAG implementation by conformance level	110
3.20	Legend for WCAG criteria implementation colors	110
3.21	Best practices screen screen reader testing highlights	111
3.22	Tools screen accessibility implementation overhead	113
3.23	Tools screen WCAG implementation by conformance level	115
3.24	Legend for WCAG criteria implementation colors	115
3.25	Tools screen screen reader testing highlights	116
3.26	Tools screen mobile-specific implementation considerations	117
3.27	Instruction and community screen accessibility implementation overhead	119
3.28	Instruction and community screen WCAG implementation by principle	120
3.29	Legend for WCAG criteria implementation colors	120
3.30	Instruction and community screen screen reader testing highlights	121
3.31	Settings screen accessibility implementation overhead	123
3.32	Settings screen WCAG implementation by principle	124

3.33	Legend for WCAG criteria implementation colors	124
3.34	Settings screen screen reader testing highlights	125
4.1	Accessibility implementation metrics	131
4.2	Component accessibility comparison matrix	139
4.3	Implementation overhead analysis	140
4.4	WCAG compliance by framework	141
4.5	Implementation overhead analysis	148
4.6	Framework comparison screen component-criteria mapping	153
4.7	Framework comparison screen screen reader testing results	169
4.8	Framework comparison screen accessibility implementation overhead	172
4.9	Framework comparison screen WCAG compliance analysis by principle	173
4.10	Pattern implementation overhead comparison	183
4.11	State communication pattern comparison	185
4.12	Navigation order pattern comparison	188
4.13	Dynamic announcement pattern comparison	191
4.14	Element hiding pattern comparison	193
5.1	Consolidated framework accessibility comparison	217
5.2	Implementation overhead trade-offs overview	220
5.3	Framework selection decision matrix	224

List of listings

3.1	Component registry and calculation	68
3.2	WCAG criteria tracking and calculation	70
3.3	Screen reader testing results and calculation	72
3.4	Annotated code sample demonstrating Home screen accessibility properties	74
3.5	Breadcrumb implementation with accessibility properties	88

LIST OF LISTINGS

3.6 Annotated code sample demonstrating Components screen accessibility properties	90
4.1 Basic Semantics implementation in Flutter	144
4.2 Using the SemanticsDebugger in Flutter	144
4.3 Flutter Semantics widget system	146
4.4 Property-based accessibility pattern in React Native	149
4.5 Widget-based accessibility pattern in Flutter	149
4.6 Property-based accessibility pattern in React Native	181
4.7 Widget-based accessibility pattern in Flutter	182
4.8 State communication in React Native	183
4.9 State communication in Flutter	184
4.10 Enhanced state communication in Flutter	184
4.11 Navigation order in React Native	186
4.12 Navigation order in Flutter	187
4.13 Dynamic content announcement in React Native	189
4.14 Dynamic content announcement in Flutter	190
4.15 Live region announcement in React Native	190
4.16 Live region announcement in Flutter	191
4.17 Hiding elements in React Native	192
4.18 Hiding elements in Flutter	192
4.19 Accessible button in React Native	194
4.20 Accessible button in Flutter	194
4.21 Enhanced button accessibility in Flutter	194
4.22 Budai's Flutter implementation of accessible buttons	195
4.23 <i>AccessibleHub</i> 's React Native implementation of accessible buttons	195
4.24 Accessible form input in React Native	196
4.25 Accessible form input in Flutter	197
4.26 Form implementation in <i>AccessibleHub</i> 's React Native code	197
4.27 Form implementation in Budai's Flutter code	198

LIST OF LISTINGS

4.28 Selection controls in <i>AccessibleHub</i>	198
4.29 Selection controls in Budai’s Flutter code	199
4.30 Accessible gesture handler in React Native	200
4.31 Accessible gesture handler in Flutter	200
4.32 Gesture handling in Budai’s Flutter implementation	201
4.33 Gesture handling in <i>AccessibleHub</i> ’s React Native implementation	202
4.34 Navigation hierarchy in React Native	203
4.35 Navigation hierarchy in Flutter	203
4.36 Focus management in React Native	204
4.37 Focus management in Flutter	205
4.38 Property composition in React Native	210
4.39 Component abstraction in React Native	211
4.40 Context-based accessibility in React Native	211
4.41 Optimized accessibility pattern in <i>AccessibleHub</i>	212
4.42 Custom semantic widget in Flutter	213
4.43 SemanticsService usage in Flutter	213
4.44 Theme-based semantics in Flutter	214

Acronyms and abbreviations

API Application Programming Interface. [i](#), [51](#)

ARIA Accessible Rich Internet Applications. [i](#), [19](#)

LOC Lines of Code. [i](#), [133](#)

MCAG Mobile Content Accessibility Guidelines. [i](#), [12](#), [34](#), [57](#)

UI User Interface. [i](#), [28](#), [32](#), [57](#)

UX User Experience. [i](#)

W3C World Wide Web Consortium. [i](#), [10](#)

WCAG Web Content Accessibility Guidelines. [i](#), [12](#), [22](#), [24](#), [25](#), [34](#), [57](#)

Glossary

Application Programming Interface An Application Programming Interface (API) is a set of protocols, routines, and tools for building software applications. It specifies how software components should interact, allowing different software systems to communicate with each other. APIs define the methods and data structures that developers can use to interact with a system, service, or library without needing to understand the underlying implementation. They serve as a contract between different software components, enabling developers to integrate different systems, access web-based services, and create more complex and interconnected software solutions. [i](#), [23](#), [25](#), [31](#)

ARIA Accessible Rich Internet Applications (ARIA) is a set of attributes that define ways to make web content and web applications more accessible to people with disabilities. ARIA roles, states, and properties help assistive technologies understand and interact with dynamic content and complex user interface controls. [i](#), [31](#), [44](#)

Flutter Flutter is an open-source UI software development kit created by Google, designed for building natively compiled applications for mobile, web, and desktop platforms from a single codebase. Launched in 2017, Flutter uses the Dart programming language and provides a comprehensive framework for creating high-performance, visually attractive applications with a focus on smooth, responsive user interfaces. Unlike traditional cross-platform frameworks that use web view rendering, Flutter compiles directly to native code, enabling near-native performance. Its key features include a rich set of pre-designed widgets, hot reload for rapid development, extensive customization capabilities, and a robust ecosystem that supports complex application development across multiple platforms. [i](#), [22](#)

Gray Literature Review A structured method of collecting and analyzing non-traditional

Glossary

published literature, much of which is published outside conventional academic channels. This research methodology concerns conducting a review of gray literature, such as technical reports, blog postings, professional forums, and industry documentation, to gain insight from practical experience. Gray literature reviews apply most to software engineering research as they represent real practices, challenges, and solutions that have taken place during implementation that may not have been captured or documented in the academic literature. This methodology acts like a bridge that closes the gap between theoretical research and its industry application. [i](#), [14](#)

Lines of Code A metric used to quantify the size or complexity of a software program by counting the number of lines in its source code. LOC is often used as an indicator of development effort, code maintenance, and project scale.. [i](#)

MCAG Mobile Content Accessibility Guidelines (MCAG) are a specialized set of accessibility recommendations specifically tailored to mobile application and mobile web content. While building upon the foundational principles of WCAG, MCAG addresses unique challenges of mobile interfaces, such as touch interactions, small screen sizes, diverse input methods, and mobile-specific assistive technologies. These guidelines provide specific considerations for creating accessible content and interfaces on smartphones, tablets, and other mobile devices, taking into account the distinct interaction patterns and technological constraints of mobile platforms. [i](#), [12](#)

React Native React Native is an open-source mobile application development framework created by Facebook (now Meta) that allows developers to build mobile applications using JavaScript and React. Introduced in 2015, React Native enables developers to create native mobile apps for both iOS and Android platforms using a single codebase, leveraging the popular React web development library. Unlike hybrid app frameworks, React Native renders components using actual native platform UI elements, providing a more authentic user experience and better performance. The framework bridges the gap between web and mobile development, allowing web developers to create mobile

Glossary

applications using familiar JavaScript and React paradigms, while still achieving near-native performance and user interface responsiveness. [i](#), [22](#), [27](#)

Screen Reader A screen reader is an assistive technology software that enables people with visual impairments or reading disabilities to interact with digital devices by converting on-screen text and elements into synthesized speech or Braille output. Screen readers navigate through user interfaces, reading text, describing graphical elements, and providing auditory feedback about the computer or mobile device's content and functionality. They interpret and verbalize user interface elements, buttons, menus, and other interactive components, allowing visually impaired users to understand and interact with digital content. Popular screen readers include VoiceOver for Apple devices, TalkBack for Android, and NVDA and JAWS for desktop computers. [i](#), [25](#)

TalkBack TalkBack is a screen reader developed by Google for Android devices. It provides spoken feedback and vibration to help visually impaired users navigate their devices and interact with apps. [i](#), [31](#), [47](#), [130](#)

User Interface The User Interface refers to the space where interactions between humans and machines occur. It includes the design and arrangement of graphical elements (such as buttons, icons, and menus) that enable users to interact with software or hardware systems. The goal of a UI is to make the user's interaction simple and efficient in accomplishing tasks within a system. [i](#), [7](#)

User Experience User Experience encompasses the overall experience a user has while interacting with a product or service. It includes not only usability and interface design but also the emotional response, satisfaction, and ease of use a person feels while using a system. UX design focuses on optimizing a product's interaction to provide meaningful and relevant experiences to users, ensuring that the system is intuitive, efficient, and enjoyable to use. [i](#)

VoiceOver VoiceOver is a screen reader built into Apple's macOS and iOS operating systems. It provides spoken descriptions of on-screen elements and allows users to navigate

Glossary

and interact with their devices using gestures and keyboard commands. [i](#), [31](#), [47](#), [130](#)

W3C The World Wide Web Consortium (W3C) is an international community that develops open standards to ensure the long-term growth and evolution of the web. Founded by Tim Berners-Lee in 1994, the W3C works to create universal web standards that promote interoperability and accessibility across different platforms, browsers, and devices. This non-profit organization brings together technology experts, researchers, and industry leaders to develop guidelines and protocols that form the fundamental architecture of the World Wide Web. Key contributions include HTML, CSS, accessibility guidelines (WCAG), and web standards that ensure a consistent, inclusive, and innovative web experience for users worldwide. [i](#), [11](#), [22](#)

WCAG The Web Content Accessibility Guidelines (WCAG) are a set of recommendations for making web content more accessible to people with disabilities. They provide a wide range of recommendations for making web content more accessible, including guidelines for text, images, sound, and more. [i](#), [11](#), [22](#)

Chapter 1

Introduction

This chapter explores the fundamental aspects of mobile accessibility, examining how different user capabilities, device interactions, and usage contexts shape the landscape of accessible mobile development.

1.1 Mobile accessibility: context & foundations

In an era where digital technology permeates every aspect of our lives, mobile devices have emerged as the primary gateway to the digital world, allowing a lot of new people to be connected at any given time, no matter the condition. An estimated number of circa 7 billions [9], representing a dramatic increase from just one billion users in 2013, is currently using mobile devices and exploiting the possibilities they offer on an everyday basis. This explosive growth has not only changed how we communicate and access information but has also created a massive market for different needs and introduced new categories of users, with different habits and cultures into a truly global market.

As mobile applications become increasingly central to daily life, ensuring their accessibility to all users, regardless of their abilities or disabilities, has become a critical imperative, since not only technology should be able to connect, but also to unite seamlessly people with different capabilities. Accessibility refers to the design and development practices enabling all users, regardless of their abilities or disabilities, to perceive, understand and navigate with digital content effectively. Not only the quantity of media increased, but also the quantity of different media which allow to access information definitely increased; finding appropri-

CHAPTER 1. INTRODUCTION

ate measurements to establish a good level of understanding and usability is important and finding appropriate levels of measurements is non-trivial.

An estimated portion of over one billion people lives globally with some forms of disability [33]. Inaccessible mobile applications can, therefore, present considerable barriers to participation in that large and growing part of modern life that involves education, employment, social interaction, and even basic services. Accessibility is not about a majority giving special dispensation to a minority but rather about providing equal access and opportunities to very big and diverse user bases.

This encompasses a wide range of considerations to be made on the actual products design and the user classes, including but not limited to:

1. *Visual accessibility*: supporting users who have a visual impairment or low vision, requiring alternative description and screen readers support;
2. *Auditory accessibility*: providing alternatives for users who have a hearing impairment or hard of hearing, offering clear controls and alternative visuals for audio content, ensuring compatibility with assistive devices and giving feedback to specific actions done by users;
3. *Motor accessibility*: accommodating users with limited dexterity or mobility, providing alternative input navigation, create a design so to help avoiding complex gestures, customize the interactions and gestures, reducing precision and accommodating errors;
4. *Cognitive accessibility*: ensuring content is understandable for users with different cognitive abilities. This includes having consistent and predictable navigation, using visual aids to help users stay focused, and making sure all parts of the interface are easy to understand, providing a language which is clear, concise and straightforward.

In the mobile environment, such considerations is important, since there is a complex web of interactions to be considered, mainly focusing on two aspects:

1. Device diversity and integration - accommodating different gestures, interfaces and interaction modalities

CHAPTER 1. INTRODUCTION

- Standard mobile devices (smartphones, tablets);
 - Emerging device formats (foldables, dual-screen devices);
 - Wearable technology (smartwatches, fitness trackers);
 - Embedded systems (vehicle interfaces, smart home controls);
 - IoT devices with mobile interfaces.
2. Usage context variations - may influence the overload of information and the cognitive load perceived by the user
- Environmental conditions (lighting, noise, movement);
 - User posture and mobility situations;
 - Attention availability and cognitive load;
 - Physical constraints and limitations;
 - Social and cultural contexts.

These considerations are important since they impact how accessibility features should go above and beyond, carefully considering how the interaction in mobile devices is used. Mobile devices offer multiple interaction modalities, which must be considered for an inclusive design:

- *Touch-based interactions*: here, traditional interactions present specific challenges and opportunities for accessibility: actions like tapping (selection/activation), double tapping (confirmation/secondary actions), long pressing (contextual menus/additional options), swiping (navigation/list scrolling) and pinching (zoom control) are used. These gestures may need alternatives regarding timing in long presses, touch stabilization and increased touch target sizes, since they can be also combined with multiple patterns e.g. multi-finger gestures and edge swipes;
- *Voice control and speech input*: navigation commands and action triggers can be activated giving directions (e.g. "go back", "scroll down"), inputting text thorough dictation, while giving auditory feedback and interactions vocally;

CHAPTER 1. INTRODUCTION

- *Motion and sensor-based input:* modern devices offer various sensor-based interaction methods, like tilting controls for navigation, shaking gestures for specific actions, orientation changes for layout adaptation, using proximity sensors to detect gestures without touch;
- *Switch access and external devices:* providing support for alternative input methods is crucial, providing physical single or multiple switch support, sequential focus navigation and customizable timing controls. Some users might find useful to have external input devices like keyboards, specialized controllers, Braille displays, but also help from custom assistive devices;
- *Haptic feedback:* tactile feedback provides important interaction cues, on actions confirmation, error notifications and context-sensitive responses, e.g. force-touch interactions and pressure-based controls.

It's useful to analyze such commands since the focus would be describing how to address accessibility issues and have a complete focus on how a user would interact with an interface and a mobile device, since each interaction provides a different degree of complexity. Understanding built-in capabilities is crucial for developers working with cross-platform frameworks, as they must effectively bridge their applications with native features. These tools will be discussed from an high-level, so to describe their role and goals, among functionalities:

- *TalkBack for Android:* Google's screen reader provides comprehensive accessibility support through:
 - Linear navigation mode that allows users to systematically explore screen content through swipe gestures, which replaces traditional mouse or direct touch interaction;
 - Touch exploration mode allowing users to hear screen content by touching it and make navigation predictable and systematic;
 - Custom gesture navigation system for efficient interface interaction;

CHAPTER 1. INTRODUCTION

- Customizable feedback settings for different user preferences;
 - Integration with external Braille displays and keyboards (also with complementary services like *BrailleBack*);
 - Support for different languages and speech rates
 - Help in combination of *Switch Access*, built-in feature to help users using switches instead of touch gestures.
- *VoiceOver for iOS*: Apple's integrated screen reader offers:
 - Rotor control for customizable navigation options;
 - Advanced gesture recognition system;
 - Direct touch exploration of screen elements;
 - Automatic language detection and switching;
 - Comprehensive Braille support across multiple standards;
 - Complete integration with *Zoom*, a built-in screen magnifier present in iOS devices to zoom in on any part of the screen;
 - Integrated with other a suite of other accessibility tools present in iOS devices, available to all users.
 - *Select to Speak for Android*: A complementary feature that provides:
 - On-demand reading of selected screen content;
 - Visual highlighting of spoken text;
 - Simple activation through dedicated gestures;
 - Integration with system-wide accessibility settings.

This thesis examines the implementation of accessibility support in two leading mobile development frameworks—Flutter and React Native—with particular attention to their integration with native accessibility features. The architectural approaches differ significantly: Flutter creates a structured accessibility tree that maps to native accessibility APIs, while

CHAPTER 1. INTRODUCTION

React Native establishes direct bindings to platform-specific accessibility features. This fundamental difference profoundly influences how developers must conceptualize and implement accessibility within their applications, a distinction that will be thoroughly explored throughout this work.

1.2 Thesis structure

In this subsection, a brief description of the rest of the thesis is given:

The second chapter presents a comprehensive literature review of mobile accessibility, examining specific guidelines for mobile applications including WCAG adaptations, platform-specific requirements for iOS and Android, regulatory frameworks, implementation considerations, and testing methodologies. This chapter establishes the theoretical foundation for understanding the current accessibility landscape;

The third chapter introduces the *AccessibleHub* project—a React Native application serving as an interactive guide for implementing accessibility features in mobile applications. This chapter details the architectural design, implementation patterns, and educational framework underpinning this novel approach to mobile accessibility. *AccessibleHub* methodically addresses the challenges developers face when translating abstract WCAG guidelines into practical implementations, extending previous research to provide a developer-centric toolkit that analyzes how React Native and Flutter handle accessibility through interactive examples and component-level guidance;

The fourth chapter provides a detailed analysis of WCAG guideline implementation across frameworks, examining implementation complexity, performance implications, developer experience, and testing methodologies. This chapter offers comparative insights into accessibility implementation between React Native and Flutter, identifying best practices, common pitfalls, and optimization strategies;

The final chapter synthesizes key findings, presents actionable recommendations for accessible mobile development, highlights best practices derived from the research, and

CHAPTER 1. INTRODUCTION

outlines promising directions for future investigation in this rapidly evolving field.

To enhance readability and ensure clarity, this thesis adopts the following typographical conventions:

- Acronyms, abbreviations, and technical terms are defined in the glossary;
- First occurrences of glossary terms use the format: *User Interface_G*;
- Foreign language terms and technical jargon appear in *italic*;
- Code examples use `monospace` formatting when discussed within text or proper custom coloring form to be used within the rest of sections.

Chapter 2

Mobile accessibility: guidelines, standards and related works

This chapter reviews mobile accessibility research and standards. It covers current accessibility legislation, key development guidelines (focusing on practical implementation), and significant studies on user experience, development challenges, and testing methodologies.

2.1 Accessibility legislative frameworks

The journey towards digital accessibility has been shaped by both legislative frameworks and technological advancements, alongside the evolution of devices and how they integrate into daily life. These developments reflect not just a response to legal requirements, but a fundamental shift in how we approach digital design and development. The goal has evolved from simple compliance to embracing universal design principles - creating products and services that can be used by everyone, regardless of their abilities or circumstances [29].

Universal design in the digital world embodies the principle that technology should be inclusive, since many times it's treated as an afterthought, while it must be considered from the earliest stages of development. This evolution has been particularly significant in the mobile ecosystem, where the constant need of connectivity and the multiple usages of these devices have opened multiple opportunities, but also challenges for both users and content creators. Connectivity, convenience and creativity are one of the main focus and purpose of the online

CHAPTER 2. MOBILE ACCESSIBILITY: GUIDELINES, STANDARDS AND RELATED WORKS

world, where Internet and access to a mobile device has been recognized to be one of the fundamental rights for human beings in general. As evidenced by the multiple ways users interact with mobile platforms, as described in [1.1](#), there are significant challenges in the current state of digital accessibility. These challenges stem from two main factors: the difficulty in addressing user needs and the lack of clear implementation guidelines for developers.

To understand the current state of mobile accessibility, it's crucial to examine the legislative landscape that has shaped its development. This progression of laws and regulations demonstrates how accessibility requirements have evolved from broad civil rights protections to specific technical standards for digital interfaces. Several key legislative milestones across different regions have shaped this evolution - we will see the main ones

- In the *United States*, the foundation was built through a number of major pieces of legislation. The *Americans with Disabilities Act (ADA)* of *1990*, while predating modern mobile technology, established a number of critical precedents regarding the rights of disabled citizens. Initially targeted at physical accessibility, interpretations of the ADA have expanded to include digital spaces, both mobile applications and websites. At the same time, OSes like Windows implemented accessibility features pre-loaded within the system itself in *1995*, instead of having them available as add-ons or plug-ins. This is further reinforced by the *Section 508 Amendment* in *1998* [[28](#)] to the Rehabilitation Act, addressing digital accessibility requirements relative to federal agencies and their contractors for websites alike. Shortly after, between *2002* and *2005*, Apple introduced both Universal Access and VoiceOver, both with the goal of increasing accessibility within options and controls present inside of their devices;
- *Italy* has developed its own robust framework for digital accessibility, building upon and extending European requirements. *Legge Stanca (Law 4/2004)*, updated in *2010*, established comprehensive accessibility requirements for public administration websites and applications. This was further enhanced by the creation of *AGID (Agenzia per l'Italia Digitale)* in *2012*, which provides detailed technical guidelines and ensures compliance across public and private sectors;

- The *European Union* has moved to more modern legislation concerning digital accessibility in recent times. The *European Accessibility Act*, passed in 2019, contains broad requirements with specific coverage of modern digital technologies. This is further codified in the *Directive (EU) 2016/2102 on the accessibility of websites and mobile applications of public sector bodies* [11], which explicitly mandates WCAG 2.1 AA compliance for all public sector mobile applications. This is different from earlier legislation, as legislation like the explicit inclusion of mobile applications as central in modern digital interaction by the EAA, is complemented by standard *EN 301 549* that provides detailed technical specifications aligned with international accessibility guidelines.

These legislative frameworks are supported by international technical standards, especially the *Web Content Accessibility Guidelines*, created by the *W3C*. WCAG has evolved from its first version in 1999 to this year's WCAG 2.2 (came out in 2023), reflecting increased sophistication in digital interfaces and interaction patterns. In each iteration, more scope and detail about the requirements have been added; recent versions place particular emphasis on mobile and touch interfaces. WCAG serves as the primary technical foundation for digital accessibility implementation worldwide, providing specific, testable criteria for making content accessible to people with disabilities, serving as one of the main foundations for developers and content creators to be used as standard of reference. The guidelines implement three levels of conformance (A, AA, and AAA), providing increasingly stringent accessibility requirements. These will be explored in depth and used as main reference for the work present inside of this research, to establish clear degrees of success criteria to be met by the frameworks relative implementations.

2.2 Accessibility standard guidelines

Accessibility guidelines and standards form the foundation upon which inclusive mobile app development practices are built. They provide a shared framework for understanding and addressing the diverse needs of users with disabilities, ensuring that mobile apps are perceivable, operable, understandable, and robust. This section explores the key accessibility

guidelines and standards relevant to mobile app development, describing them briefly before seeing how they apply to the concrete use case of this thesis' application, following the principles presented here.

2.2.1 Web Content Accessibility Guidelines (WCAG)

The *WCAG*, developed by the *W3C*, serve as the international standard for digital accessibility ([31]). Although originally designed for web content, the WCAG principles and guidelines are equally applicable to mobile app development. The WCAG is organized around four main principles:

- *Perceivable*: Information and user interface components must be presentable to users in ways they can perceive. This includes providing text alternatives for non-text content, creating content that can be presented in different ways without losing meaning, and making it easier for users content;
- *Operable*: User interface components and navigation must be operable. This means that all functionality should be available also from a keyboard, users should have enough time to read and use the content, and content should not cause seizures or physical reactions;
- *Understandable*: Information and the interactions provided by the user interface must be understandable. This involves making text content readable and understandable, making content appear and operate in predictable ways, and helping users avoid and correct mistakes;
- *Robust*: Content must be robust enough that it can be interpreted by a wide variety of user agents, including assistive technologies. This requires maximizing compatibility with current and future user agents.

Under each principle, the WCAG provides specific guidelines and success criteria at three levels of conformance (A, AA, and AAA). These success criteria are testable statements that help developers determine whether their app meets the accessibility requirements. By

understanding and applying the WCAG principles and guidelines, mobile app developers can create more inclusive and accessible experiences for their users.

2.2.2 Mobile Content Accessibility Guidelines (MCAG)

While *WCAG_G* offers a comprehensive foundation, mobile platforms introduce additional complexities that may not be fully addressed by web-centric guidelines. The *MCAG_G* ([18]) build upon the previous ones by focusing on the specific interaction patterns, form factors, and environmental contexts unique to mobile devices. For example, MCAG emphasizes:

- *Touch interaction and gestures*: Ensuring that tap targets, swipe gestures, and multi-finger interactions are usable for individuals with varying motor skills;
- *Limited screen real estate*: Designing content that remains clear and functional on smaller displays, including proper zooming and reflow behavior;
- *Diverse hardware and os versions*: Accounting for a wide range of device capabilities, operating system versions, and hardware configurations that can affect accessibility;
- *Contextual usage scenarios*: Recognizing that mobile apps are often used in changing lighting conditions, noisy environments, or while users are on the move.

In practice, *MCAG_G* complements *WCAG_G* by providing more granular, mobile-oriented guidance considering specific factors. Developers who follow these guidelines in addition to *WCAG_G* are better equipped to deliver an inclusive experience that accounts for real-world mobile usage.

2.2.3 Mobile-specific accessibility considerations

While the previous guidelines provide by themselves a solid foundation for digital accessibility, mobile apps present unique challenges and considerations that require additional attention. Some of the key mobile-specific accessibility factors include:

- *Touch interaction:* Mobile devices rely heavily on touch-based interactions, such as tapping, swiping, and multi-finger gestures. Developers must ensure that all interactive elements are large enough to be easily tapped, provide alternative input methods for complex gestures, and offer appropriate haptic and visual feedback;
- *Small screens:* The limited screen real estate on mobile devices can pose challenges for users with visual impairments. Developers should provide sufficient contrast, use clear and legible fonts, and ensure that content can be easily zoomed or resized without losing functionality;
- *Screen reader compatibility:* Mobile screen readers, such as VoiceOver on iOS and TalkBack on Android, require proper labeling and semantic structure to effectively convey content and functionality to users with visual impairments. Developers must use appropriate accessibility APIs and ensure that all elements are properly labeled and navigable;
- *Device fragmentation:* The wide range of mobile devices, screen sizes, and operating system versions can complicate accessibility testing and implementation. Developers should test their apps on a diverse range of devices and ensure that accessibility features function consistently across different configurations;
- *Mobile context:* Mobile apps are often used in a variety of contexts, such as outdoors, in low-light conditions, or in noisy environments. Developers should consider these contexts and provide appropriate accommodations, such as high-contrast modes or subtitles for audio content.

By understanding and addressing these mobile-specific accessibility considerations, developers can create apps that are more inclusive and usable for a wider range of users.

2.3 State of research and literature review

Having established the regulatory frameworks and technical standards that govern mobile accessibility, it becomes crucial to understand how these requirements translate into

practical implementation, both of research and applications. Research in mobile accessibility spans multiple areas, from user interaction studies to framework-specific analyses. This section outlines the relevant work, organized by key research themes, that informs the presented approach in comparing frameworks. Various studies will be reviewed on how people, with and without impairments, interact with mobile devices. Such studies typically report on accessibility barriers and present insights into the effectiveness of general guidelines on accessibility. This literature review focuses a great deal on research related to challenges faced by users with disabilities and the implementation of accessibility features in mobile development frameworks, discussing the practical importance of the presented work.

2.3.1 Users and developers accessibility studies

In exploring accessibility solutions for mobile applications, a notable contribution comes from Zaina et al. [23], who conducted extensive research into accessibility barriers that arise when using design patterns for building mobile user interfaces. The authors recognize that several user interface design patterns are present inside of libraries, but do not attach significant importance to accessibility features, which are already present in language. This study tried to adopt a *Gray Literature Review* approach, gathering insights and capture real practitioners' experiences and challenges in implementing UI patterns, done by investigating professional forums or blogs. This approach proved valuable, since this was recognized as a source of practical knowledge and evidence a comprehensive catalog documenting 9 different user interface design patterns, along with descriptions of accessibility barriers present for each one and specific guidelines for prevention, for example inside of Input and Data components but also animated parts. The study's validation phase involved 60 participants, highlighting the fact participants saw value in the guidelines not just for implementing accessibility features, but also for improving their overall understanding of accessible design principles. These comprehensive results demonstrated both the practical applicability of the guidelines in real development scenarios and their effectiveness as an educational tool for raising awareness about accessibility concerns among developers.

Another significant contribution to report here was conducted by Vendome et al. [10] and analyzed the implementation of accessibility features inside of Android applications both quantitatively and qualitatively, with the main goal of understanding accessibility practices among developers and identify common implementation patterns through a systematic approach, while mining the web to look for data. The methodology of the research contained two major parts: first, they did a mining-based analysis of 13,817 Android applications from GitHub that had at least one follower, star, or fork to avoid abandoned projects. They have done a static analysis on the usage of accessibility APIs and the presence of assistive content description in GUI components. A second component was a qualitative review of 366 Stack Overflow discussions related to accessibility, which were formally coded following an open-coding process with multi-author agreement.

The key results of the mining study were that while half of the apps supported assistive content descriptions for all GUI components, only 2.08% used accessibility APIs. The Stack Overflow analysis revealed that support for visually impaired users dominated the discussions - 43% of the questions-and remarkably enough, 36% of the accessibility API-related questions were about using these APIs for non-accessibility purposes. The study identified several critical barriers to accessibility implementation: lack of developer knowledge about accessibility features, limited automated support and insufficient guidance for screen readers, while having a notable gap between accessibility guidelines and implementation practices.

Another paper reporting notable findings is the one from Pandey et al. [26], an analytical work of 96 mailing list threads combined with 18 interviews carried out with programmers with visual impairments. The authors investigate how frameworks shape programming experiences and collaboration with sighted developers. As expected, it concluded that accessibility problems are difficult to be reduced either to programming tool UI frameworks alone: they result from interactions between multiple software components including IDEs, browser developer tools, UI frameworks, operating systems, and screen readers, a topic of this thesis and research. Results showed that, although UI frameworks have the potential

to enable relatively independent creation of user interfaces that reduce reliance on sighted assistance, many of those frameworks claimed themselves to be accessible out-of-the-box, but only partially lived up to this promise. Indeed, their results showed that various accessibility barriers in programming tools and UI frameworks complicate writing UI code, debugging, and testing, and even collaboration with sighted colleagues.

2.3.2 User categories and development approaches

In recent studies addressing accessibility in mobile applications, various user categories are analyzed to determine their unique needs and challenges, resulting in a range of development approaches tailored to specific user groups. A good example is the systematic mapping carried out by Oliveira et al. [8] about mobile accessibility for elderly users. The mapping underlined that this group faces physical and cognitive constraints, such as problems with small text, intricate navigation, and complex touch interactions. The authors suggest that, in order for content and functions to be more accessible and user-friendly even for those users whose limitations are a consequence of age, applications targeting elderly users should embed font adjustments, use of simpler language, and larger interactive elements. This paper does not only point to overcoming already present barriers but also supports and pleads for the development of age-inclusive mobile designs that would raise the level of usability and engagement for elderly users.

In the field of cognitive disability, the authors Jaramillo-Alcázar et al. [2] introduce a study on the accessibility of mobile serious games, a recent developing area in both education and therapy. Their study underlines the fact that for serious games, the integration of cognitive accessibility features such as adjustable speeds, simplified instructions, and interactive elements with distinct visual appearances is crucial to help users with cognitive impairments. By discussing the features of serious games that pertain to cognitive accessibility, categorized by implementation complexity and user impact, the authors created an assessment framework. The authors identify that defining which features potentially benefit users with cognitive impairments sets the call for a normal model to guide developers in

creating game interfaces accessible to the users' cognitive abilities and learning needs, with the aim of improving inclusiveness and educational potentials of mobile games.

2.3.3 Testing methodologies and evaluation frameworks

Testing and evaluating mobile accessibility presents a complex challenges, often requiring a multi-faceted approach, combining both automated tools and manual evaluation. While automated testing tools have evolved significantly, research consistently shows that no single approach can comprehensively assess all aspects of mobile accessibility. Silva et al. [6] conducted an analysis by comparing the efficiency of automated testing tools against guidelines from the WCAG and platform-specific requirements. Silva's study researched ten different automated testing platforms, evaluating their capabilities for various accessibility criteria. Their results indicated critical limitations in the way automated tools approached accessibility testing, especially regarding mobile contexts. While these tools demonstrated strong capabilities in identifying technical violations, such as missing alternative text, insufficient color and improper usage of hierarchies, they consistently struggled with more nuanced aspects of accessibility, like giving meaningful description of images or verify the logical content organization when writing headings. Tools can identify the presence of error messages but cannot see if these messages are helpful and provide clear guidance for corrections; the same holds for automated tests for touch targets sizing, which cannot be evaluated in their placement makes sense from a user perspective.

This understanding is further reinforced by a comprehensive study led by Alshayban et al., [15] where over 1,000 Android applications in the Google Play Store were analyzed. Their work examined both the technical accessibility features and user feedback, showing that different testing methodologies often identify different kinds of accessibility issues. They also reported that automated tools could identify as many as 57% of the technical accessibility violations but missed many issues with significant user experience impacts. Their study seems to indicate that the most effective approach to testing accessibility combines a number of different methodologies. The research identifies three key components for effective

accessibility testing:

- *Automated testing tools*: These tools are good at systematic checking of technical requirements through programmatic analysis. They provide continuous monitoring of accessibility violations during development, while being particularly effective at regression testing and performing both static and dynamic analysis of code for common accessibility patterns;
- *Manual expert evaluation*: This involves detailed assessment of contextual appropriateness by accessibility experts. They can validate semantic relationships between interface elements, evaluate complex interaction patterns, and assess error handling mechanisms in ways that automated tools cannot;
- *User testing*: Provides insights through real-world usage scenarios with diverse user groups, including structured feedback from users with disabilities and testing with various assistive technologies. This often reveals issues that neither automated tools nor expert evaluation can identify, particularly regarding practical usability.

It's important to consider guidelines which can be precisely implemented for testing mobile components and ensure their accessibility across different platforms and user needs. As demonstrated by the research, neither automated tools or human testing alone can guarantee complete accessibility coverage. This underscores the critical importance of having standardized guidelines working as a general guidance framework for both automated testing tools and human evaluators. Such guidelines provide measurable success criteria that can be systematically tested while also offering the context and depth needed for manual evaluation. By following these established standards, developers can ensure a more comprehensive approach to accessibility implementation, one that benefits from both automated efficiency and human insight.

2.3.4 Framework implementation approaches

While previous research has extensively documented accessibility challenges and user needs, less attention has been paid to practical implementation comparisons across frame-

works. Most comparative studies between Flutter and React Native have focused primarily on performance metrics and testing capabilities. For instance, Abu Zahra and Zein [14] conducted a systematic comparison between the two frameworks from an automation testing perspective, analyzing aspects such as reusability, integration, and compatibility across different devices. Their findings showed that React Native outperformed Flutter in terms of reusability and compatibility, though both frameworks demonstrated similar capabilities in terms of integration.

However, when it comes to accessibility-specific comparisons, the research landscape is more limited. A research discussing and comparing the two frameworks addressing accessibility issues, which this thesis wants to base upon, is the research by Gaggi and Perinello [21], investigating three main questions: whether components are accessible by default, if non-accessible components can be made accessible, and the development cost in terms of additional code required. The study examines a set of UI elements against WCAG criteria and proposes solutions when official documentation is insufficient.

2.3.5 Accessibility tools and extensions

Accessibility tools and extensions development has been instrumental in bridging the gap between theory and practice. These tools have also allowed developers to efficiently include accessibility in their applications while meeting standards. For instance, Chen et al. [5] presented *AccuBot*, a publicly available automated testing tool for mobile applications. The tool is integrated with continuous integration pipelines for the detection of WCAG 2.2 criteria violations, such as insufficient contrast ratios and missing *ARIA_G* labels. In their evaluation of 500 mobile apps, they reported that *AccuBot* reduces manual testing efforts by 40% while sustaining high precision in identifying technical accessibility barriers.

Another contribution worth mentioning is the screen-reader simulation toolkit, *Screen-Mate*, which has been proposed by Lee et al.[17]. It allows developers to simulate how their mobile interfaces would behave under popular screen readers such as VoiceOver and Talk-

Back. By simulating user interactions for visually impaired users, *ScreenMate* helps to early detect navigation inconsistencies and poorly labeled components during the development cycle. The authors have validated the toolkit in a case study with 15 development teams, showing a 30% reduction in post-release bug reports about accessibility.

In the context of framework-specific support, Nguyen et al.[\[19\]](#) implemented *AccessiFlutter*, a plugin for Flutter guiding developers to implement widgets in an accessibility-friendly manner. It provides real-time feedback on component properties, such as using semantic labels for icons or the validation of touch target size. A comparative analysis showed that apps implemented with *AccessiFlutter* attained 95% compliance with WCAG AA criteria, compared to manual implementation. Similarly, [\[27\]](#) developed *A11yReact*, a React Native library providing accessible pre-built components and automated auditing. Their study showed that the developers using *A11yReact* needed 50% fewer code changes to achieve accessibility compared to regular React Native development processes.

These tools highlight the critical role of embedding accessibility into the development process from the outset. By leveraging automation, simulation, and framework-specific support, they tackle both technical and usability challenges, promoting inclusive design practices while maintaining development efficiency. This proactive approach ensures that accessibility is not an afterthought but a fundamental aspect of the development lifecycle, ultimately leading to more inclusive and user-friendly applications.

The current body of research reveals a significant gap in practical accessibility comparisons between mobile frameworks. While numerous studies examine accessibility barriers, user experiences, and support tools, there remains a lack of systematic comparative analysis of accessibility implementation between Flutter and React Native. This thesis aims to bridge this gap by expanding on Budai’s research on Flutter, conducting an in-depth evaluation of both frameworks from a developer perspective. The objective is to provide practical, mobile-specific guidelines that enable developers to make informed decisions about acces-

CHAPTER 2. MOBILE ACCESSIBILITY: GUIDELINES, STANDARDS AND RELATED WORKS

sibility implementation, offering detailed analysis of components and widgets across both frameworks.

Chapter 3

AccessibleHub: Transforming mobile accessibility guidelines into code

This chapter introduces an accessibility learning toolkit for mobile developers. Building upon prior research, it provides a practical guide to implementing accessible mobile applications, particularly in Flutter. *AccessibleHub*, a *React Native* toolkit, offers interactive examples and component-level guidance, comparing React Native and *Flutter*. Grounded in *WCAG* principles, AccessibleHub aims to bridge the gap between accessibility guidelines and real-world application.

3.1 Introduction

3.1.1 Challenges in implementing accessibility guidelines

The importance of mobile app accessibility extends beyond mere compliance with legal regulations. Ensuring equal access to digital content and services is not only an ethical obligation but also a smart business decision. By prioritizing accessibility, app developers and companies can tap into a larger user base, improve user satisfaction, and demonstrate their commitment to social responsibility. Despite the clear benefits and moral imperatives of mobile app accessibility, many developers still struggle to effectively implement accessibility guidelines in their projects. The *WCAG*, developed by the *W3C*, serve as the international standard for digital accessibility. However, translating these guidelines into practical

implementation can be a challenging task, particularly starting from pure formal guidelines into everyday code.

One of the primary challenges lies in the complexity of the guidelines themselves. WCAG encompasses a wide range of *success criteria*, organized under four main general *principles*: perceivable, operable, understandable, and robust. Each principle contains multiple guidelines, and each guideline has several success criteria at different levels of *conformance*. Navigating this intricate web of requirements and understanding how to apply them to specific mobile app components can be overwhelming for developers, especially those new to accessibility. Moreover, the practical implementation of accessibility guidelines often varies across different platforms and frameworks. *iOS* and *Android*, the two dominant mobile operating systems, have their own unique accessibility *APIs*, tools, and best practices. Cross-platform frameworks like React Native and Flutter add another layer of complexity, as developers must ensure that their accessibility implementations are compatible with the underlying platform-specific mechanisms.

Furthermore, there is often a lack of clear, practical examples and guidance on how to implement accessibility features in real-world mobile app projects. While the *WCAG* provides a solid foundation, it is primarily focused on web content and may not always directly address the unique challenges and interaction patterns of mobile apps. Developers often struggle to bridge the gap between the theoretical guidelines and the specific implementation details required for their projects.

3.1.2 The need for practical developer education

To address these challenges and bridge the gap between accessibility guidelines and practical implementation, there is a pressing need for developer education resources that focus on real-world, hands-on learning experiences. Traditional documentation and guidelines, while valuable, often fall short in providing the level of detail and interactivity needed to effectively guide developers through the accessibility implementation process. This is where

the concept of an *accessibility learning toolkit* comes into play. An accessibility toolkit is designed to serve as a comprehensive, interactive resource that empowers developers to create accessible mobile applications by providing:

1. Clear explanations of *WCAG G* guidelines and their applicability to mobile apps;
2. Step-by-step implementation guidance for common mobile app components and interaction patterns;
3. Practical code examples and tutorials that demonstrate best practices;
4. Hands-on exercises and challenges to reinforce learning and build confidence;
5. Tools and techniques for testing and validating the accessibility of mobile apps.

The primary goal of an accessibility learning toolkit is to bridge the gap between the theoretical knowledge of accessibility guidelines and the practical skills needed to implement them effectively in real-world projects. The toolkit should cater to developers at various levels of expertise, from beginners who are new to accessibility concepts to experienced professionals seeking to deepen their knowledge and stay up-to-date with the latest best practices. By providing a comprehensive, hands-on learning resource, the accessibility toolkit can play a crucial role in promoting a culture of inclusive design and development within the mobile app industry.

Current research, including Budai's work on Flutter accessibility testing, has primarily focused on end-user validation and testing methodologies. However, developers need practical, implementation-focused guidance that bridges multiple frameworks and platforms. Despite widespread accessibility guidelines and standard, mobile application developers face significant challenges in translating theoretical requirements into practical implementations. This gap between guidelines and implementation is particularly evident in mobile development, where different platforms, screen sizes, and interaction models add complexity to accessibility implementation. Some of the most common challenges include:

- Complex testing requirements - developers must validate across multiple devices, *Screen Reader*_G, and interaction modes;
- Framework-specific implementations - each platform has unique accessibility *API*_Gs and requirements;
- Limited practical examples - most documentation focuses on theoretical guidelines rather than concrete implementation patterns;
- Performance considerations - accessibility features must be implemented without compromising app performance.

Effective developer education in accessibility requires a solid grounding in learning theories that emphasize hands-on, interactive approaches. By integrating established learning theories with technical education principles, it's possible to justify the interactive and practical approach adopted in this toolkit. In doing so, we draw on constructivist and experiential learning models, which have been widely recognized as effective frameworks in technical and developer education.

Constructivist learning theories, pioneered by Piaget [22] and Vygotsky [30], posit that learning is an active process in which individuals construct knowledge based on their prior experiences and interactions with the environment. In the context of developer education, this suggests that hands-on learning is more effective than passive instruction [25]. By engaging with real-world accessibility challenges and actively experimenting with code implementations, developers can build a deeper understanding of accessibility guidelines and best practices, by having a tool at their disposal easy to use and to navigate.

Kolb's *Experiential Learning Theory* [16] further supports this approach by describing learning as a four-stage cycle: concrete experience, reflective observation, abstract conceptualization, and active experimentation. For developers learning about accessibility, this cycle might involve encountering accessibility issues in their projects, analyzing existing solutions and guidelines, synthesizing their understanding of *WCAG*_G principles, and applying these principles to their own code. *AccessibleHub* facilitates this learning cycle by providing a

structured, interactive environment for developers to engage with accessibility concepts and implementations being organized into different core sections. By aligning with these proven pedagogical approaches, *AccessibleHub* aims to provide an effective and engaging learning experience for developers. Moreover, by fostering a community of practice around accessibility while providing easier access to learning resources, this project encourages ongoing learning and knowledge sharing among developers, promoting the continuous improvement and dissemination of accessibility best practices.

3.1.3 Research objectives and methodology

Building upon previous research into mobile accessibility, this work aims to provide a comprehensive understanding of accessibility implementation across major cross-platform frameworks. While existing research indeed set grounds for both guidelines on accessibility and testing methodologies, there is a critical need to understand how these guidelines translate into practice for developers.

This research addresses three fundamental questions about accessibility implementation in mobile development frameworks (referring to these ones as *research questions*, following the work in [21]):

- First, we investigate whether components and widgets provided by frameworks are *accessible by default*, without requiring additional developer intervention. This analysis is crucial for understanding the baseline accessibility support provided by each framework and identifying areas where additional implementation effort may be required;
- Second, we examine the *feasibility of making non-accessible components accessible* through additional development effort. This involves analyzing the technical capabilities of each framework and identifying the necessary modifications to achieve accessibility compliance;
- Third, we quantify the *development overhead required to implement accessibility features* when they are not provided by default. This includes measuring additional code

requirements, analyzing complexity increases, and evaluating the impact on development workflows.

These questions are addressed via the usage of a systematic methodology aiming to address in detail accessibility support in React Native and Flutter, focusing on component implementation patterns and native platform integration. The implementation is comparative, allowing developers to directly implement accessible code examples with different degrees of implementation complexity measured quantitatively (including lines of code, required properties, and additional components needed for accessibility support). Comprehensive testing of implementations is also done using screen readers and other assistive technologies to verify accessibility compliance.

The *goal* is to create an accessible application that serves three key purposes:

1. To provide developers with practical, interactive examples of accessibility implementation, able to be copied easily and ported inside of other projects;
2. To compare and contrast accessibility approaches between the main cross-development mobile frameworks in the current mobile landscape;
3. To establish a reusable pattern library that demonstrates engine architecture, widget systems, and native platform integration, while ensuring compliance with current accessibility guidelines and legal requirements.

The following sections will detail the development of *AccessibleHub*, an application developed in React Native designed to serve as a practical manual for implementing accessibility features. While the technical aspects of cross-platform frameworks will be discussed later, the focus remains on providing developers with actionable implementation patterns and comparative insights for building accessible applications.

3.2 React Native Overview

React Native is an open-source framework developed by Meta that enables developers to build mobile applications using *JavaScript* and the *React* paradigm ([24]). It employs

a declarative, component-based approach through the use of *JSX*, which is an XML-like syntax that allows developers to intermix *JavaScript* logic with markup. This combination not only improves code readability but also enhances modularity and facilitates code reuse.




Figure 3.1: React Native logo

3.2.1 Core architecture and features

- *Component-based architecture*: The entire user interface in React Native is built from reusable components. Each component encapsulates its own logic and presentation, which greatly aids in the maintainability and scalability of complex applications;
- *JSX syntax*: Developers write the *UI* using *JSX*, a syntax extension similar to *HTML*. This blending of code and layout simplifies the development process and enables a more intuitive understanding of the component structure;
- *Bridging mechanism*: React Native's bridge enables asynchronous communication between the *JavaScript* layer and native modules. This means that while the application is written in *JavaScript*, performance-critical tasks can be executed using native code (e.g., *Objective-C*, *Swift*, or *Java*), ensuring a native look and feel without sacrificing performance;
- *Hot reloading*: One of the standout features present in this framework, which allows developers to see changes in real time without restarting the entire application. This

accelerates the development cycle and aids in rapid prototyping;

- *Unified codebase:* React Native enables the development of applications for both iOS and Android using a single codebase. This unified approach reduces development time and effort compared to maintaining separate codebases for each platform.

3.2.2 Accessibility in React Native

React Native provides a robust set of accessibility features that are deeply integrated into its component model. This allows developers to create inclusive applications without relying on external libraries or writing platform-specific code (following what's present into [1]). Here are the key accessibility features in React Native:

- **Accessibility properties:** React Native components can be enhanced with a variety of accessibility properties that provide semantic meaning and context for assistive technologies. These properties include:
 - `accessibilityLabel`: A concise, descriptive string that identifies the component for screen reader users;
 - `accessibilityRole`: Defines the component's semantic role (e.g., `"button"`, `"header"`), helping assistive technologies interpret its purpose correctly;
 - `accessibilityHint`: Provides additional context about a component's function or the result of interacting with it;
 - `accessibilityState`: Describes the current state of a component (e.g., `selected`, `disabled`), which is essential for conveying dynamic changes.
- **Accessibility actions:** React Native allows developers to define custom accessibility actions for components, enabling advanced interactions beyond the default gestures. For example, a custom `accessibilityAction` could be added to a component to trigger a specific behavior when activated by an assistive technology;
- **Accessibility focus:** React Native manages accessibility focus automatically, ensuring that the correct component receives focus when navigating with assistive technologies.

Developers can also programmatically control focus using the `accessibilityElementsHidden` and `importantForAccessibility` properties;

- **Accessibility events:** React Native provides accessibility events that notify assistive technologies when important changes occur in the application. These events include:
 - `onAccessibilityTap`: Called when a user double-taps a component while using an assistive technology;
 - `onMagicTap`: Called when a user performs the "magic tap" gesture (a double-tap with two fingers) to activate a component;
 - `onAccessibilityFocus`: Called when a component receives accessibility focus;
 - `onAccessibilityBlur`: Called when a component loses accessibility focus.

By leveraging these built-in accessibility features, developers can create React Native applications that are inclusive and accessible to users with diverse needs and abilities. The tight integration of accessibility into the core component model ensures that developers can create accessible apps without sacrificing performance or maintainability.

3.2.3 Advantages and developer benefits

Using React Native offers several benefits for developers, briefly listed here:

- *Rapid development:* Thanks to hot reloading and a vast ecosystem of reusable components, developers can iterate quickly and efficiently;
- *Cross-platform consistency:* With a unified codebase for both iOS and Android, developers can ensure a consistent user experience without duplicating effort;
- *Integrated accessibility:* React Native's direct integration of accessibility properties allows developers to implement accessible features without having to rely on external tools or write platform-specific code;

- *Community and support:* A large and active community means extensive documentation, a wealth of third-party libraries, and a robust support network for troubleshooting and enhancements;
- *Seamless transition for web developers:* Developers familiar with React for web applications will find the transition to React Native smooth, as the core concepts and *JSX* syntax remain consistent.

3.2.4 Differences from native iOS/Android and web development

- *Native iOS/Android:* In native development, accessibility is handled through platform-specific *API_G*: *VoiceOver_G* on *iOS* and *TalkBack_G* on *Android*, which require different tools and approaches. React Native provides a unified *APIs*, streamlining the implementation of accessibility features across both platforms.
- *Web development:* Whereas web accessibility is achieved by adding *ARIA_G* attributes to *HTML*, React Native integrates accessibility directly within its component structure. This intrinsic approach treats accessibility as a core attribute of each component, rather than an external addition.

In summary, React Native offers a modern, efficient, and developer-friendly environment that not only simplifies cross-platform mobile development but also incorporates accessibility into its core design. This makes it an ideal choice for creating inclusive applications, and it forms the foundational platform upon which the *AccessibleHub* toolkit is built.

3.3 AccessibleHub: An Interactive Learning Toolkit

3.3.1 Core architecture and design principles

AccessibleHub is a React Native application designed to serve as an interactive manual for implementing accessibility features in mobile development. Unlike traditional documentation or testing frameworks, the application provides developers with hands-on examples and implementation patterns that can be directly applied to their projects.

The application is structured around four conceptual main sections:

1. *Component examples*: Interactive demonstrations of common *UI G* elements with proper accessibility implementations, including buttons, forms, media content, and navigation patterns. This allows developers to clearly see the implementation of an accessible component and easily copy the code to their convenience;
2. *Framework comparison*: A detailed analysis of accessibility implementation approaches between React Native and Flutter, highlighting differences in component structure, properties, and required code;
3. *Testing tools*: Built-in utilities for validating accessibility features, allowing developers to understand how screen readers and other assistive technologies interact with their implementations;
4. *Implementation guidelines*: Technical documentation that connects WCAG requirements to practical code examples, providing clear paths for meeting accessibility standards.

Each component presented serves dual purposes: demonstrating proper accessibility implementation while providing reusable code patterns. The application emphasizes practical implementation over theoretical guidelines, showing developers not just what to implement effectively. By focusing on developer experience, *AccessibleHub* bridges the gap between accessibility requirements and actual implementation, providing a resource that can be directly integrated into the development workflow.

The *design* philosophy of *AccessibleHub* is founded on principles that bridge theoretical accessibility guidelines with practical implementation needs. While analyzing the current landscape of mobile development frameworks and accessibility implementation presented in [2.3](#), a clear pattern emerges: developers need more practical, implementation-focused guidance that directly addresses the complexity of building accessible applications. To address this need, *AccessibleHub* adopts three fundamental architectural principles:

1. The usage of a *component-first architecture*, where each UI element exists as an independent, self-contained unit demonstrating both implementation patterns and accessibility features. In other words, each one of them is being constructed within an *accessibility-first* experience which ensures that usage of screen readers and other assistive technologies is kept as a priority. This modular approach provides two advantages: it first allows developers to comprehend and apply accessibility features in isolation, hence reducing cognitive load and implementation complexity, and enables systematic testing and validation of accessibility features of every component. Also, this means accessibility patterns can be studied, implemented, and verified in isolation from added complexity brought in by interactions among those components;
2. *Progressive enhancement* as a core design methodology. Instead of presenting accessibility as big challenge from the start, components are structured in increasing levels of complexity. This starts with basic elements like buttons and text inputs where basic accessibility patterns can be established. As developers master these foundational components, the application introduces more complex patterns such as forms, navigation systems, and gesture-based interactions. This helps into guiding the development towards more complicated scenarios;
3. Focus on *framework-agnostic patterns*, not depending on a specific framework while providing concrete code implementations. Even though *AccessibleHub* has been implemented in React Native, all the patterns and principles explained are designed to transcend into specific framework implementations. The approach wants to give importance to the compatibility and reusability in the framework on the mobile development side. It will compare the implementations, mainly between React Native and Flutter, to show how developers can port accessibility patterns across different frameworks and understand core accessibility concepts in an easy-to-implement manner within professional projects.

Through these principles, *AccessibleHub* aims to transform accessibility from an afterthought into an *accessibility-by-design*. The application serves not just as a reference

implementation, but as an educational tool that guides developers through the process of building truly accessible applications. This approach recognizes that effective accessibility implementation requires both theoretical understanding and practical experience, providing developers with the tools they need to create more inclusive mobile applications.

3.3.2 Educational framework design

AccessibleHub's educational framework is designed to provide a structured, incremental learning experience that progressively builds accessibility knowledge and skills. The content is organized into different *learning modules*, each focusing on a key aspect of mobile accessibility. This is structured incrementally, so to help a developer gather a general idea on what needs to be implemented following a practical roadmap of steps: this allows to focus on different aspects of mobile accessibility, selecting each time the most relevant ones.

The core of the application is divided into different main screens, following:

1. **Home** - The entry point for the *AccessibleHub* application (3.2). It provides an overview of the main sections and guides users on where to start their accessibility learning journey. The Home screen is designed to be intuitive and user-friendly, with clear call-to-action towards the accessible components section, allowing a developer or a user navigate to the desired section from the Home screen, comprehensive of comparison between the main mobile frameworks, learn about best practices in mobile accessibility and access testing tools documentation. There is also present a compliance dashboard provides an overview of an app's accessibility compliance status, based on the [WCAG_G](#) and [MCAG_G](#) guidelines. Developers can use this information to prioritize their accessibility efforts and focus on the areas that need the most attention;




Figure 3.2: The Home screen of *AccessibleHub*

2. **Accessible Components** - Developers can learn how to implement accessible UI components in their mobile applications ([3.3](#)).





Figure 3.3: The Components screen of *AccessibleHub*

Throughout the Components section, code implementations are shared as examples, which developers can easily copy to their clipboard and integrate into their own projects. This hands-on approach allows developers to quickly apply the accessibility principles they learn and see the results in action. It is divided into four subscreens, each focusing on a specific category of components:

- *Buttons and Touchables*: It covers the implementation of accessible buttons and touchable elements (3.4). It provides code examples and best practices for ensuring that these interactive elements are perceivable, operable, and understandable by all users, including those with disabilities;




(a) Button screen - Part 1

(b) Button screen - Part 2

Figure 3.4: Side-by-side view of the two Button and Touchables screen parts

- *Forms:* The subscreen focuses on creating accessible input forms, including text fields, checkboxes, radio buttons, and date/time pickers (3.5). It demonstrates how to properly label form elements, provide instructions and feedback, and ensure that forms can be navigated and completed using various input methods,

such as keyboards and screen readers;



The image shows two side-by-side mobile application screens. The left screen, labeled (a), is titled "Form Controls - Interactive Example" and contains a "Form Demo" section with fields for Name, Email, Gender (radio buttons for Male and Female), Preferred Contact Time (radio buttons for Morning, Afternoon, and Evening), Birth Date (a button to select date), and Appointment Time (Optional) (a button to select time). The right screen, labeled (b), is titled "Code Implementation" and shows the corresponding JSX code for the form components.

Form Demo

Name

Email

Gender

Male Female

Preferred Contact Time

Morning Afternoon Evening

Birth Date

Appointment Time (Optional)

Code Implementation

JSX

Copy

```
<View accessibilityRole="form">

  /* Input Field */
  <Text style={styles.label}>Name</Text>
  <TextInput
    value={formData.name}
    accessibilityLabel="Enter name"
    accessibilityHint="Type full name"
  />

  /* Radio Group */
  <View
    accessibilityRole="radiogroup">
    {['Option 1', 'Option 2'].map((option) => (
      <TouchableOpacity
        key={option}>
        accessibilityRole="radio"
        accessibilityState =
        {{ checked: selectedOption === option }}
      </TouchableOpacity>
    ))}
  </View>
</View>
```

(a) Form screen - Part 1

(b) Form screen - Part 2

Figure 3.5: Side-by-side view of the two Form screen parts

- *Media:* In the Media subscreen, developers learn how to make media content, such as images, videos, and audio, accessible to users with visual or auditory impairments (3.6). This includes providing alternative text for images, captions

for videos, and transcripts for audio content;

Components > Media Content

Media Content - Interactive Example

View images with detailed alternative text and roles. Use the controls below to navigate.

Media Demo



Hide Alt Text

Alternative Text:
A placeholder image (first example)
Role: Interface example

Code Implementation

```
<Image  
    source={require('./path/to/  
image.png')}  
    accessibilityLabel="Detailed  
description of the image content"  
    accessible={true}  
    accessibilityRole="image"  
    style={{  
        width: 300,  
        height: 200,  
        borderRadius: 8,  
    }}  
/>
```

← Components → Media Content ⋮

Code Implementation

JSX

```
<Image  
    source={require('./path/to/  
image.png')}  
    accessibilityLabel="Detailed  
description of the image content"  
    accessible={true}  
    accessibilityRole="image"  
    style={{  
        width: 300,  
        height: 200,  
        borderRadius: 8,  
    }}  
/>
```

Accessibility Features

Aa **Alternative Text**
Descriptive text that conveys the content and function of the image


Speaker icon **Role Announcement**
Screen readers announce the element as an image

Hand icon **Touch Target**
Interactive images should have adequate touch targets

Figure 3.6: Side-by-side view of the two Media screen parts

- *Dialogs:* It covers the creation of accessible modal dialogs, popups, and alerts (3.7). It provides guidance on how to ensure that these elements are properly announced by screen readers, can be easily dismissed, and do not interfere with

the user's ability to navigate the application, maintaining focus management and ensuring clear exit strategies;



(a) Dialog screen - Part 1

(b) Dialog screen - Part 2

Figure 3.7: Side-by-side view of the two Dialog screen parts

- *Advanced:* This particular subscreen covers elements like alerts, sliders, progress bars and tab navigation, analyzing how accessibility may regard different ani-

mated or interactive components for more complex gesture interactions used everyday by users (3.8 and 3.9).

The image shows two side-by-side mobile application screens. Both screens have a blue header bar with a back arrow, the text 'Components > Advanced Components', and a three-dot menu icon.

Screen (a) Advanced screen - Part 1:

- Section Title:** Advanced Accessible Components
- Description:** Demonstrating Tabs/Carousels, Progress Indicators, Alerts/Toasts, and Sliders in one screen
- Section Title:** Tabs & Carousels
- UI Elements:** Three tabs labeled 'Tab One' (blue), 'Tab Two' (gray), and 'Tab Three' (gray). 'Tab One' is highlighted.
- Text:** Current tab: Tab One
- Code:**

```
JSX
const [selectedTab,
setSelectedTab] = useState(0);
const tabs = ['Tab One', 'Tab Two', 'Tab Three'];

<View style={{ flexDirection:
'row' }}>
  <AccessibilityRole="tablist">
    {tabs.map((tab, idx) => (
      <TouchableOpacity
        key={idx}
        accessibilityRole="tab"
        accessibilityLabel={`Select
${tab}`}
        accessibilityState={{ selected:
selectedTab === idx }}
        onPress={() =>
        ...
      }
    )}</AccessibilityRole>
  </View>
```

Screen (b) Advanced screen - Part 2:

- Section Title:** Progress Indicators
- Description:** Current progress: 0%
- UI Elements:** A horizontal progress bar showing 0% completion. Below it are five blue buttons labeled 0%, 25%, 50%, 75%, and 100%.
- Code:**

```
JSX
const [progress, setProgress] =
useState(0);

const progressAnimated = new
Animated.Value(progress);

useEffect(() => {
  Animated.timing(progressAnimated,
{
  toValue: progress,
  duration: 300,
  useNativeDriver: false,
}).start();
}, [progress]);

<Animated.View
  style={{
    height: 10,
    backgroundColor: 'blue',
    width:
progressAnimated.interpolate({
  inputRange: [0, 100],
  outputRange: ['0%', '100%'],
}),
  }>
</Animated.View>
```

Figure 3.8: Side-by-side view of the first two Advanced screen parts




Figure 3.9: Side-by-side view of the second two Advanced screen parts

3. **Best Practices** - Designed to give developers a general understanding of the overarching principles and guidelines for creating accessible mobile applications (3.10).




Figure 3.10: The Best Practices screen of *AccessibleHub*

It is divided into five subscreens, each addressing a key aspect of mobile accessibility:

- *Gestures Tutorial*: This subscreen provides an overview of the various gesture interactions used in mobile applications and how to make them accessible to users with motor impairments or those relying on assistive technologies (3.11). It covers best practices for implementing alternative input methods and providing clear instructions and feedback. These gestures are general, tested to be used universally, both by everyday users and screen reader ones;




Figure 3.11: Side-by-side view of the Gestures Tutorial screen sections

- *Semantics Structure:* Here, developers learn about the importance of using semantic *HTML* and *ARIA_G* roles to convey the structure and meaning of the application's content (3.12). This helps screen readers and other assistive technologies better understand and navigate the application;




Figure 3.12: Side-by-side view of the Semantic Structure screen sections

- **Navigation:** This one focuses on creating accessible navigation patterns, such as menus, tabs, and breadcrumbs (3.13). It provides guidance on how to ensure that navigation elements are properly labeled, can be operated using various input methods, and provide clear feedback to the user, jumping directly to the main

context of a screen and bringing the attention to an element on-screen without distracting him from the action to be completed;




Figure 3.13: Side-by-side view of the Logical navigation screen sections

- *Screen Reader Support:* This subscreen covers the specific considerations for mak-

ing mobile applications compatible with screen readers, such as *VoiceOver* on *iOS* and *TalkBack* on *Android* (3.14). It includes best practices for labeling elements, providing alternative text, and ensuring that the application's content and functionality can be fully accessed and understood using a screen reader;




Figure 3.14: Side-by-side view of the Screen reader support screen sections

CHAPTER 3. ACCESSIBLEHUB: TRANSFORMING MOBILE ACCESSIBILITY GUIDELINES INTO CODE

- *Accessibility Guidelines:* The Accessibility Guidelines subscreen provides an overview of the key accessibility standards to be followed and a general list of principles to incorporate into a project, seeing how they apply to mobile application development (3.15). It helps developers understand the different levels of conformance and how to assess their application's accessibility against these guidelines.




Figure 3.15: Side-by-side view of the WCAG Guidelines screen sections

4. **Framework Comparison** - It provides a side-by-side comparison of the accessibility features and implementation differences between popular mobile development frameworks, such as React Native and Flutter (3.16). This section helps developers understand how accessibility is handled in each framework and provides guidance on leverag-

ing the specific accessibility APIs and tools available in each one. This is divided into different categories, offering a practical and formal overview on how such frameworks are compared with each other. By highlighting the similarities and differences between frameworks, developers can make informed decisions about which framework to use for their accessibility needs and how to optimize their implementations for each platform;




Figure 3.16: The Framework comparison screen of *AccessibleHub*

5. **Tools** - It serves as a central hub for accessing various accessibility-related tools and resources (3.17). This includes links to official documentation, such as the React Native Accessibility *API* reference and the *Flutter Accessibility package* documentation. It also provides quick access to popular accessibility testing tools, such as *Accessibility Scanner* for *Android* and *Accessibility Inspector* for *iOS*. By consolidating these resources in one place, the Tools screen makes it easy for developers to find the information and tools they need to ensure their applications are fully accessible;




Figure 3.17: The Tools screen of *AccessibleHub*

6. **Settings** - Allows users to customize various aspects of the *AccessibleHub* application to suit their individual learning needs and preferences (3.18). This includes options for adjusting the font size, color contrast (including options for gray scale and dark mode), reduced motion settings and others to help users and ensure the application itself is accessible to a wide range of users. It also provides information on how to configure the accessibility settings on the user's device, such as enabling screen readers or adjusting the display settings. By offering these customization options and guidance, the page reinforces the importance of accessibility as an everyday tool, meant to accompany practical user needs in an easy and quick way;




Figure 3.18: The Settings screen of *AccessibleHub*

A key aspect of the Settings screen is its implementation of direct accessibility customization options. Figure 3.19 illustrates the application in different accessibility modes.

CHAPTER 3. ACCESSIBLEHUB: TRANSFORMING MOBILE ACCESSIBILITY GUIDELINES INTO CODE




Figure 3.19: Settings screen with different accessibility modes enabled

Figure 3.20 demonstrates the visual feedback mechanisms when settings are toggled.




Figure 3.20: Visual notifications when accessibility settings are toggled

7. **Instruction and community** - It provides a collaborative learning environment that extends beyond technical implementation (3.21). This section offers developers an opportunity to dive deeper into accessibility knowledge through curated resources and community engagement allowing for easier exploration towards other online resources.

This provides an overview of currently open projects in the field of accessibility, provides advices on specific plugins and offers community examples of interest for a developers to be motivated into the creation of other accessible projects. By providing a platform for continuous learning and collaboration, this screen reinforces the importance of accessibility as a collective effort and a fundamental aspect of modern mobile application development.




Figure 3.21: The Instruction and community screen of *AccessibleHub*

3.3.3 From guidelines to implementation: a screen-based methodology

Accessibility guidelines and standards - most notably the *WCAG_G* and related mobile-specific considerations—establish the formal foundation for inclusive digital design, as discussed in 2.2. These criteria are essential but inherently abstract and can be challenging to implement directly in code. Building on Perinello and Gaggi’s approach focusing solely on post-implementation testing, the methodology presented embeds accessibility into the development process. We do this by analyzing each screen of the application through a structured framework that connects theoretical requirements with practical implementation strategies. The approach to be considered is built following these layers:

1. *Theoretical foundation* – This layer encompasses the abstract principles and success criteria defined by *WCAG*/*MCAG_G*. For example, *WCAG*’s four core principles require that content be presented in ways users can perceive, interact with, and understand. These criteria serve as the benchmark for our analysis;
2. *Implementation pattern* – Here, we translate the abstract requirements into concrete code structures within a mobile development context. In *AccessibleHub*, this involves the systematic use of React Native properties (such as *accessibilityLabel*, *accessibilityRole*, etc.) to ensure that *UI_G* components satisfy the established guidelines;
3. *User interaction flow* – Finally, we consider how end users interact with these components. This includes the behavior of assistive technologies (like screen readers), proper focus management, and the overall usability of the component within its real-world context.

To illustrate this methodology in practice, we first map the *UI* elements of a representative screen to their corresponding semantic roles. Next, we link each component to the relevant *WCAG_G* and *MCAG_G* criteria presented in the previous subsections, noting both the minimum compliance requirements and potential enhancements. Finally, we describe the technical solution—specifically, how React Native accessibility code properties are applied

to meet and exceed these standards. This structured approach not only bridges the gap between abstract guidelines and real-world coding tasks but also sets the stage for the more detailed, screen-by-screen analyses presented in the next section.

3.4 Accessibility implementation guidelines

Having established the overall architecture of *AccessibleHub* and the guiding principles from both *WCAG* and *MCAG*, we now present a screen-by-screen analysis. Each subsection highlights the key *success criteria* addressed, references relevant *mobile-specific considerations*, and demonstrates practical solutions in React Native. Where applicable, we contrast these with Flutter’s approach, building upon the insights from Gaggi and Perinello’s approach [4] analyzing Budai’s Flutter code - following guidelines and then giving advice into introducing new ones. These screens follow the structure presented in Section 3.3.2, analyzed both as main screens and sections.

3.4.1 Home screen

The Home screen serves as the primary entry point of the *AccessibleHub* application. It provides key metrics on accessibility compliance (e.g., number of accessible components, WCAG conformance level) and navigation to sections: *Accessible Components* (Quick Start), *Best Practices*, *Testing Tools*, and the *Framework Comparison*. A screenshot of the interface is shown in Figure 3.22.




Figure 3.22: Side-by-side view of the two Home sections, with metrics and navigation buttons

3.4.1.1 Component inventory and WCAG/MCAG mapping

Table 3.1 provides a formal mapping between the UI components, their semantic roles, the specific WCAG 2.2 criteria they address, and their React Native implementation properties.

Table 3.1: Home screen component-criteria mapping

Component	Semantic Role	WCAG 2.2 Criteria	MCAG Considerations	Implementation Properties
Hero Title	heading	1.4.3 Contrast (AA) 2.4.6 Headings (AA) 1.4.6 Contrast (Enhanced) (AAA)	Text readability on variable screen sizes	accessibility Role="header"
Stats Cards	button	1.4.3 Contrast (AA) 2.5.8 Target Size (AA) 4.1.2 Name, Role, Value (A) 2.4.9 Link Purpose (Link Only) (AAA)	Touch target size	accessibility Role="button", accessibility Label="\${value}% \${type}, tap for details"
Decorative Icons	none	1.1.1 Non-text Content (A)	Reduction of unnecessary focus stops	accessibility-ElementsHidden=true, important-ForAccessibility="no"

Continued on next page

Table 3.1 – continued from previous page

Component	Semantic Role	WCAG 2.2 Criteria	MCAG Considerations	Implementation Properties
Quick Start Button	button	1.4.3 Contrast (AA) 2.5.8 Target Size (AA) 2.5.2 Pointer Cancellation (A) 2.4.10 Section Headings (AAA)	One-handed operation	<code>accessibilityRole = "button", minHeight: 48, minWidth: 150</code>
Feature Cards	button	1.3.1 Info and Relationships (A) 1.4.3 Contrast (AA) 2.5.8 Target Size (AA) 3.2.5 Change on Request (AAA)	Logical grouping	<code>accessibilityRole="button", accessibilityLabel= "\${title}", accessibilityHint="\${hint}"</code>


Continued on next page

Table 3.1 – continued from previous page


Component	Semantic Role	WCAG 2.2 Criteria	MCAG Considerations	Implementation Properties
Modal Dialog	dialog	2.4.3 Focus Order (A) 4.1.2 Name, Role, Value (A) 2.4.8 Location (AAA)	Keyboard trap prevention	accessibility Role="dialog", Focus management implementation
Modal Tabs	tablist	2.4.7 Focus Visible (AA) 4.1.2 Name, Role, Value (A) 2.4.9 Link Purpose (Link Only) (AAA)	Touch interaction	accessibilityRole ="tablist", accessibilityState={{ selected: isActive }}

3.4.1.2 Formal metrics calculation methodology

The Home screen displays three key metrics that provide quantitative measurements of the application's accessibility. These metrics are calculated using a formal methodology defined in the `calculateAccessibilityScore` function within `index.tsx`, as shown by Figure 3.23 and Figure 3.24.



(a) WCAG compliance overview



(b) WCAG compliance details

Figure 3.23: Modal dialogs showing WCAG compliance metrics




Figure 3.24: Modal dialogs showing component accessibility metrics

An overview of the test done with screen reader with the methodology and references adopted is present in Figure 3.25 and Figure 3.26.




Figure 3.25: Modal dialogs showing screen reader testing metrics




Figure 3.26: Modal dialogs showing methodology and references

3.4.1.2.1 Component accessibility score The Component Accessibility Score is calculated using the following formula:

$$\text{ComponentScore} = \left(\frac{\text{AccessibleComponents}}{\text{TotalComponents}} \right) \times 100 \quad (3.1)$$

Where:

- **AccessibleComponents** = Number of components with properly implemented accessibility attributes (20);
- **TotalComponents** = Total number of UI components used in the application (20).

The application implements 20 distinct UI components divided into two primary categories:

- 8 basic UI components (`button`, `text`, `image`, `touchableOpacity`, `scrollView`, `view`, `textInput`, `switch`) that provide essential interaction capabilities;
- 12 complex UI components (`card`, `icon`, `linearGradient`, `modal`, `alert`, `skipLink`, `listItem`, `tabNavigator`, `checklistItem`, `buttonGroup`, `slider`, `datePicker`) that offer more sophisticated user interaction patterns.

Each component is tracked across multiple screens to ensure consistent accessibility implementation throughout the application. For example, the `text` component appears in 5 different screens, while specialized components like `datePicker` are used in specific functional areas. This comprehensive tracking system enables precise measurement of accessibility implementation across the application's component ecosystem.

The implementation in `index.tsx` maintains a formal registry of all UI components, as shown in Listing 3.1.

```

1 // Component registry with accessibility status tracking
2 const componentsRegistry = {
3   // Basic UI components
4   'button': { implemented: true, accessible: true,
5     screens: ['home', 'gestures', 'navigation'] },
6   'text': { implemented: true, accessible: true,
7     screens: ['home', 'guidelines', 'navigation', 'screen-reader',
8       'semantics'] },
9   // ... other basic components
10
11  // Complex UI components
12  'card': { implemented: true, accessible: true,
13    screens: ['home', 'guidelines', 'navigation', 'screen-reader',
14      'semantics'] },
15  'icon': { implemented: true, accessible: true,
16    screens: ['home', 'guidelines', 'screen-reader', 'semantics'] },
17  // ... other complex components
18};
19
20 // Component calculation
21 const componentsTotal = Object.keys(componentsRegistry).length;
22 const accessibleComponents = Object.values(componentsRegistry)
23   .filter(c => c.implemented && c.accessible).length;
24 const componentScore = Math.round((accessibleComponents /
25   componentsTotal) * 100);

```

Listing 3.1: Component registry and calculation

3.4.1.2.2 WCAG compliance score The WCAG compliance score employs a weighted approach that prioritizes fundamental accessibility requirements while acknowledging the aspirational nature of higher-level criteria:

$$\text{WCAGCompliance} = \left(\left(\frac{\text{AAndAAImplemented}}{\text{AAndAACriteria}} \right) \times 0.8 + \left(\frac{\text{AllImplemented}}{\text{AllCriteria}} \right) \times 0.2 \right) \times 100 \quad (3.2)$$

Where:

- **AAndAAImplemented** = Number of Level A and AA success criteria implemented;
- **AAndAACriteria** = Total number of Level A and AA criteria;
- **AllImplemented** = Number of all criteria implemented (including AAA);

- **AllCriteria** = Total number of all criteria across all levels.

This weighted approach acknowledges that Level A and AA criteria represent essential accessibility requirements that must be implemented for basic conformance (80% of the weight), while Level AAA criteria represent more advanced and specialized enhancements (20% of the weight), implemented for the highest standard of accessibility.

To enable more granular analysis, extended variables are introduced to preserve formal criteria and compliance levels reached:

- **CriteriaLevelAMet** = Number of Level A success criteria implemented (25);
- **CriteriaLevelAAMet** = Number of Level AA success criteria implemented (13);
- **CriteriaLevelAAAMet** = Number of Level AAA success criteria implemented (9);
- **LevelACompliance**, **LevelAACompliance**, **LevelAAACompliance** = Percentage of criteria met at each level.

The implementation maintains a comprehensive tracking system for WCAG criteria, as shown in Listing 3.2.

```

1 // WCAG criteria tracking with implementation status
2 const wcagCriteria = {
3   '1.1.1': { level: 'A', implemented: true,
4   name: "Non-text Content" },
5   '1.3.1': { level: 'A', implemented: true,
6   name: "Info and Relationships" },
7   // ... other A and AA criteria
8   '2.4.8': { level: 'AAA', implemented: true,
9   name: "Location" },
10  '2.4.9': { level: 'AAA', implemented: true,
11   name: "Link Purpose (Link Only)" },
12  '2.4.10': { level: 'AAA', implemented: true,
13   name: "Section Headings" },
14  '3.2.5': { level: 'AAA', implemented: true,
15   name: "Change on Request" },
16   // ... other criteria
17 };
18
19 // Simplified calculation for UI display
20 const criteriaValues = Object.values(wcagCriteria);
21 const aAndAACriteria = criteriaValues.filter(c => c.level === 'A' ||
22   c.level === 'AA');
23 const aAndAAImplemented = aAndAACriteria.filter(c =>
24   c.implemented).length;
25 const allImplemented = criteriaValues.filter(c =>
26   c.implemented).length;
27 const allCriteria = criteriaValues.length;
28
29 // 80% based on A & AA, 20% based on overall
30 const wcagCompliance = Math.round(
31   (((aAndAAImplemented / aAndAACriteria.length) * 0.8) +
32   ((allImplemented / allCriteria) * 0.2)) * 100
33 );
34
35 // Detailed tracking (preserved but not displayed in UI)
36 const levelACriteria = criteriaValues.filter(c => c.level ===
37   'A').length;
38 const levelACriteriaMet = criteriaValues
39 .filter(c => c.level === 'A' && c.implemented).length;
40 const levelACompliance = Math.round((levelACriteriaMet /
41   levelACriteria) * 100);
42 // Same for other levels...

```

Listing 3.2: WCAG criteria tracking and calculation

3.4.1.2.3 Screen reader testing score The Screen Reader Testing Score represents empirical testing with VoiceOver (iOS) and TalkBack (Android):

$$\text{TestingScore} = \left(\frac{\text{VoiceOverAvg} + \text{TalkBackAvg}}{2} \right) \times 20 \quad (3.3)$$

Where:

- VoiceOverAvg = Average score from VoiceOver testing across categories (4.34/5);
- TalkBackAvg = Average score from TalkBack testing across categories (4.18/5).

The methodology employs a Likert scale (where 5 represents perfect implementation) across five key categories that represent essential aspects of screen reader interaction:

- *Navigation*: Logical flow and ease of traversing the interface (VoiceOver: 4.5, TalkBack: 4.3)
- *Gestures*: Recognition and consistency of touch gestures (VoiceOver: 4.0, TalkBack: 4.2)
- *Labels*: Clarity and completeness of element descriptions (VoiceOver: 4.5, TalkBack: 4.4)
- *Forms*: Accessibility of input controls and feedback (VoiceOver: 4.2, TalkBack: 4.0)
- *Alerts*: Proper announcement of dialogs and notifications (VoiceOver: 4.5, TalkBack: 4.0)

The scale range of 4.0-4.9 represents "good to excellent" implementation quality, with no score falling below 4.0, indicating that all tested areas meet professional accessibility standards. The multiplication by 20 normalizes the 1-5 scale to a percentage format (0-100%) to align with the other metrics (such scale was chosen arbitrarily in order to be normalized as fairly as possible).

The scores are based on structured testing of five key aspects as shown in Listing 3.3.

```

1 // Screen reader test results from empirical testing
2 const screenReaderTests = {
3   voiceOver: { // iOS
4     navigation: 4.5, // Logical navigation flow
5     gestures: 4.0, // Gesture recognition
6     labels: 4.5, // Label clarity and completeness
7     forms: 4.2, // Form control accessibility
8     alerts: 4.5 // Alert and dialog accessibility
9   },
10  talkBack: { // Android
11    navigation: 4.3,
12    gestures: 4.2,
13    labels: 4.4,
14    forms: 4.0,
15    alerts: 4.0
16  }
17};
18
19 // Testing score calculation
20 const voiceOverScores = Object.values(screenReaderTests.voiceOver);
21 const talkBackScores = Object.values(screenReaderTests.talkBack);
22 const voiceOverAvg = voiceOverScores.reduce((sum, score) =>
23   sum + score, 0) / voiceOverScores.length;
24 const talkBackAvg = talkBackScores.reduce((sum, score) =>
25   sum + score, 0) / talkBackScores.length;
26 const testingScore = Math.round(((voiceOverAvg + talkBackAvg) / 2) *
27   20);

```

Listing 3.3: Screen reader testing results and calculation

3.4.1.2.4 Overall accessibility score The overall Accessibility Score is calculated using weighted components:

$$\begin{aligned}
 \text{OverallScore} = & (\text{ComponentScore} \times 0.35) + (\text{LevelACompliance} \times 0.25) \\
 & + (\text{LevelAACompliance} \times 0.20) + (\text{LevelAAACompliance} \times 0.15) + (\text{TestingScore} \times 0.05)
 \end{aligned} \tag{3.4}$$

This weighting system represents a formal prioritization model that:

- Prioritizes component implementation (35%) as the foundation of accessibility;
- Assigns significant weight to Level A compliance (25%) as essential requirements;
- Values Level AA compliance (20%) as important for broad accessibility;

- Recognizes Level AAA compliance (15%) as enhancing the experience for users with disabilities;
- Includes empirical testing (5%) as a validation measure.

While this weighting system is maintained in the code for methodological rigor, it is intentionally not exposed in the user interface to simplify presentation. This design decision prioritizes clarity for end users while preserving the technical accuracy needed for formal accessibility evaluation.

3.4.1.3 Technical implementation analysis

The code sample in Listing 3.4 shows the key accessibility properties implemented in the Home screen.

```
1 // 1. ScrollView container with proper role and label
2 <ScrollView
3   accessibilityRole="scrollview"
4   accessibilityLabel="AccessibleHub Home screen"
5 >
6 /* 2. Stats section with interactive metrics */
7 <View style={themedStyles.statsContainer}>
8   <View style={themedStyles.statCard}>
9     <TouchableOpacity
10       style={themedStyles.touchableStat}
11       onPress={() => openMetricDetails('component')}
12       accessible
13       accessibilityRole="button"
14       accessibilityLabel={`${value}% ${type}, tap for details`}
15       accessibilityHint={'Shows ${type} details'}
16     >
17       /* 3. Content with accessibilityElementsHidden to prevent
18          redundant announcements */
19       <Text style={themedStyles.statNumber}
20         accessibilityElementsHidden>
21         {accessibilityMetrics.componentCount}
22       </Text>
23       <Text style={themedStyles.statLabel}
24         accessibilityElementsHidden>
25         Components
26       </Text>
27     </TouchableOpacity>
28   </View>
29 </View>
30
31 /* 4. Quick Start button with appropriate sizing for touch
32    targets */
33 <TouchableOpacity
34   style={themedStyles.quickStartCard}
35   onPress={() => router.push('/components')}
36   accessibilityRole="button"
37   accessibilityLabel="Quick start with component examples"
38   accessibilityHint="Navigate to components section"
39 >
40   <View style={themedStyles.cardText}>
41     <Text style={themedStyles.cardTitle}>Quick Start</Text>
42     <Text style={themedStyles.cardDescription}>
43       Explore accessible component examples
44     </Text>
45   </View>
46 </TouchableOpacity>
47 </ScrollView>
```

Listing 3.4: Annotated code sample demonstrating Home screen accessibility properties

3.4.1.4 Screen reader support analysis

Table 3.2 presents results from systematic testing of the Home screen with screen readers on both iOS and Android platforms.

Table 3.2: Home screen screen reader testing results

Test Case	VoiceOver (iOS 16)	TalkBack (Android 14-15)	WCAG Criteria Addressed
Hero Title	✓ Announces “The ultimate accessibility-driven toolkit for developers, heading”	✓ Announces “The ultimate accessibility-driven toolkit for developers, heading”	1.3.1 - Info and Relationships (Level A), 2.4.6 - Headings and Labels (Level AA), 2.4.10 - Section Headings (Level AAA)
Metrics Cards	✓ Announces full label with metrics and hint	✓ Announces full label with metrics and hint	1.3.1 Info and Relationships (Level A), 4.1.2 Name, Role, Value (Level A), 2.4.9 Link Purpose (Link Only) (Level AAA)
Quick Start Button	✓ Announces “Quick start with component examples, button”	✓ Announces “Quick start with component examples, button”	2.4.4 Link Purpose (In Context) (Level A), 4.1.2 Name, Role, Value (Level A), 2.4.9 Link Purpose (Link Only) (Level AAA)

Continued on next page

Table 3.2 – continued from previous page

Test Case	VoiceOver (iOS 16)	TalkBack (Android 14-15)	WCAG Criteria Addressed
Feature Cards	✓ Announces title and hint	✓ Announces title and hint	2.4.4 Link Purpose (In Context) (Level A), 4.1.2 Name, Role, Value (Level A), 2.4.9 Link Purpose (Link Only) (Level AAA)
Modal Dialog Opening	✓ Focus moves to dialog title	✓ Focus moves to dialog title	2.4.3 Focus Order (Level A), 2.4.8 Location (Level AAA)
Modal Tab Navigation	✓ Announces tab selection state	✓ Announces tab selection state	4.1.2 Name, Role, Value (Level A), 3.2.5 Change on Request (Level AAA)
Modal Dialog Closing	✓ Focus returns to triggering element	✗ Occasional focus loss (fixed in v1.0.3)	2.4.3 Focus Order (Level A)

The implementation addresses several key MCAG considerations:

- Swipe optimization:** Decorative elements are marked with `importantForAccessibility="no"` to reduce unnecessary swipes;
- Clear instructions:** The modal tabs implementation provides clear state announcements, ensuring screen reader users understand the current selection;
- Platform-specific adaptations:** The implementation accounts for differences between VoiceOver and TalkBack behavior, as evidenced by the test results;

4. **Enhanced context awareness:** Implementation of AAA criteria like 2.4.8 (Location) and 2.4.9 (Link Purpose) provides enhanced context for users of assistive technologies.

3.4.1.5 Implementation overhead analysis

Table 3.3 quantifies the additional code required to implement accessibility features in the Home screen.

Table 3.3: Accessibility implementation overhead

Accessibility Feature	Lines of Code	Percentage of Total Code ¹	Complexity Impact
Semantic Roles	12 LOC	2.1%	Low
Descriptive Labels	24 LOC	4.3%	Medium
Element Hiding	8 LOC	1.4%	Low
Focus Management	18 LOC	3.2%	Medium
Contrast Handling	16 LOC	2.9%	Medium
Metrics Calculation	84 LOC	15.2%	High
AAA Specific Implementation	26 LOC	4.7%	Medium
Total	188 LOC	33.8%	Medium-High

This analysis reveals that implementing comprehensive accessibility adds approximately 33.8% to the code base of the Home screen, with the metrics calculation system representing the most significant component. The additional implementation for AAA level criteria accounts for 4.7% of the codebase. This overhead is justified by the improved user experience for people with disabilities and the educational value for developers learning to implement accessibility.

¹Calculated as (Feature LOC ÷ Total Home Screen LOC) × 100, where the total lines of code depends on the actual screen code length

3.4.1.6 WCAG conformance by principle

Table 3.4 provides a detailed analysis of WCAG 2.2 compliance by principle, including AAA criteria. The analysis organizes WCAG success criteria into the four fundamental principles of web accessibility: Perceivable, Operable, Understandable, and Robust. This structure helps assess the overall accessibility coverage of the Components screen, highlighting its comprehensive implementation of both required (A, AA) and enhanced (AAA) accessibility features. While AA compliance is typically considered the target standard for most applications, this implementation achieves 100% compliance in three of the four principles, with only a single Perceivable criterion not fully implemented.:.

Table 3.4: WCAG compliance analysis by principle

Principle	Description	Implementation Level	Key Success Criteria
1. Perceivable	Information and UI components must be presentable to users in ways they can perceive	12/15 (80.0%)	1.1.1 Non-text Content (A) 1.3.1 Info and Relationships (A) 1.3.2 Meaningful Sequence (A) 1.3.4 Orientation (AA) 1.4.3 Contrast (Minimum) (AA) 1.4.6 Contrast (Enhanced) (AAA)

Continued on next page

Table 3.4 – continued from previous page

Principle	Description	Implementation Level	Key Success Criteria
2. Operable	UI components and navigation must be operable	19/22 (86.4%)	2.1.1 Keyboard (A) 2.4.3 Focus Order (A) 2.4.7 Focus Visible (AA) 2.5.2 Pointer Cancellation (A) 2.5.8 Target Size (Minimum) (AA) 2.4.8 Location (AAA) 2.4.9 Link Purpose (Link Only) (AAA) 2.4.10 Section Headings (AAA)
3. Understandable	Information and operation of UI must be understandable	9/17 (52.9%)	3.1.1 Language of Page (A) 3.2.1 On Focus (A) 3.2.3 Consistent Navigation (AA) 3.2.4 Consistent Identification (AA) 3.3.2 Labels or Instructions (A) 3.2.5 Change on Request (AAA)

Continued on next page

Table 3.4 – continued from previous page

Principle	Description	Implementation Level	Key Success Criteria
4. Robust	Content must be robust enough to be interpreted by a wide variety of user agents	3/3 (100%)	4.1.1 Parsing (A) 4.1.2 Name, Role, Value (A) 4.1.3 Status Messages (AA)

3.4.1.7 Mobile-specific considerations

The Home screen implementation addresses several mobile-specific accessibility considerations beyond standard WCAG requirements:

1. **Touch target sizing:** All interactive elements maintain minimum dimensions of 48×48 , exceeding the WCAG 2.5.8 requirement of $24 \times 24\text{px}$ and addressing the mobile-specific need for larger touch targets;
2. **Reduced motion support:** The implementation respects the device's reduced motion settings and provides an in-app toggle, addressing vestibular disorders that are particularly relevant in mobile contexts;
3. **Dark mode support:** The application's theming system adapts to both light and dark modes, addressing the mobile-specific need for readability in various lighting conditions;
4. **Screen reader gesture optimization:** The implementation carefully manages focus to ensure efficient navigation with touch gestures, as shown in the screen reader testing results;
5. **One-handed operation:** The layout places primary interactive elements within reach of a thumb during one-handed use, a critical mobile accessibility consideration not explicitly covered by WCAG.

3.4.1.8 Beyond WCAG: metrics-driven accessibility guidelines

The Home screen implementation highlights several accessibility principles that extend beyond standard WCAG requirements, specifically addressing quantitative accessibility evaluation in mobile applications:

1. **Comprehensive metrics visualization:** Accessibility compliance are quantified and presented in a transparent, understandable format. The Home screen implements this through dedicated metric cards with clear visual indicators of implementation status, moving beyond binary compliance to represent different degrees of accessibility achievement;
2. **Multi-dimensional evaluation framework:** Accessibility assessment consider multiple dimensions including component implementation, standards compliance, and empirical testing. This weighted approach, implemented in the metrics calculation system, recognizes that true accessibility extends beyond technical conformance to include real-world usability;
3. **Transparency in methodology:** Applications should provide clear documentation of accessibility evaluation methodology including test devices, standards versions, and measurement approaches. The modal details system implements this principle by exposing the entire evaluation framework to users, creating accountability in accessibility claims;
4. **Academic grounding principle:** Accessibility implementations benefit from explicit connection to peer-reviewed research and formal standards. The References tab implements this by connecting implementation practices to specific academic papers and standards documentation;
5. **Progressive disclosure of complexity:** Technical accessibility details should be organized in layers of increasing complexity, allowing users to access the appropriate level of detail for their needs. The tabbed modal system implements this by separating overview information from detailed implementation specifics.

These guidelines extend WCAG by formalizing the quantitative evaluation of accessibility status, providing developers with concrete metrics to track implementation progress rather than treating accessibility as a binary, achieved/not-achieved state. Additionally, the incorporation of Level AAA criteria demonstrates a commitment to achieving the highest possible level of accessibility, recognizing that while AAA compliance may not be required for all components, striving toward these aspirational goals leads to a better experience for all users.

3.4.2 Accessible components main screen

The Accessible components screen serves as a catalog of reusable accessibility patterns organized by component type. It provides developers with access to implementations of common UI elements with accessibility features properly integrated. Each component category includes implementation examples, best practices, and copy-ready code samples. The screen functions as an educational index, directing developers to detailed implementations of specific accessible components. Figure 3.27 shows the Components screen interface.




Figure 3.27: Side-by-side view of the Components screen sections, showing component categories

3.4.2.1 Component inventory and WCAG/MCAG mapping

Table 3.5 provides a formal mapping between the UI components, their semantic roles, the specific WCAG 2.2 and MCAG criteria they address, and their React Native implementation properties.

Table 3.5: Components screen component-criteria mapping

Component	Semantic Role	WCAG 2.2 Criteria	MCAG Considerations	Implementation Properties
Hero Title	heading	1.4.3 Contrast (AA) 2.4.6 Headings (AA) 1.4.6 Contrast (Enhanced) (AAA)	Text readability on variable screen sizes	accessibilityRole="header"
Component Cards	button	1.4.3 Contrast (AA) 2.5.8 Target Size (AA) 4.1.2 Name, Role, Value (A) 2.4.4 Link Purpose (A) 2.4.9 Link Purpose (AAA)	Touch target size Meaningful labels Single finger operation	accessibilityRole="button", accessibilityLabel=, onPress=handle- ComponentPress
Badges (Essential, Complex, etc.)	text	1.4.3 Contrast (AA) 1.3.1 Info and Relationships (A)	Descriptive labeling Non-interactive elements	Part of parent button's accessibilityLabel

Continued on next page

Table 3.5 – continued from previous page

Component	Semantic Role	WCAG 2.2 Criteria	MCAG Considerations	Implementation Properties
Decorative Icons	none	1.1.1 Non-text Content (A)	Reduction of unnecessary focus stops	accessibility-ElementsHidden=true
Breadcrumb Navigation	navigation	2.4.4 Link Purpose (A) 2.4.8 Location (AAA) 3.2.3 Consistent Navigation (AA)	Context retention Current location	accessibility-Role="button", accessibility-Label="Go to \${label}"
Drawer Menu	menu	2.4.3 Focus Order (A) 4.1.2 Name, Role, Value (A) 3.2.3 Consistent Navigation (AA)	Keyboard trap prevention Persistent navigation	accessibility-Role="menu", accessibility-Label="Main navigation menu"
Drawer Menu Items	menuitem	2.4.7 Focus Visible (AA) 4.1.2 Name, Role, Value (A)	Touch interaction Current location	accessibility-Role="menuitem", accessibility-State={{selected: isActive}}

3.4.2.2 Navigation and orientation analysis

The Components screen implements a comprehensive navigation structure that addresses both WCAG 2.4 (Navigable) and MCAG considerations for mobile devices. This structure includes three key elements that work together to provide clear orientation for all users:

3.4.2.2.1 Breadcrumb implementation The application as shown in Figure 3.28 includes a hierarchical breadcrumb system in the header. This addresses WCAG 2.4.8 Location (Level AAA) by providing explicit path information. The breadcrumb implementation:

1. Displays the current location in the application hierarchy;
2. Provides interactive elements to navigate to parent screens;
3. Uses consistent visual styling to indicate the current position;
4. Implements proper focus management between screens.




Figure 3.28: Drawer navigation showing breadcrumb implementation in header

The breadcrumb is implemented in Listing 3.5 with proper semantic roles and accessibility labels to ensure screen reader compatibility.

```

1 <View style={styles.breadcrumbContainer}>
2   <TouchableOpacity
3     onPress={() => router.replace(`/${mapping.parentRoute}`)}
4     accessibilityRole="button"
5     accessibilityLabel={'Go to ${mapping.parentLabel}'}
6     style={{
7       padding: 8,
8       minWidth: 40,
9       minHeight: 44,
10      justifyContent: 'center',
11      backgroundColor: 'rgba(255, 255, 255, 0.1)',
12      borderRadius: 4
13    }}
14  >
15    <Text style={[styles.breadcrumbText, {fontWeight: 'normal'}]}>
16      {mapping.parentLabel}
17    </Text>
18  </TouchableOpacity>
19  <Ionicons
20    name="chevron-forward"
21    size={16}
22    color={HEADER_TEXT_COLOR}
23    style={{marginHorizontal: 4}}
24    importantForAccessibility="no"
25    accessibilityElementsHidden
26  />
27  <Text
28    style={[styles.breadcrumbText, {fontWeight: 'bold',
29      textDecorationLine: 'underline'}]}
30    accessibilityLabel={'Current screen: ${mapping.title}'}
31  >
32    {mapping.title}
33  </Text>
34</View>

```

Listing 3.5: Breadcrumb implementation with accessibility properties

3.4.2.2.2 Drawer navigation The drawer navigation provides consistent access to main application sections while addressing several key accessibility requirements:

- 1. Announcement of state changes:** The implementation announces drawer open/- close states to screen readers using `AccessibilityInfo.announceForAccessibility;`
- 2. Clear menu role:** The drawer container is properly identified with `accessibilityRole="menu";`
- 3. Selection state indication:** Active items visually indicate selection state and commu-

nicate this state to screen readers with `accessibilityState={{selected: isActive}}`;

4. **Proper touch target sizing:** All interactive elements maintain minimum dimensions of 44dp, making them easily targetable;
5. **Element hiding for decorative content:** Footer content is marked with `importantForAccessibility="no"` to prevent unnecessary screen reader interaction.

3.4.2.2.3 Component cards Each component card implements a consistent pattern that provides both visual organization and semantic structure:

1. **Comprehensive accessibility labels:** Each card's `accessibilityLabel` combines multiple information pieces (title, description, complexity) to provide context without requiring navigation through child elements;
2. **Hidden decorative icons:** All decorative icons use `accessibilityElementsHidden` to reduce unnecessary focus stops;
3. **Navigation announcement:** The `handleComponentPress` function announces the navigation action via `AccessibilityInfo.announceForAccessibility`.

This multi-layered navigation approach creates a coherent mental model for all users, including those using assistive technologies, addressing WCAG 2.4.1 Bypass Blocks (Level A) by providing multiple ways to access content.

3.4.2.3 Technical implementation analysis

The code sample present in Listing 3.6 demonstrates the key accessibility properties implemented in the Components screen.

CHAPTER 3. ACCESSIBLEHUB: TRANSFORMING MOBILE ACCESSIBILITY GUIDELINES INTO CODE

```
1  /* 1. Hero section with semantic heading */
2  <View style={themedStyles.heroCard}>
3      <Text style={themedStyles.heroTitle} accessibilityRole="header">
4          Accessibility Components
5      </Text>
6      <Text style={themedStyles.heroSubtitle}>
7          Interactive examples of accessible React Native components with
8          code samples and best practices
9      </Text>
10     </View>
11
12  /* 2. Component card with comprehensive accessibility label */
13  <TouchableOpacity
14      style={themedStyles.card}
15      onPress={() => handleComponentPress('/components/button', 'Buttons
16          & Touchables')}
17      accessibilityRole="button"
18      accessibilityLabel="Buttons and Touchables component. Create
19          accessible
20          touch targets with proper sizing and feedback. Essential
21          component type."
22  >
23      <View style={themedStyles.cardHeader}>
24          /* 3. Icon wrapper with accessibility hiding to prevent
25              redundant focus */
26          <View style={themedStyles.iconWrapper}>
27              <Ionicons
28                  name="radio-button-on-outline"
29                  size={24}
30                  color={colors.primary}
31                  accessibilityElementsHidden
32              />
33          </View>
34          <View style={themedStyles.cardContent}>
35              /* 4. Card content - hidden from screen readers as individual
36                  elements */
37              <View style={themedStyles.cardTitleRow}>
38                  <View style={themedStyles.titleArea}>
39                      <Text style={themedStyles.cardTitle}>Buttons & Touchables</Text>
40                  </View>
41                  <View style={themedStyles.badge}>
42                      <Text style={themedStyles.badgeText}>Essential</Text>
43                  </View>
44              </View>
45              <Text style={themedStyles.cardDescription}>
46                  Create accessible touch targets with proper sizing and
47                  feedback
48              </Text>
49          </View>
50      </View>
51  </TouchableOpacity>
```

Listing 3.6: Annotated code sample demonstrating Components screen accessibility properties

The implementation of the Components screen addresses several important accessibility considerations:

1. **Reduction of "garbage interactions":** Decorative elements (icons, chevrons) are properly hidden from screen readers using `accessibilityElementsHidden` to reduce unnecessary swipes;
2. **Comprehensive navigation labels:** Component cards provide detailed accessibility labels that include category, description, and complexity level, ensuring screen reader users get complete information before committing to navigation;
3. **Screen announcements:** The implementation uses `AccessibilityInfo.announceForAccessibility` to inform users about screen changes proactively;
4. **Consistent structure:** Each component card follows the same pattern, creating a predictable interaction model;
5. **Enhanced contrast ratios:** The implementation meets WCAG 1.4.6 Contrast (Enhanced) (Level AAA) criteria with contrast ratios exceeding 7:1 for normal text and 4.5:1 for large text.

3.4.2.4 Screen reader support analysis

Table 3.6 presents results from systematic testing of the Components screen with screen readers on both iOS and Android platforms.

Table 3.6: Components screen reader testing results

Test Case	VoiceOver (iOS 16)	TalkBack (Android 14-15)	WCAG Criteria Addressed
Hero Title	✓ Announces “Accessibility Components, heading”	✓ Announces “Accessibility Components, heading”	1.3.1 - Info and Relationships (Level A), 2.4.6 - Headings and Labels (Level AA)
Component Card	✓ Announces full component description with purpose and complexity	✓ Announces full component description with purpose and complexity	2.4.4 Link Purpose (In Context) (Level A), 4.1.2 Name, Role, Value (Level A), 2.4.9 Link Purpose (Link Only) (Level AAA)
Decorative Icons	✓ Not focused or announced	✓ Not focused or announced	1.1.1 Non-text Content (Level A), 2.4.1 Bypass Blocks (Level A)
Breadcrumb Navigation	✓ Announces parent and current location	✓ Announces parent and current location	2.4.4 Link Purpose (In Context) (Level A), 2.4.8 Location (Level AAA)
Drawer Opening	✓ Announces “Navigation menu opened”	✓ Announces “Navigation menu opened”	4.1.3 Status Messages (Level AA)
Drawer Menu Items	✓ Announces item name and selection state	✓ Announces item name and selection state	4.1.2 Name, Role, Value (Level A)

Continued on next page

Table 3.6 – continued from previous page

Test Case	VoiceOver (iOS 16)	TalkBack (Android 14-15)	WCAG Criteria Addressed
Navigation between Screens	✓ Announces destination screen	✓ Announces destination screen	3.2.5 Change on Request (Level AAA)

The implementation addresses several key MCAG considerations specific to mobile platforms:

1. **Touch target optimization:** All interactive elements exceed the minimum recommendation of $44 \times 44\text{dp}$, implementing MCAG best practices for touch interactions that accommodate users with motor control limitations and varying finger sizes;
2. **Swipe minimization:** Decorative elements are marked with `accessibilityElementsHidden=true` to reduce unnecessary swipes, eliminating what accessibility experts call "garbage interactions" that add no value to the screen reader experience and increase navigation time;
3. **Orientation cues:** Breadcrumb implementation provides consistent spatial orientation cues that help users understand their location in the application's information architecture, addressing mobile-specific challenges of limited viewport context;
4. **State announcements:** Changes in application state (drawer opening/closing, screen navigation) are explicitly announced using `AccessibilityInfo.announceForAccessibility`, providing crucial feedback on dynamic content changes within the constrained mobile interface;
5. **Thumb-zone design:** Interactive elements are positioned within the natural thumb zone for one-handed operation, implementing mobile ergonomic principles that aren't explicitly covered in WCAG but are crucial for mobile accessibility;

6. **Content adaptability:** Component cards implement flexible layouts that adapt to various text size preferences (AAA criterion 1.4.10 Reflow), ensuring readability when users change their system text size settings.

3.4.2.5 Implementation overhead analysis

Table 3.7 quantifies the additional code required to implement accessibility features in the Components screen.

Table 3.7: Components screen accessibility implementation overhead

Accessibility Feature	Lines of Code	Percentage of Total Code	Complexity Impact
Semantic Roles	15 LOC	2.6%	Low
Descriptive Labels	28 LOC	4.9%	Medium
Element Hiding	18 LOC	3.2%	Low
Focus Management	22 LOC	3.9%	Medium
Contrast Handling	14 LOC	2.5%	Medium
Announcements	12 LOC	2.1%	Low
Breadcrumb Implementation	42 LOC	7.4%	High
Drawer Accessibility	35 LOC	6.2%	High
AAA-specific Enhancements	20 LOC	3.5%	Medium
Total	206 LOC	36.3%	Medium-High

This analysis reveals that implementing comprehensive accessibility adds approximately 36.3% to the code base of the Components screen, slightly higher than the Home screen due to the addition of breadcrumb navigation, drawer accessibility features, and AAA-level enhancements. The AAA-specific enhancements include implementing enhanced contrast ratios (1.4.6), ensuring proper section headings (2.4.10), and supporting adaptive layouts for

text resizing (1.4.10).

3.4.2.6 WCAG conformance by principle

Table 3.8 provides a detailed analysis of WCAG 2.2 compliance by principle:

Table 3.8: Components screen WCAG compliance analysis by principle

Principle	Description	Implementation Level	Key Success Criteria
1. Perceivable	Information and UI components must be presentable to users in ways they can perceive	13/14 (92.8%)	1.1.1 Non-text Content (A) 1.3.1 Info and Relationships (A) 1.4.3 Contrast (Minimum) (AA) 1.4.6 Contrast (Enhanced) (AAA) 1.4.10 Reflow (AA)
2. Operable	UI components and navigation must be operable	18/18 (100%)	2.4.3 Focus Order (A) 2.4.6 Headings and Labels (AA) 2.4.8 Location (AAA) 2.4.9 Link Purpose (Link Only) (AAA) 2.4.10 Section Headings (AAA) 2.5.8 Target Size (Minimum) (AA)

Continued on next page

Table 3.8 – continued from previous page

Principle	Description	Implementation Level	Key Success Criteria
3. Understandable	Information and operation of UI must be understandable	10/10 (100%)	3.2.3 Consistent Navigation (AA) 3.2.4 Consistent Identification (AA) 3.2.5 Change on Request (AAA) 3.3.2 Labels or Instructions (A)
4. Robust	Content must be robust enough to be interpreted by a wide variety of user agents	3/3 (100%)	4.1.1 Parsing (A) 4.1.2 Name, Role, Value (A) 4.1.3 Status Messages (AA)

3.4.2.7 Mobile-specific considerations

The Components screen implementation addresses several mobile-specific accessibility considerations beyond standard WCAG requirements:

1. **Touch target sizing:** All interactive elements maintain minimum dimensions of 44×44dp, exceeding the WCAG 2.5.8 requirement of 24×24px and addressing the mobile-specific need for larger touch targets;
2. **Swipe efficiency:** The screen implements an optimized focus order with decorative elements hidden from screen readers, reducing the number of swipes required to navigate the content—a critical consideration for mobile screen reader users that significantly improves navigation efficiency;

3. **Visual hierarchy reinforcement:** The implementation uses consistent visual patterns (icons, badges, card layouts) that reinforce the information hierarchy, helping users with cognitive disabilities understand content organization on smaller screens;
4. **Context retention:** The breadcrumb implementation helps users maintain context when navigating between screens, addressing the mobile-specific challenge of limited viewport size and the resulting loss of visual context;
5. **Single-hand operation:** Interactive elements are positioned within the natural thumb zone for one-handed operation, a mobile-specific consideration not explicitly covered by WCAG but crucial for mobile accessibility;
6. **Rotation adaptation:** The layout adapts seamlessly to both portrait and landscape orientations, implementing WCAG 1.3.4 Orientation (AA) to ensure usability regardless of device orientation.

3.4.2.8 Breadcrumb implementation analysis

A formal analysis of the breadcrumb feature's accessibility impact reveals significant benefits for users with diverse accessibility needs.

1. **Structural navigation:** Breadcrumbs provide an explicit representation of the application's hierarchical structure, helping users with cognitive disabilities understand their location within the application;
2. **Focus reduction:** By offering direct navigation to parent screens, breadcrumbs reduce the number of focus stops required to navigate backward, benefiting screen reader users;
3. **Visual reinforcement:** The visual breadcrumb trail complements the semantic structure, providing redundant cues that benefit users with different accessibility needs;
4. **Consistent orientation:** Breadcrumbs create a consistent orientation mechanism across all screens, supporting users who rely on predictable navigation patterns.

3.4.2.8.1 Implementation considerations The breadcrumb implementation required careful consideration of several accessibility factors:

1. **Interactive vs. static elements:** Only the parent screen link is interactive, while the current screen indicator is non-interactive text, preventing unnecessary focus stops;
2. **Visual differentiation:** Current location is visually distinguished with bold text and underline, with a contrast ratio of 4.8:1 against the header background, meeting enhanced contrast requirements (AAA);
3. **Appropriate semantic roles:** Parent links use `accessibilityRole="button"` with clear labels indicating navigation purpose;
4. **Focus management:** When navigating via breadcrumbs, focus is properly transferred to the destination screen's main content, preventing focus trapping;
5. **Consistent announcement:** The implementation ensures screen readers consistently announce both the parent link and current location, providing complete contextual information.

This implementation represents a comprehensive accessibility solution that benefits all users while specifically addressing mobile navigation challenges unique to handheld touch devices.

3.4.2.9 Beyond WCAG: component categorization guidelines

The Components screen defines several accessibility principles specifically focused on organizing and categorizing interface elements to promote systematic accessibility implementation:

1. **Feature-oriented grouping:** Accessibility features are grouped by functional similarity rather than WCAG criteria, creating more intuitive implementation pathways. The Components screen implements this by organizing related controls together (e.g., "Buttons & Touchables") regardless of which specific WCAG criteria they address;

2. **Progressive implementation pathway:** Components are organized in a sequence that builds accessibility knowledge progressively, beginning with fundamental elements before introducing more complex patterns. The Components screen implements this through its hierarchical organization from basic elements (buttons) to complex patterns (dialogs, navigation);
3. **Cross-cutting feature indication:** Key accessibility features that apply across multiple component types should be visually highlighted to reinforce their importance. The feature icons within each component card implement this by consistently identifying common accessibility considerations (e.g., touch target sizing, focus management);
4. **Transition announcement principle:** Navigation between component categories should be explicitly announced to assist screen reader users in maintaining context. The Components screen implements this through the `announceForAccessibility` announcements during navigation;
5. **Contextual documentation integration:** Each component implementation include direct references to relevant accessibility guidelines, helping developers understand not just how to implement accessibility features but why they matter. The code samples in each component detail screen implement this by including explanatory comments that connect implementation choices to specific WCAG success criteria.

3.4.3 Accessible components section summary

From this section onwards, a comprehensive summary is retained for each of the screens presented, keeping the details of tables and general data for more immediate comparison. For comprehensive, screen-by-screen analysis, readers are directed to the extended technical appendix available at [AccessibleHub Extended Screen Analysis](#). The Accessible Components section forms the core educational element of *AccessibleHub*, providing practical implementations of accessibility patterns across five representative component categories: buttons and touchables, forms, dialogs, media content, and advanced components. Each screen demonstrates implementation techniques according to standard Web Content Accessibility

Guidelines (WCAG) and Mobile Content Accessibility Guidelines (MCAG), providing both functional examples and educational code snippets.

3.4.3.1 Implementation overhead analysis

A primary concern for developers implementing accessibility is the additional code overhead required. Table 3.9 presents the quantitative analysis of the code overhead for the buttons screen, representing the most fundamental component type.

Table 3.9: Buttons screen accessibility implementation overhead

Accessibility Feature	Lines of Code	Percentage of Total	Complexity Impact
Semantic Roles	10 LOC	2.2%	Low
Descriptive Labels	14 LOC	3.1%	Low
Element Hiding	12 LOC	2.7%	Low
Status Announcements	8 LOC	1.8%	Low
Touch Target Sizing	6 LOC	1.3%	Low
Modal Accessibility	10 LOC	2.2%	Medium
Total	60 LOC	13.3%	Low

This analysis reveals that for basic components like buttons, implementing comprehensive accessibility features adds approximately 13.3% to the codebase with minimal complexity impact. The primary contributors to this overhead are descriptive labels and semantic role assignments, which together account for over 5% of the implementation.

Table 3.10: WCAG criteria implementation by component type

WCAG Success Criteria	Buttons	Forms	Dialogs	Media	Advanced
1.1.1 Non-text Content (A)	✓	✓	✓	✓	✓
1.3.1 Info and Relationships (A)	✓	✓	✓	✓	✓
1.4.3 Contrast (AA)	✓	✓	✓	✓	✓
2.4.3 Focus Order (A)	✗	✓	✓	✗	✓
2.4.6 Headings (AA)	✓	✓	✓	✓	✓
2.5.5 Target Size (Enhanced) (AAA)	✓	✓	✓	✗	✓
2.5.8 Target Size (AA)	✓	✓	✓	✓	✓
3.2.5 Change on Request (AAA)	✗	✓	✓	✓	✓
3.3.1 Error Identification (A)	✗	✓	✗	✗	✗
3.3.5 Help (AAA)	✗	✓	✗	✗	✗
3.3.6 Error Prevention (AAA)	✗	✓	✗	✗	✗
4.1.2 Name, Role, Value (A)	✓	✓	✓	✓	✓
4.1.3 Status Messages (AA)	✓	✓	✓	✓	✓
Total A/AA Implementation	7/9	9/9	8/9	7/9	8/9
Total AAA Implementation	1/3	3/3	2/3	1/3	2/3

Table 3.11: Legend for WCAG criteria implementation colors

Color	Meaning
✓	A-level criteria implemented
✓	AA-level criteria implemented
✓	AAA-level criteria implemented
✗	Criteria not implemented

Key patterns identified in this analysis include:

1. Core A-level criteria (1.1.1 Non-text Content, 1.3.1 Info and Relationships, 4.1.2 Name, Role, Value) are implemented across all component types;
2. AA-level compliance is consistently high, with most components implementing all applicable AA criteria;
3. AAA-level implementation varies significantly, with forms achieving the highest level of AAA compliance (3/3 applicable criteria);
4. Component-specific criteria like 3.3.1 Error Identification are implemented only where directly applicable.

3.4.3.2 Implementation overhead comparison

The overhead required for accessibility implementation varies significantly by component complexity. Table 3.12 presents this comparative analysis across the five component types.

Table 3.12: Accessibility implementation overhead by component type

Component Type	Lines of Code	Percentage Overhead	Complexity Impact	Primary Contributors
Buttons	60	13.3%	Low	Labels, Roles
Forms	153	21.5%	Medium	State, Labels, Errors
Dialogs	94	16.2%	Medium	Focus Management
Media	68	12.7%	Low	Alt Text, Controls
Advanced	183	22.7%	High	Slider Controls, Announcements

This comparison reveals several important implementation patterns:

1. A direct correlation exists between component interaction complexity and accessibility implementation overhead;

2. Simple, static components like media content require the lowest overhead (12.7%), primarily for alternative text;
3. Components with complex state management and alternative interaction patterns (forms, advanced components) require significantly higher overhead (21-23%);
4. Components requiring focus management (dialogs) fall in the middle range (16.2%);
5. Even for the most complex components, the accessibility implementation overhead remains below 25% of the total codebase.

The Accessible Components section demonstrates that implementing comprehensive accessibility features across diverse component types typically requires a 12-23% code overhead, with complexity scaling according to the interaction patterns involved. This relatively modest overhead delivers significant improvements in usability for users relying on assistive technologies, making a compelling case for incorporating accessibility as a core development consideration rather than an optional enhancement.

More detailed analysis of each component screen, including code listings, implementation patterns, and screen reader compatibility findings, can be found in the Technical Appendix .

3.4.4 Best practices section summary

The Best practices screens provide educational content on key accessibility implementation patterns, divided into five specialized areas: WCAG Guidelines, Semantic Structure, Gesture Tutorial, Screen Reader Support, and Logical Focus Order. Each screen demonstrates proper implementation techniques while serving as both functional examples and educational references.

3.4.4.1 Implementation overhead analysis

Implementing accessibility features in educational screens adds measurable but manageable overhead to the development process. Table 3.13 quantifies this overhead across the five specialized screens.

Table 3.13: Best practices screens accessibility implementation overhead

Screen Type	Lines of Code	Percentage Overhead	Complexity Impact	Primary Contributors
WCAG Guidelines	42	10.8%	Low	Screen Reader Hiding, Semantic Roles
Semantic Structure	68	15.2%	Medium	Content Hierarchy, ARIA Roles
Gesture Tutorial	103	22.5%	High	Screen Reader Detection, Custom Actions
Screen Reader Support	89	17.4%	Medium	Platform Adaptations, Example Code
Logical Focus Order	74	16.3%	Medium	Skip Links, Focus Management

This analysis reveals several important implementation patterns:

1. The Gesture Tutorial screen requires the highest overhead (22.5%) due to complex interaction patterns and adaptations for screen reader users;
2. Screens with primarily static content (WCAG Guidelines) require substantially less accessibility overhead (10.8%);
3. Focus management and keyboard navigation features contribute significantly to implementation complexity in the Logical Focus Order screen;
4. Even with extensive educational content, accessibility overhead remains below 25% across all screens.

3.4.4.2 WCAG criteria implementation

The Best practices screens implement accessibility features addressing multiple WCAG 2.2 conformance levels. Table 3.14 analyzes the implementation by screen type.

Table 3.14: WCAG criteria implementation by best practices screen type

WCAG Success Criteria	WCAG Guidelines	Semantic Structure	Gesture Tutorial	Screen Reader	Focus Order
1.1.1 Non-text Content (A)	✓	✓	✓	✓	✓
1.3.1 Info and Relationships (A)	✓	✓	✓	✓	✓
1.4.3 Contrast (AA)	✓	✓	✓	✓	✓
2.1.1 Keyboard (A)	✗	✗	✓	✓	✓
2.4.3 Focus Order (A)	✗	✓	✓	✓	✓
2.4.6 Headings (AA)	✓	✓	✓	✓	✓
2.4.10 Section Headings (AAA)	✓	✓	✗	✓	✗
2.5.2 Pointer Cancellation (A)	✗	✗	✓	✗	✗
2.5.5 Target Size (Enhanced) (AAA)	✓	✓	✓	✓	✓
2.5.8 Target Size (AA)	✓	✓	✓	✓	✓
3.2.5 Change on Request (AAA)	✓	✓	✓	✓	✓
3.3.2 Labels or Instructions (A)	✓	✓	✓	✓	✓
4.1.2 Name, Role, Value (A)	✓	✓	✓	✓	✓
4.1.3 Status Messages (AA)	✓	✓	✓	✓	✓
Total A/AA Implementation	5/8	6/8	8/8	7/8	7/8
Total AAA Implementation	3/3	3/3	2/3	3/3	2/3

Key patterns identified in this analysis include:

1. All screens implement core A-level criteria (1.1.1 Non-text Content, 1.3.1 Info and Relationships, 4.1.2 Name, Role, Value);

Table 3.15: Legend for WCAG criteria implementation colors

Color	Meaning
✓	A-level criteria implemented
✓	AA-level criteria implemented
✓	AAA-level criteria implemented
✗	Criteria not implemented

2. The Gesture Tutorial screen achieves the highest A/AA compliance level (8/8) due to its comprehensive implementation of interaction patterns;
3. AAA-level criteria implementation is notably strong across all screens, with three screens implementing all applicable AAA criteria;
4. Keyboard accessibility (2.1.1) is implemented only in screens with complex interaction patterns, highlighting an area for potential improvement in the more static screens.

3.4.4.3 Screen reader compatibility analysis

Empirical testing with screen readers on both major mobile platforms reveals important patterns in accessibility implementation. Table 3.21 presents key findings from this analysis.

Table 3.16: Best practices screens screen reader testing highlights

Screen Type	Key Accessibility Features	Screen Reader Behavior
WCAG Guidelines	Element Hiding, Semantic Structure	Icons properly hidden, consistent heading hierarchy announced
Semantic Structure	Role Assignments, Hierarchical Headings	Proper heading levels announced, landmarks communicated
Gesture Tutorial	Screen Reader Detection, Alternative Actions	Screen reader-specific instructions provided, custom actions supported
Screen Reader Support	Platform-Specific Adaptations, Code Examples	Platform detection informs appropriate guidance, examples properly labeled
Focus Order	Skip Links, Focus Management	Skip links operational, logical tab order maintained

These findings demonstrate several effective accessibility implementation patterns:

1. Screen reader detection enables adaptive experiences tailored to assistive technology users;
2. Proper element hiding streamlines navigation and reduces cognitive load;
3. Implementation of custom actions provides alternative input methods when standard gestures are unavailable;
4. Logical focus management enables efficient keyboard and screen reader navigation.

3.4.4.4 Implementation techniques comparison

Analysis of the implementation techniques across the best practices screens reveals distinct approaches to addressing common accessibility challenges. Table 3.17 compares these techniques.

Table 3.17: Implementation techniques comparison across best practices screens

Accessibility Challenge	Implementation Technique	Screen Examples
Non-visual Access	<code>accessibilityLabel</code> , <code>accessibilityRole</code> , <code>accessibilityHint</code>	All screens implement these properties consistently
Decorative Elements	<code>accessibilityElements</code> <code>Hidden</code> , <code>importantFor Accessibility</code>	Guidelines screen for icons, Screen Reader screen for platform icons
Screen Reader Adaptation	Screen reader detection, conditional rendering	Gesture Tutorial provides alternative interaction patterns
Interactive Elements	<code>accessibilityState</code> , <code>accessibilityActions</code>	Gesture Tutorial demonstrates custom actions for alternative input
Navigation Structure	Skip links, focus management	Logical Focus Order demonstrates programmatic focus control

The implementation comparison reveals robust patterns that can be applied across diverse interface types:

1. Core accessibility properties are implemented consistently across all screens;
2. Screen reader adaptations provide equivalent functionality through alternative interaction patterns;
3. Skip links enable efficient navigation of complex content structures;
4. Custom actions extend screen reader capabilities beyond standard interactions.

The Best practices screens demonstrate that implementing accessibility requires consideration of both standard WCAG criteria and platform-specific interaction patterns. While the implementation overhead varies by screen complexity (10.8% to 22.5%), the resulting accessibility benefits provide substantial value for users relying on assistive technologies. These screens not only serve as educational resources but also demonstrate practical implementation patterns that developers can adapt to their own applications.

3.4.5 Best practices main screen summary

The Best practices main screen serves as the educational knowledge hub within *AccessibleHub*, providing developers with a structured approach to mobile accessibility implementation. It organizes accessibility knowledge into five key categories: WCAG Guidelines, Semantic Structure, Gesture Tutorial, Screen Reader Support, and Logical Focus Order. Each category employs a unified card-based interface that combines visual cues, descriptive labels, and educational badges to create an accessible learning path. The detailed analysis of this screen's implementation can be found in Appendix ??, while this section presents key findings and insights from the analysis.

3.4.5.1 Implementation overhead analysis

Implementing comprehensive accessibility features in the Best practices screen adds a measurable but manageable overhead to the development process. Table 3.18 quantifies this overhead across the primary accessibility features.

Table 3.18: Best practices screen accessibility implementation overhead

Accessibility Feature	Lines of Code	Percentage of Total	Complexity Impact
Semantic Roles	14 LOC	2.5%	Low
Descriptive Labels	25 LOC	4.5%	Medium
Element Hiding	30 LOC	5.4%	Low
Screen Announcements	15 LOC	2.7%	Low
Contrast Handling	18 LOC	3.2%	Medium
Gradient Background	12 LOC	2.2%	Low
Touch Target Sizing	20 LOC	3.6%	Medium
Total	134 LOC	24.1%	Medium

This analysis reveals that accessibility implementation accounts for approximately 24.1% of the screen's total code base, with element hiding (5.4%) and descriptive labels (4.5%) representing the largest contributors to this overhead. Despite this additional code, the overall complexity impact remains moderate, suggesting that accessibility features can be integrated into educational interfaces without imposing excessive development burden. Notably, this implementation overhead is lower than that observed in more complex interactive screens like the Component screen (32.8%), indicating that educational content with a consistent structure can achieve high accessibility standards with relatively modest code additions.

3.4.5.2 WCAG criteria implementation

The Best practices screen implements accessibility features that address multiple WCAG 2.2 conformance levels. Table 3.19 analyzes the implementation by conformance level, using color-coded indicators to highlight compliance status.

Table 3.19: Best practices screen WCAG implementation by conformance level

Conformance Level	Description	Implementation Rate	Notable Implementations
A (Level A)	Basic accessibility requirements that must be satisfied	15/15 (100%)	<ul style="list-style-type: none"> ✓ 1.1.1 Non-text Content ✓ 1.3.1 Info and Relationships ✓ 4.1.2 Name, Role, Value
AA (Level AA)	Advanced requirements beyond Level A	13/13 (100%)	<ul style="list-style-type: none"> ✓ 1.4.3 Contrast (Minimum) ✓ 2.4.6 Headings and Labels ✓ 4.1.3 Status Messages
AAA (Level AAA)	Highest level of accessibility	2/5 (40%)	<ul style="list-style-type: none"> ✓ 2.5.5 Target Size (Enhanced) ✓ 3.2.5 Change on Request ✗ 2.4.10 Section Headings

Table 3.20: Legend for WCAG criteria implementation colors

Color	Meaning
✓	A-level criteria implemented
✓	AA-level criteria implemented
✓	AAA-level criteria implemented
✗	Criteria not implemented

This analysis reveals complete compliance with Level A and AA requirements, while also implementing two key AAA-level criteria:

1. 2.5.5 Target Size (Enhanced): The implementation exceeds the enhanced target size requirement of 44×44 pixels through large, card-based interaction targets that provide ample touch area;
2. 3.2.5 Change on Request: All navigation and state changes occur only in response to explicit user actions, with clear announcements of context changes for screen reader users.

The remaining AAA criteria were not implemented either because they were not applicable to this screen type or because implementation would have added significant complexity without proportional benefit.

3.4.5.3 Screen reader compatibility analysis

Empirical testing with screen readers on both major mobile platforms reveals consistent behavior patterns that contribute to a streamlined navigation experience. Table 3.21 highlights key findings from this testing.

Table 3.21: Best practices screen reader testing highlights

Component Type	Screen Reader Behavior	Accessibility Benefit
Headings	Both VoiceOver and TalkBack correctly announce heading role and content	Provides clear navigation landmarks and content structure
Practice Cards	Announced as buttons with complete descriptive labels	Communicates both control type and destination content in a single announcement
Decorative Elements	Successfully hidden from screen reader focus	Reduces navigation steps by approximately 60% compared to non-optimized implementation
Screen Transitions	Destination screen explicitly announced	Maintains context during navigation between different sections

The screen reader analysis reveals that careful implementation of accessibility properties significantly improves the navigation experience by:

1. Streamlining the swipe path through elimination of decorative and redundant focus stops;
2. Providing comprehensive context through detailed card labels that include both identification and purpose information;

3. Maintaining orientation through explicit announcements of destination screens during navigation;
4. Preserving semantic meaning through proper role assignments that communicate component types.

These findings demonstrate that educational interfaces can achieve both comprehensive content delivery and efficient screen reader navigation when accessibility properties are thoughtfully applied.

3.4.5.4 Mobile-specific considerations

The Best practices screen implementation addresses several mobile-specific accessibility considerations that extend beyond standard WCAG requirements. These considerations are particularly important for educational interfaces on mobile devices, where limited screen space and touch-based interaction present unique challenges.

Key mobile-specific implementations include:

1. **Card-based architecture:** The screen uses semantically and visually distinct content cards that create clear information boundaries, addressing the mobile challenge of limited screen space while maintaining content separation;
2. **Badge-based categorization:** Compact visual badges efficiently communicate content types without consuming excessive screen space, providing important educational context within the constraints of mobile interfaces;
3. **Touch-optimized targets:** All interactive elements maintain minimum dimensions of $44 \times 44\text{dp}$, with practice cards providing substantially larger touch targets that accommodate various motor capabilities;
4. **Minimal navigation depth:** The implementation maintains a shallow information architecture with all primary categories accessible from a single scrollable view, reducing the risk of disorientation common in deeply-nested mobile interfaces.

These mobile-specific considerations demonstrate that effective accessibility implementation must adapt to the unique constraints and interaction patterns of mobile platforms, extending beyond generic WCAG guidelines to address platform-specific challenges.

3.4.6 Accessibility tools screen summary

The Accessibility tools screen serves as a comprehensive resource guide within *AccessibleHub*, providing developers with a structured catalog of essential tools and resources for testing and improving mobile application accessibility. The screen organizes tools into three key categories: screen readers, development tools, and testing utilities, presenting each with expandable cards that offer practical usage guidance and direct links to official documentation. The implementation demonstrates both educational value and accessibility-first design patterns.

3.4.6.1 Implementation overhead analysis

Implementing accessibility features in the Tools screen adds a quantifiable but manageable overhead to the development process. Table 3.22 presents the analysis of this implementation overhead.

Table 3.22: Tools screen accessibility implementation overhead

Accessibility Feature	Lines of Code	Percentage of Total	Complexity Impact
Semantic Roles	16 LOC	2.7%	Low
Descriptive Labels	24 LOC	4.1%	Medium
Element Hiding	32 LOC	5.5%	Low
List Semantics	10 LOC	1.7%	Low
Link Announcements	12 LOC	2.1%	Low
Expansion State Management	18 LOC	3.1%	Medium
Total	112 LOC	19.2%	Medium

This analysis reveals that implementing a fully accessible tools catalog requires approximately 19.2% additional code, with element hiding (5.5%) and descriptive labels (4.1%)

representing the largest contributors. The information-dense nature of this screen necessitates careful screen reader optimization, yet the overall complexity impact remains moderate, suggesting that accessibility can be effectively integrated into educational reference screens without imposing excessive development burden.

3.4.6.2 WCAG criteria implementation

The Tools screen implements accessibility features addressing multiple WCAG 2.2 conformance levels. Table 3.23 presents the analysis of this implementation by conformance level.

Table 3.23: Tools screen WCAG implementation by conformance level

WCAG Success Criteria	Screen Readers	Development Tools	Testing Checklist
1.1.1 Non-text Content (A)	✓	✓	✓
1.3.1 Info and Relationships (A)	✓	✓	✓
1.4.3 Contrast (AA)	✓	✓	✓
2.1.1 Keyboard (A)	✓	✓	✓
2.4.3 Focus Order (A)	✓	✓	✓
2.4.4 Link Purpose (A)	✓	✓	✓
2.4.6 Headings (AA)	✓	✓	✓
2.5.5 Target Size (Enhanced) (AAA)	✓	✓	✓
2.5.8 Target Size (AA)	✓	✓	✓
3.2.5 Change on Request (AAA)	✓	✓	✓
4.1.2 Name, Role, Value (A)	✓	✓	✓
4.1.3 Status Messages (AA)	✓	✓	✓
Total A/AA Implementation	9/9	9/9	9/9
Total AAA Implementation	2/2	2/2	2/2

Table 3.24: Legend for WCAG criteria implementation colors

Color	Meaning
✓	A-level criteria implemented
✓	AA-level criteria implemented
✓	AAA-level criteria implemented
✗	Criteria not implemented

This analysis demonstrates complete A and AA compliance across all tool categories, with consistent implementation of two key AAA criteria:

1. 2.5.5 Target Size (Enhanced): All interactive elements implement the enhanced target size requirement through large, card-based interaction targets;
2. 3.2.5 Change on Request: All content expansions and link activations occur only through explicit user actions, with appropriate screen reader announcements.

3.4.6.3 Screen reader support analysis

Empirical testing with screen readers reveals consistent behavior patterns across platforms. Table 3.25 highlights key findings from this testing.

Table 3.25: Tools screen reader testing highlights

Component Type	Screen Reader Behavior	Accessibility Benefit
Headings	Both VoiceOver and TalkBack correctly announce heading role and content	Provides clear navigation landmarks and content structure
Tool Cards	Announced as buttons with state information	Communicates both control type and expansion state clearly
Decorative Elements	Successfully hidden from screen reader focus	Reduces navigation steps by approximately 60% compared to non-optimized implementation
Documentation Links	Properly labeled with destination context	Prepares users for context changes when activating external links

The screen reader analysis demonstrates that proper implementation of accessibility properties significantly improves navigation efficiency through:

1. Streamlined focus path via strategic element hiding;
2. Clear state communication in expandable components;

3. Proper semantic structuring of content with appropriate headings and lists;
4. Contextual hints for external link activation.

3.4.6.4 Mobile-specific implementation considerations

The Tools screen addresses several mobile-specific accessibility considerations that extend beyond standard WCAG requirements. Table 3.26 presents the analysis of these mobile-specific implementations.

Table 3.26: Tools screen mobile-specific implementation considerations

Mobile Consideration	Implementation Approach	Accessibility Benefit
Progressive Disclosure	Expandable card implementation	Reduces cognitive load on small screens while maintaining content completeness
Touch Target Optimization	Large card headers ($>44 \times 44\text{dp}$)	Improves usability for users with motor impairments
Platform-Specific Content	Explicit iOS/Android tool separation	Addresses differences in platform-specific accessibility implementations
External Link Context	Clear <code>accessibilityHint</code> for browser opening	Prepares users for disruptive context switches on mobile
Practical Usage Emphasis	Dedicated sections for real-world application	Bridges the gap between tool features and implementation needs

These mobile-specific implementations demonstrate that accessibility on mobile platforms requires considerations beyond standard WCAG criteria, particularly in areas of interaction design, content organization, and context management.

Key patterns identified in this analysis include:

1. Comprehensive implementation of A and AA-level WCAG criteria across all tool categories;

2. Strategic implementation of AAA criteria with significant usability impact;
3. Consistent patterns for element hiding and descriptive labeling;
4. Mobile-specific adaptations focused on reducing cognitive load and optimizing touch interactions;
5. Educational content organization that supports a developmental learning path.

The Tools screen demonstrates that implementing accessibility in educational reference screens requires thoughtful consideration of both standard guidelines and mobile-specific interaction patterns. The implementation overhead (19.2%) delivers significant improvements in usability for all users, demonstrating that accessibility can be effectively integrated into educational interfaces with reasonable development effort.

3.4.7 Instruction and community screen summary

The instruction and community screen serves as a collaborative learning hub within *AccessibleHub*, extending beyond technical implementation details to connect developers with the broader accessibility community. This screen provides practical examples, community resources, and pathways for contribution to accessibility projects. Through collapsible code snippets, project cards, and community channel connections, it demonstrates both educational value and practical accessibility implementation patterns.

3.4.7.1 Implementation overhead analysis

Implementing comprehensive accessibility features in the instruction and community screen adds a measurable but manageable overhead to the development process. Table 3.27 quantifies this overhead across the primary accessibility features.

Table 3.27: Instruction and community screen accessibility implementation overhead

Accessibility Feature	Lines of Code	Percentage of Total	Complexity Impact
Semantic Roles	24 LOC	3.1%	Low
Descriptive Labels	32 LOC	4.2%	Medium
Element Hiding	18 LOC	2.3%	Low
Status Announcements	16 LOC	2.1%	Medium
Link Handling	14 LOC	1.8%	Low
Collapsible Content Management	28 LOC	3.6%	High
Code Snippet Presentation	24 LOC	3.1%	Medium
Total	156 LOC	20.2%	Medium

This analysis reveals that accessibility implementation accounts for approximately 20.2% of the screen's total code base, with descriptive labels (4.2%) and collapsible content management (3.6%) representing the largest contributors to this overhead. Despite this additional code, the overall complexity impact remains moderate, suggesting that accessibility features can be integrated into community-focused interfaces without imposing excessive development burden.

3.4.7.2 WCAG criteria implementation

The instruction and community screen implements accessibility features addressing multiple WCAG 2.2 conformance levels. Table 3.28 analyzes the implementation by principle.

Table 3.28: Instruction and community screen WCAG implementation by principle

Principle	Description	Implementation Rate	Notable Implementations
Perceivable	Information and UI components must be presentable in ways users can perceive	78.6%	✓ 1.1.1 Non-text Content ✓ 1.3.1 Info and Relationships ✓ 1.4.3 Contrast (Minimum)
Operable	UI components and navigation must be operable	76.5%	✓ 2.4.3 Focus Order ✓ 2.4.6 Headings and Labels ✓ 2.5.5 Target Size (Enhanced)
Understandable	Information and operation of UI must be understandable	70%	✓ 3.3.2 Labels or Instructions ✓ 3.2.5 Change on Request
Robust	Content must be interpreted by a wide variety of user agents	100%	✓ 4.1.2 Name, Role, Value ✓ 4.1.3 Status Messages

Table 3.29: Legend for WCAG criteria implementation colors

Color	Meaning
✓	A-level criteria implemented
✓	AA-level criteria implemented
✓	AAA-level criteria implemented
✗	Criteria not implemented

The screen achieves 100% compliance with the Robust principle, demonstrating strong semantic implementation. The somewhat lower rates for the other principles reflect the complex balance between rich content presentation and accessibility in educational contexts. Notable implementations include enhanced target sizes and explicit change announcements for screen reader users.

3.4.7.3 Screen reader compatibility analysis

Empirical testing with screen readers on both major mobile platforms reveals important patterns in accessibility implementation. Table 3.30 presents key findings from this analysis.

Table 3.30: Instruction and community screen reader testing highlights

Component Type	Screen Reader Behavior	Accessibility Benefit
Headings	Both VoiceOver and TalkBack correctly announce heading role and content	Provides clear navigation landmarks and content structure
Collapsible Content	Expansion state changes are explicitly announced	Maintains user context during dynamic content changes
Project Cards	Clear announcement of project name, description, and contributors	Delivers comprehensive context in a single announcement
Code Snippets	Properly formatted and read as text content	Makes technical examples accessible to screen reader users
External Links	Purpose and activation are clearly announced	Prepares users for context shifts when activating resources

These findings demonstrate several effective accessibility implementation patterns:

1. Explicit state change announcements using `AccessibilityInfo.announceForAccessibility` keep screen reader users informed during dynamic content changes;
2. Strategic element hiding streamlines navigation flow by eliminating decorative elements from the focus path;
3. Comprehensive project card labels combine identifying information with contextual details, delivering complete information efficiently;
4. External link handling with appropriate announcements prepares users for application context changes when accessing external resources;

5. Properly structured code snippets ensure that technical examples remain accessible to screen reader users.

3.4.7.4 Mobile-specific accessibility considerations

The instruction and community screen addresses several mobile-specific accessibility challenges that extend beyond standard WCAG requirements:

1. **Progressive disclosure:** Collapsible content patterns optimize limited screen space while maintaining content accessibility;
2. **Link context preparation:** Special handling of external links through explicit announcements prepares users for disruptive context switches common in mobile environments;
3. **Touch-optimized targets:** All interactive elements maintain minimum dimensions of $44 \times 44\text{dp}$, with project cards and community channel links providing substantially larger touch targets;
4. **Platform-specific adaptations:** Conditional styling based on platform detection (`Platform.OS === 'ios' ? 'Menlo' : 'monospace'`) ensures appropriate presentation across diverse devices;
5. **Battery-conscious implementation:** Gradient backgrounds use platform-optimized implementations to balance visual design with power consumption considerations.

The instruction and community screen demonstrates that educational and community-focused interfaces can achieve both comprehensive content delivery and efficient accessibility implementation. The overhead of 20.2% delivers significant improvements in usability for all users, demonstrating that accessibility can be effectively integrated into social learning interfaces with reasonable development effort.

3.4.8 Settings screen summary

The settings screen serves as a comprehensive control center within *AccessibleHub*, allowing users to adjust accessibility and display preferences. It offers fine-grained control over visual appearance, text size, motion effects, and interaction modes, exemplifying an embedded accessibility approach where adaptation is treated as a core feature rather than an afterthought. Through its implementation of toggleable accessibility options with multi-modal feedback, the screen demonstrates both practical utility and accessibility-first design principles.

3.4.8.1 Implementation overhead analysis

Implementing accessibility features in the settings screen adds a quantifiable but manageable overhead to the development process. Table 3.31 presents the analysis of this implementation overhead.

Table 3.31: Settings screen accessibility implementation overhead

Accessibility Feature	Lines of Code	Percentage of Total	Complexity Impact
Semantic Roles	12 LOC	2.1%	Low
Comprehensive Labels	16 LOC	2.8%	Medium
Element Hiding	18 LOC	3.2%	Low
Status Announcements	14 LOC	2.5%	Medium
Platform-specific Feedback	12 LOC	2.1%	Medium
Dynamic Styling	22 LOC	3.9%	Medium
Accessibility State	8 LOC	1.4%	Low
Total	102 LOC	18.0%	Medium

This analysis reveals that implementing comprehensive accessibility for the settings screen adds approximately 18.0% to the code base. The most significant contributors are dynamic styling (3.9%) and element hiding (3.2%), reflecting the need to adapt visual presentation based on user preferences while maintaining streamlined screen reader navigation. Despite this overhead, the complexity impact remains moderate, demonstrating that accessibility

implementation can be achieved with reasonable development effort.

3.4.8.2 WCAG criteria implementation

The settings screen implements accessibility features addressing multiple WCAG 2.2 conformance levels. Table 3.32 presents the analysis of this implementation by principle.

Table 3.32: Settings screen WCAG implementation by principle

Principle	Description	Implementation Rate	Notable Implementations
Perceivable	Information and UI components must be presentable in ways users can perceive	100%	✓ 1.1.1 Non-text Content ✓ 1.3.1 Info and Relationships ✓ 1.4.4 Resize Text
Operable	UI components and navigation must be operable	88%	✓ 2.4.6 Headings and Labels ✓ 2.5.8 Target Size ✓ 2.3.3 Animation from Interactions
Understandable	Information and operation of UI must be understandable	100%	✓ 3.2.1 On Focus ✓ 3.3.2 Labels or Instructions ✓ 3.3.5 Help
Robust	Content must be interpreted by a wide variety of user agents	100%	✓ 4.1.2 Name, Role, Value ✓ 4.1.3 Status Messages

Table 3.33: Legend for WCAG criteria implementation colors

Color	Meaning
✓	A-level criteria implemented
✓	AA-level criteria implemented
✓	AAA-level criteria implemented
✗	Criteria not implemented

The screen achieves 100% compliance with the Perceivable, Understandable, and Robust principles, reflecting its central role in providing accessibility adjustments. The slightly lower

compliance with the Operable principle (88%) is due to the absence of specific keyboard navigation optimizations, which are less relevant in the predominantly touch-based mobile context.

3.4.8.3 Screen reader compatibility analysis

Empirical testing with screen readers on both major mobile platforms reveals consistent behavior patterns that contribute to a streamlined navigation experience. Table 3.34 highlights key findings from this testing.

Table 3.34: Settings screen reader testing highlights

Component Type	Screen Reader Behavior	Accessibility Benefit
Section Headers	Both VoiceOver and TalkBack correctly announce heading role and content	Provides clear navigation landmarks and content structure
Switch Controls	Comprehensive labels combine title, description, and state	Delivers complete context in a single announcement
Setting Cards	Proper semantic grouping of related settings	Creates logical navigation flow through related options
Dividers	Successfully hidden from screen reader focus	Reduces unnecessary navigation steps
Feedback Mechanisms	Setting changes announced through multiple channels	Ensures changes are perceivable regardless of user capabilities

The screen reader analysis reveals that careful implementation of accessibility properties significantly improves the navigation experience by:

1. Providing comprehensive context through detailed switch control labels that include title, description, and current state;
2. Streamlining the focus path through strategic hiding of decorative elements;

3. Maintaining user orientation through clear section headings and logical content grouping;
4. Ensuring state changes are perceivable through multiple feedback channels (visual, auditory, and haptic).

3.4.8.4 Mobile-specific accessibility considerations

The settings screen addresses several mobile-specific accessibility considerations that extend beyond standard WCAG requirements:

1. **Multiple adaptation pathways:** The screen provides six distinct accessibility adjustments (dark mode, high contrast, large text, reduced motion, color filtering, and large touch targets), addressing the diverse needs of mobile users;
2. **Multimodal feedback:** Implementation of visual, auditory, and haptic feedback mechanisms ensures setting changes are perceivable in varied mobile contexts where one sensory channel may be unavailable or limited;
3. **Battery-conscious implementation:** Dark mode and reduced motion settings consider not just accessibility but also device power consumption, an important consideration for mobile users;
4. **Touch ergonomics:** The implementation of larger touch targets addresses the specific challenges of touch interaction for users with motor impairments, exceeding WCAG minimum requirements;
5. **Platform-specific integration:** The implementation follows platform conventions for controls and feedback, integrating with native expectations on both iOS and Android.

3.4.8.5 Self-adapting interface principles

The settings screen exemplifies several principles for self-adapting interfaces that extend beyond standard WCAG requirements:

1. **Embedded customization principle:** Accessibility adjustments are directly embedded within the application rather than relying solely on system-level settings;
2. **Multi-sensory feedback guideline:** Setting changes provide feedback through multiple sensory channels to ensure perceivability regardless of user capabilities;
3. **Contextual help principle:** Setting controls provide context-specific guidance through comprehensive labels that explain both purpose and current state;
4. **Complementary settings grouping:** Related accessibility features are organized into logical categories (Visual Settings, Readability Enhancements, Color & Touch Settings) that help users understand how different options work together;
5. **Proportional adaptation:** The implementation includes both binary toggles and settings that affect the degree of adaptation (text size, contrast levels), providing fine-grained control.

The settings screen demonstrates that proper accessibility implementation extends beyond compliance with standards to embrace the concept of interfaces that adapt to diverse user needs. With a reasonable implementation overhead of 18.0%, the screen provides substantial accessibility benefits, illustrating how adaptability can be integrated as a core application feature rather than a specialized accommodation.

Chapter 4

Accessibility analysis: framework comparison and implementation patterns

This chapter offers a systematic, comparative analysis of accessibility implementation in React Native and Flutter. Through empirical evaluation of equivalent components and detailed analysis of architectural approaches, three core questions are addressed: the default accessibility of components, the feasibility of implementing accessibility for non-accessible components, and the development effort required for these implementations. Combining quantitative metrics with qualitative assessments of developer experience, this analysis provides practical insights into how each framework's fundamental design influences accessibility implementation patterns and guides developers in creating more inclusive mobile applications.

4.1 Research methodology

This chapter builds upon the detailed screen-by-screen analysis of *AccessibleHub*, extending that evaluation framework to a comparative analysis of React Native and Flutter.

4.1.1 Research questions and objectives

This comparative analysis addresses three fundamental research questions about accessibility implementation across React Native and Flutter:

1. **RQ1: Default accessibility support** - To what extent are components and widgets provided by each framework accessible by default, without requiring additional developer intervention? This analysis examines the baseline accessibility support provided by each framework and identifies areas where implementation gaps exist;
2. **RQ2: Implementation feasibility** - When components are not accessible by default, what is the technical feasibility of enhancing them to meet accessibility standards? This includes analyzing the technical capabilities of each framework and identifying the necessary modifications to achieve accessibility compliance;
3. **RQ3: Development overhead** - What is the quantifiable development overhead required to implement accessibility features when they are not provided by default? This includes measuring additional code requirements, analyzing complexity increases, and evaluating the impact on development workflows.

These research questions provide a structured framework for evaluating how React Native and Flutter support developers in creating accessible mobile applications. By addressing these questions, we aim to provide practical insights that can guide framework selection and implementation strategies for accessibility-focused development.

4.1.2 Testing approach and criteria

The comparative testing approach builds upon the formal evaluation methodology established in Chapter 3, applying those same rigorous criteria to Flutter implementations. This ensures consistent evaluation across frameworks and enables direct comparison of accessibility support. Our testing methodology consists of four key components:

1. **Component equivalence mapping:** We establish functional equivalence between

React Native components and Flutter widgets to ensure fair comparison. This mapping is based on the component's purpose and role rather than implementation details;

2. **WCAG/MCAG criteria mapping:** Each component is evaluated against the same set of WCAG 2.2 and MCAG criteria used in Chapter 3, ensuring consistent application of accessibility standards across frameworks;
3. **Implementation testing:** For each component, we develop and test equivalent implementations in both frameworks, focusing on:
 - Default accessibility support without modifications;
 - Implementation requirements to achieve full accessibility;
 - Code complexity and verbosity of accessible implementations.
4. **Assistive technology testing:** All implementations are tested with:
 - iOS *VoiceOver* on iPhone 14 with iOS 16;
 - Android *TalkBack* on Google Pixel 7, running Android 15 (tests were conducted also on Android 13 and 14 on same device).

This multi-faceted testing approach ensures that our evaluation captures both the technical capabilities of each framework and the practical experience of users with disabilities.

4.1.3 Evaluation metrics and quantification methods

To provide rigorous quantitative comparison between frameworks, the formal metrics present in Table 4.1 are employed.

These metrics are calculated using the same methodology established in Chapter 3, ensuring consistency across the comparative analysis and objective comparison between the frameworks.

Table 4.1: Accessibility implementation metrics

Metric	Description
Component Accessibility Score (CAS)	Percentage of components accessible by default without modification
Implementation Overhead (IMO)	Additional lines of code required to implement accessibility features
Complexity Impact Factor (CIF)	Calculated as: $CIF = \frac{IMO}{TC} \times CF$ where TC is total component code and CF is a complexity factor based on nesting depth and property count
Screen Reader Support Score (SRSS)	Empirical score (1-5) based on VoiceOver and TalkBack compatibility testing
WCAG Compliance Ratio (WCR)	Percentage of applicable WCAG 2.2 success criteria satisfied
Developer Time Estimation (DTE)	Estimated development time required to implement accessibility features, based on component complexity

4.1.4 Metric calculation methodologies

To ensure rigor and reproducibility, each metric employed in our comparative analysis follows a formalized methodology. These methodologies build upon the approaches already established while incorporating analytical frameworks specific to cross-platform comparison.

4.1.4.1 Component Accessibility Score methodology

The Component Accessibility Score (CAS) quantifies the percentage of components that are accessible by default without requiring additional developer intervention. The methodology for calculating CAS follows a systematic process:

- 1. Component identification:** Components are selected according to the criteria outlined in Section 4.1.5, ensuring equivalent functionality across frameworks;
- 2. Default implementation testing:** Each component is implemented using the framework's standard documentation without any accessibility-specific modifications;
- 3. Accessibility evaluation criteria:** A component is considered "accessible by default" if and only if it meets all of the following criteria without modification:

- Correct role announcement by screen readers (e.g., button announced as "button");
- Complete content announcement (all text content is read);
- Proper focus management (can be reached and navigated with screen reader gestures);
- State communication (selected/unselected, enabled/disabled states are announced).

4. **Binary classification:** Each component receives a binary classification (accessible/not accessible) based on meeting all criteria;

5. **Score calculation:** CAS is calculated as:

$$CAS = \frac{\text{Number of accessible components}}{\text{Total number of components tested}} \times 100\% \quad (4.1)$$

This methodology was applied to 30 common components across both frameworks, ensuring a statistically significant sample size while maintaining focus on components essential to typical mobile applications.

4.1.4.2 Implementation Overhead methodology

Implementation Overhead (IMO) measures the additional code required to implement accessibility features. The methodology follows these steps:

1. **Baseline implementation:** For each component not accessible by default, a minimal functional implementation is created without accessibility features;
2. **Accessible implementation:** The same component is then enhanced with all necessary accessibility features to achieve full compliance with WCAG 2.2 AA standards;
3. **Code isolation:** Lines of code specifically related to accessibility are identified through:
 - Direct accessibility properties (e.g., `accessibilityLabel`, `semantics`);
 - Accessibility wrappers (e.g., `Semantics` widget in Flutter);

- Support code specifically added for accessibility (e.g., handlers for accessibility actions).

4. **Quantification:** Implementation overhead is measured in absolute lines of code (LOC_G) and as a percentage increase over the baseline:

$$IMO\% = \frac{\text{Accessibility LOC}}{\text{Baseline LOC}} \times 100\% \quad (4.2)$$

5. **Verification:** The counting methodology is verified by multiple reviewers to ensure consistency.

This methodology focuses on production-quality implementations, excluding comments and development scaffolding, to accurately reflect real-world implementation costs.

4.1.4.3 Complexity Impact Factor methodology

The Complexity Impact Factor (CIF) provides a weighted measure of implementation complexity beyond simple line counts. The methodology involves:

1. **Total component calculation:** The total component code (TC) includes all code necessary for the component's implementation, including both baseline and accessibility code;
2. **Complexity factor determination:** The complexity factor (CF) is calculated through a weighted formula:

$$CF = (W_N \times N) + (W_D \times D) + (W_P \times P) \quad (4.3)$$

Where:

- N = Number of nested levels introduced by accessibility implementation;
- D = Dependency count (number of imported libraries/modules required specifically for accessibility);

- P = Property count (number of accessibility-specific properties or parameters);
- W_N, W_D, W_P = Respective weights (1.5, 1.0, 0.5 in the analysis).

The weights ($W_N = 1.5, W_D = 1.0, W_P = 0.5$) were determined based on a qualitative assessment of each factor's impact on development complexity during our implementation process.

Through practical implementation of components across both frameworks, we observed that nesting depth (N) consistently created the most significant challenges for code readability, debugging, and maintenance. Each additional nesting level substantially increased cognitive load during development, warranting the highest weight (1.5).

- Dependency count (D) demonstrated a moderate impact on implementation complexity. Additional dependencies created integration challenges and increased setup requirements, but these challenges were more manageable than deep nesting issues, justifying an intermediate weight (1.0);
- Property count (P) had the least significant impact on overall implementation complexity. While additional properties increased code volume, they had minimal effect on structural complexity or cognitive load, leading to the lowest assigned weight (0.5);
- This weighting system, while not derived from large-scale quantitative studies, reflects the practical difficulties observed during our hands-on implementation process and provides a reasonable heuristic for comparing relative complexity across frameworks.

3. **CIF calculation:** The final CIF is calculated as:

$$CIF = \frac{IO}{TC} \times CF \quad (4.4)$$

4. **Complexity classification:** CIF values are classified as:

- Low: $CIF < 0.2$;
- Medium: $0.2 \leq CIF < 0.5$;
- High: $CIF \geq 0.5$.

This weighted approach ensures that complexity assessment considers not just code volume but structural complexity factors that impact maintainability and comprehension.

4.1.4.4 Screen Reader Support Score methodology

The Screen Reader Support Score (SRSS) quantifies the effectiveness of screen reader interaction using a standardized Likert scale. SRSS evaluation involves:

1. **Test case definition:** Each component is evaluated across five criteria, involving role announcement, content reading and focus behavior;
2. **Rating scale:** Each criterion is rated on a 5-point scale aligned with WCAG conformance levels:
 - 1: Fails Level A compliance - Component inaccessible or critically misleading;
 - 2: Partially meets Level A - Basic accessibility with significant usability barriers;
 - 3: Meets Level A - Functional accessibility with complete core requirements;
 - 4: Meets Level AA - Comprehensive accessibility with enhanced requirements met;
 - 5: Meets Level AAA - Optimal accessibility exceeding requirements with ideal patterns.
3. **Testing environment:** All evaluations use:
 - iOS: iPhone 14 with iOS 16, VoiceOver screen reader;
 - Android: Google Pixel 7 with Android 15, TalkBack screen reader.
4. **Score calculation:** SRSS is calculated as the mean of all criteria scores for each platform separately, reported to one decimal place;

5. **Validation:** Each component is independently evaluated by two accessibility specialists, with discrepancies resolved through consensus.

Category scores represent the mean of component scores within each category, with weighting based on component usage frequency in typical mobile applications.

4.1.4.5 WCAG Compliance Ratio methodology

The WCAG Compliance Ratio (WCR) measures conformance to Web Content Accessibility Guidelines 2.2. The methodology follows these steps:

1. **Criteria applicability assessment:** Each WCAG 2.2 success criterion is evaluated for applicability to mobile interfaces in general and to each component category specifically;
2. **Compliance evaluation:** For applicable criteria, each framework's implementation is evaluated against the specific requirements of the criterion;
3. **Conformance levels:** Testing focuses on Level AA conformance, with Level AAA criteria noted but not required for calculating WCR;
4. **Ratio calculation:** WCR is calculated as:

$$WCR = \frac{\text{Number of satisfied criteria}}{\text{Total number of applicable criteria}} \times 100\% \quad (4.5)$$

5. **Principle-level aggregation:** Results are aggregated by WCAG principle (Perceivable, Operable, Understandable, Robust) to identify pattern differences between frameworks.

This methodology allows for identification of not just overall compliance differences but specific areas where frameworks excel or struggle with particular accessibility principles.

4.1.4.6 Developer Time Estimation methodology

Developer Time Estimation (DTE) quantifies the time required to implement accessibility features. The methodology involves:

1. **Task definition:** Implementation tasks are precisely defined to include all necessary accessibility enhancements for equivalent functionality;
2. **Developer proficiency normalization:** Estimates assume developers with intermediate proficiency in both frameworks and basic accessibility knowledge;
3. **Time measurement:** Implementation times are measured through:
 - Time logging of subtasks (research, implementation, testing);
 - Exclusion of debugging unrelated to accessibility features.
4. **Complexity factoring:** Raw implementation times are adjusted by component complexity using:

$$DTE = T_{\text{raw}} \times (1 + (0.1 \times C)) \quad (4.6)$$

Where T_{raw} is the raw implementation time and C is the component complexity score (1-5);

5. **Data aggregation:** Final DTE values represent the mean of adjusted implementation times across all test subjects, reported in minutes.

This approach combines empirical measurement with complexity-based adjustments to provide realistic time estimates independent of individual developer variations.

4.1.5 Component selection methodology

To ensure comprehensive and representative comparison, components for analysis were selected based on the following criteria:

1. **Functional equivalence:** Selected components must have clear functional equivalents across both frameworks;

2. **Accessibility relevance:** Components must be essential to implementing accessible user interfaces;
3. **Usage frequency:** Priority given to components that appear frequently in mobile applications;
4. **Interaction complexity:** Selection includes a range of components from simple (static text) to complex (multi-state interactive elements);
5. **WCAG criteria coverage:** The component set must collectively address all four WCAG principles.

Based on these criteria, components were selected from three categories that represent the building blocks of mobile interfaces:

1. **Text and typography components:** Headings, paragraphs, language declarations, and abbreviations;
2. **Interactive components:** Buttons, form elements, custom gesture handlers;
3. **Navigation components:** Navigation systems, tab controls, focus management systems;
4. **Media and complex components:** Image rendering, data visualization, dynamic content.

Table 4.2 presents a comparative analysis of default component accessibility and the enhancements required to make them fully accessible. The "Default" columns indicate whether components are accessible without modification, while the "Enhanced" columns document the specific modifications required (additional properties and/or widgets) to achieve full accessibility compliance according to WCAG 2.2 criteria. For React Native, enhancement typically involves adding accessibility properties (P) to existing components, while Flutter often requires both additional wrapper widgets (W) and properties (P).

Table 4.2: Component accessibility comparison matrix

Component	React Native Default	React Native Enhanced	Flutter Default	Flutter Enhanced	Implementation Difference (%)
Heading	✗	✓ (+1P)	✗	✓ (+1W +1P)	+40%
Text language	✓	-	✗	✓ (+1W +1P)	+200%
Text abbreviation	✗	✓ (+1P)	✗	✓ (+1P)	+0%
Button	✓	-	✗	✓ (+1W)	+100%
Form input	✗	✓ (+2P)	✗	✓ (+1W +1P)	+50%
Custom gesture	✗	✓ (+3P)	✗	✓ (+1W +2P)	+33%

Legend: ✓: accessible by default, ✗: not accessible, P: property, W: widget

Table 4.3 quantifies the implementation effort required to make equivalent components accessible in both frameworks. The analysis reveals significant differences in code verbosity between React Native and Flutter implementations. Most notably, Flutter's semantics implementation for text language requires 21 lines of code compared to React Native's 7 lines, representing a 200% increase and resulting in "High" complexity impact. This substantial difference stems from Flutter's requirement for explicit `AttributedString` and `LocaleStringAttribute` declarations versus React Native's straightforward `accessibilityLanguage` property.

The Complexity Impact classification is determined by combining both the absolute increase in LOC and the relative complexity introduced by the implementation pattern. Low

complexity impacts (such as for Headings and Buttons) indicate that despite some additional code, the implementations remain straightforward and maintainable. Medium complexity impacts (Text abbreviation, Form field, Custom gesture) suggest that the additional code introduces moderate cognitive load for developers. High complexity impacts (Text language in Flutter) indicate implementations that significantly increase both code volume and structural complexity, potentially creating maintenance challenges and higher learning curves for development teams.

Table 4.3: Implementation overhead analysis

Component	React Native LOC	Flutter LOC	Difference (LOC)	Complexity Impact
Heading	7	11	+4 (57%)	Low
Text language	7	21	+14 (200%)	High
Text abbreviation	7	14	+7 (100%)	Medium
Button	12	18	+6 (50%)	Low
Form field	15	23	+8 (53%)	Medium
Custom gesture	22	28	+6 (27%)	Medium

Table 4.4 presents the compliance percentages for each WCAG principle across both frameworks, derived from systematic testing with VoiceOver and TalkBack screen readers. These percentages represent the proportion of applicable success criteria that were successfully implemented in our reference components. The results reveal that while both frameworks can achieve strong accessibility compliance, there are notable differences in their default capabilities.

React Native demonstrates superior compliance with Perceivable criteria (92% vs. Flutter's 85%), primarily due to its more straightforward handling of text alternatives and adaptable content. In the Operable principle, React Native achieves 100% compliance compared to Flutter's 88%, with the difference largely attributable to Flutter's more complex implementation of keyboard accessibility and focus management. Both frameworks achieve identical compliance rates for Understandable (80%) and Robust (100%) principles, indicating similar capabilities in predictable operation and compatibility with assistive technologies.

These differences highlight React Native's advantage in implementation simplicity while demonstrating that both frameworks can ultimately achieve full WCAG compliance with appropriate development effort.

Table 4.4: WCAG compliance by framework

WCAG Principle	Key Success Criteria	React Native	Flutter
1. Perceivable	1.1.1, 1.3.1, 1.4.3, 1.4.11	92%	85%
2. Operable	2.1.1, 2.4.3, 2.4.7, 2.5.1, 2.5.8	100%	88%
3. Understandable	3.2.1, 3.2.4, 3.3.1, 3.3.2	80%	80%
4. Robust	4.1.1, 4.1.2, 4.1.3	100%	100%

4.2 Flutter overview

4.2.1 Core architecture and widget system

Flutter, developed by Google and released in 2018, is an open-source UI software development kit for building natively compiled applications for mobile, web, and desktop from a single codebase [12]. Unlike React Native's component-based architecture, Flutter employs a widget-based system where everything is a widget, from structural elements to styling and animations.



Figure 4.1: Flutter logo

Flutter's architecture consists of several key layers:

- **Framework layer:** Written in *Dart*, contains the widget system, rendering, animation, and gestures;
- **Engine layer:** A C++ implementation that provides low-level rendering using *Skia* graphics library;
- **Embedder layer:** Platform-specific code that integrates Flutter with each target platform.

The widget system forms the foundation of Flutter applications, with two primary types:

- **StatelessWidget:** Immutable widgets whose properties cannot change during runtime;
- **StatefulWidget:** Widgets that can rebuild themselves when their state changes.

4.2.2 Accessibility in Flutter

Flutter approaches accessibility through a dedicated Semantics system that creates an accessibility tree parallel to the widget tree. This architecture differs fundamentally from React Native's property-based approach, instead using specialized widgets to enhance accessibility:

- **Semantics:** The primary tool for adding accessibility information to existing widgets, acts as a container that annotates the widget subtree with a collection of semantic properties;
- **MergeSemantics:** Combines child semantics into a single accessible entity, useful for creating composite elements that should be treated as a single unit by assistive technologies;
- **ExcludeSemantics:** Removes descendants from the accessibility tree, preventing purely decorative elements from being announced;

- **BlockSemantics**: Prevents semantics information from ancestor widgets from being included, useful for modal dialogs;
- **SemanticsConfiguration**: Controls detailed semantic properties like labels, hints, and actions.

Flutter's semantic properties include:

- **label**: Provides descriptive text for screen readers;
- **hint**: Explains the result of an action;
- **header**: Identifies heading elements for hierarchical navigation;
- **button**: Identifies interactive elements;
- **textField**: Provides context for input fields;
- **checked, selected**: Communicates selection states for checkboxes, radio buttons, and similar controls;
- **onTap, onLongPress**: Actions that can be triggered by assistive technologies.

Flutter's accessibility implementation is managed through the `SemanticsNode` class, which represents a node in the semantic tree. During the rendering phase, Flutter builds both the widget tree for visual representation and a parallel semantic tree for accessibility. This dual-tree approach differs from React Native's direct property enhancement model and offers more granular control over accessibility information, but typically requires more explicit configuration from developers.

A basic example of applying semantics in Flutter is shown in Listing 4.1:

```
1 // Making a button accessible with semantics
2 Semantics(
3   hint: 'Saves your current work to the cloud',
4   button: true,
5   onTap: () => saveDocument(),
6   child: ElevatedButton(
7     onPressed: saveDocument,
8     child: Text('Save'),
9   ),
10 )
```

Listing 4.1: Basic Semantics implementation in Flutter

Flutter provides tools for debugging accessibility features, most notably the `SemanticsDebugger`, which visualizes the semantic tree and helps developers understand how assistive technologies interpret their applications. This tool can be enabled with a simple flag as shown in Listing 4.2:

```
1 // Enable the semantics debugger in a Flutter app
2 void main() {
3   runApp(
4     Directionality(
5       textDirection: TextDirection.ltr,
6       child: SemanticsDebugger(
7         child: MyApp(),
8       ),
9     ),
10 );
11 }
```

Listing 4.2: Using the SemanticsDebugger in Flutter

4.2.3 Development workflow and advantages

Flutter offers several distinctive features that impact the developer experience:

- **Hot reload:** Allows immediate reflection of code changes during development, significantly speeding up the implementation and testing of accessibility features;
- **Consistent rendering:** Custom rendering engine ensures visual and behavioral consistency across platforms, reducing platform-specific accessibility divergences;

- **Widget catalog:** Extensive built-in widget collection with Material Design and Cupertino (iOS-style) implementations, many with accessibility features pre-configured;
- **Declarative UI:** UI is built by describing the desired state rather than through imperative commands, making it easier to reason about accessibility requirements.

4.2.4 Platform integration and accessibility capabilities

Flutter applications integrate with native platform capabilities through several mechanisms:

- **Platform channels:** Message-passing system for communicating with platform-specific code, allowing access to native accessibility APIs when needed;
- **Plugin system:** Pre-built modules that access native features like camera, location, etc., some specifically designed to enhance accessibility;
- **FFI (Foreign Function Interface):** Direct access to C libraries for performance-critical functions;
- **Accessibility bridges:** Platform-specific code that translates Flutter's semantic properties into native accessibility API calls understood by VoiceOver on iOS and TalkBack on Android.

4.3 Framework architecture and accessibility approach

This section examines the architectural differences between React Native and Flutter, with particular focus on how these differences impact accessibility implementation patterns. Understanding the underlying architecture provides essential context for interpreting the quantitative comparisons presented later in this chapter and correlating them with Budai's implementation findings [4].

4.3.1 Flutter accessibility model

Flutter takes a fundamentally different approach to accessibility, using a widget-based semantic system rather than properties. It automatically creates a parallel accessibility tree alongside the widget tree, with each widget potentially contributing to the semantic structure.

The core of Flutter's accessibility model is the `Semantics` widget, which wraps other widgets to provide accessibility information, as Listing 4.3.

```
1 // Widget wrapped with Semantics for accessibility
2 Semantics(
3   label: 'Section title',
4   header: true,
5   child: Text('My Heading'),
6 )
7
8 Semantics(
9   label: 'Submit form',
10  hint: 'Sends your data to the server',
11  button: true,
12  enabled: !isDisabled,
13  onTap: () => handleSubmit(),
14  child: ElevatedButton(
15    onPressed: isDisabled ? null : handleSubmit,
16    child: Text('Submit'),
17  ),
18 )
```

Listing 4.3: Flutter Semantics widget system

Flutter's approach also includes specialized semantic widgets that modify how semantic information is processed:

- `MergeSemantics`: Combines the semantics of its children into a single node;
- `ExcludeSemantics`: Prevents children from appearing in the accessibility tree;
- `BlockSemantics`: Prevents semantics from ancestors being included.

The characteristics of Flutter's accessibility model include:

- **Explicit semantic nodes:** Accessibility information is explicitly defined through dedicated widgets;

- **Parallel accessibility tree:** A separate tree structure for accessibility that maps to, but is distinct from, the widget tree;
- **Composable semantics:** Semantic information can be composed and modified through widget nesting;
- **Direct native platform integration:** Semantic information is directly mapped to platform accessibility APIs.

4.3.2 Architectural differences affecting implementation

The architectural differences between React Native and Flutter fundamentally influence how developers implement accessibility features. These differences can be categorized into five key areas, which are consistently reflected in Budai's implementation.

4.3.2.1 Mental model and developer workflow

React Native encourages developers to think about accessibility as properties to be added to existing components, similar to adding styling properties. This approach integrates accessibility naturally into the component development process.

Flutter, in contrast, requires developers to think about accessibility as a separate layer of widgets that wrap content widgets. This separation creates a clearer distinction between visual presentation and accessibility semantics, but it also requires developers to maintain two parallel structures.

These paradigms reflect fundamentally different strategies: one based on enhancing existing components through properties, the other on explicitly wrapping them to assign accessibility roles.

4.3.2.2 Code organization and implementation overhead

The property-based approach of React Native generally results in more concise and readable code, as accessibility information is integrated directly into component definitions. This can make the code easier to understand at a glance, particularly for simpler components.

Flutter's widget-based approach tends to increase code verbosity and nesting depth, potentially making code more difficult to follow. However, this explicit structure can also make accessibility considerations more visible and harder to overlook.

The quantitative analysis conducted reveals significant differences in implementation overhead. As shown in Table 4.5, Flutter implementations typically require more lines of code than equivalent React Native implementations, with differences ranging from 40% to 200% for common components.

Table 4.5: Implementation overhead analysis

Component	React Native LOC	Flutter LOC	Difference (LOC)	Complexity Impact
Heading	7	11	+4 (57%)	Low
Text language	7	21	+14 (200%)	High
Text abbreviation	7	14	+7 (100%)	Medium
Button	12	18	+6 (50%)	Low
Form field	15	23	+8 (53%)	Medium
Custom gesture	22	28	+6 (27%)	Medium

4.3.2.3 Platform integration approach

React Native's JavaScript bridge mediates between components and native accessibility APIs, which can introduce performance considerations for complex interfaces. Flutter's direct C++ implementation provides more direct access to native accessibility features, potentially offering performance benefits for accessibility-heavy applications.

The different architectural approaches also impact testing and debugging workflows. React Native's property-based model makes it easier to inspect accessibility properties directly within component definitions.

Flutter's separate semantic tree can be more challenging to debug, but the framework provides specialized tools like the `SemanticsDebugger` widget that visualizes the accessibility tree, offering more comprehensive introspection capabilities.

4.3.3 Framework architecture comparison

The comparative analysis implemented in the Framework comparison screen reveals fundamental architectural differences between React Native and Flutter that significantly impact accessibility implementation patterns. These differences can be categorized into five key areas:

4.3.3.1 Mental model and developer workflow

React Native encourages developers to think about accessibility as properties to be added to existing components, similar to adding styling properties. This approach integrates accessibility naturally into the component development process, as shown in Listing 4.4.

```
1 <TouchableOpacity
2   onPress={handlePress}
3   accessibilityRole="button"
4   accessibilityLabel="Submit form"
5   accessibilityHint="Activates form submission"
6 >
7   <Text>Submit</Text>
8 </TouchableOpacity>
```

Listing 4.4: Property-based accessibility pattern in React Native

Flutter, in contrast, requires developers to think about accessibility as a separate layer of widgets that wrap content widgets. This separation creates a clearer distinction between visual presentation and accessibility semantics, but it also requires developers to maintain two parallel structures, as shown in Listing 4.5.

```
1 Semantics(
2   label: 'Submit form',
3   hint: 'Activates form submission',
4   button: true,
5   child: ElevatedButton(
6     onPressed: handleSubmit,
7     child: Text('Submit'),
8   ),
9 )
```

Listing 4.5: Widget-based accessibility pattern in Flutter

4.3.3.2 Code organization and implementation overhead

The property-based approach of React Native generally results in more concise and readable code, as accessibility information is integrated directly into component definitions. This can make the code easier to understand at a glance, particularly for simpler components.

Flutter's widget-based approach tends to increase code verbosity and nesting depth, potentially making code more difficult to follow. However, this explicit structure can also make accessibility considerations more visible and harder to overlook.

As quantified in Table 4.3, Flutter implementations typically require more lines of code than equivalent React Native implementations, with differences ranging from 40% to 200% for common components.

4.3.3.3 Platform integration approach

React Native's JavaScript bridge mediates between components and native accessibility APIs, which can introduce performance considerations for complex interfaces. Flutter's direct C++ implementation provides more direct access to native accessibility features, potentially offering performance benefits for accessibility-heavy applications.

The different architectural approaches also impact testing and debugging workflows. React Native's property-based model makes it easier to inspect accessibility properties directly within component definitions.

Flutter's separate semantic tree can be more challenging to debug, but the framework provides specialized tools like the `SemanticsDebugger` widget that visualizes the accessibility tree, offering more comprehensive introspection capabilities.

4.4 Framework comparison screen: a detailed analysis

To provide a comprehensive, empirical foundation for comparing implementation patterns, the *AccessibleHub* includes a dedicated Framework comparison screen that offers a formal, evidence-based analysis tool for evaluating accessibility implementation across mobile development frameworks. This screen transforms the theoretical architectural differences

CHAPTER 4. ACCESSIBILITY ANALYSIS: FRAMEWORK COMPARISON AND IMPLEMENTATION PATTERNS

discussed above into quantifiable metrics and side-by-side comparisons.

The Framework comparison screen's formal methodology aligns with the analysis provided in Section 3.3.3, but extends it through visual representation and interactive exploration of metrics. Unlike other screens in the *AccessibleHub* application that focus primarily on educational content or component examples, this screen implements a structured, academically-grounded system for comparing React Native and Flutter using transparent metrics, formal methodology, and verifiable data. Figure 4.2 shows the main interface of the Framework comparison screen.

CHAPTER 4. ACCESSIBILITY ANALYSIS: FRAMEWORK COMPARISON AND IMPLEMENTATION PATTERNS




Figure 4.2: Framework comparison screen showing overview information for both frameworks

4.4.0.1 Component inventory and WCAG/MCAG mapping

Table 4.6 provides a formal mapping between the UI components, their semantic roles, the specific WCAG 2.2 criteria they address, and their React Native implementation properties.

CHAPTER 4. ACCESSIBILITY ANALYSIS: FRAMEWORK COMPARISON AND IMPLEMENTATION PATTERNS

Table 4.6: Framework comparison screen component-criteria mapping

Component	Semantic Role	WCAG 2.2 Criteria	MCAG Considerations	Implementation Properties
Hero Title	heading	1.4.3 Contrast (AA) 2.4.6 Headings (AA)	Text readability on variable screen sizes	accessibility Role="header"
Hero Subtitle	text	1.4.3 Contrast (AA)	Content description	Text styling with semantic connection to title
Framework Selection Buttons	button	1.4.3 Contrast (AA) 2.5.8 Target Size (AA) 4.1.2 Name, Role, Value (A)	Touch target size Framework choice	accessibility Role="button", accessibility Label, accessibility State={{selected: ...}}
Category Tabs	tab	1.4.3 Contrast (AA) 4.1.2 Name, Role, Value (A)	Categorical organization	accessibility Role="tab", accessibility State={{selected: ...}}
Tab Icons	none	1.1.1 Non-text Content (A)	Reduction of unnecessary focus stops	importantFor Accessibility="no-hide descendants"

Continued on next page

CHAPTER 4. ACCESSIBILITY ANALYSIS: FRAMEWORK COMPARISON AND IMPLEMENTATION PATTERNS

Table 4.6 – continued from previous page

Component	Semantic Role	WCAG 2.2 Criteria	MCAG Considerations	Implementation Properties
Framework Info Card	none	1.3.1 Info and Relationships (A) 1.4.3 Contrast (AA)	Content grouping	Semantic container with proper styling
Statistic Cards	button	1.4.3 Contrast (AA) 4.1.2 Name, Role, Value (A)	Information presentation Touch target size	accessibility Role="button", accessibilityLabel
Rating Bar	progressbar	1.4.3 Contrast (AA) 4.1.2 Name, Role, Value (A)	Progress visualization	accessibility Role="progressbar", accessibilityLabel
Info Button	button	1.4.3 Contrast (AA) 4.1.2 Name, Role, Value (A)	Information access	accessibility Role="button", accessibilityLabel
Modal Dialog	dialog	2.4.3 Focus Order (A) 4.1.2 Name, Role, Value (A)	Keyboard trap prevention	accessibilityView IsModal, Focus management implementation

Continued on next page

Table 4.6 – continued from previous page

Component	Semantic Role	WCAG 2.2 Criteria	MCAG Considerations	Implementation Properties
Modal Tabs	tablist	2.4.7 Focus Visible (AA) 4.1.2 Name, Role, Value (A)	Touch interaction	accessibility Role="tablist", accessibility State={{selected: isActive}}

4.4.0.2 Formal methodology system implementation

The Framework comparison screen implements a formal, academically rigorous methodology system that establishes a systematic approach to framework evaluation. Unlike other screens in the application that focus on practical implementation examples, this screen incorporates a formal methodological framework evidenced in Figure 4.3.

CHAPTER 4. ACCESSIBILITY ANALYSIS: FRAMEWORK COMPARISON AND IMPLEMENTATION PATTERNS




Figure 4.3: Methodology tabs of Framework comparison screen

The formal methodology system implements several critical characteristics of academic accessibility research:

- 1. Explicit methodology declaration:** The screen clearly states the research method-

ology used, including both empirical testing and documentation analysis;


2. **Transparent testing protocol:** The methodology specifically documents testing with screen readers on precisely identified devices (VoiceOver iOS 16, TalkBack Android 13) and references WCAG 2.2 compliance verification;
3. **Source citation:** The methodology includes proper citation of academic sources, establishing an evidence-based foundation;
4. **Device specification:** The methodology includes explicit hardware specifications (iPhone 14, Pixel 7), creating reproducibility for the evaluation.

This formal methodology implementation exemplifies the application's commitment to rigorous, evidence-based accessibility evaluation that moves beyond subjective assessments to create verifiable, reproducible comparisons.

4.4.0.3 Academic reference implementation

A distinctive feature of the Framework comparison screen is its comprehensive implementation of academic references. This feature directly connects framework evaluation to peer-reviewed research and formal documentation, creating an evidence-based foundation for accessibility comparisons. Figure 4.4 shows the academic references card and its expanded modal dialog.

CHAPTER 4. ACCESSIBILITY ANALYSIS: FRAMEWORK COMPARISON AND IMPLEMENTATION PATTERNS



(a) Academic references overview

(b) References modal with formal citations

Figure 4.4: Academic references implementation with formal citation structure

The academic reference system implements several key features:

- 1. Formal citation structure:** Each reference includes complete bibliographic information including authors, publication venue, year, and DOI identifiers where applicable;

2. **Multi-category reference system:** References are categorized by type (research paper, official documentation), creating a clear hierarchy of evidence;
3. **Modal dialog organization:** References are presented in a structured, tabbed modal dialog with overview, details, and references tabs, providing progressive disclosure of information;
4. **Systematic literature inclusion:** The reference system integrates both primary research by Gaggi and Perinello [21] and systematic reviews by Palmieri [20], creating a comprehensive evidence base.

Figure 4.5 shows the extended References tab with complete citation information including access dates and URLs for official documentation.




Figure 4.5: References tab showing formatted citations with complete bibliographic information

This academic reference implementation exemplifies how accessibility evaluation can be grounded in formal, verifiable sources, creating accountability and reproducibility in framework comparison.

4.4.0.4 Framework data structure

The Framework comparison screen implements a comparative analysis through a structured data repository for both React Native and Flutter. This structured approach is visualized through framework selection buttons and framework-specific information cards shown

CHAPTER 4. ACCESSIBILITY ANALYSIS: FRAMEWORK COMPARISON AND IMPLEMENTATION PATTERNS

in Figure 4.6.

The figure displays two side-by-side screenshots of a mobile application interface titled "Framework Comparison". Both screens show the same basic layout with minor differences in button colors and overall design.

Top Bar: Both screens have a blue header bar with the text "Home > Framework Comparison" and three vertical dots on the right. The time "11:45" and battery level "90%" are visible at the top right.

Main Content Area: Both screens feature a large white box labeled "Framework Comparison" and a sub-section describing "Evidence-based comparison of accessibility features in React Native and Flutter".

Framework Selection: Below the main section, there are two buttons: "React Native" (blue) and "Flutter" (white). Underneath these buttons are two rounded rectangular buttons: "Overview" (blue with white text) and "Accessibility" (white with black text).

React Native Details: A large white box contains the following information:

- React Native**
- by Meta (Facebook)
- Version 0.73**
- A framework for building native applications using React

Flutter Details: A large white box contains the following information:

- Flutter**
- by Google
- Version 3.16**
- A framework for building multi-platform apps using Dart

Bottom Metrics: Both screens show three metrics in white boxes:

- Language:** React Native uses "JavaScript/TypeScript" (indicated by a code icon), while Flutter uses "Dart" (indicated by a code icon).
- Learning Curve:** React Native has a "Moderate" learning curve (indicated by a line graph icon), while Flutter has a "Steep" learning curve (indicated by a line graph icon).
- Hot Reload:** Both frameworks support "Yes" (indicated by a lightning bolt icon).

(a) React Native framework details (left screenshot)

(b) Flutter framework details (right screenshot)

Figure 4.6: Framework selection interface showing structured framework data

The framework data structure implements several key features:

- 1. Consistent metadata structure:** Each framework includes consistent metadata

fields (name, company, version, description), enabling direct comparison;

2. **Visual state indication:** The selected framework is visually indicated through background color changes and maintains this state for screen readers via `accessibilityState`;
3. **Feature categorization:** Framework features are consistently categorized into core attributes (Language, Learning Curve, Hot Reload), creating a systematic comparison structure;
4. **Quantitative representation:** Features include both qualitative descriptions (e.g., "Moderate" learning curve) and quantitative indicators where applicable, enabling objective comparison.

This structured data approach transforms subjective framework comparisons into a systematic, consistent evaluation framework that enables developers to make evidence-based decisions about framework selection based on accessibility considerations.

4.4.0.5 Implementation complexity analysis

A key contribution of the Framework comparison screen is its formal analysis of implementation complexity across frameworks. Unlike simple feature comparisons, this screen implements a detailed complexity analysis using multiple metrics. Figure 4.7 shows both the complexity analysis card and its expanded modal view.

CHAPTER 4. ACCESSIBILITY ANALYSIS: FRAMEWORK COMPARISON AND IMPLEMENTATION PATTERNS




Figure 4.7: Implementation complexity analysis with detailed metrics

The implementation complexity analysis incorporates multiple evaluation dimensions:

- 1. Lines of code (LOC) metric:** The analysis quantifies implementation complexity through precise LOC counts for each accessibility feature, providing an objective

measure of implementation effort;

2. **Qualitative complexity assessment:** Features are categorized using a standardized Low/Medium/High complexity scale, with color coding (green/yellow/red) for visual differentiation;
3. **Framework knowledge requirement:** The analysis considers the required knowledge of framework-specific concepts, addressing the learning curve aspect of accessibility implementation;
4. **Real-world testing verification:** Complexity assessments are validated through testing on real devices with actual screen readers, ensuring practical relevance.


Figure 4.8 shows the detailed implementation comparison for specific accessibility features across both frameworks.

The feature-level implementation analysis in Figure 4.8 demonstrates significant differences between frameworks:

1. **Heading element implementation:** React Native requires 7 LOC with Low complexity, while Flutter requires 11 LOC with Medium complexity;
2. **Language declaration:** The contrast is more pronounced for language declaration, with React Native requiring 7 LOC and Flutter requiring 21 LOC;
3. **Default accessibility status:** The analysis shows React Native has 1/3 features accessible by default, while Flutter has 0/3, providing a clear metric for out-of-the-box accessibility;
4. **Total implementation overhead:** React Native requires 21 total LOC for implementation, while Flutter requires 46 LOC, quantifying the overall implementation effort difference.

This detailed implementation comparison provides developers with concrete, evidence-based metrics for understanding the accessibility implementation effort required for each framework.

CHAPTER 4. ACCESSIBILITY ANALYSIS: FRAMEWORK COMPARISON AND IMPLEMENTATION PATTERNS



(a) Feature implementation comparison

(b) Implementation code examples

Figure 4.8: Implementation details showing feature-level comparison and code examples

4.4.0.6 Specific accessibility feature comparison

The Framework comparison screen implements detailed comparisons of specific accessibility features, providing both implementation attributes and code examples. Figure 4.9 shows

CHAPTER 4. ACCESSIBILITY ANALYSIS: FRAMEWORK COMPARISON AND IMPLEMENTATION PATTERNS

implementation details for language declaration and text abbreviations in React Native.




Figure 4.9: Language modals of Framework comparison screen

The feature implementation comparison includes several key elements:

1. **WCAG success criteria mapping:** Each feature is explicitly mapped to relevant

WCAG criteria (e.g., Text Abbreviations maps to 3.1.4), creating a clear connection between implementation and compliance;

2. **Default accessibility status:** The comparison explicitly indicates whether each feature is accessible by default (Yes/No), highlighting areas requiring developer intervention;
3. **Implementation notes:** Each feature includes specific implementation notes explaining the required approach (e.g., "Requires adding accessibilityLabel property");
4. **Concrete code examples:** The comparison provides complete, executable code examples that developers can directly reference for implementation.

This feature-level comparison transforms abstract accessibility requirements into concrete implementation guidance with direct reference to standards compliance, helping developers understand not just what to implement but why and how.

4.4.0.7 Modal dialog accessibility implementation

The Framework comparison screen implements several modal dialogs that incorporate comprehensive accessibility features. Figure 4.10 shows the implementation details modal with properly structured tabs.

CHAPTER 4. ACCESSIBILITY ANALYSIS: FRAMEWORK COMPARISON AND IMPLEMENTATION PATTERNS




Figure 4.10: Modal dialogs for the Implementation Tab

The modal dialog implementation addresses several critical accessibility requirements:

- 1. Clear semantic role:** Modals are properly identified with `accessibilityViewIsModal`, ensuring screen readers understand their role;

2. **Tab role assignment:** Tab navigation properly implements `accessibilityRole="tab"` and `accessibilityState` to communicate selection state;
3. **Focus management:** When modals open, focus moves to the modal header and returns to the triggering element when closed, maintaining context;
4. **Hierarchical content structure:** Content within modals maintains proper heading structure and semantic relationships, ensuring screen reader users can navigate efficiently.

This accessible modal implementation ensures that complex information like methodology details and academic references remains accessible to all users, including those using screen readers.

4.4.0.8 Screen reader support analysis

Table 4.7 presents results from systematic testing of the Framework comparison screen with screen readers on both iOS and Android platforms.

Table 4.7: Framework comparison screen reader testing results

Test Case	VoiceOver (iOS 16)	TalkBack (Android 14-15)	WCAG Criteria Addressed
Hero Title	✓ Announces “Framework Comparison, heading”	✓ Announces “Framework Comparison, heading”	1.3.1 Info and Relationships (A), 2.4.6 Headings and Labels (AA)
Framework Selection	✓ Announces framework name and selection state	✓ Announces framework name and selection state	4.1.2 Name, Role, Value (A)

Continued on next page

Table 4.7 – continued from previous page

Test Case	VoiceOver (iOS 16)	TalkBack (Android 14-15)	WCAG Criteria Addressed
Category Tabs	✓ Announces tab name and selection state	✓ Announces tab name and selection state	4.1.2 Name, Role, Value (A)
Framework Info	✓ Announces framework details in logical order	✓ Announces framework details in logical order	1.3.1 Info and Relationships (A), 1.3.2 Meaningful Sequence (A)
Statistic Cards	✓ Announces label and value	✓ Announces label and value	1.3.1 Info and Relationships (A)
Rating Bars	✓ Announces value and range	✓ Announces value and range	1.3.1 Info and Relationships (A), 4.1.2 Name, Role, Value (A)
Info Buttons	✓ Announces purpose and action	✓ Announces purpose and action	2.4.4 Link Purpose (In Context) (A), 2.4.9 Link Purpose (Link Only) (AAA)
Modal Dialog Opening	✓ Focus moves to dialog title	✓ Focus moves to dialog title	2.4.3 Focus Order (A)
Modal Tab Navigation	✓ Announces tab selection state	✓ Announces tab selection state	4.1.2 Name, Role, Value (A)
Implementation Examples	✓ Announces code examples as text blocks	✓ Announces code examples as text blocks	1.3.1 Info and Relationships (A)

Continued on next page

Table 4.7 – continued from previous page

Test Case	VoiceOver (iOS 16)	TalkBack (Android 14-15)	WCAG Criteria Addressed
Color-coded Complexity	✓ Announces complexity level, not just color	✓ Announces complexity level, not just color	1.4.1 Use of Color (A)

The implementation addresses several key screen reader considerations:

1. **State communication:** Selection states for frameworks and tabs are explicitly communicated via `accessibilityState`, ensuring screen reader users understand current selection;
2. **Logical focus order:** Screen elements follow a logical navigation order that matches visual presentation, creating a coherent mental model for screen reader users;
3. **Code example accessibility:** Code examples are presented in accessible text blocks with proper structure, rather than as images, ensuring screen reader users can access implementation details;
4. **Non-reliance on color:** Information conveyed through color (complexity indicators) is redundantly provided through explicit text labels, ensuring color-blind users and screen reader users receive the same information.

4.4.0.9 Implementation overhead analysis

Table 4.8 quantifies the additional code required to implement accessibility features in the Framework comparison screen.

Table 4.8: Framework comparison screen accessibility implementation overhead

Accessibility Feature	Lines of Code	Percentage of Total Code	Complexity Impact
Semantic Roles	24 LOC	2.8%	Low
Accessibility Labels	36 LOC	4.2%	Medium
Element Hiding	22 LOC	2.6%	Low
Focus Management	28 LOC	3.3%	High
Accessibility Values	18 LOC	2.1%	Medium
Status Announcements	16 LOC	1.9%	Medium
Modal Accessibility	32 LOC	3.7%	High
Tab Role Assignment	12 LOC	1.4%	Medium
Accessibility State	20 LOC	2.3%	Medium
Rating Bar Accessibility	22 LOC	2.6%	Medium
Total	230 LOC	26.9%	Medium-High

This analysis reveals that implementing comprehensive accessibility for the Framework comparison screen adds approximately 26.9% to the code base. The most significant contributors are accessibility labels (4.2%) and modal accessibility (3.7%), reflecting the information-rich nature of this screen and the complex interaction patterns with modals and tabs. The implementation overhead is justified by the improved user experience for people with disabilities and the educational value demonstrated through the formal framework comparison.

4.4.0.10 WCAG conformance by principle

Table 4.9 provides a detailed analysis of WCAG 2.2 compliance by principle for the Framework comparison screen:

CHAPTER 4. ACCESSIBILITY ANALYSIS: FRAMEWORK COMPARISON AND IMPLEMENTATION PATTERNS

Table 4.9: Framework comparison screen WCAG compliance analysis by principle

Principle	Description	Implementation Level	Key Success Criteria
1. Perceivable	Information and UI components must be presentable to users in ways they can perceive	12/13 (92%)	1.1.1 Non-text Content (A) 1.3.1 Info and Relationships (A) 1.4.1 Use of Color (A) 1.4.3 Contrast (Minimum) (AA) 1.4.8 Visual Presentation (AAA)
2. Operable	UI components and navigation must be operable	16/17 (94%)	2.4.3 Focus Order (A) 2.4.4 Link Purpose (A) 2.4.6 Headings and Labels (AA) 2.4.7 Focus Visible (AA) 2.5.8 Target Size (Minimum) (AA) 2.4.8 Location (AAA) 2.4.9 Link Purpose (Link Only) (AAA)

Continued on next page

Table 4.9 – continued from previous page

Principle	Description	Implementation Level	Key Success Criteria
3. Understandable	Information and operation of UI must be understandable	9/10 (90%)	3.2.1 On Focus (A) 3.2.2 On Input (A) 3.2.4 Consistent Identification (AA) 3.3.2 Labels or Instructions (A) 3.2.5 Change on Request (AAA)
4. Robust	Content must be robust enough to be interpreted by a wide variety of user agents	3/3 (100%)	4.1.1 Parsing (A) 4.1.2 Name, Role, Value (A) 4.1.3 Status Messages (AA)

The WCAG compliance analysis in Table 4.9 demonstrates exceptional conformance across all principles, with particular strength in the Robust principle (100% compliance). The implementation of multiple AAA criteria, including 1.4.8 (Visual Presentation), 2.4.8 (Location), 2.4.9 (Link Purpose - Link Only), and 3.2.5 (Change on Request) exceeds standard requirements to create an enhanced user experience for people with disabilities. The Framework comparison screen achieves high compliance across all WCAG principles, with particular strength in the Perceivable, Operable, and Robust principles.

4.4.0.11 Mobile-specific considerations

The Framework comparison screen addresses several mobile-specific accessibility considerations beyond standard WCAG requirements:

1. **Framework-specific adaptation:** The comparison explicitly evaluates each frame-

work's support for mobile-specific accessibility features, addressing the challenges of cross-platform development;

2. **Screen reader gesture support:** The evaluation includes specific assessment of each framework's support for screen reader gestures, a mobile-specific consideration not fully captured in WCAG;
3. **Touch target optimization:** Interactive elements implement generous touch targets exceeding the minimum size requirements, addressing the specific challenges of touch interaction;
4. **Responsive layout adaptation:** The interface adapts to different screen orientations and device types, maintaining accessibility across the varied landscape of mobile form factors;
5. **Platform-specific implementation patterns:** The comparison addresses the platform-specific nature of accessibility implementation, recognizing that mobile accessibility often requires different approaches for iOS and Android.

4.4.0.12 Beyond WCAG: evidence-based accessibility evaluation guidelines

The Framework comparison screen embodies several principles that extend beyond standard WCAG requirements, particularly focusing on evidence-based evaluation and formal methodology:

1. **Academic grounding principle:** Accessibility evaluations are grounded in peer-reviewed research and formal methodologies. The screen implements this through explicit citations to academic papers and clearly defined evaluation protocols;
2. **Quantitative metric transparency:** Framework evaluations use explicit, quantitative metrics with clearly defined calculation methodologies. The implementation demonstrates this through LOC counts and explicit complexity ratings;
3. **Implementation complexity consideration:** Accessibility evaluation assess not just feature presence but implementation complexity. The screen implements this

through multi-dimensional complexity assessment (LOC, qualitative rating, knowledge requirements);

4. **Empirical testing validation:** Accessibility claims are validated through documented testing on specific devices and platforms. The implementation includes explicit references to test devices and operating system versions;
5. **Comparative analysis principle:** Accessibility features are evaluated through direct side-by-side comparison using consistent metrics. The screen implements this through structured comparison of identical features across frameworks.

These extended principles establish a foundation for evidence-based accessibility evaluation that moves beyond subjective assessments or checklist compliance, creating a more rigorous, academically grounded approach to framework comparison.


4.4.0.13 Screen reader support comparison methodology

The Framework comparison screen implements a rigorous methodology for evaluating screen reader support across frameworks. This methodology, shown in Figure 4.11, quantifies support using multiple dimensions with specific weighting.

The screen reader support analysis implements a formal evaluation methodology with the following characteristics:

1. **Component-based weighting:** Screen reader compatibility receives a 30% weighting in the overall accessibility score, recognizing its critical importance for blind users;
2. **Platform-specific assessment:** The methodology explicitly evaluates both VoiceOver (iOS) and TalkBack (Android) support separately, addressing the platform-specific nature of screen reader implementation;
3. **Multi-dimensional evaluation:** Screen reader support is assessed across multiple dimensions including announcement quality, gesture support, and semantics interpretation;

CHAPTER 4. ACCESSIBILITY ANALYSIS: FRAMEWORK COMPARISON AND IMPLEMENTATION PATTERNS



(a) Screen reader testing methodology

(b) Screen reader metrics calculation

Figure 4.11: Screen reader support comparison methodology and calculation approach

4. **Empirical validation:** Ratings are based on actual testing with specific device and operating system configurations, creating reproducible results.

This formal screen reader evaluation methodology establishes a systematic approach to

CHAPTER 4. ACCESSIBILITY ANALYSIS: FRAMEWORK COMPARISON AND IMPLEMENTATION PATTERNS

comparing screen reader support that moves beyond subjective assessments to create quantifiable, verifiable metrics.

4.4.0.14 Implementation complexity calculation methodology

The Framework comparison screen implements a formal methodology for calculating implementation complexity, shown in Figure 4.11.




Figure 4.12: Formal calculation methodology for implementation complexity

The implementation complexity calculation methodology includes several key components:

1. **Explicit mathematical formula:** The methodology includes a formal mathematical formula for calculating implementation scores based on lines of code:

```
implementationScore = Math.max(0, Math.min(5, 5 - (totalLinesOfCode / 10)));
```

2. **Normalization mechanism:** Scores are explicitly normalized to a 0-5 scale to enable consistent comparison;
3. **LOC-based quantification:** The formula establishes an inverse relationship between lines of code and implementation score, recognizing that lower implementation overhead (fewer LOC) represents better accessibility support;
4. **Source citation:** The methodology cites specific sources including static code analysis and WCAG 2.2 implementation examples.

This formal calculation methodology creates a transparent, reproducible approach to quantifying implementation complexity that enables objective framework comparison.

4.4.0.15 Feature-specific implementation comparison

The Framework comparison screen implements detailed feature-by-feature comparison of accessibility implementations across frameworks. Figure 4.11 shows the implementation details for specific accessibility features.

The feature-specific comparison implements several key analytical elements:

1. **Consistent metric application:** Each feature is evaluated using the same metrics (LOC, complexity) across frameworks, enabling direct comparison;
2. **Complexity visualization:** Complexity ratings are visually coded (green for Low, orange for Medium) for quick comprehension while maintaining accessibility through text labels;
3. **WCAG criteria mapping:** Features are explicitly mapped to relevant WCAG success criteria (e.g., Heading Elements to 1.3.1, 2.4.6), creating a standards-based evaluation framework;

4. **Code example comparison:** Implementation examples show directly comparable code implementations for identical features, highlighting the practical differences in syntax and structure.

This feature-level comparison transforms abstract accessibility requirements into concrete, comparable implementations that developers can directly reference for their own work.

4.5 Accessibility implementation patterns

Accessibility implementation in mobile frameworks reveals fundamental architectural differences that impact developer experience, code complexity, and ultimately, the accessibility of the final application. This section examines the core implementation patterns observed in React Native and Flutter, drawing from real-world examples in the *AccessibleHub* and Budai's implementations. While Section 4.3 established the architectural foundations, this section analyzes the practical manifestations of these differences through concrete implementation patterns.

4.5.1 Property-based vs widget-based implementation patterns

The most fundamental difference between React Native and Flutter's accessibility approaches is visible in their core implementation pattern: React Native follows a property-based model, while Flutter employs a widget-based approach. This distinction profoundly affects code structure, verbosity, and maintainability.

In React Native, accessibility features are applied directly to components through properties, integrating seamlessly with the component definition as seen in Listing 4.6.

```
1 <TouchableOpacity
2   style={themedStyles.card}
3   onPress={() => handleComponentPress(route, title)}
4   accessibilityRole="button"
5   accessibilityLabel="Buttons and Touchables component"
6   accessibilityHint="Navigate to component details"
7 >
8   <View style={themedStyles.cardHeader}>
9     <View style={themedStyles.iconWrapper}>
10    <Ionicons
11      name="radio-button-on-outline"
12      size={24}
13      color={colors.primary}
14      accessibilityElementsHidden
15    />
16  </View>
17  <Text style={themedStyles.cardTitle}>Buttons &
18    Touchables</Text>
19 </View>
</TouchableOpacity>
```

Listing 4.6: Property-based accessibility pattern in React Native

In contrast, Flutter's widget-based approach requires wrapping existing widgets within specialized `Semantics` widgets to add accessibility information, creating additional nesting levels as demonstrated in Listing 4.7.

```
1 Semantics(
2   label: _gestureOneCompleted
3     ? 'Gesture one completed'
4     : 'Gesture one',
5   excludeSemantics: _gestureOneCompleted,
6   child: GestureDetector(
7     onTap: () {
8       setState(() {
9         _gestureOneCompleted = true;
10      });
11      _handleTap();
12    },
13    child: ScaleTransition(
14      scale: _animation1,
15      child: Container(
16        color: Colors.blue,
17        width: 100,
18        height: 100,
19      ),
20    ),
21  ),
22)
```

Listing 4.7: Widget-based accessibility pattern in Flutter

The property-based approach allows developers to integrate accessibility directly within the component definition, maintaining a flat structure. The widget-based approach requires additional wrapper widgets, increasing nesting depth and potentially complicating code readability.

This fundamental architectural difference directly impacts implementation overhead measurements in Table 4.5, where Flutter implementations consistently require more code (typically 27%-200% more lines) for equivalent functionality compared to React Native.

Table 4.10: Pattern implementation overhead comparison

Pattern	React Native	Flutter	Impact on Verbosity
Accessibility Role	accessibility Role="button"	Semantics (button: true, child: Widget)	+75%
Label	accessibility Label="text"	Semantics(label: "text", child: Widget)	+100%
Hide from Screen Readers	accessibility ElementsHidden	Semantics(exclude Semantics: true, child: Widget)	+120%

As shown in Table 4.10, even the most basic accessibility patterns require significantly more code in Flutter compared to React Native. This increased verbosity can impact developer productivity and code maintainability in larger projects.

4.5.2 State communication patterns

Communicating component states to assistive technologies represents a critical accessibility requirement. Both frameworks provide mechanisms for this, but with different implementation patterns.

React Native's pattern uses the `accessibilityState` property to communicate states like "checked," "disabled," or "selected" as shown in Listing 4.8.

```

1 <Switch
2   value={value}
3   onValueChange={onToggle}
4   trackColor={{ false: '#767577', true: colors.primary }}
5   thumbColor={value ? '#fff' : '#f4f3f4'}
6   accessibilityLabel={`${title}. ${description}. ${value ? 'Enabled' :
7     'Disabled'}.`}
8   accessibilityRole="switch"
9   accessibilityState={{ checked: value }}>

```

Listing 4.8: State communication in React Native

Flutter's approach relies on specific semantic properties for each state type, as demon-

strated in Budai's form implementation in Listing 4.9.

```
1 SwitchListTile(  
2   title: Text('Accept Terms'),  
3   value: _acceptTerms,  
4   onChanged: (value) {  
5     setState(() {  
6       _acceptTerms = value;  
7     });  
8   },  
9 ),
```

Listing 4.9: State communication in Flutter

The Flutter approach appears simpler at first glance but lacks the explicit state communication seen in React Native's implementation. To achieve equivalent functionality in Flutter with explicit accessibility state announcement, Listing 4.10 implementation would require additional Semantics wrapping:

```
1 Semantics(  
2   toggled: _acceptTerms,  
3   child: SwitchListTile(  
4     title: Text('Accept Terms'),  
5     value: _acceptTerms,  
6     onChanged: (value) {  
7       setState(() {  
8         _acceptTerms = value;  
9       });  
10    },  
11  ),  
12 )
```

Listing 4.10: Enhanced state communication in Flutter

This comparison highlights how React Native's property-based approach explicitly communicates state information to assistive technologies with minimal code, while Flutter often requires additional semantic wrappers to achieve the same level of state communication.

Table 4.11 provides an overview of the different state communication patterns and their implementation complexity across both frameworks.

Table 4.11: State communication pattern comparison

State Type	React Native	Flutter	Default Support
Checked	<code>accessibility State={checked: true}</code>	Semantics(toggled: true, child: Widget)	RN: ✓, FL: ✗
Disabled	<code>accessibility State={disabled: true}</code>	Semantics(enabled: false, child: Widget)	RN: ✓, FL: ✓
Selected	<code>accessibility State={selected: true}</code>	Semantics(selected: true, child: Widget)	RN: ✓, FL: ✓

As shown in Table 4.11, React Native provides default accessibility state communication for all common states through a unified property structure, while Flutter requires additional semantic wrappers for some state types.

4.5.3 Navigation order and focus management patterns

Screen reader navigation order significantly impacts the usability of applications for visually impaired users. The frameworks employ different strategies to control this critical aspect.

React Native relies primarily on the natural DOM order supplemented by optional properties to influence navigation, as shown in *AccessibleHub*'s implementation in Listing 4.11.

```
1 <ScrollView
2   contentContainerStyle={{ paddingBottom: 24 }}
3   accessibilityRole="scrollview"
4   accessibilityLabel="Mobile Accessibility Best Practices Screen"
5 >
6   <View style={themedStyles.heroCard}>
7     <Text style={themedStyles.heroTitle} accessibilityRole="header">
8       Mobile Accessibility Best Practices
9     </Text>
10    <Text style={themedStyles.heroSubtitle}>
11      Essential guidelines for creating accessible React Native
12      applications
13    </Text>
14  </View>
15
16  <View style={themedStyles.section}>
17    /* Navigation flows naturally through component hierarchy */
18    <TouchableOpacity
19      style={themedStyles.card}
20      accessibilityRole="button"
21      accessibilityLabel="WCAG Guidelines"
22    >
23      /* Component content */
24    </TouchableOpacity>
25  </View>
</ScrollView>
```

Listing 4.11: Navigation order in React Native

In contrast, Flutter provides more granular control through explicit `sortKey` values, which can override the natural widget order. Budai's implementation uses this approach extensively, as seen in Listing 4.12.

CHAPTER 4. ACCESSIBILITY ANALYSIS: FRAMEWORK COMPARISON AND IMPLEMENTATION PATTERNS

```
1 Scaffold(
2   appBar: AppBar(
3     title: Semantics(
4       sortKey: OrdinalSortKey(2.0), // Explicit order control
5       header: true,
6       child: Text(
7         'Gestures',
8         textAlign: TextAlign.center,
9       ),
10    ),
11   leading: Semantics(
12     sortKey: OrdinalSortKey(3.0), // Explicit order control
13     child: IconButton(
14       icon: Icon(Icons.arrow_back, semanticLabel: 'Back to the
15           HomePage'),
16       onPressed: () {
17         Navigator.pushNamedAndRemoveUntil(
18           context, '/',
19           (route) => false,
20         );
21       },
22     ),
23   body: SingleChildScrollView(
24     child: Column(
25       children: [
26         Semantics(
27           sortKey: OrdinalSortKey(1.0), // Explicit order control
28           label: _gestureOneCompleted ? 'Gesture one completed' :
29               'Gesture one',
30           excludeSemantics: _gestureOneCompleted,
31           child: GestureDetector(
32             // Implementation details
33           ),
34         ),
35       ],
36     ),
37   )
)
```

Listing 4.12: Navigation order in Flutter

The Flutter approach offers more precise control but requires developers to explicitly manage the navigation order through `sortKey` values. This creates a maintenance burden and potential for errors if sort keys are not kept consistent throughout the application. React Native's approach is more implicit, relying on the natural component hierarchy with occasional interventions when needed.

An interesting observation is that while Flutter's approach requires more developer effort, it can provide more consistent cross-platform navigation behavior in complex interfaces. React Native's approach is simpler but may require platform-specific adjustments for complex navigation patterns.

Table 4.12 summarizes the key differences in navigation control between the frameworks.

Table 4.12: Navigation order pattern comparison

Framework	Order Control	Implementation Approach	Developer Overhead
React Native	Implicit, component-based	Natural DOM flow with optional overrides	Low
Flutter	Explicit, developer-defined	Semantics sortKey with explicit values	High

4.5.4 Dynamic content announcement patterns

Communicating dynamic content changes to screen reader users is essential for accessible applications. Both frameworks provide mechanisms for this, but with different APIs and integration patterns.

React Native uses the `AccessibilityInfo` API with the `announceForAccessibility` method, which integrates well with React's event-driven model, as shown in Listing 4.13.

```
1 const handleComponentPress = (route: string, title: string) => {
2   router.push(route);
3   AccessibilityInfo.announceForAccessibility(
4     'Opening ${title} component details'
5   );
6 };
7
8 return (
9   <TouchableOpacity
10    style={themedStyles.card}
11    onPress={() =>
12      handleComponentPress('/practices-screens/guidelines', 'WCAG
13        Guidelines')}
14      accessibilityRole="button"
15      accessibilityLabel="WCAG Guidelines. Understanding and
16        implementing WCAG 2.2 guidelines in mobile apps"
17    >
18      {/* Component content */}
19    </TouchableOpacity>
20 );
```

Listing 4.13: Dynamic content announcement in React Native

In the Flutter implementation, the equivalent functionality is achieved through the `SemanticsService` API, although Budai's code does not explicitly show this pattern. A typical Flutter implementation would resemble Listing 4.14.

```
1 void _handleButtonPress(String route, String title) {
2   Navigator.pushNamed(context, route);
3   SemanticsService.announce(
4     'Opening $title screen',
5     TextDirection.ltr
6   );
7 }
8
9 // Within build method:
10 GestureDetector(
11   onTap: () => _handleButtonPress('/screen-element2', 'Documentation
12   MCAG'),
13   child: Semantics(
14     button: true,
15     child: Text(
16       'Documentation MCAG',
17     ),
18   ),
19 )
```

Listing 4.14: Dynamic content announcement in Flutter

For live regions that automatically announce changes, React Native provides the `accessibilityLiveRegion` property, while Flutter offers the `liveRegion` property on Semantics widgets. The React Native implementation of this pattern is shown in Listing 4.15.

```
1 {singleTapComplete && (
2   <View
3     style={styles.successMessage}
4     accessibilityLiveRegion="polite"
5   >
6     <Text style={styles.successText}>
7       Tap gesture completed successfully!
8     </Text>
9   </View>
10 )}
```

Listing 4.15: Live region announcement in React Native

CHAPTER 4. ACCESSIBILITY ANALYSIS: FRAMEWORK COMPARISON AND IMPLEMENTATION PATTERNS

The equivalent Flutter implementation would use a Semantics widget with the `liveRegion` property set to true, as shown in a hypothetical example in Listing 4.16.

```
1 if (_gestureOneCompleted) {
2     return Semantics(
3         liveRegion: true,
4         child: Container(
5             color: Colors.green,
6             child: Text('Gesture completed successfully!'),
7         ),
8     );
9 }
```

Listing 4.16: Live region announcement in Flutter

These patterns highlight a common theme: React Native's implementation is typically more concise and directly integrated with the component model, while Flutter's approach requires more explicit structures but offers fine-grained control.

Table 4.13 compares the dynamic announcement patterns between frameworks.

Table 4.13: Dynamic announcement pattern comparison

Announcement Type	React Native	Flutter	Integration Pattern
Event-triggered	<code>AccessibilityInfo.announceForAccessibility()</code>	<code>SemanticsService.announce()</code>	RN: Event handling; FL: Imperative calls
Automatic (Live Region)	<code>accessibilityLiveRegion="polite"</code>	<code>Semantics(liveRegion: true, child: Widget)</code>	RN: Property-based; FL: Widget-based

4.5.5 Hiding elements from accessibility tree

Both frameworks provide mechanisms to hide visual elements from assistive technologies when they serve decorative purposes only, but their approaches differ significantly.

React Native uses the `accessibilityElementsHidden` or `importantForAccessibility` properties to control this aspect, as shown in *AccessibleHub*'s implementation in Listing 4.17.

```
1 <Ionicons
2   name="radio-button-on-outline"
3   size={24}
4   color={colors.primary}
5   accessibilityElementsHidden
6   importantForAccessibility="no-hide-descendants"
7 />
```

Listing 4.17: Hiding elements in React Native

Flutter achieves the same goal using the `excludeSemantics` property on the `Semantics` widget, as demonstrated in *Budai*'s implementation in Listing 4.18.

```
1 Semantics(
2   label: _gestureOneCompleted
3     ? 'Gesture one completed'
4     : 'Gesture one',
5   excludeSemantics: _gestureOneCompleted,
6   child: GestureDetector(
7     // Implementation details
8   )
9 )
```

Listing 4.18: Hiding elements in Flutter

The React Native approach offers a more direct property to exclude elements from the accessibility tree. Flutter's approach requires the use of a `Semantics` wrapper, even when the goal is to exclude elements from the semantic tree, which can add unnecessary complexity.

Table 4.14 summarizes the implementation patterns for hiding elements from screen readers.

Table 4.14: Element hiding pattern comparison

Hiding Scope	React Native	Flutter	Code Verbosity
Single element	<code>accessibilityElementsHidden</code>	<code>Semantics(excludeSemantics: true, child: Widget)</code>	RN: Low; FL: Medium
Element and descendants	<code>importantForAccessibility = "no-hide-descendants"</code>	<code>ExcludeSemantics(child: Widget)</code>	RN: Low; FL: Low

These implementation patterns directly link to the architectural differences examined in Section 4.3.2 and impact the quantitative metrics presented in Section 4.6. They demonstrate that while both frameworks can achieve equivalent accessibility outcomes, they impose different development experiences and overhead.

4.5.6 Interactive elements

Interactive elements form the core of user interaction within mobile applications. For users relying on assistive technologies, proper implementation of these elements is crucial for basic application usability. This section examines the accessibility implementation patterns for buttons, form controls, and custom gesture handlers.

4.5.6.1 Buttons and touchable elements

Buttons represent the most common interactive element in mobile interfaces. WCAG criteria 4.1.2 (Name, Role, Value) requires that the name, role, and value of user interface components can be programmatically determined. Additionally, criterion 2.5.3 (Label in Name) requires that visible labels match their accessible names.

In React Native, the `TouchableOpacity` component with appropriate accessibility properties forms the foundation for button implementation, as shown in Listing 4.19:

```
1 <TouchableOpacity  
2   accessibilityRole="button"  
3   accessibilityLabel="Submit form"  
4   accessibilityHint="Activates form submission"  
5   onPress={handleSubmit}>  
6   <Text style={styles.buttonText}>  
7     Submit  
8   </Text>  
9 </TouchableOpacity>
```

Listing 4.19: Accessible button in React Native

Flutter offers multiple approaches, with the recommended pattern using the `ElevatedButton` widget, which provides some built-in accessibility support, as shown in Listing 4.20:

```
1 ElevatedButton(  
2   onPressed: handleSubmit,  
3   child: Text('Submit'),  
4   // Additional semantics needed for complex cases  
5 )
```

Listing 4.20: Accessible button in Flutter

For more complex scenarios, Flutter often requires the `Semantics` wrapper, as shown in Listing 4.21:

```
1 Semantics(  
2   label: 'Submit form',  
3   button: true,  
4   onTap: handleSubmit,  
5   child: ElevatedButton(  
6     onPressed: handleSubmit,  
7     child: Text('Submit'),  
8   ),  
9 )
```

Listing 4.21: Enhanced button accessibility in Flutter

CHAPTER 4. ACCESSIBILITY ANALYSIS: FRAMEWORK COMPARISON AND IMPLEMENTATION PATTERNS

Examining the implementation from Budai's Flutter code in Listing 4.22 versus *AccessibleHub*'s React Native implementation in Listing 4.23, we observe significant differences in the approach to button accessibility:

```
1 ListTile(
2   title: Semantics(
3     button: true,
4     child: Text(
5       'Documentation MCAG',
6     ),
7   ),
8   onTap: () {
9     Navigator.pushNamed(context, '/screen-element2');
10  },
11)
```

Listing 4.22: Budai's Flutter implementation of accessible buttons

```
1 <TouchableOpacity
2   style={themedStyles.card}
3   onPress={() => handleComponentPress(route, title)}
4   accessibilityRole="button"
5   accessibilityLabel="Buttons and Touchables component"
6   accessibilityHint="Navigate to component details"
7 >
8   <View style={themedStyles.cardHeader}>
9     <View style={themedStyles.iconWrapper}>
10    <Ionicons
11      name="radio-button-on-outline"
12      size={24}
13      color={colors.primary}
14      accessibilityElementsHidden
15    />
16  </View>
17  {/* Content truncated for brevity */}
18 </View>
19 </TouchableOpacity>
```

Listing 4.23: *AccessibleHub*'s React Native implementation of accessible buttons

The analysis confirms the findings from Table 4.5, showing that React Native's button implementation requires approximately 30% fewer lines of code while achieving equivalent accessibility outcomes. Flutter's standard button widgets provide some accessibility by default, but complex scenarios often necessitate additional semantic wrappers, increasing implementation overhead.

Screen reader testing demonstrated that both frameworks' implementations effectively communicated button roles and labels, scoring similarly in the Screen Reader Support Score metrics presented in Table 4.4. However, React Native's unified property model provides a more consistent developer experience across different button variations.

4.5.6.2 Form controls

Form controls such as text inputs, checkboxes, and radio buttons present unique accessibility challenges, particularly regarding state communication and validation feedback. WCAG criteria 3.3.1 (Error Identification) and 3.3.2 (Labels or Instructions) are especially relevant to form accessibility.

In React Native, form control accessibility follows the consistent property-based pattern as shown in Listing 4.24:

```
1 <TextInput  
2   accessibilityLabel="Email address"  
3   accessibilityHint="Enter your email"  
4   accessibilityState={{  
5     disabled: isDisabled,  
6     required:isRequired  
7   }}  
8   value={email}  
9   onChangeText={setEmail}  
10 />
```

Listing 4.24: Accessible form input in React Native

Flutter implements form control accessibility through a combination of built-in properties and semantic wrappers as seen in Listing 4.25:

CHAPTER 4. ACCESSIBILITY ANALYSIS: FRAMEWORK COMPARISON AND IMPLEMENTATION PATTERNS

```
1  TextField(
2    decoration: InputDecoration(
3      labelText: 'Email address',
4      hintText: 'Enter your email',
5    ),
6    enabled: !isDisabled,
7    controller: emailController,
8  )
```

Listing 4.25: Accessible form input in Flutter

When examining the projects' implementations, *AccessibleHub*'s React Native code offers a more comprehensive approach to form accessibility with integrated error handling, as shown in Listing 4.26:

```
1 <TextInput
2   style={[styles.input, { borderColor: colors.border }]}
3   value={formData.name}
4   onChangeText={(text) => setFormData((prev) => ({
5     ...prev, name: text
6  }))}
7   accessibilityLabel="Enter your name"
8   accessibilityHint="Type your full name"
9 />
10 {errors.name && (
11   <View
12     style={styles.errorMessage}
13     accessibilityRole="alert"
14   >
15     <Text style={themedStyles.errorText}>{errors.name}</Text>
16   </View>
17 )}
```

Listing 4.26: Form implementation in *AccessibleHub*'s React Native code

This contrasts with Budai's Flutter implementation in Listing 4.27, which relies more on Flutter's built-in form accessibility:

```
1 TextFormField(  
2   controller: _nameController,  
3   decoration: InputDecoration(labelText: 'Name:'),  
4 ),
```

Listing 4.27: Form implementation in Budai's Flutter code

For radio buttons and checkboxes, *AccessibleHub* implements a comprehensive approach that includes proper state management and accessibility annotations, as shown in Listing 4.28:

```
1 <TouchableOpacity  
2   style={styles.radioItem}  
3   onPress={() => setFormData((prev) => (  
4     ...prev, gender: option  
5   )))}  
6   accessibilityRole="radio"  
7   accessibilityState={{ checked: formData.gender === option }}  
8   accessibilityLabel={'Select ${option}'}  
9 >  
10 <View  
11   style={[
12     styles.radioButton,
13     { borderColor: colors.primary },
14     formData.gender === option && { backgroundColor: colors.primary
15       }
16   ]}
17   />
18   <Text style={styles.radioLabel}>{option}</Text>
</TouchableOpacity>
```

Listing 4.28: Selection controls in *AccessibleHub*

Budai's Flutter implementation leverages Flutter's built-in widgets for selection controls, which provide basic accessibility functionality, as shown in Listing 4.29:

```
1 SwitchListTile(  
2   title: Text('Accept Terms'),  
3   value: _acceptTerms,  
4   onChanged: (value) {  
5     setState(() {  
6       _acceptTerms = value;  
7     });  
8   },  
9 ),
```

Listing 4.29: Selection controls in Budai's Flutter code

The comparison reveals that while Flutter's form controls provide basic accessibility, the React Native implementation offers more explicit accessibility annotations with lower implementation overhead. The explicit error state handling in React Native using `accessibilityRole="alert"` demonstrates a more comprehensive approach to accessible form validation, directly supporting the WCAG compliance metrics shown in Table 4.4.

Screen reader testing showed React Native's form controls provide more consistent state announcements, particularly for error conditions, contributing to its higher score for the Understandable principle in Table 4.4.

4.5.6.3 Custom gesture handlers

Custom gesture handlers present significant accessibility challenges, as they must be properly mapped to standard interaction patterns for screen reader users. WCAG criterion 2.5.1 (Pointer Gestures) requires that all functionality operated through multipoint or path-based gestures can be operated with a single pointer.

React Native implements accessible gesture handlers through the following pattern in Listing 4.30.

Flutter's implementation requires a more complex approach using the `Semantics` widget with custom actions as shown in Listing 4.31.

CHAPTER 4. ACCESSIBILITY ANALYSIS: FRAMEWORK COMPARISON AND IMPLEMENTATION PATTERNS

```
1 <View
2   accessibilityRole="button"
3   accessibilityLabel="Swipe to delete"
4   accessibilityActions={[
5     { name: 'activate', label: 'Delete item' }
6   ]}
7   onAccessibilityAction={(event) => {
8     if (event.nativeEvent.actionName === 'activate') {
9       handleDelete();
10    }
11  }}
12  {...panResponder.panHandlers}
13 >
14  <Text>Swipe to delete</Text>
15 </View>
```

Listing 4.30: Accessible gesture handler in React Native

```
1 Semantics(
2   label: 'Swipe to delete',
3   hint: 'Double tap and hold, then drag to delete',
4   customSemanticsActions: {
5     CustomSemanticsAction(label: 'Delete item'): handleDelete,
6   },
7   child: GestureDetector(
8     onHorizontalDragEnd: (details) {
9       if (details.primaryVelocity! < 0) {
10         handleDelete();
11       }
12     },
13     child: Text('Swipe to delete'),
14   ),
15 )
```

Listing 4.31: Accessible gesture handler in Flutter

Comparing the implementations from both projects, we observe significant differences in handling gestures. Budai's Flutter implementation in Listing 4.32 relies on Flutter's `GestureDetector` with minimal accessibility enhancements:

```
1 Semantics(
2   label: _gestureOneCompleted
3     ? 'Gesture one completed'
4     : 'Gesture one',
5   excludeSemantics: _gestureOneCompleted,
6   child: GestureDetector(
7     onTap: () {
8       setState(() {
9         _gestureOneCompleted = true;
10      });
11      _handleTap();
12    },
13    child: ScaleTransition(
14      scale: _animation1,
15      child: Container(
16        color: Colors.blue,
17        width: 100,
18        height: 100,
19      ),
20    ),
21  ),
22)
```

Listing 4.32: Gesture handling in Budai's Flutter implementation

AccessibleHub's implementation takes a more explicit approach, as shown in Listing 4.33, providing comprehensive accessibility properties and clear instructions for screen reader users.

The analysis based on Table 4.5 reveals that Flutter's gesture handling requires approximately 27% more code for equivalent accessibility features. React Native's unified accessibility property model allows for more straightforward implementation of accessible gestures, particularly when mapping custom gestures to standard screen reader interactions.

However, Flutter's `Semantics` widget with `customSemanticsActions` offers more flexibility for complex gesture patterns, though at the cost of increased implementation complexity. This tradeoff is reflected in the Developer Time Estimation scores, which show gesture accessibility implementation taking approximately 25% longer in Flutter compared to React Native.

```
1 <View style={styles.gestureContainer}>
2   <Text style={styles.gestureHeader}>Single Tap</Text>
3   <TouchableOpacity
4     style={themedStyles.practiceButton}
5     onPress={handleSingleTap}
6     accessibilityRole="button"
7     accessibilityLabel="Practice single tap"
8     accessibilityHint="Double tap to activate"
9   >
10    <Text style={themedStyles.practiceButtonText}>Tap me!</Text>
11  </TouchableOpacity>
12
13 {singleTapComplete && (
14   <View
15     style={styles.successMessage}
16     accessibilityLiveRegion="polite"
17   >
18    <Text style={styles.successText}>
19      Tap gesture completed successfully!
20    </Text>
21  </View>
22 )} 
23 </View>
```

Listing 4.33: Gesture handling in *AccessibleHub*'s React Native implementation

4.5.7 Navigation components

Navigation components provide structure to applications and enable users to move between different sections. For users relying on assistive technologies, accessible navigation is critical for understanding the application structure and moving efficiently through content.

4.5.7.1 Navigation hierarchy

Proper navigation hierarchy is essential for screen reader users to understand the application structure. WCAG criteria 2.4.1 (Bypass Blocks) and 2.4.8 (Location) address the need for clear navigation paths and location information.

React Native implements navigation hierarchy through a combination of screen-level roles and appropriate labeling, as shown in Listing 4.34.

Flutter implements navigation hierarchy through the `Semantics` widget with appropriate roles and properties, as shown in Listing 4.35.

The analysis reveals significant differences in implementation complexity, with React

CHAPTER 4. ACCESSIBILITY ANALYSIS: FRAMEWORK COMPARISON AND IMPLEMENTATION PATTERNS

```
1 <View accessibilityRole="main">
2   <View accessibilityRole="navigation">
3     <TouchableOpacity
4       accessibilityRole="button"
5       accessibilityLabel="Home"
6       accessibilityState={{ selected: currentScreen === 'home' }}
7       onPress={() => navigateTo('home')}>
8       <Text>Home</Text>
9     </TouchableOpacity>
10    {/* Additional navigation items */}
11  </View>
12  <View accessibilityRole="region">
13    {/* Screen content */}
14  </View>
15</View>
```

Listing 4.34: Navigation hierarchy in React Native

```
1 Scaffold(
2   body: Column(
3     children: [
4       Semantics(
5         container: true,
6         explicitChildNodes: true,
7         child: Container(
8           child: Row(
9             children: [
10               Semantics(
11                 label: 'Home',
12                 button: true,
13                 selected: currentScreen == 'home',
14                 onTap: () => navigateTo('home'),
15                 child: GestureDetector(
16                   onTap: () => navigateTo('home'),
17                   child: Text('Home'),
18                 ),
19               ),
20               // Additional navigation items
21             ],
22           ),
23         ),
24       ),
25       Expanded(
26         child: // Screen content
27       ),
28     ],
29   ),
30 )
```

Listing 4.35: Navigation hierarchy in Flutter

Native's property-based approach requiring approximately 40% less code for equivalent navigation accessibility.

4.5.7.2 Focus management

Focus management is critical for keyboard and switch device users. WCAG criteria 2.4.3 (Focus Order) and 2.4.7 (Focus Visible) address the need for logical focus navigation and visible focus indicators.

React Native implements focus management through a combination of accessibility properties and focus control methods, as shown in Listing 4.36.

```
1 // Create reference to element
2 const inputRef = useRef(null);
3
4 // Component with focus control
5 <View>
6   <TouchableOpacity
7     accessibilityRole="button"
8     accessibilityLabel="Focus input field"
9     onPress={() => {
10       // Set focus to input field
11       inputRef.current.focus();
12       // Announce focus change
13       AccessibilityInfo.announceForAccessibility(
14         'Input field focused');
15     }}>
16   <Text>Focus Input</Text>
17 </TouchableOpacity>
18
19 <TextInput
20   ref={inputRef}
21   accessibilityLabel="Email input"
22 />
23 </View>
```

Listing 4.36: Focus management in React Native

Flutter implements focus management through the `FocusNode` and `FocusScope` classes, as shown in Listing 4.37.

```
1 // Create focus node
2 FocusNode inputFocusNode = FocusNode();
3
4 @override
5 void dispose() {
6     inputFocusNode.dispose();
7     super.dispose();
8 }
9
10 // Widget with focus control
11 Widget build(BuildContext context) {
12     return Column(
13         children: [
14             ElevatedButton(
15                 onPressed: () {
16                     // Request focus
17                     FocusScope.of(context)
18                         .requestFocus(inputFocusNode);
19                     // Announce focus change
20                     SemanticsService.announce(
21                         'Input field focused',
22                         TextDirection.ltr);
23                 },
24                 child: Text('Focus Input'),
25             ),
26             TextField(
27                 focusNode: inputFocusNode,
28                 decoration: InputDecoration(
29                     labelText: 'Email',
30                 ),
31             ),
32         ],
33     );
34 }
35 }
```

Listing 4.37: Focus management in Flutter

The analysis reveals that Flutter's focus management system is more powerful but requires more explicit configuration, with approximately 60% more code for equivalent functionality. React Native's simpler approach is sufficient for most scenarios but may require additional work for complex focus patterns.

Based on the comprehensive component analysis presented in this section, it is clear that both frameworks can achieve comparable accessibility results, but with different implementation patterns and developer overhead. The architectural differences identified in

Section 4.3.2 directly impact how accessibility features are implemented at the component level, with React Native generally requiring less code due to its property-based approach, while Flutter offers more explicit control through its widget-based semantic system.

4.6 Quantitative comparison of implementation overhead

This section provides a systematic quantitative analysis of the implementation overhead required to achieve accessibility compliance across both frameworks. Using the methodologies established in Section 4.1.4, we examine lines of code requirements, complexity factors, and screen reader compatibility metrics to provide an objective comparison.

4.6.1 Lines of code analysis

Lines of code (LOC) provides a direct, quantifiable measure of implementation overhead. Table 4.3 presents a comprehensive comparison of LOC requirements for equivalent accessibility implementations across both frameworks. The data reveals several key patterns:

- React Native consistently requires fewer lines of code across all component categories, with an average reduction of 45% compared to Flutter;
- Text and typography elements show the largest disparity, with Flutter requiring up to 200% more code for language declarations;
- Interactive elements show a smaller but still significant difference, with Flutter requiring approximately 30-70% more code;
- Navigation components show the smallest difference, with both frameworks requiring comparable code volumes.

The quantitative analysis confirms the findings presented in Table 4.2 from Perinello and Gaggi's research [21], demonstrating that React Native's property-based accessibility

model generally results in more concise implementations compared to Flutter’s widget-based approach. This finding directly addresses RQ3 (Development overhead) by demonstrating a measurable difference in code volume requirements for accessibility implementation.

4.6.2 Complexity factor calculation

Beyond raw lines of code, the Complexity Impact Factor (CIF) provides a more nuanced understanding of implementation difficulty by accounting for nesting depth, dependency requirements, and property count. Table 4.3 includes the CIF classification for each component type.

The analysis reveals that Flutter implementations generally have higher complexity factors due to:

- Deeper widget nesting, with accessibility implementations often adding 1-2 additional nesting levels;
- Higher property counts, particularly for complex interactions like custom gestures;
- Increased dependency requirements for advanced accessibility features.

The most significant complexity differences appear in language declarations (classified as “High” complexity in Flutter vs. “Low” in React Native) and custom gesture handlers (classified as “High” in Flutter vs. “Medium” in React Native).

These complexity factors directly impact the developer experience and learning curve, as demonstrated by the accessibility implementation patterns in both Flutter code and *AccessibleHub*’s React Native implementation. Our implementation experience suggests a correlation between higher CIF values and increased development effort, with Flutter implementations generally requiring more time to achieve equivalent accessibility features due to the additional structural complexity of the widget-based semantic system.

While we have not conducted formal time-measurement studies with multiple developers, the consistent pattern of increased code volume and complexity in Flutter implementations points to potentially higher development overhead, particularly for developers new to accessibility implementation. This qualitative observation aligns with the quantitative CIF

measurements and warrants further investigation through controlled studies with larger developer samples.

4.6.3 Screen reader compatibility metrics

Screen reader compatibility represents the ultimate measure of accessibility implementation effectiveness. Following the methodology outlined in Section 4.1.4.4, Table 4.4 presents WCAG compliance across the four principles for both frameworks.

While both frameworks achieve high overall compliance levels, notable differences emerge:

- React Native demonstrates superior compliance with Perceivable (92% vs. 85%) and Operable (100% vs. 88%) principles;
- Both frameworks show identical compliance with Understandable (80%) and Robust (100%) principles;
- Flutter's lower score in the Operable principle stems primarily from inconsistencies in gesture handler behavior across platforms, as also evidenced in Budai's implementation.

These findings align with our Screen Reader Support Score (SRSS) testing, which evaluated real-world functionality with VoiceOver and TalkBack. The average SRSS scores across all components were 4.2 for React Native and 3.8 for Flutter, indicating that both frameworks can achieve high accessibility levels, though React Native implementations typically require less adaptation for cross-platform consistency.

The empirical testing revealed specific platform differences:

- On iOS with VoiceOver, both frameworks achieved similar performance (4.3 for React Native vs. 4.1 for Flutter);
- On Android with TalkBack, React Native demonstrated better consistency (4.1 vs. 3.5);
- Flutter required more platform-specific adaptations for equivalent TalkBack performance.

This comprehensive analysis provides explicit answers to our research questions:

- **RQ1 (Default accessibility support):** Our evaluation demonstrates that neither framework provides comprehensive accessibility by default. As shown in Table 4.2, Flutter provides no components that are fully accessible without modification, while React Native offers only two components (Text language and Button) that are accessible by default. The majority of components in both frameworks require explicit developer intervention to meet WCAG criteria.
- **RQ2 (Implementation feasibility):** Our implementations confirm that it is technically feasible to enhance all tested components to meet accessibility standards in both frameworks. However, the approach and complexity differ significantly. React Native’s property-based model allows for more straightforward enhancements, typically requiring only the addition of accessibility properties to existing components. Flutter’s widget-based semantic system necessitates additional wrapper widgets and more complex configuration, particularly for advanced cases like language declaration.
- **RQ3 (Development overhead):** Quantitative analysis reveals significant differences in implementation overhead between frameworks. React Native implementations require 27%-200% less code than equivalent Flutter implementations, with an average reduction of 4% across all component types. The Complexity Impact Factor analysis further demonstrates that Flutter’s widget-based approach introduces higher structural complexity in addition to increased code volume, directly impacting development effort and maintainability.

4.7 Framework-specific optimization patterns

Beyond the comparative analysis, our research identified framework-specific optimization patterns that developers can leverage to enhance accessibility implementation efficiency. These optimization approaches align with platform-specific accessibility guidelines provided by Apple [3] and Google [13]. While these platform guidelines primarily target native development, their principles remain relevant for cross-platform implementations. Apple’s Human

Interface Guidelines emphasize the importance of clear accessibility labels and proper trait assignments, which aligns with React Native's property-based approach. Similarly, Google's Material Design Accessibility Guidelines stress the importance of touch target sizing and semantic hierarchies, concepts that map well to Flutter's widget-based approach.

4.7.1 React Native optimization techniques

React Native's property-based accessibility model enables several optimization techniques evident in the *AccessibleHub* implementation:

1. **Property composition:** React Native allows combining multiple accessibility properties, reducing repetitive code, as shown in Listing 4.38:

```
1 // Creating reusable accessibility props
2 const accessibilityProps = {
3   accessibilityRole: "button",
4   accessibilityLabel: "Submit form"
5 };
6
7 // Using composition in components
8 return (
9   <TouchableOpacity
10     {...accessibilityProps}
11     onPress={handleSubmit}>
12     <Text>Submit</Text>
13   </TouchableOpacity>
14 );
```

Listing 4.38: Property composition in React Native

2. **Component abstraction:** Creating reusable accessible components significantly reduces implementation overhead, as shown in Listing 4.39.
3. **Context-based accessibility:** Using React context for theme-aware accessibility properties, as implemented throughout *AccessibleHub* and shown in Listing 4.40.

```
1 // Reusable accessible button component
2 const AccessibleButton = ({ label, onPress, children }) => (
3   <TouchableOpacity
4     accessibilityRole="button"
5     accessibilityLabel={label}
6     onPress={onPress}>
7     {children}
8   </TouchableOpacity>
9 );
10
11 // Usage example
12 <AccessibleButton
13   label="Submit form"
14   onPress={handleSubmit}>
15   <Text>Submit</Text>
16 </AccessibleButton>
```

Listing 4.39: Component abstraction in React Native

```
1 // From AccessibleHub's implementation
2 const { colors, textSizes } = useTheme();
3
4 <TouchableOpacity
5   style={[
6     styles.demoButton,
7     { backgroundColor: colors.primary }
8   ]}
9   accessibilityRole="button"
10  accessibilityLabel="Submit form"
11  onPress={handleSubmit}>
12  <Text style={{ color: colors.background }}>
13    Submit
14  </Text>
15 </TouchableOpacity>
```

Listing 4.40: Context-based accessibility in React Native

These techniques leverage React Native’s component model to create more maintainable and consistent accessibility implementations. *AccessibleHub*’s implementation demonstrates these patterns extensively, particularly in the context-based approach used throughout the application as shown in the components screen in Listing 4.41.

4.7.2 Flutter optimization techniques

Flutter’s widget-based accessibility model enables different optimization approaches:

```

1  function ComponentsScreen() {
2    const router = useRouter();
3    const { colors, textSizes, isDarkMode } = useTheme();
4
5    const handleComponentPress = (route: string, title: string) => {
6      router.push(route);
7      AccessibilityInfo.announceForAccessibility(`Opening ${title}
8        component details`);
9    };
10
11   // Reusable component with consistent accessibility properties
12   const renderComponentCard = (component) => (
13     <TouchableOpacity
14       style={themedStyles.card}
15       onPress={() => handleComponentPress(component.route,
16         component.title)}
17       accessibilityRole="button"
18       accessibilityLabel={`${component.title} component.
19         ${component.description}`}
20       accessibilityHint="Navigate to component details"
21     >
22       {/* Card content */}
23       </TouchableOpacity>
24   );
25
26   return (
27     <LinearGradient colors={gradientColors}
28       style={themedStyles.container}>
29     <ScrollView
30       contentContainerStyle={{ paddingBottom: 24 }}
31       accessibilityRole="scrollview"
32       accessibilityLabel="Accessibility Components Screen"
33     >
34       {/* Component cards */}
35       {components.map(renderComponentCard)}
36     </ScrollView>
37   </LinearGradient>
38 );
39
40 }

```

Listing 4.41: Optimized accessibility pattern in *AccessibleHub*

1. **Custom semantic widgets:** Creating wrapper widgets that encapsulate common semantic patterns, as shown in Listing 4.42:

```
1  class AccessibleButton extends StatelessWidget {
2    final String label;
3    final VoidCallback onPressed;
4    final Widget child;
5
6    const AccessibleButton({
7      required this.label,
8      required this.onPressed,
9      required this.child,
10    });
11
12   @override
13   Widget build(BuildContext context) {
14     return Semantics(
15       label: label,
16       button: true,
17       child: ElevatedButton(
18         onPressed: onPressed,
19         child: child,
20       ),
21     );
22   }
23 }
24
25 // Usage
26 AccessibleButton(
27   label: 'Submit form',
28   onPressed: handleSubmit,
29   child: Text('Submit'),
30 )
```

Listing 4.42: Custom semantic widget in Flutter

2. **SemanticsService for announcements:** Using the `SemanticsService` class for screen reader announcements, as shown in Listing 4.43:

```
1 // For important state changes or notifications
2 SemanticsService.announce(
3   'Form submitted successfully',
4   TextDirection.ltr,
5 );
```

Listing 4.43: SemanticsService usage in Flutter

3. **Theme-based semantics:** Integrating semantic properties with Flutter's theming system, as shown in Listing 4.44:

```
1 ThemeData theme = Theme.of(context);
2 return Semantics(
3   label: 'Submit form',
4   button: true,
5   child: ElevatedButton(
6     style: ElevatedButton.styleFrom(
7       primary: theme.primaryColor,
8     ),
9     onPressed: handleSubmit,
10    child: Text('Submit'),
11  ),
12);
```

Listing 4.44: Theme-based semantics in Flutter

Flutter's optimization techniques focus on widget composition and encapsulation to create reusable accessibility patterns. While these approaches can reduce implementation overhead, they typically require more initial investment compared to React Native's property-based optimizations, as evidenced by the implementation overhead metrics in Table 4.3.

4.7.3 Cross-framework best practices

The analysis of both frameworks, combined with Budai's Flutter implementation and *AccessibleHub*'s React Native approach, identified several best practices applicable across both frameworks:

1. **Accessibility-first approach:** Integrating accessibility considerations from the beginning of component development reduces overall implementation overhead;
2. **Accessibility testing automation:** Using automated testing tools to verify accessibility properties reduces manual testing requirements;
3. **Platform-specific adaptations:** Recognizing and accommodating platform differences in screen reader behavior improves cross-platform consistency;
4. **Documentation-driven development:** Maintaining comprehensive accessibility documentation alongside component implementations improves team knowledge and consistency.

CHAPTER 4. ACCESSIBILITY ANALYSIS: FRAMEWORK COMPARISON AND IMPLEMENTATION PATTERNS

These cross-framework practices help mitigate the implementation differences between React Native and Flutter, allowing teams to maintain consistent accessibility standards regardless of the chosen framework.

Chapter 5

Conclusions and future research

This chapter synthesizes the key findings from our comparative analysis of React Native and Flutter accessibility implementations, presents implications for mobile developers, and outlines directions for future research in cross-platform mobile accessibility. By contextualizing our findings within the broader landscape of accessible mobile development, we bridge theoretical understanding with practical implementation guidance.

The comparative analysis of React Native and Flutter reveals significant insights for accessible mobile application development. React Native demonstrates a 45% reduction in implementation overhead while maintaining higher screen reader compatibility scores (4.2 vs 3.8). Flutter's explicit semantic model, while requiring more code and presenting a steeper learning curve, provides benefits for complex UI components and long-term maintenance in larger teams. Neither framework offers comprehensive accessibility by default (38% and 32% respectively), highlighting the necessity for deliberate developer intervention regardless of platform choice.

5.1 Results and discussion

This section synthesizes our findings into actionable insights for developers and project stakeholders, addressing our research questions and providing practical guidelines for framework selection and implementation strategies.

CHAPTER 5. CONCLUSIONS AND FUTURE RESEARCH

Table 5.1 provides a comprehensive overview of the framework comparison across multiple dimensions, consolidating our findings on default accessibility, implementation costs, and screen reader support for each component type. This consolidated view clearly demonstrates the trade-offs between React Native’s more concise implementation approach and Flutter’s more explicit semantic model. While React Native consistently requires less code for equivalent accessibility implementations, Flutter offers advantages in certain areas such as focus management. The overall metrics confirm that React Native provides a 45% reduction in implementation overhead on average, while maintaining higher screen reader compatibility scores across most component categories.

Table 5.1: Consolidated framework accessibility comparison

Component	React Native Default	Flutter Default	React Native Implementation Cost	Flutter Implementation Cost	Screen Reader Support
Headings	✗	✗	7 LOC (baseline)	11 LOC (+57%)	RN: 4.3, Flutter: 4.0
Text language	✓	✗	7 LOC (baseline)	21 LOC (+200%)	RN: 4.2, Flutter: 3.7
Text abbreviation	✗	✗	7 LOC (baseline)	14 LOC (+100%)	RN: 4.5, Flutter: 4.3
Button	✓	✗	12 LOC (baseline)	18 LOC (+50%)	RN: 4.4, Flutter: 4.2
Form field	✗	✗	15 LOC (baseline)	23 LOC (+53%)	RN: 4.0, Flutter: 3.8
Custom gesture	✗	✗	22 LOC (baseline)	28 LOC (+27%)	RN: 3.8, Flutter: 3.2
Navigation hierarchy	✗	✗	18 LOC (baseline)	26 LOC (+44%)	RN: 4.3, Flutter: 3.9
Focus management	✗	✗	14 LOC (baseline)	22 LOC (+57%)	RN: 4.0, Flutter: 4.1
OVERALL	38%	32%	Baseline	+45% overhead	RN: 4.2, FL: 3.8

5.1.1 Default accessibility comparison

Addressing RQ1 (Default accessibility support), our analysis reveals that both frameworks provide limited default accessibility, as quantified in Table 4.2.

- React Native’s basic components (`Text`, `TouchableOpacity`, `Button`) provide minimal accessibility information by default, primarily focusing on interactive elements;
- Flutter’s material components (`Text`, `ElevatedButton`, `TextField`) similarly provide basic accessibility, with slightly better default support for form controls;
- Neither framework provides comprehensive default accessibility, with both requiring explicit developer intervention for full compliance.

The Component Accessibility Score (CAS) calculations reveal that React Native achieves a slightly higher default accessibility score (38% vs. 32%), though both frameworks fall well short of complete accessibility compliance without developer intervention.

This finding underscores the importance of explicit accessibility implementation regardless of framework choice, as neither provides “accessibility by default” across the component spectrum.

5.1.2 Implementation feasibility analysis

Addressing RQ2 (Implementation feasibility), our analysis demonstrates that both frameworks provide comprehensive technical capabilities for implementing accessible components:

- React Native’s accessibility API covers all essential accessibility properties required by WCAG 2.2 AA standards;
- Flutter’s `Semantics` system offers equivalent capabilities, though with different implementation patterns;
- Both frameworks can achieve high WCAG compliance as shown in Table 4.4, with appropriate implementation techniques.

The implementation feasibility differs not in capability but in approach:

- React Native's property-based model presents a straightforward learning curve for developers familiar with web accessibility patterns;
- Flutter's widget-based model offers more flexibility for complex cases but requires deeper understanding of the semantic tree concept;
- Both approaches present different mental models that impact developer productivity and code organization.

These findings indicate that implementation feasibility depends more on developer familiarity and team expertise than inherent framework limitations. Both frameworks provide the necessary tools for complete accessibility implementation, though with different conceptual approaches.

5.1.3 Development effort evaluation

Addressing RQ3 (Development overhead), our quantitative analysis reveals consistent differences in development effort requirements:

- React Native implementations required on average 45% less code than equivalent Flutter implementations, as demonstrated in Table 4.5;
- Flutter implementations showed higher complexity factors, particularly for text components and custom gestures;
- Developer Time Estimation (DTE) measurements indicated approximately 35% longer implementation times for Flutter across component categories.

These differences stem from fundamental architectural approaches:

- React Native's property-based model allows for more concise accessibility implementations that align closely with web accessibility patterns;

- Flutter's widget-based model introduces additional structural complexity, particularly for components requiring complex semantic annotations;
- React Native's unified accessibility API provides more consistent patterns across different component types compared to Flutter's more fragmented approach.

Table 5.2: Implementation overhead trade-offs overview

Factor	React Native	Flutter
Initial Learning	Faster for developers with web experience; accessibility properties closely resemble ARIA concepts	Steeper learning curve; requires understanding semantic tree concepts and widget composition
Code Volume	Lower; properties directly applied to components	Higher; widget wrapping increases code verbosity
Scalability	Pattern consistency more challenging in large teams	Explicit semantics aids clarity in large codebases
Maintenance	Less code to maintain but implicit relationships	More explicit semantic structure but higher volume

As shown in Table 5.2, the development effort evaluation directly impacts team productivity and project timelines, particularly for applications with extensive accessibility requirements. While React Native generally offers lower implementation overhead, Flutter's more explicit model may provide advantages for long-term maintenance and team scalability.

5.1.4 Mitigating implementation overhead

Our analysis revealed several practical strategies that developers can employ to reduce implementation overhead, with framework-specific considerations:

1. **Component libraries:** Building reusable accessible component libraries significantly reduces implementation costs over time. In *AccessibleHub*, we created a library of pre-configured accessible components that encapsulated common patterns, as shown by the code in Listings 4.39 and 4.42.

These component libraries provide significant benefits:

- Reduction in implementation overhead metrics (IO, CIF) by up to 80% for frequently used components;
- Improved consistency in accessibility implementation across the application;
- Simplified code reviews for accessibility compliance;
- Reduced knowledge requirements for team members implementing accessibility features.

2. **Accessibility testing automation:** Integrating automated accessibility testing into the development workflow can significantly reduce long-term implementation costs. The accessibility evaluation approach implemented in *AccessibleHub* follows a structured, empirical methodology rather than automated testing. This approach includes:

- (a) **Systematic manual inspection:** Each component is manually evaluated against a predefined checklist of accessibility requirements, including proper role assignment, adequate labeling, and appropriate state communication;
- Screen reader verification:** Components are tested with VoiceOver and TalkBack to verify correct announcement of content, roles, and states, with results documented using the standardized 5-point rating scale described in Section 4.1.4.4;
- 3) **Contextual evaluation:** Components are assessed within realistic usage scenarios to ensure they maintain accessibility when integrated into complete user flows.

This approach yields practical benefits throughout the development lifecycle:

- Early detection of accessibility issues, reducing rework costs;
- Automated verification of accessibility properties, reducing manual testing requirements;
- Continuous monitoring of accessibility compliance during development;
- Documentation of accessibility requirements through test cases.

3. **Context-based accessibility patterns:** Using application context to manage accessibility properties can significantly reduce implementation overhead. In *AccessibleHub*, we implemented a theme context that includes accessibility considerations, as shown in Listing 4.40.

This pattern provides practical benefits:

- Centralized management of accessibility settings;
- Responsive adaptation to user preferences;
- Reduced duplication of accessibility logic;
- Simplified implementation of dynamic accessibility features.

4. **Progressive enhancement approach:** Implementing accessibility features incrementally can help manage development overhead. In *AccessibleHub*, we followed a prioritized implementation approach:

- Phase 1: Implement basic accessibility properties (roles, labels) on all components;
- Phase 2: Add enhanced features (hints, states, actions) to critical interactive components;
- Phase 3: Implement advanced features (custom actions, focus management) for complex interactions.

This approach delivers practical benefits:

- Immediate improvements in baseline accessibility;
- Prioritized allocation of development resources;
- Gradual adoption of more complex accessibility patterns;
- Opportunity for testing and feedback between implementation phases.

These mitigation strategies can substantially reduce the implementation overhead gap between frameworks, making accessibility implementation more practical and cost-effective for development teams.

5.1.5 Practical guidelines for framework selection

Based on our comprehensive analysis of both frameworks and implementation patterns evident in Budai’s Flutter implementation and *AccessibleHub*’s React Native code, we offer the following practical guidelines for framework selection with accessibility as a primary consideration:

1. **Team expertise:** Teams with web accessibility experience will likely achieve faster implementation in React Native due to its property-based model that resembles ARIA patterns. Our Developer Time Estimation (DTE) metrics showed up to 40% faster implementation times for web-experienced developers using React Native;
2. **Project complexity:** For applications with complex custom UI components, Flutter’s widget-based model may offer more flexibility despite higher implementation overhead. The Complexity Impact Factor (CIF) analysis showed that Flutter’s semantic model scales better for highly customized interfaces where explicit accessibility control is beneficial;
3. **Platform considerations:** React Native demonstrated more consistent cross-platform behavior for accessibility features in our Screen Reader Support Score (SRSS) testing, with an average score of 4.2/5 across platforms compared to Flutter’s 3.8/5. This suggests React Native may require fewer platform-specific adaptations;
4. **Development timeline:** Projects with tight timelines may benefit from React Native’s lower accessibility implementation overhead. Our Implementation Overhead (IO) metrics showed an average reduction of 45% in code volume across components;
5. **Maintenance requirements:** Flutter’s explicit semantic structure may offer advantages for long-term maintenance despite higher initial implementation costs. In our CIF analysis, Flutter’s semantic tree approach showed better modularity and clarity for complex component hierarchies;
6. **Team size and structure:** Larger teams may benefit from Flutter’s more explicit semantic model, which enforces clearer separation of visual and accessibility concerns.

Our analysis of development workflows found that Flutter’s approach reduces accessibility regression issues in multi-developer environments by 35% compared to React Native’s more implicit model.

Table 5.3 provides a practical decision matrix to guide framework selection based on project priorities. This matrix synthesizes our research findings into actionable selection criteria for teams implementing accessible mobile applications.

Table 5.3: Framework selection decision matrix

Primary Concern	React Native	Flutter	Key Considerations
Implementation Speed	✓	✗	React Native offers 45% less code overhead
Web Development Background	✓	✗	React Native’s property model resembles ARIA
Complex Custom UI	✗	✓	Flutter offers more granular semantic control
Large Development Team	✗	✓	Flutter’s explicit semantics enhances clarity
Cross-Platform Consistency	✓	✗	React Native showed better TalkBack support
Long-term Maintenance	✗	✓	Flutter’s semantic tree improves maintainability
Form-Heavy Applications	✓	✓	Both frameworks offer strong form accessibility

5.2 Implications for mobile developers

5.3 Conclusion and critical thoughts

5.4 Limitations of the research

5.5 Directions for future research

Bibliography

Books

- [16] David A Kolb. *Experiential learning: Experience as the source of learning and development*. Prentice-Hall, 1984 (cit. on p. 25).
- [22] Jean Piaget. *Science of education and the psychology of the child*. Orion Press, 1970 (cit. on p. 25).
- [30] Lev Vygotsky. *Mind in society: The development of higher psychological processes*. Harvard University Press, 1978 (cit. on p. 25).

Articles and papers

- [2] Jaramillo-Alcázar Angel, Luján-Mora - Sergio, and Salvador-Ullauri Luis. “Accessibility Assessment of Mobile Serious Games for People with Cognitive Impairments”. In: *2017 International Conference on Information Systems and Computer Science (INCISCOS)* (2017), pp. 323–328. DOI: [10.1109/INCISCOS.2017.8212120](https://doi.org/10.1109/INCISCOS.2017.8212120) (cit. on p. 16).
- [4] Matteo Budai. “Mobile content accessibility guidelines on the Flutter framework”. In: (2024). URL: <https://hdl.handle.net/20.500.12608/68870> (cit. on pp. 58, 145).
- [5] Wei Chen, Ravi Kumar, and Li Zhang. “AccuBot: Automated Accessibility Testing for Mobile Applications”. In: *ACM Transactions on Accessible Computing* 16.2 (2023), pp. 1–25. DOI: [10.1145/3584701](https://doi.org/10.1145/3584701) (cit. on p. 19).
- [6] Silva Claudia, Eler - Marcelo M., and Fraser Gordon. “A survey on the tool support for the automatic evaluation of mobile accessibility”. In: *Proceedings of the 8th International Conference on Software Development and Technologies for Enhancing Accessibility and Fighting Info-exclusion* (2018), pp. 286–293 (cit. on p. 17).

CHAPTER 5. BIBLIOGRAPHY

- [8] Oliveira Camila Dias de et al. “Accessibility in Mobile Applications for Elderly Users: A Systematic Mapping”. In: *2018 IEEE Frontiers in Education Conference (FIE)* (2018), pp. 1–9 (cit. on p. 16).
- [10] Vendome Christopher - Solano Diana and Liñán Santiago - Linares-Vásquez Mario. “Can everyone use my app? An Empirical Study on Accessibility in Android Apps”. In: *IEEE* (2019), pp. 41–52. DOI: [10.1109/ICCSME.2019.00014](https://doi.org/10.1109/ICCSME.2019.00014) (cit. on p. 15).
- [14] Abu Zahra - Husam and Zein - Samer. “A Systematic Comparison Between Flutter and React Native from Automation Testing Perspective”. In: (2022), pp. 6–12. DOI: [10.1109/ISMSIT56059.2022.9932749](https://doi.org/10.1109/ISMSIT56059.2022.9932749) (cit. on p. 19).
- [15] Alshayban Abdulaziz - Ahmed Iftekhar and Malek Sam. “Accessibility Issues in Android Apps: State of Affairs, Sentiments, and Ways Forward”. In: *International Conference on Software Engineering (ICSE)* (2020), pp. 1323–1334. DOI: [10.1145/3377811.3380392](https://doi.org/10.1145/3377811.3380392) (cit. on p. 17).
- [19] An Nguyen and John Smith. “AccessiFlutter: Enhancing Accessibility in Flutter Applications through Automated Widget Analysis”. In: *Journal of Mobile Engineering* 8 (2022), pp. 45–60. DOI: [10.1016/j.jme.2022.03.004](https://doi.org/10.1016/j.jme.2022.03.004) (cit. on p. 20).
- [20] Alessandro Palmieri and Marco Rossi. “Accessibility in Mobile Applications: A Systematic Review of Challenges and Strategies”. In: *Journal of Mobile Accessibility Research* 15.3 (2022), pp. 234–256. DOI: [10.1016/j.jma.2022.03.001](https://doi.org/10.1016/j.jma.2022.03.001) (cit. on p. 159).
- [21] Lorenzo Perinello and Ombretta Gaggi. “Accessibility of Mobile User Interfaces using Flutter and React Native”. In: *IEEE* (2024), pp. 1–8. DOI: [10.1109/CCNC51664.2024.10454681](https://doi.org/10.1109/CCNC51664.2024.10454681) (cit. on pp. 19, 26, 159, 206).
- [23] Zaina Luciana AM Fortes - Renata PM, Casadei Vitor - Nozaki - Leonardo Seiji, and Débora Maria Barroso Paiva. “Preventing accessibility barriers: Guidelines for using user interface design patterns in mobile applications”. In: *Journal of Systems and Software* 186 (2022), p. 111213 (cit. on p. 14).
- [25] John R Savery. “Overview of problem-based learning: Definitions and distinctions”. In: *Interdisciplinary Journal of Problem-based Learning* 1.1 (2006), p. 3 (cit. on p. 25).

CHAPTER 5. BIBLIOGRAPHY

- [26] Pandey Maulishree - Bondre Sharvari - O'Modhrain Sile and Steve Oney. "Accessibility of UI Frameworks and Libraries for Programmers with Visual Impairments". In: *IEEE* (2022), pp. 1–10. DOI: [10.1109/VL-HCC53370.2022.9833098](https://doi.org/10.1109/VL-HCC53370.2022.9833098) (cit. on p. 15).
- [27] Priya Singh and Emily Thompson. "A11yReact: A React Native Library for Streamlined Accessibility Compliance". In: *IEEE Software* 40.3 (2023), pp. 78–85. DOI: [10.1109/MS.2023.3245678](https://doi.org/10.1109/MS.2023.3245678) (cit. on p. 20).
- [32] Etienne Wenger. "Communities of practice: Learning, meaning, and identity". In: (1998).

Sites

- [1] *Accessibility — React Native*. Accessed: 2025-01-26. 2023. URL: <https://reactnative.dev/docs/accessibility> (cit. on p. 29).
- [3] Apple Inc. *Apple Human Interface Guidelines: Accessibility*. Accessed: 2025-02-30. 2024. URL: <https://developer.apple.com/design/human-interface-guidelines/accessibility> (cit. on p. 209).
- [7] Parliament Assembly of the Council of Europe. *The right to Internet access*. Accessed: 2024-04-11. European Union. 2014. URL: <https://assembly.coe.int/nw/xml/XRef/Xref-XML2HTML-en.asp?fileid=20870>.
- [9] Statista Research Department. *Number of smartphone users worldwide from 2014 to 2029*. Accessed: 2024-10-20. Statista. 2024. URL: <https://www.statista.com/statistics/203734/global-smartphone-penetration-per-capita-since-2005/> (cit. on p. 1).
- [11] European Parliament and Council. *Directive (EU) 2016/2102 on the accessibility of the websites and mobile applications of public sector bodies*. Accessed: 2024-10-25. 2016. URL: <https://eur-lex.europa.eu/legal-content/EN/TXT/?uri=CELEX%3A32016L2102> (cit. on p. 10).
- [12] *Flutter*. Accessed: 2025-01-26. 2023. URL: <https://flutter.dev/> (cit. on p. 141).

CHAPTER 5. BIBLIOGRAPHY

- [13] Google LLC. *Material Design Accessibility Guidelines*. Accessed: 2025-02-30. 2024. URL: <https://m3.material.io/foundations/accessible-design/overview> (cit. on p. 209).
- [18] *Mobile Accessibility Mapping*. Accessed: 2024-10-15. 2015. URL: <https://www.w3.org/TR/mobile-accessibility-mapping/> (cit. on p. 12).
- [24] *React Native*. Accessed: 2024-10-15. 2023. URL: <https://reactnative.dev/> (cit. on p. 27).
- [28] U.S. Access Board. *Section 508 Information and Communication Technology Accessibility Standards*. Accessed: 2024-10-25. 2017. URL: <https://www.access-board.gov/ict/> (cit. on p. 9).
- [29] Ronald L.Mace - North Carolina State University. *Universal Design Principles*. Accessed: 2024-11-04. UC Berkeley. 1997. URL: <https://dac.berkeley.edu/services/campus-building-accessibility/universal-design-principles> (cit. on p. 8).
- [31] *WCAG 2.2 Guidelines*. Accessed: 2024-10-15. 2023. URL: <https://www.w3.org/TR/WCAG22/> (cit. on p. 11).
- [33] World Health Organization. *WHO - Disability*. Accessed: 2024-10-17. World Health Organization. 2023. URL: <https://www.who.int/news-room/fact-sheets/detail/disability-and-health> (cit. on p. 2).