

Mobile Programming and Multimedia

The Xamarin Framework

Prof. Ombretta Gaggi
University of Padua



Xamarin is a cross-platform framework based on different approaches:

- Interpreted approach for Android and Windows
- Compiled approach for iOS


It is a project started in 2014 from Xamarin, a company based in California acquired by Microsoft in 2016

It is a general-purpose framework based on different parts

- Xamarin.Forms
- Xamarin Native
- XAML: XML language for interface building

Based on C#

System architecture



Widely used



UNIVERSITÀ
DEGLI STUDI
DI PADOVA

BOSCH



3M



Alaska
AIRLINES

CINEMARK

McKESSON



Honeywell



jetBlue



Kellogg's



Two possibilities available:

- Xamarin Native: allows writing code for a single platform (especially for the interface). Allows to use native APIs
- Xamarin.Forms: provides a set of APIs that can be used for each platform but with a native *look&feel*

To develop applications using Xamarin, it is necessary to install Microsoft Visual Studio

Which one is the best approach? - 1

Xamarin allows several choices:

- C# or XAML
- Native vs. general purpose

Which one is the best approach?

Xamarin.Form is more appropriate for:

- Apps that do not require functionalities specific to the platform
- When it is more important to reuse code instead of interface personalization
- If XAML is already known

Which one is the best approach? - 2

Xamarin.iOS & Xamarin.Android are more appropriate for:

- Apps that require native interactions (native *look&feel* is essential)
- Apps that make abundant use of native APIs
- When personalization of the interface is more important than code reuse with all the platforms

Xamarin.Forms



It is the combination of two projects,
Xamarin.iOS e Xamarin.Android

Xamarin.Forms is strongly focused on interfaces,
than can be visualized equally everywhere

Uses the MVVM model




Allows a fast prototypization

An interface can be developed using C# or **XAML**
(eXstensible Application Markup Language)

Same but different interfaces



UNIVERSITÀ
DEGLI STUDI
DI PADOVA



Xamarin.Forms allows writing the same code for the interfaces of all platforms

Each page and each component are mapped in a specific widget specific for each platform at runtime.

For example, a Xamarin.Forms entry becomes:

- A **UIView** on iOS
- A **EditText** on Android
- A **TextBox** on Windows

C#

Basic types



Type	Description
bool	true/false
byte	Positive integer, 8 bits
char	characters, 8 bits
int	4 bytes
short	2 bytes
float	4 bytes
double	8 bytes
object	Basic type
string	Sequence of characters

Variables names must have at least one character, cannot start with a number, and cannot have spaces

```
string text = "Hello" + "world!"
```

In C# arrays are defined with [] and can contain only data of the same type

Arrays can contain other arrays

```
int [] grades;  
grades = new int[5];  
grades[0] = 18;  
int numbers [];  
numbers = new int[5] {1, 2, 3, 4, 5}  
Console.WriteLine(numbers.Length);  
Console.ReadLine();
```

Lists are objects.

Constructor:

- `List<type> name = new List<type>();`

```
List<string> vegetables = new List<string>();
```

```
vegetables.Add("carrots");
```

```
vegetables.Add("zucchini");
```

```
vegetables.Remove("zucchini");
```

```
vegetables.AddRange(otherList) → concatenation
```


Dictionaries in C# are associative arrays. Each value has an associated key

```
Dictionary<string, long> numbers = new  
    Dictionary<string, long>();  
numbers.Add("Giorgio", 3481111);  
numbers["Giovanni"] = 3482222;  
numbers.Remove("Giorgio");  
numbers.Count;
```

If ... then ... else



```
if (condition) {  
    then instructions  
} else {  
    else instructions  
}
```

Loops



```
while (condition){  
    instructions  
}
```

```
for(init; condition; increment){  
    instructions  
}
```

```
do{  
    instructions  
} while (condition)
```

```
foreach (string day in days) {  
    MessageBox.Show(day)  
}
```

Switch



```
switch(expression){  
    case A:  
        instructions  
        break;  
    case B:  
        instructions  
        break;  
    default:  
        instructions  
}
```

Tools and file management



UNIVERSITÀ
DEGLI STUDI
DI PADOVA

The screenshot displays the Microsoft Visual Studio interface. The main editor shows the `App.xaml.cs` file with the following code:

```
1 using System;
2 using System.Collections.Generic;
3 using System.Linq;
4 using System.Text;
5
6 using Xamarin.Forms;
7
8 namespace nuovo
9 {
10     public partial class App : Application
11     {
12         public App ()
13         {
14             InitializeComponent();
15         }
16     }
17 }
```

The **Esplora soluzioni** (Solution Explorer) on the right shows the project structure:

- Soluzione 'nuovo' (3 progetti)
 - nuovo
 - App.xaml
 - App.xaml.cs
 - MainPage.xaml
 - nuovo.Android
 - Connected Services
 - Properties
 - Riferimenti
 - Assets
 - Resources
 - MainActivity.cs
 - nuovo.iOS
 - Connected Services

The **Proprietà** (Properties) window shows the project properties for `nuovo.iOS`:


nuovo.iOS Proprietà del progetto	
Cartella di progetto	C:\Users\ombre\Dropbox\mpm\m
File di progetto	nuovo.iOS.csproj

The **Xamarin Live Player** window is open, displaying a QR code and instructions for previewing the app on a device. The instructions are:

- 1 Download **Xamarin Live Player** from the **App Store** or **Google Play**
- 2 Open the app and scan the **QR code**

Below the QR code, there is a text input field with the code `123456` and a **Connect** button.

A simple example



```
using System;
using Xamarin.Forms;

namespace Xuzzle{
    public class App : Application{
        public App (){
            MainPage = new XuzzlePage();
        }
    }
}
```

Classe XuzzlePage – main page

```
using System; using System.Threading.Tasks; using Xamarin.Forms;
namespace Xuzzle{
    class XuzzlePage : ContentPage{ //variables definition
        static readonly int NUM = 4;
        XuzzleSquare[,] squares = new XuzzleSquare[NUM, NUM];
        int emptyRow = NUM - 1; int emptyCol = NUM - 1;
        StackLayout stackLayout;
        AbsoluteLayout absoluteLayout;
        Button randomizeButton;
        Label timeLabel;
        double squareSize;
        bool isBusy;
        bool isPlaying;
        //functions definition
    }
```



```
public XuzzlePage () {  
    // AbsoluteLayout to draw the puzzle  
    absoluteLayout = new AbsoluteLayout () {  
        HorizontalOptions = LayoutOptions.Center,  
        VerticalOptions = LayoutOptions.Center  
    };  
    // strings  
    string text = "{XAMARIN.FORMS}";  
    string winText = "CONGRATULATIONS";  
    int index = 0;  
    ...  
}
```

Drawing the interface - 1



```
for (int row = 0; row < NUM; row++) {  
    for (int col = 0; col < NUM; col++) {  
        if (row == NUM - 1 && col == NUM - 1) break; //do not fill the last square  
        XuzzleSquare square = new XuzzleSquare (text [index], winText [index], index) {  
            Row = row, //initialization and draw of each card  
            Col = col  
        }; // Add tap recognition  
        TapGestureRecognizer tapGestureRecognizer = new TapGestureRecognizer {  
            Command = new Command (OnSquareTapped),  
            CommandParameter = square  
        };  
        square.GestureRecognizers.Add (tapGestureRecognizer);  
        // adding to tile array and to absoluteLayout for visualization  
        squares [row, col] = square;  
        absoluteLayout.Children.Add (square);  
        index++;  
    }  
}
```

Botton for repositioning



```
randomizeButton = new Button {  
    Text = "Randomize",  
    HorizontalOptions = LayoutOptions.Center,  
    VerticalOptions = LayoutOptions.CenterAndExpand  
};  
randomizeButton.Clicked += OnRandomizeButtonClicked;
```

Text for timer



```
timeLabel = new Label {  
    FontSize = Device.GetNamedSize (NamedSize.Large,  
                                     typeof(Label)),  
    FontAttributes = FontAttributes.Bold,  
    HorizontalOptions = LayoutOptions.Center,  
    VerticalOptions = LayoutOptions.CenterAndExpand  
};
```

Drawing the interface - 2



```
stackLayout = new StackLayout {  
    Children = {  
        new StackLayout {  
            VerticalOptions = LayoutOptions.FillAndExpand,  
            HorizontalOptions = LayoutOptions.FillAndExpand,  
            Children = {  
                randomizeButton,  
                timeLabel  
            }  
        },  
        absoluteLayout  
    }  
};  
stackLayout.SizeChanged += OnStackSizeChanged; //insert into the page  
this.Padding = new Thickness(0, Device.RuntimePlatform == Device.iOS ? 20 : 0, 0, 0);  
this.Content = stackLayout;  
//end of XuzzlePage() constructor
```

OnStackSizeChanged



```
void OnStackSizeChanged (object sender, EventArgs args){  
    double width = stackLayout.Width;  
    double height = stackLayout.Height;  
    if (width <= 0 || height <= 0) return;  
    // check landscape or portrait  
    stackLayout.Orientation = (width < height) ?  
        StackOrientation.Vertical:StackOrientation.Horizontal;  
    // calculating position and size of each card based on screen size  
    squareSize = Math.Min (width, height) / NUM;  
    absoluteLayout.WidthRequest = NUM * squareSize;  
    absoluteLayout.HeightRequest = NUM * squareSize;  
    foreach (View view in absoluteLayout.Children) {  
        XuzzleSquare square = (XuzzleSquare)view;  
        square.SetLabelFont (0.4 * squareSize, FontAttributes.Bold);  
        AbsoluteLayout.SetLayoutBounds (square,  
            new Rectangle (square.Col * squareSize,  
                square.Row * squareSize, squareSize, squareSize));  
    }  
}
```

OnSquareTapped



```
async void OnSquareTapped (object parameter){  
    if (isBusy) return;  
    isBusy = true;  
    XuzzleSquare tappedSquare = (XuzzleSquare)parameter;  
    await ShiftIntoEmpty (tappedSquare.Row, tappedSquare.Col);  
    isBusy = false; //check if player wins  
    if (isPlaying) {  
        int index;  
        for (index = 0; index < NUM * NUM - 1; index++) {  
            int row = index / NUM; int col = index % NUM;  
            XuzzleSquare square = squares [row, col];  
            if (square == null || square.Index != index) break;  
        } // win  
        if (index == NUM * NUM - 1) {  
            isPlaying = false;  
            await DoWinAnimation ();  
        }  
    }  
}
```

```
}}
```

ShiftIntoEmpty



```
async Task ShiftIntoEmpty (int tappedRow, int tappedCol, int length = 100)
    if (tappedRow == emptyRow && tappedCol != emptyCol) { // Shift columns
        int inc = Math.Sign (tappedCol - emptyCol);
        int begCol = emptyCol + inc;
        int endCol = tappedCol + inc;
        for (int col = begCol; col != endCol; col += inc) {
            await AnimateSquare (emptyRow, col, emptyRow, emptyCol, length);
        } // Shift rows
    } else if (tappedCol == emptyCol && tappedRow != emptyRow) {
        int inc = Math.Sign (tappedRow - emptyRow);
        int begRow = emptyRow + inc;
        int endRow = tappedRow + inc;
        for (int row = begRow; row != endRow; row += inc) {
            await AnimateSquare (row, emptyCol, emptyRow, emptyCol, length);
        }
    }
}
```


AnimateSquare



```
async Task AnimateSquare (int row, int col, int newRow, int newCol, int length){  
    XuzzleSquare animaSquare = squares [row, col]; // card to animate  
    //destination rectangle  
    Rectangle rect = new Rectangle (squareSize * emptyCol,  
                                     squareSize * emptyRow, squareSize, squareSize);  
    await animaSquare.LayoutTo (rect, length);  
    //variables for the new layout  
    squares [newRow, newCol] = animaSquare;  
    animaSquare.Row = newRow;  
    animaSquare.Col = newCol;  
    squares [row, col] = null;  
    emptyRow = row;  
    emptyCol = col;  
}
```

OnRandomizeButtonClicked - 1



```
async void OnRandomizeButtonClicked (object sender, EventArgs args) {  
    Button button = (Button)sender;  
    button.IsEnabled = false;  
    Random rand = new Random ();  
    isBusy = true;  
    // Simulate some fast crazy taps  
    for (int i = 0; i < 100; i++) {  
        await ShiftIntoEmpty (rand.Next (NUM), emptyCol, 25);  
        await ShiftIntoEmpty (emptyRow, rand.Next (NUM), 25);  
    }  
    button.IsEnabled = true;  
    isBusy = false;  
    ...  
}
```

OnRandomizeButtonClicked - 2



```
async void OnRandomizeButtonClicked (object sender, EventArgs args) {  
    ... // preparation of the game  
    DateTime startTime = DateTime.Now;  
    Device.StartTimer ((TimeSpan.FromSeconds (1), () => {  
        // Round duration and get rid of milliseconds.  
        TimeSpan timeSpan = (DateTime.Now - startTime) + TimeSpan  
            .FromSeconds(0.5);  
        timeSpan = new TimeSpan (timeSpan.Hours, timeSpan.Minutes,  
            timeSpan.Seconds);  
        if (isPlaying) // shows the duration  
            timeLabel.Text = timeSpan.ToString ("t");  
        return isPlaying;  
    }));  
    this.isPlaying = true;  
}
```

```
async Task DoWinAnimation (){  
    //blocking input  
    randomizeButton.IsEnabled = false;  
    isBusy = true;  
    for (int cycle = 0; cycle < 2; cycle++) {  
        foreach (XuzzleSquare square in squares)  
            if (square != null)  
                await square.AnimateWinAsync (cycle == 1);  
        if (cycle == 0)  
            await Task.Delay (1500);  
    }  
    //restarting input  
    randomizeButton.IsEnabled = true;  
    isBusy = false;  
}
```

```
using System;
using System.Threading.Tasks;
using Xamarin.Forms;

namespace Xuzzle{
    class XuzzleSquare : ContentView{
        Label label;
        string normText, winText;
        //constructor and functions
        // current position
        public int Index { private set; get; }
        public int Row { set; get; }
        public int Col { set; get; }
    }
}
```

Constructor - 1



```
public XuzzleSquare (char normChar, char winChar, int index){  
    this.Index = index;  
    this.normText = normChar.ToString ();  
    this.winText = winChar.ToString ();  
    // each card is a frame with two labels  
    label = new Label {  
        Text = this.normText,  
        HorizontalOptions = LayoutOptions.Center,  
        VerticalOptions = LayoutOptions.CenterAndExpand  
    };  
    Label tinyLabel = new Label {  
        Text = (index + 1).ToString (),  
        FontSize = Device.GetNamedSize (NamedSize.Micro, typeof(Label)),  
        HorizontalOptions = LayoutOptions.End  
    };  
    ...  
}
```

Constructor - 2



```
public XuzzleSquare (char normChar, char winChar, int index){  
    ...  
    this.Padding = new Thickness (3);  
    this.Content = new Frame {  
        OutlineColor = Color.Accent,  
        Padding = new Thickness (5, 10, 5, 0),  
        Content = new StackLayout {  
            Spacing = 0,  
            Children = {  
                label,  
                tinyLabel,  
            }  
        }  
    };  
    // blocks touch event that is managed by this object and not by the ones below  
    this.BackgroundColor = Color.Transparent;  
}
```

```
public async Task AnimateWinAsync (bool isReverse) {  
    uint length = 150;  
    await Task.WhenAll (this.ScaleTo (3, length),  
                        this.RotateTo (180, length));  
    label.Text = isReverse ? normText : winText;  
    await Task.WhenAll (this.ScaleTo (1, length),  
                        this.RotateTo (360, length));  
    this.Rotation = 0;  
}
```



```
public void SetLabelFont(double fontSize,  
                          FontAttributes attributes){  
    label.FontSize = fontSize;  
    label.FontAttributes = attributes;  
}
```

Official site

- <https://www.xamarin.com/>

Documentation

- <https://developer.xamarin.com/guides/>

Puzzle example

- <https://developer.xamarin.com/samples/xamarin-forms/Xuzzle/>