



University of Brasilia at Gama – FGA/UnB
Software Engineering

**GENERATIVE ADVERSARIAL NETWORK PRIOR INFORMATION
FOR IMPROVED COMPRESSED SENSING
MAGNETIC RESONANCE IMAGE RECONSTRUCTION**

GABRIEL GOMES ZIEGLER

Advisor: CRISTIANO JACQUES MIOSSO, PhD
Co-advisor: DAVI BENEVIDES GUSMÃO, MSc



UNB – UNIVERSITY OF BRASILIA

FGA – GAMA FACULTY

SOFTWARE ENGINEERING

GABRIEL GOMES ZIEGLER

ADVISOR: CRISTIANO JACQUES MIOSSO, PHD

CO-ADVISOR: DAVI BENEVIDES GUSMÃO, MSC

BACHELOR THESIS

SOFTWARE ENGINEERING

BRASILIA/DF, SEPTEMBER 2020

UNB – UNIVERSITY OF BRASILIA
FGA – GAMA FACULTY
SOFTWARE ENGINEERING

GABRIEL GOMES ZIEGLER

**SUBMITTED IN PARTIAL FULFILLMENT FOR THE BACHELOR DEGREE IN SOFTWARE
ENGINEERING (HONOR’S DEGREE) TO THE DEPARTMENT OF ENGINEERING OF UNI-
VERSITY OF BRASILIA**

APPROVED BY:

Cristiano Jacques Miosso, PhD

(Advisor)

Prof. José da Silva, PhD

Prof. João da Silva, PhD

FICHA CATALOGRÁFICA

ZIEGLER, GABRIEL

Título para a ficha,

[Distrito Federal], 2018.

xviii p., 210 × 297 mm (FGA/UnB Gama, Bacharelado em Engenharia de Software, 2018).

Trabalho de Conclusão de Curso, Faculdade UnB Gama, Engenharia de Software

1. Imaging

2. Magnetic Resonance Image Reconstruction

3. *Machine Learning*

4. Compressive Sensing

I. FGA UnB/UnB.

II. Título (série)

REFERÊNCIA

ZIEGLER, GABRIEL (2020). Título para a ficha (parte 2). Trabalho de Conclusão de Curso, Engenharia de Software, Faculdade UnB Gama, Universidade de Brasília, Brasília, DF, xviii p.

CESSÃO DE DIREITOS

AUTHOR: Gabriel Gomes Ziegler

TITLE: Título para a ficha (parte 2)

GRAU: Bacharel em Engenharia de Software

ANO: 2020

É concedida à Universidade de Brasília permissão para reproduzir cópias desta monografia de conclusão de curso e para emprestar ou vender tais cópias somente para propósitos acadêmicos e científicos. O autor reserva outros direitos de publicação e nenhuma parte desta monografia pode ser reproduzida sem a autorização por escrito do autor.

gabrielziegler3@gmail.com

Brasília, DF – Brasil

RESUMO

A versão final do documento incluirá um resumo de todo o trabalho, incluindo metodologia, resultados e conclusão.

ABSTRACT

The final version of this document will include an abstract. This will summarize the introduction (contextualization, objectives, justification), the methodology, the results, and the conclusion.

TABLE OF CONTENTS

1	Introduction	xi
1.1	Context	xi
1.2	Scientific Problem Definition and Proposal	xii
1.3	Objectives	xiii
1.3.1	General Objective	xiii
1.3.2	Specific Objective	xiii
2	Theory Foundation and State-of-Art	xiv
3	Methodology	xv
4	Results	xvi
5	Conclusion	xvii

LIST OF TABLES

LIST OF FIGURES

NOMENCLATURE AND ABBREVIATIONS

MRI Magnetic Resonance Imaging	xi
MR Magnetic Resonance	xi
ANN Artificial Neural Networks	xii
DL Deep Learning	xii
ML Machine Learning	xi
GAN Generative Adversarial Network	xi
CNN Convolutional Neural Network	xii
GPU Graphics Processing Units	xi
CV Computer Vision	xii
NLP Natural Language Processing	xii
CS Compressed Sensing	xi

1 INTRODUCTION

In this thesis, we propose a Generative Adversarial Network (GAN) approach for prior information extraction to feed a Compressed Sensing (CS) algorithm, aiming to reconstruct images with both reduced signal-to-noise error and less acquisition time compared to conventional CS. Achieving higher quality with reduced number of samples allows faster exam procedures, making Magnetic Resonance Imaging (MRI) cheaper, faster and more convenient for both patients and clinics.

1.1 Context

MRI is a widely used imaging modality in medical practice because of its great tissue contrast capabilities, it has evolved into the richest and most versatile biomedical imaging technique today[1], making MRI the best option for medical imaging whenever it is possible to use.

However, like everything in life, there is a trade-off to consider when using MRI. Typically, reconstructing an MRI is an ill-posed linear inverse task (a problem that has either none or infinite solutions in the desired class). Problems of this nature impose a trade-off between *accuracy* and *speed*[2]. The information obtained from Magnetic Resonance (MR) is commonly represented by individual samples in the k-space, which translates to the Fourier transform of the image to be reconstructed[3]. This MR sampling sparse nature makes CS a liable technique to use when reconstructing MRI, hence we here propose a novel CS prior information approach for better results.

CS has been for years the state-of-art technique in MRI reconstruction and has been improved later by the use of prior information[3]. CS uses the premise that given a signal with a sparse representation in some known domain, it is possible to reconstruct the signal using limited linear measurements taken from a non-sparse representation.

Machine Learning (ML) methods have been utterly developed and improved recently with the use of higher computing power derived from the invention of Graphics Processing

Units (GPU) and other hardware improvements, allowing Artificial Neural Networks (ANN) to come to practicality. These ANN models, often referenced as Deep Learning (DL), have become the state-of-art in various areas, such as Computer Vision (CV), Natural Language Processing (NLP), Recommendation Systems, amongst other fields [4, 5, 6]. These fast-paced developments led to improvements in medical data processing using DL as well. ML techniques can be used in several different manners to improve medical analysis, here we focus on applying GAN in the process of attaining improved prior information to feed the CS algorithm obtaining higher signal-to-noise ratios and faster computation procedures.

1.2 Scientific Problem Definition and Proposal

MRI is great for high-quality tissue images, but there are some drawbacks: MRI exams are often very long and require the patient to be in a static position throughout the whole process, this makes the exam challenging for patients that have difficulties in keeping a still position for several minutes. Another intrinsic complication in MRI procedures is that it is nearly impossible to get images from moving tissues like a beating heart and flowing blood veins as that would require an enormous amount of samples, making it practicality impossible with current technologies used in clinics. Algorithms that reconstruct MRI try to tackle this sampling issue by producing the best possible quality images for the least amount of samples collected, making the exams faster and less sample-dependent.

CS algorithms have been the state-of-art in MRI reconstruction for the past few years, and now with the advances of DL, new techniques are being produced taking advantages of how ANN are powerful in imaging processing, especially Convolutional Neural Network (CNN) and, more recently, GAN networks are becoming the new state-of-art techniques in several computer vision areas. A problem with CS applications is that the reconstruction process can be very slow. Newer CS algorithms try to tackle this issue by adding prior information to make the algorithm abstract static information in the region analysed.

Prior information for CS can go from previous MRI frames and exams to even medical records. Prior information is normally generated by simplistic mathematical approaches like filtering and thresholding on the images. Besides the simpler technique applied, these information extraction procedures oftentimes is restricted to few frames and does not take into account the nature of organs and tissues structures, a feature that DL should be able to identify and use in order to generate better quality information. This means that there

is a lot of room for improvement towards prior information engineering techniques, as DL models have been proven superior in tasks of this nature.

Within this context, we propose a modern prior information engineering system with the usage of GAN, aiming for higher quality prior information to feed the CS and reducing the number of samples dependability. This will reduce the number of samples needed, making the MRI exams faster and, consequently, cheaper.

1.3 Objectives

1.3.1 General Objective

This thesis' goal is to develop an MR prior information system retriever based on GAN architecture to improve the quality of the prior information fed to CS algorithms, hence improving quality in reconstructed MRI and decreased necessity for larger sampling.

1.3.2 Specific Objective

In order to achieve the general objective described above, we have set the following specific goals:

- Implement direct and indirect CS MRI reconstruction algorithm and apply to k -space measurements.
- Evaluate direct and indirect CS MRI reconstructions varying sampling size for 1-dimensional signal and k -space measurements.
- Implement a GAN for regular image generation with a known CV dataset.
- Implement a GAN architecture for prior information retrieval and train it against k -space measurements.
- Evaluate the use of GAN architecture for prior information retrieval against state-of-art prior information techniques.

2 THEORY FOUNDATION AND STATE-OF-ART

3 METHODOLOGY

4 RESULTS

5 CONCLUSION

Referências Bibliográficas

- [1] R Nick Bryan. Introduction to the Science of Medical Imaging. page 336.
- [2] S. I. Kabanikhin. Definitions and examples of inverse and ill-posed problems. *Journal of Inverse and Ill-posed Problems*, 16(4), January 2008.
- [3] Cristiano Jacques Miosso. *Compressive Sensing with Prior Information Applied to Magnetic Resonance Imaging*. PhD Thesis, Department of Electrical and Computer Engineering, University of Texas at El Paso (UTEP).
- [4] Li Wan, Matthew Zeiler, Sixin Zhang, Yann LeCun, e Rob Fergus. Regularization of neural networks using dropconnect. In *30th International Conference on Machine Learning, ICML 2013*, pages 2095–2103. International Machine Learning Society (IMLS), 2013. 30th International Conference on Machine Learning, ICML 2013 ; Conference date: 16-06-2013 Through 21-06-2013.
- [5] Jacob Devlin, Ming-Wei Chang, Kenton Lee, e Kristina Toutanova. BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 4171–4186, Minneapolis, Minnesota, June 2019. Association for Computational Linguistics.
- [6] Daeryong Kim e Bongwon Suh. Enhancing vaes for collaborative filtering. *Proceedings of the 13th ACM Conference on Recommender Systems*, Sep 2019.