New Web Service

Source Code

gabrivdev / pagomovil-verify • 17m ago Edit

Name

A unique name for your web service.

pagomovil-verify

Project Optional

Add this web service to a project once it's created.

Select a project...

Select an environment...

Language

Choose the runtime environment for this service.

Rust

Branch

The Git branch to build and deploy.

main

Region

Your services in the same region can communicate over a private network. You currently have services running in **Ohio**.

Deploy web service Cancel **$0** / month **0.1** CPU **512** MB RAM

Root Directory Optional

If set, Render runs commands from this directory instead of the repository root. Additionally, code changes outside of this directory do not trigger an auto-deploy. Most commonly used with a monorepo.

e.g. src

Build Command

Render runs this command to build your app before each deploy.

```
$ cargo build --release
```

Start Command

Render runs this command to start your app with each deploy.

```
$ cargo run --release
```

Compute

For more power and to get the most out of Render, we recommend using one of our paid compute plans.

All paid compute plans support:

- Zero Downtime
- SSH Access
- Scaling
- One-off jobs
- Support for persistent disks

Selected:

$0 / month **0.1** CPU **512** MB RAM

Free instances spin down after periods of inactivity. They do not support SSH access, scaling, one-off jobs, or persistent disks.

◉	$0 / month	0.1 CPU	512 MB RAM	Free
○	$7 / month	0.5 CPU	512 MB RAM	0.5c-512mb
○	$25 / month	1 CPU	2 GB RAM	1c-2g
○	$85 / month	2 CPU	4 GB RAM	2c-4g

Show all 15 compute plans

Environment Variables

Set environment-specific config and secrets (such as API keys), then read those values from your code. Learn more.

KEY	VALUE	
NAME_OF_VARIABLE	value	Generate

+ Add Environment Variable

Add from .env

Advanced