WEB SERVICE

verificador-pagomovil

Connect

Manual Deploy

Node Free

Upgrade your instance

Service ID: srv-dbl3vu8n74is73cvidl0

gabrivdev / pagomovil-verify main

https://verificador-pagomovil-swlm.onrender.com

Failed 43,6s

c86b081

Settings

General

Name

A unique name for your Web Service.

verificador-pagomovil

Edit

G Gabriel Antonio's w... Search ^ K + New Upgrade ? G

Region

Your services in the same region can communicate over a private network.

Ohio (US East)

Instance Type

Dashboard

verificador-pagomovil

Deploys

Settings

MONITOR

Events

Logs

Metrics

MANAGE

Compute

Environment

Shell

Previews

Disk

One-Off Jobs

Changelog

Status

Collapse

Instance Type is now Compute Plan. Read the announcement.

See remaining free usage, or learn about free service limits.

Build

Source

The build source for your Web Service

gabrivdev / pagomovil-verify Edit

Branch

The Git branch to build and deploy.

main

Edit

Root Directory Optional

If set, Render runs commands from this directory instead of the repository root. Additionally, code changes outside of this directory do not trigger an auto-deploy. Most commonly used with a monorepo.

Edit

Build Command

Render runs this command to build your app before each deploy.

```
$ npm install && npm run build
```

Edit

Git Credentials

User providing the credentials to pull the repository.

gabrielvelez.dev@gmail.com (you)

Use My Credentials

Build Filters

Include or ignore specific paths in your repo when determining whether to trigger an auto-deploy. Paths are relative to your repo's root directory. Learn more.

Edit

Included Paths
Changes that match these paths will trigger a new build.

+ Add Included Path

Ignored Paths
Changes that match these paths will not trigger a new build.

+ Add Ignored Path

Deploy

Pre-Deploy Command Optional

Render runs this command before the start command. Useful for database migrations and static asset uploads.

Edit

Start Command

Render runs this command to start your app with each deploy.

```
$ npm start
```

Edit

Auto-Deploy

By default, Render automatically deploys your service whenever you update its code or configuration. Disable to handle deploys manually. Learn more.

On Commit

Edit

Deploy Hook

Your private URL to trigger a deploy for this server. Remember to keep this a secret.

Regenerate hook

Loading...

PR Previews

Pull Request Previews

Spin up temporary instances to test pull requests opened against the `main` branch of `gabrivdev/pagomovil-verify`. Choose **Automatic** to preview all PRs, or **Manual** for only PRs with `[render preview]` in their title. Pull Request Previews create a new instance for just this service. Use Preview Environments to clone a group of services for every PR.

Off

Edit

Networking

Edge Caching

Serve static content at the edge to improve performance and reduce service load. Learn more.

Cacheable File Types

Specify which file types Render is allowed to cache for your service. You can fine-tune this

behavior with `Cache-Control` headers.

None

Edit

PAID Edge Caching is only available for paid instances. Upgrade

Notifications

Service Notifications

Set notifications to receive for your service. This setting will override your workspace's default settings.

Use workspace default (Only failure notificati...

Edit

Preview Environment Notifications

Configure notifications for preview environments and service previews.

Use account default (Disabled)

Edit

Health Checks

Health Check Path

Provide an HTTP endpoint path that Render messages periodically to monitor your service. Learn More.

Edit

Maintenance Mode

Maintenance Mode

Temporarily disable public access to your service. While enabled, Render serves a static maintenance page for all incoming requests. Learn more.

Maintenance Mode Disabled

Custom Maintenance Page Optional

If provided, Render uses the specified URL for your maintenance page instead of serving the default page.

PAID Maintenance mode is only available for paid instances. Upgrade

Delete Web Service Suspend Web Service