

Lab Assignment: Maximum Activity Points using Priority Queue

Objective

To implement a C program to determine the maximum number of activity points that can be earned by participating in at most k events using a **min-heap (priority queue)**.

Problem Statement

The CSE department is organizing a tech fest with several exciting events. Each event i offers $A[i]$ activity points. A student is allowed to participate in at most k events. The goal is to find the **maximum total activity points** that can be earned.

Function Signature

```
int maxActivityPoints(int A[], int n, int k);
```

Concept

- A **min-heap** (priority queue) is used to efficiently track the top k highest values.
- Traverse through the array:
 1. Insert the current element into the heap.
 2. If the heap size exceeds k , remove the smallest element.
- After processing all elements, the heap contains the largest k activity points.
- Sum all elements in the heap to obtain the result.

Example Walkthrough

$$A = [10, 40, 20, 30, 50], \quad k = 3$$

1. Insert 10 Heap = [10]
2. Insert 40 Heap = [10, 40]
3. Insert 20 Heap = [10, 40, 20]
4. Insert 30 Heap = [20, 40, 30] (Remove 10)
5. Insert 50 Heap = [30, 40, 50] (Remove 20)

$$\text{Sum of heap elements} = 30 + 40 + 50 = 120$$

| |
|-------------------------------|
| Maximum Activity Points = 120 |
|-------------------------------|

Expected Output

The program should correctly compute the maximum achievable activity points when participating in at most k events.