Clean Job Babysitting

1. Configure Job with HPCJobConfigurator:
   `python configureJob.py -x Job.ini`
   `-p 92 -l 500 -r 4000 -t 720 -n 2`



Clean Job Babysitting

1. Configure Job with HPCJobConfigurator:
   `python configureJob.py -x Job.ini -p 92 -l 500 -r 4000 -t 720 -n 2`



Clean Job Babysitting

1. Configure Job with HPCJobConfigurator:
   `python configureJob.py -x Job.ini`
   `-p 92 -l 500 -r 4000 -t 720 -n 2`





Clean Job Babysitting

1. Configure Job with HPCJobConfigurator:
   `python configureJob.py -x Job.ini -p 92 -l 500 -r 4000 -t 720 -n 2`



Clean Job Babysitting

1. Configure Job with HPCJobConfigurator:
   `python configureJob.py -x Job.ini`
   `-p 92 -l 500 -r 4000 -t 720 -n 2`



Clean Job Babysitting

1. Configure Job with HPCJobConfigurator:
   `python configureJob.py -x Job.ini -p 92 -l 500 -r 4000 -t 720 -n 2`
2. Submit Job with **`bsub`**



Clean Job Babysitting

1. Configure Job with HPCJobConfigurator:
   `python configureJob.py -x Job.ini -p 92 -l 500 -r 4000 -t 720 -n 2`
2. Submit Job with **`bsub`**
3. Trink coffee and **hope for the best!**



Clean Job Babysitting

1. Configure Job with HPCJobConfigurator:
   `python configureJob.py -x Job.ini -p 92 -l 500 -r 4000 -t 720 -n 2`
2. Submit Job with **`bsub`**
3. Trink coffee and **hope for the best!**
4. Job launched: woo!



Clean Job Babysitting

1. Configure Job with HPCJobConfigurator:
   `python configureJob.py -x Job.ini -p 92 -l 500 -r 4000 -t 720 -n 2`
2. Submit Job with **`bsub`**
3. Trink coffee and **hope for the best!**
4. Job launched: woo!



Clean Job Babysitting

1. Configure Job with HPCJobConfigurator:
   `python configureJob.py -x Job.ini -p 92 -l 500 -r 4000 -t 720 -n 2`
2. Submit Job with **`bsub`**
3. Trink coffee and **hope for the best!**
4. Job launched: woo!



Clean Job Babysitting

1. Configure Job with HPCJobConfigurator:
   `python configureJob.py -x Job.ini -p 92 -l 500 -r 4000 -t 720 -n 2`
2. Submit Job with **`bsub`**
3. Trink coffee and **hope for the best!**
4. Job launched: woo!



Clean Job Babysitting

1. Configure Job with HPCJobConfigurator:
   `python configureJob.py -x Job.ini -p 92 -l 500 -r 4000 -t 720 -n 2`
2. Submit Job with **`bsub`**
3. Trink coffee and **hope for the best!**
4. Job launched: woo!



postProcess-PerNode.sh:
I/O from scratch to global

Clean Job Babysitting

1. Configure Job with HPCJobConfigurator:
   `python configureJob.py -x Job.ini -p 92 -l 500 -r 4000 -t 720 -n 2`
2. Submit Job with **`bsub`**
3. Trink coffee and **hope for the best!**
4. Job launched: woo!



Clean Job Babysitting

1. Configure Job with HPCJobConfigurator:
   `python configureJob.py -x Job.ini -p 92 -l 500 -r 4000 -t 720 -n 2`
2. Submit Job with **`bsub`**
3. Trink coffee and **hope for the best!**
4. Job launched: woo!



#!
.sh

end:
- (file validation)
- notify user

Clean Job Babysitting

1. Configure Job with HPCJobConfigurator:
   `python configureJob.py -x Job.ini -p 92 -l 500 -r 4000 -t 720 -n 2`
2. Submit Job with **`bsub`**
3. Trink coffee and **hope for the best!**
4. Job launched: woo!
5. Job run successfully: copy data back



#! .sh

end:
- (file validation)
- notify user